Web Application Vulnerability Report

I conducted a web Vulnerability assessment on Playkart Stores to identify security weaknesss and misconfigurations.I used common penetration testing tools within a controlled Kali Linux environment.
Through the test I was able to identify several low to medium risk misconfiguration issues,which included security headers and potential information disclosure.I discovered no critical Vulnerabilities as enumeration attempts resulted in HTTPS 404 responses.

1.0 Target information

Target Domain: www.playkartstores.com
Target Ip: 145.79.14.2
Testing Machine: Kali Linux
Testing Date: March 4,202.
Time Taken: 45 minutes.
Testing type: passive and active reconnaissance.

1.1 Methodology

I followed a structured penetration testing approach in Vulnerability assessment as follows;

Phase 1; Information gathering

I conducted initial reconnaissance to identify server information and configurations in the web server.

Tools I used

-Nikto
-Nmap
-Gobuster

2.0 Vulnerability Scanning

2.1 Web Server Scanning(nikto)

I scanned for Vulnerabilities and security misconfiguration on the web server using nikto.

2.2 Key Findings

Missing X-Frame-Options Header

This allows the website to be embedded in malicious forms hence enabling clickjacking attacks.

Missing X-Content-Type-Options Header

From this a browser my interpret files incorrectly enabling MIME-Sniffing attacks.

Missing HSTS Header

HTTPS is not strictly enforced,allowing possible downgrade attacks.

Server Header Disclosure

Headers reveal hosting information which is hostinger and hpanel.

Server information discovered

Component.	Value
Web server;	Litespeed
SSL certificate;	Let's Encrypt
TLS cipher;	TLS_AES_256_GCM_SHA384

All this findings are shown in the figure below:



```
File  Actions  Edit  View  Help
┌──(dickens㉿vboxkali)-[~]
└─$ nikto -h https://WWW.Playkartstore.com

- Nikto v2.5.0
---------------------------------------------------------------------------
+ Multiple IPs found: 145.79.14.2, 2a02:4780:6:2081:0:66c:511a:2
+ Target IP:          145.79.14.2
+ Target Hostname:    WWW.Playkartstore.com
+ Target Port:        443
---------------------------------------------------------------------------
+ SSL Info:        Subject:  /CN=playkartstore.com
                   Altnames: playkartstore.com, www.playkartstore.com
                   Ciphers:  TLS_AES_256_GCM_SHA384
                   Issuer:   /C=US/O=Let's Encrypt/CN=R13
+ Start Time:         2026-03-04 12:03:41 (GMT0)
---------------------------------------------------------------------------
+ Server: LiteSpeed
+ /: Retrieved x-powered-by header: PHP/8.3.28.
+ /: The anti-clickjacking X-Frame-Options header is not present. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Frame-Options
+ /: Uncommon header 'platform' found, with contents: hostinger.
+ /: Uncommon header 'panel' found, with contents: hpanel.
+ /: The site uses TLS and the Strict-Transport-Security HTTP header is not defined. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Strict-Transport-S
ecurity
+ /: An alt-svc header was found which is advertising HTTP/3. The endpoint is: ':443'. Nikto cannot test HTTP/3 over QUIC. See: https://developer.mozilla.org/en-US/do
cs/Web/HTTP/Headers/alt-svc
+ /: The X-Content-Type-Options header is not set. This could allow the user agent to render the content of the site in a different fashion to the MIME type. See: htt
ps://www.netsparker.com/web-vulnerability-scanner/vulnerabilities/missing-content-type-header/
+ /ChtPisXm.php4: Server may leak inodes via ETags, header found with file /ChtPisXm.php4, inode: 119f, size: 6819e1a6, mtime: a799d3b3cd1818be;;;. See: http://cve.mi
tre.org/cgi-bin/cvename.cgi?name=CVE-2003-1418
```

3.0 Network Port Scanning (Nmap)

I performed a port Scanning to identify open ports and exposed services.

3.1 Results of Open ports

Port	Service	Risk
21	FTP	Possible file transfer exposure
80	HTTP	Web services
443	HTTPS	Secure web services

3306 MYSQL Possible database exposure

3.2 Security Concern

MYSQL port (3306) being publicly accessible may expose the database if authentication controls are weak.

The results for network port Scanning are shown in figure below;

```
┌──(dickens㉿vboxkali)-[~]
└─$ nmap 145.79.14.2

Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-04 12:08 GMT
Nmap scan report for 145.79.14.2
Host is up (0.029s latency).
Not shown: 985 filtered tcp ports (no-response)
PORT      STATE  SERVICE
21/tcp    open   ftp
80/tcp    open   http
443/tcp   open   https
2111/tcp  closed kx
2161/tcp  closed apc-agent
2170/tcp  closed eyetv
2179/tcp  closed vmrdp
2190/tcp  closed tivoconnect
2196/tcp  closed unknown
2200/tcp  closed ici
2222/tcp  closed EtherNetIP-1
2301/tcp  closed compaqdiag
2366/tcp  closed qip-login
3306/tcp  open   mysql
60443/tcp closed unknown

Nmap done: 1 IP address (1 host up) scanned in 29.12 seconds
```

4.0 Directory Enumeration (Gobuster)

I conducted directory brute-forcing to discover hidden web resources.

4.1 Results

The server responded with HTTP status code 404- page not found as shown below;



This means;
-The requested page does not exist or no hidden directories were discovered using the tested wordlists.
-The server returns a wildcard response for non-existing paths.The results are best on this simple gobuster scan;



5.0 Risk Assessment

-Missing Security Headers: Potential clickjacking or browser exploitation.
-Server information disclosure:Attackers can identify hosting infrastructure.
-MYSQL port exposure: Possible database attack surface.

6.0 Recommendations

I would recommend the following to improve the security of the web server according to my test results;
1.Implement X-Frame-Otions Header to protect against clickjacking attacks.
2.ConfigureX-Content-Type-Options:nonsniff to prevent MIME type sniffing.
3.Enable Strict Transport Security(HSTS) to enforce HTTPS.
4.Restrict MYSQL port(3306) to internal network access only.
6.Disable FTP if not necessary or migrate to Secure FTP.

8.0 Conclusion

In the assessment,I found no critical Vulnerabilities on the target web server.However,I identified configuration weaknesses that could potentially be leveraged by attackers.Implementing recommended security headers and restricting exposed services will significantly improve the servers security posture.