

# Range Minimum Query

Range Minimum Query ([RMQ](#)) is a set of problems which deals with finding a property (here minimum) of a range. Segment Tree can be very helpful when solving with such problems. A segment tree is a tree like data structure which is used to store the information about intervals. Here's the [[wiki link](#)] of it.

You are given a array of  $N$  integers,  $arr[0], arr[1], \dots, arr[(N-1)]$ . And you are given a list of ranges. For each range,  $(l, r)$  you have to find the minimum value between range  $arr[l], arr[l+1], arr[l+2], \dots, arr[r]$ .

## Input

First line will contain two integers,  $N$   $M$ , length of array and number of queries. Then in next line, there are  $N$  space separated integers which represent the array,  $arr[0], arr[1], \dots, arr[N-1]$ . Then  $M$  line follows. Each  $M$  line will contain two integers,  $l$   $r$ , representing a range.

## Output

For each range,  $(l, r)$ , you have to print the minimum integer in subarray  $arr[l], arr[l+1], \dots, arr[r]$  in separate line.

## Constraints

$1 \leq N, M \leq 10^5$

$-10^5 \leq arr[i] \leq 10^5$ , where  $0 \leq i < N$

$0 \leq l \leq r < N$

## Sample Input

```
10 5
10 20 30 40 11 22 33 44 15 5
0 5
1 2
8 9
0 9
4 6
```

## Sample Output

```
10
20
5
5
11
```

## Explanation

- For range (0, 5), subarray will be [10, 20, 30, 40, 11, 22]. So minimum value will be 10.
- For range (1, 2), subarray will be [20, 30]. Minimum value = 20.
- For range (8, 9), subarray is [15, 5]. Minimum value = 5.
- For range (0, 9), Here we have to find the minimum (5) of the whole array.
- For range (3, 5), subarray is [40, 11, 22]. Minimum value = 11.