

Fichier texte des commandes à injecter dans les équipements réseaux



*Ote Melissa
Gales Quentin
Guiffre Matteo
Falcomer Matheo
Groupe Alt*

Table des matières

----- COUCHE CŒUR DE RÉSEAU -----	2
ASA (USB13):	2
Ra11 (USB15) :	6
Ra12 (USB 14):	8
----- COUCHE DE DISTRIBUTION -----	10
SWx31 (USB 20) :	10
SWx32 (USB 21):	15
SWx33 (USB 22):	20
SWx34 (USB 23):	23
-----COUCHE ACCES -----	26
SW21 (USB 16):	26
SW22 (USB 17):	28
SW23 (USB 18):	30
SW24 (USB 19):	32

----- COUCHE CŒUR DE RÉSEAU -----

ASA (USB13):

en

conf t

hostname ASAa

clock timezone CET 1

clock summer-time CEST recurring last Sun Mar 02:00 last Sun Oct 03:00

ntp server 172.16.16.21

names

interface Ethernet0/0

switchport access vlan 10

no sh

interface Ethernet0/1

switchport access vlan 11

no sh

interface Ethernet0/2

switchport access vlan 11

no sh

interface Ethernet0/5

switchport access vlan 12

no sh

interface Vlan10

nameif outside

security-level 0

ip address 10.200.2.1 255.255.255.252

interface Vlan11

nameif inside

security-level 100

ip address 172.16.16.1 255.255.255.248

interface Vlan12

nameif dmz

security-level 50

ip address 192.168.22.254 255.255.255.0

route outside 0.0.0.0 0.0.0.0 10.200.2.2 1

route inside 192.168.16.0 255.255.255.192 172.16.16.2 1 track 1

route inside 192.168.16.0 255.255.255.192 172.16.16.3 10

route inside 192.168.17.0 255.255.255.192 172.16.16.2 1 track 1

route inside 192.168.17.0 255.255.255.192 172.16.16.3 10

route inside 192.168.19.0 255.255.255.248 172.16.16.2 1 track 1

route inside 192.168.19.0 255.255.255.248 172.16.16.3 10

route inside 10.10.16.0 255.255.255.240 172.16.16.2 1 track 1

route inside 10.10.16.0 255.255.255.240 172.16.16.3 10

route inside 172.16.16.8 255.255.255.252 172.16.16.2 1 track 1

route inside 172.16.16.8 255.255.255.252 172.16.16.3 10

route inside 172.16.16.12 255.255.255.252 172.16.16.2 1 track 1

route inside 172.16.16.12 255.255.255.252 172.16.16.3 10

route inside 172.16.16.16 255.255.255.252 172.16.16.2 1 track 1

route inside 172.16.16.16 255.255.255.252 172.16.16.3 10

route inside 172.16.16.20 255.255.255.252 172.16.16.2 1 track 1

route inside 172.16.16.20 255.255.255.252 172.16.16.3 10

telnet timeout 5

ssh timeout 5

dhcpd auto_config outside

end

conf t

policy-map global_policy

class inspection_default

inspect icmp

icmp permit 172.16.16.0 255.255.255.248 inside

icmp permit 172.16.16.8 255.255.255.252 inside

icmp permit 172.16.16.12 255.255.255.252 inside

icmp permit 172.16.16.20 255.255.255.252 inside

icmp permit 172.16.16.16 255.255.255.252 inside

icmp permit 172.16.16.0 255.255.255.248 dmz

icmp permit 192.168.22.0 255.255.255.0 dmz

Exit

conf t

access-list INSIDE_IN extended permit icmp any 192.168.22.0 255.255.255.0

access-group INSIDE_IN in interface inside

access-list DMZ_IN extended permit icmp 192.168.22.0 255.255.255.0 host 172.16.16.1

access-list DMZ_IN extended permit tcp 192.168.22.0 255.255.255.0 host 172.16.16.1 eq 443

access-list DMZ_IN extended permit tcp 192.168.22.0 255.255.255.0 host 172.16.16.1 eq www

access-group DMZ_IN in interface dmz

conf t

track 1 rtr 1 reachability

```
sla monitor 1

type echo protocol iplcmpEcho 172.16.16.2 interface inside

num-packets 3

frequency 5

timeout 1000

sla monitor schedule 1 life forever start-time now

end

write mem
```

TUNNEL IPSEC (PAS SUR) :

```
access-list VPN-BE extended permit ip 192.168.16.0 255.255.255.192 192.168.40.0 255.255.248.0
access-list VPN-BE extended permit ip 192.168.17.0 255.255.255.192 192.168.40.0 255.255.248.0
access-list VPN-BE extended permit ip 192.168.19.0 255.255.255.248 192.168.40.0 255.255.248.0
access-list VPN-BE extended permit ip 10.10.16.0 255.255.255.240 192.168.40.0 255.255.248.0
access-list VPN-BF extended permit ip 192.168.16.0 255.255.255.192 192.168.48.0 255.255.248.0
access-list VPN-BF extended permit ip 192.168.17.0 255.255.255.192 192.168.48.0 255.255.248.0
access-list VPN-BF extended permit ip 192.168.19.0 255.255.255.248 192.168.48.0 255.255.248.0
access-list VPN-BF extended permit ip 10.10.16.0 255.255.255.240 192.168.48.0 255.255.248.0
access-list VPN-B409 extended permit ip 192.168.16.0 255.255.255.192 192.168.100.0
255.255.255.0
access-list VPN-B409 extended permit ip 192.168.17.0 255.255.255.192 192.168.100.0
255.255.255.0
access-list VPN-B409 extended permit ip 192.168.19.0 255.255.255.248 192.168.100.0
255.255.255.0
access-list VPN-B409 extended permit ip 10.10.16.0 255.255.255.240 192.168.100.0 255.255.255.0
crypto ikev1 policy 10
 authentication pre-share
 encryption aes
 hash sha
 group 2
 lifetime 3600
crypto ikev1 enable outside
crypto ipsec ikev1 transform-set XXX esp-aes-256 esp-sha-hmac
crypto map MAP 10 match address VPN-BE
crypto map MAP 10 set peer 10.200.5.1
crypto map MAP 10 set transform-set XXX
crypto map MAP 20 match address VPN-BF
crypto map MAP 20 set peer 10.200.6.1
crypto map MAP 20 set transform-set XXX
crypto map MAP 30 match address VPN-B409
crypto map MAP 30 set peer 10.4.109.166
crypto map MAP 30 set transform-set XXX
crypto map MAP interface outside
object network LAN-E
 subnet 192.168.40.0 255.255.248.0
 description Local network – Department E
object network LAN-F
```

```
subnet 192.168.48.0 255.255.248.0
description Local network – Department F
object network LAN-409
subnet 192.168.100.0 255.255.255.0
description Professor gateway – Room 409
tunnel-group 10.200.5.1 type ipsec-l2l
tunnel-group 10.200.5.1 ipsec-attributes
ikev1 pre-shared-key SAEdept-2E
tunnel-group 10.200.6.1 type ipsec-l2l
tunnel-group 10.200.6.1 ipsec-attributes
ikev1 pre-shared-key SAEdept-2F
tunnel-group 10.4.109.166 type ipsec-l2l
tunnel-group 10.4.109.166 ipsec-attributes
ikev1 pre-shared-key SAEdept-2409
end
write memory
```

Ra11 (USB15) :

```
en
conf t
ip route 192.168.22.0 255.255.255.0 172.16.16.1
hostname RA11
clock timezone CET 1
clock summer-time CEST recurring last Sun Mar 02:00 last Sun Oct 03:00
ntp server 193.190.230.65
interface range s0/0-1
shutdown
interface fa0/0
ip address 172.16.16.21 255.255.255.252
no shutdown
interface fa0/1
ip address 172.16.16.17 255.255.255.252
no shutdown
interface fa1/0
ip address 172.16.16.2 255.255.255.248
no shutdown
exit
```

```
router ospf 1
default-information originate always
redistribute static subnets
router-id 2.2.2.2
log-adjacency-changes
network 172.16.16.20 0.0.0.3 area 10
network 172.16.16.16 0.0.0.3 area 10
network 172.16.16.0 0.0.0.7 area 10
end
```

```
configure terminal
no ip domain-lookup
ip domain-name RA11.domainname.com
security passwords min-length 14
enable secret pwdEn@b!3RA111
banner motd #Unauthorized access to this device is prohibited, property of BUT2ALTGrp2!#
username admin privilege 15 secret pwdSSHv.2RA111
crypto key generate rsa
1024
ip ssh version 2
ip ssh time-out 60
ip ssh authentication-retries 3
line console 0
password pwC0ns0!3RA111
login
logging synchronous
exit
line vty 0 4
login local
transport input ssh
exit
```

exit

write mem

Ra12 (USB 14):

en

conf t

hostname RA12

clock timezone CET 1

clock summer-time CEST recurring last Sun Mar 02:00 last Sun Oct 03:00

ntp server 172.16.16.21

interface fast0/0

ip address 172.16.16.9 255.255.255.252

no shut

Exit

interface range s0/0 - 2

shutdown

interface range eth1/2 - 3

shutdown

interface eth1/1

ip address 172.16.16.3 255.255.255.248

no shut

exit

interface eth1/0

no shut

ip address 172.16.16.13 255.255.255.252

router ospf 1

default-information originate always


```
redistribute static subnets
router-id 3.3.3.3
log-adjacency-changes
network 172.16.16.0 0.0.0.7 area 10
network 172.16.16.8 0.0.0.3 area 10
network 172.16.16.12 0.0.0.3 area 10
end
```

```
configure terminal
no ip domain-lookup
ip domain-name RA12.domainname.com
security passwords min-length 14
enable secret pwdEn@b!3RA122
banner motd #Unauthorized access to this device is prohibited, property of BUT2ALTGrp2!#
username admin privilege 15 secret pwdSSHv.2RA122
crypto key generate rsa
1024
ip ssh version 2
ip ssh time-out 60
ip ssh authentication-retries 3
line console 0
password pwC0ns0!3RA122
login
logging synchronous
exit
line vty 0 4
login local
transport input ssh
exit
exit
```

----- COUCHE DE DISTRIBUTION -----

SWx31 (USB 20) :

enable

configure terminal

hostname SWx31

clock timezone CET 1

clock summer-time CEST recurring last Sun Mar 2:00 last Sun Oct 3:00

system mtu routing 1500

ip subnet-zero

ip routing

authentication mac-move permit

ip dhcp excluded-address 192.168.16.1 192.168.16.3

ip dhcp excluded-address 192.168.16.32 192.168.16.63

ip dhcp pool VLAN2-SW32

network 192.168.16.0 255.255.255.192

default-router 192.168.16.1

dns-server 8.8.8.8

ip dhcp excluded-address 192.168.17.1 192.168.17.3

ip dhcp excluded-address 192.168.17.32 192.168.17.63

ip dhcp pool VLAN3-SW32

network 192.168.17.0 255.255.255.192

default-router 192.168.17.1

dns-server 8.8.8.8

ip dhcp excluded-address 192.168.19.0

```
ip dhcp excluded-address 192.168.19.4 192.168.19.7
ip dhcp pool VLAN4-SW32
network 192.168.19.0 255.255.255.248
default-router 192.168.19.1
option 150 ip 192.168.19.3
dns-server 8.8.8.8
spanning-tree mode rapid-pvst
spanning-tree etherchannel guard misconfig
spanning-tree extend system-id
spanning-tree vlan 2-3 priority 4096
spanning-tree vlan 4,7 priority 8192
vlan 2
name Filaire_Collaborateurs
vlan 3
name Administration
vlan 4
name Telephonie_IP
vlan 7
name Gestion
interface FastEthernet0/9
description Interface connecte au RA11 de la Couche Coeur de Reseau
no switchport
ip address 172.16.16.22 255.255.255.252
no shut
interface FastEthernet0/10
description Interface connecte au Ra12 de la couche Coeur de Reseau
no switchport
ip address 172.16.16.14 255.255.255.252
no shut
interface FastEthernet0/11
description Interface connecte au SWx24 de la Couche Acces
```

```
switchport mode trunk
switchport trunk allowed vlan 2-4,7
interface FastEthernet0/12
description Interface connecte au SWx21 de la Couche Acces
switchport mode trunk
switchport trunk allowed vlan 2-4,7
interface FastEthernet0/4
description Interface connecte au SWx34 de la Couche Distribution
switchport mode trunk
switchport trunk allowed vlan 2-4,7
interface FastEthernet0/3
description Interface connecte au SWx33 de la Couche Distribution
switchport mode trunk
switchport trunk allowed vlan 2-4,7
interface FastEthernet0/2
description Interface connecte au SWx32 de la Couche Distribution
switchport mode trunk
switchport trunk allowed vlan 2-4,7
interface range fa0/1
shutdown
interface range fa0/5 - 8
shutdown
interface range fa0/13 - 24
shutdown
interface range gi0/1 - 2
shutdown
interface Vlan1
no ip address
shutdown
interface Vlan2
ip address 192.168.16.2 255.255.255.192
```

```
standby 2 ip 192.168.16.1
standby 2 priority 110
standby 2 preempt
interface Vlan3
ip address 192.168.17.2 255.255.255.192
standby 3 ip 192.168.17.1
standby 3 priority 80
standby 3 preempt
interface Vlan4
ip address 192.168.19.2 255.255.255.248
standby 4 ip 192.168.19.1
standby 4 priority 110
standby 4 preempt
interface Vlan7
ip address 10.10.16.3 255.255.255.240
standby 7 ip 10.10.16.1
standby 7 priority 80
standby 7 preempt
exit
ip dhcp snooping
ip dhcp snooping vlan 2,3,4,7
ip arp inspection vlan 2,3,4
interface range fa0/11, fa0/12, fa0/22 - 24
no ip dhcp snooping trust
no ip arp inspection trust
exit
router ospf 1
router-id 1.1.1.1
log-adjacency-changes
network 172.16.16.12 0.0.0.3 area 10
network 172.16.16.20 0.0.0.3 area 10
```

```
network 192.168.16.0 0.0.0.63 area 10
network 192.168.17.0 0.0.0.63 area 10
network 192.168.19.0 0.0.0.7 area 10
ip default-gateway 10.10.16.1
ip route 192.168.22.0 255.255.255.0 172.16.16.21
ip route 192.168.22.0 255.255.255.0 172.16.16.13 10
ip classless
ip http server
ip http secure-server
ntp server 172.16.16.21
end
```

```
configure terminal
no ip domain-lookup
ip domain-name SWA31.domainname.com
security passwords min-length 14
enable secret pwdEn@b!3SWA31
banner motd #Unauthorized access to this device is prohibited, property of BUT2ALTGrp2!#
username admin privilege 15 secret pwdSSHv.2SWA31
crypto key generate rsa
1024
ip ssh version 2
ip ssh time-out 60
ip ssh authentication-retries 3
line console 0
password pwC0ns0!3SWA31
login
logging synchronous
exit
line vty 0 4
login local
```

```
transport input ssh
end
```

SWx32 (USB 21):

```
en
conf t
hostname SWx32
clock timezone CET 1
clock summer-time CEST recurring last Sun Mar 02:00 last Sun Oct 03:00
ntp server 172.16.16.21
interface vlan 1
shutdown
no ip address
vlan 2
name Collab
vlan 3
name Admin
vlan 4
name Tel-IP
vlan 7
name Gestion
interface vlan 2
ip address 192.168.16.3 255.255.255.192
standby 2 ip 192.168.16.1
standby 2 priority 80
standby 2 preempt
no shut
interface fa0/2
```

```
shutdown
interface range fa0/5 - 8
shutdown
interface range fa0/13 - 20
shutdown
interface range fa0/22 - 24
shutdown
interface range g0/1 - 2
shutdown
interface vlan 3
ip address 192.168.17.3 255.255.255.192
standby 3 ip 192.168.17.1
standby 3 priority 110
standby 3 preempt
no shut
interface vlan 4
ip address 192.168.19.3 255.255.255.248
standby 4 ip 192.168.19.1
standby 4 priority 80
standby 4 preempt
no shut
interface vlan 7
ip address 10.10.16.2 255.255.255.240
standby 7 ip 10.10.16.1
standby 7 priority 110
standby 7 preempt
no shut
ip default-gateway 10.10.16.1
spanning-tree mode rapid-pvst
spanning-tree vlan 2,3 priority 8192
spanning-tree vlan 4,7 priority 4096
```


ip dhcp snooping

ip dhcp snooping vlan 2,3,4,7

ip arp inspection vlan 2,3,4

no ip dhcp snooping information option

interface fa0/11

description Interface connecte au SWx22 de la Couche Acces

switchport mode trunk

switchport trunk allowed vlan 2,3,4,7

no shut

interface fa0/12

description Interface connecte au SWx23 de la Couche Acces

switchport mode trunk

switchport trunk allowed vlan 2,3,4,7

no shut

interface fa0/21

switchport mode trunk

switchport trunk allowed vlan 2,3,4,7

no shut

interface fa0/3

description Interface connecte au SWx33 de la Couche Distribution

switchport mode trunk

switchport trunk allowed vlan 2,3,4,7

no shut

interface fa0/4

description Interface connecte au SWx34 de la Couche Distribution

switchport mode trunk

switchport trunk allowed vlan 2,3,4,7

no shut

interface fa0/1

description Interface connecte au SWx31 de la Couche Distribution

switchport mode trunk

```
switchport trunk allowed vlan 2,3,4,7
no shut
interface fa0/9
description Interface connecte au Ra11 de la couche Coeur de Reseau
no switchport
ip address 172.16.16.18 255.255.255.252
no shut
interface fa0/10
description Interface connecte au Ra12 de la couche Coeur de Reseau
no switchport
ip address 172.16.16.10 255.255.255.252
no shut
ip routing
service dhcp
ip dhcp excluded-address 192.168.16.1 192.168.16.31
ip dhcp excluded-address 192.168.16.63 192.168.16.63
ip dhcp pool VLAN2-SW32
network 192.168.16.0 255.255.255.192
default-router 192.168.16.1
dns-server 8.8.8.8
ip dhcp excluded-address 192.168.17.1 192.168.17.31
ip dhcp excluded-address 192.168.17.63 192.168.17.63
ip dhcp pool VLAN3-SW32
network 192.168.17.0 255.255.255.192
default-router 192.168.17.1
dns-server 8.8.8.8
ip dhcp excluded-address 192.168.19.1 192.168.19.3
ip dhcp excluded-address 192.168.19.7 192.168.19.7
ip dhcp pool VLAN4-SW32
network 192.168.19.0 255.255.255.248
default-router 192.168.19.1
```

```
option 150 ip 192.168.19.3
dns-server 8.8.8.8
router ospf 1
router-id 4.4.4.4
log-adjacency-changes
network 172.16.16.8 0.0.0.3 area 10
network 172.16.16.16 0.0.0.3 area 10
network 192.168.16.0 0.0.0.63 area 10
network 192.168.17.0 0.0.0.63 area 10
network 192.168.19.0 0.0.0.7 area 10
exit
conf t
ip route 192.168.22.0 255.255.255.0 172.16.16.9
interface range fa0/11, fa0/12, fa0/21, fa0/23 - 24
no ip dhcp snooping trust
no ip arp inspection trust
end
configure terminal
no ip domain-lookup
ip domain-name SWA32.domainname.com
security passwords min-length 14
enable secret pwdEn@b!3SWA32
banner motd #Unauthorized access to this device is prohibited, property of BUT2ALTGrp2!#
username admin privilege 15 secret pwdSSHv.2SWA32
crypto key generate rsa
1024
ip ssh version 2
ip ssh time-out 60
ip ssh authentication-retries 3
line console 0
password pwC0ns0!3SWA32
```

```
login
logging synchronous
exit
line vty 0 4
login local
transport input ssh
exit
exit
```

SWx33 (USB 22):

```
en
conf t
hostname SWx33
clock timezone CET 1
clock summer-time CEST recurring last Sun Mar 02:00 last Sun Oct 03:00
ntp server 172.16.16.21
interface vlan 1
shutdown
no ip address
vlan 2
name Collab
vlan 3
name Admin
vlan 4
name Tel-IP
vlan 7
name Gestion
interface vlan 7
ip address 10.10.16.4 255.255.255.240
```

```
no shut
ip default-gateway 10.10.16.1
ip dhcp snooping
ip dhcp snooping vlan 2,3,4,7
ip arp inspection vlan 2,3,4
no ip dhcp snooping information option
int fa0/11
description Interface connecte au SWx22 de la Couche Acces
switchport mode trunk
switchport trunk allowed vlan 2,3,4,7
no shut
int fa0/12
description Interface connecte au SWx23 de la Couche Acces
switchport mode trunk
switchport trunk allowed vlan 2,3,4,7
no shut
int fa0/3
description Interface connecte au SWx34 de la Couche Distribution
switchport mode trunk
switchport trunk allowed vlan 2,3,4,7
no shut
int fa0/2
description Interface connecte au SWx32 de la Couche Distribution
switchport mode trunk
switchport trunk allowed vlan 2,3,4,7
no shut
int fa0/1
description Interface connecte au SWx31 de la Couche Distribution
switchport mode trunk
switchport trunk allowed vlan 2,3,4,7
no shut
```

```
int range fa0/4- 10
shutdown
int range fa0/13- 48
shutdown
int range gi0/1 - 4
shutdown
spanning-tree mode rapid-pvst
spanning-tree vlan 2,3,4,7 priority 24576
end
configure terminal
no ip domain-lookup
ip domain-name SWA33.domainname.com
security passwords min-length 14
enable secret pwdEn@b!3SWA33
banner motd #Unauthorized access to this device is prohibited, property of BUT2ALTGrp2!#
username admin privilege 15 secret pwdSSHv.2SWA33
crypto key generate rsa
1024
ip ssh version 2
ip ssh time-out 60
ip ssh authentication-retries 3
line console 0
password pwC0ns0!3SWA33
login
logging synchronous
exit
line vty 0 4
login local
transport input ssh
exit
exit
```

SWx34 (USB 23):

en

conf t

hostname SWx34

clock timezone CET 1

clock summer-time CEST recurring last Sun Mar 02:00 last Sun Oct 03:00

ntp server 172.16.16.21

interface vlan 1

shutdown

no ip address

vlan 2

name Collab

vlan 3

name Admin

vlan 4

name Tel-IP

vlan 7

name Gestion

interface vlan 7

ip address 10.10.16.9 255.255.255.240

no shut

exit

ip default-gateway 10.10.16.1

ip dhcp snooping

ip dhcp snooping vlan 2,3,4,7

ip arp inspection vlan 2,3,4

no ip dhcp snooping information option

int g1/0/11

description Interface connecte au SWx21 de la Couche Acces

switchport mode trunk

switchport trunk allowed vlan 2,3,4,7

no shut

Exit

int g0/0

shutdown

int g1/0/3

shutdown

int range gi1/0/5 - 10

shutdown

int range gi1/0/13 - 24

shutdown

int range gi1/1/1 - 4

shutdown

int g1/0/12

description Interface connecte au SWx24 de la Couche Acces

switchport mode trunk

switchport trunk allowed vlan 2,3,4,7

no shut

exit

int g1/0/1

description Interface connecte au SWx31 de la Couche Distribution

switchport mode trunk

switchport trunk allowed vlan 2,3,4,7

no shut

exit

int g1/0/2

description Interface connecte au SWx32


```
switchport mode trunk
switchport trunk allowed vlan 2,3,4,7
no shut
int g1/0/4
description Interface connecte au SWx33
switchport mode trunk
switchport trunk allowed vlan 2,3,4,7
no shut
exit
spanning-tree mode rapid-pvst
spanning-tree vlan 2,3,4,7 priority 24576
end
```

```
configure terminal
hostname SWA34
no ip domain-lookup
ip domain-name SWA34.domainname.com
security passwords min-length 14
enable secret pwdEn@b!3SWA34
banner motd #Unauthorized access to this device is prohibited, property of BUT2ALTGrp2!#
username admin privilege 15 secret pwdSSHv.2SWA34
crypto key generate rsa
1024
ip ssh version 2
ip ssh time-out 60
ip ssh authentication-retries 3
line console 0
password pwC0ns0!3SWA34
login
logging synchronous
exit
```

```
line vty 0 4
login local
transport input ssh
exit
exit
```

-----COUCHE ACCES -----

SW21 (USB 16):

```
en
conf t
hostname SW21
ip dhcp snooping
ip dhcp snooping vlan 2,3,4,7
ip arp inspection vlan 2,3,4
no ip dhcp snooping information option
Int range gig1/0/22 - gig1/0/28
shutdown
int range Gig1/0/1 - 21
switchport mode access
switchport port-security
switchport port-security maximum 1
switchport port-security violation restrict
switchport port-security mac-address sticky
int range Gig 1/0/23 - 24 description Uplink vers Distribution
switchport mode trunk
```

switchport trunk allowed vlan 2,3,4,7

ip dhcp snooping trust

ip arp inspection trust

int range Gig 1/0/1 - 10

description Interface sur le vlan 2

switchport access vlan 2

no shut

in range Gig 1/0/11 - 20

description Interface sur le vlan 3

switchport access vlan 3

no shut

int Gig 1/0/21

description Interface sur le vlan 4

switchport access vlan 4

no shut

exit

line vty 0 4

login local

transport input ssh

end

configure terminal

no ip domain-lookup

ip domain-name SWA21.domainname.com

security passwords min-length 14

enable secret pwdEn@b!3SWA21

banner motd #Unauthorized access to this device is prohibited, property of BUT2ALTGrp2!#

username admin privilege 15 secret pwdSSHv.2SWA21

crypto key generate rsa

1024

ip ssh version 2

```
ip ssh time-out 60
ip ssh authentication-retries 3
line console 0
password pwC0ns0!3SWA21
login
logging synchronous
exit
line vty 0 4
login local
transport input ssh
exit
exit
```

SW22 (USB 17):

```
en
conf t
hostname SW22
ip dhcp snooping
ip dhcp snooping vlan 2,3,4,7
ip arp inspection vlan 2,3,4
no ip dhcp snooping information option
int range Gig 0/23 – 24
description Uplink vers Distribution
switchport mode trunk
switchport trunk allowed vlan 2,3,4,7
ip dhcp snooping trust
ip arp inspection trust
int range gig0/22 - 24
```

```
shutdown
int range Gig 0/1 – 21
switchport mode access
switchport port-security
switchport port-security maximum 1
switchport port-security violation restrict
switchport port-security mac-address sticky
```

```
int range Gig 0/1 - 10
description Interface sur le vlan 2
switchport access vlan 2
no shut
```

```
int range Gig 0/11 - 20
description Interface sur le vlan 3
switchport access vlan 3
no shut
```

```
int Gig 0/21
description Interface sur le vlan 4
switchport access vlan 4
no shut
```

```
exit
line vty 0 4
login local
transport input ssh
end
```

```
configure terminal
no ip domain-lookup
ip domain-name SWA22.domainname.com
security passwords min-length 14
enable secret pwdEn@b!3SWA22
banner motd #Unauthorized access to this device is prohibited, property of BUT2ALTGrp2!#
```

```
username admin privilege 15 secret pwdSSHv.2SWA22
crypto key generate rsa
1024
ip ssh version 2
ip ssh time-out 60
ip ssh authentication-retries 3
line console 0
password pwC0ns0!3SWA22
login
logging synchronous
exit
line vty 0 4
login local
transport input ssh
end
```

SW23 (USB 18):

```
en
conf t
hostname SW23
ip dhcp snooping
ip dhcp snooping vlan 2,3,4,7
ip arp inspection vlan 2,3,4
no ip dhcp snooping information option
int range Fas 0/23 – 24
description Uplink vers Distribution
switchport mode trunk
switchport trunk allowed vlan 2,3,4,7
```

```
ip dhcp snooping trust
ip arp inspection trust
int range fa0/22 - 48
shutdown
int range g0/1 - 4
shutdown
int range Fas 0/1 - 21
switchport mode access
switchport port-security
switchport port-security maximum 1
switchport port-security violation restrict
switchport port-security mac-address sticky
int range Fas 0/1 – 10
description Interface sur le vlan 2
switchport access vlan 2
no shut
int range Fas 0/11 – 20
description Interface sur le vlan 3
switchport access vlan 3
no shut
int Fas 0/21
description Interface sur le vlan 4
switchport access vlan 4
no shut
exit
line vty 0 4
login local
transport input ssh
end
```

configure terminal

```
no ip domain-lookup
ip domain-name SWA23.domainname.com
security passwords min-length 14
enable secret pwdEn@b!3SWA23
banner motd #Unauthorized access to this device is prohibited, property of BUT2ALTGrp2!#
username admin privilege 15 secret pwdSSHv.2SWA23
crypto key generate rsa
1024
ip ssh version 2
ip ssh time-out 60
ip ssh authentication-retries 3
line console 0
password pwC0ns0!3SWA23
login
logging synchronous
exit
line vty 0 4
login local
transport input ssh
exit
exit
```

SW24 (USB 19):

```
en
conf t
hostname SW24
ip dhcp snooping
ip dhcp snooping vlan 2,3,4,7
ip arp inspection vlan 2,3,4
```



```
no ip dhcp snooping information option
int range Fas 0/23 – 24
description Uplink vers Distribution
switchport mode trunk
switchport trunk allowed vlan 2,3,4,7
ip dhcp snooping trust
ip arp inspection trust
int range fa0/22 - 48
shutdown
int range gi0/1- 4
shutdown
int range Fas 0/1 - 21
switchport mode access
switchport port-security
switchport port-security maximum 1
switchport port-security violation restrict
switchport port-security mac-address sticky
int range Fas 0/1 – 10
description Interface sur le vlan 2
switchport access vlan 2
no shut
int range Fas 0/11 - 20
description Interface sur le vlan 3
switchport access vlan 3
no shut
int Fas 0/21
description Interface sur le vlan 4
switchport access vlan 4
no shut
exit
line vty 0 4
```

login local

transport input ssh

end

configure terminal

no ip domain-lookup

ip domain-name SWA24.domainname.com

security passwords min-length 14

enable secret pwdEn@b!3SWA24

banner motd #Unauthorized access to this device is prohibited, property of BUT2ALTGrp2!#

username admin privilege 15 secret pwdSSHv.2SWA24

crypto key generate rsa

1024

ip ssh version 2

ip ssh time-out 60

ip ssh authentication-retries 3

line console 0

password pwC0ns0!3SWA24

login

logging synchronous

exit

line vty 0 4

login local

transport input ssh

exit

exit