# **Habit Tracker API**

# **Authentication Endpoints - api/auth.php**

# Login

- Method: GET
- Parameters: username (string), password (string)
- Returns: JSON object with user data and a session token if successful
- Throws: Exception if no results found
- HTTP Response Codes:
  - 200 if successful
  - 204 if no results found
  - 400 if parameters are missing or invalid

#### **Example Request:**

```
GET /auth.php?username=johndoe&password=pass123
```

#### Example Response:

# Register

- Method: POST
- Parameters: username (string), password (string), email (string)
- Returns: "Created" message if successful
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid, or username or email already in use

## **Example Request:**

POST /auth.php?username=johndoe&password=pass123&email=johndoe@example.com

#### Example Response:

```
Created
```

#### **Get User Info**

- Method: PUT
- Parameters: session (string)
- Returns: JSON object with user data if session is valid and not expired
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid
  - 401 if session is expired

#### **Example Request:**

```
PUT /auth.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb
```

#### Example Response:

# **CRUD Endpoints - api/crud.php**

## Creating a habit

- Method: POST
- Parameters: session (string), task (string), tag (string), start (string), end(string)
- Date Format: yyyy-mm-dd
- Returns: "Created" message if successful
- HTTP Response Codes:
  - 200 if successful.
  - 400 if parameters are missing or invalid

#### Example request:

```
POST /crud.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb&task=Re
ad%20a%20book&tag=Reading&start=2022-01-01&end=2022-01-31
```

#### Example response:

```
HTTP/1.1 200 OK
Content-Length: 7
Created
```

# **Retrieving habits**

- Method: GET
- Parameters: session (string)
- Returns: JSON object with habit data if session is valid and not expired
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid

#### Example request:

```
GET /crud.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb
```

#### Example response:

# **Updating a habit**

- Method: PUT
- Parameters: session (string), id (string), task (string Optional), tag (string Optional), start (string Optional), end(string Optional)
- Date Format: yyyy-mm-dd
- Returns: "Updated" message if successful
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid

#### Example request:

```
PUT /crud.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb&id=1&task=Read%20two%20books
```

#### Example response:

```
HTTP/1.1 200 OK
Content-Length: 7
Updated
```

## **Deleting a habit**

- Method: DELETE
- Parameters: session (string), id (string)
- Returns: "Deleted" message if successful
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid

#### Example request:

```
DELETE /crud.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb&id=1
```

#### Example response:

```
HTTP/1.1 200 OK
Content-Length: 7
Deleted
```

# Search Endpoint - api/search.php

#### Search habits

- Method: GET
- Parameters: session (string), task (string Optional), tag (string Optional), start (string Optional), end(string Optional)
- Date Format: yyyy-mm-dd
- Returns: JSON object with habit data if session is valid and not expired
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid

#### Example request:

```
GET /search.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb&id=1&ta
sk=Read%20two%20books
```

#### Example response:

```
[
    "id": "1",
    "uid": "123",
    "task": "Read a book",
    "tag": "Reading",
    "start": "2022-01-01",
    "end": "2022-01-31"
    }
]
```

# Calendar Endpoint - api/calendar.php

#### **Calendar Sort habits**

- · Method: GET
- Parameters: session (string), date (string ['end' or 'first]'), date\_start (string), date\_end (string)
- Date Format: yyyy-mm-dd
- Returns: JSON object with sorted habit data based on dates if session is valid and not expired
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid

#### Example request:

```
GET /calendar.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb&date=20
22-01-01&date start=2022-01-01&date end=2022-01-31
```

#### Example response:

```
{
    "id": "2",
    "uid": "1",
    "task": "test",
    "tag": "tested",
    "start": "2023-02-14 00:00:00",
    "end": "2023-02-15 00:00:00",
    "created": "2023-02-14 19:23:28"
},
    "id": "3".
    "uid": "1",
    "task": "TestTask",
    "tag": "TestTag",
    "start": "2023-02-27 00:00:00",
    "end": "2023-02-28 00:00:00",
    "created": "2023-02-27 19:50:45"
}
```

# Statistics Endpoint - api/statistics.php

#### Calculate Stats for Habits

- Method: GET
- Parameters: session (string), date (string), length (string)
- Date Format: yyyy-mm-dd

- Returns: JSON object with sorted habit data based on dates if session is valid and not expired
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid

#### Example request:

```
GET /statistics.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb&date=20
22-01-01&date=2022-01-01&length=60
```

#### Example response:

```
"HabitsCount": 2,
"TagPercent": {
    "tested": 50,
    "TestTag": 50
},
"HabitsDays": [
    {
        "end": "2023-02-15 00:00:00",
        "count": "1"
    },
    {
        "end": "2023-02-28 00:00:00",
        "count": "1"
    }
],
"ShortestHabit": "1",
"LongestHabit": "3"
```

# Goals Endpoint - api/goals.php

#### **Create Goals**

- Method: POST
- Parameters: session (string), tag (string), goal (string), end (string)
- Date Format: yyyy-mm-dd
- Returns: Created or Failed
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid

#### Example request:

```
GET /goals.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb&goal=dr
ink&end=2022-01-01
```

#### Example response:

```
HTTP/1.1 200 OK
Content-Length: 7
Created
```

## **Get Goals**

- Method: GET
- Parameters: session (string)
- Date Format: yyyy-mm-dd
- Returns: JSON object with goals for that user
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid

#### Example request:

```
GET /goals.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb
```

#### Example response:

#### **Delete Goal**

- Method: DELETE
- Parameters: session (string), id (string)
- Date Format: yyyy-mm-dd
- Returns: Deletes the goal
- HTTP Response Codes:
  - 200 if successful
  - 400 if parameters are missing or invalid

#### Example request:

```
GET /goals.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb&id=1
```

#### Example response:

```
HTTP/1.1 200 OK
Content-Length: 7
Deleted
```

# Leaderboard Endpoint - api/leaderboard.php

## **Get leaderboard**

Method: GET

• Parameters: session (string)

• Date Format: yyyy-mm-dd

• Returns: returns Leaderboard JSON object

• HTTP Response Codes:

• 200 if successful

• 400 if parameters are missing or invalid

#### Example request:

```
GET /leaderboard.php?
session=9tAKsZ7rxW2s8Yr7TjTbTcJTjVgsTtJ4hKj4D4PmDKZzt0eI1jYw1mJlKTlLNMb
```

#### Example response: