

RC4 Algorithm

Quentin Stickler, B.Sc.

April 7, 2024

Agenda



The Rise and Fall of RC4

Why it's not really used anymore

- Stream cipher with variable key-size length
- Used to be most wiedely used stream cipher in Software applications
- Invented in 1987 by Ron Rivest for RSA security
- Kept secret but got leaked in 1994
- Easy to implement and quite fast
- ...but also very vulnerable

RC4 Algorithm

How does it work?

- Consists of two parts
- Part 1: Initialization
- Part 2: Keystream Generator
- S-Box (Array) with length of 256
- Two 8-byte sized counters i and i

RC4 Initialization

Part One: Filling S-Box and T-Box

- S-Box with length 256
- Counters i and i set to 0
- Linear filling of the S-Box from 0 to 255 (S[0] = 0, S[1] = 1...)
- Following loop will be run:

```
for x in range(256): ###Initilaze S-Box and T-Box
S[x] = x
T[x] = asciikev[x % kevlength]
```

Initialization

Example

- Text = "TestText"
- Key = "TestKey"
- S-Box = [0, 1, 2, 3 ..., 255]
- Initialization of T-Box:
 - Keylength = 7
 - Ascii-Text = 84 101 115 116 75 101 121

```
      84
      101
      115
      116
      75
      101
      121

      84
      101
      115
      116
      75
      101
      121

      ...
      ...
      ...
      ...
      ...
      ...

      ...
      ...
      84
      101
      115
      116
```

RC4 Initialization

Part Two: Permutation

- Permutate S-Box based on given key
- We always use modulo n = 256 because of the given length

```
j = 0
for i in range(256):
    j = (j + S[i] + T[i]) % 256
    currentvalue = S[i]
    S[i] = S[j]
    S[j] = currentvalue
```

• At the end: (Pseudo-)randomly generated S-Box

Permutation Example

```
• S-Box Initialization: 0 1 2 3 4 5 6 ... ... ... ... 249 250 251 252 253 254 255
```

- j = 0
- $j = (j + S[i] + T[i]) \mod(256)$
- $j = (84 + 0 + 84) \mod(256) = 168 \mod(256) = 168$
- Swap S[i] (0) and S[j] (84)
- S[i] = 84, S[j] = 0

Permutation Example Cont'd

```
    84
    1
    2
    3
    4
    5
    6

    ...
    ...
    ...
    ...
    ...
    ...
    ...

    80
    81
    82
    83
    0
    85
    86

    ...
    ...
    ...
    ...
    ...
    ...
    ...

    249
    250
    251
    252
    253
    254
    255
```

- j = 1
- $j = (j + S[i] + T[i]) \mod(256)$
- j = (186 + 1 + 101) mod(256) = 288 mod (256) = 32
- Swap S[i] (1) and S[j] (186)
- S[i] = 186, S[j] = 1



Permutation Example Cont'd

- i = 2
- $j = (j + S[i]) + T[i] \mod(256)$
- j = (47 + 2 + 115) mod(256) = 126 mod (256) = 126
- Swap S[i] (1) and S[j] (47)
- S[i] = 47, S[j] = 2

Permutation Example

Final S-Box Form

```
47
                                   95
                                                                                           38
                                                                             246
138
                                   143
                                                                                                  196
                                                                                                         146
                            34
                                                               183
                                                                                                          4
                     67
                                                               87
                                                                                    97
44
                     48
                            141
                                                        94
                                                                                           89
                                                                                                         24
              181
                                          43
                                                                      243
              140
                            145
                                          182
                                                                      189
                                                                             81
                                          147
                                                        106
                                                                                                          18
                                                                                           6
                     46
                            49
                                                               40
                                                 136
                     64
                                          149
                                                                      187
                                                                             214
                                                                                    86
                                                                                           242
                                                                                                         76
              142
                                                        180
                                                                                           36
                     61
                                                                                                          14
                           247
                                   85
96
                                                                                                         241
```

- Result = Permutated S-Box
- All numbers from 0-255 in "random" places

Generate keystream depending on length of given plaintext

```
for x in range(plaintextlength):
    i = (i + 1) % 256
    j = (j + S[i]) % 256
    currentValue = S[i]
    S[i] = S[j]
    S[j] = currentValue
    t = (S[i] + S[j]) % 256
    keystream.append(S[t])
    return keystream
```

Example, i = 0

- i = 0, j = 0
- $i = (0 + 1) \mod 256 = 1$
- j = (0 + 186) mod 256 = 186 mod 256 = 186
- Swap S[i] (186) and S[j] (202)
- t = (202 + 186) mod 256 = 388 mod 256 = 132
- keystream = [132,]

Example, i = 1

- i = 1, j = 186
- $i = (1 + 1) \mod 256 = 2$
- j = (186 + 47) mod 256 = 233 mod 256 = 233
- Swap S[i] (47) and S[j] (11)
- t = (47 + 11) mod 256 = 58 mod 256 = 58
- keystream = [132, 58,]

Example, i = 2

- i = 2, j = 233
- $i = (2 + 1) \mod 256 = 3$
- j = (233 + 208) mod 256 = 451 mod 256 = 185
- Swap S[i] (208) and S[j] (90)
- t = (208 + 90) mod 256 = 298 mod 256 = 42
- keystream = [132, 58, 42,]
- Final keystream = [132, 58, 42, 7, 129, 233, 245, 149]

Encryption

- Plaintext XOR keystream
- Plaintext = "TestText"
- Ascii:

Decryption

Ciphertext XOR keystream

Attacks on RC4

WEP

Short summary

Attacking RC4 in WEP

Prevention against this attack