

Tera

Render templates from inline text or named files



Install & load

```
INSTALL tera FROM community;  
LOAD tera;
```

01 At a glance

Render JSON context with Tera's variables, filters, loops, and conditionals. Keep short templates in SQL, or load named files for larger templates and inheritance. Results are ordinary text columns ready for export or further processing.

Text or file → JSON context → Rendered text

02 SQL entry point + template syntax

`tera_render(template)`

Render inline template text without context.

`tera_render(template, context)`

Render with a JSON object supplying variables.

`autoescape := false`

Turn off HTML escaping for non-HTML output.

`template_path := glob`

Load template files; the first argument becomes a name.

`{{ value | upper }}`

Interpolate a value and apply a Tera filter.

`{% for x in items %}`

Loop through context items; finish with `endfor`.

03 Keep in mind

Choose inline text or a file

Without `template_path`, the first argument is template source. With a file glob, use a matching template name such as `email.html`. Files support includes, inheritance, and reusable template authoring outside SQL.

04 Render HTML from context

```
SELECT tera_render(  
  '<p>{{ name | upper }}</p>',  
  '{"name": "Ada & Grace"}'  
);  
-- <p>ADA & GRACE</p>
```

HTML escaping applies to the interpolated value.

05 Render a plain-text list

```
SELECT tera_render(  
  '{% for x in xs %}{{ x }}' ||  
  '{% if not loop.last %}, {% endif %}' ||  
  '{% endfor %}',  
  '{"xs": ["B&O", "Acme"]}',  
  autoescape := false  
);  
-- B&O, Acme
```

Use `loop.last` for separators; disable `autoescape` for plain text.

06 Use a named template file

REQUIRES SETUP

```
SELECT tera_render(  
  'email.html', '{"name": "Ada"}',  
  template_path := './templates/*.html'  
);
```

Requires `./templates/email.html`, for example: `Hello {{ name }}!`

07 In practice

Escaping follows the output

HTML `autoescape` is enabled by default. Turn it off for plain text or configuration output, and keep templates trusted. For generated SQL, pass untrusted values through prepared-statement parameters instead of interpolating them.

[Full docs & examples ↗](#) [Source ↗](#)