

Textplot

Small charts inside your query results.



Install & load

```
INSTALL textplot FROM community;
LOAD textplot;
```

01 At a glance

Render a numeric sequence or progress value as terminal-friendly text. Keep the underlying values for sorting and computation; add plots as a compact visual summary.

Numbers



Plot function



VARCHAR chart

02 Core SQL surface

`tp_bar(value, ...)`

Render one value against a configured range.

`tp_sparkline(values, ...)`

Render a DOUBLE list as a compact sequence.

`tp_density(values, ...)`

Render the distribution of a DOUBLE list.

`tp_qr(text, ...)`

Render text as an ASCII or Unicode QR code.

`width := n`

Control chart width with a named argument.

`array_agg(value ORDER BY time)`

Build an ordered sequence before rendering a sparkline.

03 Keep in mind

Match the terminal

Use ASCII styles where Unicode width or emoji rendering is unreliable. Dense characters can look different across terminal fonts and exported logs.

04 An ASCII progress bar

```
SELECT tp_bar(0.7, width := 15,
  "on" := '#', "off" := '-');
```

Quote reserved named arguments such as on and off.

05 A sequence & a distribution

```
SELECT tp_sparkline([1, 3, 2, 5, 4, 6],
  theme := 'ascii_basic');

SELECT tp_density([1, 5, 3, 8, 2],
  style := 'ascii');
```

Sparklines preserve sequence; density summarizes the distribution.

06 Aggregate in order

```
SELECT tp_sparkline(
  array_agg(value ORDER BY step),
  theme := 'ascii_basic'
) AS trend
FROM (VALUES (1, 4.0), (2, 7.0),
  (3, 5.0)) AS t(step, value);
```

Use ORDER BY inside array_agg so chronology is explicit.

07 In practice

A picture is a string

Plot functions return VARCHAR. Aggregate and order the numeric data before plotting; sort results on the numbers, not on the rendered bars.

[Full docs & examples ↗](#) [Source ↗](#)