Inflector

Normalize names, keys, and query result columns

Install & load

```
SET allow_extension_repositories = 'allowed';
CREATE EXTENSION REPOSITORY IF NOT EXISTS query_farm WITH PREFIX 'https://duckdb-extensions.query.farm';
INSTALL inflector FROM query_farm;  LOAD inflector FROM query_farm;
```

01 At a glance

Apply consistent naming conventions to strings, struct keys, or every column of a query. Combine case conversion with English inflection helpers when cleaning imported schemas, generating identifiers, or shaping data for another system.

Mixed names → Choose a format → Consistent shape

02 Core SQL surface

`inflect(format, value)`

Transform a string or rename keys in a struct.

`FROM inflect(format, (query))`

Rename all result columns from a query.

`inflector_to_snake_case(text)`

Convert one name; _camel_case and _pascal_case also exist.

`inflector_to_table_case(text)`

Build a plural snake_case table name.

`inflector_to_plural / _to_singular(word)`

Apply English pluralization or singularization rules.

`inflector_humanize / _parameterize(text)`

Readable labels and URL slugs; inflector_classify builds class names.

`SET inflector_acronyms = ['API']`

Keep acronyms uppercase in camel and Pascal output; per connection.

03 Keep in mind

Select the shape you mean

inflect changes string contents, struct field names, or result column names according to the input type. Values inside a renamed struct or query remain unchanged. Common formats include snake, camel, pascal, and kebab.

04 Normalize nested data keys

```
SELECT inflect('snake', {
  'firstName': 'Ada',
  'lastName': 'Lovelace'
});
-- {first_name: Ada, last_name: Lovelace}
```

Pass a STRUCT; field names change while their values stay intact.

05 Rename a complete result

```
SELECT * FROM inflect('snake', (
  SELECT 'Ada' AS firstName,
         'Lovelace' AS lastName
));
-- columns: first_name, last_name
```

Replace the inner SELECT with your import or transformation query.

06 Derive table and word names

```
SELECT inflector_to_table_case('UserAccount');
-- user_accounts
SELECT inflector_to_singular('people');
-- person
SELECT inflector_parameterize('Hello World!');
-- hello-world
```

Use scalar helpers for individual naming decisions.

07 In practice

Check English edge cases

Inflection is English-specific and not always reversible, though irregulars such as people → person and children → child are handled. If two names collide after renaming, later ones get _1, _2 in column order. Validate the vocabulary that matters to your data.

Full docs & examples ↗ Source ↗