Tera

Render templates from inline text or named files

Install & load

```
SET allow_extension_repositories = 'allowed';
CREATE EXTENSION REPOSITORY IF NOT EXISTS query_farm WITH PREFIX 'https://duckdb-extensions.query.farm';
INSTALL tera FROM query_farm;  LOAD tera FROM query_farm;
```

01 At a glance

Render JSON context with Tera's variables, filters, loops, and conditionals. Keep short templates in SQL, or load named files for larger templates and inheritance. Results are ordinary text columns ready for export or further processing.

Text or file → JSON context → Rendered text

02 SQL entry point + template syntax

`tera_render(template)`

Render inline template text without context.

`tera_render(template, context)`

Render with a JSON object or struct; arrays and scalars are errors.

`autoescape := false`

Turn off HTML escaping for non-HTML output.

`template_path := glob`

Load template files through DuckDB's file system; the first argument becomes a name.

`SET tera_allow_get_env = true`

Opt in to get_env(); it is disabled by default and without external access.

`{{ value | upper }}`

Interpolate a value and apply a Tera filter.

`{% for x in items %}`

Loop through context items; finish with endfor.

03 Keep in mind

Choose inline text or a file

Without template_path, the first argument is template source. With a file or glob, use a matching template name such as email.html; a glob that matches nothing is an error. Files support includes, inheritance and macros, and respect allowed_directories when external access is off.

04 Render HTML from context

```
SELECT tera_render(
  '<p>{{ name | upper }}</p>',
  '{"name":"Ada & Grace"}'
);
-- <p>ADA &amp;amp; GRACE</p>
```

HTML escaping applies to the interpolated value.

05 Render a plain-text list

```
SELECT tera_render(
  '{% for x in xs %}{{ x }}' ||
  '{% if not loop.last %}, {% endif %}' ||
  '{% endfor %}',
  {'xs': ['B&O', 'Acme']},
  autoescape := false
);
-- B&O, Acme
```

A struct casts to the JSON context; disable autoescape for plain text.

06 Use a named template file

REQUIRES SETUP

```
SELECT tera_render(
  'email.html', '{"name":"Ada"}',
  template_path := './templates/*.html'
);
```

Requires ./templates/email.html, for example: Hello {{ name }}!

07 In practice

Escaping follows the output

HTML autoescape is enabled by default. Turn it off for plain text or configuration output, and keep templates trusted. For generated SQL, pass untrusted values through prepared-statement parameters instead of interpolating them.

Full docs & examples ↗ Source ↗