WebMacro

Share SQL macros through a trusted URL.

Install & load

```
SET allow_extension_repositories = 'allowed';
CREATE EXTENSION REPOSITORY IF NOT EXISTS query_farm WITH PREFIX 'https://duckdb-extensions.query.farm';
INSTALL webmacro FROM query_farm;  LOAD webmacro FROM query_farm;
```

01 At a glance

Load a DuckDB macro definition from an HTTPS endpoint and call it in ordinary SQL. Use reviewed, versioned SQL files to distribute reusable scalar expressions and table queries across notebooks and applications.

SQL at a URL → Load definition → Call the macro

02 Loading & macro lifecycle

`load_macro_from_url(url)`

Fetch over HTTPS and register one macro; return a status string.

`CREATE MACRO name(args) AS expression`

Define a scalar macro in the hosted SQL file.

`CREATE MACRO name(args) AS TABLE …`

Define a table macro called from a FROM clause.

`CREATE OR REPLACE MACRO …`

Let reloading replace a previously registered definition.

`SET webmacro_allow_http = true`

Permit plain http:// URLs, refused by default; trusted networks only.

`SET webmacro_max_response_size = n`

Largest accepted response in bytes; the default is 1 MiB.

`duckdb_functions()`

Inspect registered macros with function_type = 'macro'.

`DROP MACRO name`

Remove a loaded macro with DuckDB's ordinary lifecycle command.

03 Keep in mind

The SQL file is executable code

Load only reviewed SQL from a trusted host. The response must hold exactly one CREATE MACRO statement, but that check is not a sandbox. Pin immutable revision URLs when reproducibility matters; a branch URL can change after review.

04 Prepare a reusable definition

```
CREATE OR REPLACE MACRO normalize_tag(s)
AS lower(trim(s));
SELECT normalize_tag('  Farm  ') AS tag;
-- Result: farm
```

Test locally, then publish the CREATE statement as normalize_tag.sql on your host.

05 Load the hosted SQL

REQUIRES SETUP

```
SELECT load_macro_from_url(
  'https://example.com/normalize_tag.sql'
);
SELECT normalize_tag('  Farm  ') AS tag;
```

Replace the placeholder URL with the trusted SQL file prepared above.

06 Inspect and remove a macro

```
SELECT function_name, macro_definition
FROM duckdb_functions()
WHERE function_type = 'macro'
  AND function_name = 'normalize_tag';
DROP MACRO normalize_tag;
```

After creation or loading, it behaves like an ordinary DuckDB macro.

07 In practice

Load dependencies first

Each call fetches its URL again through DuckDB's HTTP stack: http_timeout, http_proxy and HTTP secrets apply, and redirects are rechecked. There is no dependency resolver, so load prerequisite macros first. Nothing is fetched while enable_external_access is false.

Full docs & examples ↗ Source ↗