UDP Header

Bit Number

1111111111222222222233

01234567890123456789012345678901

Source Port	Destination Port
Length	Checksum

UDP Header Information

Common UDP Well-Known Server Ports

7	echo	138	netbios-dgm
19	chargen	161	snmp
37	time	162	snmp-trap
53	domain	500	isakmp
67	bootps (DHCP)	514	syslog
68	bootpc (DHCP)	520	rip
69	tftp	33434	traceroute
137	netbios-ns		

Length
(Number of bytes in entire datagram including header; minimum value = 8)

Checksum
(Covers pseudo-header and entire UDP datagram)

ARP

Bit Number

1111111111222222222233

01234567890123456789012345678901

Hardware Address Type		Protocol Address Type
H/w Addr Len	Prot. Addr Len	Operation
Source Hardware Address		
Source Hardware Addr (cont.)		Source Protocol Address
Source Protocol Addr (cont.)		Target Hardware Address
Target Hardware Address (cont.)		
Target Protocol Address		

ARP Parameters (for Ethernet and IPv4)

Hardware Address Type
1 Ethernet
6 IEEE 802 LAN

Protocol Address Type
2048 IPv4 (0x0800)

Hardware Address Length
6 for Ethernet/IEEE 802

Protocol Address Length
4 for IPv4

Operation
1 Request
2 Reply

SANS

INTERNET STORM CENTER

TCP/IP and tcpdump

Version July-2010

POCKET REFERENCE GUIDE

ISC@sans.org • www.sans.org • http://isc.sans.org

tcpdump Usage

```
tcpdump  [-aenStvx]  [-F file]
[-i int]  [-r file]  [-s snaplen]
[-w file]  ['filter_expression']

-e Display data link header.
-F Filter expression in file.
-i Listen on int interface.
-n Don't resolve IP addresses.
-r Read packets from file.
-s Get snaplen bytes from each packet.
-S Use absolute TCP sequence numbers.
-t Don't print timestamp.
-v Verbose mode.
-w Write packets to file.
-x Display in hex.
-X Display in hex and ASCII.
```

Acronyms

AH	Authentication Header (RFC 2402)
ARP	Address Resolution Protocol (RFC 826)
BGP	Border Gateway Protocol (RFC 1771)
CWR	Congestion Window Reduced (RFC 2481)
DF	Don't Fragment bit (IP)
DHCP	Dynamic Host Configuration Protocol (RFC 2131)
DNS	Domain Name System (RFC 1035)
ECN	Explicit Congestion Notification (RFC 3168)
EIGRP	Extended IGRP (Cisco)
ESP	Encapsulating Security Payload (RFC 2406)
FTP	File Transfer Protocol (RFC 959)
GRE	Generic Routing Encapsulation (RFC 2784)
HTTP	Hypertext Transfer Protocol (RFC 1945)
ICMP	Internet Control Message Protocol (RFC 792)
IGMP	Internet Group Management Protocol (RFC 2236)
IGRP	Interior Gateway Routing Protocol (Cisco)
IMAP	Internet Message Access Protocol (RFC 2060)
IP	Internet Protocol (RFC 791)
ISAKMP	Internet Security Association & Key Management Protocol (RFC 2408)
L2TP	Layer 2 Tunneling Protocol (RFC 2661)
NNTP	Network News Transfer Protocol (RFC 977)
OSPF	Open Shortest Path First (RFC 1583)
POP3	Post Office Protocol v3 (RFC 1460)
RFC	Request for Comments
RIP	Routing Information Protocol (RFC 2453)
LDAP	Lightweight Directory Access Protocol (RFC 2251)
SKIP	Simple Key-Management for Internet Protocols
SMTP	Simple Mail Transfer Protocol (RFC 821)
SNMP	Simple Network Management Protocol (RFC 1157)
SSH	Secure Shell
SSL	Secure Sockets Layer (Netscape)
TCP	Transmission Control Protocol (RFC 793)
TFTP	Trivial File Transfer Protocol (RFC 1350)
TOS	Type of Service field (IP)
UDP	User Datagram Protocol (RFC 768)

All RFCs can be found at http://www.rfc-editor.org

DNS

Bit Number

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
LENGTH (TCP ONLY)															
ID.															
QR	Opcode				AA	TC	RD	RA	Z				RCODE		
QDCOUNT															
ANCOUNT															
NSCOUNT															
ARCOUNT															
Question Section															
Answer Section															
Authority Section															
Additional Information Section															

DNS Parameters

Query/Response
0 Query
1 Response

Opcode
0 Standard query (QUERY)
1 Inverse query (IQUERY)
2 Server status request (STATUS)

AA
(1 = Authoritative Answer)

TC
(1 = TrunCation)

RD
(1 = Recursion Desired)

RA
(1 = Recursion Available)

Z
(Reserved; set to 0)

Response code
0 No error
1 Format error
2 Server failure
3 Non-existant domain (NXDOMAIN)
4 Query type not implemented
5 Query refused

QDCOUNT
(No. of entries in Question section)

ANCOUNT
(No. of resource records in Answer section)

NSCOUNT
(No. of name server resource records in Authority section)

ARCOUNT
(No. of resource records in Additional Information section.

ICMP

Bit Number

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Type								Code								Checksum															
Other message-specific information...																															

Type Name/Codes (Code=0 unless otherwise specified)

0 Echo Reply
3 Destination Unreachable
0 Net Unreachable
1 Host Unreachable
2 Protocol Unreachable
3 Port Unreachable
4 Fragmentation Needed & DF Set
5 Source Route Failed
6 Destination Network Unknown
7 Destination Host Unknown
8 Source Host Isolated
9 Network Administratively Prohibited
10 Host Administratively Prohibited
11 Network Unreachable for TOS
12 Host Unreachable for TOS
13 Communication Administratively Prohibited
4 Source Quench
5 Redirect
0 Redirect Datagram for the Network
1 Redirect Datagram for the Host
2 Redirect Datagram for the TOS & Network
3 Redirect Datagram for the TOS & Host
8 Echo
9 Router Advertisement
10 Router Selection
11 Time Exceeded
0 Time to Live exceeded in Transit
1 Fragment Reassembly Time Exceeded
12 Parameter Problem
0 Pointer indicates the error
1 Missing a Required Option
2 Bad Length
13 Timestamp
14 Timestamp Reply
15 Information Request
16 Information Reply
17 Address Mask Request
18 Address Mask Reply
30 Traceroute

PING (Echo/Echo Reply)

Bit Number

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Type (8 or 0)								Code (0)								Checksum															
Identifier																Sequence Number															
Data...																															

IP Header

Bit Number

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Version				IHL				Type of Service								Total Length															
Identification																Flags			Fragment Offset											
Time to Live								Protocol								Header Checksum															
Source Address																															
Destination Address																															
Options (optional)																															

IP Header Contents

Version
4 IP version 4

Internet Header Length
Number of 32-bit words in IP header; minimum value = 5 (20 bytes) & maximum value = 15 (60 bytes)

Type of Service (PreDTRCx) --> Differentiated Services

Precedence	(000-111)	000
D	(1 = minimize delay)	0
T	(1 = maximize throughout)	0
R	(1 = maximize reliability)	0
C	(1 = minimize cost)	1 = ECN capable
x	(reserved and set to 0)	1 = congestion experienced

Total Length
Number of bytes in packet; maximum length = 65,535

Flags (xDM)
x (reserved and set to 0)
D (1 = Don't Fragment)
M (1 = More Fragments)

Fragment Offset
Position of this fragment in the original datagram, in units of 8 bytes

Protocol

1 ICMP	17 UDP	57 SKIP
2 IGMP	47 GRE	88 EIGRP
6 TCP	50 ESP	89 OSPF
9 IGRP	51 AH	115 L2TP

Header Checksum
Covers IP header only

Addressing

NET_ID	RFC 1918 PRIVATE ADDRESSES
0-127 Class A	10.0.0.0-10.255.255.255
128-191 Class B	172.16.0.0-172.31.255.255
192-223 Class C	192.168.0.0-192.168.255.255
224-239 Class D	(multicast)
240-255 Class E	(experimental)

HOST_ID
0 Network value; broadcast (old)
255 Broadcast

Options (0-40 bytes; padded to 4-byte boundary)

0 End of Options list	68 Timestamp
1 No operation (pad)	131 Loose source route
7 Record route	137 Strict source route

TCP Header

Bit Number

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Source Port																Destination Port															
Sequence Number																															
Acknowledgment Number																															
Offset (Header Length)				Reserved						Flags						Window															
Checksum																Urgent Pointer															
Options (optional)																															

TCP Header Contents

Common TCP Well-Known Server Ports

7 echo	110 pop3
19 chargen	111 sunrpc
20 ftp-data	119 nntp
21 ftp-control	139 netbios-ssn
22 ssh	143 imap
23 telnet	179 bgp
25 smtp	389 ldap
53 domain	443 https (ssl)
79 finger	445 microsoft-ds
80 http	1080 socks

Offset
Number of 32-bit words in TCP header; minimum value = 5

Reserved
4 bits; set to 0

Flags (CEUAPRSF)

ECN bits (used when ECN employed; else 00)
CWR (1 = sender has cut congestion window in half)
ECN-Echo (1 = receiver cuts congestion window in half)

U (1 = Consult urgent pointer, notify server application of urgent data)
A (1 = Consult acknowledgement field)
P (1 = Push data)
R (1 = Reset connection)
S (1 = Synchronize sequence numbers)
F (1 = no more data; Finish connection)

Checksum
Covers pseudoheader and entire TCP segment

Urgent Pointer
Offset pointer to urgent data

Options

0 End of Options list	3 Window scale
1 No operation (pad)	4 Selective ACK ok
2 Maximum segment size	8 Timestamp