Grind Karo Coach Admin — Copy Phone on Athlete Page

30-Minute Screen Recording Guide (narration ↔ input sync)

Task title: Copy phone on athlete page
Repository: `Grind-karo-Admin`
Route under test: `/users/:id` (`UserDetailPage.tsx`)
Coding on camera: ~~6–8 minutes (~~25%)
Walkthrough + verification: ~22–24 minutes

How to read synced beats

Each **beat** has three lanes—perform them **in order**, left to right:

Lane	Meaning
Mouse / keyboard	Exact UI input (pause ~1s after each click)
Narration (what / where / why)	Full sentences; name **files**, **symbols**, and **UI labels**—avoid “this”, “that”, “here”, “it” without a noun
Expected on screen	What the viewer should see before the next beat

Narration rule: Replace vague pointers with concrete names.

- Weak: “I click this and copy that.”
- Strong: “I click the **Copy phone** ghost button beside `phoneStatus.label` in the athlete header.”

Table of contents

1. Definition of done
2. Prerequisites
3. TODO map
4. Walkthrough beats (5–7 minutes)
5. Coding beats — TODO 1–6
6. Verification beats
7. Minute-by-minute master timeline
8. Closing summary narration
9. Deliverables checklist

---

1. Definition of done

Requirement	Detail
Where	Athlete header on `UserDetailPage`, phone row next to the `Phone` lucide icon
What	New `CopyPhoneButton` copies `phoneStatus.label` (formatted display string)
Feedback	Button text **Copy phone** → **Copied** → **Copy phone** (~2 seconds)
When hidden	Amber **Number missing** pill — **no** `CopyPhoneButton`

What not to do	No `PUT`/`PATCH` user APIs; clipboard only

Reference: `CopyEmailButton.tsx` (same clipboard + timer pattern).

---

2. Prerequisites

Environment

```
cp .env.example .env   # VITE_API_BASE_URL=https://api.grindkaro.in
npm install
npm run dev            # http://localhost:5173
```

Test athletes (fake data on camera — no PII)

Label	Phone on record	URL pattern	Header expectation
Athlete A	Valid digits	`/users/<uuid-a>`	`phoneStatus.label` + **Copy phone** after TODO 6
Athlete B	Empty / null	`/users/<uuid-b>`	**Number missing** only

Apps (Metadata topology)

Brave (LOOKUP) → Visual Studio Code (CREATE/MODIFY) → Brave (LOOKUP) → VS Code integrated Terminal (LOOKUP)

---

3. TODO map

TODO	File	Where to look	Outcome
1	`src/components/users/CopyPhoneButton.tsx`	Below file header comment	`COPIED_CONFIRMATION_MS` constant
2	Same	Inside `CopyPhoneButton`	`copied` state + reset `useEffect`
3	Same	Before `return`	`copyPhone()` clipboard handler
4	Same	Replace `return null`	Ghost `Button` UI
5	`src/pages/UserDetailPage.tsx`	Imports ~line 68	`import { CopyPhoneButton } ...`
6	Same	Phone row ~line 405	`<CopyPhoneButton phone={phoneStatus.label} />` in `else` branch only

---

4. Walkthrough beats (5–7 minutes)

Beat W1 — Intro goal (0:00–0:20)

Mouse / keyboard	Narration	Expected
Open Word or Google Docs; show one-line Goal; minimize window	"The goal is to add **Copy phone** on the Grind Karo coach admin **athlete detail page** at route `/users/:id`, copying the **formatted phone label** already shown beside the phone icon, with a two-second **Copied** confirmation and **no** profile API updates."	Goal text visible briefly

Beat W2 — Repository stack (0:20–1:15)

Mouse / keyboard	Narration	Expected
VS Code: Explorer → open `package.json`	"The admin app is a **Vite** React 19 project; script `npm run dev` starts the dev server."	`"dev": "vite"` visible
Scroll `dependencies`	"Routing uses **react-router-dom**; server state uses **TanStack React Query**; HTTP uses **axios**."	Dependency list
Open `src/main.tsx`	"`QueryClientProvider` wraps `App`, so athlete data on `UserDetailPage` is cached query data."	Provider wrapper

Beat W3 — Route to athlete page (1:15–2:15)

Mouse / keyboard	Narration	Expected
Open `src/App.tsx`; `Cmd+F` → `UserDetailPage`	"Staff users reach **UserDetailPage** on path `/users/:id`."	Route element line
Open `src/pages/UserDetailPage.tsx`; scroll to header JSX (~line 370+)	"The header block renders name, **email row**, **phone row**, role, and join date."	Mail + Phone rows

Beat W4 — Configuration (2:15–3:00)

Mouse / keyboard	Narration	Expected
Open `.env.example`	"API base URL is **VITE_API_BASE_URL**; Copy phone does not add new environment variables."	Single env line
Open `src/services/api.ts`	"Axios reads `import.meta.env.VITE_API_BASE_URL` for all REST calls; clipboard copy does not use Axios."	Base URL assignment

Beat W5 — Phone data path (3:00–4:15)

Mouse / keyboard	Narration	Expected

In `UserDetailPage.tsx`, `Cmd+F` → `phoneStatus`	"After `useUserDetail` loads `user`, line `const phoneStatus = formatAdminPhone(user.phone)` derives display label and missing flag."	`formatAdminPhone` call ~line 295
Open `src/utils/phoneStatus.ts`	"**formatAdminPhone** trims input, keeps digits, prefixes + when digits exist; **missing** is true when the label is empty."	Function body
Return to `UserDetailPage` phone `<span>`	"The ternary shows amber **Number missing** when `phoneStatus.missing` is true; otherwise it prints `phoneStatus.label`."	Conditional JSX

Beat W6 — Copy email reference (4:15–5:15)

Mouse / keyboard	Narration	Expected
Open `src/components/users/CopyEmailButton.tsx`	"**CopyEmailButton** already implements clipboard write, **Copied** state, and a two-second timeout—**CopyPhoneButton** mirrors that structure with prop `phone` instead of `email`."	Full component
Open `src/components/users/CopyPhoneButton.tsx`	"Starter file **CopyPhoneButton.tsx** lists **TODO 1–4** and returns `null` until the recording implementation."	TODO comments, `return null`

Beat W7 — Page wiring gap (5:15–6:00)

Mouse / keyboard	Narration	Expected
`UserDetailPage.tsx` imports ~line 68	"**TODO 5** adds the **CopyPhoneButton** import after **CopyEmailButton**."	Commented TODO 5
Phone row comment `TODO 6`	"**TODO 6** mounts **CopyPhoneButton** only in the branch where `phoneStatus.missing` is false, passing `phone={phoneStatus.label}`."	No live Copy phone button yet

---

5. Coding beats — TODO 1–6

> *Type code in **small saves**; narrate the **file name** and **symbol name** on each save.*

Beat C1 — TODO 1 constant

Mouse / keyboard	Narration	Expected
Focus `CopyPhoneButton.tsx`; place cursor below imports	"**TODO 1** adds **COPIED_CONFIRMATION_MS** at module scope so the **Copied** label duration matches **CopyEmailButton**."	—
Type: `const COPIED_CONFIRMATION_MS =`	"Two thousand milliseconds gives coaches time to read **Copied** before the label reverts to **Copy**	Constant in file

`2000;`	**phone**."	
`Cmd+S`	"Saved **CopyPhoneButton.tsx** after **TODO 1**."	Tab dirty dot clears

Beat C2 — TODO 2 state and timer

Mouse / keyboard	Narration	Expected
Inside `CopyPhoneButton`, below props destructuring	"**TODO 2** introduces boolean state **copied** and a **useEffect** keyed on **copied**."	—
Type `useState` + `useEffect` block (see snippet below)	"When **copied** becomes true, **useEffect** schedules **setCopied(false)** after **COPIED_CONFIRMATION_MS**; cleanup calls **window.clearTimeout**."	No TypeScript errors
`Cmd+S`	"Saved **CopyPhoneButton.tsx** after **TODO 2**."	—

```
const [copied, setCopied] = useState(false);

useEffect(() => {
  if (!copied) return;
  const timer = window.setTimeout(
    () => setCopied(false),
    COPIED_CONFIRMATION_MS,
  );
  return () => window.clearTimeout(timer);
}, [copied]);
```

Beat C3 — TODO 3 clipboard handler

Mouse / keyboard	Narration	Expected
Below **useEffect**, add `async function copyPhone()`	"**TODO 3** writes the **phone** prop string to the system clipboard—already formatted for display by **formatAdminPhone**."	—
Type try/catch with `navigator.clipboard.writeText(phone)`	"Success sets **copied** to true; denial or error sets **copied** false without a toast."	Function present
`Cmd+S`	"Saved **CopyPhoneButton.tsx** after **TODO 3**."	—

```
async function copyPhone() {
  try {
    await navigator.clipboard.writeText(phone);
    setCopied(true);
  } catch {
    setCopied(false);
```

```
  }
}
```

Beat C4 — TODO 4 button UI

Mouse / keyboard	Narration	Expected
Delete `return null;`	"**TODO 4** renders the shared **Button** primitive from `@/components/ui/Button`."	—
Paste JSX (snippet below); `Cmd+S`	"Ghost variant, small size, same **className** as **CopyEmailButton**; **onClick** calls **void copyPhone()** because **copyPhone** is async."	Component exports UI

```tsx
return (
  <Button
    type="button"
    variant="ghost"
    size="sm"
    className="h-6 px-2 py-0 text-xs text-gray-600 dark:text-gray-300"
    onClick={() => void copyPhone()}
  >
    {copied ? "Copied" : "Copy phone"}
  </Button>
);
```

Beat C5 — TODO 5 import

Mouse / keyboard	Narration	Expected
Open `UserDetailPage.tsx`; go to **TODO 5** comment ~line 68	"**TODO 5** imports **CopyPhoneButton** next to **CopyEmailButton**."	Comment visible
Replace comment with `import { CopyPhoneButton } from "@/components/users/CopyPhoneButton";`	"The import path uses the `@/components/users` alias configured in **tsconfig**."	Import line active
`Cmd+S`	"Saved **UserDetailPage.tsx** after **TODO 5**."	—

Beat C6 — TODO 6 wire phone row

Mouse / keyboard	Narration	Expected
Scroll to phone row; find **TODO 6** inside `else` branch	"**TODO 6** places **CopyPhoneButton** immediately after `{phoneStatus.label}`."	Fragment with label

Add `<CopyPhoneButton phone={phoneStatus.label} />`; remove TODO comment; `Cmd+S`	"Prop **phone** receives **phoneStatus.label** so paste matches the header text, not an unformatted database value."	HMR may update Brave tab

---

6. Verification beats

Beat V1 — Start dev server

Mouse / keyboard	Narration	Expected
VS Code Terminal: `npm run dev`	"Vite serves the admin at **localhost:5173**."	Local URL in terminal
Brave: open `http://localhost:5173`; sign in as staff if needed	"Staff session can open **Users** and athlete **UUID** routes."	Dashboard or users list

Beat V2 — Athlete A happy path

Mouse / keyboard	Narration	Expected
Navigate to `/users/<uuid-a>`	"Athlete A shows a formatted phone in the header row beside the **Phone** icon."	Label + **Copy phone**
Click **Copy phone**; wait 2 seconds	"Label changes to **Copied**, then returns to **Copy phone**."	Label cycle
Click address bar or Notes; `Cmd+V`	"Pasted text equals **phoneStatus.label** from the header."	Paste matches display

Beat V3 — Athlete B missing phone

Mouse / keyboard	Narration	Expected
Navigate to `/users/<uuid-b>`	"Athlete B triggers **phoneStatus.missing**."	Amber **Number missing**
Scan phone row	"**CopyPhoneButton** is not mounted because **TODO 6** lives only in the non-missing branch."	No **Copy phone** control

Beat V4 — Network quiet

Mouse / keyboard	Narration	Expected
DevTools → **Network** → filter **Fetch/XHR**	"I monitor XHR while clicking **Copy phone**."	Network panel open
Click **Copy phone** three times	"Clipboard actions do not send **PUT** or **PATCH** to user profile endpoints."	No new profile mutations

Beat V5 — Copy email regression

Mouse / keyboard	Narration	Expected

On Athlete A, click **Copy email**; paste once	"**CopyEmailButton** still copies **user.email**."	Email paste works
Click **Copy phone** again	"Phone copy still works after email copy."	Both controls OK

Beat V6 — Lint and build

Mouse / keyboard	Narration	Expected
Terminal: `npm run lint`	"ESLint scans **CopyPhoneButton** and **UserDetailPage** imports."	Exit code 0
Terminal: `npm run build`	"TypeScript project build includes the new component."	Exit code 0

---

7. Minute-by-minute master timeline

Time	Segment	Mouse / keyboard (summary)	Narration anchor (what / where / why)	Expected
0:00–0:20	Intro	Docs Goal	Task: **Copy phone** on `/users/:id`	Goal shown
0:20–2:00	Stack	`package.json`, `main.tsx`	Vite + React Query architecture	Files open
2:00–3:00	Routing	`App.tsx`, `UserDetailPage` header	Route `/users/:id`	Header JSX
3:00–4:15	Phone data	`phoneStatus`, `phoneStatus.ts`	**formatAdminPhone** label vs missing	Code + ternary
4:15–5:15	Reference	`CopyEmailButton`, starter `CopyPhoneButton`	Mirror email pattern	TODOs visible
5:15–6:30	Page gap	`UserDetailPage` TODO 5–6 comments	Import + conditional mount	No button yet
6:30–8:00	**C1–C2**	Type TODO 1–2 in `CopyPhoneButton.tsx`	Constant + timer	Saved file
8:00–9:30	**C3–C4**	Type TODO 3–4	Clipboard + **Button**	Component complete
9:30–10:30	**C5–C6**	`UserDetailPage` import + JSX	Wire `phoneStatus.label`	HMR / refresh
10:30–14:00	**V1–V2**	`npm run dev`, Athlete A paste	Happy path verification	Paste match
14:00–16:00	**V3**	Athlete B	Missing phone gating	No button

16:00–18:00	**V4–V5**	Network tab + email click	No API + regression	Quiet network
18:00–19:30	**V6**	lint + build	Quality gate	Green output
19:30–28:00	Buffer	Repeat V2 slowly	Reinforce DoD	Same results
28:00–30:00	Close	Speak to camera	§8 summary	—

---

8. Closing summary narration

Read verbatim or paraphrase with the same nouns:

“On the Grind Karo coach admin **UserDetailPage**, I added **CopyPhoneButton** beside the formatted **phoneStatus.label** in the athlete header. The component uses **navigator.clipboard.writeText** with the **phone** prop, shows **Copied** for **COPIED_CONFIRMATION_MS** milliseconds, and resets via **useEffect** and **clearTimeout**. **UserDetailPage** imports **CopyPhoneButton** and renders it only when **phoneStatus.missing** is false; athletes with **Number missing** see no copy control. I verified paste content on Athlete A, absence of the button on Athlete B, no profile XHR on copy, **Copy email** regression, and **npm run lint** plus **npm run build**. Files changed: **CopyPhoneButton.tsx** and **UserDetailPage.tsx**.”

---

9. Deliverables checklist

- [ ] **TODO 1–6** complete; `npm run dev` runs
- [ ] Beats **V2–V4** on camera
- [ ] **final output 2.mp4** — coding visible; narration matches clicks (~1s pause)
- [ ] **final output 3.rtf** — Topology chronological; Request = Copy phone brief
- [ ] **Deliverables.zip** — code only; no `.env` , `node_modules` , video, Metadata
- [ ] **No PII** — fake athletes only; Do Not Disturb on

Metadata quick reference

Request: Add **Copy phone** on `/users/:id` when **phoneStatus.label** is shown; copy that label; **Copied** confirmation; hide when **Number missing**; no user updates.

Topology: Brave (LOOKUP) → Brave (LOOKUP) → Visual Studio Code (LOOKUP) → Visual Studio Code (CREATE) → Visual Studio Code (MODIFY) → Brave (LOOKUP) → Terminal (LOOKUP)

Document version: 2026-10-22 — Copy phone guide with synced narration and input beats.