

Beck, Calvin Huang, Jiani Li, Yishuai

November 29, 2018

What is this talk about?

What is this talk about?

FuzzChick!

What is this talk about?

FuzzChick!

What is FuzzChick...?

What is this talk about?

FuzzChick!

What is FuzzChick...?

FuzzChick is an experiment to improve QuickChick using ideas from fuzzing, such as AFL [3].

What is this talk about?

FuzzChick!

What is FuzzChick...?

FuzzChick is an experiment to improve QuickChick using ideas from fuzzing, such as AFL [3].

We'll come back to this...

QuickChick: A Brief Review

QuickChick is a properties based testing framework for Coq.

- You build (or derive) generators for data types.
- Using those generators you can feed data into test cases.
- These test cases can be any arbitrary predicate.

QuickChick: Pros and Cons

So what's great about QuickChick?

- Relatively easy to build / derive generators.
- Can generate lots of tests for specific properties automatically.

QuickChick: Pros and Cons

So what's great about QuickChick?

- Relatively easy to build / derive generators.
- Can generate lots of tests for specific properties automatically.

What's not so great about QuickChick?

QuickChick: Pros and Cons

So what's great about QuickChick?

- Relatively easy to build / derive generators.
- Can generate lots of tests for specific properties automatically.

What's not so great about QuickChick?

- Getting *good* generators can be hard!

What makes a good generator?

The basic idea of what makes a generator “good” can vary somewhat based on the context.

What makes a good generator?

The basic idea of what makes a generator “good” can vary somewhat based on the context.

In general you want good coverage. How can you achieve that with minimal work?

Finally, FuzzChick!

FuzzChick uses AFL to make the choices between constructors for building data types for tests.

Finally, FuzzChick!

FuzzChick uses AFL to make the choices between constructors for building data types for tests.

Why is this good?

FuzzChick Intuition

AFL uses DSE to attempt to get good coverage while fuzzing...

FuzzChick Intuition

AFL uses DSE to attempt to get good coverage while fuzzing...
Maybe we can utilize AFL's smarts to achieve better test coverage.

QuickChick: Now With Coverage!

We instrumented QuickChick using `bisect_ppx` to get coverage estimates!

QuickChick: Now With Coverage!

We instrumented QuickChick using `bisect_ppx` to get coverage estimates!

This *mostly* went smoothly...

Compiling with absolute paths cause an infinite loop #180



Chobbes opened this issue 2 days ago · 7 comments

QuickChick: Now With Coverage!

We instrumented QuickChick using `bisect_ppx` to get coverage estimates!

This *mostly* went smoothly...

Compiling with absolute paths cause an infinite loop #180

 **Closed** Chobbes opened this issue 2 days ago · 7 comments

Maintainer fixed this issue promptly, which was *awesome*!

QuickChick with coverage... Still needs some polish

QuickChick with coverage is cool, but it still does need some polish.

QuickChick with coverage... Still needs some polish

QuickChick with coverage is cool, but it still does need some polish.

- Includes a lot of excessive extracted Coq code.

QuickChick with coverage... Still needs some polish

QuickChick with coverage is cool, but it still does need some polish.

- Includes a lot of excessive extracted Coq code.
 - ▶ Like... All of QuickChick :(.
 - ▶ So, the percentages are a little off.

QuickChick with coverage... Still needs some polish

QuickChick with coverage is cool, but it still does need some polish.

- Includes a lot of excessive extracted Coq code.
 - ▶ Like... All of QuickChick :(.
 - ▶ So, the percentages are a little off.
- QuickChick generates “random” files for each test, and the names aren’t all that useful
 - ▶ Modified QuickChick to include test case in name, but still not ideal.

QuickChick with coverage... Still needs some polish

QuickChick with coverage is cool, but it still does need some polish.

- Includes a lot of excessive extracted Coq code.
 - ▶ Like... All of QuickChick :(.
 - ▶ So, the percentages are a little off.
- QuickChick generates “random” files for each test, and the names aren’t all that useful
 - ▶ Modified QuickChick to include test case in name, but still not ideal.

But...

QuickChick with coverage... Still needs some polish

QuickChick with coverage is cool, but it still does need some polish.

- Includes a lot of excessive extracted Coq code.
 - ▶ Like... All of QuickChick :(.
 - ▶ So, the percentages are a little off.
- QuickChick generates “random” files for each test, and the names aren’t all that useful
 - ▶ Modified QuickChick to include test case in name, but still not ideal.













But...

It works! We can measure stuff!

QuickChick Coverage: ifc-basic

Coverage with QuickChick in the ifc-basic example:


Coverage report 44.33%

 	42%	/tmp/QuickChick/214311/QuickChick_prop_SSNldefault_table_e0cd62.ml
 	46%	/tmp/QuickChick/214315/QuickChick_prop_SSNl_deriveddefault_table_65753a.ml
 	43%	/tmp/QuickChick/214320/QuickChick_prop_MSNIdefault_table_31e78d.ml
 	43%	/tmp/QuickChick/214324/QuickChick_myArgs_71227b.ml
 	44%	/tmp/QuickChick/214327/QuickChick_myArgs_81c382.ml
 	49%	/tmp/QuickChick/214330/QuickChick_myArgs_100552.ml

Generated on 2018-11-28 21:43:33 by *Bisect_ppx* 1.3.4


QuickChick vs FuzzChick: ifc-basic

QuickChick:




QuickChick vs FuzzChick: ifc-basic

QuickChick:



FuzzChick:



For some reason it seems that FuzzChick actually gets worse coverage than QuickChick on this test case... At least in the time I let it run (I'm not terribly patient)

Why Worse Coverage?

- Just need to let it run longer?
 - ▶ AFL needs a while to “warm up”?

Why Worse Coverage?

- Just need to let it run longer?
 - ▶ AFL needs a while to “warm up”?
- QuickChick test already managed to get good coverage in this instance, so fuzzing doesn't give us much on top of it?
 - ▶ Hard to tell what “good coverage” is due to the extraneous code extracted by QuickChick.

Why Worse Coverage?

- Just need to let it run longer?
 - ▶ AFL needs a while to “warm up”?
- QuickChick test already managed to get good coverage in this instance, so fuzzing doesn't give us much on top of it?
 - ▶ Hard to tell what “good coverage” is due to the extraneous code extracted by QuickChick.
- Something's not instrumented correctly?

Why Worse Coverage?

- Just need to let it run longer?
 - ▶ AFL needs a while to “warm up”?
- QuickChick test already managed to get good coverage in this instance, so fuzzing doesn't give us much on top of it?
 - ▶ Hard to tell what “good coverage” is due to the extraneous code extracted by QuickChick.
- Something's not instrumented correctly?
- This test case, for whatever reason, is fuzzer unfriendly?
 - ▶ Maybe extracted Coq could be fuzzer unfriendly? Lots of inefficient data types like `nat` (basically a linked list whose length represents a number).
 - ▶ Could result in excessively long paths and hard to solve predicates for DSE?
 - ▶ Not sure that having pointers everywhere would be AFL's strength...

Some Further Coverage Testing...

Test case:

```
Extract Constant unlikely_branch =>
" fun i ->
  if (0 < i)
  then if (i mod 100 == 0)
    then if (i mod 1000 == 0)
      then if (i mod 10000 == 0)
        then if (i mod 100000 == 0)
          then if (i mod 1000000 == 0)
            then if (i < 1000001)
              then 42
              else 0
            else 0
          else 0
        else 0
      else 0
    else 0
  else 0
else 0
".

Definition always_zero := forAll (choose (0%Z, 9999999%Z)) (fun n =>
  unlikely_branch n =? 0).
```

Some Further Coverage Testing...

Test case:

```
Extract Constant unlikely_branch =>
" fun i ->
  if (0 < i)
  then if (i mod 100 == 0)
    then if (i mod 1000 == 0)
      then if (i mod 10000 == 0)
        then if (i mod 100000 == 0)
          then if (i mod 1000000 == 0)
            then if (i < 1000001)
              then 42
              else 0
            else 0
          else 0
        else 0
      else 0
    else 0
  else 0
else 0
".

Definition always_zero := forAll (choose (0%Z, 9999999%Z)) (fun n =>
  unlikely_branch n =? 0).
```

Trying to give AFL a good chance to find the failing branch...

Results

In the equivalent C code AFL does quite well...

Results

In the equivalent C code AFL does quite well...

QuickChick:

```
then if (i mod 1000000 == 0)                                then if (i < 1000001)
```

FuzzChick:

```
then if (i mod 10000 == 0)                                then if (i mod 100000 == 0)                                then if (i mod 1
```

Results

In the equivalent C code AFL does quite well...

QuickChick:

```
then if (i mod 1000000 == 0)                then if (i < 1000001)
```

FuzzChick:

```
then if (i mod 10000 == 0)                then if (i mod 100000 == 0)                then if (i mod 1
```

Here not so much? FuzzChick doesn't make it as far...

Results

In the equivalent C code AFL does quite well...

QuickChick:

```
then if (i mod 1000000 == 0)                then if (i < 1000001)
```

FuzzChick:

```
then if (i mod 10000 == 0)                then if (i mod 100000 == 0)                then if (i mod 1
```

Here not so much? FuzzChick doesn't make it as far...

Well, in fairness, it does eventually, but it takes a good 30 minutes. QuickChick was much faster.

Honourable Mentions: Some Other Stuff We Did

Honourable Mentions: Some Other Stuff We Did

- Honggfuzz!

Honourable Mentions: Some Other Stuff We Did

■ Honggfuzz!

- ▶ Finally got this working...
- ▶ Didn't really work out because it takes a long time to find bugs by fuzzing.
- ▶ Decided it wasn't really a great comparison to FuzzChick which is a properties based testing tool anyway.
- ▶ Some useful scripts / documentation to get this running in our git repo. [1]

Honourable Mentions: Some Other Stuff We Did

■ Honggfuzz!

- ▶ Finally got this working...
- ▶ Didn't really work out because it takes a long time to find bugs by fuzzing.
- ▶ Decided it wasn't really a great comparison to FuzzChick which is a properties based testing tool anyway.
- ▶ Some useful scripts / documentation to get this running in our git repo. [1]

■ Plain AFL!

Honourable Mentions: Some Other Stuff We Did

■ Honggfuzz!

- ▶ Finally got this working...
- ▶ Didn't really work out because it takes a long time to find bugs by fuzzing.
- ▶ Decided it wasn't really a great comparison to FuzzChick which is a properties based testing tool anyway.
- ▶ Some useful scripts / documentation to get this running in our git repo. [1]




■ Plain AFL!

- ▶ Similar story to Honggfuzz.

Conclusion! Questions?

Whew! Questions?

References

-  Calvin Beck, Jiani Huang, and Yishuai Li. *Quick700*. 2018. URL: <https://github.com/Quick700/Quick700> (visited on 11/29/2018).
-  Leonidas Lampropoulos, Zoe Paraskevopoulou, and Benjamin C Pierce. “Generating Good Generators for Inductive Relations”. In: ().
-  Michal Zalewski. *AFL*. URL: <http://lcamtuf.coredump.cx/afl/> (visited on 11/29/2018).

These are all good resources! You should look at them!