

1. Description

1.1. Project

Project Name	ui
Board Name	custom
Generated with:	STM32CubeMX 6.8.0
Date	04/21/2023


1.2. MCU

MCU Series	STM32F4
MCU Line	STM32F405/415
MCU name	STM32F405RGTx
MCU Package	LQFP64
MCU Pin number	64

1.3. Core(s) information

Core(s)	Arm Cortex-M4

2. Pinout Configuration




3. Pins Configuration

Pin Number	Pin Name	Pin Type	Alternate	Label
LQFP64	(function after		Function(s)	
	reset)			
1	VBAT	Power		
3	PC14-OSC32_IN *	I/O	GPIO_Output	KB_COL3
4	PC15-OSC32_OUT *	I/O	GPIO_Output	KB_COL4
5	PH0-OSC_IN	I/O	RCC_OSC_IN	MCLK
6	PH1-OSC_OUT	I/O	RCC_OSC_OUT	NC NC
7	NRST	Reset	1.00_000_001	110
8	PC0 *	I/O	GPIO_Output	UI_LED_G
9	PC1 *	I/O	GPIO_Output	UI_LED_R
12	VSSA	Power		
13	VDDA	Power		
14	PA0-WKUP	I/O	ADC1_IN0	BATTERY_MON
15	PA1 *	I/O	GPIO_Output	DISP_CS
16	PA2	I/O	USART2_TX	UI_TX2_MGMT
17	PA3	I/O	USART2_RX	UI_RX2_MGMT
18	VSS	Power		
19	VDD	Power		
20	PA4	I/O	12S3_WS	I2S_DACLRC
21	PA5	I/O	SPI1_SCK	DISP_SPI_SCK
22	PA6	I/O	SPI1_MISO	DISP_RSTR
23	PA7	I/O	SPI1_MOSI	DISP_SPI_MOSI
24	PC4 *	I/O	GPIO_Output	UI_DBG1
25	PC5 *	I/O	GPIO_Output	UI_DBG2
26	PB0 *	I/O	GPIO_Output	DISP_DC
27	PB1	I/O	ADC2_IN9	KB_MIC
28	PB2 *	I/O	GPIO_Input	KK_ROW5
29	PB10	I/O	USART3_TX	UI_TX3
30	PB11	I/O	USART3_RX	UI_RX3
31	VCAP_1	Power		
32	VDD	Power		
33	PB12 *	I/O	GPIO_Input	KB_ROW1
34	PB13 *	I/O	GPIO_Input	KB_ROW2
35	PB14 *	I/O	GPIO_Input	KB_ROW3
36	PB15 *	I/O	GPIO_Input	KB_ROW4
37	PC6 *	I/O	GPIO_Output	UI_DBG3
38	PC7 *	I/O	GPIO_Output	UI_DBG4
41	PA8 *	I/O	GPIO_Output	UI_STAT

Pin Number LQFP64	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
42	PA9	I/O	USART1_TX	UI_TX1_NET
43	PA10	I/O	USART1_RX	UI_RX1_NET
46	PA13	I/O	SYS_JTMS-SWDIO	UI_SWDIO
47	VCAP_2	Power		
48	VDD	Power		
49	PA14	I/O	SYS_JTCK-SWCLK	UI_SWDCLK
50	PA15 *	I/O	GPIO_Output	DISP_BL
51	PC10	I/O	12S3_CK	I2S_BCLK
52	PC11	I/O	I2S3_ext_SD	I2S_ADCDAT
53	PC12	I/O	12S3_SD	I2S_DACDAT
54	PD2 *	I/O	GPIO_Output	UI_LED_B
55	PB3 *	I/O	GPIO_Input	KB_ROW6
56	PB4 *	I/O	GPIO_Input	KB_ROW7
57	PB5 *	I/O	GPIO_Output	KB_COL5
58	PB6	I/O	I2C1_SCL	UI_SCL
59	PB7	I/O	I2C1_SDA	UI_SDA
60	воото	Boot		
61	PB8 *	I/O	GPIO_Output	KB_COL2
62	PB9 *	I/O	GPIO_Output	KB_COL1
63	VSS	Power		
64	VDD	Power		

^{*} The pin is affected with an I/O function

4. Clock Tree Configuration



5. Software Project

5.1. Project Settings

Name	Value	
Project Name	ui	
Project Folder	/Users/fluffy/src/hactar/firmware/ui	
Toolchain / IDE	EWARM V8.50	
Firmware Package Name and Version	STM32Cube FW_F4 V1.27.1	
Application Structure	Advanced	
Generate Under Root	No	
Do not generate the main()	No	
Minimum Heap Size	0x200	
Minimum Stack Size	0x400	

5.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy all used libraries into the project folder
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power	No
consumption)	
Enable Full Assert	No

5.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO
3	MX_ADC1_Init	ADC1
4	MX_I2C1_Init	I2C1
5	MX_I2S3_Init	12\$3
6	MX_SPI1_Init	SPI1
7	MX_USART1_UART_Init	USART1
8	MX_USART2_UART_Init	USART2
9	MX_USART3_UART_Init	USART3
10	MX_ADC2_Init	ADC2

ui Project
Configuration Report

6. Power Consumption Calculator report

6.1. Microcontroller Selection

Series	STM32F4
Line	STM32F405/415
MCU	STM32F405RGTx
Datasheet	DS8626_Rev8

6.2. Parameter Selection

Temperature	25
Vdd	3.3

6.3. Battery Selection

Battery	Li-SOCL2(A3400)
Capacity	3400.0 mAh
Self Discharge	0.08 %/month
Nominal Voltage	3.6 V
Max Cont Current	100.0 mA
Max Pulse Current	200.0 mA
Cells in series	1
Cells in parallel	1


6.4. Sequence

Step	Step1	Step2
Mode	RUN	STOP
Vdd	3.3	3.3
Voltage Source	Battery	Battery
Range	Scale1-High	No Scale
Fetch Type	FLASH	n/a
CPU Frequency	168 MHz	0 Hz
Clock Configuration	HSE PLL	Regulator LP Flash-PwrDwn
Clock Source Frequency	4 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	46 mA	280 μA
Duration	0.1 ms	0.9 ms
DMIPS	210.0	0.0
Ta Max	98.02	104.96
Category	In DS Table	In DS Table

6.5. Results

Sequence Time	1 ms	Average Current	4.85 mA
Battery Life	29 days. 4 hours	Average DMIPS	210.0 DMIPS

6.6. Chart



7. Peripherals and Middlewares Configuration

7.1. ADC1 mode: IN0

7.1.1. Parameter Settings:

ADCs_Common_Settings:

Mode Independent mode

ADC_Settings:

Clock Prescaler PCLK2 divided by 4

Resolution 12 bits (15 ADC Clock cycles)

Data Alignment Right alignment

Scan Conversion Mode Disabled
Continuous Conversion Mode Disabled
Discontinuous Conversion Mode Disabled
DMA Continuous Requests Disabled

End Of Conversion Selection EOC flag at the end of single channel conversion

ADC_Regular_ConversionMode:

Number Of Conversion 1

External Trigger Conversion Source Regular Conversion launched by software

External Trigger Conversion Edge None Rank 1

Channel Channel 0
Sampling Time 3 Cycles

ADC_Injected_ConversionMode:

Number Of Conversions 0

WatchDog:

Enable Analog WatchDog Mode false

7.2. ADC2

mode: IN9

7.2.1. Parameter Settings:

ADCs_Common_Settings:

Mode Independent mode

ADC_Settings:

Clock Prescaler PCLK2 divided by 4

Resolution 12 bits (15 ADC Clock cycles)

Data Alignment Right alignment

Scan Conversion Mode Disabled
Continuous Conversion Mode Disabled
Discontinuous Conversion Mode Disabled
DMA Continuous Requests Disabled

End Of Conversion Selection EOC flag at the end of single channel conversion

ADC_Regular_ConversionMode:

Number Of Conversion 1

External Trigger Conversion Source Regular Conversion launched by software

External Trigger Conversion Edge None
Rank 1

Channel Channel 9
Sampling Time 3 Cycles

ADC_Injected_ConversionMode:

Number Of Conversions 0

WatchDog:

Enable Analog WatchDog Mode false

7.3. I2C1 I2C: I2C

7.3.1. Parameter Settings:

Master Features:

I2C Speed Mode Standard Mode

I2C Clock Speed (Hz) 100000

Slave Features:

Clock No Stretch Mode Disabled

Primary Address Length selection 7-bit

Dual Address Acknowledged Disabled

Primary slave address 0

General Call address detection Disabled

7.4. I2S3

Mode: Full-Duplex Master 7.4.1. Parameter Settings:

Generic Parameters:

Transmission Mode Mode Master Transmit

Communication Standard I2S Philips

Data and Frame Format 16 Bits Data on 16 Bits Frame

Selected Audio Frequency 8 KHz

Real Audio Frequency 7.971 KHz *
Error between Selected and Real -0.36 % *

Clock Parameters:

Clock Source I2S PLL Clock

Clock Polarity Low

7.5. RCC

High Speed Clock (HSE): BYPASS Clock Source

7.5.1. Parameter Settings:

System Parameters:

VDD voltage (V) 3.3
Instruction Cache Enabled
Prefetch Buffer Enabled
Data Cache Enabled

Flash Latency(WS) 2 WS (3 CPU cycle)

RCC Parameters:

HSI Calibration Value 16
HSE Startup Timout Value (ms) 100
LSE Startup Timout Value (ms) 5000

Power Parameters:

Power Regulator Voltage Scale Power Regulator Voltage Scale 1

7.6. SPI1

Mode: Full-Duplex Master

7.6.1. Parameter Settings:

Basic Parameters:

Frame Format Motorola

Data Size 8 Bits

First Bit MSB First

Clock Parameters:

Prescaler (for Baud Rate) 2

Baud Rate 42.0 MBits/s *

Clock Polarity (CPOL) Low
Clock Phase (CPHA) 1 Edge

Advanced Parameters:

CRC Calculation Disabled
NSS Signal Type Software

7.7. SYS

Debug: Serial Wire

Timebase Source: SysTick

7.8. USART1

Mode: Asynchronous

7.8.1. Parameter Settings:

Basic Parameters:

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit

Over Sampling 16 Samples

7.9. USART2

Mode: Asynchronous

7.9.1. Parameter Settings:

Basic Parameters:

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit

Over Sampling 16 Samples

7.10. USART3

Mode: Asynchronous

7.10.1. Parameter Settings:

Basic Parameters:

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit

Over Sampling 16 Samples

^{*} User modified value

8. System Configuration

8.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
ADC1	PA0-WKUP	ADC1_IN0	Analog mode	No pull-up and no pull-down	n/a	BATTERY_MON
ADC2	PB1	ADC2_IN9	Analog mode	No pull-up and no pull-down	n/a	KB_MIC
I2C1	PB6	I2C1_SCL	Alternate Function Open Drain	No pull-up and no pull-down	Very High	UI_SCL
	PB7	I2C1_SDA	Alternate Function Open Drain	No pull-up and no pull-down	Very High	UI_SDA
12\$3	PA4	I2S3_WS	Alternate Function Push Pull	No pull-up and no pull-down	Low	I2S_DACLRC
	PC10	12S3_CK	Alternate Function Push Pull	No pull-up and no pull-down	Low	I2S_BCLK
	PC11	I2S3_ext_SD	Alternate Function Push Pull	No pull-up and no pull-down	Low	I2S_ADCDAT
	PC12	I2S3_SD	Alternate Function Push Pull	No pull-up and no pull-down	Low	I2S_DACDAT
RCC	PH0- OSC_IN	RCC_OSC_IN	n/a	n/a	n/a	MCLK
	PH1- OSC_OUT	RCC_OSC_OUT	n/a	n/a	n/a	NC
SPI1	PA5	SPI1_SCK	Alternate Function Push Pull	No pull-up and no pull-down	Very High	DISP_SPI_SCK
	PA6	SPI1_MISO	Alternate Function Push Pull	No pull-up and no pull-down	Very High	DISP_RSTR
	PA7	SPI1_MOSI	Alternate Function Push Pull	No pull-up and no pull-down	Very High	DISP_SPI_MOSI
SYS	PA13	SYS_JTMS- SWDIO	n/a	n/a	n/a	UI_SWDIO
	PA14	SYS_JTCK- SWCLK	n/a	n/a	n/a	UI_SWDCLK
USART1	PA9	USART1_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	UI_TX1_NET
	PA10	USART1_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	UI_RX1_NET
USART2	PA2	USART2_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	UI_TX2_MGMT
	PA3	USART2_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	UI_RX2_MGMT
USART3	PB10	USART3_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	UI_TX3
	PB11	USART3_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	UI_RX3

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
					*	
GPIO	PC14- OSC32_IN	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	KB_COL3
	PC15- OSC32_OU T	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	KB_COL4
	PC0	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	UI_LED_G
	PC1	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	UI_LED_R
	PA1	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	DISP_CS
	PC4	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	UI_DBG1
	PC5	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	UI_DBG2
	PB0	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	DISP_DC
	PB2	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	KK_ROW5
	PB12	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	KB_ROW1
	PB13	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	KB_ROW2
	PB14	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	KB_ROW3
	PB15	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	KB_ROW4
	PC6	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	UI_DBG3
	PC7	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	UI_DBG4
	PA8	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	UI_STAT
	PA15	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	DISP_BL
	PD2	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	UI_LED_B
	PB3	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	KB_ROW6
	PB4	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	KB_ROW7
	PB5	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	KB_COL5
	PB8	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	KB_COL2
	PB9	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	KB_COL1

8.2. DMA configuration

nothing configured in DMA service

8.3. NVIC configuration

8.3.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
Memory management fault	true	0	0
Pre-fetch fault, memory access fault	true	0	0
Undefined instruction or illegal state	true	0	0
System service call via SWI instruction	true	0	0
Debug monitor	true	0	0
Pendable request for system service	true	0	0
System tick timer	true	15	0
PVD interrupt through EXTI line 16	unused		
Flash global interrupt	unused		
RCC global interrupt		unused	
ADC1, ADC2 and ADC3 global interrupts		unused	
I2C1 event interrupt		unused	
I2C1 error interrupt		unused	
SPI1 global interrupt	unused		
USART1 global interrupt	unused		
USART2 global interrupt	unused		
USART3 global interrupt	unused		
SPI3 global interrupt	unused		
FPU global interrupt		unused	

8.3.2. NVIC Code generation


Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true

* User modified value	

9. System Views

9.1. Category view

9.1.1. Current



10. Docs & Resources

Type Link

BSDL files https://www.st.com/resource/en/bsdl_model/stm32f405-415_407-

417 bsdl.zip

IBIS models https://www.st.com/resource/en/ibis_model/stm32f405-415_407-

417_ibis.zip

System View https://www.st.com/resource/en/svd/stm32f4_svd.zip

Description

BSDL files https://www.st.com/resource/en/bsdl_model/stm32f405-415_407-

417_bsdl.zip

IBIS models https://www.st.com/resource/en/ibis_model/stm32f405-415_407-

417_ibis.zip

System View https://www.st.com/resource/en/svd/stm32f4_svd.zip

Description

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_embedded_software_solutions.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_eval-

tools_portfolio.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_stm8_functi

onal-safety-packages.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_software_development_tools.pdf

Training Material https://www.st.com/resource/en/sales_guide/sg_sc2154.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32nucleo.pdf

Flyers https://www.st.com/resource/en/flyer/flstmcsuite.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32trust.pdf

Product https://www.st.com/resource/en/certification_document/stm32_authenticat

Certifications ion_can.pdf

Application Notes https://www.st.com/resource/en/application_note/an1181-electrostatic-

discharge-sensitivity-measurement-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an1709-emc-design-

- guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2606-stm32-microcontroller-system-memory-boot-mode-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2639-solderingrecommendations-and-package-information-for-leadfree-ecopack-mcusand-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2834-how-to-get-the-best-adc-accuracy-in-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2867-oscillator-design-guide-for-stm8afals-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2945-stm8s-and-stm32-mcus-a-consistent-832bit-product-line-for-painless-migration-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3070-managing-the-driver-enable-signal-for-rs485-and-iolink-communications-with-the-stm32s-usart-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3154-can-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3364-migration-and-compatibility-guidelines-for-stm32-microcontroller-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3371-using-the-hardware-realtime-clock-rtc-in-stm32-f0-f2-f3-f4-and-l1-series-of-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3997-audio-playback-and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application_note/an3998-pdm-audio-software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4013-stm32-crossseries-timer-overview-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4031-using-the-stm32f2-stm32f4-and-stm32f7-series-dma-controller-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4073-how-to-improve-adc-accuracy-when-using-stm32f2xx-and-stm32f4xx-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4076-two-or-three-shunt-resistor-based-current-sensing-circuit-design-in-3phase-inverters-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4221-i2c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4229-how-to-implement-a-vocoder-solution-using-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4230-stm32-microcontroller-random-number-generation-validation-using-the-nist-statistical-test-suite-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4277-using-stm32-device-pwm-shutdown-features-for-motor-control-and-digital-power-conversion-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4286-spi-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4488-getting-started-with-stm32f4xxxx-mcu-hardware-development-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4566-extending-the-dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4640-peripherals-interconnections-on-stm32f4057xx-stm32f4157xx-stm32f42xxx-stm32f43xxx-stm32f446xx-and-stm32f469479xx-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4739-stm32cube-firmware-examples-for-stm32f4-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4759-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4821-migrating-from-stm32f405415-line-and-stm32f407417-line-to-stm32l4-series-and-stm32l4-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4838-managing-memory-protection-unit-in-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4850-stm32-mcusspreadspectrum-clock-generation-principles-properties-andimplementation-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4879-usb-hardware-and-pcb-guidelines-using-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4908-stm32-usart-automatic-baud-rate-detection-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4995-using-anelectromyogram-technique-to-detect-muscle-activitystmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5027-interfacing-pdm-

digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application_note/an5036-thermalmanagement-guidelines-for-stm32-applications-stmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application_note/an5073-receiving-spdifaudio-stream-with-the-stm32f4f7h7-series-stmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application_note/an5225-usb-typecpower-delivery-using-stm32-mcus-and-mpus-stmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application note/an5543-enhancedmethods-to-handle-spi-communication-on-stm32-devicesstmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application_note/an4899-stm32microcontroller-gpio-hardware-settings-and-lowpower-consumptionstmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application_note/an5612-esd-protectionof-stm32-mcus-and-mpus-stmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application_note/an5156-introduction-tostm32-microcontrollers-security-stmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application_note/an1202_freertos_guidefor related Tools freertos-guide-stmicroelectronics.pdf & Software Application Notes https://www.st.com/resource/en/application_note/an1602_semihosting_in for related Tools _truestudio-how-to-do-semihosting-in-truestudio-stmicroelectronics.pdf & Software Application Notes https://www.st.com/resource/en/application_note/an1801_stm32cubeprog for related Tools rammer_in_truestudio-installing-stm32cubeprogrammer-in-truestudio-& Software stmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application_note/atollic_editing_keyboard for related Tools _shortcuts-atollic-editing-keyboard-shortcuts-stmicroelectronics.pdf & Software Application Notes https://www.st.com/resource/en/application_note/iar_to_atollic_truestudio for related Tools __migration_guide-truestudio-for-arm-migration-guide-iar-embedded-& Software workbench-to-truestudio-stmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application_note/stm32cubemx_installatio for related Tools n_in_truestudio-stm32cubemx-installation-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2656-stm32f10xxx-

for related Tools Icd-glass-driver-firmware-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an2790-tft-lcd-

for related Tools interfacing-with-the-highdensity-stm32f10xxx-fsmc-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3078-stm32-for related Tools inapplication-programming-over-the-ic-bus-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3116-stm32s-adc-

for related Tools modes-and-their-applications-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3174-implementing-for related Tools receivers-for-infrared-remote-control-protocols-using-stm32f10xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3241-qvga-tftlcd-for related Tools direct-drive-using-the-stm32f10xx-fsmc-peripheral-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3307-guidelines-for-for related Tools obtaining-iec-60335-class-b-certification-for-any-stm32-application-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3364-migration-and-

for related Tools compatibility-guidelines-for-stm32-microcontroller-applications-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3965-

for related Tools stm32f40xstm32f41x-inapplication-programming-using-the-usart-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an3969-eeprom-

for related Tools emulation-in-stm32f40xstm32f41x-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3988-clock-for related Tools configuration-tool-for-stm32f40xx41xx427x437x-microcontrollers-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3990-upgrading-

for related Tools stm32f4discovery-board-firmware-using-a-usb-key-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3997-audio-playback-

for related Tools and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3998-pdm-audio-

for related Tools software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4044-floating-point-

for related Tools unit-demonstration-on-stm32-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4323-getting-started-

for related Tools with-stemwin-library-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4365-using-stm32f4-

for related Tools mcu-power-modes-with-best-dynamic-efficiency-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4435-guidelines-for-

for related Tools obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32-

& Software application-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4457-implementing-

for related Tools an-emulated-uart-on-stm32f4-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4499-stm32--

for related Tools nrf51822-bluetooth-low-energy-system-solution-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4502-stm32-

for related Tools smbuspmbus-embedded-software-expansion-for-stm32cube-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4657-stm32-

for related Tools inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4666-parallel-for related Tools synchronous-transmission-using-gpio-and-dma-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application_note/an4678-full-duplex-spifor related Tools emulation-for-stm32f4-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application_note/an4701-proprietary-for related Tools code-readout-protection-on-microcontrollers-of-the-stm32f4-series-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4739-stm32cube-

for related Tools firmware-examples-for-stm32f4-series-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4758-proprietary-for related Tools code-readout-protection-on-stm32l4-stm32l4-stm32g4-and-stm32wb-

& Software series-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4759-using-the-

for related Tools hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-

& Software stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4841-digital-signal-for related Tools processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4968-proprietary-for related Tools code-read-out-protection-pcrop-on-stm32f72xxx-and-stm32f73xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5054-secure-for related Tools programming-using-stm32cubeprogrammer-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5056-integration-

for related Tools guide-for-the-xcubesbsfu-stm32cube-expansion-package-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5360-getting-started-

for related Tools with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5361-getting-started-

for related Tools with-projects-based-on-dualcore-stm32h7-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5394-getting-started-

for related Tools with-projects-based-on-the-stm32l5-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5418-how-to-build-a-for related Tools simple-usbpd-sink-application-with-stm32cubemx-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5426-migrating-for related Tools graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-

& Software 550-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5464-position-control-

for related Tools of-a-threephase-permanent-magnet-motor-using-xcubemcsdk-or-

& Software xcubemcsdkful-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5564-getting-started-

for related Tools with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5698-adapting-the-for related Tools xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-

& Software other-safety-standards-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5731-stm32cubemx-

for related Tools and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf

& Software

Errata Sheets https://www.st.com/resource/en/errata_sheet/es0182-stm32f405407xx-

and-stm32f415417xx-device-limitations-stmicroelectronics.pdf

Datasheet https://www.st.com/resource/en/datasheet/dm00037051.pdf

Programming https://www.st.com/resource/en/programming_manual/pm0214-stm32-Manuals cortexm4-mcus-and-mpus-programming-manual-stmicroelectronics.pdf

Reference https://www.st.com/resource/en/reference_manual/rm0090-

Manuals stm32f405415-stm32f407417-stm32f427437-and-stm32f429439-

advanced-armbased-32bit-mcus-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn0516-overview-of-the-

& Articles stm32f0xf100xxf103xx-and-stm32f2xxf30xf4xx-mcus-pmsm-singledual-

foc-sdk-v40-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1163-description-of-

& Articles wlcsp-for-microcontrollers-and-recommendations-for-its-use-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1204-tape-and-reel-

& Articles shipping-media-for-stm32-microcontrollers-in-bga-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1205-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical note/tn1206-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1207-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1208-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-

packages-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1433-reference-device-

& Articles marking-schematics-for-stm32-microcontrollers-and-microprocessors-

stmicroelectronics.pdf