COMP9313 2017s2 Assignment

z5045582

Yunhe Zhang

Question 1. MapReduce

```
class mapper {
HashMap<Integer, String> myMap {
      map (key, record) {
            Split record to get price and product;
             If myMap size less than 5 {
                   Use price as key, product as value, put them into myMap;
             } else {
                   if price greater than first key in myMap {
                         Remove first key in myMap;
                         Use price as key, product as value, put them into myMap;
      }
      cleanup() {
            for each entry in myMap
                   emit (null, entry's value);
class reducer {
      reducer (key, records) {
            for record in records
                   emit record;
}
```

Question 2. MinHash

Row	C_1	C_2
0	0	1
1	1	0
2	0	1
3	0	0
4	1	1
5	1	1
6	1	0

$$h1(n) = (3n + 2) \mod 7$$

 $h2(n) = (2n - 1) \mod 7$

	Sig1	Sig2	
	∞	∞	
h1(0) = 2	∞	2	update Sig2
h2(0) = 6	∞	6	update Sig2
h1(1) = 5	5	2	update Sig1
h2(1) = 1	1	6	update Sig1
h1(2) = 1	5	1	update Sig2
h2(2) = 3	1	3	update Sig2
h1(3) = 4	5	1	no change
h2(3) = 5	1	3	no change
h1(4) = 0	0	0	update Sig1 Sig2
h2(4) = 0	0	0	update Sig1 Sig2
h1(5) = 3	0	0	no change
h2(5) = 2	0	0	no change
h1(6) = 6	0	0	no change
h2(6) = 4	0	0	no change

Result

	Sig1	Sig2
hI(n)		0
h2(n)	0	0

Question 3. Streaming Data

```
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (1, 197) (1, 200)
Input from 200 to 210: 0101010101
201 Input: 0
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (1, 197) (1, 200)
202 Input: 1
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (1, 197) (1, 200) (1, 202)
Combine (1, 197) (1, 200)
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (1, 202)
203 Input: 0
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (1, 202)
204 Input: 1
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (1, 202) (1, 204)
205 Input: 0
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (1, 202) (1, 204)
206 Input: 1
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (1, 202) (1, 204) (1, 206)
Combine (1, 202) (1, 204)
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (2, 204) (1, 206)
Combine (2, 192) (2, 200)
(16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (1, 206)
207 Input: 0
(16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (1, 206)
208: Input: 1
(16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (1, 206) (1, 208)
209: Input: 0
(16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (1, 206) (1, 208)
210 Input: 1
(16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (1, 206) (1, 208) (1, 210)
```

Combine (1, 206) (1, 208) (16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (2, 208) (1, 210)

The result is (16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (2, 208) (1, 210)

Question 4. Collaborative Filtering

(a)

	m1	m2	m3
u1	2		3
u2	5	2	
u3	3	3	1
u4		2	2

$$sim(x, y) = \frac{\sum_{i} r_{xi} \cdot r_{yi}}{\sqrt{\sum_{i} r_{xi}^{2}} \cdot \sqrt{\sum_{i} r_{yi}^{2}}}$$

$$sim (u1, u2) = 0.515$$

 $sim (u1, u3) = 0.573$
 $sim (u1, u4) = 0.588$

Predict u1 to m2 =
$$(0.515*2 + 0.573*3 + 0.588*2) / (0.515 + 0.573 + 0.588)$$

= 2.34

(b)

	u1	u2	u3	u4
m1	2	5	3	
m2		2	3	2
m3	3		1	2

$$sim(x, y) = \frac{\sum_{i} r_{xi} \cdot r_{yi}}{\sqrt{\sum_{i} r_{xi}^{2}} \cdot \sqrt{\sum_{i} r_{yi}^{2}}}$$

$$sim (m2, m1) = 0.748$$

 $sim (m2, m3) = 0.454$

Predict u1 to m2 =
$$(0.748*2 + 0.454*3) / (0.748 + 0.454)$$

= 2.38