COMP9313 2017s2 Assignment

z5045582

Yunhe Zhang

Question 1. MapReduce

```
class mapper {
     map (key, record) {
           split_record ← split record with '\s+'
           product ← split record[1]
           price \Leftarrow split record[2]
           EMIT(product, price)
class reducer {
      HashMap< String, Integer> myMap
     reducer (key, values) {
           for all value ∈ values
                 myMap.put(key, record)
                 break
      cleanup() {
           counter \leftarrow 0
           for all entry ∈ sortedMap {
                 if counter == 5
                       break
                 counter++
                 EMIT(null, entry's key)
     }
```

Question 2. MinHash

| Row | C_1 | C_2 |
|--------------------------------------|-------|-------|
| 0 | 0 | 1 |
| 1 | 1 | 0 |
| 2 | 0 | 1 |
| $\begin{vmatrix} 2\\3 \end{vmatrix}$ | 0 | 0 |
| 4 | 1 | 1 |
| 5 | 1 | 1 |
| 6 | 1 | 0 |

$$h1(n) = (3n + 2) \mod 7$$

 $h2(n) = (2n - 1) \mod 7$

| | a | ~. - | |
|-----------|----------|-------------|------------------|
| | Sig1 | Sig2 | |
| | ∞ | ∞ | |
| h1(0) = 2 | ∞ | 2 | update Sig2 |
| h2(0) = 6 | ∞ | 6 | update Sig2 |
| | | | |
| h1(1) = 5 | 5 | 2 | update Sig1 |
| h2(1) = 1 | 1 | 6 | update Sig1 |
| | | | |
| h1(2) = 1 | 5 | 1 | update Sig2 |
| h2(2) = 3 | 1 | 3 | update Sig2 |
| | | | |
| h1(3) = 4 | 5 | 1 | no change |
| h2(3) = 5 | 1 | 3 | no change |
| | | | |
| hI(4) = 0 | 0 | 0 | update Sig1 Sig2 |
| h2(4) = 0 | 0 | 0 | update Sig1 Sig2 |
| | | | |
| hI(5) = 3 | 0 | 0 | no change |
| h2(5) = 2 | 0 | 0 | no change |
| | | | |
| hI(6) = 6 | 0 | 0 | no change |
| h2(6) = 4 | 0 | 0 | no change |

Result

| | Sig1 | Sig2 |
|-------|------|------|
| h1(n) | 0 | 0 |
| h2(n) | 0 | 0 |

Question 3. Streaming Data

```
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (1, 197) (1, 200)
Input from 200 to 210: 0101010101
201 Input: 0
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (1, 197) (1, 200)
202 Input: 1
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (1, 197) (1, 200) (1, 202)
Combine (1, 197) (1, 200)
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (1, 202)
203 Input: 0
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (1, 202)
204 Input: 1
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (1, 202) (1, 204)
205 Input: 0
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (1, 202) (1, 204)
206 Input: 1
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (1, 202) (1, 204) (1, 206)
Combine (1, 202) (1, 204)
(16, 148) (8, 162) (8, 177) (4, 183) (2, 192) (2, 200) (2, 204) (1, 206)
Combine (2, 192) (2, 200)
(16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (1, 206)
207 Input: 0
(16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (1, 206)
208: Input: 1
(16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (1, 206) (1, 208)
209: Input: 0
(16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (1, 206) (1, 208)
210 Input: 1
(16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (1, 206) (1, 208) (1, 210)
```

Combine (1, 206) (1, 208) (16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (2, 208) (1, 210)

The result is (16, 148) (8, 162) (8, 177) (4, 183) (4, 200) (2, 204) (2, 208) (1, 210)

Question 4. Collaborative Filtering

(a)

| | m1 | m2 | m3 |
|----|----|----|----|
| u1 | 2 | | 3 |
| u2 | 5 | 2 | |
| u3 | 3 | 3 | 1 |
| u4 | | 2 | 2 |

$$sim(x, y) = \frac{\sum_{i} r_{xi} \cdot r_{yi}}{\sqrt{\sum_{i} r_{xi}^{2}} \cdot \sqrt{\sum_{i} r_{yi}^{2}}}$$

$$sim (u1, u2) = 0.515$$

 $sim (u1, u3) = 0.573$

$$sim (u1, u4) = 0.588$$

Predict u1 to m2 =
$$(0.515*2 + 0.573*3 + 0.588*2) / (0.515 + 0.573 + 0.588)$$

= 2.34

(b)

| | u1 | u2 | u3 | u4 |
|----|----|----|----|----|
| m1 | 2 | 5 | 3 | |
| m2 | | 2 | 3 | 2 |
| m3 | 3 | | 1 | 2 |

$$sim(x, y) = \frac{\sum_{i} r_{xi} \cdot r_{yi}}{\sqrt{\sum_{i} r_{xi}^{2}} \cdot \sqrt{\sum_{i} r_{yi}^{2}}}$$

$$sim (m2, m1) = 0.748$$

 $sim (m2, m3) = 0.454$

Predict u1 to m2 =
$$(0.748*2 + 0.454*3) / (0.748 + 0.454)$$

= 2.38