

PROF. DR.-ING. MARK SCHUTERA

DGX SPARK

UNFINISHED LECTURE NOTES

Copyright © 2026 Prof. Dr.-Ing. Mark Schutera

PUBLISHED BY UNFINISHED LECTURE NOTES

Combobulated with the help of multiple large language model driven tools. Licensed under the Creative Commons Attribution-NonCommercial 4.0 International License ("CC BY-NC-SA 4.0"). You may not use this file for commercial purposes. If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original You must obtain explicit permission from the author for uses beyond those permitted by this license. To view a copy of this license, visit <https://creativecommons.org/licenses/by-nc-sa/4.0/>. Unless required by applicable law or agreed to in writing, distributed material is provided on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the license for details.

These notes are, by their very nature, unfinished, and they improve with every reader. If you spot an error, disagree with a framing, or want to add a source, a question, or a position, open a pull request at https://github.com/Quillstacks/LectureMaterial/tree/main/lecturenotes/notes_dgxspark. Every contribution is welcome.



Quickstart.

2026-10-01 · *deft strawberry Antelope*

Ignition

THE SPARK HAS ONE USER ACCOUNT PER PERSON. Request yours by mail. The reply carries your username and password, and the setup folder as an attached zip with the WireGuard configuration and the Spark's IP address.

YOUR ACCOUNT IS AN ADMIN ACCOUNT on a shared machine. With sudo you can install what you need, and also break the machine for everyone. With great power comes great responsibility: Store nothing sensitive on it, leave other users' files and processes alone, sandbox your stuff and never touch the system config itself. Protect yourself from others, and protect others from yourself. While you have your own user, two users being logged in at the same time will produce lag and slowdowns. If you experience this, please log out and try again later. That also means the Spark is used most efficiently when you spend as little time as possible to deploy your jobs and leave, not for interactive development. If you need to develop interactively, please do so on your own machine.

WIREGUARD OPENS A TUNNEL INTO THE LAB NETWORK. Only traffic to the lab goes through it; the rest of your connection stays as it is. Install the WireGuard client, choose Import tunnel(s) from file, pick dgx-spark.conf from the setup folder, and press Activate. The status should now read Active and Latest handshake is seconds old. No handshake means your network blocks the tunnel.

THEN LOG IN with the IP address from the mail:

```
ssh <username>@<spark-ip>
```

BEFORE YOU START A JOB, run `nvidia-smi` to see who is on the GPU.

THIS SETUP IS FAR FROM PERFECT. If you want to build a job scheduler, per-user VPN configurations, or sandboxes that keep users apart, reach out.

SCAN THE CODE and send a mail stating your name, why you need access, which course, and what you want to run.



REMEMBER? Chapter 1 of Full Stack Handwerkszeug, Development and Production, covers this split, along with SSH and Linux servers. https://material.schutera.com/lecturenotes/notes_missingsemester/notes_missingsemester.pdf

YOU LEARN USEFUL STUFF HERE. QED.

DOWNLOAD. <https://www.wireguard.com/install/>