

The Ethereum network: a graph analysis

Quinten Bruynseraede
R0674455

Louis Van Looy
R0861408

April 20, 2021

Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Vestibulum laoreet dapibus purus. Maecenas eleifend, ipsum eget pretium blandit, nibh diam fermentum turpis, quis semper urna orci eget dolor. Aliquam at vehicula odio. Sed facilisis, odio vitae faucibus consequat, nisi metus condimentum leo, et malesuada sapien metus nec odio. Etiam vel orci non dolor interdum ultricies. Nullam in justo dui. Aenean ut eros non felis molestie lacinia eget ut turpis. Mauris malesuada efficitur libero, at volutpat arcu imperdiet ac. Vivamus gravida sodales felis, varius ultrices magna luctus sit amet. Donec blandit ante neque, at blandit dui vestibulum in. Nam vel lorem.

1 Introduction

The Ethereum network is a blockchain-based network for distributed processing. It contains a thriving ecosystem of distributed applications (dapps), ranging from financial tools to games and gambling. Ethereum's native token is called Ether (ETH), and it has become a acknowledged way of storing and transferring money: a so-called *store-of-value*. In this report, we analyze how ETH is distributed among users, and how it flows between them. In particular, we analyze the role of a group of very wealthy users (called *whales*), and we investigate how important these whales are for the network, and to what degree they contribute to wealth inequality.

In Chapter 2, we introduce some basic concepts related to the ethereum network. Chapter 3 outlines past work about network analysis of cryptocurrency networks, in particular the Ethereum network. In Chapter 4, we describe how we collected the necessary data. Chapter 6 analyzes the network using a set of network analysis tools, and try to show the importance of whales. Chapter 7 focuses on inequality within the Ethereum network. In Chapter 8, we try to analyze clusters in the network, and try to link these clusters to their utility in the network.

2 Ethereum

In the following section, we explain fundamental terms and definitions needed to understand the Ethereum network. Based on this, it is also intended to better understand the network and thus observe and understand the specific characteristics of the particular network.

2.1 Ethereum

First of all a formal definition of Ethereum is needed. Ethereum is an open-source, blockchain-based and decentralized software platform. It makes use of its own cryptocurrency, called Ether. The main nov-

elty of Ethereum is its ability to execute smart contracts and create decentralized, distributed applications without any downtime, fraud, control or involvement from a third party. A smart contract can be seen as a piece of code that describes the rules for a transaction between two parties. Smart contracts on the Ethereum network are Turing-complete (i.e. they can describe arbitrary computations), and are mostly programmed in the Solidity programming language.

2.2 Addresses and transactions

Users store their Ether in an account, uniquely represented by a 20-byte address, such as `0xed9a430d9a11616eb1cb07ebc28c9e20a03bd486`. Transactions contain (among other fields), a sender, a recipient and a transaction value expressed in *wei*. 1 Ether is equal to 10^{18} wei. Smart contracts are also identified by a 20-byte address, and executing these smart contracts can be done by sending them a transaction. All transactions are public by default, but there is no direct link between the identify of a user and his address: the vast majority of transactions happen anonymously. However, many services use addresses that are publicly known. For example, Binance, one of the largest cryptocurrency marketplaces, has at least 20 known addresses ¹.

2.3 Whales

An important element within the composition of the Ethereum network are whales. Ma (2021) gives the following definition: "The term *whale* is used to describe an individual or organization that holds a large amount of a particular cryptocurrency." This amount is not clearly defined, but within the cryptocurrency community a threshold of around 1.000 of a particular cryptocurrency is being seen as the standard. It is clear that this value can fluctuate, based on the underlying value of the cryptocurrency. In

¹<https://etherscan.io/accounts/label/binance>

the Ethereum network this threshold is set on owners who own 10.000 Ethereum or more, these holders control approximately 70

2.4 The network

The Ethereum network has seen tremendous growth since its inception in 2015, and contains over 350 million transactions at the time of writing. Since June 2020, the daily number of transactions exceeds 1 million ². Over 100 million addresses have been registered, and over 600 thousand addresses take part in transactions every day ³. This means a full analysis is generally not feasible.

3 Related Work

It has to be said: the literature around graph analysis of the Ethereum network is quite young but strongly emerging. Guo et al. (2019) [3] were one of the first to address the properties of this network. They investigated the ETH network in the initial phase and in a more developed phase. They found out that several transaction features, such as the transaction volume, transaction relation, and component structure of the graph, exhibit the same heavy-tail property which can be approximated statistically by the power law function. Our work gives a more complete overview of the *evolution* of the network, because we analyze it at six stages instead of just two.

Chen et al. (2020) [2] performed a graph analysis on the Ethereum network. They focus on the characteristics of its users, smart contracts, and the relationships among them to get a deeper understanding of the network. Money transfers, smart contract creations and smart contract invocations are central within their work. These three elements are vital for the users to send money, to create smart contracts on Ethereum, and for the users or applications to invoke the created smart contracts. In this work, metrics like degree distribution, degree centrality, Pearson coefficient, clustering coefficient, PageRank are used and therefore forms a good benchmark for this work. Victor & Lüders (2019) [4] focus on the trade of tokens on the Ethereum network, more specifically called ERC20 token networks. These tokens can be seen as digital assets, built on top of ETH and strengthen the Ethereum ecosystem by driving demand for ETH, needed to power the smart contracts. They provide an overview of 64,000 ERC20 token network and focus graphically on the top 1,000. In this work, they observe that the token networks are frequently dominated by a single hub and spoke pattern, supplemented with very small clustering coefficients. The token network looks disassortative and a lot of the network activity is directed towards exchanges whereby many owners never transfer their tokens at all. As ERC-20 tokens can be considered a smart contract, we will not spend much time investigating this aspect, but they are an indispensable part of the Ethereum ecosystem.

²<https://etherscan.io/chart/tx>

³<https://bitinfocharts.com/comparison/ethereum-activeaddresses.html>

4 Data collection

Given the size of the Ethereum network, we have to resort to sampling techniques. One type of sampling uses *random walks*, that start at a given point and follow edges while collecting the necessary data. Random walks are particularly useful for networks where it is not possible to delimit a part of the network in advance [1]. Ethereum is such a network: addresses are not ordered or structured in any way. We collect transactions using a Breadth-first search (BFS). To analyze the evolution of the network, we create six separate snapshots: each snapshot spans 1 month and is limited to 1 million transactions.

```
T = ∅
Initialize Queue with 100 known addresses
while T.size ≤ 1e6 do
    1. Pop an address A from Queue
    2. Fetch all transactions by A during the time period
    3. Add all transactions to T
    4. Add all addresses that occur in these transactions to Queue
end
```

Although transactions contain many more features, we only use the columns **from**, **to**, and **value**. Each snapshot can then be considered a graph: nodes are addresses and edges are transactions between addresses. The value of the transaction is the weight of the edge. If multiple transactions occur between the same pair of addresses, we sum their values.

The following table shows the size of each snapshot:

Snapshot	#txs	#nodes	#edges
Jan '17	475 598 ⁴	81 242	186 942
Nov '17	988 086	548 355	657 697
Sep '18	1 000 258	528 506	635 623
Jul '19	1 006 153	550 393	673 967
May 20	1 003 812	474 030	580 773
Mar '21	1 001 864	566 733	701 482

To account for seasonal effects, the time between two snapshots is always 10 months. We also don't consider the state of the network before January 2017, when it was still relatively new and the number of transactions was low.

5 Analysis of the Ethereum network

First of all, it appears the average degree has remained constant over time (between 1 and 1.25), except for the snapshot Jan'17. We suspect the smaller size and consequentially larger influence of the starting addresses cause this larger average degree in 2017.

Figure 1 shows the degree distribution for each

snapshot. The distribution appears to follow a power law at first (estimated $k^{-2.1}$), but as the degree increases, the distribution is more or less uniform. In particular nodes with a degree above 5000 would be very rare in a perfect scale-free network, but we observe them often. It is noteworthy that Guo et al.

[3] find a power law distribution with an exponent of $k = 3.23$, whereas we find $k = 2.1$. We suspect this difference can be explained by our data collection method, which favours nodes with a high degree (i.e. transactions with many other nodes).




Figure 1: Degree distribution for all snapshots

Next, we look at the transaction volume in each snapshot. For our network, the transaction volume of a node is simply the sum of all outgoing transactions. Similar to what Guo et al. discovered [3], the transaction volume appears to follow a power law.




Figure 2: Distribution of transaction volumes

This logarithmic plot shows how the transaction volumes are distributed for each snapshot. First of all, it appears that transaction volumes have not changed much over time. A deviation is observed in the 2017 snapshots, in which transaction volumes were a bit higher than average. We suspect this deviation may be caused by the so-called *2017 bull run*, a period of spiking prices, which attracts many new investors. Interestingly enough, the bull run that is currently ongoing is not reflected in the transaction volumes of the March 2021 snapshot.

6 Inequality

TODO

7 Clustering

References

- [1] Luca Becchetti, Carlos Castillo, Debora Donato, and Adriano Fazzzone. A comparison of sampling techniques for web graph characterization, 2006.

- [2] T. Chen, Y. Zhu, Z. Li, J. Chen, X. Li, X. Luo, X. Lin, and X. Zhange. Understanding ethereum via graph analysis. In *IEEE INFOCOM 2018 - IEEE Conference on Computer Communications*, pages 1484–1492, 2018.
- [3] Dongchao Guo, Jiaqing Dong, and Kai Wang. Graph structure and statistical properties of ethereum transaction relationships. *Information Sciences*, 492:58–71, 2019.
- [4] Friedhelm Victor and Bianca Lüders. *Measuring Ethereum-Based ERC20 Token Networks*, pages 113–129. 09 2019.