

# Machine learning triggers: feasibility study

status report, what did I do last month, 09.22



# Topics today

- **Training with random traces**
  - Results seem promising so far but...
  - need to effectively tell single muons apart
  - lack (accurate) estimates for  $Q_{\text{Peak}}$  and  $Q_{\text{Area}}$
- **Extracting monitoring data from random traces**
  - Online estimate finally accesible
  - Random traces aren't timestamped
  - Daily average most likely not good enough
- **Doing the online/offline estimate myself**
  - A bunch of problems
  - A lot of work so far



# Training with random traces

- **Hardware triggers** ~ **2 / 1000 false signals**
  - **Neural networks** ~ **2 / 5000 false signals**
- } Rates depend on my injection, so take this with a grain of salt

```

DATASET
HardwareClassifier validation_data -> Acc = 84.09%, TPR = 99.8375%

ENSEMBLES/minimal_conv2d_real_background/ensemble_1/ validation_data -> Acc = 99.63%, TPR = 99.9708%
ENSEMBLES/minimal_conv2d_real_background/ensemble_2/ validation_data -> Acc = 99.63%, TPR = 99.9490%
ENSEMBLES/minimal_conv2d_real_background/ensemble_3/ validation_data -> Acc = 99.62%, TPR = 99.9465%
ENSEMBLES/minimal_conv2d_real_background/ensemble_4/ validation_data -> Acc = 99.61%, TPR = 99.9808%
ENSEMBLES/minimal_conv2d_real_background/ensemble_5/ validation_data -> Acc = 99.62%, TPR = 99.9736%
ENSEMBLES/minimal_conv2d_real_background/ensemble_6/ validation_data -> Acc = 99.63%, TPR = 99.9493%
ENSEMBLES/minimal_conv2d_real_background/ensemble_7/ validation_data -> Acc = 99.63%, TPR = 99.9485%
ENSEMBLES/minimal_conv2d_real_background/ensemble_8/ validation_data -> Acc = 99.63%, TPR = 99.9386%
ENSEMBLES/minimal_conv2d_real_background/ensemble_9/ validation_data -> Acc = 99.62%, TPR = 99.9730%
ENSEMBLES/minimal_conv2d_real_background/ensemble_10/ validation_data -> Acc = 99.61%, TPR = 99.9683%

```

# Training with random traces

- **Hardware triggers** ~ **2 / 1000 false signals**
  - **Neural networks** ~ **2 / 5000 false signals**
- } Rates depend on my injection, so take this with a grain of salt

```

DATASET
HardwareClassifier validation_data -> Acc = 84.09%, TPR = 99.8375%

ENSEMBLES/minimal_conv2d_real_background/ensemble_1/ validation_data -> Acc = 99.63%, TPR = 99.9708%
ENSEMBLES/minimal_conv2d_real_background/ensemble_2/ validation_data -> Acc = 99.63%, TPR = 99.9490%
ENSEMBLES/minimal_conv2d_real_background/ensemble_3/ validation_data -> Acc = 99.62%, TPR = 99.9465%
ENSEMBLES/minimal_conv2d_real_background/ensemble_4/ validation_data -> Acc = 99.61%, TPR = 99.9808%
ENSEMBLES/minimal_conv2d_real_background/ensemble_5/ validation_data -> Acc = 99.62%, TPR = 99.9736%
ENSEMBLES/minimal_conv2d_real_background/ensemble_6/ validation_data -> Acc = 99.63%, TPR = 99.9493%
ENSEMBLES/minimal_conv2d_real_background/ensemble_7/ validation_data -> Acc = 99.63%, TPR = 99.9485%
ENSEMBLES/minimal_conv2d_real_background/ensemble_8/ validation_data -> Acc = 99.63%, TPR = 99.9386%
ENSEMBLES/minimal_conv2d_real_background/ensemble_9/ validation_data -> Acc = 99.62%, TPR = 99.9730%
ENSEMBLES/minimal_conv2d_real_background/ensemble_10/ validation_data -> Acc = 99.61%, TPR = 99.9683%

```

**Use online  
daily avg.  
 $Q_{\text{Peak}}$ ,  $Q_{\text{Area}}$   
for calibration**

# Training with random traces

- **Hardware triggers** ~ **2 / 1000 false signals**
- **Neural networks** ~ **2 / 5000 false signals**

Rates depend on my injection, so take this with a grain of salt

```

DATASET
HardwareClassifier validation_data -> Acc = 84.09%, TPR = 99.8375%

ENSEMBLES/minimal_conv2d_real_background/ensemble_1/ validation_data -> Acc = 99.63%, TPR = 99.9708%
ENSEMBLES/minimal_conv2d_real_background/ensemble_2/ validation_data -> Acc = 99.63%, TPR = 99.9490%
ENSEMBLES/minimal_conv2d_real_background/ensemble_3/ validation_data -> Acc = 99.62%, TPR = 99.9465%
ENSEMBLES/minimal_conv2d_real_background/ensemble_4/ validation_data -> Acc = 99.61%, TPR = 99.9808%
ENSEMBLES/minimal_conv2d_real_background/ensemble_5/ validation_data -> Acc = 99.62%, TPR = 99.9736%
ENSEMBLES/minimal_conv2d_real_background/ensemble_6/ validation_data -> Acc = 99.63%, TPR = 99.9493%
ENSEMBLES/minimal_conv2d_real_background/ensemble_7/ validation_data -> Acc = 99.63%, TPR = 99.9485%
ENSEMBLES/minimal_conv2d_real_background/ensemble_8/ validation_data -> Acc = 99.63%, TPR = 99.9386%
ENSEMBLES/minimal_conv2d_real_background/ensemble_9/ validation_data -> Acc = 99.62%, TPR = 99.9730%
ENSEMBLES/minimal_conv2d_real_background/ensemble_10/ validation_data -> Acc = 99.63%, TPR = 99.9490%
    
```

**Use online  
daily avg.  
 $Q_{\text{Peak}}$ ,  $Q_{\text{Area}}$   
for calibration**

- **Triggers at a rate of  $\approx 30$  kHz ...**
- **Mostly noise, but also ... Muons?**



```

random traces injected: 10000
summed traces duration: 0.17s
total T2 trigger found: 5714
*****
TRIGGER FREQUENCY = 33614.9285 Hz
    
```

# Training with random traces

- Single muons from shower library:  $\sim \mathcal{O}(1 \text{ in } 4 - 5 \text{ trace batches})$
- Background muons in random traces:  $\sim \mathcal{O}(1 \text{ in } 12 \text{ trace batches})$
- How to account for this?
  - Cut on  $Q_{\text{Area}}$  (e.g.  $1 \text{ VEM}_{\text{Charge}}$ )

```

Acc = 87.01%, TPR = 99.7535%
Acc = 87.15%, TPR = 99.8088%
Acc = 87.49%, TPR = 99.7859%
Acc = 86.94%, TPR = 99.7316%
Acc = 86.97%, TPR = 99.8168%
Acc = 87.02%, TPR = 99.7796%
Acc = 87.21%, TPR = 99.7249%
Acc = 87.19%,
Acc = 86.99%,
Acc = 87.14%,

```

```

random traces injected: 10000
summed traces duration: 0.17s
total T2 trigger found: 192
*****
TRIGGER FREQUENCY = 1129.5181 Hz

```

# Training with random traces

- Single muons from shower library:  $\sim \mathcal{O}(1 \text{ in } 4 - 5 \text{ trace batches})$
- Background muons in random traces:  $\sim \mathcal{O}(1 \text{ in } 12 \text{ trace batches})$
- How to account for this?
  - Cut on  $Q_{\text{Area}}$  (e.g.  $1 \text{ VEM}_{\text{Charge}}$ )
  - Train with lower prior

```

Acc = 87.01%, TPR = 99.7535%
Acc = 87.15%, TPR = 99.8088%
Acc = 87.49%, TPR = 99.7859%
Acc = 86.94%, TPR = 99.7316%
Acc = 86.97%, TPR = 99.8168%
Acc = 87.02%, TPR = 99.7796%
Acc = 87.21%, TPR = 99.7249%
Acc = 87.19%,
Acc = 86.99%,
Acc = 87.14%,

```


```

random traces injected: 10000
summed traces duration: 0.17s
total T2 trigger found: 192
*****
TRIGGER FREQUENCY = 1129.5181 Hz

```

# Training with random traces

- Single muons from shower library:  $\sim \mathcal{O}(1 \text{ in } 4 - 5 \text{ trace batches})$
- Background muons in random traces:  $\sim \mathcal{O}(1 \text{ in } 12 \text{ trace batches})$
- How to account for this?
  - Cut on  $Q_{\text{Area}}$  (e.g.  $1 \text{ VEM}_{\text{Charge}}$ )
  - Train with lower prior





# Training with random traces

- Single muons from shower library:  $\sim \mathcal{O}(1 \text{ in } 4 - 5 \text{ trace batches})$
- Background muons in random traces:  $\sim \mathcal{O}(1 \text{ in } 12 \text{ trace batches})$
- How to account for this?
  - Cut on  $Q_{\text{Area}}$  (e.g.  $1 \text{ VEM}_{\text{Charge}}$ )
  - Train with lower prior

```

Acc = 97.01%, TPR = 99.7525%
Acc = 98.45%, TPR = 98.2711%
Acc = 98.49%, TPR = 98.2218%
Acc = 98.37%, TPR = 98.3233%
Acc = 98.53%, TPR = 98.4573%
Acc = 98.56%, TPR = 98.3118%
Acc = 98.42%, TPR = 98.5586%
Acc = 98.51%, TPR = 98.1261%
Acc = 98.55%,
Acc = 98.45%,
Acc = 98.50%,

random traces injected: 10000
summed traces duration: 0.17s
total T2 trigger found: 537
*****
TRIGGER FREQUENCY = 3159.1209 Hz

```

# Training with random traces

- Single muons from shower library:  $\sim \mathcal{O}(1 \text{ in } 4 - 5 \text{ trace batches})$
- Background muons in random traces:  $\sim \mathcal{O}(1 \text{ in } 12 \text{ trace batches})$
- How to account for this?
  - Cut on  $Q_{\text{Area}}$  (e.g.  $1 \text{ VEM}_{\text{Charge}}$ )
  - Train with lower prior
  - TODO: Cut + low prior

```

Acc = 97.01%, TPR = 99.7525%
Acc = 98.45%, TPR = 98.2711%
Acc = 98.49%, TPR = 98.2218%
Acc = 98.37%, TPR = 98.3233%
Acc = 98.53%, TPR = 98.4573%
Acc = 98.56%, TPR = 98.3118%
Acc = 98.42%, TPR = 98.5586%
Acc = 98.51%, TPR = 98.1261%
Acc = 98.55%,
Acc = 98.45%,
Acc = 98.50%,

random traces injected: 10000
summed traces duration: 0.17s
total T2 trigger found: 537
*****
TRIGGER FREQUENCY = 3159.1209 Hz

```

# Training with random traces

- Single muons from shower library:  $\sim \mathcal{O}(1 \text{ in } 4 - 5 \text{ trace batches})$
- Background muons in random traces:  $\sim \mathcal{O}(1 \text{ in } 12 \text{ trace batches})$
- How to account for this?
  - Cut on  $Q_{\text{Area}}$  (e.g.  $1 \text{ VEM}_{\text{Charge}}$ )
  - Train with lower prior
  - TODO: Cut + low prior
- Flag single muon showers as background somehow
  - Will have to redo simulations!

```


Acc = 97.01%, TPR = 99.7525%
Acc = 98.45%, TPR = 98.2711%
Acc = 98.49%, TPR = 98.2218%
Acc = 98.37%, TPR = 98.3233%
Acc = 98.53%, TPR = 98.4573%
Acc = 98.56%, TPR = 98.3118%
Acc = 98.42%, TPR = 98.5586%
Acc = 98.51%, TPR = 98.1261%
Acc = 98.55%, TPR = 98.1261%
Acc = 98.45%, TPR = 98.1261%
Acc = 98.50%, TPR = 98.1261%

random traces injected: 10000
summed traces duration: 0.17s
total T2 trigger found: 537
*****
TRIGGER FREQUENCY = 3159.1209 Hz

```


# Extracting monitoring data from random traces

■ Online values for  $Q_{\text{Peak}}$  and  $Q_{\text{Area}}$  available @ 5 min. resolution




# Extracting monitoring data from random traces

■ Online values for  $Q_{\text{Peak}}$  and  $Q_{\text{Area}}$  available @ 5 min. resolution



# Extracting monitoring data from random traces

■ Online values for  $Q_{\text{Peak}}$  and  $Q_{\text{Area}}$  available @ 5 min. resolution



■ Nuria, ID: 0056

- $Q_{\text{Peak}}$ :  $\sigma = 0.5\% \mid 2.2\%$
- $Q_{\text{Area}}$ :  $\sigma = 1.2\% \mid 6.9\%$

■ Peru, ID: 1737

- $Q_{\text{Peak}}$ :  $\sigma = 3.1\% \mid 15.3\%$
- $Q_{\text{Area}}$ :  $\sigma = 3.4\% \mid 18.5\%$

■ (Le Qui Don)

- not analysed due to low statistics in random trace files

# Doing the online/offline estimate myself

## ■ Offline estimation of $Q_{\text{Peak}}$ and $Q_{\text{Area}}$ - **GAP2020-0??**

## ■ Consider only traces that satisfy calibration trigger:


- Extract 20 bins before and 49 bins after latch bin
- Latch bin  $\geq$  Baseline + 30 ADC
- Multiplicity = 1

## ■ $Q_{\text{Peak}}$ → Histogram max of each trace

## ■ $Q_{\text{Area}}$ → Histogram sum of each trace

## ■ Fit parabola to histogram

## ■ Maximum = Offline estimate



# Doing the online/offline estimate myself

■ Offline estimation of  $Q_{\text{Peak}}$  and  $Q_{\text{Area}}$  - **GAP2020-0??**

■ Consider only traces that satisfy calibration trigger:


- Extract 20 bins before and 49 bins after latch bin
- Latch bin  $\geq$  Baseline + 30 ADC
- Multiplicity = 1

■  $Q_{\text{Peak}}$  → Histogram max of each trace

■  $Q_{\text{Area}}$  → Histogram sum of each trace

■ Fit parabola to histogram

■ Maximum = Offline estimate





# Doing the online/offline estimate myself

■ Offline estimation of  $Q_{\text{Peak}}$  and  $Q_{\text{Area}}$  - **GAP2020-0??**

■ Consider only traces that satisfy calibration trigger:

- Extract 20 bins before and 49 bins after latch bin
- Latch bin  $\geq$  Baseline + 30 ADC
- Multiplicity = 1


■  $Q_{\text{Peak}}$  → Histogram max of each trace

■  $Q_{\text{Area}}$  → Histogram sum of each trace

■ Fit parabola to histogram


■ Maximum = Offline estimate

→ Too few traces to fill histogram



# Doing the online/offline estimate myself

- Random traces taken locally at 4 stations
- Fill buffer with data, then write it to USB



- Increasing statistics by combining 3 files (~5 minutes) should be okay

# Doing the online/offline estimate myself

## ■ Offline estimation of $Q_{\text{Peak}}$ and $Q_{\text{Area}}$ - **GAP2020-0??**

## ■ Consider only traces that satisfy calibration trigger:


- Extract 20 bins before and 49 bins after latch bin
- Latch bin  $\geq$  Baseline + 30 ADC
- Multiplicity = 1

## ■ $Q_{\text{Peak}}$ → Histogram max of each trace

## ■ $Q_{\text{Area}}$ → Histogram sum of each trace

## ■ Fit parabola to histogram

## ■ Maximum = Offline estimate



# Doing the online/offline estimate myself

■ Offline estimation of  $Q_{\text{Peak}}$  and  $Q_{\text{Area}}$  - **GAP2020-0??**

■ Consider only traces that satisfy calibration trigger:

- Extract 20 bins before and 49 bins after latch bin
- Latch bin  $\geq$  Baseline + 30 ADC
- Multiplicity = 1


■  $Q_{\text{Peak}}$  → Histogram max of each trace

■  $Q_{\text{Area}}$  → Histogram sum of each trace

■ Fit parabola to histogram


■ Maximum = Offline estimate

→ Improves statistics, but not shape




# Doing the online/offline estimate myself

## Pauls' offline estimate



## Online monitoring



# Doing the online/offline estimate myself

- Online estimation of  $Q_{\text{Peak}}$  and  $Q_{\text{Area}}$  - <https://doi.org/10.1016/j.nima.2006.07.066>
- Calibration trigger with threshold  $1.75 \cdot Q_{\text{Peak}} \Big|_{M=3} \&\& 2.5 \cdot Q_{\text{Peak}} \Big|_{M=1}$  :
  - Set  $Q_{\text{Peak}} / Q_{\text{Peak}}$  s.t. trigger rate = 70 Hz
- Should result in Th2 rate of 20 Hz
- Error in my implementation?
- Why not set thresholds with Th?
- Is this reasonable what I'm doing?



```

pmt_has_converged = 0
n_triggers = np.zeros(3)

for pmt1, pmt2, pmt3 in zip(station[:,0], station[:,1], station[:,2]):

    for bins in zip(pmt1, pmt2, pmt3):

        # assume all PMTs are working, k70 = 1.75
        # check the actual trigger rate
        if np.all(bins >= 1.75 * I_vem):

            for i in range(3):
                if bins[i] >= 2.5 * I_vem[i]: n_triggers[i] += 1

trigger_rates = n_triggers / (len(Buffer._these_traces) * 2048 * 8.33e-8)

print(f"VEM_peak estimate: {I_vem} ==> {trigger_rates} Hz")

for i in range(3):
    if trigger_rates[i] <= 60: I_vem[i] -= 10
    elif 60 < trigger_rates[i] <= 68: I_vem[i] -= 1
    elif 68 < trigger_rates[i] <= 72: pmt_has_converged += 1
    elif 72 < trigger_rates[i] <= 80: I_vem[i] += 1
    elif 80 < trigger_rates[i]: I_vem[i] += 10

if pmt_has_converged >= 3: break
    
```