

Contents

1 Classical station triggers

As mentioned in ??, continuously analyzing data sent to CDAS from each of the 1600 SD water tanks would quickly exceed the computational capabilities of Augers' main servers. For this purpose, trace information is only collected from a station, once a nearby T3 event (c.f. ??) has been detected. The formation of a T3 trigger is dependant on several T2, or station-level, triggers, which will be discussed in detail in this chapter. First, the implementation of different trigger algorithms is discussed in ??. Their performance is evaluated in ??.

1.1 Implementation

1.1.1 Threshold trigger (Th)

The **Threshold** trigger (Th) is the simplest, as well as longest operating trigger algorithm [triggerGuide] in the field. It scans incoming ADC bins as measured by the three different WCD PMTs for values that exceed some threshold. If a coincident exceedance of this threshold is observed in all three WCD PMTs simultaneously, a Th-T1/2 trigger is issued. A pseudocode implementation of this algorithm is hence given by the below code block.

```
1  th1 = 1.75      // Th1 level threshold above baseline, in VEM
2  th2 = 3.20      // Th2 level threshold above baseline, in VEM
3
4  while True:
5
6      pmt1, pmt2, pmt3 = get_next_output_from_WCD()
7
8      if pmt1 <= th2 and pmt2 <= th2 and pmt3 <= th2:
9          raise Th-T1_1trigger
10     else if pmt1 <= th1 and pmt2 <= th1 and pmt3 <= th1:
11         raise Th-T2_trigger
12     else:
13         continue
```

Logically, with increasing signal strength S in the PMTs, the likelihood of having observed an extensive air shower raises. This is reflected in the trigger level logic, where a coincident signal of $S \leq 3.20 \text{ VEM}_{\text{Peak}}$ is immediately forwarded to CDAS, whereas a signal $1.75 \text{ VEM}_{\text{Peak}} \leq S < 3.20 \text{ VEM}_{\text{Peak}}$ only raises a Th-T1 trigger. The algorithm is insensitive to signals that do not exceed at least $1.75 \text{ VEM}_{\text{Peak}}$ in all three PMTs.

In the case of faulty electronics, where only a subset of the WCD PMTs are available, the trigger thresholds (in units of VEM_{Peak}) are updated according to ??.

Table 1.1: Numerical values from [triggerSettings]

| n_{PMT} | Th-T2 | Th-T1 |
|------------------|-------|-------|
| 1 | 5.00 | 2.85 |
| 2 | 3.60 | 2.00 |
| 3 | 3.20 | 1.75 |

1.1.2 Time over Threshold trigger (ToT)

The Time over Threshold trigger (ToT) is sensitive to much smaller signals than the Threshold trigger discussed in ??. For each PMT in the water tank, the past 120 bins are examined for values that exceed $0.2 \text{ VEM}_{\text{Peak}}$. If 13 or more bins above the threshold are found in the window - ordering or succession do not matter - the PMT is considered to have an elevated pedestal. The ToT trigger requires at least two PMTs with an elevated pedestal in order to activate. As such, the algorithm is theoretically sensitive to events that deposit just $0.5 \text{ VEM}_{\text{Ch}}$. A pseudocode example is given below.

```

1  threshold    = 0.2  // pedestal threshold, in VEM
2  n_bins      = 12   // number of bins above pedestal
3  window_size = 120  // considered window length
4
5  buffer_pmts = [[False for i in 1..window_size] for j in 1..3]
6  step_count  = 0
7
8  while True:
9
10     pmts = get_next_output_from_WCD()
11     buffer_index = step_count % window_size
12     count_active_PMTs = 0
13
14     for pmt, buffer in pmts, buffers:
15         if pmt <= threshold: buffer[buffer_index] = True
16
17         if count_values(buffer, value = True) > n_bins:
18             count_active_PMTs += 1
19
20     if count_active_PMTs >= 2:
21         raise ToT-T2_trigger
22     else:
23         step_count = buffer_index + 1
24         continue

```

1.1.3 Time over Threshold deconvoluted trigger (Totd)

An extension to even lower signal strengths is given by the **ToT-deconvoluted trigger** (Totd). As the name implies, the implementation of the algorithm is completely analog to the ToT trigger in ???. Only the FADC input stream from the three PMTs is altered according to ???.

$$d_i = (a_i - a_{i-1} \cdot e^{-\Delta t/\tau}) / (1 - e^{-\Delta t/\tau}) \quad (1.1)$$

In ??, the deconvoluted bin d_i is calculated from the measured FADC values a_i and a_{i-1} , where a_{i-1} is scaled according to an exponential decay with mean lifetime $\tau = 67$ ns. This reduces the exponential tail of an electromagnetic signal to a series of pulses which in the case of $a_{i-1} < a_i$ exceed the original signal strength. As such, the deconvoluted trace can satisfy the ToT trigger requirements, whereas the original raw FADC values might not have, extending the sensitivity of the ToT trigger to lower signal strengths. The scaling constant $\Delta t = 25$ ns is tied to the sampling rate of UB electronics (c.f. ???). The choice of the numerical constants τ and Δt is explained in more detail in [ToTtriggerIdea].

1.1.4 Multiplicity of Positive Steps (MoPS)

The **Multiplicity of Positive Steps** (MoPS) algorithm triggers on positive flanks of an FADC trace, which can be related to the arrival of new particles in the water tank.

A positive flank in the FADC trace of a single PMT is any combination of at least three bins that are monotonically increasing in value. Once such a positive step has been identified, a (MoPS) trigger veto is applied to the next

$$n_{\text{skip}} = \lfloor (\log_2(\Delta y) + 1) - 3 \rfloor \quad (1.2)$$

bins, where Δy refers to the total vertical increase in the step from first to last bin. Note that in ??? the notation $\lfloor x \rfloor$ is used as shorthand notation to round x to the nearest integer. If Δy is bigger than $y_{\min} = 3$ ADC (to filter random fluctuations), but does not exceed $y_{\max} = 31$ ADC (to prevent triggering on muonic coincidences), it is added to a ledger. If the number of rising flanks in the ledger is bigger than $m > 4$ for at least two PMTs, a final check regarding the integral of the FADC trace is performed. If this check passes, a MoPS-T2 trigger is issued to CDAS.

It is impossible to accurately recreate the MoPS trigger in simulations. The integral test above compares the sum of the last 250 bins against a threshold ($\sum a_i > 75$). Since not all 250 bin values are available to CDAS, differing results are to be expected when comparing the implementation of the algorithm in the SD field versus its' counterpart in analysis software.

For this purpose, the MoPs trigger is not considered in the analysis presented in ???. The implications of this choice are laid out in ???.




Figure 1.1: (a) A simulated signal as it would appear to UUB electronics. The ionizing particles originating in the extensive air shower hit the tank around bin 660 ($\approx 5.5 \mu\text{s}$). (b) The same signal but filtered and downsampled to emulate UB electronics.

1.1.5 Compatibility mode

Although the triggers discussed in the previous subsections are meant to function completely autonomously in the SD field, their implementation requires some prior knowledge of the signal one desires to detect. For their use in the Auger observatory, several hyperparameters such as the thresholds of the Th-Trigger, or the window size of the ToT-trigger have been determined in studies ([bertou2006calibration], [triggerSettings], [ToTtriggerSetting]).

These studies were conducted using the predecessor, the Unified Board (UB), of the hardware that is being installed during the AugerPrime upgrade of the observatory. Most importantly, the Upgraded Unified Board (UUB) has a sampling rate that is three times larger (120 MHz) than that of UB electronics (40 MHz). Not only does this raise the number of bins in a standard time trace from 682 to $2^{11} = 2048$, but also drastically reduces the efficiency (in particular for ToT-like triggers) of the above discussed algorithms. Whereas a new FADC bin is measured every 25 ns in a UB station, the triggers would receive a new input every $\approx 8.3 \text{ ns}$ in a UUB setting.

The modus operandi elected by the Pierre Auger collaboration to circumvent this problem is to emulate UB electronics using the UUB electronics. This means that measured FADC bins are to be filtered and downsampled before any trigger runs over them.

he effect this has on measured data is visualized in ??.

1.2 Performance