

Qumulo REST API Guide



Copyright © 2026 Qumulo, Inc.

Table of Contents

Access Tokens V1 (auth)

auth/access-tokens.....	15
auth/access-tokens/{id}.....	21

Active Directory V1 (ad)

ad/cancel.....	29
ad/dismiss-error	30
ad/distinguished-names/{dn}/object.....	33
ad/gids/{gid}/sids	35
ad/join	36
ad/leave	38
ad/monitor	40
ad/reconfigure	43
ad/settings	45
ad/sids/{sid}/expanded-groups	49
ad/sids/{sid}/gid.....	50
ad/sids/{sid}/object	51
ad/sids/{sid}/uid.....	53
ad/sids/{sid}/username	54
ad/status.....	55
ad/uids/{uid}/sids.....	58
ad/usernames/{username}/objects.....	59
ad/usernames/{username}/sids.....	61

Analytics V1 (analytics)

analytics/activity/current.....	62
analytics/capacity-history	64
analytics/capacity-history/{timestamp}	66
analytics/time-series	68

Audit Log V1 (audit)

audit/cloudwatch/config	70
audit/cloudwatch/status	74
audit/syslog/config	76
audit/syslog/status	82

Audit Log V2 (audit)

audit/destinations.....	84
audit/destinations/{id}.....	89
audit/destinations/{id}/status.....	97

Authentication V1 (auth)

auth/auth-ids/{id}/related-identities.....	99
auth/clear-cache.....	101
auth/identities/{id}/attributes.....	102
auth/identity/expand.....	105
auth/identity/find.....	116
auth/kerberos-keytab.....	119
auth/kerberos-settings.....	125
auth/local-username/{username}/related-identities.....	127
auth/posix-gids/{id}/related-identities.....	129
auth/posix-uids/{id}/related-identities.....	131
auth/sids/{id}/related-identities.....	133
auth/user-defined-mappings.....	135

Authoritative DNS Methods V1 (authoritative-dns)

authoritative-dns/settings.....	138
---------------------------------	-----

Capacity Clamp V1 (capacity)

capacity/clamp.....	141
---------------------	-----

Cloud Data Fabric V1 (portal)

portal/file-systems.....	143
portal/file-systems/{id}.....	144
portal/files/{file_id}/evict.....	145
portal/ping.....	146
portal/quorum/events.....	149
portal/spokes/eviction-settings.....	152

Cloud Data Fabric V2 (portal)

portal/hubs	155
portal/hubs/{id}	158
portal/hubs/{id}/accept	165
portal/hubs/{id}/roots/{dir}	169
portal/spokes	174
portal/spokes/{id}	180
portal/spokes/{id}/roots	188
portal/spokes/{id}/roots/{dir}	191

Cluster Creation V2 (cluster)

cluster/create	194
cluster/data-core/create	196
cluster/unprotected-edge/create	198

Cluster Creation V3 (cluster)

cluster/calculate-supported-protection-info	199
---	-----

Cluster Creation V4 (cluster)

cluster/object-backed/create	202
------------------------------------	-----

Cluster Creation V5 (cluster)

cluster/object-backed/create	206
cluster/object-backed/create-stratus	210

Cluster Data Protection V1 (cluster)

cluster/object-backed/protection/fault-tolerance	213
cluster/protection/restriper/status	215
cluster/protection/status	217

Cluster Management V1 (cluster)

cluster/calculate-node-add-capacity.....	219
cluster/node-replacement-plan.....	222
cluster/nodes.....	225
cluster/nodes/chassis.....	228
cluster/nodes/uid-lights.....	230
cluster/nodes/{id}.....	231
cluster/nodes/{id}/chassis.....	233
cluster/nodes/{id}/identify	235
cluster/nodes/{id}/uid-light	236
cluster/restriper/status.....	238

Cluster Management V2 (cluster)

cluster/nodes.....	240
cluster/nodes/dry-run.....	242
cluster/object-backed/nodes	245
cluster/object-backed/nodes/dry-run.....	248

Cluster Settings V1 (cluster)

cluster/settings.....	252
cluster/settings/ssl	254

Cluster Settings V2 (cluster)

cluster/settings/ssl/ca-certificate	255
cluster/settings/ssl/certificate.....	258
cluster/settings/ssl/ciphers	259

Cluster Slots V1 (cluster)

cluster/slots.....	262
cluster/slots/node/{node_id}	266
cluster/slots/{id}	270

DNS Config Methods V1 (dns)

dns/configs/system.....	277
-------------------------	-----

DNS Methods V1 (dns)

dns/clear-dns-cache	281
dns/lookup-override-config	282
dns/resolve	285
dns/resolve-ips-to-names	287
dns/resolve-names-to-ips	289

Directory Quotas V1 (files)

files/quotas	291
files/quotas/status	294
files/quotas/status/{id}	296
files/quotas/{id}	298

Encryption at Rest V1 (encryption)

encryption/rotate-keys	301
encryption/status	302

Encryption at Rest V2 (encryption)

encryption/external-kms/keys/create	303
encryption/key-store	305
encryption/key-store/status	309
encryption/rotate-keys	311

FTP Methods V0 (ftp)

ftp/settings	312
ftp/status	321

File System V1 (file-system)

file-system	324
file-system/security/keys	326
file-system/security/keys/{key_ref}	329
file-system/security/keys/{key_ref}/key-replacement-challenge	335
file-system/security/keys/{key_ref}/replace	336
file-system/security/keys/{key_ref}/usages	338
file-system/settings/atime	340
file-system/settings/notify	345
file-system/settings/permissions	348

Files V1 (files)

files/locks/nfs4/byte-range	351
files/locks/nlm/byte-range	354
files/locks/nlm/byte-range/waiters	357
files/locks/smb/byte-range	360
files/locks/smb/share-mode	363
files/resolve	366
files/try-resolve	368
files/{ref}	370
files/{ref}/aggregates	371
files/{ref}/copy-chunk	375
files/{ref}/data	378
files/{ref}/entries	391
files/{ref}/entries/{name}	410
files/{ref}/fetch-data	411
files/{ref}/file-lock	413
files/{ref}/info/acl	420
files/{ref}/info/acl/explain-posix-mode	431
files/{ref}/info/acl/explain-rights	447
files/{ref}/info/acl/explain-set-mode	469
files/{ref}/info/attributes	492
files/{ref}/locks/nfs4/byte-range	510
files/{ref}/locks/nlm/byte-range	513
files/{ref}/locks/nlm/byte-range/waiters	517
files/{ref}/locks/smb/byte-range	520
files/{ref}/locks/smb/share-mode	523
files/{ref}/notify	526
files/{ref}/punch-hole	528
files/{ref}/recursive-aggregates	535
files/{ref}/sample	539
files/{ref}/streams	542
files/{ref}/streams/{stream_id}	546
files/{ref}/streams/{stream_id}/attributes	547
files/{ref}/streams/{stream_id}/copy-chunk	555
files/{ref}/streams/{stream_id}/data	559
files/{ref}/streams/{stream_id}/punch-hole	564
files/{ref}/streams/{stream_id}/rename	566

files/{ref}/user-metadata	568
files/{ref}/user-metadata/{type}	570
files/{ref}/user-metadata/{type}/{key}	572

Files V2 (files)

files/{ref}/info/acl.....	576
---------------------------	-----

Hardware Health Methods V1 (health)

health/ssd-endurance.....	588
---------------------------	-----

Identity V1 (identity)

identity/expand.....	589
identity/find.....	600

LDAP Server V1 (ldap)

ldap/login-name/{login_name}/gid-numbers.....	603
ldap/login-name/{login_name}/uid-numbers.....	605
ldap/status	606
ldap/uid-number/{uid_number}/login-name	608

LDAP Server V2 (ldap)

ldap/settings.....	609
--------------------	-----

License Management V1 (license)

license/enforcement.....	621
license/status	622

Local Group Methods V1 (groups)

groups.....	623
groups/{group_id}/members.....	626
groups/{group_id}/members/{member_id}.....	629
groups/{id}.....	630

Local User Methods V1 (users)

users	633
users/{id}	637
users/{id}/groups.....	641
users/{id}/setpassword	643

Metrics V2 (metrics)

metrics/endpoints/default/data.....	644
-------------------------------------	-----

Monitoring Configuration and Status V1 (support)

support/settings.....	645
support/status	652
support/vpn-keys	654
support/vpn/key/certificate-signing-request	658
support/vpn/key/generate	659

NFS Methods V2 (nfs)

nfs/exports	660
nfs/exports/{ref}	671
nfs/settings	690

NFS Methods V3 (nfs)

nfs/exports	695
nfs/exports/{export_id}	707

NFS Multitenancy Methods V1 (multitenancy)

multitenancy/nfs/global-settings.....	726
multitenancy/nfs/settings	732
multitenancy/nfs/settings/{id}	734

Network Configuration V1 (network)

network/floating-ip-allocation	740
network/settings.....	741
network/static-ip-allocation.....	748
network/status	750
network/status/{id}	754

Network Configuration V2 (network)

network/connections	759
network/interfaces	761
network/interfaces/{id}/status.....	763
network/interfaces/{interface_id}	770
network/interfaces/{interface_id}/networks.....	775
network/interfaces/{interface_id}/networks/{network_id}	780
network/interfaces/{interface_id}/status/{node_id}	788

Network Configuration V3 (network)

- network795
- network/backend-interfaces806
- network/frontend-interfaces.....807
- network/status808
- network/status/{node_id}817
- network/validate 826

Nexus Configuration V1 (nexus)

- nexus/connection832
- nexus/registration837
- nexus/registration/rotate 841

Node Management V1 (node)

- node/state842

Object Storage V1 (object-storage)

- object-storage/add-uris844
- object-storage/external-credentials-source 845
- object-storage/uris846

Object Storage V2 (object-storage)

- object-storage/add-uris 847

Replication V2 (replication)

replication/source-relationships	849
replication/source-relationships/reverse-target-relationship	859
replication/source-relationships/status	863
replication/source-relationships/{id}	872
replication/source-relationships/{id}/abort-replication	888
replication/source-relationships/{id}/dismiss-error	889
replication/source-relationships/{id}/queued-snapshots	890
replication/source-relationships/{id}/replicate	893
replication/source-relationships/{id}/status	894
replication/source-relationships/{relationship_id}/queued-snapshots/{snapshot_id}	903
replication/target-relationships/status	904
replication/target-relationships/{id}/authorize	910
replication/target-relationships/{id}/delete	917
replication/target-relationships/{id}/dismiss-error	918
replication/target-relationships/{id}/lock	919
replication/target-relationships/{id}/make-writable	921
replication/target-relationships/{id}/reconnect	928
replication/target-relationships/{id}/status	935

Replication V3 (replication)

replication/object-relationships	941
replication/object-relationships/status	947
replication/object-relationships/{id}	948
replication/object-relationships/{id}/abort-replication	951
replication/object-relationships/{id}/replicate	952
replication/object-relationships/{id}/status	953

Roles V1 (auth)

auth/privileges	954
auth/roles	955
auth/roles/{role_name}	975
auth/roles/{role_name}/members	1008
auth/roles/{role_name}/members/{member_id}	1013

S3 Server Methods V1 (s3)

s3/access-keys.....	1016
s3/access-keys/{id}	1022
s3/buckets	1023
s3/buckets/{name}	1028
s3/buckets/{name}/policy.....	1032
s3/buckets/{name}/policy/explain-access	1034
s3/buckets/{name}/uploads.....	1038
s3/buckets/{name}/uploads/{id}.....	1042
s3/settings	1043

SAML Configuration V1 (saml)

saml/settings.....	1047
--------------------	------

SMB File Administration V1 (smb)

smb/files	1054
smb/files/close	1058

SMB Multitenancy Methods V1 (multitenancy)

multitenancy/smb/global-settings.....	1060
multitenancy/smb/settings.....	1069
multitenancy/smb/settings/{id}	1072

SMB Server Settings V1 (smb)

smb/settings.....	1082
-------------------	------

SMB Session Administration V1 (smb)

smb/sessions	1091
smb/sessions/close.....	1095

SMB Shares Methods V1 (smb)

smb/shares	1099
smb/shares/{id}	1104

SMB Shares Methods V2 (smb)

smb/shares	1109
smb/shares/{ref}	1125

SMB Shares Methods V3 (smb)

smb/shares	1152
smb/shares/{share_id}	1169

Session Management V1 (session)

session/change-password	1198
session/login	1199
session/retrieve-saml-login	1201
session/roles	1203
session/start-saml-login	1204
session/who-am-i	1206

Shutdown V1 (shutdown)

shutdown/container-restart	1214
shutdown/container-restart/{node_id}	1215
shutdown/halt	1216
shutdown/halt/{node_id}	1217
shutdown/reboot/pause	1218
shutdown/reboot/resume	1219
shutdown/reboot/start	1220
shutdown/reboot/status	1221
shutdown/reboot/{node_id}	1223

Snapshots V1 (snapshots)

snapshots	1224
snapshots/policies	1228
snapshots/policies/status	1239
snapshots/policies/status/{id}	1244
snapshots/policies/{id}	1249
snapshots/total-used-capacity	1267
snapshots/{id}	1268

Snapshots V2 (snapshots)

snapshots.....	1275
snapshots/policies	1279
snapshots/policies/status	1290
snapshots/policies/status/{id}	1295
snapshots/policies/{id}	1300
snapshots/status.....	1318
snapshots/status/{id}	1320
snapshots/{id}	1322
snapshots/{newer_id}/changes-since/{older_id}	1330
snapshots/{newer_id}/changes-since/{older_id}/files/{ref}	1332

Snapshots V3 (snapshots)

snapshots.....	1334
snapshots/policies	1338
snapshots/policies/status	1349
snapshots/policies/status/{id}	1354
snapshots/policies/{id}	1359
snapshots/status.....	1378
snapshots/status/{id}	1381
snapshots/{id}	1384
snapshots/{id}/lock	1391
snapshots/{id}/unlock	1393
snapshots/{id}/unlock-challenge	1394
snapshots/{newer_id}/changes-since/{older_id}/files/{ref}	1395

Snapshots V4 (snapshots)

snapshots/status.....	1397
-----------------------	------

Tenant Configuration V1 (multitenancy)

multitenancy/tenants.....	1400
multitenancy/tenants/{tenant_id}	1405

Time Configuration Methods V1 (time)

time/settings	1413
time/status.....	1417
time/timezones	1419

Time Configuration Methods V2 (time)

time/default-settings.....	1420
time/settings	1422
time/status.....	1427
time/timezones	1429

Tree Delete V1 (tree-delete)

tree-delete/jobs	1430
tree-delete/jobs/restart/{id}	1433
tree-delete/jobs/{id}	1434

Unconfigured Node Management V1 (node)

node/state	1437
------------------	------

Unconfigured Nodes V1 (unconfigured)

unconfigured/nodes.....	1439
-------------------------	------

Unconfigured Nodes Discovery V1 (unconfigured)

unconfigured/nodes.....	1442
-------------------------	------

Unconfigured Version V1 (version)

version.....	1445
--------------	------

Upgrade V2 (upgrade)

upgrade/blocked	1446
upgrade/commit	1447
upgrade/prepare	1448
upgrade/status	1450
upgrade/verify-image	1452

Upgrade V3 (upgrade)

upgrade/status	1454
----------------------	------

Version V1 (version)

version.....	1456
--------------	------

Web UI Settings V1 (web-ui)

web-ui/settings.....	1457
----------------------	------

auth/access-tokens/

Endpoint

/v1/auth/access-tokens/

GET

List all access tokens for the cluster or specified user. Privilege ACCESS_TOKENS_READ is required to list keys for users other than yourself

Parameters

Name	Description	Required
<code>user</code>	Filters access tokens by user identity if specified.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_access_token_metadata_list_model",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "entries",
        "type": "object",
        "properties": {
          "id": {
            "description": "The access token's identifier for management APIs.",
            "type": "string"
          }
        }
      }
    }
  }
}
```



```

},
"user": {
  "description": "The user that the access token was created for.",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR  
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN  
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`  
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL  
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER  
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`  
- POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {

```

```

        "description": "name",
        "type": "string"
    }
}
},
"creator": {
    "description": "The user that created the access token.",
    "type": "object",
    "properties": {
        "domain": {
            "type": "string",
            "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",
                "API_INVALID_DOMAIN",
                "API_RESERVED_DOMAIN",
                "API_INTERNAL_DOMAIN",
                "API_OPERATOR_DOMAIN",
                "API_QUMULO_SUPPORT_DOMAIN",
                "API_CREATOR_DOMAIN"
            ],
            "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
        },
        "auth_id": {
            "description": "auth_id",
            "type": "string"
        },
        "uid": {
            "description": "uid",
            "type": "number"
        },
        "gid": {
            "description": "gid",
            "type": "number"
        },
        "sid": {

```

```
    "description": "sid",  
    "type": "string"  
  },  
  "name": {  
    "description": "name",  
    "type": "string"  
  }  
}  
  
},  
"creation_time": {  
  "description": "The time that the access token was created.",  
  "type": "string"  
},  
"expiration_time": {  
  "description": "The time after which the access token is expired.",  
  "type": "string"  
},  
"enabled": {  
  "description": "This access token can be used to authenticate.",  
  "type": "boolean"  
}  
}  
}  
}
```

Create an access token for the specified user. Privilege `ACCESS_TOKENS_WRITE` is required to create a key for a user other than yourself.

This resource has no parameters.

Schema

```

"type": "object",
"properties": {
  "domain": {
    "type": "string",
    "enum": [
      "LOCAL",
      "API_NULL_DOMAIN",
      "WORLD",
      "POSIX_USER",
      "POSIX_GROUP",
      "ACTIVE_DIRECTORY",
      "API_INVALID_DOMAIN",
      "API_RESERVED_DOMAIN",
      "API_INTERNAL_DOMAIN",
      "API_OPERATOR_DOMAIN",
      "API_QUMULO_SUPPORT_DOMAIN",
      "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
  },
  "auth_id": {
    "description": "auth_id",
    "type": "string"
  },
  "uid": {
    "description": "uid",
    "type": "number"
  },
  "gid": {
    "description": "gid",
    "type": "number"
  },
  "sid": {
    "description": "sid",
    "type": "string"
  },
  "name": {
    "description": "name",
    "type": "string"
  }
}

```

```

    }
  },
  "expiration_time": {
    "description": "The time after which the access token is expired.",
    "type": "string"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_access_token",
  "type": "object",
  "properties": {
    "id": {
      "description": "The access token's identifier for management APIs.",
      "type": "string"
    },
    "bearer_token": {
      "description": "The bearer token for authenticating over REST. Can be used in  
qq, REST bindings, or an HTTP Authorization header.",
      "type": "string"
    }
  }
}

```

auth/access-tokens/{id}

Endpoint

/v1/auth/access-tokens/{id}

GET

Get metadata about the specified access token. Privilege ACCESS_TOKENS_READ is required if the token is for a user other than yourself.

Parameters

Name	Description	Required
id	Access Token ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_access_token_metadata",
  "type": "object",
  "properties": {
    "id": {
      "description": "The access token's identifier for management APIs.",
      "type": "string"
    },
    "user": {
      "description": "The user that the access token was created for.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",

```

```

        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
  },
  "auth_id": {
    "description": "auth_id",
    "type": "string"
  },
  "uid": {
    "description": "uid",
    "type": "number"
  },
  "gid": {
    "description": "gid",
    "type": "number"
  },
  "sid": {
    "description": "sid",
    "type": "string"
  },
  "name": {
    "description": "name",
    "type": "string"
  }
},
"creator": {
  "description": "The user that created the access token.",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",

```

```

    "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
  },
  "auth_id": {
    "description": "auth_id",
    "type": "string"
  },
  "uid": {
    "description": "uid",
    "type": "number"
  },
  "gid": {
    "description": "gid",
    "type": "number"
  },
  "sid": {
    "description": "sid",
    "type": "string"
  },
  "name": {
    "description": "name",
    "type": "string"
  }
}
},
"creation_time": {
  "description": "The time that the access token was created.",

```



```

    "type": "string"
  },
  "expiration_time": {
    "description": "The time after which the access token is expired.",
    "type": "string"
  },
  "enabled": {
    "description": "This access token can be used to authenticate.",
    "type": "boolean"
  }
}
}

```

DELETE

Delete the specified access token. Privilege ACCESS_TOKENS_WRITE is required to delete a token for a user other than yourself.

Parameters

Name	Description	Required
<code>id</code>	Access Token ID	Yes

Response

Codes

Code	Description
200	Return value on success

PATCH

Modify metadata for the specified access token. Privilege ACCESS_TOKENS_WRITE is required to modify a token for a user other than yourself.

Parameters

Name	Description	Required
<code>id</code>	Access Token ID	Yes

Request

Schema

```
{
  "description": "api_access_token_modify_metadata_patch",
  "type": "object",
  "properties": {
    "expiration_time": {
      "description": "The time after which the access token is expired.",
      "type": "string"
    },
    "enabled": {
      "description": "This access token can be used to authenticate.",
      "type": "boolean"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_access_token_metadata",
  "type": "object",
  "properties": {
    "id": {
      "description": "The access token's identifier for management APIs.",
      "type": "string"
    },
    "user": {
      "description": "The user that the access token was created for.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",

```

```

        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
  },
  "auth_id": {
    "description": "auth_id",
    "type": "string"
  },
  "uid": {
    "description": "uid",
    "type": "number"
  },
  "gid": {
    "description": "gid",
    "type": "number"
  },
  "sid": {
    "description": "sid",
    "type": "string"
  },
  "name": {
    "description": "name",
    "type": "string"
  }
}
},
"creator": {
  "description": "The user that created the access token.",
  "type": "object",
  "properties": {

```

```

"domain": {
  "type": "string",
  "enum": [
    "LOCAL",
    "API_NULL_DOMAIN",
    "WORLD",
    "POSIX_USER",
    "POSIX_GROUP",
    "ACTIVE_DIRECTORY",
    "API_INVALID_DOMAIN",
    "API_RESERVED_DOMAIN",
    "API_INTERNAL_DOMAIN",
    "API_OPERATOR_DOMAIN",
    "API_QUMULO_SUPPORT_DOMAIN",
    "API_CREATOR_DOMAIN"
  ],
  "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
},
"auth_id": {
  "description": "auth_id",
  "type": "string"
},
"uid": {
  "description": "uid",
  "type": "number"
},
"gid": {
  "description": "gid",
  "type": "number"
},
"sid": {
  "description": "sid",
  "type": "string"
},
"name": {
  "description": "name",
  "type": "string"
}
},
},

```

```
"creation_time": {
  "description": "The time that the access token was created.",
  "type": "string"
},
"expiration_time": {
  "description": "The time after which the access token is expired.",
  "type": "string"
},
"enabled": {
  "description": "This access token can be used to authenticate.",
  "type": "boolean"
}
}
```

ad/cancel

Endpoint

/v1/ad/cancel

POST

Cancel current join or leave operation.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
202	Return value on success

ad/dismiss-error

Endpoint

/v1/ad/dismiss-error

POST

Dismiss the last error recorded from a join, reconfigure, or leave operation.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "ad_domain_monitor",
  "type": "object",
  "properties": {
    "status": {
      "type": "string",
      "enum": [
        "LEAVE_SUCCEEDED",
        "JOIN_SUCCEEDED",
        "LEAVE_FAILED",
        "JOIN_FAILED",
        "LEAVE_IN_PROGRESS",
        "JOIN_IN_PROGRESS",
        "RECONFIGURE_IN_PROGRESS"
      ],
      "description": "status:\n * `JOIN_FAILED` - JOIN_FAILED,\n * `JOIN_IN_PROGRESS` - JOIN_IN_PROGRESS,\n * `JOIN_SUCCEEDED` - JOIN_SUCCEEDED,\n * `LEAVE_FAILED` - LEAVE_FAILED,\n * `LEAVE_IN_PROGRESS` - LEAVE_IN_PROGRESS,\n * `LEAVE_SUCCEEDED` - LEAVE_SUCCEEDED,\n * `RECONFIGURE_IN_PROGRESS` - RECONFIGURE_IN_PROGRESS"
    },
    "last_error": {
      "description": "last_error",

```

```

"type": "object",
"properties": {
  "module": {
    "description": "module",
    "type": "string"
  },
  "error_class": {
    "description": "error_class",
    "type": "string"
  },
  "description": {
    "description": "description",
    "type": "string"
  },
  "stack": {
    "description": "stack",
    "type": "string"
  },
  "user_visible": {
    "description": "user_visible",
    "type": "boolean"
  }
},
"last_action_time": {
  "description": "last_action_time",
  "type": "string"
},
"id": {
  "description": "id",
  "type": "number"
},
"domain": {
  "description": "domain",
  "type": "string"
},
"domain_netbios": {
  "description": "domain_netbios",
  "type": "string"
},
"ou": {
  "description": "ou",
  "type": "string"
},
"search_trusted_domains": {
  "description": "search_trusted_domains",

```



```
    "type": "boolean"
  },
  "use_ad_posix_attributes": {
    "description": "use_ad_posix_attributes",
    "type": "boolean"
  },
  "base_dn": {
    "description": "base_dn",
    "type": "string"
  },
  "configured_dcs": {
    "type": "array",
    "items": {
      "description": "configured_dcs",
      "type": "string"
    }
  }
}
```

ad/distinguished-names/{dn}/object

Endpoint

`/v1/ad/distinguished-names/{dn}/object`

GET

Return the AD account object that has the given distinguished name.

Parameters

Name	Description	Required
<code>dn</code>	The distinguished name to use to look up an AD user or group.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "ad_ldap_object",
  "type": "object",
  "properties": {
    "dn": {
      "description": "dn",
      "type": "string"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    }
  }
}
```

```
},
"name": {
  "description": "name",
  "type": "string"
},
"groups": {
  "type": "array",
  "items": {
    "description": "groups",
    "type": "string"
  }
},
"primary_group_sid": {
  "description": "primary_group_sid",
  "type": "string"
},
"classes": {
  "type": "array",
  "items": {
    "description": "classes",
    "type": "string"
  }
}
}
```

ad/gids/{gid}/sids/

Endpoint

/v1/ad/gids/{gid}/sids/

GET

Return the SIDs for the given GID as found by issuing an AD query against the current domain the cluster is joined to.

Parameters

Name	Description	Required
gid	The GID to use to look up its SIDs	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

ad/join

Endpoint

/v1/ad/join

POST

Joins the cluster to an Active Directory domain.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "ad_domain_join_args",
  "type": "object",
  "properties": {
    "domain": {
      "description": "domain",
      "type": "string"
    },
    "domain_netbios": {
      "description": "domain_netbios",
      "type": "string"
    },
    "user": {
      "description": "user",
      "type": "string"
    },
    "password": {
      "description": "password",
      "type": "string",
      "format": "password"
    },
    "ou": {
      "description": "OU",
      "type": "string"
    },
    "search_trusted_domains": {
      "description": "Allows the cluster to search trusted domains for user informat
ion.",
      "type": "boolean"
    }
  }
}
```

```
    },
    "use_ad_posix_attributes": {
      "description": "Use AD POSIX attributes",
      "type": "boolean"
    },
    "base_dn": {
      "description": "Base DN",
      "type": "string"
    },
    "domain_controllers": {
      "description": "A comma-separated list of domain controllers (DCs) to use with the specified AD domain.",
      "type": "string"
    },
    "dns_config_id": {
      "description": "The unique ID of the DNS configuration to use for joining this AD domain",
      "type": "number"
    }
  }
}
```

Response

Codes

Code	Description
202	Return value on success

ad/leave

Endpoint

/v1/ad/leave

POST

Removes the cluster from Active Directory.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "ad_domain_leave_args",
  "type": "object",
  "properties": {
    "domain": {
      "description": "domain",
      "type": "string"
    },
    "user": {
      "description": "user",
      "type": "string"
    },
    "password": {
      "description": "password",
      "type": "string",
      "format": "password"
    },
    "dns_config_id": {
      "description": "The unique ID of the DNS configuration to use for leaving this AD domain",
      "type": "number"
    }
  }
}
```

Response

Codes

Code	Description
202	Return value on success

ad/monitor

Endpoint

/v1/ad/monitor

GET

Gets details on a join or leave operation.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "ad_domain_monitor",
  "type": "object",
  "properties": {
    "status": {
      "type": "string",
      "enum": [
        "LEAVE_SUCCEEDED",
        "JOIN_SUCCEEDED",
        "LEAVE_FAILED",
        "JOIN_FAILED",
        "LEAVE_IN_PROGRESS",
        "JOIN_IN_PROGRESS",
        "RECONFIGURE_IN_PROGRESS"
      ],
      "description": "status:\n * `JOIN_FAILED` - JOIN_FAILED,\n * `JOIN_IN_PROGRESS` - JOIN_IN_PROGRESS,\n * `JOIN_SUCCEEDED` - JOIN_SUCCEEDED,\n * `LEAVE_FAILED` - LEAVE_FAILED,\n * `LEAVE_IN_PROGRESS` - LEAVE_IN_PROGRESS,\n * `LEAVE_SUCCEEDED` - LEAVE_SUCCEEDED,\n * `RECONFIGURE_IN_PROGRESS` - RECONFIGURE_IN_PROGRESS"
    },
    "last_error": {
      "description": "last_error",

```

```

"type": "object",
"properties": {
  "module": {
    "description": "module",
    "type": "string"
  },
  "error_class": {
    "description": "error_class",
    "type": "string"
  },
  "description": {
    "description": "description",
    "type": "string"
  },
  "stack": {
    "description": "stack",
    "type": "string"
  },
  "user_visible": {
    "description": "user_visible",
    "type": "boolean"
  }
},
"last_action_time": {
  "description": "last_action_time",
  "type": "string"
},
"id": {
  "description": "id",
  "type": "number"
},
"domain": {
  "description": "domain",
  "type": "string"
},
"domain_netbios": {
  "description": "domain_netbios",
  "type": "string"
},
"ou": {
  "description": "ou",
  "type": "string"
},
"search_trusted_domains": {
  "description": "search_trusted_domains",

```

```
    "type": "boolean"
  },
  "use_ad_posix_attributes": {
    "description": "use_ad_posix_attributes",
    "type": "boolean"
  },
  "base_dn": {
    "description": "base_dn",
    "type": "string"
  },
  "configured_dcs": {
    "type": "array",
    "items": {
      "description": "configured_dcs",
      "type": "string"
    }
  }
}
```

ad/reconfigure

Endpoint

/v1/ad/reconfigure

POST

Enables/disables POSIX attributes, sets Base DN.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "ad_domain_reconfigure_args",
  "type": "object",
  "properties": {
    "domain": {
      "description": "domain",
      "type": "string"
    },
    "search_trusted_domains": {
      "description": "Allows the cluster to search trusted domains for user information.",
      "type": "boolean"
    },
    "use_ad_posix_attributes": {
      "description": "use_ad_posix_attributes",
      "type": "boolean"
    },
    "base_dn": {
      "description": "base_dn",
      "type": "string"
    },
    "domain_controllers": {
      "description": "A comma-separated list of domain controllers (DCs) to use with the specified AD domain.",
      "type": "string"
    },
    "dns_config_id": {
      "description": "The unique ID of the DNS configuration to use for reconfiguring this AD domain",
      "type": "string"
    }
  }
}
```

```
    "type": "number"  
  }  
}  
}
```

Response

Codes

Code	Description
202	Return value on success

ad/settings

Endpoint

/v1/ad/settings

GET

Gets advanced Active Directory settings.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "ad_settings",
  "type": "object",
  "properties": {
    "signing": {
      "type": "string",
      "enum": [
        "NO_SIGNING",
        "WANT_SIGNING",
        "REQUIRE_SIGNING"
      ],
      "description": "Setting for DCERPC signing; only use if sealing is not negotiated:\n * `NO_SIGNING` - Do not use DCERPC signing.,\n * `REQUIRE_SIGNING` - Require the use of DCERPC signing.,\n * `WANT_SIGNING` - Prefer to use DCERPC signing; allow server to decide."
    },
    "sealing": {
      "type": "string",
      "enum": [
        "NO_SEALING",
        "WANT_SEALING",
        "REQUIRE_SEALING"
      ]
    }
  }
}
```

```

    ],
    "description": "Setting for DCERPC sealing.:\\n * `NO_SEALING` - Do not use sea
ling.,\\n * `REQUIRE_SEALING` - Require the use of sealing.,\\n * `WANT_SEALING` - Pre
fer to use sealing; allow server to decide."
  },
  "crypto": {
    "type": "string",
    "enum": [
      "NO_AES",
      "WANT_AES",
      "REQUIRE_AES"
    ],
    "description": "Setting for authenticator and sealing crypto.:\\n * `NO_AES` -
Do not use AES.,\\n * `REQUIRE_AES` - Require the use of AES.,\\n * `WANT_AES` - Prefe
r use of AES; allow server to decide."
  }
}
}

```

PUT

Sets advanced Active Directory settings.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "ad_settings",
  "type": "object",
  "properties": {
    "signing": {
      "type": "string",
      "enum": [
        "NO_SIGNING",
        "WANT_SIGNING",
        "REQUIRE_SIGNING"
      ],
      "description": "Setting for DCERPC signing; only use if sealing is not negotia

```

```

ted:\n * `NO_SIGNING` - Do not use DCERPC signing.,\n * `REQUIRED_SIGNING` - Require
the use of DCERPC signing.,\n * `WANT_SIGNING` - Prefer to use DCERPC signing; allo
w server to decide."
    },
    "sealing": {
      "type": "string",
      "enum": [
        "NO_SEALING",
        "WANT_SEALING",
        "REQUIRED_SEALING"
      ],
      "description": "Setting for DCERPC sealing.:\\n * `NO_SEALING` - Do not use sea
ling.,\\n * `REQUIRED_SEALING` - Require the use of sealing.,\\n * `WANT_SEALING` - Pre
fer to use sealing; allow server to decide."
    },
    "crypto": {
      "type": "string",
      "enum": [
        "NO_AES",
        "WANT_AES",
        "REQUIRED_AES"
      ],
      "description": "Setting for authenticator and sealing crypto.:\\n * `NO_AES` -
Do not use AES.,\\n * `REQUIRED_AES` - Require the use of AES.,\\n * `WANT_AES` - Prefe
r use of AES; allow server to decide."
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "ad_settings",
  "type": "object",
  "properties": {
    "signing": {
      "type": "string",

```



```

    "enum": [
        "NO_SIGNING",
        "WANT_SIGNING",
        "REQUIRE_SIGNING"
    ],
    "description": "Setting for DCERPC signing; only use if sealing is not negotiated:\n * `NO_SIGNING` - Do not use DCERPC signing.,\n * `REQUIRE_SIGNING` - Require the use of DCERPC signing.,\n * `WANT_SIGNING` - Prefer to use DCERPC signing; allow server to decide."
  },
  "sealing": {
    "type": "string",
    "enum": [
        "NO_SEALING",
        "WANT_SEALING",
        "REQUIRE_SEALING"
    ],
    "description": "Setting for DCERPC sealing:.\n * `NO_SEALING` - Do not use sealing.,\n * `REQUIRE_SEALING` - Require the use of sealing.,\n * `WANT_SEALING` - Prefer to use sealing; allow server to decide."
  },
  "crypto": {
    "type": "string",
    "enum": [
        "NO_AES",
        "WANT_AES",
        "REQUIRE_AES"
    ],
    "description": "Setting for authenticator and sealing crypto:.\n * `NO_AES` - Do not use AES.,\n * `REQUIRE_AES` - Require the use of AES.,\n * `WANT_AES` - Prefer use of AES; allow server to decide."
  }
}

```

ad/sids/{sid}/expanded-groups/

Endpoint

/v1/ad/sids/{sid}/expanded-groups/

GET

Return the SIDs of all the groups that the given SID is a member of, (including all nested groups).

Parameters

Name	Description	Required
<code>sid</code>	The SID to use to look up the SIDs of all the groups that this SID belongs to (this includes all nested groups).	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_ad_group_sid",
    "type": "object",
    "properties": {
      "sid": {
        "description": "sid",
        "type": "string"
      }
    }
  }
}
```

ad/sids/{sid}/gid

Endpoint

/v1/ad/sids/{sid}/gid

GET

Return the GID for the given group SID as found by issuing an AD query against the current domain the cluster is joined to.

Parameters

Name	Description	Required
sid	The group SID to use to look up a GID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_ad_gid",
  "type": "object",
  "properties": {
    "gid": {
      "description": "gid",
      "type": "number"
    }
  }
}
```

ad/sids/{sid}/object

Endpoint

/v1/ad/sids/{sid}/object

GET

Return the AD account object that has the given SID.

Parameters

Name	Description	Required
<code>sid</code>	The SID to use to look up an AD user or group.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "ad_ldap_object",
  "type": "object",
  "properties": {
    "dn": {
      "description": "dn",
      "type": "string"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    }
  }
}
```

```
},
"name": {
  "description": "name",
  "type": "string"
},
"groups": {
  "type": "array",
  "items": {
    "description": "groups",
    "type": "string"
  }
},
"primary_group_sid": {
  "description": "primary_group_sid",
  "type": "string"
},
"classes": {
  "type": "array",
  "items": {
    "description": "classes",
    "type": "string"
  }
}
}
```

ad/sids/{sid}/uid

Endpoint

/v1/ad/sids/{sid}/uid

GET

Return the UID for the given SID as found by issuing an AD query against the current domain the cluster is joined to.

Parameters

Name	Description	Required
<code>sid</code>	The SID to use to look up a UID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_ad_uid",
  "type": "object",
  "properties": {
    "uid": {
      "description": "uid",
      "type": "number"
    }
  }
}
```

ad/sids/{sid}/username

Endpoint

/v1/ad/sids/{sid}/username

GET

Return the Username for the given SID as found by querying the domain controller for the domain the cluster is joined to.

Parameters

Name	Description	Required
sid	The SID to use to looukup a username	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "string"
}
```

ad/status

Endpoint

/v1/ad/status

GET

Get Active Directory configuration and status.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_ad_status",
  "type": "object",
  "properties": {
    "status": {
      "type": "string",
      "enum": [
        "NOT_IN_DOMAIN",
        "JOINED_TO_DOMAIN"
      ],
      "description": "status:\n * `JOINED_TO_DOMAIN` - JOINED_TO_DOMAIN,\n * `NOT_I
N_DOMAIN` - NOT_IN_DOMAIN"
    },
    "domain": {
      "description": "domain",
      "type": "string"
    },
    "ou": {
      "description": "ou",
      "type": "string"
    },
    "search_trusted_domains": {
```



```

    "description": "search_trusted_domains",
    "type": "boolean"
  },
  "use_ad_posix_attributes": {
    "description": "use_ad_posix_attributes",
    "type": "boolean"
  },
  "base_dn": {
    "description": "base_dn",
    "type": "string"
  },
  "domain_netbios": {
    "description": "domain_netbios",
    "type": "string"
  },
  "dcs": {
    "type": "array",
    "items": {
      "description": "dcs",
      "type": "object",
      "properties": {
        "name": {
          "description": "name",
          "type": "string"
        },
        "address": {
          "description": "address",
          "type": "string"
        }
      }
    }
  },
  "ldap_connection_states": {
    "type": "array",
    "items": {
      "description": "ldap_connection_states",
      "type": "object",
      "properties": {
        "node_id": {
          "description": "node_id",
          "type": "number"
        },
        "servers": {
          "type": "array",
          "items": {
            "description": "servers",

```


ad/uids/{uid}/sids/

Endpoint

/v1/ad/uids/{uid}/sids/

GET

Return the SIDs for the given UID as found by issuing an AD query against the current domain the cluster is joined to.

Parameters

Name	Description	Required
uid	The UID to use to look up its SIDs	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

ad/usernames/{username}/objects/

Endpoint

/v1/ad/usernames/{username}/objects/

GET

Return any AD account objects that have the given sAMAccountName.

Parameters

Name	Description	Required
username	The sAMAccountName to use to look up AD users or groups.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "ad_ldap_object",
    "type": "object",
    "properties": {
      "dn": {
        "description": "dn",
        "type": "string"
      },
      "sid": {
        "description": "sid",
        "type": "string"
      },
      "uid": {
        "description": "uid",
        "type": "number"
      },
      "gid": {
```

```

    "description": "gid",
    "type": "number"
  },
  "name": {
    "description": "name",
    "type": "string"
  },
  "groups": {
    "type": "array",
    "items": {
      "description": "groups",
      "type": "string"
    }
  },
  "primary_group_sid": {
    "description": "primary_group_sid",
    "type": "string"
  },
  "classes": {
    "type": "array",
    "items": {
      "description": "classes",
      "type": "string"
    }
  }
}
}
}
}
}

```

ad/usernames/{username}/sids/

Endpoint

/v1/ad/usernames/{username}/sids/

GET

Return the SIDs for the given username as found by querying the domain controller for the domain the cluster is joined to.

Parameters

Name	Description	Required
username	The username to use to look up SIDs	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

analytics/activity/current

Endpoint

/v1/analytics/activity/current

GET

Returns the current sampled IOPS and throughput from the cluster.

Parameters

Name	Description	Required
type	Filters activity to a specific type. If not specified, all activity is returned.: * `file-iops-read` - file-iops-read, * `file-iops-write` - file-iops-write, * `file-throughput-read` - file-throughput-read, * `file-throughput-write` - file-throughput-write, * `metadata-iops-read` - metadata-iops-read, * `metadata-iops-write` - metadata-iops-write	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_rates",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "entries",
        "type": "object",
        "properties": {
          "id": {
            "description": "id",
            "type": "string"
          },
          "ip": {
```


analytics/capacity-history/

Endpoint

/v1/analytics/capacity-history/

GET

Returns capacity history data for the cluster. Does not return entries for timeslots without capacity data. Returned history data will be sorted by ascending time.

Parameters

Name	Description	Required
<code>begin-time</code>	Lower bound on history returned, in RFC 3339 format or epoch seconds.	Yes
<code>end-time</code>	Upper bound on history returned, in RFC 3339 format or epoch seconds. If not specified, defaults to the current system time.	No
<code>interval</code>	Sampling interval. If not specified, defaults to 'hourly': * `daily` - daily, * `hourly` - hourly, * `weekly` - weekly	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "overall_historical_capacity",
    "type": "object",
    "properties": {
      "period_start_time": {
        "description": "period_start_time",
        "type": "number"
      },
      "capacity_used": {
```

```

    "description": "capacity_used",
    "type": "string"
  },
  "data_used": {
    "description": "data_used",
    "type": "string"
  },
  "metadata_used": {
    "description": "metadata_used",
    "type": "string"
  },
  "snapshot_used": {
    "description": "snapshot_used",
    "type": "string"
  },
  "total_usable": {
    "description": "total_usable",
    "type": "string"
  },
  "details_status": {
    "type": "string",
    "enum": [
      "AVAILABLE",
      "UNAVAILABLE",
      "PENDING"
    ],
    "description": "details_status:\n * `AVAILABLE` - DETAILED_PATH_CAPACITY_AVAILABLE,\n * `PENDING` - DETAILED_PATH_CAPACITY_PENDING,\n * `UNAVAILABLE` - DETAILED_PATH_CAPACITY_UNAVAILABLE"
  }
}
}
}

```

analytics/capacity-history/{timestamp}/

Endpoint

/v1/analytics/capacity-history/{timestamp}/

GET

Returns all paths using more than 0.1% of overall used capacity at a given timestamp. A path that meets the threshold with many items smaller than the threshold will be aggregated. Individual items above the threshold will be reported separately.

Parameters

Name	Description	Required
<code>timestamp</code>	Time in epoch seconds	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "historical_capacity_details",
  "type": "object",
  "properties": {
    "threshold_for_inclusion": {
      "description": "threshold_for_inclusion",
      "type": "string"
    },
    "status": {
      "type": "string",
      "enum": [
        "AVAILABLE",
        "UNAVAILABLE",
        "PENDING"
      ],
      "description": "status:\n * `AVAILABLE` - DETAILED_PATH_CAPACITY_AVAILABLE,\n * `PENDING` - DETAILED_PATH_CAPACITY_PENDING,\n * `UNAVAILABLE` - DETAILED_PATH_CAPA"
    }
  }
}
```

```
CITY_UNAVAILABLE"
  },
  "largest_paths": {
    "type": "array",
    "items": {
      "description": "largest_paths",
      "type": "object",
      "properties": {
        "capacity_used": {
          "description": "capacity_used",
          "type": "string"
        },
        "path": {
          "description": "path",
          "type": "string"
        }
      }
    }
  }
}
```

analytics/time-series/

Endpoint

/v1/analytics/time-series/

GET

Returns all time series data maintained by the cluster.

Parameters

Name	Description	Required
<code>begin-time</code>	Lower bound on intervals returned, in RFC 3339 format or epoch seconds. If not specified, defaults to the current system time.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_time_series_dataset",
    "type": "object",
    "properties": {
      "id": {
        "description": "id",
        "type": "string"
      },
      "times": {
        "type": "array",
        "items": {
          "description": "times",
          "type": "number"
        }
      },
      "values": {
```

```
"type": "array",  
  "items": {  
    "description": "values",  
    "type": "number"  
  }  
}  
}  
}  
}
```

audit/cloudwatch/config

Endpoint

/v1/audit/cloudwatch/config

GET

Retrieves audit log CloudWatch configuration for the cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "cloudwatch_audit_user_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    },
    "log_group_name": {
      "description": "log_group_name",
      "type": "string"
    },
    "region": {
      "description": "region",
      "type": "string"
    }
  }
}
```

PUT

Sets audit log CloudWatch configuration for the cluster.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "cloudwatch_audit_user_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    },
    "log_group_name": {
      "description": "log_group_name",
      "type": "string"
    },
    "region": {
      "description": "region",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "cloudwatch_audit_user_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
```



```

    "type": "boolean"
  },
  "log_group_name": {
    "description": "log_group_name",
    "type": "string"
  },
  "region": {
    "description": "region",
    "type": "string"
  }
}
}

```

PATCH

Modifies audit log CloudWatch configuration for the cluster.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "cloudwatch_audit_user_config_delta",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    },
    "log_group_name": {
      "description": "log_group_name",
      "type": "string"
    },
    "region": {
      "description": "region",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "cloudwatch_audit_user_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    },
    "log_group_name": {
      "description": "log_group_name",
      "type": "string"
    },
    "region": {
      "description": "region",
      "type": "string"
    }
  }
}
```

audit/cloudwatch/status

Endpoint

/v1/audit/cloudwatch/status

GET

Retrieves audit log CloudWatch status for the cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "cloudwatch_audit_status",
  "type": "object",
  "properties": {
    "node_statuses": {
      "description": "node_statuses",
      "type": "object",
      "properties": {},
      "additionalProperties": {
        "description": "node_statuses value",
        "type": "object",
        "properties": {
          "last_seen_error": {
            "description": "last_seen_error",
            "type": "object",
            "properties": {
              "error_message": {
                "description": "error_message",
                "type": "string"
              }
            },
            "error_details": {
              "description": "error_details",
```

```
    "type": "string"  
  }  
}  
}  
}  
}  
}  
}  
}
```

audit/syslog/config

Endpoint

/v1/audit/syslog/config

GET

Retrieves audit log syslog configuration for the cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "syslog_audit_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Enable remote audit log.",
      "type": "boolean"
    },
    "server_address": {
      "description": "The IP address, hostname, or fully qualified domain name of your remote syslog server.",
      "type": "string"
    },
    "server_port": {
      "description": "server_port",
      "type": "number"
    },
    "local_enabled": {
      "description": "Enable per-node local audit log.",
      "type": "boolean"
    },
    "format": {
```

```

    "type": "string",
    "enum": [
        "csv",
        "json"
    ],
    "description": "Output syslog as CSV or JSON.:\\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\\n * `json` - SYSLOG_AUDIT_FORMAT_JSON"
  }
}
}

```

PUT

Modifies audit log syslog configuration for the cluster.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "syslog_audit_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Enable remote audit log.",
      "type": "boolean"
    },
    "server_address": {
      "description": "The IP address, hostname, or fully qualified domain name of your remote syslog server.",
      "type": "string"
    },
    "server_port": {
      "description": "server_port",
      "type": "number"
    },
    "local_enabled": {
      "description": "Enable per-node local audit log.",
      "type": "boolean"
    }
  }
}

```

```

    },
    "format": {
      "type": "string",
      "enum": [
        "csv",
        "json"
      ],
      "description": "Output syslog as CSV or JSON.:\\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\\n * `json` - SYSLOG_AUDIT_FORMAT_JSON"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "syslog_audit_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Enable remote audit log.",
      "type": "boolean"
    },
    "server_address": {
      "description": "The IP address, hostname, or fully qualified domain name of your remote syslog server.",
      "type": "string"
    },
    "server_port": {
      "description": "server_port",
      "type": "number"
    },
    "local_enabled": {
      "description": "Enable per-node local audit log.",
      "type": "boolean"
    },
    "format": {

```

```

    "type": "string",
    "enum": [
      "csv",
      "json"
    ],
    "description": "Output syslog as CSV or JSON.:\\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\\n * `json` - SYSLOG_AUDIT_FORMAT_JSON"
  }
}
}

```

PATCH

Modifies audit log syslog configuration for the cluster.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "syslog_audit_config_delta",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Enable remote audit log.",
      "type": "boolean"
    },
    "server_address": {
      "description": "The IP address, hostname, or fully qualified domain name of your remote syslog server.",
      "type": "string"
    },
    "server_port": {
      "description": "server_port",
      "type": "number"
    },
    "local_enabled": {
      "description": "Enable per-node local audit log.",
      "type": "boolean"
    }
  }
}

```



```

    },
    "format": {
      "type": "string",
      "enum": [
        "csv",
        "json"
      ],
      "description": "Output syslog as CSV or JSON.:\\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\\n * `json` - SYSLOG_AUDIT_FORMAT_JSON"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "syslog_audit_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Enable remote audit log.",
      "type": "boolean"
    },
    "server_address": {
      "description": "The IP address, hostname, or fully qualified domain name of your remote syslog server.",
      "type": "string"
    },
    "server_port": {
      "description": "server_port",
      "type": "number"
    },
    "local_enabled": {
      "description": "Enable per-node local audit log.",
      "type": "boolean"
    },
    "format": {

```

```
    "type": "string",
    "enum": [
      "csv",
      "json"
    ],
    "description": "Output syslog as CSV or JSON.:\\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\\n * `json` - SYSLOG_AUDIT_FORMAT_JSON"
  }
}
```

audit/syslog/status

Endpoint

/v1/audit/syslog/status

GET

Retrieves the syslog connection status of audit log.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "syslog_audit_log_status",
  "type": "object",
  "properties": {
    "connection_status": {
      "type": "string",
      "enum": [
        "AUDIT_LOG_CONNECTED",
        "AUDIT_LOG_CONNECTING",
        "AUDIT_LOG_DISABLED",
        "AUDIT_LOG_DISCONNECTED"
      ],
      "description": "The current connection status of the audit logger.\n * `AUDIT_LOG_CONNECTED` - AUDIT_LOG_CONNECTED,\n * `AUDIT_LOG_CONNECTING` - AUDIT_LOG_CONNECTING,\n * `AUDIT_LOG_DISABLED` - AUDIT_LOG_DISABLED,\n * `AUDIT_LOG_DISCONNECTED` - AUDIT_LOG_DISCONNECTED"
    },
    "error_message": {
      "description": "The current error, if audit is disconnected.",
      "type": "string"
    },
    "error_details": {
```

```
    "description": "Internal details for the current error, if audit is disconnected.",  
    "type": "string"  
  }  
}  
}
```

audit/destinations/

Endpoint

/v2/audit/destinations/

GET

Lists all audit log destinations.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_audit_destination_list",
  "type": "object",
  "properties": {
    "destinations": {
      "type": "array",
      "items": {
        "description": "destinations",
        "type": "object",
        "properties": {
          "id": {
            "description": "id",
            "type": "string"
          },
          "config": {
            "description": "config",
            "type": "object",
            "properties": {
              "type": {
                "type": "string",
                "enum": [
                  "SYSLOG"
                ]
              }
            }
          }
        }
      }
    }
  }
}
```


POST

Creates a new audit log destination.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_audit_destination_post",
  "type": "object",
  "properties": {
    "config": {
      "description": "config",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "SYSLOG",
            "CLOUDWATCH",
            "LOCAL"
          ],
          "description": "type:\n * `CLOUDWATCH` - AUDIT_DESTINATION_CLOUDWATCH,\n * `LOCAL` - AUDIT_DESTINATION_LOCAL,\n * `SYSLOG` - AUDIT_DESTINATION_SYSLOG"
        },
        "name": {
          "description": "name",
          "type": "string"
        },
        "enabled": {
          "description": "enabled",
          "type": "boolean"
        },
        "server_address": {
          "description": "server_address",
          "type": "string"
        },
        "server_port": {
          "description": "server_port",
          "type": "number"
        },
        "log_format": {
```

```

        "type": "string",
        "enum": [
            "csv",
            "json"
        ],
        "description": "log_format:\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\n * `json` - SYSLOG_AUDIT_FORMAT_JSON"
    },
    "log_group_name": {
        "description": "log_group_name",
        "type": "string"
    },
    "region": {
        "description": "region",
        "type": "string"
    }
}
}
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_audit_destination",
  "type": "object",
  "properties": {
    "id": {
      "description": "id",
      "type": "string"
    },
    "config": {
      "description": "config",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",

```



```

        "enum": [
            "SYSLOG",
            "CLOUDWATCH",
            "LOCAL"
        ],
        "description": "type:\n * `CLOUDWATCH` - AUDIT_DESTINATION_CLOUDWATCH,\n
* `LOCAL` - AUDIT_DESTINATION_LOCAL,\n * `SYSLOG` - AUDIT_DESTINATION_SYSLOG"
    },
    "name": {
        "description": "name",
        "type": "string"
    },
    "enabled": {
        "description": "enabled",
        "type": "boolean"
    },
    "server_address": {
        "description": "server_address",
        "type": "string"
    },
    "server_port": {
        "description": "server_port",
        "type": "number"
    },
    "log_format": {
        "type": "string",
        "enum": [
            "csv",
            "json"
        ],
        "description": "log_format:\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\n * `jso
n` - SYSLOG_AUDIT_FORMAT_JSON"
    },
    "log_group_name": {
        "description": "log_group_name",
        "type": "string"
    },
    "region": {
        "description": "region",
        "type": "string"
    }
}
}
}
}
}

```

audit/destinations/{id}

Endpoint

/v2/audit/destinations/{id}

GET

Retrieves the configuration for the specified audit log destination.

Parameters

Name	Description	Required
id	The audit log destination ID.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_audit_destination",
  "type": "object",
  "properties": {
    "id": {
      "description": "id",
      "type": "string"
    },
    "config": {
      "description": "config",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "SYSLOG",
            "CLOUDWATCH",
            "LOCAL"
          ]
        }
      }
    }
  }
}
```

```

        "description": "type:\n * `CLOUDWATCH` - AUDIT_DESTINATION_CLOUDWATCH,\n * `LOCAL` - AUDIT_DESTINATION_LOCAL,\n * `SYSLOG` - AUDIT_DESTINATION_SYSLOG"
    },
    "name": {
        "description": "name",
        "type": "string"
    },
    "enabled": {
        "description": "enabled",
        "type": "boolean"
    },
    "server_address": {
        "description": "server_address",
        "type": "string"
    },
    "server_port": {
        "description": "server_port",
        "type": "number"
    },
    "log_format": {
        "type": "string",
        "enum": [
            "csv",
            "json"
        ],
        "description": "log_format:\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\n * `json` - SYSLOG_AUDIT_FORMAT_JSON"
    },
    "log_group_name": {
        "description": "log_group_name",
        "type": "string"
    },
    "region": {
        "description": "region",
        "type": "string"
    }
}
}
}
}
}

```

PUT

Replaces the configuration for the specified audit log destination.

Parameters

Name	Description	Required
<code>id</code>	The audit log destination ID.	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_audit_destination_config",
  "type": "object",
  "properties": {
    "type": {
      "type": "string",
      "enum": [
        "SYSLOG",
        "CLOUDWATCH",
        "LOCAL"
      ],
      "description": "type:\n * `CLOUDWATCH` - AUDIT_DESTINATION_CLOUDWATCH,\n * `LOCAL` - AUDIT_DESTINATION_LOCAL,\n * `SYSLOG` - AUDIT_DESTINATION_SYSLOG"
    },
    "name": {
      "description": "name",
      "type": "string"
    },
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    },
    "server_address": {
      "description": "server_address",
      "type": "string"
    },
    "server_port": {
      "description": "server_port",
      "type": "number"
    },
    "log_format": {
      "type": "string",
      "enum": [
        "csv",

```

```

        "json"
    ],
    "description": "log_format:\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\n * `json` - SYSLOG_AUDIT_FORMAT_JSON"
  },
  "log_group_name": {
    "description": "log_group_name",
    "type": "string"
  },
  "region": {
    "description": "region",
    "type": "string"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_audit_destination",
  "type": "object",
  "properties": {
    "id": {
      "description": "id",
      "type": "string"
    },
    "config": {
      "description": "config",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "SYSLOG",
            "CLOUDWATCH",
            "LOCAL"
          ]
        }
      }
    }
  }
}

```

```
* `LOCAL` - AUDIT_DESTINATION_LOCAL,\n * `SYSLOG` - AUDIT_DESTINATION_SYSLOG"\n},\n  "name": {\n    "description": "name",\n    "type": "string"\n  },\n  "enabled": {\n    "description": "enabled",\n    "type": "boolean"\n  },\n  "server_address": {\n    "description": "server_address",\n    "type": "string"\n  },\n  "server_port": {\n    "description": "server_port",\n    "type": "number"\n  },\n  "log_format": {\n    "type": "string",\n    "enum": [\n      "csv",\n      "json"\n    ],\n    "description": "log_format:\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\n * `json` - SYSLOG_AUDIT_FORMAT_JSON"\n  },\n  "log_group_name": {\n    "description": "log_group_name",\n    "type": "string"\n  },\n  "region": {\n    "description": "region",\n    "type": "string"\n  }\n}\n}\n}
```

DELETE

Deletes the specified audit log destination.

Parameters

Name	Description	Required
<code>id</code>	The audit log destination ID.	Yes
<code>If-Match</code>	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

Modifies the configuration for the specified audit log destination.

Parameters

Name	Description	Required
<code>id</code>	The audit log destination ID.	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "audit_destination_config_delta",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_audit_destination",
  "type": "object",
  "properties": {
    "id": {
      "description": "id",
      "type": "string"
    },
    "config": {
      "description": "config",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "SYSLOG",
            "CLOUDWATCH",
            "LOCAL"
          ],
          "description": "type:\n * `CLOUDWATCH` - AUDIT_DESTINATION_CLOUDWATCH,\n * `LOCAL` - AUDIT_DESTINATION_LOCAL,\n * `SYSLOG` - AUDIT_DESTINATION_SYSLOG"
        },
        "name": {
          "description": "name",
          "type": "string"
        },
        "enabled": {
          "description": "enabled",
          "type": "boolean"
        },
        "server_address": {
          "description": "server_address",
          "type": "string"
        },
        "server_port": {
          "description": "server_port",
```



```

        "type": "number"
    },
    "log_format": {
        "type": "string",
        "enum": [
            "csv",
            "json"
        ],
        "description": "log_format:\n * `csv` - SYSLOG_AUDIT_FORMAT_CSV,\n * `json` - SYSLOG_AUDIT_FORMAT_JSON"
    },
    "log_group_name": {
        "description": "log_group_name",
        "type": "string"
    },
    "region": {
        "description": "region",
        "type": "string"
    }
}
}
}
}
}

```

audit/destinations/{id}/status

Endpoint

/v2/audit/destinations/{id}/status

GET

Retrieves the per-node connection status for the specified audit log destination.

Parameters

Name	Description	Required
id	The audit log destination ID.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "audit_destination_cluster_status",
  "type": "object",
  "properties": {
    "node_statuses": {
      "type": "array",
      "items": {
        "description": "node_statuses",
        "type": "object",
        "properties": {
          "node_id": {
            "description": "node_id",
            "type": "number"
          },
          "status": {
            "description": "status",
            "type": "object",
            "properties": {
              "connection_status": {
```


auth/auth-ids/{id}/related-identities/

Endpoint

/v1/auth/auth-ids/{id}/related-identities/

GET

Given an auth_id of any kind, return all related identities (equivalents in other domains, and containing groups). This API is deprecated in favor of /v1/identity/expand

Parameters

Name	Description	Required
id	The auth_id to expand to all its related identities.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_identity_v1",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ]
      },
    }
  },
}
```

```

        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
}
}

```

auth/clear-cache

Endpoint

/v1/auth/clear-cache

POST

Clear all cached authentication information.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

auth/identities/{id}/attributes

Endpoint

/v1/auth/identities/{id}/attributes

GET

Get the identity attributes for an identity.

Parameters

Name	Description	Required
id	URI parameter id	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "identity_attributes",
  "type": "object",
  "properties": {
    "home_directory": {
      "description": "home_directory",
      "type": "string"
    }
  }
}
```

PUT

Set the identity attributes for an identity.

Parameters

Name	Description	Required
------	-------------	----------

id	URI parameter id	Yes
----	------------------	-----

Request

Schema

```
{
  "description": "identity_attributes",
  "type": "object",
  "properties": {
    "home_directory": {
      "description": "home_directory",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "identity_attributes",
  "type": "object",
  "properties": {
    "home_directory": {
      "description": "home_directory",
      "type": "string"
    }
  }
}
```

DELETE

Delete the identity attributes for an identity.

Parameters

Name	Description	Required
id	URI parameter id	Yes

Response

Codes

Code	Description
200	Return value on success

auth/identity/expand

Endpoint

/v1/auth/identity/expand

POST

Find all equivalents and the group membership of the given identity. This API is deprecated in favor of /v1/identity/expand

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_id_to_expand",
  "type": "object",
  "properties": {
    "id": {
      "description": "The identity to expand.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ],
          "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NUL
```

```

L_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_D
OMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAI
N,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_US
ER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  }
},
"equivalent_ids": {
  "type": "array",
  "items": {
    "description": "Additional identities that should be considered equivalent,
and also expanded.",
    "type": "object",
    "properties": {
      "domain": {
        "type": "string",
        "enum": [
          "LOCAL",
          "API_NULL_DOMAIN",
          "WORLD",
          "POSIX_USER",
          "POSIX_GROUP",
          "ACTIVE_DIRECTORY",
          "API_INVALID_DOMAIN",
          "API_RESERVED_DOMAIN",
          "API_INTERNAL_DOMAIN",

```

```

        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n *
`API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNA
L_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - AP
I_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPP
ORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DO
MAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSI
X_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"group_ids": {
    "type": "array",
    "items": {
        "description": "Additional groups that the id should be considered a member
of, and also expanded.",
        "type": "object",
        "properties": {
            "domain": {
                "type": "string",
                "enum": [
                    "LOCAL",

```


Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_expanded_id",
  "type": "object",
  "properties": {
    "id": {
      "description": "The identity that was expanded.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ],
          "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
        },
        "auth_id": {
          "description": "auth_id",
          "type": "string"
        }
      }
    }
  }
}
```

```

    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  },
  "type": {
    "type": "string",
    "enum": [
      "UNKNOWN",
      "USER",
      "GROUP"
    ],
    "description": "Whether the expanded identity is a user, group, or indeterminate.\n * `GROUP` - RESOLVED_ID_IS_GROUP,\n * `UNKNOWN` - RESOLVED_ID_IS_UNKNOWN,\n * `USER` - RESOLVED_ID_IS_USER"
  },
  "smb_id": {
    "description": "The equivalent identity that would be shown to SMB clients.",
    "type": "object",
    "properties": {
      "domain": {
        "type": "string",
        "enum": [
          "LOCAL",
          "API_NULL_DOMAIN",
          "WORLD",
          "POSIX_USER",
          "POSIX_GROUP",
          "ACTIVE_DIRECTORY",
          "API_INVALID_DOMAIN",
          "API_RESERVED_DOMAIN",
          "API_INTERNAL_DOMAIN",
          "API_OPERATOR_DOMAIN",

```

```

        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
    }
},
"nfs_id": {
    "description": "The equivalent identity that would be shown to NFS clients.",
    "type": "object",
    "properties": {
        "domain": {
            "type": "string",
            "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",

```



```

        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
    },
    "equivalent_ids": {
        "type": "array",
        "items": {
            "description": "Identities that are the same as the expanded ID, and which have the same rights.",
            "type": "object",
            "properties": {
                "domain": {
                    "type": "string",

```

```

    "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n *
`API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNA
L_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - AP
I_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPP
ORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DO
MAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSI
X_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"group_ids": {

```

```

"type": "array",
"items": {
  "description": "Groups that the expanded ID is a member of.",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n *  

`API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNA  

L_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - AP  

I_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPP  

ORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DO  

MAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSI  

X_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {

```

```
        "description": "name",  
        "type": "string"  
    }  
    }  
    }  
    }  
}
```

auth/identity/find

Endpoint

/v1/auth/identity/find

POST

Search for identity and expand all fields. This API is deprecated in favor of /v1/identity/find

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_identity",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
```

```

    "description": "auth_id",
    "type": "string"
  },
  "uid": {
    "description": "uid",
    "type": "number"
  },
  "gid": {
    "description": "gid",
    "type": "number"
  },
  "sid": {
    "description": "sid",
    "type": "string"
  },
  "name": {
    "description": "name",
    "type": "string"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_identity",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",

```

```

        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CR
EATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAI
N,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_D
OMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMA
IN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n
 * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USE
R,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
}

```

auth/kerberos-keytab

Endpoint

/v1/auth/kerberos-keytab

GET

Get the entries from the current keytab configuration

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "kerberos_keytab",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "entries",
        "type": "object",
        "properties": {
          "principal": {
            "description": "principal",
            "type": "string"
          },
          "version": {
            "description": "version",
            "type": "number"
          },
          "enctype": {
            "type": "string",
            "enum": [
              "KERBEROS_ENCRYPTION_TYPE_NULL",

```



```

"KERBEROS_ENCRYPTION_TYPE_DES_CBC_CRC",
"KERBEROS_ENCRYPTION_TYPE_DES_CBC_MD4",
"KERBEROS_ENCRYPTION_TYPE_DES_CBC_MD5",
"KERBEROS_ENCRYPTION_TYPE_DES3_CBC_MD5",
"KERBEROS_ENCRYPTION_TYPE_OLD_DES3_CBC_SHA1",
"KERBEROS_ENCRYPTION_TYPE_SIGN_DSA_GENERATE",
"KERBEROS_ENCRYPTION_TYPE_ENCRYPT_RSA_PRIV",
"KERBEROS_ENCRYPTION_TYPE_ENCRYPT_RSA_PUB",
"KERBEROS_ENCRYPTION_TYPE_DES3_CBC_SHA1",
"KERBEROS_ENCRYPTION_TYPE_AES128_CTS_HMAC_SHA1_96",
"KERBEROS_ENCRYPTION_TYPE_AES256_CTS_HMAC_SHA1_96",
"KERBEROS_ENCRYPTION_TYPE_AES128_CTS_HMAC_SHA256_128",
"KERBEROS_ENCRYPTION_TYPE_AES256_CTS_HMAC_SHA384_192",
"KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_MD5",
"KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_MD5_56",
"KERBEROS_ENCRYPTION_TYPE_ENCTYPE_PK_CROSS",
"KERBEROS_ENCRYPTION_TYPE_ARCFOUR_MD4",
"KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_OLD",
"KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_OLD_EXP",
"KERBEROS_ENCRYPTION_TYPE_DES_CBC_NONE",
"KERBEROS_ENCRYPTION_TYPE_DES3_CBC_NONE",
"KERBEROS_ENCRYPTION_TYPE_DES_CFB64_NONE",
"KERBEROS_ENCRYPTION_TYPE_DES_PCBC_NONE",
"KERBEROS_ENCRYPTION_TYPE_DIGEST_MD5_NONE",
"KERBEROS_ENCRYPTION_TYPE_CRAM_MD5_NONE"

```

```
],
```

```

"description": "enctype:\n * `KERBEROS_ENCRYPTION_TYPE_AES128_CTS_HMAC_S
HA1_96` - KERBEROS_ENCRYPTION_TYPE_AES128_CTS_HMAC_SHA1_96,\n * `KERBEROS_ENCRYPTIO
N_TYPE_AES128_CTS_HMAC_SHA256_128` - KERBEROS_ENCRYPTION_TYPE_AES128_CTS_HMAC_SHA25
6_128,\n * `KERBEROS_ENCRYPTION_TYPE_AES256_CTS_HMAC_SHA1_96` - KERBEROS_ENCRYPTIO
N_TYPE_AES256_CTS_HMAC_SHA1_96,\n * `KERBEROS_ENCRYPTION_TYPE_AES256_CTS_HMAC_SHA38
4_192` - KERBEROS_ENCRYPTION_TYPE_AES256_CTS_HMAC_SHA384_192,\n * `KERBEROS_ENCRYPTI
ON_TYPE_ARCFOUR_HMAC_MD5` - KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_MD5,\n * `KERBERO
S_ENCRYPTION_TYPE_ARCFOUR_HMAC_MD5_56` - KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_MD5_5
6,\n * `KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_OLD` - KERBEROS_ENCRYPTION_TYPE_ARCFOU
R_HMAC_OLD,\n * `KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_OLD_EXP` - KERBEROS_ENCRYPTIO
N_TYPE_ARCFOUR_HMAC_OLD_EXP,\n * `KERBEROS_ENCRYPTION_TYPE_ARCFOUR_MD4` - KERBEROS_E
NCRYPTION_TYPE_ARCFOUR_MD4,\n * `KERBEROS_ENCRYPTION_TYPE_CRAM_MD5_NONE` - KERBERO
S_ENCRYPTION_TYPE_CRAM_MD5_NONE,\n * `KERBEROS_ENCRYPTION_TYPE_DES3_CBC_MD5` - KERBE
ROS_ENCRYPTION_TYPE_DES3_CBC_MD5,\n * `KERBEROS_ENCRYPTION_TYPE_DES3_CBC_NONE` - KER
BEROS_ENCRYPTION_TYPE_DES3_CBC_NONE,\n * `KERBEROS_ENCRYPTION_TYPE_DES3_CBC_SHA1` -
KERBEROS_ENCRYPTION_TYPE_DES3_CBC_SHA1,\n * `KERBEROS_ENCRYPTION_TYPE_DES_CBC_CRC`
- KERBEROS_ENCRYPTION_TYPE_DES_CBC_CRC,\n * `KERBEROS_ENCRYPTION_TYPE_DES_CBC_MD4`
- KERBEROS_ENCRYPTION_TYPE_DES_CBC_MD4,\n * `KERBEROS_ENCRYPTION_TYPE_DES_CBC_MD5`
- KERBEROS_ENCRYPTION_TYPE_DES_CBC_MD5,\n * `KERBEROS_ENCRYPTION_TYPE_DES_CBC_NONE`
- KERBEROS_ENCRYPTION_TYPE_DES_CBC_NONE,\n * `KERBEROS_ENCRYPTION_TYPE_DES_CFB64_NON

```

```
E` - KERBEROS_ENCRYPTION_TYPE_DES_CFB64_NONE,\n * `KERBEROS_ENCRYPTION_TYPE_DES_PCBC_NONE` - KERBEROS_ENCRYPTION_TYPE_DES_PCBC_NONE,\n * `KERBEROS_ENCRYPTION_TYPE_DIGEST_MD5_NONE` - KERBEROS_ENCRYPTION_TYPE_DIGEST_MD5_NONE,\n * `KERBEROS_ENCRYPTION_TYPE_ENCRYPT_RSA_PRIV` - KERBEROS_ENCRYPTION_TYPE_ENCRYPT_RSA_PRIV,\n * `KERBEROS_ENCRYPTION_TYPE_ENCRYPT_RSA_PUB` - KERBEROS_ENCRYPTION_TYPE_ENCRYPT_RSA_PUB,\n * `KERBEROS_ENCRYPTION_TYPE_ENCTYPE_PK_CROSS` - KERBEROS_ENCRYPTION_TYPE_ENCTYPE_PK_CROSS,\n * `KERBEROS_ENCRYPTION_TYPE_NULL` - KERBEROS_ENCRYPTION_TYPE_NULL,\n * `KERBEROS_ENCRYPTION_TYPE_OLD_DES3_CBC_SHA1` - KERBEROS_ENCRYPTION_TYPE_OLD_DES3_CBC_SHA1,\n * `KERBEROS_ENCRYPTION_TYPE_SIGN_DSA_GENERATE` - KERBEROS_ENCRYPTION_TYPE_SIGN_DSA_GENERATE"

    },
    "key": {
      "description": "key",
      "type": "string"
    }
  }
}
}
}
}
```

PUT

Set the Kerberos keytab from a generated keytab file. This API also accepts a kerberos keytab in the JSON form returned by the corresponding GET request.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "type": "object"
}
```

Response

Codes

Code	Description
------	-------------

200	Return value on success
-----	-------------------------

Schema

```
{
  "description": "kerberos_keytab",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "entries",
        "type": "object",
        "properties": {
          "principal": {
            "description": "principal",
            "type": "string"
          },
          "version": {
            "description": "version",
            "type": "number"
          },
          "enctype": {
            "type": "string",
            "enum": [
              "KERBEROS_ENCRYPTION_TYPE_NULL",
              "KERBEROS_ENCRYPTION_TYPE_DES_CBC_CRC",
              "KERBEROS_ENCRYPTION_TYPE_DES_CBC_MD4",
              "KERBEROS_ENCRYPTION_TYPE_DES_CBC_MD5",
              "KERBEROS_ENCRYPTION_TYPE_DES3_CBC_MD5",
              "KERBEROS_ENCRYPTION_TYPE_OLD_DES3_CBC_SHA1",
              "KERBEROS_ENCRYPTION_TYPE_SIGN_DSA_GENERATE",
              "KERBEROS_ENCRYPTION_TYPE_ENCRYPT_RSA_PRIV",
              "KERBEROS_ENCRYPTION_TYPE_ENCRYPT_RSA_PUB",
              "KERBEROS_ENCRYPTION_TYPE_DES3_CBC_SHA1",
              "KERBEROS_ENCRYPTION_TYPE_AES128_CTS_HMAC_SHA1_96",
              "KERBEROS_ENCRYPTION_TYPE_AES256_CTS_HMAC_SHA1_96",
              "KERBEROS_ENCRYPTION_TYPE_AES128_CTS_HMAC_SHA256_128",
              "KERBEROS_ENCRYPTION_TYPE_AES256_CTS_HMAC_SHA384_192",
              "KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_MD5",
              "KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_MD5_56",
              "KERBEROS_ENCRYPTION_TYPE_ENCTYPE_PK_CROSS",
              "KERBEROS_ENCRYPTION_TYPE_ARCFOUR_MD4",
              "KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_OLD",
              "KERBEROS_ENCRYPTION_TYPE_ARCFOUR_HMAC_OLD_EXP",
            ]
          }
        }
      }
    }
  }
}
```



```
}
```

DELETE

Delete the current Kerberos keytab configuration

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

auth/kerberos-settings

Endpoint

/v1/auth/kerberos-settings

GET

Get the Kerberos settings

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "kerberos_config",
  "type": "object",
  "properties": {
    "use_alt_security_identities_mapping": {
      "description": "use_alt_security_identities_mapping",
      "type": "boolean"
    }
  }
}
```

PUT

Set the Kerberos settings

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "kerberos_config",
  "type": "object",
  "properties": {
    "use_alt_security_identities_mapping": {
      "description": "use_alt_security_identities_mapping",
      "type": "boolean"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "kerberos_config",
  "type": "object",
  "properties": {
    "use_alt_security_identities_mapping": {
      "description": "use_alt_security_identities_mapping",
      "type": "boolean"
    }
  }
}
```

auth/local-username/{username}/related-identities/

Endpoint

`/v1/auth/local-username/{username}/related-identities/`

GET

Given a local username, return all related identities (equivalents in other domains, and containing groups). This API is deprecated in favor of `/v1/identity/expand`

Parameters

Name	Description	Required
<code>username</code>	The local username to expand.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_identity_v1",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",

```



```

        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
  },
  "id_value": {
    "description": "id_value",
    "type": "string"
  }
}
}
}

```

auth/posix-gids/{id}/related-identities/

Endpoint

/v1/auth/posix-gids/{id}/related-identities/

GET

Given a POSIX GID, return all related identities (equivalents in other domains, and containing groups). This API is deprecated in favor of /v1/identity/expand

Parameters

Name	Description	Required
id	The POSIX GID to expand.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_identity_v1",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ]
      },
    }
  },
}
```

```

        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
}
}

```

auth/posix-uids/{id}/related-identities/

Endpoint

/v1/auth/posix-uids/{id}/related-identities/

GET

Given a POSIX UID, return all related identities (equivalents in other domains, and containing groups). This API is deprecated in favor of /v1/identity/expand

Parameters

Name	Description	Required
id	The POSIX UID to expand.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_identity_v1",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ]
      }
    }
  }
}
```

```

        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
}
}

```

auth/sids/{id}/related-identities/

Endpoint

/v1/auth/sids/{id}/related-identities/

GET

Given a Windows NT Security Identifier, return all related identities (equivalents in other domains, and containing groups). This API is deprecated in favor of /v1/identity/expand

Parameters

Name	Description	Required
id	The Windows NT security identifier to expand.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_identity_v1",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ]
      }
    }
  }
}
```

```

        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
}
}

```

auth/user-defined-mappings/

Endpoint

/v1/auth/user-defined-mappings/

GET

Get the configured set of AD/LDAP static user defined mappings.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "user_equivalence",
    "type": "object",
    "properties": {
      "down_level_logon_name": {
        "description": "down_level_logon_name",
        "type": "string"
      },
      "ldap_name": {
        "description": "ldap_name",
        "type": "string"
      }
    }
  }
}
```

PUT

Replace the configured set of AD/LDAP static user defined mappings with the supplied set.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "type": "array",
  "items": {
    "description": "user_equivalence",
    "type": "object",
    "properties": {
      "down_level_logon_name": {
        "description": "down_level_logon_name",
        "type": "string"
      },
      "ldap_name": {
        "description": "ldap_name",
        "type": "string"
      }
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "user_equivalence",
    "type": "object",
    "properties": {
      "down_level_logon_name": {
```

```
    "description": "down_level_logon_name",
    "type": "string"
  },
  "ldap_name": {
    "description": "ldap_name",
    "type": "string"
  }
}
```

authoritative-dns/settings

Endpoint

/v1/authoritative-dns/settings

GET

Retrieve current Authoritative DNS Configuration

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "authoritative_dns_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    },
    "fqdn": {
      "description": "fqdn",
      "type": "string"
    },
    "host_restrictions": {
      "description": "host_restrictions",
      "type": "string"
    }
  }
}
```

PATCH

Modify current Authoritative DNS configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_authoritative_dns_config_patch",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    },
    "fqdn": {
      "description": "fqdn",
      "type": "string"
    },
    "host_restrictions": {
      "description": "host_restrictions",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "authoritative_dns_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
```

```
    "type": "boolean"
  },
  "fqdn": {
    "description": "fqdn",
    "type": "string"
  },
  "host_restrictions": {
    "description": "host_restrictions",
    "type": "string"
  }
}
```

capacity/clamp

Endpoint

/v1/capacity/clamp

GET

Retrieve the capacity clamp value in bytes. You can set this value by using a PUT API call or as an argument to the cluster creation API. The cluster uses this value to determine the maximum capacity that it can provision, regardless of the maximum capacity of the underlying storage.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_capacity_clamp",
  "type": "object",
  "properties": {
    "capacity_clamp": {
      "description": "The value, in bytes, to clamp usable capacity to",
      "type": "string"
    }
  }
}
```

PUT

Specify the capacity clamp value in bytes. This value limits maximum provisioned capacity. The actual provisioned space is limited to the maximum capacity of the underlying storage. In addition, the actual provisioned space is close to the requested value in bytes, without exceeding it. If the system applies this value successfully, it abandons quorum and allocates storage capacity in a new quorum.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_capacity_clamp",
  "type": "object",
  "properties": {
    "capacity_clamp": {
      "description": "The value, in bytes, to clamp usable capacity to",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

portal/file-systems/

Endpoint

/v1/portal/file-systems/

GET

Retrieve portal information for all file systems.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "v1_portal_fs_info",
    "type": "object",
    "properties": {
      "uuid": {
        "description": "File System UUID",
        "type": "string"
      },
      "usage_bytes": {
        "description": "Capacity used by portal data in bytes",
        "type": "string"
      }
    }
  }
}
```


portal/file-systems/{id}

Endpoint

/v1/portal/file-systems/{id}

GET

Retrieve portal information for a file system.

Parameters

Name	Description	Required
id	File System UUID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v1_portal_fs_info",
  "type": "object",
  "properties": {
    "uuid": {
      "description": "File System UUID",
      "type": "string"
    },
    "usage_bytes": {
      "description": "Capacity used by portal data in bytes",
      "type": "string"
    }
  }
}
```

portal/files/{file_id}/evict

Endpoint

/v1/portal/files/{file_id}/evict

POST

Reclaim all cluster capacity used by the targeted file or directory. This does not affect children of a targeted directory.

Parameters

Name	Description	Required
<code>file_id</code>	File or Directory ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v1_portal_eviction_result",
  "type": "object",
  "properties": {
    "evicted_blocks": {
      "description": "Number of 4096 byte blocks that have been freed. It can be less than requested and even 0 if no eviction was possible. The cluster's reported free capacity may take time to reflect the eviction.",
      "type": "string"
    }
  }
}
```

portal/ping

Endpoint

/v1/portal/ping

POST

[preview] Returns a connectivity report for each node to each provided remote host.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "v1_portal_ping_request",
  "type": "object",
  "properties": {
    "hosts": {
      "type": "array",
      "items": {
        "description": "IP addresses and TCP ports of nodes in the remote cluster",
        "type": "object",
        "properties": {
          "address": {
            "description": "address",
            "type": "string"
          },
          "port": {
            "description": "port",
            "type": "number"
          }
        }
      }
    },
    "peer_uuid": {
      "description": "Optional UUID of the peer cluster for verification",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v1_portal_ping_result",
  "type": "object",
  "properties": {
    "results": {
      "type": "array",
      "items": {
        "description": "results",
        "type": "object",
        "properties": {
          "node": {
            "description": "Node that attempted the connection",
            "type": "number"
          },
          "host": {
            "description": "Remote host that was tested",
            "type": "object",
            "properties": {
              "address": {
                "description": "address",
                "type": "string"
              },
              "port": {
                "description": "port",
                "type": "number"
              }
            }
          },
          "unreachable_reason": {
            "description": "Error message if connection failed, empty if successful",
            "type": "string"
          }
        }
      }
    }
  }
}
```

```
}  
}
```

portal/quorum/events

Endpoint

/v1/portal/quorum/events

GET

List recent portal quorum success and abandon events recorded by the nodes of this cluster, oldest first. Success events are recorded by the cluster quorum leader; abandon events are recorded by each node that observed a reason for the abandon. History is bounded by event log rotation; roughly the trailing 24 hours are available.

Parameters

Name	Description	Required
<code>begin-time</code>	Inclusive lower bound on event time, in RFC 3339 format or epoch seconds. If not specified, all available history is returned.	No
<code>end-time</code>	Exclusive upper bound on event time, in RFC 3339 format or epoch seconds. If not specified, defaults to the current system time.	No
<code>type</code>	Only return events of this kind: success or abandon.: * `abandon` - abandon, * `success` - success	No
<code>node-id</code>	Only return events recorded by this node.	No
<code>fs-id</code>	Only return events for this file system.	No
<code>limit</code>	Maximum entries returned, oldest first. Defaults to 1000.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
```

```

"description": "v1_portal_quorum_events",
"type": "object",
"properties": {
  "entries": {
    "type": "array",
    "items": {
      "description": "Matching events from all queried nodes, oldest first",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "success",
            "abandon"
          ],
          "description": "Event kind: success (portal quorum formed) or abandon\n:\n * `abandon` - PORTAL_QUORUM_EVENT_KIND_ABANDON,\n * `success` - PORTAL_QUORUM_EVENT_KIND_SUCCESS"
        },
        "node_id": {
          "description": "Node that recorded the event",
          "type": "number"
        },
        "event_time": {
          "description": "When the node recorded the event",
          "type": "string"
        },
        "portal_quorum_id": {
          "description": "portal_quorum_id",
          "type": "object",
          "properties": {
            "portal_quorum_seq": {
              "description": "portal_quorum_seq",
              "type": "string"
            }
          }
        },
        "fs_id": {
          "description": "File system the portal quorum serves",
          "type": "number"
        },
        "total_clusters": {
          "description": "Total clusters this node knows about, in quorum or not",
          "type": "number"
        },
        "missing_clusters": {

```

```

        "type": "array",
        "items": {
            "description": "Cluster UUIDs missing from the portal quorum",
            "type": "string"
        }
    },
    "end_reason": {
        "description": "Why the portal quorum was abandoned; abandon events only",
        "type": "string"
    },
    "uptime": {
        "description": "Seconds the portal quorum was active; abandon events only",
        "type": "number"
    },
    "downtime": {
        "description": "Seconds since the previous portal quorum abandoned; success events only",
        "type": "number"
    },
    "formation_time": {
        "description": "Seconds this node spent starting; success events only",
        "type": "number"
    }
}
},
"nodes_queried": {
    "type": "array",
    "items": {
        "description": "Nodes whose event logs contributed; nodes outside cluster quorum are absent and their events are unavailable until they rejoin",
        "type": "number"
    }
}
}
}

```


portal/spokes/eviction-settings

Endpoint

/v1/portal/spokes/eviction-settings

GET

Retrieve the configuration for recovering cluster capacity by removing cached data automatically.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v1_portal_eviction_settings",
  "type": "object",
  "properties": {
    "free_threshold": {
      "description": "Fraction of free total cluster capacity that the system will try to maintain by evicting cached spoke portal data, in the range [0.0, 1.0]. Default is 0.15, 0.0 means no eviction, 1.0 means always evict.",
      "type": "number"
    }
  }
}
```

PUT

Overwrite the configuration for recovering cluster capacity by removing cached data automatically.

Parameters

Name	Description	Required
------	-------------	----------

If-Match	ETag for expected version	No
----------	---------------------------	----

Request

Schema

```
{
  "description": "v1_portal_eviction_settings",
  "type": "object",
  "properties": {
    "free_threshold": {
      "description": "Fraction of free total cluster capacity that the system will try to maintain by evicting cached spoke portal data, in the range [0.0, 1.0]. Default is 0.15, 0.0 means no eviction, 1.0 means always evict.",
      "type": "number"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v1_portal_eviction_settings",
  "type": "object",
  "properties": {
    "free_threshold": {
      "description": "Fraction of free total cluster capacity that the system will try to maintain by evicting cached spoke portal data, in the range [0.0, 1.0]. Default is 0.15, 0.0 means no eviction, 1.0 means always evict.",
      "type": "number"
    }
  }
}
```

PATCH

Change the configuration for recovering cluster capacity by removing cached data automatically.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "v1_portal_eviction_settings",
  "type": "object",
  "properties": {
    "free_threshold": {
      "description": "Fraction of free total cluster capacity that the system will try to maintain by evicting cached spoke portal data, in the range [0.0, 1.0]. Default is 0.15, 0.0 means no eviction, 1.0 means always evict.",
      "type": "number"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v1_portal_eviction_settings",
  "type": "object",
  "properties": {
    "free_threshold": {
      "description": "Fraction of free total cluster capacity that the system will try to maintain by evicting cached spoke portal data, in the range [0.0, 1.0]. Default is 0.15, 0.0 means no eviction, 1.0 means always evict.",
      "type": "number"
    }
  }
}
```

portal/hubs/

Endpoint

/v2/portal/hubs/

GET

List the relationship status and configuration for all hub portals on the current cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v2_portal_hubs",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of hub portals",
        "type": "object",
        "properties": {
          "id": {
            "description": "Hub portal ID",
            "type": "number"
          },
          "type": {
            "type": "string",
            "enum": [
              "PORTAL_READ_ONLY",
              "PORTAL_READ_WRITE"
            ],
            "description": "Type of the portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
          }
        }
      }
    }
  }
}
```

```

    },
    "state": {
      "type": "string",
      "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
      ],
      "description": "State of the portal:\n * `ACCEPTED` - A portal that is i
n an active relationship.,\n * `DELETING` - A portal in the process of synchronizin
g outstanding changes before deletion.,\n * `PENDING` - A portal not yet in an activ
e relationship."
    },
    "status": {
      "type": "string",
      "enum": [
        "INACTIVE",
        "ACTIVE",
        "DEGRADED"
      ],
      "description": "Status of the portal:\n * `ACTIVE` - A fully connected p
ortal ready for use.,\n * `DEGRADED` - A portal missing one or more connections wit
h the other cluster in the relationship.,\n * `INACTIVE` - A portal that is not read
y for use."
    },
    "spoke_hosts": {
      "type": "array",
      "items": {
        "description": "IP addresses and TCP ports of nodes in the remote clus
ter",
        "type": "object",
        "properties": {
          "address": {
            "description": "address",
            "type": "string"
          },
          "port": {
            "description": "port",
            "type": "number"
          }
        }
      }
    },
    "spoke_cluster_uuid": {
      "description": "UUID of the cluster with the spoke portal",
      "type": "string"
    }
  }
}

```

```

    },
    "spoke_cluster_name": {
      "description": "Name of the cluster with the spoke portal",
      "type": "string"
    },
    "pending_roots": {
      "type": "array",
      "items": {
        "description": "Set of hub root directories that are pending authoriza
tion",
        "type": "string"
      }
    },
    "authorized_roots": {
      "type": "array",
      "items": {
        "description": "Set of hub root directories that are authorized for ac
cess",
        "type": "string"
      }
    }
  }
}

```

portal/hubs/{id}

Endpoint

/v2/portal/hubs/{id}

GET

Retrieve the relationship status and configuration for the specified hub portal.

Parameters

Name	Description	Required
id	Portal ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v2_portal_hub",
  "type": "object",
  "properties": {
    "id": {
      "description": "Hub portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "state": {
      "type": "string",
```

```

    "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
    ],
    "description": "State of the portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relationship."
},
"status": {
    "type": "string",
    "enum": [
        "INACTIVE",
        "ACTIVE",
        "DEGRADED"
    ],
    "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal ready for use,\n * `DEGRADED` - A portal missing one or more connections with the other cluster in the relationship,\n * `INACTIVE` - A portal that is not ready for use."
},
"spoke_hosts": {
    "type": "array",
    "items": {
        "description": "IP addresses and TCP ports of nodes in the remote cluster",
        "type": "object",
        "properties": {
            "address": {
                "description": "address",
                "type": "string"
            },
            "port": {
                "description": "port",
                "type": "number"
            }
        }
    }
},
"spoke_cluster_uuid": {
    "description": "UUID of the cluster with the spoke portal",
    "type": "string"
},
"spoke_cluster_name": {
    "description": "Name of the cluster with the spoke portal",
    "type": "string"
}

```



```

    },
    "pending_roots": {
      "type": "array",
      "items": {
        "description": "Set of hub root directories that are pending authorization",
        "type": "string"
      }
    },
    "authorized_roots": {
      "type": "array",
      "items": {
        "description": "Set of hub root directories that are authorized for access",
        "type": "string"
      }
    }
  }
}

```

DELETE

Delete the specified hub portal from the current cluster.

Parameters

Name	Description	Required
<code>id</code>	Portal ID	Yes
<code>force</code>		No

Response

Codes

Code	Description
202	Return value on success

PATCH

Change the spoke hosts or the type of the specified hub portal. The portal must be accepted, and PORTAL_READ_WRITE is the only type that may be set.

Parameters

Name	Description	Required
------	-------------	----------

id	Portal ID	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "v2_portal_hub_patch",
  "type": "object",
  "properties": {
    "id": {
      "description": "Hub portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "state": {
      "type": "string",
      "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
      ],
      "description": "State of the portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relationship."
    },
    "status": {
      "type": "string",
      "enum": [
        "INACTIVE",
        "ACTIVE",
        "DEGRADED"
      ],
      "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal ready for use,\n * `DEGRADED` - A portal missing one or more connections with the o"
    }
  }
}
```

ther cluster in the relationship.,\n * `INACTIVE` - A portal that is not ready for use."

```
{
  },
  "spoke_hosts": {
    "type": "array",
    "items": {
      "description": "IP addresses and TCP ports of nodes in the remote cluster",
      "type": "object",
      "properties": {
        "address": {
          "description": "address",
          "type": "string"
        },
        "port": {
          "description": "port",
          "type": "number"
        }
      }
    }
  },
  "spoke_cluster_uuid": {
    "description": "UUID of the cluster with the spoke portal",
    "type": "string"
  },
  "spoke_cluster_name": {
    "description": "Name of the cluster with the spoke portal",
    "type": "string"
  },
  "pending_roots": {
    "type": "array",
    "items": {
      "description": "Set of hub root directories that are pending authorization",
      "type": "string"
    }
  },
  "authorized_roots": {
    "type": "array",
    "items": {
      "description": "Set of hub root directories that are authorized for access",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v2_portal_hub",
  "type": "object",
  "properties": {
    "id": {
      "description": "Hub portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "state": {
      "type": "string",
      "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
      ],
      "description": "State of the portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relationship."
    },
    "status": {
      "type": "string",
      "enum": [
        "INACTIVE",
        "ACTIVE",
        "DEGRADED"
      ],
    },
  },
}
```

```

    "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal
ready for use.,\n * `DEGRADED` - A portal missing one or more connections with the o
ther cluster in the relationship.,\n * `INACTIVE` - A portal that is not ready for u
se."
  },
  "spoke_hosts": {
    "type": "array",
    "items": {
      "description": "IP addresses and TCP ports of nodes in the remote cluster",
      "type": "object",
      "properties": {
        "address": {
          "description": "address",
          "type": "string"
        },
        "port": {
          "description": "port",
          "type": "number"
        }
      }
    }
  },
  "spoke_cluster_uuid": {
    "description": "UUID of the cluster with the spoke portal",
    "type": "string"
  },
  "spoke_cluster_name": {
    "description": "Name of the cluster with the spoke portal",
    "type": "string"
  },
  "pending_roots": {
    "type": "array",
    "items": {
      "description": "Set of hub root directories that are pending authorization",
      "type": "string"
    }
  },
  "authorized_roots": {
    "type": "array",
    "items": {
      "description": "Set of hub root directories that are authorized for access",
      "type": "string"
    }
  }
}

```

portal/hubs/{id}/accept

Endpoint

/v2/portal/hubs/{id}/accept

POST

Accept the specified pending hub portal. Accepting a hub portal establishes a relationship with a spoke portal but does not provide data access.

Parameters

Name	Description	Required
id	Portal ID	Yes

Request

Schema

```
{
  "description": "v2_portal_accept_request",
  "type": "object",
  "properties": {
    "spoke_hosts": {
      "type": "array",
      "items": {
        "description": "IP addresses and TCP ports of nodes in the cluster that prop
osed the portal relationship",
        "type": "object",
        "properties": {
          "address": {
            "description": "address",
            "type": "string"
          },
          "port": {
            "description": "port",
            "type": "number"
          }
        }
      }
    }
  },
  "authorized_roots": {
    "type": "array",
  }
```

```

    "items": {
      "description": "List of hub portal root directories to authorize",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "v2_portal_hub",
  "type": "object",
  "properties": {
    "id": {
      "description": "Hub portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "state": {
      "type": "string",
      "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
      ],
      "description": "State of the portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relat

```

```

ionship."
  },
  "status": {
    "type": "string",
    "enum": [
      "INACTIVE",
      "ACTIVE",
      "DEGRADED"
    ],
    "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal ready for use.,\n * `DEGRADED` - A portal missing one or more connections with the other cluster in the relationship.,\n * `INACTIVE` - A portal that is not ready for use."
  },
  "spoke_hosts": {
    "type": "array",
    "items": {
      "description": "IP addresses and TCP ports of nodes in the remote cluster",
      "type": "object",
      "properties": {
        "address": {
          "description": "address",
          "type": "string"
        },
        "port": {
          "description": "port",
          "type": "number"
        }
      }
    }
  },
  "spoke_cluster_uuid": {
    "description": "UUID of the cluster with the spoke portal",
    "type": "string"
  },
  "spoke_cluster_name": {
    "description": "Name of the cluster with the spoke portal",
    "type": "string"
  },
  "pending_roots": {
    "type": "array",
    "items": {
      "description": "Set of hub root directories that are pending authorization",
      "type": "string"
    }
  }
},

```



```
"authorized_roots": {  
  "type": "array",  
  "items": {  
    "description": "Set of hub root directories that are authorized for access",  
    "type": "string"  
  }  
}  
}  
}
```

portal/hubs/{id}/roots/{dir}

Endpoint

/v2/portal/hubs/{id}/roots/{dir}

POST

Authorize the specified hub root directory for the specified hub portal. This allows the spoke portal to access the data in the hub root directory.

Parameters

Name	Description	Required
id	Portal ID	Yes
dir	Directory ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v2_portal_hub",
  "type": "object",
  "properties": {
    "id": {
      "description": "Hub portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    }
  }
}
```

```

},
"state": {
  "type": "string",
  "enum": [
    "PENDING",
    "ACCEPTED",
    "DELETING"
  ],
  "description": "State of the portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relationship."
},
"status": {
  "type": "string",
  "enum": [
    "INACTIVE",
    "ACTIVE",
    "DEGRADED"
  ],
  "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal ready for use,\n * `DEGRADED` - A portal missing one or more connections with the other cluster in the relationship,\n * `INACTIVE` - A portal that is not ready for use."
},
"spoke_hosts": {
  "type": "array",
  "items": {
    "description": "IP addresses and TCP ports of nodes in the remote cluster",
    "type": "object",
    "properties": {
      "address": {
        "description": "address",
        "type": "string"
      },
      "port": {
        "description": "port",
        "type": "number"
      }
    }
  }
},
"spoke_cluster_uuid": {
  "description": "UUID of the cluster with the spoke portal",
  "type": "string"
},

```

```

"spoke_cluster_name": {
  "description": "Name of the cluster with the spoke portal",
  "type": "string"
},
"pending_roots": {
  "type": "array",
  "items": {
    "description": "Set of hub root directories that are pending authorization",
    "type": "string"
  }
},
"authorized_roots": {
  "type": "array",
  "items": {
    "description": "Set of hub root directories that are authorized for access",
    "type": "string"
  }
}
}
}

```

DELETE

Deny access to the specified hub root directory for the specified hub portal. This action does not affect the data in the hub root directory.

Parameters

Name	Description	Required
<code>id</code>	Portal ID	Yes
<code>dir</code>	Directory ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v2_portal_hub",
  "type": "object",
  "properties": {
    "id": {
      "description": "Hub portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "state": {
      "type": "string",
      "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
      ],
      "description": "State of the portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relationship."
    },
    "status": {
      "type": "string",
      "enum": [
        "INACTIVE",
        "ACTIVE",
        "DEGRADED"
      ],
      "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal ready for use,\n * `DEGRADED` - A portal missing one or more connections with the other cluster in the relationship,\n * `INACTIVE` - A portal that is not ready for use."
    },
    "spoke_hosts": {
      "type": "array",
      "items": {
```

```

    "description": "IP addresses and TCP ports of nodes in the remote cluster",
    "type": "object",
    "properties": {
      "address": {
        "description": "address",
        "type": "string"
      },
      "port": {
        "description": "port",
        "type": "number"
      }
    }
  },
  "spoke_cluster_uuid": {
    "description": "UUID of the cluster with the spoke portal",
    "type": "string"
  },
  "spoke_cluster_name": {
    "description": "Name of the cluster with the spoke portal",
    "type": "string"
  },
  "pending_roots": {
    "type": "array",
    "items": {
      "description": "Set of hub root directories that are pending authorization",
      "type": "string"
    }
  },
  "authorized_roots": {
    "type": "array",
    "items": {
      "description": "Set of hub root directories that are authorized for access",
      "type": "string"
    }
  }
}

```

portal/spokes/

Endpoint

/v2/portal/spokes/

GET

List the relationship status and configuration for all spoke portals on the current cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v2_portal_spokes",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of spoke portals",
        "type": "object",
        "properties": {
          "id": {
            "description": "Spoke portal ID",
            "type": "number"
          },
          "type": {
            "type": "string",
            "enum": [
              "PORTAL_READ_ONLY",
              "PORTAL_READ_WRITE"
            ],
            "description": "Type of the spoke portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
          }
        }
      }
    }
  }
}
```

```

    },
    "state": {
      "type": "string",
      "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
      ],
      "description": "State of the spoke portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relationship."
    },
    "status": {
      "type": "string",
      "enum": [
        "INACTIVE",
        "ACTIVE",
        "DEGRADED"
      ],
      "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal ready for use,\n * `DEGRADED` - A portal missing one or more connections with the other cluster in the relationship,\n * `INACTIVE` - A portal that is not ready for use."
    },
    "hub_hosts": {
      "type": "array",
      "items": {
        "description": "IP addresses and TCP ports of nodes in the remote cluster",
        "type": "object",
        "properties": {
          "address": {
            "description": "address",
            "type": "string"
          },
          "port": {
            "description": "port",
            "type": "number"
          }
        }
      }
    },
    "hub_id": {
      "description": "Corresponding remote hub portal ID",
      "type": "number"
    }
  }

```



```

    },
    "hub_cluster_uuid": {
      "description": "UUID of the cluster with the hub portal",
      "type": "string"
    },
    "roots": {
      "type": "array",
      "items": {
        "description": "Map of spoke root directories to hub root directorie",
        "type": "object",
        "properties": {
          "local_root": {
            "description": "Local spoke root directory file ID",
            "type": "string"
          },
          "remote_root": {
            "description": "Remote hub root directory file ID",
            "type": "string"
          },
          "authorized": {
            "description": "Whether the spoke portal is authorized to access t",
            "type": "boolean"
          }
        }
      }
    }
  }
}

```

POST

Create a spoke portal in the current cluster and propose a relationship between this spoke portal and a hub portal on another cluster.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "v2_portal_create_request",
  "type": "object",
  "properties": {
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Whether to create a read-only or read-write spoke portal:\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "hub_hosts": {
      "type": "array",
      "items": {
        "description": "IP addresses and TCP ports of nodes in the remote cluster",
        "type": "object",
        "properties": {
          "address": {
            "description": "address",
            "type": "string"
          },
          "port": {
            "description": "port",
            "type": "number"
          }
        }
      }
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v2_portal_spoke",
  "type": "object",
  "properties": {
    "id": {
      "description": "Spoke portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the spoke portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "state": {
      "type": "string",
      "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
      ],
      "description": "State of the spoke portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relationship."
    },
    "status": {
      "type": "string",
      "enum": [
        "INACTIVE",
        "ACTIVE",
        "DEGRADED"
      ],
      "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal ready for use,\n * `DEGRADED` - A portal missing one or more connections with the other cluster in the relationship,\n * `INACTIVE` - A portal that is not ready for use."
    },
    "hub_hosts": {
      "type": "array",
      "items": {
```

```

    "description": "IP addresses and TCP ports of nodes in the remote cluster",
    "type": "object",
    "properties": {
      "address": {
        "description": "address",
        "type": "string"
      },
      "port": {
        "description": "port",
        "type": "number"
      }
    }
  },
  "hub_id": {
    "description": "Corresponding remote hub portal ID",
    "type": "number"
  },
  "hub_cluster_uuid": {
    "description": "UUID of the cluster with the hub portal",
    "type": "string"
  },
  "roots": {
    "type": "array",
    "items": {
      "description": "Map of spoke root directories to hub root directories",
      "type": "object",
      "properties": {
        "local_root": {
          "description": "Local spoke root directory file ID",
          "type": "string"
        },
        "remote_root": {
          "description": "Remote hub root directory file ID",
          "type": "string"
        },
        "authorized": {
          "description": "Whether the spoke portal is authorized to access the remote root",
          "type": "boolean"
        }
      }
    }
  }
}

```

portal/spokes/{id}

Endpoint

/v2/portal/spokes/{id}

GET

Retrieve the relationship status and configuration for the specified spoke portal.

Parameters

Name	Description	Required
id	Portal ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v2_portal_spoke",
  "type": "object",
  "properties": {
    "id": {
      "description": "Spoke portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the spoke portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "state": {
      "type": "string",
```

```

    "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
    ],
    "description": "State of the spoke portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relationship."
},
"status": {
    "type": "string",
    "enum": [
        "INACTIVE",
        "ACTIVE",
        "DEGRADED"
    ],
    "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal ready for use,\n * `DEGRADED` - A portal missing one or more connections with the other cluster in the relationship,\n * `INACTIVE` - A portal that is not ready for use."
},
"hub_hosts": {
    "type": "array",
    "items": {
        "description": "IP addresses and TCP ports of nodes in the remote cluster",
        "type": "object",
        "properties": {
            "address": {
                "description": "address",
                "type": "string"
            },
            "port": {
                "description": "port",
                "type": "number"
            }
        }
    }
},
"hub_id": {
    "description": "Corresponding remote hub portal ID",
    "type": "number"
},
"hub_cluster_uuid": {
    "description": "UUID of the cluster with the hub portal",
    "type": "string"
}

```

```

},
"roots": {
  "type": "array",
  "items": {
    "description": "Map of spoke root directories to hub root directories",
    "type": "object",
    "properties": {
      "local_root": {
        "description": "Local spoke root directory file ID",
        "type": "string"
      },
      "remote_root": {
        "description": "Remote hub root directory file ID",
        "type": "string"
      },
      "authorized": {
        "description": "Whether the spoke portal is authorized to access the remote root",
        "type": "boolean"
      }
    }
  }
}
}
}
}

```

DELETE

Delete the specified spoke portal from the current cluster. Requires connectivity with the hub portal host cluster.

Parameters

Name	Description	Required
<code>id</code>	Portal ID	Yes
<code>force</code>		No

Response

Codes

Code	Description
202	Return value on success

PATCH

Change configuration for the specified spoke portal.

Parameters

Name	Description	Required
<code>id</code>	Portal ID	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "v2_portal_spoke_patch",
  "type": "object",
  "properties": {
    "id": {
      "description": "Spoke portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the spoke portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "state": {
      "type": "string",
      "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
      ],
      "description": "State of the spoke portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relationship."
    },
    "status": {
```



```

    "type": "string",
    "enum": [
        "INACTIVE",
        "ACTIVE",
        "DEGRADED"
    ],
    "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal
ready for use.,\n * `DEGRADED` - A portal missing one or more connections with the o
ther cluster in the relationship.,\n * `INACTIVE` - A portal that is not ready for u
se."
},
"hub_hosts": {
    "type": "array",
    "items": {
        "description": "IP addresses and TCP ports of nodes in the remote cluster",
        "type": "object",
        "properties": {
            "address": {
                "description": "address",
                "type": "string"
            },
            "port": {
                "description": "port",
                "type": "number"
            }
        }
    }
},
"hub_id": {
    "description": "Corresponding remote hub portal ID",
    "type": "number"
},
"hub_cluster_uuid": {
    "description": "UUID of the cluster with the hub portal",
    "type": "string"
},
"roots": {
    "type": "array",
    "items": {
        "description": "Map of spoke root directories to hub root directories",
        "type": "object",
        "properties": {
            "local_root": {
                "description": "Local spoke root directory file ID",
                "type": "string"
            }
        }
    }
},

```

```

        "remote_root": {
            "description": "Remote hub root directory file ID",
            "type": "string"
        },
        "authorized": {
            "description": "Whether the spoke portal is authorized to access the remote root",
            "type": "boolean"
        }
    }
}
}
}
}
}
}
}
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "v2_portal_spoke",
  "type": "object",
  "properties": {
    "id": {
      "description": "Spoke portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the spoke portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "state": {
      "type": "string",
      "enum": [

```

```

        "PENDING",
        "ACCEPTED",
        "DELETING"
    ],
    "description": "State of the spoke portal:\n * `ACCEPTED` - A portal that is i
n an active relationship.\n * `DELETING` - A portal in the process of synchronizin
g outstanding changes before deletion.\n * `PENDING` - A portal not yet in an activ
e relationship."
    },
    "status": {
        "type": "string",
        "enum": [
            "INACTIVE",
            "ACTIVE",
            "DEGRADED"
        ],
        "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal
ready for use.\n * `DEGRADED` - A portal missing one or more connections with the o
ther cluster in the relationship.\n * `INACTIVE` - A portal that is not ready for u
se."
    },
    "hub_hosts": {
        "type": "array",
        "items": {
            "description": "IP addresses and TCP ports of nodes in the remote cluster",
            "type": "object",
            "properties": {
                "address": {
                    "description": "address",
                    "type": "string"
                },
                "port": {
                    "description": "port",
                    "type": "number"
                }
            }
        }
    },
    "hub_id": {
        "description": "Corresponding remote hub portal ID",
        "type": "number"
    },
    "hub_cluster_uuid": {
        "description": "UUID of the cluster with the hub portal",
        "type": "string"
    },
    },

```

```

"roots": {
  "type": "array",
  "items": {
    "description": "Map of spoke root directories to hub root directories",
    "type": "object",
    "properties": {
      "local_root": {
        "description": "Local spoke root directory file ID",
        "type": "string"
      },
      "remote_root": {
        "description": "Remote hub root directory file ID",
        "type": "string"
      },
      "authorized": {
        "description": "Whether the spoke portal is authorized to access the remote root",
        "type": "boolean"
      }
    }
  }
}

```

portal/spokes/{id}/roots/

Endpoint

/v2/portal/spokes/{id}/roots/

POST

Propose a spoke root directory for the specified spoke portal. This action creates a pending hub root directory on the paired remote hub portal.

Parameters

Name	Description	Required
id	Portal ID	Yes

Request

Schema

```
{
  "description": "v2_portal_root_propose_request",
  "type": "object",
  "properties": {
    "spoke_root_path": {
      "description": "Full path to the spoke portal root directory",
      "type": "string"
    },
    "hub_root_path": {
      "description": "Full path to the hub portal root directory",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v2_portal_spoke",
  "type": "object",
  "properties": {
    "id": {
      "description": "Spoke portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the spoke portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    },
    "state": {
      "type": "string",
      "enum": [
        "PENDING",
        "ACCEPTED",
        "DELETING"
      ],
      "description": "State of the spoke portal:\n * `ACCEPTED` - A portal that is in an active relationship,\n * `DELETING` - A portal in the process of synchronizing outstanding changes before deletion,\n * `PENDING` - A portal not yet in an active relationship."
    },
    "status": {
      "type": "string",
      "enum": [
        "INACTIVE",
        "ACTIVE",
        "DEGRADED"
      ],
      "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal ready for use,\n * `DEGRADED` - A portal missing one or more connections with the other cluster in the relationship,\n * `INACTIVE` - A portal that is not ready for use."
    },
    "hub_hosts": {
      "type": "array",
      "items": {
```

```

    "description": "IP addresses and TCP ports of nodes in the remote cluster",
    "type": "object",
    "properties": {
      "address": {
        "description": "address",
        "type": "string"
      },
      "port": {
        "description": "port",
        "type": "number"
      }
    }
  },
  "hub_id": {
    "description": "Corresponding remote hub portal ID",
    "type": "number"
  },
  "hub_cluster_uuid": {
    "description": "UUID of the cluster with the hub portal",
    "type": "string"
  },
  "roots": {
    "type": "array",
    "items": {
      "description": "Map of spoke root directories to hub root directories",
      "type": "object",
      "properties": {
        "local_root": {
          "description": "Local spoke root directory file ID",
          "type": "string"
        },
        "remote_root": {
          "description": "Remote hub root directory file ID",
          "type": "string"
        },
        "authorized": {
          "description": "Whether the spoke portal is authorized to access the remote root",
          "type": "boolean"
        }
      }
    }
  }
}

```

portal/spokes/{id}/roots/{dir}

Endpoint

/v2/portal/spokes/{id}/roots/{dir}

DELETE

Delete the specified spoke root directory for the specified spoke portal. This action does not affect the data in the hub root directory. Requires connectivity with the hub portal host cluster.

Parameters

Name	Description	Required
<code>id</code>	Portal ID	Yes
<code>dir</code>	Directory ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "v2_portal_spoke",
  "type": "object",
  "properties": {
    "id": {
      "description": "Spoke portal ID",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "PORTAL_READ_ONLY",
        "PORTAL_READ_WRITE"
      ],
      "description": "Type of the spoke portal (read-only or read-write):\n * `PORTAL_READ_ONLY` - PORTAL_READ_ONLY,\n * `PORTAL_READ_WRITE` - PORTAL_READ_WRITE"
    }
  }
}
```



```

},
"state": {
  "type": "string",
  "enum": [
    "PENDING",
    "ACCEPTED",
    "DELETING"
  ],
  "description": "State of the spoke portal:\n * `ACCEPTED` - A portal that is i
n an active relationship.\n * `DELETING` - A portal in the process of synchronizin
g outstanding changes before deletion.\n * `PENDING` - A portal not yet in an activ
e relationship."
},
"status": {
  "type": "string",
  "enum": [
    "INACTIVE",
    "ACTIVE",
    "DEGRADED"
  ],
  "description": "Status of the portal:\n * `ACTIVE` - A fully connected portal
ready for use.\n * `DEGRADED` - A portal missing one or more connections with the o
ther cluster in the relationship.\n * `INACTIVE` - A portal that is not ready for u
se."
},
"hub_hosts": {
  "type": "array",
  "items": {
    "description": "IP addresses and TCP ports of nodes in the remote cluster",
    "type": "object",
    "properties": {
      "address": {
        "description": "address",
        "type": "string"
      },
      "port": {
        "description": "port",
        "type": "number"
      }
    }
  }
},
"hub_id": {
  "description": "Corresponding remote hub portal ID",
  "type": "number"
},

```

```

"hub_cluster_uuid": {
  "description": "UUID of the cluster with the hub portal",
  "type": "string"
},
"roots": {
  "type": "array",
  "items": {
    "description": "Map of spoke root directories to hub root directories",
    "type": "object",
    "properties": {
      "local_root": {
        "description": "Local spoke root directory file ID",
        "type": "string"
      },
      "remote_root": {
        "description": "Remote hub root directory file ID",
        "type": "string"
      },
      "authorized": {
        "description": "Whether the spoke portal is authorized to access the remote root",
        "type": "boolean"
      }
    }
  }
}
}
}
}
}
}

```

cluster/create

Endpoint

/v2/cluster/create

POST

Create a cluster with the given set of node UUIDs and admin password.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_creation_request_v2",
  "type": "object",
  "properties": {
    "eula_accepted": {
      "description": "The user accepts the End User License Agreement",
      "type": "boolean"
    },
    "cluster_name": {
      "description": "Name of the cluster",
      "type": "string"
    },
    "node_uuids": {
      "type": "array",
      "items": {
        "description": "List of node uuids to form a cluster with",
        "type": "string"
      }
    },
    "node_ips": {
      "type": "array",
      "items": {
        "description": "List of node IPs to form a cluster with",
        "type": "string"
      }
    },
    "admin_password": {
      "description": "The administrator password",
      "type": "string",
    }
  }
}
```

```
    "format": "password"
  },
  "host_instance_id": {
    "description": "EC2 instance ID for the node handling this request",
    "type": "string"
  },
  "blocks_per_stripe": {
    "description": "Number of blocks per stripe in the cluster's erasure coding configuration",
    "type": "number"
  },
  "max_drive_failures": {
    "description": "The maximum number of drive failures this cluster will be able to sustain",
    "type": "number"
  },
  "max_node_failures": {
    "description": "The maximum number of node failures this cluster will be able to sustain",
    "type": "number"
  }
}
```

Response

Codes

Code	Description
202	Return value on success

cluster/data-core/create

Endpoint

/v2/cluster/data-core/create

POST

Create a stratus data core cluster with the given set of node UUIDs and admin password.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_creation_data_core_request_v2",
  "type": "object",
  "properties": {
    "eula_accepted": {
      "description": "The user accepts the End User License Agreement",
      "type": "boolean"
    },
    "cluster_name": {
      "description": "Name of the cluster",
      "type": "string"
    },
    "node_uuids": {
      "type": "array",
      "items": {
        "description": "List of node uuids to form a cluster with",
        "type": "string"
      }
    },
    "admin_password": {
      "description": "The administrator password",
      "type": "string",
      "format": "password"
    },
    "blocks_per_stripe": {
      "description": "Number of blocks per stripe in the cluster's erasure coding configuration",
      "type": "number"
    }
  }
}
```

```
"max_drive_failures": {  
  "description": "The maximum number of drive failures this cluster will be able to sustain",  
  "type": "number"  
},  
"max_node_failures": {  
  "description": "The maximum number of node failures this cluster will be able to sustain",  
  "type": "number"  
}  
}
```

Response

Codes

Code	Description
202	Return value on success

cluster/unprotected-edge/create

Endpoint

/v2/cluster/unprotected-edge/create

POST

Create an unprotected single-node edge device given an admin password.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_creation_unprotected_request_v2",
  "type": "object",
  "properties": {
    "eula_accepted": {
      "description": "The user accepts the End User License Agreement",
      "type": "boolean"
    },
    "name": {
      "description": "The name of the Edge Device",
      "type": "string"
    },
    "admin_password": {
      "description": "The administrator password",
      "type": "string",
      "format": "password"
    }
  }
}
```

Response

Codes

Code	Description
202	Return value on success

cluster/calculate-supported-protection-info

Endpoint

/v3/cluster/calculate-supported-protection-info

POST

Returns list of supported data protection stripe configuration(s). This includes the stripe width and usable capacity using that width. For use with unconfigured nodes only.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_supported_protection_info_request_v2",
  "type": "object",
  "properties": {
    "node_uuids": {
      "type": "array",
      "items": {
        "description": "List of unconfigured node UUIDs to query supported protection levels and capacities",
        "type": "string"
      }
    },
    "node_ips": {
      "type": "array",
      "items": {
        "description": "List of unconfigured node IPs to query supported protection levels and capacities",
        "type": "string"
      }
    }
  }
}
```


Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_supported_protection_configs",
  "type": "object",
  "properties": {
    "supported_configs": {
      "type": "array",
      "items": {
        "description": "Vector of supported protection configurations",
        "type": "object",
        "properties": {
          "blocks_per_stripe": {
            "description": "Number of blocks per stripe for this stripe config",
            "type": "number"
          },
          "max_drive_failures": {
            "description": "Number of simultaneous drive failures supported for this stripe config",
            "type": "number"
          },
          "max_node_failures": {
            "description": "Number of simultaneous node failures supported for this stripe config",
            "type": "number"
          },
          "max_cluster_node_count": {
            "description": "The max amount of nodes supported to guarantee data safety with this stripe config",
            "type": "number"
          },
          "usable_capacity_in_bytes": {
            "description": "The usable capacity in bytes if the node/SKU configuration uses this stripe config",
            "type": "string"
          }
        }
      }
    }
  }
}
```

```
}  
}  
}
```

/v4/cluster/object-backed/create

Endpoint

/v4/cluster/object-backed/create

POST

Create an object-backed cluster with the given set of node IPs, fault domain IDs, object storage URIs and admin password. This API is deprecated in favor of /v5/cluster/object-backed/create

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_creation_object_backed_request_v4",
  "type": "object",
  "properties": {
    "eula_accepted": {
      "description": "The user accepts the End User License Agreement",
      "type": "boolean"
    },
    "cluster_name": {
      "description": "Name of the cluster",
      "type": "string"
    },
    "node_ips_and_fault_domains": {
      "type": "array",
      "items": {
        "description": "List of node IP and their respective fault domains to form a cluster with",
        "type": "object",
        "properties": {
          "node_ip": {
            "description": "node_ip",
            "type": "string"
          },
          "fault_domain_id": {
            "description": "fault_domain_id",
            "type": "number"
          }
        }
      }
    }
  }
}
```

```

    }
  },
  "admin_password": {
    "description": "The administrator password",
    "type": "string",
    "format": "password"
  },
  "host_instance_id": {
    "description": "EC2 instance ID for the node handling this request",
    "type": "string"
  },
  "azure_key_vault": {
    "description": "The key vault for accessing Azure blobs (only used on Azure cl
usters).",
    "type": "string"
  },
  "object_storage_uris": {
    "type": "array",
    "items": {
      "description": "The URI to the object storage that backs the Object Tier fo
r the cluster",
      "type": "string"
    }
  },
  "usable_capacity_clamp": {
    "description": "Usable capacity, in bytes, to clamp the file system to",
    "type": "string"
  },
  "product_type": {
    "type": "string",
    "enum": [
      "ACTIVE_WITH_STANDARD_STORAGE",
      "ACTIVE_WITH_INTELLIGENT_STORAGE",
      "ACTIVE_WITH_HOT_STORAGE",
      "ARCHIVE_WITH_IA_STORAGE",
      "ARCHIVE_WITH_GIR_STORAGE",
      "ARCHIVE_WITH_COLD_STORAGE"
    ],
    "description": "The product type of cluster to create. Valid options are: ACTI
VE_WITH_STANDARD_STORAGE, ACTIVE_WITH_HOT_STORAGE, ACTIVE_WITH_INTELLIGENT_STORAGE,
ARCHIVE_WITH_IA_STORAGE, ARCHIVE_WITH_GIR_STORAGE, ARCHIVE_WITH_COLD_STORAGE. Not al
l product types are available on all platforms.:\\n * `ACTIVE_WITH_HOT_STORAGE` - ACT
IVE_WITH_HOT_STORAGE,\\n * `ACTIVE_WITH_INTELLIGENT_STORAGE` - ACTIVE_WITH_INTELLIGEN
T_STORAGE,\\n * `ACTIVE_WITH_STANDARD_STORAGE` - ACTIVE_WITH_STANDARD_STORAGE,\\n * `A
RCHIVE_WITH_COLD_STORAGE` - ARCHIVE_WITH_COLD_STORAGE,\\n * `ARCHIVE_WITH_GIR_STORAG

```

```

E` - ARCHIVE_WITH_GIR_STORAGE,\n * `ARCHIVE_WITH_IA_STORAGE` - ARCHIVE_WITH_IA_STORA
GE"
  },
  "pbkdf2_admin_hash": {
    "description": "The PBKDF2 has parameters for the administrative user: a hexad
ecimal hash, a hexadecimal salt, and the number of iterations. It is possible to us
e these parameters for administrative password or a different password.",
    "type": "object",
    "properties": {
      "hash": {
        "description": "hash",
        "type": "string"
      },
      "salt": {
        "description": "salt",
        "type": "string"
      },
      "num_iterations": {
        "description": "num_iterations",
        "type": "number"
      }
    }
  },
  "operator_public_keys": {
    "type": "array",
    "items": {
      "description": "The set of public keys allowed to sign operator bearer token
s",
      "type": "object",
      "properties": {
        "data": {
          "description": "data",
          "type": "string"
        }
      }
    }
  }
}

```

Response

Codes

Code	Description
------	-------------

202	Return value on success
-----	-------------------------

/v5/cluster/object-backed/create

Endpoint

/v5/cluster/object-backed/create

POST

Create an object-backed cluster with the given set of node IPs, fault domain IDs, object storage URIs and admin password.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_creation_object_backed_request_v5",
  "type": "object",
  "properties": {
    "eula_accepted": {
      "description": "The user accepts the End User License Agreement",
      "type": "boolean"
    },
    "cluster_name": {
      "description": "Name of the cluster",
      "type": "string"
    },
    "node_ips_and_fault_domains": {
      "type": "array",
      "items": {
        "description": "List of node IP and their respective fault domains to form a cluster with",
        "type": "object",
        "properties": {
          "node_ip": {
            "description": "node_ip",
            "type": "string"
          },
          "fault_domain_id": {
            "description": "fault_domain_id",
            "type": "number"
          }
        }
      }
    }
  }
}
```

```

    }
  },
  "admin_password": {
    "description": "The administrator password",
    "type": "string",
    "format": "password"
  },
  "host_instance_id": {
    "description": "EC2 instance ID for the node handling this request",
    "type": "string"
  },
  "key_vault": {
    "description": "The key vault for accessing object storage. This is a key vault URL on Azure, and a secret bundle ID on OCI.",
    "type": "string"
  },
  "object_storage_uris": {
    "type": "array",
    "items": {
      "description": "The URI to the object storage that backs the Object Tier for the cluster",
      "type": "string"
    }
  },
  "usable_capacity_clamp": {
    "description": "Usable capacity, in bytes, to clamp the file system to",
    "type": "string"
  },
  "product_type": {
    "type": "string",
    "enum": [
      "ACTIVE_WITH_STANDARD_STORAGE",
      "ACTIVE_WITH_INTELLIGENT_STORAGE",
      "ACTIVE_WITH_HOT_STORAGE",
      "ARCHIVE_WITH_IA_STORAGE",
      "ARCHIVE_WITH_GIR_STORAGE",
      "ARCHIVE_WITH_COLD_STORAGE"
    ],
    "description": "The product type of cluster to create. Valid options are: ACTIVE_WITH_STANDARD_STORAGE, ACTIVE_WITH_HOT_STORAGE, ACTIVE_WITH_INTELLIGENT_STORAGE, ARCHIVE_WITH_IA_STORAGE, ARCHIVE_WITH_GIR_STORAGE, ARCHIVE_WITH_COLD_STORAGE. Not all product types are available on all platforms.:\\n * `ACTIVE_WITH_HOT_STORAGE` - ACTIVE_WITH_HOT_STORAGE,\\n * `ACTIVE_WITH_INTELLIGENT_STORAGE` - ACTIVE_WITH_INTELLIGENT_STORAGE,\\n * `ACTIVE_WITH_STANDARD_STORAGE` - ACTIVE_WITH_STANDARD_STORAGE,\\n * `ARCHIVE_WITH_COLD_STORAGE` - ARCHIVE_WITH_COLD_STORAGE,\\n * `ARCHIVE_WITH_GIR_STORAGE`"
  }
}

```



```

E` - ARCHIVE_WITH_GIR_STORAGE,\n * `ARCHIVE_WITH_IA_STORAGE` - ARCHIVE_WITH_IA_STORA
GE"
    },
    "pbkdf2_admin_hash": {
      "description": "The PBKDF2 has parameters for the administrative user: a hexad
ecimal hash, a hexadecimal salt, and the number of iterations. It is possible to us
e these parameters for administrative password or a different password.",
      "type": "object",
      "properties": {
        "hash": {
          "description": "hash",
          "type": "string"
        },
        "salt": {
          "description": "salt",
          "type": "string"
        },
        "num_iterations": {
          "description": "num_iterations",
          "type": "number"
        }
      }
    },
    "operator_public_keys": {
      "type": "array",
      "items": {
        "description": "The set of public keys allowed to sign operator bearer token
s",
        "type": "object",
        "properties": {
          "data": {
            "description": "data",
            "type": "string"
          }
        }
      }
    }
  }
}

```

Response

Codes

Code	Description
------	-------------

202	Return value on success
-----	-------------------------

/v5/cluster/object-backed/create-stratus

Endpoint

/v5/cluster/object-backed/create-stratus

POST

Create a Stratus tenant cluster with the given set of node UUIDs and one or more object storage URIs that reference data core cluster(s).

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_stratus_cluster_creation_request",
  "type": "object",
  "properties": {
    "eula_accepted": {
      "description": "The user accepts the End User License Agreement",
      "type": "boolean"
    },
    "cluster_name": {
      "description": "Name of the cluster",
      "type": "string"
    },
    "cluster_uuid": {
      "description": "UUID of the cluster. If this is not supplied, one will be generated by the system.",
      "type": "string"
    },
    "pbkdf2_admin_hash": {
      "description": "The PBKDF2 has parameters for the administrative user: a hexadecimal hash, a hexadecimal salt, and the number of iterations. It is possible to use these parameters for administrative password or a different password.",
      "type": "object",
      "properties": {
        "hash": {
          "description": "hash",
          "type": "string"
        }
      }
    }
  }
}
```

```

    "salt": {
      "description": "salt",
      "type": "string"
    },
    "num_iterations": {
      "description": "num_iterations",
      "type": "number"
    }
  },
  "operator_public_keys": {
    "type": "array",
    "items": {
      "description": "The set of public keys allowed to sign operator bearer tokens",
      "type": "object",
      "properties": {
        "data": {
          "description": "data",
          "type": "string"
        }
      }
    }
  },
  "node_uuids_and_fault_domains": {
    "type": "array",
    "items": {
      "description": "List of node UUIDs and their respective fault domains as cluster members",
      "type": "object",
      "properties": {
        "node_uuid": {
          "description": "node_uuid",
          "type": "string"
        },
        "fault_domain_id": {
          "description": "fault_domain_id",
          "type": "number"
        }
      }
    }
  },
  "admin_password": {
    "description": "The administrator password",
    "type": "string",
    "format": "password"
  }
}

```

```

    },
    "usable_capacity": {
      "description": "File system usable capacity in bytes",
      "type": "string"
    },
    "object_store_uris": {
      "type": "array",
      "items": {
        "description": "URI(s) of the object store(s) to be used by this tenant cluster",
        "type": "string"
      }
    },
    "object_store_credentials": {
      "type": "array",
      "items": {
        "description": "Credentials for accessing the object stores referenced by the list of object storage URIs",
        "type": "object",
        "properties": {
          "store_name": {
            "description": "store_name",
            "type": "string"
          },
          "access_key_id": {
            "description": "access_key_id",
            "type": "string"
          },
          "secret_access_key": {
            "description": "secret_access_key",
            "type": "string",
            "format": "password"
          }
        }
      }
    }
  }
}

```

Response

Codes

Code	Description
202	Return value on success

cluster/object-backed/protection/fault-tolerance

Endpoint

/v1/cluster/object-backed/protection/fault-tolerance

GET

Gets the current fault tolerance of an object-backed cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_object_backed_fault_tolerance",
  "type": "object",
  "properties": {
    "disks": {
      "description": "The maximum number of arbitrary disks that cluster currently supports losing.",
      "type": "number"
    },
    "nodes": {
      "description": "The maximum number of arbitrary nodes that cluster currently supports losing.",
      "type": "number"
    },
    "fault_domains": {
      "description": "The maximum number of arbitrary fault_domains that cluster currently supports losing.",
      "type": "number"
    }
  }
}
```

}

cluster/protection/restriper/status

Endpoint

/v1/cluster/protection/restriper/status

GET

Get current status of restriper, including data protection status and current restriper phase (if running)

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_restriper_status_v2",
  "type": "object",
  "properties": {
    "state": {
      "type": "string",
      "enum": [
        "NOT_STARTED",
        "RUNNING",
        "FINISHED"
      ],
      "description": "Restriper state (one of NOT_STARTED, RUNNING, FINISHED).:\n * `FINISHED` - FINISHED,\n * `NOT_STARTED` - NOT_STARTED,\n * `RUNNING` - RUNNING"
    },
    "phase": {
      "type": "string",
      "enum": [
        "PLANNING",
        "REPROTECT",
        "REBALANCE",
        "PARTITIONED_REBALANCE",

```



```

        "TRANSCODE"
    ],
    "description": "Restriper phase when state is RUNNING (one of PLANNING, REPROTECT, REBALANCE, PARTITIONED_REBALANCE, TRANSCODE). Empty otherwise.:\\n * `PARTITIONED_REBALANCE` - PARTITIONED_REBALANCE,\\n * `PLANNING` - PLANNING,\\n * `REBALANCE` - REBALANCE,\\n * `REPROTECT` - REPROTECT,\\n * `TRANSCODE` - TRANSCODE"
},
    "blocked_reason": {
        "description": "If state is FINISHED but restriper did not complete all required work, this field provides the reason for the work being incomplete. Empty otherwise.",
        "type": "string"
    },
    "data_at_risk": {
        "description": "True if any data is not fully protected, false otherwise.",
        "type": "boolean"
    },
    "elapsed_seconds": {
        "description": "Elapsed time since the current phase began (0 if state is not RUNNING).",
        "type": "number"
    },
    "percent_complete": {
        "description": "Percent completion of the current phase (0 if state is not RUNNING).",
        "type": "number"
    },
    "coordinator_node": {
        "description": "Restriper coordinator node ID in this quorum, where reports are being recorded.",
        "type": "number"
    }
}
}

```

cluster/protection/status

Endpoint

/v1/cluster/protection/status

GET

Gets detailed status information for the data protection of the cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_protection_status",
  "type": "object",
  "properties": {
    "blocks_per_stripe": {
      "description": "The total number of blocks per stripe, including parity.",
      "type": "number"
    },
    "data_blocks_per_stripe": {
      "description": "The number of data blocks per stripe.",
      "type": "number"
    },
    "protection_system_type": {
      "description": "The data protection type for this cluster.",
      "type": "string"
    },
    "max_node_failures": {
      "description": "The maximum number of node failures this cluster can sustain and remain operational.",
      "type": "number"
    },
    "max_drive_failures": {
```

```

    "description": "The maximum number of drive failures this cluster can sustain
and remain operational.",
    "type": "number"
},
"max_drive_spares": {
    "description": "DEPRECATED: The approximate number of drives of sparing space
that this cluster has reserved for reprotect.",
    "type": "number"
},
"remaining_node_failures": {
    "description": "The number of node failures this cluster can currently sustain
and remain operational.",
    "type": "number"
},
"remaining_drive_failures": {
    "description": "The number of drive failures this cluster can currently sustain
and remain operational.",
    "type": "number"
},
"pending_configuration": {
    "description": "The configuration to which this cluster is being changed.",
    "type": "object",
    "properties": {
        "blocks_per_stripe": {
            "description": "Number of blocks per stripe for this stripe config",
            "type": "number"
        },
        "max_drive_failures": {
            "description": "Number of simultaneous drive failures supported for this s
trip stripe config",
            "type": "number"
        },
        "max_node_failures": {
            "description": "Number of simultaneous node failures supported for this st
ripe config",
            "type": "number"
        }
    }
}
}
}
}

```

cluster/calculate-node-add-capacity

Endpoint

/v1/cluster/calculate-node-add-capacity

POST

Calculate changes to cluster usable capacity from a proposed node-add operation. This endpoint is deprecated in favor of /v2/cluster/nodes/dry-run.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_calculate_node_add_capacity_request",
  "type": "object",
  "properties": {
    "node_uuids": {
      "type": "array",
      "items": {
        "description": "Identifiers of nodes to add to existing cluster",
        "type": "string"
      }
    },
    "node_ips": {
      "type": "array",
      "items": {
        "description": "IP addresses of nodes to add to existing cluster",
        "type": "string"
      }
    }
  }
}
```

Response

Codes

Code	Description
------	-------------

200	Return value on success
-----	-------------------------

Schema

```
{
  "description": "api_cluster_calculate_node_add_capacity_response",
  "type": "object",
  "properties": {
    "new_usable_capacity_in_bytes": {
      "description": "The cluster's usable capacity (in bytes) after node-add operations",
      "type": "string"
    },
    "increase_from_current_usable_capacity_in_bytes": {
      "description": "The increase of the cluster's usable capacity (in bytes) after node-add operations",
      "type": "string"
    },
    "max_node_failures": {
      "description": "The maximum number of tolerable cluster node failures after node-add operations",
      "type": "number"
    },
    "node_add_capacity_optimized_for_fault_tolerance": {
      "description": "This field is only populated if it is possible to optimize the cluster for increased node fault tolerance instead of usable capacity during node-add operations. When populated, it shows the usable cluster capacity and node fault tolerance for the optimized cluster.",
      "type": "object",
      "properties": {
        "new_usable_capacity_in_bytes": {
          "description": "The cluster's usable capacity (in bytes) after node-add operations and optimization for increased node fault tolerance",
          "type": "string"
        },
        "increase_from_current_usable_capacity_in_bytes": {
          "description": "The increase of the cluster's usable capacity (in bytes) after node-add operations and optimization for increased node fault tolerance",
          "type": "string"
        },
        "max_node_failures": {
          "description": "The maximum number of tolerable cluster node failures after node-add operations and optimization for increased node fault tolerance",
          "type": "number"
        }
      }
    }
  }
}
```

```
}  
  }  
}
```

cluster/node-replacement-plan/

Endpoint

/v1/cluster/node-replacement-plan/

GET

Get the current node replacement plan. This plan lists the nodes pending replacement and nodes currently in process of being replaced.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_node_replacement_plan",
  "type": "object",
  "properties": {
    "nodes_to_be_replaced": {
      "type": "array",
      "items": {
        "description": "Nodes selected for replacement.",
        "type": "number"
      }
    },
    "nodes_currently_being_replaced": {
      "type": "array",
      "items": {
        "description": "Nodes currently in process of being replaced.",
        "type": "number"
      }
    },
    "target_stripe_config": {
      "description": "The target EC stripe config. If this value is empty, it indicates that the cluster's stripe config will remain unchanged throughout the node repla
```

```

cement.",
  "type": "object",
  "properties": {
    "blocks_per_stripe": {
      "description": "Number of blocks per EC stripe including parity.",
      "type": "number"
    },
    "data_blocks_per_stripe": {
      "description": "The number of data blocks per stripe.",
      "type": "number"
    }
  }
}
}
}
}

```

POST

To initiate node replacement, specify the nodes to replace.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "api_cluster_node_replacement_request",
  "type": "object",
  "properties": {
    "nodes_to_be_replaced": {
      "type": "array",
      "items": {
        "description": "Nodes selected for replacement.",
        "type": "number"
      }
    },
    "target_stripe_config": {
      "description": "The optional target EC stripe config.",
      "type": "object",
      "properties": {
        "blocks_per_stripe": {
          "description": "Number of blocks per EC stripe including parity.",
          "type": "number"
        }
      }
    }
  }
}

```



```
    },  
    "data_blocks_per_stripe": {  
      "description": "The number of data blocks per stripe.",  
      "type": "number"  
    }  
  }  
}  
}
```

Response

Codes

Code	Description
200	Return value on success

cluster/nodes/

Endpoint

/v1/cluster/nodes/

GET

List nodes.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_node",
    "type": "object",
    "properties": {
      "id": {
        "description": "id",
        "type": "number"
      },
      "node_status": {
        "description": "Status of the node",
        "type": "string"
      },
      "node_name": {
        "description": "User friendly node name",
        "type": "string"
      },
      "uuid": {
        "description": "Unique node identifier",
        "type": "string"
      }
    }
  }
}
```

```

    "label": {
      "description": "Physically identifiable label assigned to the hardware",
      "type": "string"
    },
    "model_number": {
      "description": "Node model number",
      "type": "string"
    },
    "serial_number": {
      "description": "Serial number",
      "type": "string"
    },
    "mac_address": {
      "description": "MAC address for the first network interface on this node",
      "type": "string"
    }
  }
}

```

POST

Add one or more unconfigured nodes with the given node uuids and admin password. This endpoint is deprecated in favor of `/v2/cluster/nodes`.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "api_cluster_nodes_modify_request_v1",
  "type": "object",
  "properties": {
    "node_uuids": {
      "type": "array",
      "items": {
        "description": "Identifiers of nodes to add to existing cluster",
        "type": "string"
      }
    },
    "node_ips": {
      "type": "array",

```

```
    "items": {
      "description": "IP addresses of nodes to add to existing cluster",
      "type": "string"
    },
    "optimize_node_fault_tolerance_over_usable_capacity": {
      "description": "True to trade-off some increase in usable capacity for increased node fault tolerance. Defaults to False.",
      "type": "boolean"
    }
  }
}
```

Response

Codes

Code	Description
202	Return value on success

cluster/nodes/chassis/

Endpoint

/v1/cluster/nodes/chassis/

GET

List the status of the chassis for nodes. This API is deprecated in favor of /v1/cluster/nodes/uid-lights and /v2/metrics/endpoints/default/data for PSU information

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_node_chassis",
    "type": "object",
    "properties": {
      "id": {
        "description": "id",
        "type": "number"
      },
      "light_visible": {
        "description": "Visibility of the node identifier light",
        "type": "boolean"
      },
      "psu_statuses": {
        "type": "array",
        "items": {
          "description": "psu_statuses",
          "type": "object",
          "properties": {
            "name": {
```


cluster/nodes/uid-lights/

Endpoint

/v1/cluster/nodes/uid-lights/

GET

List the status of the identification lights for nodes.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_node_uid_light_status",
    "type": "object",
    "properties": {
      "id": {
        "description": "Integer ID of the node being reported.",
        "type": "number"
      },
      "light_visible": {
        "description": "Visibility of the node identification light",
        "type": "boolean"
      }
    }
  }
}
```

cluster/nodes/{id}

Endpoint

/v1/cluster/nodes/{id}

GET

Retrieve node-specific info, such as serial number, mac address, uuid, etc

Parameters

Name	Description	Required
id	The unique ID of the node	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_node",
  "type": "object",
  "properties": {
    "id": {
      "description": "id",
      "type": "number"
    },
    "node_status": {
      "description": "Status of the node",
      "type": "string"
    },
    "node_name": {
      "description": "User friendly node name",
      "type": "string"
    },
    "uuid": {
      "description": "Unique node identifier",
      "type": "string"
    }
  }
}
```



```
},
"label": {
  "description": "Physically identifiable label assigned to the hardware",
  "type": "string"
},
"model_number": {
  "description": "Node model number",
  "type": "string"
},
"serial_number": {
  "description": "Serial number",
  "type": "string"
},
"mac_address": {
  "description": "MAC address for the first network interface on this node",
  "type": "string"
}
}
```

cluster/nodes/{id}/chassis

Endpoint

/v1/cluster/nodes/{id}/chassis

GET

List the status of the chassis for a node. This API is deprecated in favor of /v1/cluster/nodes//uid-light and /v2/metrics/endpoints/default/data for PSU information

Parameters

Name	Description	Required
id	The unique ID of the node	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_node_chassis",
  "type": "object",
  "properties": {
    "id": {
      "description": "id",
      "type": "number"
    },
    "light_visible": {
      "description": "Visibility of the node identifier light",
      "type": "boolean"
    },
    "psu_statuses": {
      "type": "array",
      "items": {
        "description": "psu_statuses",
        "type": "object",
        "properties": {
```

```

    "name": {
      "description": "name",
      "type": "string"
    },
    "state": {
      "type": "string",
      "enum": [
        "UNKNOWN",
        "MISSING",
        "NO AC",
        "GOOD",
        "FAILED",
        "PREFAIL"
      ],
      "description": "state:\n * `FAILED` - PSU_STATE_FAILED,\n * `GOOD` - PSU_STATE_GOOD,\n * `MISSING` - PSU_STATE_MISSING,\n * `NO AC` - PSU_STATE_NO_AC,\n * `PREFAIL` - PSU_STATE_PREFAIL,\n * `UNKNOWN` - PSU_STATE_UNKNOWN"
    },
    "location": {
      "type": "string",
      "enum": [
        "right",
        "left",
        "top",
        "bottom"
      ],
      "description": "location:\n * `bottom` - PSU_LOCATION_BOTTOM,\n * `left` - PSU_LOCATION_LEFT,\n * `right` - PSU_LOCATION_RIGHT,\n * `top` - PSU_LOCATION_TOP"
    }
  }
}
}
}
}
}

```

cluster/nodes/{id}/identify

Endpoint

/v1/cluster/nodes/{id}/identify

POST

Turn the identification light on the node on or off. There may be a slight delay for the change to take effect.

Parameters

Name	Description	Required
id	The unique ID of the node	Yes

Request

Schema

```
{
  "description": "api_node_uid_light",
  "type": "object",
  "properties": {
    "light_visible": {
      "description": "Visibility of the node identifier light",
      "type": "boolean"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

cluster/nodes/{id}/uid-light

Endpoint

/v1/cluster/nodes/{id}/uid-light

GET

Status of the identification (UID) light for this node.

Parameters

Name	Description	Required
id	The unique ID of the node	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_node_uid_light",
  "type": "object",
  "properties": {
    "light_visible": {
      "description": "Visibility of the node identifier light",
      "type": "boolean"
    }
  }
}
```

POST

Turn the identification light on the node on or off. There may be a slight delay for the change to take effect.

Parameters

Name	Description	Required
------	-------------	----------

id	The unique ID of the node	Yes
----	---------------------------	-----

Request

Schema

```
{
  "description": "api_node_uid_light",
  "type": "object",
  "properties": {
    "light_visible": {
      "description": "Visibility of the node identifier light",
      "type": "boolean"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

cluster/restriper/status

Endpoint

/v1/cluster/restriper/status

GET

Get current status of restriper, including data protection status and current restripe phase (if running). This API is deprecated in favor of /v1/cluster/protection/restriper/status after v5.3.4.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_restriper_status",
  "type": "object",
  "properties": {
    "status": {
      "type": "string",
      "enum": [
        "RUNNING",
        "NOT_RUNNING",
        "BLOCKED"
      ],
      "description": "Restriper status (one of RUNNING, BLOCKED, NOT_RUNNING).:\n * `BLOCKED` - API_RESTRIPER_STATE_BLOCKED,\n * `NOT_RUNNING` - API_RESTRIPER_STATE_NOT_RUNNING,\n * `RUNNING` - API_RESTRIPER_STATE_RUNNING"
    },
    "data_at_risk": {
      "description": "True if any data in the cluster needs to be reprotected, false otherwise.",
      "type": "boolean"
    },
    "blocked_reason": {
```

```

    "description": "If status is BLOCKED, this field provides more information.",
    "type": "string"
  },
  "phase": {
    "type": "string",
    "enum": [
      "PLANNING",
      "REPROTECT",
      "REBALANCE",
      "PARTITIONED_REBALANCE",
      "TRANSCODE",
      ""
    ],
    "description": "Restriper phase when status is RUNNING (one of PLANNING, REPROTECT, REBALANCE, PARTITIONED_REBALANCE, TRANSCODE), empty otherwise.:\\n * `` - API_RESTRIPER_PHASE_NOT_RUNNING,\\n * `PARTITIONED_REBALANCE` - API_RESTRIPER_PHASE_PARTITIONED_REBALANCE,\\n * `PLANNING` - API_RESTRIPER_PHASE_PLANNING,\\n * `REBALANCE` - API_RESTRIPER_PHASE_REBALANCE,\\n * `REPROTECT` - API_RESTRIPER_PHASE_REPROTECT,\\n * `TRANSCODE` - API_RESTRIPER_PHASE_TRANSCODING"
  },
  "elapsed_seconds": {
    "description": "How long since the current phase began (0 if status != RUNNING).",
    "type": "number"
  },
  "estimated_seconds_left": {
    "description": "How much longer the current phase is expected to take (UINTMAX if status != RUNNING).",
    "type": "number"
  },
  "percent_complete": {
    "description": "Percent of work completed by the current phase.",
    "type": "number"
  },
  "coordinator_node": {
    "description": "Restriper coordinator for this quorum (where reports will get stored).",
    "type": "number"
  }
}

```


cluster/nodes/

Endpoint

/v2/cluster/nodes/

POST

Modify the composition of the cluster by adding unconfigured nodes or replacing configured nodes.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_nodes_modify_request_v2",
  "type": "object",
  "properties": {
    "node_uuids": {
      "type": "array",
      "items": {
        "description": "The UUIDs of the unconfigured nodes to add to the cluster",
        "type": "string"
      }
    },
    "node_ips": {
      "type": "array",
      "items": {
        "description": "The IP addresses of the unconfigured nodes to add to the cluster",
        "type": "string"
      }
    },
    "nodes_to_replace": {
      "type": "array",
      "items": {
        "description": "The configured nodes to replace. Note: These nodes must be a subset of the node replacement plan.",
        "type": "number"
      }
    }
  }
}
```

```
"target_max_node_failures": {
  "description": "The minimum node-fault-tolerance level for the resulting cluster configuration. Note: In certain cases, a lower node-fault-tolerance level can result in higher usable capacity.",
  "type": "number"
},
"target_stripe_config": {
  "description": "The final stripe configuration to use.",
  "type": "object",
  "properties": {
    "blocks_per_stripe": {
      "description": "Number of blocks per EC stripe including parity.",
      "type": "number"
    },
    "data_blocks_per_stripe": {
      "description": "The number of data blocks per stripe.",
      "type": "number"
    }
  }
}
}
```

Response

Codes

Code	Description
202	Return value on success

cluster/nodes/dry-run

Endpoint

/v2/cluster/nodes/dry-run

POST

Validate a node-add operation or node replacement step and, if it succeeds, return the projected usable capacity and node fault tolerance level.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_nodes_modify_request_v2",
  "type": "object",
  "properties": {
    "node_uuids": {
      "type": "array",
      "items": {
        "description": "The UUIDs of the unconfigured nodes to add to the cluster",
        "type": "string"
      }
    },
    "node_ips": {
      "type": "array",
      "items": {
        "description": "The IP addresses of the unconfigured nodes to add to the cluster",
        "type": "string"
      }
    },
    "nodes_to_replace": {
      "type": "array",
      "items": {
        "description": "The configured nodes to replace. Note: These nodes must be a subset of the node replacement plan.",
        "type": "number"
      }
    }
  }
}
```

```

    "target_max_node_failures": {
      "description": "The minimum node-fault-tolerance level for the resulting cluster configuration. Note: In certain cases, a lower node-fault-tolerance level can result in higher usable capacity.",
      "type": "number"
    },
    "target_stripe_config": {
      "description": "The final stripe configuration to use.",
      "type": "object",
      "properties": {
        "blocks_per_stripe": {
          "description": "Number of blocks per EC stripe including parity.",
          "type": "number"
        },
        "data_blocks_per_stripe": {
          "description": "The number of data blocks per stripe.",
          "type": "number"
        }
      }
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_cluster_nodes_modify_dry_run_response",
  "type": "object",
  "properties": {
    "current_capacity": {
      "description": "The cluster's current usable capacity (in bytes)",
      "type": "string"
    },
    "current_max_node_failures": {
      "description": "The cluster's current node-fault-tolerance level",
      "type": "number"
    }
  },
}

```

```
"projected_capacity": {  
  "description": "The cluster's usable capacity (in bytes) after the operation",  
  "type": "string"  
},  
"projected_max_node_failures": {  
  "description": "The cluster's node-fault-tolerance level after the operation",  
  "type": "number"  
}  
}  
}
```

cluster/object-backed/nodes

Endpoint

/v2/cluster/object-backed/nodes

GET

List all object-backed nodes in the cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_cluster_object_backed_nodes_get_response",
  "type": "object",
  "properties": {
    "membership": {
      "description": "The list of nodes that are currently in the cluster (ordered by node id).",
      "type": "object",
      "properties": {
        "node_ips_and_fault_domains": {
          "type": "array",
          "items": {
            "description": "The IP addresses and fault domains of the nodes in the cluster.",
            "type": "object",
            "properties": {
              "node_ip": {
                "description": "node_ip",
                "type": "string"
              },
              "fault_domain_id": {
                "description": "fault_domain_id",
```

POST

Modify the composition of the object-backed cluster by adding unconfigured nodes or replacing configured nodes. Allows for the specification of fault domains on added or replaced nodes.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_object_backed_nodes_modify_request_v2",
  "type": "object",
  "properties": {
    "target_membership": {
      "description": "The nodes that should be in the cluster after the modification. The nodes that must be added or removed are implicitly derived from the target membership and the current membership of the cluster.",
      "type": "object",
      "properties": {
        "node_ips_and_fault_domains": {
          "type": "array",
          "items": {
            "description": "The IP addresses and fault domains of the nodes in the cluster.",
            "type": "object",
            "properties": {
              "node_ip": {
                "description": "node_ip",
                "type": "string"
              },
              "fault_domain_id": {
                "description": "fault_domain_id",

```

```
    "type": "number"  
  }  
}  
}  
}  
}  
}  
}  
}  
}
```

Response

Codes

Code	Description
202	Return value on success

cluster/object-backed/nodes/dry-run

Endpoint

/v2/cluster/object-backed/nodes/dry-run

POST

Validate a node-add, node-remove, or node replacement operation and, if it succeeds, return the projected fault domain counts.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_object_backed_nodes_modify_request_v2",
  "type": "object",
  "properties": {
    "target_membership": {
      "description": "The nodes that should be in the cluster after the modification. The nodes that must be added or removed are implicitly derived from the target membership and the current membership of the cluster.",
      "type": "object",
      "properties": {
        "node_ips_and_fault_domains": {
          "type": "array",
          "items": {
            "description": "The IP addresses and fault domains of the nodes in the cluster.",
            "type": "object",
            "properties": {
              "node_ip": {
                "description": "node_ip",
                "type": "string"
              },
              "fault_domain_id": {
                "description": "fault_domain_id",
                "type": "number"
              }
            }
          }
        }
      }
    }
  }
}
```

```

    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_cluster_object_backed_modify_dry_run_response",
  "type": "object",
  "properties": {
    "target_membership": {
      "type": "array",
      "items": {
        "description": "The IP addresses and fault domains of the nodes that should be in the cluster after the modification.",
        "type": "object",
        "properties": {
          "node_ip": {
            "description": "node_ip",
            "type": "string"
          },
          "fault_domain_id": {
            "description": "fault_domain_id",
            "type": "number"
          }
        }
      }
    },
    "current_membership": {
      "type": "array",
      "items": {
        "description": "The nodes that are currently in the cluster.",
        "type": "object",
        "properties": {
          "node_id": {

```

```

        "description": "node_id",
        "type": "number"
    },
    "node_ip": {
        "description": "node_ip",
        "type": "string"
    },
    "fault_domain_id": {
        "description": "fault_domain_id",
        "type": "number"
    }
}
},
"nodes_being_added": {
    "type": "array",
    "items": {
        "description": "The IP addresses of the nodes that are being added to the cluster during the modification.",
        "type": "object",
        "properties": {
            "node_ip": {
                "description": "node_ip",
                "type": "string"
            },
            "fault_domain_id": {
                "description": "fault_domain_id",
                "type": "number"
            }
        }
    }
},
"nodes_being_removed": {
    "type": "array",
    "items": {
        "description": "The nodes that are being removed from the cluster during the modification.",
        "type": "object",
        "properties": {
            "node_id": {
                "description": "node_id",
                "type": "number"
            },
            "node_ip": {
                "description": "node_ip",
                "type": "string"
            }
        }
    }
}
}

```

```
    },  
    "fault_domain_id": {  
      "description": "fault_domain_id",  
      "type": "number"  
    }  
  }  
}  
}  
}
```

cluster/settings

Endpoint

/v1/cluster/settings

GET

Returns cluster settings.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_cluster_name_settings",
  "type": "object",
  "properties": {
    "cluster_name": {
      "description": "Name of the cluster",
      "type": "string"
    }
  }
}
```

PUT

Set the name of the cluster

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_cluster_name_settings",
  "type": "object",
  "properties": {
    "cluster_name": {
      "description": "Name of the cluster",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_cluster_name_settings",
  "type": "object",
  "properties": {
    "cluster_name": {
      "description": "Name of the cluster",
      "type": "string"
    }
  }
}
```

cluster/settings/ssl

Endpoint

/v1/cluster/settings/ssl

PUT

Set the SSL certificates used by the cluster. Mostly used for HTTP traffic.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_ssl_settings",
  "type": "object",
  "properties": {
    "certificate": {
      "description": "Public certificate for the cluster in PEM format",
      "type": "string"
    },
    "private_key": {
      "description": "Private key for the cluster in PEM format",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

cluster/settings/ssl/ca-certificate

Endpoint

/v2/cluster/settings/ssl/ca-certificate

GET

Get the SSL certificate authority the cluster trusts when authenticating outbound connections.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_cluster_ssl_ca_certificate_settings",
  "type": "object",
  "properties": {
    "ca_certificate": {
      "description": "Public certificate of the certificate authority to trust for o
utbound connections",
      "type": "string"
    }
  }
}
```

PUT

Set the SSL certificate authority the cluster trusts when authenticating outbound connections.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_cluster_ssl_ca_certificate_settings",
  "type": "object",
  "properties": {
    "ca_certificate": {
      "description": "Public certificate of the certificate authority to trust for o
utbound connections",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_cluster_ssl_ca_certificate_settings",
  "type": "object",
  "properties": {
    "ca_certificate": {
      "description": "Public certificate of the certificate authority to trust for o
utbound connections",
      "type": "string"
    }
  }
}
```

DELETE

Delete the SSL certificate authority the cluster trusts when authenticating outbound connections.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

cluster/settings/ssl/certificate

Endpoint

/v2/cluster/settings/ssl/certificate

PUT

Set the SSL certificates used by the cluster to authenticate its own identity.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_cluster_ssl_settings",
  "type": "object",
  "properties": {
    "certificate": {
      "description": "Public certificate for the cluster in PEM format",
      "type": "string"
    },
    "private_key": {
      "description": "Private key for the cluster in PEM format",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

cluster/settings/ssl/ciphers

Endpoint

/v2/cluster/settings/ssl/ciphers

GET

Get the SSL cipher suites that are accepted for TLS 1.2 and TLS 1.3 connections.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_cluster_ssl_ciphers",
  "type": "object",
  "properties": {
    "tls_1_2": {
      "type": "array",
      "items": {
        "description": "Cipher suites for the TLS 1.2 protocol",
        "type": "string"
      }
    },
    "tls_1_3": {
      "type": "array",
      "items": {
        "description": "Cipher suites for the TLS 1.3 protocol",
        "type": "string"
      }
    }
  }
}
```

PUT

Set the SSL cipher suites that are accepted for TLS 1.2 and TLS 1.3 connections. Note that ciphers required by Qumulo Core to function cannot be removed.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_cluster_ssl_ciphers",
  "type": "object",
  "properties": {
    "tls_1_2": {
      "type": "array",
      "items": {
        "description": "Cipher suites for the TLS 1.2 protocol",
        "type": "string"
      }
    },
    "tls_1_3": {
      "type": "array",
      "items": {
        "description": "Cipher suites for the TLS 1.3 protocol",
        "type": "string"
      }
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_cluster_ssl_ciphers",
  "type": "object",
  "properties": {
    "tls_1_2": {
      "type": "array",
      "items": {
        "description": "Cipher suites for the TLS 1.2 protocol",
        "type": "string"
      }
    },
    "tls_1_3": {
      "type": "array",
      "items": {
        "description": "Cipher suites for the TLS 1.3 protocol",
        "type": "string"
      }
    }
  }
}
```

cluster/slots/

Endpoint

/v1/cluster/slots/

GET

List slots.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_disk_slot",
    "type": "object",
    "properties": {
      "id": {
        "description": "Node:Slot representation identifying the slot",
        "type": "string"
      },
      "node_id": {
        "description": "Integer ID of the node containing the slot.",
        "type": "number"
      },
      "slot": {
        "description": "Integer ID of slot on the given node",
        "type": "number"
      },
      "state": {
        "type": "string",
        "enum": [
          "empty",

```

```

        "healthy",
        "missing",
        "dead",
        "wrong_node",
        "wrong_cluster",
        "wrong_version"
    ],
    "description": "Disk slot state (healthy, dead, empty):\n * `dead` - API_DEVICE_UI_STATE_DEAD,\n * `empty` - API_DEVICE_UI_STATE_EMPTY,\n * `healthy` - API_DEVICE_UI_STATE_HEALTHY,\n * `missing` - API_DEVICE_UI_STATE_MISSING,\n * `wrong_cluster` - API_DEVICE_UI_STATE_WRONG_CLUSTER,\n * `wrong_node` - API_DEVICE_UI_STATE_WRONG_NODE,\n * `wrong_version` - API_DEVICE_UI_STATE_WRONG_VERSION"
},
"slot_type": {
    "type": "string",
    "enum": [
        "SSD",
        "HDD",
        "Premium Page Blob",
        "Standard Page Blob",
        "Ephemeral SSD",
        "Write Tier SSD"
    ],
    "description": "Device type for slot (SSD, HDD):\n * `Ephemeral SSD` - API_DEVICE_SLOT_TYPE_EPHEMERAL_SSD,\n * `HDD` - API_DEVICE_SLOT_TYPE_SPINNING_DISK,\n * `Premium Page Blob` - API_DEVICE_SLOT_TYPE_PREMIUM_PAGE_BLOB,\n * `SSD` - API_DEVICE_SLOT_TYPE_SSD,\n * `Standard Page Blob` - API_DEVICE_SLOT_TYPE_STANDARD_PAGE_BLOB,\n * `Write Tier SSD` - API_DEVICE_SLOT_TYPE_WRITE_TIER_SSD"
},
"disk_type": {
    "type": "string",
    "enum": [
        "",
        "DEVICE_MEDIA_TYPE_UNKNOWN",
        "SSD",
        "HDD",
        "Premium Page Blob",
        "Standard Page Blob",
        "Ephemeral SSD",
        "Write Tier SSD"
    ],
    "description": "Type of disk, if present (SSD, HDD):\n * `` - API_DEVICE_MEDIA_TYPE_MISSING,\n * `DEVICE_MEDIA_TYPE_UNKNOWN` - API_DEVICE_MEDIA_TYPE_UNKNOWN,\n * `Ephemeral SSD` - The device type of a disk used for the read cache on object-backed clusters,\n * `HDD` - API_DEVICE_MEDIA_TYPE_SPINNING_DISK,\n * `Premium Page Blob` - API_DEVICE_MEDIA_TYPE_PREMIUM_PAGE_BLOB,\n * `SSD` - API_DEVICE_MEDIA_TYPE_SS

```


D,\n * `Standard Page Blob` - API_DEVICE_MEDIA_TYPE_STANDARD_PAGE_BLOB,\n * `Write Tier SSD` - The device type of a disk used for the write cache on object-backed clusters"

```
    },
    "disk_model": {
      "description": "Disk model (empty if no disk)",
      "type": "string"
    },
    "disk_serial_number": {
      "description": "Serial number of this disk (empty if no disk)",
      "type": "string"
    },
    "capacity": {
      "description": "Capacity in bytes (0 if slot is empty)",
      "type": "string"
    },
    "raw_capacity": {
      "description": "Raw capacity in bytes (0 if slot is empty)",
      "type": "string"
    },
    "slot_command_capacity": {
      "description": "The number of in-flight I/Os this device can handle.",
      "type": "number"
    },
    "minimum_raw_capacity": {
      "description": "Minimum raw capacity in bytes for slot",
      "type": "string"
    },
    "high_endurance": {
      "description": "Is this device a high endurance model",
      "type": "boolean"
    },
    "drive_bay": {
      "description": "Drive bay label",
      "type": "string"
    },
    "led_pattern": {
      "type": "string",
      "enum": [
        "LED_PATTERN_NORMAL",
        "LED_PATTERN_LOCATE",
        "LED_PATTERN_FAILURE"
      ],
      "description": "Current state of the slot's LED:\n * `LED_PATTERN_FAILURE` - failure,\n * `LED_PATTERN_LOCATE` - locate,\n * `LED_PATTERN_NORMAL` - normal"
    }
  }
```

```
}  
}  
}
```

cluster/slots/node/{node_id}

Endpoint

/v1/cluster/slots/node/{node_id}

GET

Retrieve info about the node's disk slots

Parameters

Name	Description	Required
node_id	The unique ID of the node	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_disk_slot",
    "type": "object",
    "properties": {
      "id": {
        "description": "Node:Slot representation identifying the slot",
        "type": "string"
      },
      "node_id": {
        "description": "Integer ID of the node containing the slot.",
        "type": "number"
      },
      "slot": {
        "description": "Integer ID of slot on the given node",
        "type": "number"
      },
      "state": {
```

```

    "type": "string",
    "enum": [
        "empty",
        "healthy",
        "missing",
        "dead",
        "wrong_node",
        "wrong_cluster",
        "wrong_version"
    ],
    "description": "Disk slot state (healthy, dead, empty):\n * `dead` - API_DEVICE_UI_STATE_DEAD,\n * `empty` - API_DEVICE_UI_STATE_EMPTY,\n * `healthy` - API_DEVICE_UI_STATE_HEALTHY,\n * `missing` - API_DEVICE_UI_STATE_MISSING,\n * `wrong_cluster` - API_DEVICE_UI_STATE_WRONG_CLUSTER,\n * `wrong_node` - API_DEVICE_UI_STATE_WRONG_NODE,\n * `wrong_version` - API_DEVICE_UI_STATE_WRONG_VERSION"
},
    "slot_type": {
        "type": "string",
        "enum": [
            "SSD",
            "HDD",
            "Premium Page Blob",
            "Standard Page Blob",
            "Ephemeral SSD",
            "Write Tier SSD"
        ],
        "description": "Device type for slot (SSD, HDD):\n * `Ephemeral SSD` - API_DEVICE_SLOT_TYPE_EPHEMERAL_SSD,\n * `HDD` - API_DEVICE_SLOT_TYPE_SPINNING_DISK,\n * `Premium Page Blob` - API_DEVICE_SLOT_TYPE_PREMIUM_PAGE_BLOB,\n * `SSD` - API_DEVICE_SLOT_TYPE_SSD,\n * `Standard Page Blob` - API_DEVICE_SLOT_TYPE_STANDARD_PAGE_BLOB,\n * `Write Tier SSD` - API_DEVICE_SLOT_TYPE_WRITE_TIER_SSD"
    },
    "disk_type": {
        "type": "string",
        "enum": [
            "",
            "DEVICE_MEDIA_TYPE_UNKNOWN",
            "SSD",
            "HDD",
            "Premium Page Blob",
            "Standard Page Blob",
            "Ephemeral SSD",
            "Write Tier SSD"
        ],
        "description": "Type of disk, if present (SSD, HDD):\n * `` - API_DEVICE_MEDIA_TYPE_MISSING,\n * `DEVICE_MEDIA_TYPE_UNKNOWN` - API_DEVICE_MEDIA_TYPE_UNKNOWN,\n"
    }
}

```

* `Ephemeral SSD` - The device type of a disk used for the read cache on object-backed clusters,\n * `HDD` - API_DEVICE_MEDIA_TYPE_SPINNING_DISK,\n * `Premium Page Blob` - API_DEVICE_MEDIA_TYPE_PREMIUM_PAGE_BLOB,\n * `SSD` - API_DEVICE_MEDIA_TYPE_SSD,\n * `Standard Page Blob` - API_DEVICE_MEDIA_TYPE_STANDARD_PAGE_BLOB,\n * `Write Tier SSD` - The device type of a disk used for the write cache on object-backed clusters"

```
,
"disk_model": {
  "description": "Disk model (empty if no disk)",
  "type": "string"
},
"disk_serial_number": {
  "description": "Serial number of this disk (empty if no disk)",
  "type": "string"
},
"capacity": {
  "description": "Capacity in bytes (0 if slot is empty)",
  "type": "string"
},
"raw_capacity": {
  "description": "Raw capacity in bytes (0 if slot is empty)",
  "type": "string"
},
"slot_command_capacity": {
  "description": "The number of in-flight I/Os this device can handle.",
  "type": "number"
},
"minimum_raw_capacity": {
  "description": "Minimum raw capacity in bytes for slot",
  "type": "string"
},
"high_endurance": {
  "description": "Is this device a high endurance model",
  "type": "boolean"
},
"drive_bay": {
  "description": "Drive bay label",
  "type": "string"
},
"led_pattern": {
  "type": "string",
  "enum": [
    "LED_PATTERN_NORMAL",
    "LED_PATTERN_LOCATE",
    "LED_PATTERN_FAILURE"
  ],
}
```

```
        "description": "Current state of the slot's LED:\n * `LED_PATTERN_FAILURE`\n - failure,\n * `LED_PATTERN_LOCATE` - locate,\n * `LED_PATTERN_NORMAL` - normal"\n    }\n}\n}
```

cluster/slots/{id}

Endpoint

/v1/cluster/slots/{id}

GET

Retrieve info about the disk slot, such as its capacity, type, model, etc.

Parameters

Name	Description	Required
id	The unique ID of the disk slot	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_disk_slot",
  "type": "object",
  "properties": {
    "id": {
      "description": "Node:Slot representation identifying the slot",
      "type": "string"
    },
    "node_id": {
      "description": "Integer ID of the node containing the slot.",
      "type": "number"
    },
    "slot": {
      "description": "Integer ID of slot on the given node",
      "type": "number"
    },
    "state": {
      "type": "string",
      "enum": [
```

```

        "empty",
        "healthy",
        "missing",
        "dead",
        "wrong_node",
        "wrong_cluster",
        "wrong_version"
    ],
    "description": "Disk slot state (healthy, dead, empty):\n * `dead` - API_DEVICE_UI_STATE_DEAD,\n * `empty` - API_DEVICE_UI_STATE_EMPTY,\n * `healthy` - API_DEVICE_UI_STATE_HEALTHY,\n * `missing` - API_DEVICE_UI_STATE_MISSING,\n * `wrong_cluster` - API_DEVICE_UI_STATE_WRONG_CLUSTER,\n * `wrong_node` - API_DEVICE_UI_STATE_WRONG_NODE,\n * `wrong_version` - API_DEVICE_UI_STATE_WRONG_VERSION"
},
"slot_type": {
    "type": "string",
    "enum": [
        "SSD",
        "HDD",
        "Premium Page Blob",
        "Standard Page Blob",
        "Ephemeral SSD",
        "Write Tier SSD"
    ],
    "description": "Device type for slot (SSD, HDD):\n * `Ephemeral SSD` - API_DEVICE_SLOT_TYPE_EPHEMERAL_SSD,\n * `HDD` - API_DEVICE_SLOT_TYPE_SPINNING_DISK,\n * `Premium Page Blob` - API_DEVICE_SLOT_TYPE_PREMIUM_PAGE_BLOB,\n * `SSD` - API_DEVICE_SLOT_TYPE_SSD,\n * `Standard Page Blob` - API_DEVICE_SLOT_TYPE_STANDARD_PAGE_BLOB,\n * `Write Tier SSD` - API_DEVICE_SLOT_TYPE_WRITE_TIER_SSD"
},
"disk_type": {
    "type": "string",
    "enum": [
        "",
        "DEVICE_MEDIA_TYPE_UNKNOWN",
        "SSD",
        "HDD",
        "Premium Page Blob",
        "Standard Page Blob",
        "Ephemeral SSD",
        "Write Tier SSD"
    ],
    "description": "Type of disk, if present (SSD, HDD):\n * `` - API_DEVICE_MEDIA_TYPE_MISSING,\n * `DEVICE_MEDIA_TYPE_UNKNOWN` - API_DEVICE_MEDIA_TYPE_UNKNOWN,\n * `Ephemeral SSD` - The device type of a disk used for the read cache on object-backed clusters,\n * `HDD` - API_DEVICE_MEDIA_TYPE_SPINNING_DISK,\n * `Premium Page Blo

```



```

b` - API_DEVICE_MEDIA_TYPE_PREMIUM_PAGE_BLOB,\n * `SSD` - API_DEVICE_MEDIA_TYPE_SS
D,\n * `Standard Page Blob` - API_DEVICE_MEDIA_TYPE_STANDARD_PAGE_BLOB,\n * `Write T
ier SSD` - The device type of a disk used for the write cache on object-backed clust
ers"
},
"disk_model": {
  "description": "Disk model (empty if no disk)",
  "type": "string"
},
"disk_serial_number": {
  "description": "Serial number of this disk (empty if no disk)",
  "type": "string"
},
"capacity": {
  "description": "Capacity in bytes (0 if slot is empty)",
  "type": "string"
},
"raw_capacity": {
  "description": "Raw capacity in bytes (0 if slot is empty)",
  "type": "string"
},
"slot_command_capacity": {
  "description": "The number of in-flight I/Os this device can handle.",
  "type": "number"
},
"minimum_raw_capacity": {
  "description": "Minimum raw capacity in bytes for slot",
  "type": "string"
},
"high_endurance": {
  "description": "Is this device a high endurance model",
  "type": "boolean"
},
"drive_bay": {
  "description": "Drive bay label",
  "type": "string"
},
"led_pattern": {
  "type": "string",
  "enum": [
    "LED_PATTERN_NORMAL",
    "LED_PATTERN_LOCATE",
    "LED_PATTERN_FAILURE"
  ],
  "description": "Current state of the slot's LED:\n * `LED_PATTERN_FAILURE` - f
ailure,\n * `LED_PATTERN_LOCATE` - locate,\n * `LED_PATTERN_NORMAL` - normal"

```

```
}  
}  
}
```

PATCH

Control the slot's locate LED.

Parameters

Name	Description	Required
<code>id</code>	The unique ID of the disk slot	Yes

Request

Schema

```
{  
  "description": "api_disk_slot_patch",  
  "type": "object",  
  "properties": {  
    "led_pattern": {  
      "type": "string",  
      "enum": [  
        "LED_PATTERN_NORMAL",  
        "LED_PATTERN_LOCATE",  
        "LED_PATTERN_FAILURE"  
      ],  
      "description": "led_pattern:\n * `LED_PATTERN_FAILURE` - failure,\n * `LED_PATTERN_LOCATE` - locate,\n * `LED_PATTERN_NORMAL` - normal"  
    }  
  }  
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_disk_slot",
  "type": "object",
  "properties": {
    "id": {
      "description": "Node:Slot representation identifying the slot",
      "type": "string"
    },
    "node_id": {
      "description": "Integer ID of the node containing the slot.",
      "type": "number"
    },
    "slot": {
      "description": "Integer ID of slot on the given node",
      "type": "number"
    },
    "state": {
      "type": "string",
      "enum": [
        "empty",
        "healthy",
        "missing",
        "dead",
        "wrong_node",
        "wrong_cluster",
        "wrong_version"
      ],
      "description": "Disk slot state (healthy, dead, empty):\n * `dead` - API_DEVICE_UI_STATE_DEAD,\n * `empty` - API_DEVICE_UI_STATE_EMPTY,\n * `healthy` - API_DEVICE_UI_STATE_HEALTHY,\n * `missing` - API_DEVICE_UI_STATE_MISSING,\n * `wrong_cluster` - API_DEVICE_UI_STATE_WRONG_CLUSTER,\n * `wrong_node` - API_DEVICE_UI_STATE_WRONG_NODE,\n * `wrong_version` - API_DEVICE_UI_STATE_WRONG_VERSION"
    },
    "slot_type": {
      "type": "string",
      "enum": [
        "SSD",
        "HDD",
        "Premium Page Blob",
        "Standard Page Blob",
        "Ephemeral SSD",
        "Write Tier SSD"
      ],
      "description": "Device type for slot (SSD, HDD):\n * `Ephemeral SSD` - API_DEV
```

```

ICE_SLOT_TYPE_EPHEMERAL_SSD,\n * `HDD` - API_DEVICE_SLOT_TYPE_SPINNING_DISK,\n * `Premium Page Blob` - API_DEVICE_SLOT_TYPE_PREMIUM_PAGE_BLOB,\n * `SSD` - API_DEVICE_SLOT_TYPE_SSD,\n * `Standard Page Blob` - API_DEVICE_SLOT_TYPE_STANDARD_PAGE_BLOB,\n * `Write Tier SSD` - API_DEVICE_SLOT_TYPE_WRITE_TIER_SSD"
},
"disk_type": {
  "type": "string",
  "enum": [
    "",
    "DEVICE_MEDIA_TYPE_UNKNOWN",
    "SSD",
    "HDD",
    "Premium Page Blob",
    "Standard Page Blob",
    "Ephemeral SSD",
    "Write Tier SSD"
  ],
  "description": "Type of disk, if present (SSD, HDD):\n * `` - API_DEVICE_MEDIA_TYPE_MISSING,\n * `DEVICE_MEDIA_TYPE_UNKNOWN` - API_DEVICE_MEDIA_TYPE_UNKNOWN,\n * `Ephemeral SSD` - The device type of a disk used for the read cache on object-backed clusters,\n * `HDD` - API_DEVICE_MEDIA_TYPE_SPINNING_DISK,\n * `Premium Page Blob` - API_DEVICE_MEDIA_TYPE_PREMIUM_PAGE_BLOB,\n * `SSD` - API_DEVICE_MEDIA_TYPE_SSD,\n * `Standard Page Blob` - API_DEVICE_MEDIA_TYPE_STANDARD_PAGE_BLOB,\n * `Write Tier SSD` - The device type of a disk used for the write cache on object-backed clusters"
},
"disk_model": {
  "description": "Disk model (empty if no disk)",
  "type": "string"
},
"disk_serial_number": {
  "description": "Serial number of this disk (empty if no disk)",
  "type": "string"
},
"capacity": {
  "description": "Capacity in bytes (0 if slot is empty)",
  "type": "string"
},
"raw_capacity": {
  "description": "Raw capacity in bytes (0 if slot is empty)",
  "type": "string"
},
"slot_command_capacity": {
  "description": "The number of in-flight I/Os this device can handle.",
  "type": "number"
},
},

```

```

"minimum_raw_capacity": {
  "description": "Minimum raw capacity in bytes for slot",
  "type": "string"
},
"high_endurance": {
  "description": "Is this device a high endurance model",
  "type": "boolean"
},
"drive_bay": {
  "description": "Drive bay label",
  "type": "string"
},
"led_pattern": {
  "type": "string",
  "enum": [
    "LED_PATTERN_NORMAL",
    "LED_PATTERN_LOCATE",
    "LED_PATTERN_FAILURE"
  ],
  "description": "Current state of the slot's LED:\n * `LED_PATTERN_FAILURE` - failure,\n * `LED_PATTERN_LOCATE` - locate,\n * `LED_PATTERN_NORMAL` - normal"
}
}
}

```

dns/configs/system

Endpoint

/v1/dns/configs/system

GET

Get the system's DNS configuration.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_dns_config",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this DNS configuration.",
      "type": "number"
    },
    "dns_servers": {
      "type": "array",
      "items": {
        "description": "The list of DNS servers associated with this DNS configuration.",
        "type": "string"
      }
    },
    "dns_search_domains": {
      "type": "array",
      "items": {
        "description": "The list of DNS search domains associated with this DNS configuration.",
        "type": "string"
      }
    }
  }
}
```

```

    }
  },
  "lookup_overrides": {
    "type": "array",
    "items": {
      "description": "The list of DNS lookup overrides associated with this DNS configuration.",
      "type": "object",
      "properties": {
        "ip_address": {
          "description": "ip_address",
          "type": "string"
        },
        "aliases": {
          "type": "array",
          "items": {
            "description": "aliases",
            "type": "string"
          }
        }
      }
    }
  }
}

```

PATCH

Update the system's DNS configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_system_dns_config_patch",
  "type": "object",
  "properties": {
    "dns_servers": {

```

```

    "type": "array",
    "items": {
      "description": "The list of DNS servers associated with this DNS configuration.",
      "type": "string"
    }
  },
  "dns_search_domains": {
    "type": "array",
    "items": {
      "description": "The list of DNS search domains associated with this DNS configuration.",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_dns_config",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this DNS configuration.",
      "type": "number"
    },
    "dns_servers": {
      "type": "array",
      "items": {
        "description": "The list of DNS servers associated with this DNS configuration.",
        "type": "string"
      }
    },
    "dns_search_domains": {

```



```

    "type": "array",
    "items": {
      "description": "The list of DNS search domains associated with this DNS configuration.",
      "type": "string"
    }
  },
  "lookup_overrides": {
    "type": "array",
    "items": {
      "description": "The list of DNS lookup overrides associated with this DNS configuration.",
      "type": "object",
      "properties": {
        "ip_address": {
          "description": "ip_address",
          "type": "string"
        },
        "aliases": {
          "type": "array",
          "items": {
            "description": "aliases",
            "type": "string"
          }
        }
      }
    }
  }
}

```

dns/clear-dns-cache

Endpoint

/v1/dns/clear-dns-cache

POST

Clears the Qumulo local DNS cache

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_dns_clear_cache",
  "type": "object",
  "properties": {
    "dns_config_id": {
      "description": "dns_config_id",
      "type": "number"
    },
    "skip_reverse_cache": {
      "description": "When true, reverse lookup results will not be cleared from the cache.",
      "type": "boolean"
    },
    "skip_forward_cache": {
      "description": "When true, forward lookup results will not be cleared from the cache.",
      "type": "boolean"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

dns/lookup-override-config

Endpoint

/v1/dns/lookup-override-config

GET

List the DNS lookup overrides configured on the cluster. These rules override any lookup results from the configured DNS servers and serve as static mappings between IP address and hostname

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_dns_lookup_override_config",
  "type": "object",
  "properties": {
    "lookup_overrides": {
      "type": "array",
      "items": {
        "description": "lookup_overrides",
        "type": "object",
        "properties": {
          "ip_address": {
            "description": "ip_address",
            "type": "string"
          },
          "aliases": {
            "type": "array",
            "items": {
              "description": "aliases",
              "type": "string"
            }
          }
        }
      }
    }
  }
}
```

```

    }
  }
}
}
}
}

```

PUT

Overwrite the DNS lookup overrides configured on the cluster. These rules override any lookup results from the configured DNS servers and serve as static mappings between IP address and hostname

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_dns_lookup_override_config",
  "type": "object",
  "properties": {
    "lookup_overrides": {
      "type": "array",
      "items": {
        "description": "lookup_overrides",
        "type": "object",
        "properties": {
          "ip_address": {
            "description": "ip_address",
            "type": "string"
          },
          "aliases": {
            "type": "array",
            "items": {
              "description": "aliases",
              "type": "string"
            }
          }
        }
      }
    }
  }
}

```

```
}
  }
}
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_dns_lookup_override_config",
  "type": "object",
  "properties": {
    "lookup_overrides": {
      "type": "array",
      "items": {
        "description": "lookup_overrides",
        "type": "object",
        "properties": {
          "ip_address": {
            "description": "ip_address",
            "type": "string"
          },
          "aliases": {
            "type": "array",
            "items": {
              "description": "aliases",
              "type": "string"
            }
          }
        }
      }
    }
  }
}
```

dns/resolve/

Endpoint

/v1/dns/resolve/

POST

Deprecated. Use /v1/dns/resolve-ips-to-names instead.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_resolved_ip",
    "type": "object",
    "properties": {
      "ip_address": {
        "description": "The IP address which was resolved",
        "type": "string"
      }
    },
  },
}
```

```

    "hostname": {
      "description": "The resolved name of the IP address",
      "type": "string"
    },
    "result": {
      "type": "string",
      "enum": [
        "OK",
        "ERROR",
        "NOT_FOUND",
        "TIMEOUT"
      ],
      "description": "The status of the resolution:\n * `ERROR` - An error occurred while resolving the hostname,\n * `NOT_FOUND` - No hostname was found for the IP address,\n * `OK` - The hostname for the IP address was successfully resolved,\n * `TIMEOUT` - Timeout occurred before this address was resolved"
    }
  }
}

```

dns/resolve-ips-to-names

Endpoint

/v1/dns/resolve-ips-to-names

POST

Resolve a list of IP addresses to canonical hostnames.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_resolved_ip",
    "type": "object",
    "properties": {
      "ip_address": {
        "description": "The IP address which was resolved",
        "type": "string"
      }
    }
  }
}
```



```

    "hostname": {
      "description": "The resolved name of the IP address",
      "type": "string"
    },
    "result": {
      "type": "string",
      "enum": [
        "OK",
        "ERROR",
        "NOT_FOUND",
        "TIMEOUT"
      ],
      "description": "The status of the resolution:\n * `ERROR` - An error occurred while resolving the hostname,\n * `NOT_FOUND` - No hostname was found for the IP address,\n * `OK` - The hostname for the IP address was successfully resolved,\n * `TIMEOUT` - Timeout occurred before this address was resolved"
    }
  }
}

```

dns/resolve-names-to-ips

Endpoint

/v1/dns/resolve-names-to-ips

POST

Resolve a list of hostnames to their set of associated IP addresses.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_resolved_hostname",
    "type": "object",
    "properties": {
      "hostname": {
        "description": "The hostname which was resolved",
        "type": "string"
      }
    }
  }
}
```

```

    "ip_addresses": {
      "type": "array",
      "items": {
        "description": "The IP addresses to which the hostname resolved",
        "type": "string"
      }
    },
    "result": {
      "type": "string",
      "enum": [
        "OK",
        "ERROR",
        "NOT_FOUND",
        "TIMEOUT"
      ],
      "description": "The status of the resolution:\n * `ERROR` - An error occurred while resolving the hostname,\n * `NOT_FOUND` - No hostname was found for the IP address,\n * `OK` - The hostname for the IP address was successfully resolved,\n * `TIMEOUT` - Timeout occurred before this address was resolved"
    }
  }
}

```

files/quotas/

Endpoint

/v1/files/quotas/

GET

List all set directory quotas.

Parameters

Name	Description	Required
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_quota_entries",
  "type": "object",
  "properties": {
    "quotas": {
      "type": "array",
      "items": {
        "description": "quotas",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique ID of this directory.",
            "type": "string"
          },
          "limit": {
            "description": "Limit in bytes of the cumulative size of this directory"
          }
        }
      }
    }
  }
}
```

```

and its descendants.",
    "type": "string"
  }
}
}
}
}
}
}
}
}
}

```

POST

Add a directory quota.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "api_files_quota",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique ID of this directory.",
      "type": "string"
    },
    "limit": {
      "description": "Limit in bytes of the cumulative size of this directory and its descendants.",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_quota",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique ID of this directory.",
      "type": "string"
    },
    "limit": {
      "description": "Limit in bytes of the cumulative size of this directory and its descendants.",
      "type": "string"
    }
  }
}
```

files/quotas/status/

Endpoint

/v1/files/quotas/status/

GET

List all directory quotas and their corresponding directories' paths and cumulative sizes.

Parameters

Name	Description	Required
after	Return entries after the given key (keys are returned in the paging object)	No
limit	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_quota_status_entries",
  "type": "object",
  "properties": {
    "quotas": {
      "type": "array",
      "items": {
        "description": "quotas",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique ID of this directory.",
            "type": "string"
          },
          "path": {
            "description": "Full path of this directory.",
```


files/quotas/status/{id}

Endpoint

/v1/files/quotas/status/{id}

GET

Get the directory quota for a directory, its limit in bytes, and current capacity usage.

Parameters

Name	Description	Required
id	Directory ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_quota_status",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique ID of this directory.",
      "type": "string"
    },
    "path": {
      "description": "Full path of this directory.",
      "type": "string"
    },
    "limit": {
      "description": "Limit in bytes of the cumulative size of this directory and its descendants.",
      "type": "string"
    },
    "capacity_usage": {
      "description": "Capacity used by this directory and all of its children, in by
```

```
tes.",  
    "type": "string"  
  }  
}  
}
```

files/quotas/{id}

Endpoint

/v1/files/quotas/{id}

GET

Get the directory quota for a directory and its limit in bytes

Parameters

Name	Description	Required
id	Directory ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_quota",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique ID of this directory.",
      "type": "string"
    },
    "limit": {
      "description": "Limit in bytes of the cumulative size of this directory and its descendants.",
      "type": "string"
    }
  }
}
```

PUT

Modify the quota for a given directory.

Parameters

Name	Description	Required
<code>id</code>	Directory ID	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_files_quota",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique ID of this directory.",
      "type": "string"
    },
    "limit": {
      "description": "Limit in bytes of the cumulative size of this directory and its descendants.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_quota",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique ID of this directory.",
      "type": "string"
    }
  }
}
```

```
    },
    "limit": {
      "description": "Limit in bytes of the cumulative size of this directory and its descendants.",
      "type": "string"
    }
  }
}
```

DELETE

Delete the quota for a given directory.

Parameters

Name	Description	Required
<code>id</code>	Directory ID	Yes
<code>If-Match</code>	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

encryption/rotate-keys

Endpoint

/v1/encryption/rotate-keys

POST

Rotate the encryption at rest keys.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

encryption/status

Endpoint

/v1/encryption/status

GET

View the status of encryption at rest.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "encryption_status_api_response",
  "type": "object",
  "properties": {
    "status": {
      "type": "string",
      "enum": [
        "Encrypted",
        "Not Encrypted"
      ],
      "description": "Whether or not encryption at rest is enabled:\n * `Encrypted` - ENCRYPTION_STATUS_ENCRYPTED,\n * `Not Encrypted` - ENCRYPTION_STATUS_NOT_ENCRYPTED"
    },
    "last_key_rotation_time": {
      "description": "When encryption at rest is enabled, the time at which the current master key became active",
      "type": "string"
    }
  }
}
```

encryption/external-kms/keys/create

Endpoint

/v2/encryption/external-kms/keys/create

POST

Create a Key in the Key Management Server.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "encryption_api_v2_create_kmip_key",
  "type": "object",
  "properties": {
    "kms_config": {
      "description": "The Key Management Server server parameters. If this is omitted and a Key Management Server is already configured, the parameters from the existing configuration will be used. It is an error to omit this field if Key Management Server is not already configured on the cluster.",
      "type": "object",
      "properties": {
        "server_ca_cert": {
          "description": "The Certificate Authority certificate that Qumulo Core uses to validate the certificate that the Key Management Server presents to client TLS connections.",
          "type": "string"
        },
        "client_cert": {
          "description": "The client certificate that Qumulo Core uses to authenticate the cluster to the Key Management Server.",
          "type": "string"
        },
        "client_private_key": {
          "description": "The private key that corresponds to the specified client certificate.",
          "type": "string"
        },
        "hostname": {
          "description": "The hostname of the Key Management Server.",

```



```

        "type": "string"
    },
    "port": {
        "description": "The port number of the Key Management Server, 5696 by default.",
        "type": "number"
    }
},
"key_name": {
    "description": "The name of the key that will be created in the Key Management Server.",
    "type": "string"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
    "description": "encryption_api_v2_create_kmip_key_result",
    "type": "object",
    "properties": {
        "key_id": {
            "description": "The key id of the newly created key on the Key Management Server.",
            "type": "string"
        }
    }
}

```

encryption/key-store

Endpoint

/v2/encryption/key-store

GET

View the active at-rest encryption configuration.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "encryption_api_v2_key_store_response_union",
  "type": "object",
  "properties": {
    "type": {
      "type": "string",
      "enum": [
        "Local",
        "KMS"
      ],
      "description": "type:\n * `KMS` - ENCRYPTION_TYPE_KMS,\n * `Local` - ENCRYPTION_TYPE_LOCAL"
    },
    "local_store": {
      "description": "Value present when type is ENCRYPTION_TYPE_LOCAL.",
      "type": "object",
      "properties": {
        "status": {
          "type": "string",
          "enum": [
            "Encrypted",
            "Not Encrypted"
          ]
        }
      }
    }
  }
}
```

```

    ],
    "description": "Whether or not encryption at rest is enabled:\n * `Encrypted` - ENCRYPTION_STATUS_ENCRYPTED,\n * `Not Encrypted` - ENCRYPTION_STATUS_NOT_ENCRYPTED"
  }
},
"kms_store": {
  "description": "Value present when type is ENCRYPTION_TYPE_KMS.",
  "type": "object",
  "properties": {
    "hostname": {
      "description": "The hostname of the Key Management Server.",
      "type": "string"
    },
    "port": {
      "description": "The port number of the Key Management Server, 5696 by default.",
      "type": "number"
    },
    "key_id": {
      "description": "The unique ID of the master key for at-rest encryption that is stored in the Key Management Server.",
      "type": "string"
    },
    "config_creation_time": {
      "description": "The time at which the current configuration became active.",
      "type": "string"
    }
  }
}
}
}
}

```

PUT

Update the active at-rest encryption configuration.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "encryption_api_v2_put_key_store_union",
  "type": "object",
  "properties": {
    "type": {
      "type": "string",
      "enum": [
        "Local",
        "KMS"
      ],
      "description": "type:\n * `KMS` - ENCRYPTION_TYPE_KMS,\n * `Local` - ENCRYPTION_TYPE_LOCAL"
    },
    "kms_store": {
      "description": "Value present when type is ENCRYPTION_TYPE_KMS.",
      "type": "object",
      "properties": {
        "server_ca_cert": {
          "description": "The Certificate Authority certificate that Qumulo Core uses to validate the certificate that the Key Management Server presents to client TLS connections.",
          "type": "string"
        },
        "client_cert": {
          "description": "The client certificate that Qumulo Core uses to authenticate the cluster to the Key Management Server.",
          "type": "string"
        },
        "client_private_key": {
          "description": "The private key that corresponds to the specified client certificate.",
          "type": "string"
        },
        "hostname": {
          "description": "The hostname of the Key Management Server.",
          "type": "string"
        },
        "port": {
          "description": "The port number of the Key Management Server, 5696 by default.",
          "type": "number"
        },
        "key_id": {
```

```
        "description": "The unique ID of the master key for at-rest encryption tha  
t is stored in the Key Management Server.",  
        "type": "string"  
    }  
}  
}  
}
```

Response

Codes

Code	Description
200	Return value on success

encryption/key-store/status

Endpoint

/v2/encryption/key-store/status

GET

View the status of at-rest encryption.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "encryption_api_v2_status_response",
  "type": "object",
  "properties": {
    "type": {
      "type": "string",
      "enum": [
        "Local",
        "KMS"
      ],
      "description": "Does the cluster connect to a Key Management Server?:\n * `KM\nS` - ENCRYPTION_TYPE_KMS,\n * `Local` - ENCRYPTION_TYPE_LOCAL"
    },
    "status": {
      "type": "string",
      "enum": [
        "Not Encrypted",
        "Encrypted",
        "Configuration Corrupted",
        "KMS Available",
        "KMS Authentication Error",
        "Cannot connect to KMS server."
      ]
    }
  }
}
```

```

        "KMS Key Not Found",
        "KMS Key Inactive"
    ],
    "description": "Is the Key Management Server accessible?:\n * `Cannot connect to KMS server.` - ENCRYPTION_CONFIG_STATUS_KMS_CANNOT_CONNECT,\n * `Configuration Corrupted` - ENCRYPTION_CONFIG_STATUS_CONFIG_CORRUPTED,\n * `Encrypted` - ENCRYPTION_CONFIG_STATUS_LOCAL,\n * `KMS Authentication Error` - ENCRYPTION_CONFIG_STATUS_KMS_AUTHENTICATION_ERROR,\n * `KMS Available` - ENCRYPTION_CONFIG_STATUS_KMS_AVAILABLE,\n * `KMS Key Inactive` - ENCRYPTION_CONFIG_STATUS_KMS_KEY_INACTIVE,\n * `KMS Key Not Found` - ENCRYPTION_CONFIG_STATUS_KMS_KEY_NOT_FOUND,\n * `Not Encrypted` - ENCRYPTION_CONFIG_STATUS_NOT_ENCRYPTED"
    },
    "ca_cert_expiry": {
        "description": "The expiry date for the Key Management Server Certificate Authority certificate.",
        "type": "string"
    },
    "client_cert_expiry": {
        "description": "The expiry date for the client certificate.",
        "type": "string"
    },
    "last_key_rotation_time": {
        "description": "The time at which the current encryption key became active.",
        "type": "string"
    },
    "last_status_update_time": {
        "description": "The time at which this status of the configuration was last updated.",
        "type": "string"
    }
}
}

```

encryption/rotate-keys

Endpoint

/v2/encryption/rotate-keys

POST

Rotate the encryption at rest keys.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_encryption_rotate_key_v2",
  "type": "object",
  "properties": {
    "key_id": {
      "description": "The unique ID of the master key for at-rest encryption that Qumulo Core uses if a Key Management Server is in use.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

/v0/ftp/settings

Endpoint

/v0/ftp/settings

GET

Retrieve the current FTP server settings. To see server status on all nodes, use Get FTP Server Status.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "ftp_api_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, the cluster allows FTP connections.",
      "type": "boolean"
    },
    "check_remote_host": {
      "description": "When enabled, the cluster ensures that all connections for a session come from the same host. Disabling this allows for FXP.",
      "type": "boolean"
    },
    "log_operations": {
      "description": "log_operations",
      "type": "boolean"
    },
    "chroot_users": {
      "description": "chroot_users",
      "type": "boolean"
    }
  }
}
```

```

"allow_unencrypted_connections": {
  "description": "allow_unencrypted_connections",
  "type": "boolean"
},
"expand_wildcards": {
  "description": "When enabled, LIST and NLST commands support posix-like shell
wild cards on the final directory component.",
  "type": "boolean"
},
"anonymous_user": {
  "description": "anonymous_user",
  "type": "object",
  "properties": {
    "id_type": {
      "type": "string",
      "enum": [
        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
      ],
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  }
},
"greeting": {
  "description": "Greeting to display with the 220 successful connection messag
e.",
  "type": "string"
}
}

```

PUT

Modify the current FTP server settings. To see server status on all nodes, use Get FTP Server

Status.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "ftp_api_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, the cluster allows FTP connections.",
      "type": "boolean"
    },
    "check_remote_host": {
      "description": "When enabled, the cluster ensures that all connections for a session come from the same host. Disabling this allows for FXP.",
      "type": "boolean"
    },
    "log_operations": {
      "description": "log_operations",
      "type": "boolean"
    },
    "chroot_users": {
      "description": "chroot_users",
      "type": "boolean"
    },
    "allow_unencrypted_connections": {
      "description": "allow_unencrypted_connections",
      "type": "boolean"
    },
    "expand_wildcards": {
      "description": "When enabled, LIST and NLST commands support posix-like shell wild cards on the final directory component.",
      "type": "boolean"
    },
    "anonymous_user": {
      "description": "anonymous_user",
      "type": "object",
      "properties": {
```

```

    "id_type": {
      "type": "string",
      "enum": [
        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
      ],
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  },
  "greeting": {
    "description": "Greeting to display with the 220 successful connection messag
e.",
    "type": "string"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "ftp_api_config",
  "type": "object",
  "properties": {

```

```

"enabled": {
  "description": "When enabled, the cluster allows FTP connections.",
  "type": "boolean"
},
"check_remote_host": {
  "description": "When enabled, the cluster ensures that all connections for a session come from the same host. Disabling this allows for FXP.",
  "type": "boolean"
},
"log_operations": {
  "description": "log_operations",
  "type": "boolean"
},
"chroot_users": {
  "description": "chroot_users",
  "type": "boolean"
},
"allow_unencrypted_connections": {
  "description": "allow_unencrypted_connections",
  "type": "boolean"
},
"expand_wildcards": {
  "description": "When enabled, LIST and NLST commands support posix-like shell wild cards on the final directory component.",
  "type": "boolean"
},
"anonymous_user": {
  "description": "anonymous_user",
  "type": "object",
  "properties": {
    "id_type": {
      "type": "string",
      "enum": [
        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
      ]
    },
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
  }
}

```

```

    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  },
  "greeting": {
    "description": "Greeting to display with the 220 successful connection message.",
    "type": "string"
  }
}

```

PATCH

Modify the current FTP server settings. To see server status on all nodes, use Get FTP Server Status.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "ftp_api_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, the cluster allows FTP connections.",
      "type": "boolean"
    },
    "check_remote_host": {
      "description": "When enabled, the cluster ensures that all connections for a session come from the same host. Disabling this allows for FXP.",
      "type": "boolean"
    },
    "log_operations": {
      "description": "log_operations",

```

```

    "type": "boolean"
  },
  "chroot_users": {
    "description": "chroot_users",
    "type": "boolean"
  },
  "allow_unencrypted_connections": {
    "description": "allow_unencrypted_connections",
    "type": "boolean"
  },
  "expand_wildcards": {
    "description": "When enabled, LIST and NLST commands support posix-like shell
wild cards on the final directory component.",
    "type": "boolean"
  },
  "anonymous_user": {
    "description": "anonymous_user",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ],
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
      },
      "id_value": {
        "description": "id_value",
        "type": "string"
      }
    }
  },
  "greeting": {
    "description": "Greeting to display with the 220 successful connection messag
e.",
    "type": "string"
  }

```

```
}  
}  
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{  
  "description": "ftp_api_config",  
  "type": "object",  
  "properties": {  
    "enabled": {  
      "description": "When enabled, the cluster allows FTP connections.",  
      "type": "boolean"  
    },  
    "check_remote_host": {  
      "description": "When enabled, the cluster ensures that all connections for a session come from the same host. Disabling this allows for FXP.",  
      "type": "boolean"  
    },  
    "log_operations": {  
      "description": "log_operations",  
      "type": "boolean"  
    },  
    "chroot_users": {  
      "description": "chroot_users",  
      "type": "boolean"  
    },  
    "allow_unencrypted_connections": {  
      "description": "allow_unencrypted_connections",  
      "type": "boolean"  
    },  
    "expand_wildcards": {  
      "description": "When enabled, LIST and NLST commands support posix-like shell wild cards on the final directory component.",  
      "type": "boolean"  
    },  
    "anonymous_user": {
```



```

    "description": "anonymous_user",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ],
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
      },
      "id_value": {
        "description": "id_value",
        "type": "string"
      }
    }
  },
  "greeting": {
    "description": "Greeting to display with the 220 successful connection messag
e.",
    "type": "string"
  }
}

```

/v0/ftp/status

Endpoint

/v0/ftp/status

GET

Retrieve the current FTP server settings and the status of the server on each node.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "ftp_status",
  "type": "object",
  "properties": {
    "settings": {
      "description": "The current FTP server settings.",
      "type": "object",
      "properties": {
        "enabled": {
          "description": "When enabled, the cluster allows FTP connections.",
          "type": "boolean"
        },
        "check_remote_host": {
          "description": "When enabled, the cluster ensures that all connections for a session come from the same host. Disabling this allows for FXP.",
          "type": "boolean"
        },
        "log_operations": {
          "description": "log_operations",
          "type": "boolean"
        },
        "chroot_users": {
```

```

        "description": "chroot_users",
        "type": "boolean"
    },
    "allow_unencrypted_connections": {
        "description": "allow_unencrypted_connections",
        "type": "boolean"
    },
    "expand_wildcards": {
        "description": "When enabled, LIST and NLST commands support posix-like shell wild cards on the final directory component.",
        "type": "boolean"
    },
    "anonymous_user": {
        "description": "anonymous_user",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",
                    "INTERNAL",
                    "QUMULO_OPERATOR",
                    "QUMULO_SUPPORT"
                ],
                "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
            },
            "id_value": {
                "description": "id_value",
                "type": "string"
            }
        }
    },
    "greeting": {
        "description": "Greeting to display with the 220 successful connection message.",
        "type": "string"
    }
}

```

```
"statuses": {  
  "type": "array",  
  "items": {  
    "description": "The current FTP server status on each node.",  
    "type": "object",  
    "properties": {  
      "node_id": {  
        "description": "node_id",  
        "type": "number"  
      },  
      "status": {  
        "description": "The status of the server on this node.",  
        "type": "string"  
      }  
    }  
  }  
}
```

file-system

Endpoint

/v1/file-system

GET

Retrieve general file system statistics.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_fs_attributes",
  "type": "object",
  "properties": {
    "block_size_bytes": {
      "description": "File system block size in bytes",
      "type": "number"
    },
    "total_size_bytes": {
      "description": "Total file system size in bytes",
      "type": "string"
    },
    "free_size_bytes": {
      "description": "Available file system size in bytes",
      "type": "string"
    },
    "snapshot_size_bytes": {
      "description": "Capacity used by all snapshots in bytes",
      "type": "string"
    },
    "portal_cache_size_bytes": {
      "description": "Capacity used by portal caching in bytes. Does not count again"
    }
  }
}
```

```
st free_size_bytes",  
    "type": "string"  
  }  
}  
}
```

file-system/security/keys/

Endpoint

/v1/file-system/security/keys/

GET

List the file system's public keys.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_change_lock_keys",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "A list of the key\u2019s properties.",
        "type": "object",
        "properties": {
          "id": {
            "description": "The identifier associated with the specified key.",
            "type": "string"
          },
          "name": {
            "description": "The unique name of the specified key.",
            "type": "string"
          },
          "comment": {
            "description": "A descriptive comment about the specified key.",
            "type": "string"
          }
        }
      }
    }
  }
}
```

```

    "disabled": {
      "description": "Specifies whether the key is disabled.",
      "type": "boolean"
    },
    "public_key": {
      "description": "The contents of the public key.",
      "type": "string"
    }
  }
}
}
}
}
}

```

POST

Register a new file system public key.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "api_change_lock_key_create_request",
  "type": "object",
  "properties": {
    "name": {
      "description": "The unique name of the specified key.",
      "type": "string"
    },
    "comment": {
      "description": "A descriptive comment about the specified key.",
      "type": "string"
    },
    "public_key": {
      "description": "The public key.",
      "type": "string"
    },
    "verification_signature": {
      "description": "The name of the key signed with the private key.",
      "type": "string"
    }
  }
}

```



```
}  
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{  
  "description": "api_change_lock_key",  
  "type": "object",  
  "properties": {  
    "id": {  
      "description": "The identifier associated with the specified key.",  
      "type": "string"  
    },  
    "name": {  
      "description": "The unique name of the specified key.",  
      "type": "string"  
    },  
    "comment": {  
      "description": "A descriptive comment about the specified key.",  
      "type": "string"  
    },  
    "disabled": {  
      "description": "Specifies whether the key is disabled.",  
      "type": "boolean"  
    },  
    "public_key": {  
      "description": "The contents of the public key.",  
      "type": "string"  
    }  
  }  
}
```

file-system/security/keys/{key_ref}

Endpoint

/v1/file-system/security/keys/{key_ref}

GET

Get the file system public key by using the name or identifier of the specified key.

Parameters

Name	Description	Required
key_ref	The name or identifier of the key.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_change_lock_key",
  "type": "object",
  "properties": {
    "id": {
      "description": "The identifier associated with the specified key.",
      "type": "string"
    },
    "name": {
      "description": "The unique name of the specified key.",
      "type": "string"
    },
    "comment": {
      "description": "A descriptive comment about the specified key.",
      "type": "string"
    },
    "disabled": {
      "description": "Specifies whether the key is disabled.",
      "type": "boolean"
    }
  }
}
```

```

    },
    "public_key": {
      "description": "The contents of the public key.",
      "type": "string"
    }
  }
}

```

PUT

Put the file system public key by using the name or identifier of the specified key.

Parameters

Name	Description	Required
key_ref	The name or identifier of the key.	Yes
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_change_lock_key",
  "type": "object",
  "properties": {
    "id": {
      "description": "The identifier associated with the specified key.",
      "type": "string"
    },
    "name": {
      "description": "The unique name of the specified key.",
      "type": "string"
    },
    "comment": {
      "description": "A descriptive comment about the specified key.",
      "type": "string"
    },
    "disabled": {
      "description": "Specifies whether the key is disabled.",
      "type": "boolean"
    },
    "public_key": {

```

```
    "description": "The contents of the public key.",
    "type": "string"
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_change_lock_key",
  "type": "object",
  "properties": {
    "id": {
      "description": "The identifier associated with the specified key.",
      "type": "string"
    },
    "name": {
      "description": "The unique name of the specified key.",
      "type": "string"
    },
    "comment": {
      "description": "A descriptive comment about the specified key.",
      "type": "string"
    },
    "disabled": {
      "description": "Specifies whether the key is disabled.",
      "type": "boolean"
    },
    "public_key": {
      "description": "The contents of the public key.",
      "type": "string"
    }
  }
}
```

DELETE

Delete the file system public key by using the name or identifier of the specified key.

Parameters

Name	Description	Required
<code>key_ref</code>	The name or identifier of the key.	Yes

Response

Codes

Code	Description
200	Return value on success

PATCH

Patch the file system public key by using the name or identifier of the specified key.

Parameters

Name	Description	Required
<code>key_ref</code>	The name or identifier of the key.	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_change_lock_key_patch",
  "type": "object",
  "properties": {
    "id": {
      "description": "The identifier associated with the specified key.",
      "type": "string"
    },
    "name": {
      "description": "The unique name of the specified key.",
      "type": "string"
    },
    "comment": {
      "description": "A descriptive comment about the specified key.",
      "type": "string"
    }
  }
}
```

```

    "disabled": {
      "description": "Specifies whether the key is disabled.",
      "type": "boolean"
    },
    "public_key": {
      "description": "The contents of the public key.",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_change_lock_key",
  "type": "object",
  "properties": {
    "id": {
      "description": "The identifier associated with the specified key.",
      "type": "string"
    },
    "name": {
      "description": "The unique name of the specified key.",
      "type": "string"
    },
    "comment": {
      "description": "A descriptive comment about the specified key.",
      "type": "string"
    },
    "disabled": {
      "description": "Specifies whether the key is disabled.",
      "type": "boolean"
    },
    "public_key": {
      "description": "The contents of the public key.",
      "type": "string"
    }
  }
}

```

```
}  
}
```

file-system/security/keys/{key_ref}/key-replacement-challenge

Endpoint

/v1/file-system/security/keys/{key_ref}/key-replacement-challenge

GET

Get file system public key replacement challenge by using the name or identifier of the specified key.

Parameters

Name	Description	Required
<code>key_ref</code>	The name or identifier of the key for which to get a security challenge for key replacement.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_change_lock_key_replace_challenge",
  "type": "object",
  "properties": {
    "challenge": {
      "description": "The security challenge for replacing the specified key.",
      "type": "string"
    }
  }
}
```


file-system/security/keys/{key_ref}/replace

Endpoint

/v1/file-system/security/keys/{key_ref}/replace

POST

Replace the file system public key by using the name or identifier of the specified key.

Parameters

Name	Description	Required
key_ref	The name or identifier of the key to replace.	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_change_lock_key_replace_request",
  "type": "object",
  "properties": {
    "replacement_key": {
      "description": "The replacement public key.",
      "type": "string"
    },
    "old_key_verification_signature": {
      "description": "The key replacement challenge signed with the current private key.",
      "type": "string"
    },
    "replacement_key_verification_signature": {
      "description": "The key replacement challenge signed with the replacement private key.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_change_lock_key",
  "type": "object",
  "properties": {
    "id": {
      "description": "The identifier associated with the specified key.",
      "type": "string"
    },
    "name": {
      "description": "The unique name of the specified key.",
      "type": "string"
    },
    "comment": {
      "description": "A descriptive comment about the specified key.",
      "type": "string"
    },
    "disabled": {
      "description": "Specifies whether the key is disabled.",
      "type": "boolean"
    },
    "public_key": {
      "description": "The contents of the public key.",
      "type": "string"
    }
  }
}
```

file-system/security/keys/{key_ref}/usages

Endpoint

/v1/file-system/security/keys/{key_ref}/usages

GET

Get file system public key usage by using the name or identifier of the specified key.

Parameters

Name	Description	Required
<code>key_ref</code>	The name or identifier of the public key for which to show snapshot and snapshot policy usage.	Yes
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_change_lock_key_usage_page",
  "type": "object",
  "properties": {
    "usages": {
      "type": "array",
      "items": {
        "description": "Usages of the key",
        "type": "object",
        "properties": {
          "type": {
            "type": "string",
            "enum": [
```


file-system/settings/ptime

Endpoint

/v1/file-system/settings/ptime

GET

Get ptime-related settings.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "ptime_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Whether ptime update is enabled",
      "type": "boolean"
    },
    "granularity": {
      "type": "string",
      "enum": [
        "HOUR",
        "DAY",
        "WEEK"
      ],
      "description": "Granularity for ptime updates (HOUR/DAY/WEEEEK):\n * `DAY` - ATIME_GRANULARITY_DAY,\n * `HOUR` - ATIME_GRANULARITY_HOUR,\n * `WEEK` - ATIME_GRANULARITY_WEEK"
    }
  }
}
```

PUT

Set atime-related settings.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "atime_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Whether atime update is enabled",
      "type": "boolean"
    },
    "granularity": {
      "type": "string",
      "enum": [
        "HOUR",
        "DAY",
        "WEEK"
      ],
      "description": "Granularity for atime updates (HOUR/DAY/WEEEEK):\n * `DAY` - ATIME_GRANULARITY_DAY,\n * `HOUR` - ATIME_GRANULARITY_HOUR,\n * `WEEK` - ATIME_GRANULARITY_WEEK"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "atime_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Whether atime update is enabled",
      "type": "boolean"
    },
    "granularity": {
      "type": "string",
      "enum": [
        "HOUR",
        "DAY",
        "WEEK"
      ],
      "description": "Granularity for atime updates (HOUR/DAY/WEEEEK):\n * `DAY` - ATIME_GRANULARITY_DAY,\n * `HOUR` - ATIME_GRANULARITY_HOUR,\n * `WEEK` - ATIME_GRANULARITY_WEEK"
    }
  }
}
```

PATCH

Update atime-related settings.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "atime_config_patch",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Whether atime update is enabled",
      "type": "boolean"
    }
  }
}
```

```

    },
    "granularity": {
      "type": "string",
      "enum": [
        "HOUR",
        "DAY",
        "WEEK"
      ],
      "description": "Granularity for atime updates (HOUR/DAY/WEEEEK):\n * `DAY` - ATIME_GRANULARITY_DAY,\n * `HOUR` - ATIME_GRANULARITY_HOUR,\n * `WEEK` - ATIME_GRANULARITY_WEEK"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "atime_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Whether atime update is enabled",
      "type": "boolean"
    },
    "granularity": {
      "type": "string",
      "enum": [
        "HOUR",
        "DAY",
        "WEEK"
      ],
      "description": "Granularity for atime updates (HOUR/DAY/WEEEEK):\n * `DAY` - ATIME_GRANULARITY_DAY,\n * `HOUR` - ATIME_GRANULARITY_HOUR,\n * `WEEK` - ATIME_GRANULARITY_WEEK"
    }
  }
}

```


}

file-system/settings/notify

Endpoint

/v1/file-system/settings/notify

GET

Get FS notify related settings.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "fs_notify_config",
  "type": "object",
  "properties": {
    "recursive_mode": {
      "type": "string",
      "enum": [
        "DISABLED_ERROR",
        "DISABLED_IGNORE",
        "ENABLED"
      ],
      "description": "recursive_mode:\n * `DISABLED_ERROR` - Recursive change-notify requests return errors immediately.\n * `DISABLED_IGNORE` - The system accepts recursive change-notify requests but sends notifications only for the top directory that it watches. In other words, the system behaves as if the user doesn't specify the recursive flag. You can use this setting to improve compatibility with applications that request recursive behavior but don't actually depend on it. Important: For scenarios that require recursive behavior, this setting can cause an application to become unresponsive or exhibit other unexpected behavior.\n * `ENABLED` - The ENABLED option is the default mode, unless you set a different one. This option provides full support for recursive change-notify requests. The system pushes notifications for all descendants of the watched directory to the watcher. Important: This configura
```

tion can affect system performance significantly. For example, watching the root of the file system creates a notification for every change on the entire cluster."

```
}  
}  
}
```

PUT

Set FS notify related settings.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{  
  "description": "fs_notify_config",  
  "type": "object",  
  "properties": {  
    "recursive_mode": {  
      "type": "string",  
      "enum": [  
        "DISABLED_ERROR",  
        "DISABLED_IGNORE",  
        "ENABLED"  
      ],  
      "description": "recursive_mode:\n * `DISABLED_ERROR` - Recursive change-notify requests return errors immediately.,\n * `DISABLED_IGNORE` - The system accepts recursive change-notify requests but sends notifications only for the top directory that it watches. In other words, the system behaves as if the user doesn't specify the recursive flag. You can use this setting to improve compatibility with applications that request recursive behavior but don't actually depend on it. Important: For scenarios that require recursive behavior, this setting can cause an application to become unresponsive or exhibit other unexpected behavior.,\n * `ENABLED` - The ENABLED option is the default mode, unless you set a different one. This option provides full support for recursive change-notify requests. The system pushes notifications for all descendants of the watched directory to the watcher. Important: This configuration can affect system performance significantly. For example, watching the root of the file system creates a notification for every change on the entire cluster."  
    }  
  }  
}
```

```
}  
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{  
  "description": "fs_notify_config",  
  "type": "object",  
  "properties": {  
    "recursive_mode": {  
      "type": "string",  
      "enum": [  
        "DISABLED_ERROR",  
        "DISABLED_IGNORE",  
        "ENABLED"  
      ],  
      "description": "recursive_mode:\n * `DISABLED_ERROR` - Recursive change-notif  
y requests return errors immediately.,\n * `DISABLED_IGNORE` - The system accepts re  
cursive change-notify requests but sends notifications only for the top directory th  
at it watches. In other words, the system behaves as if the user doesn't specify th  
e recursive flag. You can use this setting to improve compatibility with application  
s that request recursive behavior but don't actually depend on it. Important: For sc  
enarios that require recursive behavior, this setting can cause an application to be  
come unresponsive or exhibit other unexpected behavior.,\n * `ENABLED` - The ENABLE  
D option is the default mode, unless you set a different one. This option provides f  
ull support for recursive change-notify requests. The system pushes notifications fo  
r all descendants of the watched directory to the watcher. Important: This configura  
tion can affect system performance significantly. For example, watching the root of  
the file system creates a notification for every change on the entire cluster."  
    }  
  }  
}
```

file-system/settings/permissions

Endpoint

/v1/file-system/settings/permissions

GET

Get permissions settings.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_permissions_settings",
  "type": "object",
  "properties": {
    "mode": {
      "type": "string",
      "enum": [
        "NATIVE",
        "_DEPRECATED_MERGED_V1",
        "CROSS_PROTOCOL",
        "CROSS_PROTOCOL_POSIX_PRIORITY"
      ],
      "description": "mode:\n * `CROSS_PROTOCOL` - CROSS_PROTOCOL,\n * `CROSS_PROTOCOL_POSIX_PRIORITY` - CROSS_PROTOCOL_POSIX_PRIORITY,\n * `NATIVE` - NATIVE,\n * `_DEPRECATED_MERGED_V1` - _DEPRECATED_MERGED_V1"
    }
  }
}
```

PUT

Set permissions settings.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_permissions_settings",
  "type": "object",
  "properties": {
    "mode": {
      "type": "string",
      "enum": [
        "NATIVE",
        "_DEPRECATED_MERGED_V1",
        "CROSS_PROTOCOL",
        "CROSS_PROTOCOL_POSIX_PRIORITY"
      ],
      "description": "mode:\n * `CROSS_PROTOCOL` - CROSS_PROTOCOL,\n * `CROSS_PROTOCOL_POSIX_PRIORITY` - CROSS_PROTOCOL_POSIX_PRIORITY,\n * `NATIVE` - NATIVE,\n * `_DEPRECATED_MERGED_V1` - _DEPRECATED_MERGED_V1"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_permissions_settings",
  "type": "object",
  "properties": {
    "mode": {
      "type": "string",
      "enum": [
        "NATIVE",
```

```

        "_DEPRECATED_MERGED_V1",
        "CROSS_PROTOCOL",
        "CROSS_PROTOCOL_POSIX_PRIORITY"
    ],
    "description": "mode:\n * `CROSS_PROTOCOL` - CROSS_PROTOCOL,\n * `CROSS_PROTOCOL_POSIX_PRIORITY` - CROSS_PROTOCOL_POSIX_PRIORITY,\n * `NATIVE` - NATIVE,\n * `_DEPRECATED_MERGED_V1` - _DEPRECATED_MERGED_V1"
}
}
}

```

files/locks/nfs4/byte-range/

Endpoint

/v1/files/locks/nfs4/byte-range/

GET

Return a list of all granted file locks that the specified machine owns.

Parameters

Name	Description	Required
<code>owner_name</code>	The lock owner's name. The client provides the name. Typically, it is the client hostname.	No
<code>owner_address</code>	The lock owner's address. This is the IP address of the machine that acquires the lock. If the machine's IP address changes, any existing lock entries are still listed under the old address.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_nfs4_byte_range_grants",
  "type": "object",
  "properties": {
    "grants": {
      "type": "array",
      "items": {
        "description": "grants",
```



```

"type": "object",
"properties": {
  "file_id": {
    "description": "file_id",
    "type": "string"
  },
  "stream_id": {
    "description": "stream_id",
    "type": "string"
  },
  "snapshot_id": {
    "description": "The locked file's snapshot ID. Empty if the file is at t
he head version (not from a snapshot).",
    "type": "string"
  },
  "mode": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "API_BYTE_RANGE_EXCLUSIVE",
        "API_BYTE_RANGE_SHARED",
        "API_BYTE_RANGE_READ_OP",
        "API_BYTE_RANGE_WRITE_OP"
      ],
      "description": "mode:\n * `API_BYTE_RANGE_EXCLUSIVE` - API_BYTE_RANG
E_EXCLUSIVE,\n * `API_BYTE_RANGE_READ_OP` - API_BYTE_RANGE_READ_OP,\n * `API_BYTE_RA
NGE_SHARED` - API_BYTE_RANGE_SHARED,\n * `API_BYTE_RANGE_WRITE_OP` - API_BYTE_RANG
E_WRITE_OP"
    }
  },
  "offset": {
    "description": "offset",
    "type": "string"
  },
  "size": {
    "description": "size",
    "type": "string"
  },
  "owner_id": {
    "description": "The unique identifier for the process that owns the fil
e lock.",
    "type": "string"
  },
  "owner_name": {
    "description": "The name of the machine that owns the lock.",

```


files/locks/nlm/byte-range/

Endpoint

/v1/files/locks/nlm/byte-range/

GET

Return a list of all granted file locks that the specified machine owns.

Parameters

Name	Description	Required
<code>owner_name</code>	The lock owner's name. The client provides the name. Typically, it is the client hostname.	No
<code>owner_address</code>	The lock owner's address. This is the IP address of the machine that acquires the lock. If the machine's IP address changes, any existing lock entries are still listed under the old address.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_byte_range_grants",
  "type": "object",
  "properties": {
    "grants": {
      "type": "array",
      "items": {
        "description": "grants",
```

```

"type": "object",
"properties": {
  "file_id": {
    "description": "file_id",
    "type": "string"
  },
  "stream_id": {
    "description": "stream_id",
    "type": "string"
  },
  "snapshot_id": {
    "description": "The locked file's snapshot ID. Empty if the file is at t
he head version (not from a snapshot).",
    "type": "string"
  },
  "mode": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "API_BYTE_RANGE_EXCLUSIVE",
        "API_BYTE_RANGE_SHARED",
        "API_BYTE_RANGE_READ_OP",
        "API_BYTE_RANGE_WRITE_OP"
      ],
      "description": "mode:\n * `API_BYTE_RANGE_EXCLUSIVE` - API_BYTE_RANG
E_EXCLUSIVE,\n * `API_BYTE_RANGE_READ_OP` - API_BYTE_RANGE_READ_OP,\n * `API_BYTE_RA
NGE_SHARED` - API_BYTE_RANGE_SHARED,\n * `API_BYTE_RANGE_WRITE_OP` - API_BYTE_RANG
E_WRITE_OP"
    }
  },
  "offset": {
    "description": "offset",
    "type": "string"
  },
  "size": {
    "description": "size",
    "type": "string"
  },
  "owner_id": {
    "description": "The unique identifier for the process that owns the fil
e lock.",
    "type": "string"
  },
  "owner_name": {
    "description": "The name of the machine that owns the lock.",

```

```
{
  "type": "string",
},
"owner_address": {
  "description": "The IP address to use for acquiring the file lock.",
  "type": "string",
},
"node_address": {
  "description": "The IP address of the node that receives the request.",
  "type": "string",
}
}
}
```

DELETE

Release all locks held by a particular client. This is dangerous, and should only be used after confirming that the client is dead.

Parameters

Name	Description	Required
<code>owner_name</code>	The lock owner's name. The client provides the name. Typically, it is the client hostname.	No
<code>owner_address</code>	The lock owner's address. This is the IP address of the machine that acquires the lock. If the machine's IP address changes, any existing lock entries are still listed under the old address.	No

Response

Codes

Code	Description
200	Return value on success

files/locks/nlm/byte-range/waiters/

Endpoint

/v1/files/locks/nlm/byte-range/waiters/

GET

Return a list of all NLM byte range requests currently waiting on the specified machine.

Parameters

Name	Description	Required
<code>owner_name</code>	The lock owner's name. The client provides the name. Typically, it is the client hostname.	No
<code>owner_address</code>	The waiter's address. The IP address of the machine (the waiter) that sends the lock request. If the machine's IP address changes, any outstanding requests are still listed under the old address.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_byte_range_waiters",
  "type": "object",
  "properties": {
    "waiters": {
      "type": "array",
      "items": {
        "description": "waiters",
```

```

"type": "object",
"properties": {
  "file_id": {
    "description": "file_id",
    "type": "string"
  },
  "stream_id": {
    "description": "stream_id",
    "type": "string"
  },
  "snapshot_id": {
    "description": "The locked file's snapshot ID. Empty if the file is at the head version (not from a snapshot).",
    "type": "string"
  },
  "mode": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "API_BYTE_RANGE_EXCLUSIVE",
        "API_BYTE_RANGE_SHARED",
        "API_BYTE_RANGE_READ_OP",
        "API_BYTE_RANGE_WRITE_OP"
      ]
    },
    "description": "mode:\n * `API_BYTE_RANGE_EXCLUSIVE` - API_BYTE_RANGE_EXCLUSIVE,\n * `API_BYTE_RANGE_READ_OP` - API_BYTE_RANGE_READ_OP,\n * `API_BYTE_RANGE_SHARED` - API_BYTE_RANGE_SHARED,\n * `API_BYTE_RANGE_WRITE_OP` - API_BYTE_RANGE_WRITE_OP"
  },
  "offset": {
    "description": "offset",
    "type": "string"
  },
  "size": {
    "description": "size",
    "type": "string"
  },
  "owner_id": {
    "description": "The unique identifier for the process that owns the file lock.",
    "type": "string"
  },
  "owner_name": {
    "description": "The name of the machine that owns the lock.",

```

```
    "type": "string"
  },
  "owner_address": {
    "description": "The IP address to use for acquiring the file lock.",
    "type": "string"
  },
  "node_address": {
    "description": "The IP address of the node that receives the request.",
    "type": "string"
  }
}
}
```


files/locks/smb/byte-range/

Endpoint

/v1/files/locks/smb/byte-range/

GET

Return a list of all granted file locks that the specified machine owns.

Parameters

Name	Description	Required
<code>owner_address</code>	IP Address of the client that owns the lock.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_byte_range_grants",
  "type": "object",
  "properties": {
    "grants": {
      "type": "array",
      "items": {
        "description": "grants",
        "type": "object",
        "properties": {
          "file_id": {
            "description": "file_id",
```

```

        "type": "string"
    },
    "stream_id": {
        "description": "stream_id",
        "type": "string"
    },
    "snapshot_id": {
        "description": "The locked file's snapshot ID. Empty if the file is at the head version (not from a snapshot).",
        "type": "string"
    },
    "mode": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "API_BYTE_RANGE_EXCLUSIVE",
                "API_BYTE_RANGE_SHARED",
                "API_BYTE_RANGE_READ_OP",
                "API_BYTE_RANGE_WRITE_OP"
            ],
            "description": "mode:\n * `API_BYTE_RANGE_EXCLUSIVE` - API_BYTE_RANGE_EXCLUSIVE,\n * `API_BYTE_RANGE_READ_OP` - API_BYTE_RANGE_READ_OP,\n * `API_BYTE_RANGE_SHARED` - API_BYTE_RANGE_SHARED,\n * `API_BYTE_RANGE_WRITE_OP` - API_BYTE_RANGE_WRITE_OP"
        }
    },
    "offset": {
        "description": "offset",
        "type": "string"
    },
    "size": {
        "description": "size",
        "type": "string"
    },
    "owner_id": {
        "description": "The unique identifier for the process that owns the file lock.",
        "type": "string"
    },
    "owner_name": {
        "description": "The name of the machine that owns the lock.",
        "type": "string"
    },
    "owner_address": {
        "description": "The IP address to use for acquiring the file lock.",

```

```
        "type": "string"
    },
    "node_address": {
        "description": "The IP address of the node that receives the request.",
        "type": "string"
    }
}
}
```

files/locks/smb/share-mode/

Endpoint

/v1/files/locks/smb/share-mode/

GET

Return a list of all granted file locks that the specified machine owns.

Parameters

Name	Description	Required
<code>owner_address</code>	IP Address of the client that owns the lock.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_share_mode_grants",
  "type": "object",
  "properties": {
    "grants": {
      "type": "array",
      "items": {
        "description": "grants",
        "type": "object",
        "properties": {
          "file_id": {
            "description": "file_id",
```

```

        "type": "string"
    },
    "stream_id": {
        "description": "stream_id",
        "type": "string"
    },
    "snapshot_id": {
        "description": "The locked file's snapshot ID. Empty if the file is at the head version (not from a snapshot).",
        "type": "string"
    },
    "mode": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "API_SHARE_MODE_READ",
                "API_SHARE_MODE_WRITE",
                "API_SHARE_MODE_DELETE",
                "API_SHARE_MODE_EXCLUDE_READ",
                "API_SHARE_MODE_EXCLUDE_WRITE",
                "API_SHARE_MODE_EXCLUDE_DELETE"
            ],
            "description": "mode:\n * `API_SHARE_MODE_DELETE` - API_SHARE_MODE_DELETE,\n * `API_SHARE_MODE_EXCLUDE_DELETE` - API_SHARE_MODE_EXCLUDE_DELETE,\n * `API_SHARE_MODE_EXCLUDE_READ` - API_SHARE_MODE_EXCLUDE_READ,\n * `API_SHARE_MODE_EXCLUDE_WRITE` - API_SHARE_MODE_EXCLUDE_WRITE,\n * `API_SHARE_MODE_READ` - API_SHARE_MODE_READ,\n * `API_SHARE_MODE_WRITE` - API_SHARE_MODE_WRITE"
        }
    },
    "owner_id": {
        "description": "The unique identifier for the process that owns the file lock.",
        "type": "string"
    },
    "owner_address": {
        "description": "The IP address to use for acquiring the file lock.",
        "type": "string"
    },
    "node_address": {
        "description": "The IP address of the node that receives the request.",
        "type": "string"
    }
}
}
}

```

```
}  
}
```

files/resolve

Endpoint

/v1/files/resolve

POST

Return the full paths for each specified file ID. If a file has more than one path (due to hard links) a canonical path is chosen.

Parameters

Name	Description	Required
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Request

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "fs_api_file_id_path",
    "type": "object",
  }
}
```

```
"properties": {  
  "id": {  
    "description": "Unique ID of this file or directory",  
    "type": "string"  
  },  
  "path": {  
    "description": "Full path of this file or directory",  
    "type": "string"  
  }  
}  
}
```


files/try-resolve

Endpoint

/v1/files/try-resolve

POST

[preview] Attempt to return the full path for each specified file ID, grouped by outcome: success with path, file deleted, file temporarily unavailable. Resolution for a temporarily unavailable file should be attempted again later. If a file has more than one path (due to hard links) a canonical path is chosen.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "fs_api_try_resolve_request",
  "type": "object",
  "properties": {
    "ids": {
      "type": "array",
      "items": {
        "description": "File IDs to resolve",
        "type": "string"
      }
    },
    "snapshot": {
      "description": "Snapshot to resolve against. Defaults to the live file system.",
      "type": "number"
    }
  }
}
```

Response

Codes

Code	Description
------	-------------

200

Return value on success

Schema

```
{
  "description": "fs_api_try_resolve_result",
  "type": "object",
  "properties": {
    "available": {
      "type": "array",
      "items": {
        "description": "Full path of each file or directory whose path was resolved",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique ID of this file or directory",
            "type": "string"
          },
          "path": {
            "description": "Full path of this file or directory",
            "type": "string"
          }
        }
      }
    },
    "unavailable": {
      "type": "array",
      "items": {
        "description": "File IDs that are temporarily unavailable",
        "type": "string"
      }
    },
    "deleted": {
      "type": "array",
      "items": {
        "description": "File IDs that have been deleted",
        "type": "string"
      }
    }
  }
}
```

files/{ref}

Endpoint

/v1/files/{ref}

DELETE

Delete the file system object specified by 'ref'. When 'ref' is a path, the exact specified name is deleted. If 'ref' is a file ID and the file has multiple links, then the link to be deleted is the one that '/v1/files/resolve' would return.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes

Response

Codes

Code	Description
200	Return value on success

files/{ref}/aggregates/

Endpoint

/v1/files/{ref}/aggregates/

GET

Return aggregated data for a directory (used capacity, number of files, and so on)

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
max-entries	Maximum number of directory entries to return. Specifying 0 entries causes only the specified directory's aggregates to be returned. (default: 1000)	No
order-by	Ordering field used for top N selection and sorting (default: total_blocks): * `total_blocks` - total_blocks, * `total_datablocks` - total_datablocks, * `total_directories` - total_directories, * `total_files` - total_files, * `total_metablocks` - total_metablocks, * `total_named_stream_datablocks` - total_named_stream_datablocks, * `total_named_streams` - total_named_streams, * `total_other` - total_other, * `total_symlinks` - total_symlinks	No
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Response

Codes

Code	Description
200	Return value on success

```

{
  "description": "api_files_dir_aggregates",
  "type": "object",
  "properties": {
    "path": {
      "description": "path",
      "type": "string"
    },
    "id": {
      "description": "id",
      "type": "string"
    },
    "files": {
      "type": "array",
      "items": {
        "description": "files",
        "type": "object",
        "properties": {
          "name": {
            "description": "Name of this file or directory",
            "type": "string"
          },
          "type": {
            "type": "string",
            "enum": [
              "FS_FILE_TYPE_FILE",
              "FS_FILE_TYPE_DIRECTORY",
              "FS_FILE_TYPE_SYMLINK",
              "FS_FILE_TYPE_UNIX_PIPE",
              "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
              "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
              "FS_FILE_TYPE_UNIX_SOCKET"
            ],
            "description": "type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
          },
          "id": {
            "description": "Unique ID of this file or directory",
            "type": "string"
          }
        }
      }
    }
  }
}

```

```

    "capacity_usage": {
      "description": "Capacity used by this file, or directory and all its children, in bytes",
      "type": "string"
    },
    "data_usage": {
      "description": "Capacity used for data by this file, or directory and all its children, in bytes",
      "type": "string"
    },
    "meta_usage": {
      "description": "Capacity used for metadata by this file, or directory and all its children, in bytes",
      "type": "string"
    },
    "num_files": {
      "description": "Total number of files in the directory",
      "type": "string"
    },
    "num_directories": {
      "description": "Total number of directories in the directory",
      "type": "string"
    },
    "num_symlinks": {
      "description": "Total number of symlinks in the directory",
      "type": "string"
    },
    "num_other_objects": {
      "description": "Total number of Unix devices, pipes, and sockets in the directory",
      "type": "string"
    },
    "named_stream_data_usage": {
      "description": "Capacity used for data by named streams on this file, or directory and all its children, in bytes",
      "type": "string"
    },
    "num_named_streams": {
      "description": "Total number of named streams in the directory",
      "type": "string"
    }
  }
},
"total_capacity": {
  "description": "total_capacity",

```

```

    "type": "string"
  },
  "total_data": {
    "description": "total_data",
    "type": "string"
  },
  "total_named_stream_data": {
    "description": "total_named_stream_data",
    "type": "string"
  },
  "total_meta": {
    "description": "total_meta",
    "type": "string"
  },
  "total_files": {
    "description": "total_files",
    "type": "string"
  },
  "total_directories": {
    "description": "total_directories",
    "type": "string"
  },
  "total_symlinks": {
    "description": "total_symlinks",
    "type": "string"
  },
  "total_other_objects": {
    "description": "total_other_objects",
    "type": "string"
  },
  "total_named_streams": {
    "description": "total_named_streams",
    "type": "string"
  }
}
}

```

files/{ref}/copy-chunk

Endpoint

/v1/files/{ref}/copy-chunk

POST

Copies the contents of the source file specified in the body of the request to the default stream. The file must already exist.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_files_copy_chunk",
  "type": "object",
  "properties": {
    "source_id": {
      "description": "File ID of the source file. Exactly one of source_id or source_path must be provided.",
      "type": "string"
    },
    "source_path": {
      "description": "Path of the source file. Exactly one of source_id or source_path must be provided.",
      "type": "string"
    },
    "source_stream_id": {
      "description": "Stream ID of the source file. Defaults to default stream.",
      "type": "string"
    }
  }
}
```



```

    "source_snapshot": {
      "description": "Snapshot ID specifying the version of the file to copy from. Defaults to head version.",
      "type": "number"
    },
    "source_offset": {
      "description": "Specifies the offset in bytes to start copying from. Defaults to 0.",
      "type": "string"
    },
    "target_offset": {
      "description": "Specifies the offset in bytes to start copying to. Defaults to 0.",
      "type": "string"
    },
    "length": {
      "description": "Specifies the maximum length of copy in bytes. Defaults to copy to the end of the source file. The server may not be able to copy the entire length requested. If that is the case, the response body returned can be used as request body for the remaining copy.",
      "type": "string"
    },
    "source_etag": {
      "description": "Expected ETag of the source file returned from /v1/files/{source-id}/info/attributes. If provided, this ETag will be validated against the server to ensure no intermediate change has occurred.",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_files_copy_chunk",
  "type": "object",
  "properties": {

```

```

    "source_id": {
      "description": "File ID of the source file. Exactly one of source_id or source_path must be provided.",
      "type": "string"
    },
    "source_path": {
      "description": "Path of the source file. Exactly one of source_id or source_path must be provided.",
      "type": "string"
    },
    "source_stream_id": {
      "description": "Stream ID of the source file. Defaults to default stream.",
      "type": "string"
    },
    "source_snapshot": {
      "description": "Snapshot ID specifying the version of the file to copy from. Defaults to head version.",
      "type": "number"
    },
    "source_offset": {
      "description": "Specifies the offset in bytes to start copying from. Defaults to 0.",
      "type": "string"
    },
    "target_offset": {
      "description": "Specifies the offset in bytes to start copying to. Defaults to 0.",
      "type": "string"
    },
    "length": {
      "description": "Specifies the maximum length of copy in bytes. Defaults to copy to the end of the source file. The server may not be able to copy the entire length requested. If that is the case, the response body returned can be used as request body for the remaining copy.",
      "type": "string"
    },
    "source_etag": {
      "description": "Expected ETag of the source file returned from /v1/files/{source-id}/info/attributes. If provided, this ETag will be validated against the server to ensure no intermediate change has occurred.",
      "type": "string"
    }
  }
}

```

files/{ref}/data

Endpoint

/v1/files/{ref}/data

GET

Return the contents of the file as an HTTP octet stream. The etag returned by this method represents the whole state of this file. In another word, if you are reading just a portion of the data, etag could be invalid because of other changes happened to the file, even the specific portion of data you read is still intact.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
offset	Read data from the requested file starting at the given 64-bit integer offset. If the offset is larger than the size of the file, the read will succeed and no data will be returned.	No
length	Read up to length bytes from the requested file. If the read extends beyond the end of the file, the read will return as many bytes as possible, up to length.	No
skip-atime-update	If true, suppress the update of the file's access time for this read.	No

Response

Codes

Code	Description
200	Return value on success

PUT

Replace the contents of the file with the body of the request. The target file must already exist, and the content-type of the request must be application/octet-stream.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "type": "object"
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_attributes",
  "type": "object",
  "properties": {
    "path": {
      "description": "Filesystem path of the object",
      "type": "string"
    },
    "name": {
```

```

    "description": "Name of this file",
    "type": "string"
  },
  "num_links": {
    "description": "How many directory entries are associated with this file",
    "type": "number"
  },
  "type": {
    "type": "string",
    "enum": [
      "FS_FILE_TYPE_FILE",
      "FS_FILE_TYPE_DIRECTORY",
      "FS_FILE_TYPE_SYMLINK",
      "FS_FILE_TYPE_UNIX_PIPE",
      "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
      "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
      "FS_FILE_TYPE_UNIX_SOCKET"
    ],
    "description": "Resource type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
  },
  "major_minor_numbers": {
    "description": "The major and minor numbers for UNIX device files",
    "type": "object",
    "properties": {
      "major": {
        "description": "major",
        "type": "number"
      },
      "minor": {
        "description": "minor",
        "type": "number"
      }
    }
  },
  "symlink_target_type": {
    "type": "string",
    "enum": [
      "FS_FILE_TYPE_UNKNOWN",
      "FS_FILE_TYPE_FILE",
      "FS_FILE_TYPE_DIRECTORY"
    ],
  },

```

```

    "description": "The type of the target file if this file is a symlink:\n * `F
S_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - AP
I_SYMLINK_TARGET_FILE,\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNOWN"
  },
  "file_number": {
    "description": "Unique ID of this file",
    "type": "string"
  },
  "id": {
    "description": "Unique ID of this file",
    "type": "string"
  },
  "mode": {
    "description": "POSIX-style file mode (octal)",
    "type": "string"
  },
  "owner": {
    "description": "File owner",
    "type": "string"
  },
  "owner_details": {
    "description": "File owner details",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ]
      },
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  }
}

```

```

},
"group": {
  "description": "File group",
  "type": "string"
},
"group_details": {
  "description": "File group details",
  "type": "object",
  "properties": {
    "id_type": {
      "type": "string",
      "enum": [
        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
      ],
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  }
},
"blocks": {
  "description": "Number of blocks used by the file on this cluster",
  "type": "string"
},
"datablocks": {
  "description": "Number of data blocks used by the file on this cluster",
  "type": "string"
},
"metablocks": {
  "description": "Number of meta blocks used by the file on this cluster",
  "type": "string"
},
"logical_datablocks": {
  "description": "Number of data blocks used by the file",

```

```

    "type": "string"
  },
  "size": {
    "description": "File size in bytes",
    "type": "string"
  },
  "access_time": {
    "description": "Last time content was read, RFC 3339 format",
    "type": "string"
  },
  "modification_time": {
    "description": "Last time content was modified, RFC 3339 format",
    "type": "string"
  },
  "change_time": {
    "description": "Last time content or attributes were modified, RFC 3339 format",
    "type": "string"
  },
  "creation_time": {
    "description": "File creation time, RFC 3339 format",
    "type": "string"
  },
  "child_count": {
    "description": "Count of children (valid for directories)",
    "type": "number"
  },
  "extended_attributes": {
    "description": "SMB extended file attributes",
    "type": "object",
    "properties": {
      "read_only": {
        "description": "read_only",
        "type": "boolean"
      },
      "hidden": {
        "description": "hidden",
        "type": "boolean"
      },
      "system": {
        "description": "system",
        "type": "boolean"
      },
      "archive": {
        "description": "archive",
        "type": "boolean"
      }
    }
  }
}

```



```

    },
    "temporary": {
      "description": "temporary",
      "type": "boolean"
    },
    "compressed": {
      "description": "compressed",
      "type": "boolean"
    },
    "not_content_indexed": {
      "description": "not_content_indexed",
      "type": "boolean"
    },
    "sparse_file": {
      "description": "sparse_file",
      "type": "boolean"
    },
    "offline": {
      "description": "offline",
      "type": "boolean"
    }
  }
},
"directory_entry_hash_policy": {
  "type": "string",
  "enum": [
    "FS_DIRECTORY_HASH_VERSION_LOWER",
    "FS_DIRECTORY_HASH_VERSION_FOLDED"
  ],
  "description": "Hash policy for directory entries:\n * `FS_DIRECTORY_HASH_VERSION_FOLDED` - FS_DIRECTORY_HASH_VERSION_FOLDED,\n * `FS_DIRECTORY_HASH_VERSION_LOWER` - FS_DIRECTORY_HASH_VERSION_LOWER"
},
"data_revision": {
  "description": "The revision for changes to the underlying file data.",
  "type": "string"
},
"user_metadata_revision": {
  "description": "The revision for changes to the user defined metadata of the file.",
  "type": "string"
}
}
}

```

PATCH

Set the contents of the file, at the given offset, to the body of the request. The target file must

already exist, and the Content-Type of the request must be application/octet-stream.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
offset	Write the provided data at the given 64-bit integer offset. If the offset is greater than the size of the file, the file will be zero-extended up to offset before the data is written. (default: 0)	No
If-Match	ETag for expected version	No

Request

Schema

```
{
  "type": "object"
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_attributes",
  "type": "object",
  "properties": {
    "path": {
      "description": "Filesystem path of the object",
      "type": "string"
    },
  },
}
```

```

"name": {
  "description": "Name of this file",
  "type": "string"
},
"num_links": {
  "description": "How many directory entries are associated with this file",
  "type": "number"
},
"type": {
  "type": "string",
  "enum": [
    "FS_FILE_TYPE_FILE",
    "FS_FILE_TYPE_DIRECTORY",
    "FS_FILE_TYPE_SYMLINK",
    "FS_FILE_TYPE_UNIX_PIPE",
    "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
    "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
    "FS_FILE_TYPE_UNIX_SOCKET"
  ],
  "description": "Resource type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
},
"major_minor_numbers": {
  "description": "The major and minor numbers for UNIX device files",
  "type": "object",
  "properties": {
    "major": {
      "description": "major",
      "type": "number"
    },
    "minor": {
      "description": "minor",
      "type": "number"
    }
  }
},
"symlink_target_type": {
  "type": "string",
  "enum": [
    "FS_FILE_TYPE_UNKNOWN",
    "FS_FILE_TYPE_FILE",
    "FS_FILE_TYPE_DIRECTORY"
  ]
}

```

```

    ],
    "description": "The type of the target file if this file is a symlink:\n * `F
S_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - AP
I_SYMLINK_TARGET_FILE,\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNOWN"
  },
  "file_number": {
    "description": "Unique ID of this file",
    "type": "string"
  },
  "id": {
    "description": "Unique ID of this file",
    "type": "string"
  },
  "mode": {
    "description": "POSIX-style file mode (octal)",
    "type": "string"
  },
  "owner": {
    "description": "File owner",
    "type": "string"
  },
  "owner_details": {
    "description": "File owner details",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ]
      },
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  }
}

```

```

    }
  },
  "group": {
    "description": "File group",
    "type": "string"
  },
  "group_details": {
    "description": "File group details",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ],
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO  

        CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N  

        FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO  

        RT,\n * `SMB_SID` - SMB_SID"
      },
      "id_value": {
        "description": "id_value",
        "type": "string"
      }
    }
  },
  "blocks": {
    "description": "Number of blocks used by the file on this cluster",
    "type": "string"
  },
  "datablocks": {
    "description": "Number of data blocks used by the file on this cluster",
    "type": "string"
  },
  "metablocks": {
    "description": "Number of meta blocks used by the file on this cluster",
    "type": "string"
  },
  "logical_datablocks": {

```

```

    "description": "Number of data blocks used by the file",
    "type": "string"
  },
  "size": {
    "description": "File size in bytes",
    "type": "string"
  },
  "access_time": {
    "description": "Last time content was read, RFC 3339 format",
    "type": "string"
  },
  "modification_time": {
    "description": "Last time content was modified, RFC 3339 format",
    "type": "string"
  },
  "change_time": {
    "description": "Last time content or attributes were modified, RFC 3339 format",
    "type": "string"
  },
  "creation_time": {
    "description": "File creation time, RFC 3339 format",
    "type": "string"
  },
  "child_count": {
    "description": "Count of children (valid for directories)",
    "type": "number"
  },
  "extended_attributes": {
    "description": "SMB extended file attributes",
    "type": "object",
    "properties": {
      "read_only": {
        "description": "read_only",
        "type": "boolean"
      },
      "hidden": {
        "description": "hidden",
        "type": "boolean"
      },
      "system": {
        "description": "system",
        "type": "boolean"
      },
      "archive": {
        "description": "archive",

```

```

        "type": "boolean"
    },
    "temporary": {
        "description": "temporary",
        "type": "boolean"
    },
    "compressed": {
        "description": "compressed",
        "type": "boolean"
    },
    "not_content_indexed": {
        "description": "not_content_indexed",
        "type": "boolean"
    },
    "sparse_file": {
        "description": "sparse_file",
        "type": "boolean"
    },
    "offline": {
        "description": "offline",
        "type": "boolean"
    }
}
},
"directory_entry_hash_policy": {
    "type": "string",
    "enum": [
        "FS_DIRECTORY_HASH_VERSION_LOWER",
        "FS_DIRECTORY_HASH_VERSION_FOLDED"
    ],
    "description": "Hash policy for directory entries:\n * `FS_DIRECTORY_HASH_VERSION_FOLDED` - FS_DIRECTORY_HASH_VERSION_FOLDED,\n * `FS_DIRECTORY_HASH_VERSION_LOWER` - FS_DIRECTORY_HASH_VERSION_LOWER"
},
"data_revision": {
    "description": "The revision for changes to the underlying file data.",
    "type": "string"
},
"user_metadata_revision": {
    "description": "The revision for changes to the user defined metadata of the file.",
    "type": "string"
}
}
}

```

files/{ref}/entries/

Endpoint

/v1/files/{ref}/entries/

GET

Get directory entries. Path or ID must reference a directory.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
<code>smb-pattern</code>	Return only entries matching the give SMB pattern	No
<code>skip-atime-update</code>	If true, suppress the update of the directory's access time for this read.	No
<code>include-acls</code>	If set to true, include the ACL for each entry in the response. To retrieve the ACL for files[i], look up file_acls.acl_pool[file_acls.acl_indices[i]]. When the caller doesn't have the READ_ACL permission for a file, the entry in acl.acl_indices is null. False by default.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
------	-------------

200	Return value on success
-----	-------------------------

Schema

```
{
  "description": "api_files_directory_entries",
  "type": "object",
  "properties": {
    "path": {
      "description": "path",
      "type": "string"
    },
    "id": {
      "description": "Unique ID of this directory",
      "type": "string"
    },
    "child_count": {
      "description": "child_count",
      "type": "number"
    },
    "files": {
      "type": "array",
      "items": {
        "description": "files",
        "type": "object",
        "properties": {
          "path": {
            "description": "Filesystem path of the object",
            "type": "string"
          },
          "name": {
            "description": "Name of this file",
            "type": "string"
          },
          "num_links": {
            "description": "How many directory entries are associated with this file",
            "type": "number"
          }
        }
      },
      "type": {
        "type": "string",
        "enum": [
          "FS_FILE_TYPE_FILE",
          "FS_FILE_TYPE_DIRECTORY",
          "FS_FILE_TYPE_SYMLINK",

```

```

        "FS_FILE_TYPE_UNIX_PIPE",
        "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
        "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
        "FS_FILE_TYPE_UNIX_SOCKET"
    ],
    "description": "Resource type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TY
PE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLIN
K` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNI
X_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACT
ER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYP
E_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
    },
    "major_minor_numbers": {
        "description": "The major and minor numbers for UNIX device files",
        "type": "object",
        "properties": {
            "major": {
                "description": "major",
                "type": "number"
            },
            "minor": {
                "description": "minor",
                "type": "number"
            }
        }
    },
    "symlink_target_type": {
        "type": "string",
        "enum": [
            "FS_FILE_TYPE_UNKNOWN",
            "FS_FILE_TYPE_FILE",
            "FS_FILE_TYPE_DIRECTORY"
        ],
        "description": "The type of the target file if this file is a symlin
k:\n * `FS_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\n * `FS_FILE_TYPE_FI
LE` - API_SYMLINK_TARGET_FILE,\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNO
WN"
    },
    "file_number": {
        "description": "Unique ID of this file",
        "type": "string"
    },
    "id": {
        "description": "Unique ID of this file",
        "type": "string"
    },
    },

```

```

"mode": {
  "description": "POSIX-style file mode (octal)",
  "type": "string"
},
"owner": {
  "description": "File owner",
  "type": "string"
},
"owner_details": {
  "description": "File owner details",
  "type": "object",
  "properties": {
    "id_type": {
      "type": "string",
      "enum": [
        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
      ],
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU\nP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U\nID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL\nO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  }
},
"group": {
  "description": "File group",
  "type": "string"
},
"group_details": {
  "description": "File group details",
  "type": "object",
  "properties": {
    "id_type": {
      "type": "string",
      "enum": [

```

```

        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
},
"blocks": {
    "description": "Number of blocks used by the file on this cluster",
    "type": "string"
},
"datablocks": {
    "description": "Number of data blocks used by the file on this cluster",
    "type": "string"
},
"metablocks": {
    "description": "Number of meta blocks used by the file on this cluster",
    "type": "string"
},
"logical_datablocks": {
    "description": "Number of data blocks used by the file",
    "type": "string"
},
"size": {
    "description": "File size in bytes",
    "type": "string"
},
"access_time": {
    "description": "Last time content was read, RFC 3339 format",
    "type": "string"
},
"modification_time": {
    "description": "Last time content was modified, RFC 3339 format",

```

```

        "type": "string"
    },
    "change_time": {
        "description": "Last time content or attributes were modified, RFC 3339
format",
        "type": "string"
    },
    "creation_time": {
        "description": "File creation time, RFC 3339 format",
        "type": "string"
    },
    "child_count": {
        "description": "Count of children (valid for directories)",
        "type": "number"
    },
    "extended_attributes": {
        "description": "SMB extended file attributes",
        "type": "object",
        "properties": {
            "read_only": {
                "description": "read_only",
                "type": "boolean"
            },
            "hidden": {
                "description": "hidden",
                "type": "boolean"
            },
            "system": {
                "description": "system",
                "type": "boolean"
            },
            "archive": {
                "description": "archive",
                "type": "boolean"
            },
            "temporary": {
                "description": "temporary",
                "type": "boolean"
            },
            "compressed": {
                "description": "compressed",
                "type": "boolean"
            },
            "not_content_indexed": {
                "description": "not_content_indexed",
                "type": "boolean"
            }
        }
    }
}

```

```

    },
    "sparse_file": {
      "description": "sparse_file",
      "type": "boolean"
    },
    "offline": {
      "description": "offline",
      "type": "boolean"
    }
  }
},
"directory_entry_hash_policy": {
  "type": "string",
  "enum": [
    "FS_DIRECTORY_HASH_VERSION_LOWER",
    "FS_DIRECTORY_HASH_VERSION_FOLDED"
  ],
  "description": "Hash policy for directory entries:\n * `FS_DIRECTORY_HASH_VERSION_FOLDED` - FS_DIRECTORY_HASH_VERSION_FOLDED,\n * `FS_DIRECTORY_HASH_VERSION_LOWER` - FS_DIRECTORY_HASH_VERSION_LOWER"
},
"data_revision": {
  "description": "The revision for changes to the underlying file data.",
  "type": "string"
},
"user_metadata_revision": {
  "description": "The revision for changes to the user defined metadata of the file.",
  "type": "string"
}
}
},
"file_acls": {
  "description": "Provides the ACL for each file. When include_acls is not requested, file_acls is null.",
  "type": "object",
  "properties": {
    "acl_pool": {
      "type": "array",
      "items": {
        "description": "The ACL pool which acl_indices references. To retrieve the ACL for files[i] look up acl_pool[acl_indices[i]].",
        "type": "object",
        "properties": {
          "control": {

```

```

    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "PRESENT",
        "DEFAULTED",
        "TRUSTED",
        "AUTO_INHERIT",
        "PROTECTED"
      ],
      "description": "control:\n * `AUTO_INHERIT` - Set whether the ACL was created through inheritance,\n * `DEFAULTED` - Sets whether the ACL was established by default means,\n * `PRESENT` - Set when ACL is present on the object,\n * `PROTECTED` - Protects ACL from inherit operations,\n * `TRUSTED` - Set when ACL is provided by a trusted source"
    },
    "posix_special_permissions": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "STICKY_BIT",
          "SET_GID",
          "SET_UID"
        ],
        "description": "posix_special_permissions:\n * `SET_GID` - SET_GID,\n * `SET_UID` - SET_UID,\n * `STICKY_BIT` - STICKY_BIT"
      },
      "aces": {
        "type": "array",
        "items": {
          "description": "aces",
          "type": "object",
          "properties": {
            "type": {
              "type": "string",
              "enum": [
                "ALLOWED",
                "DENIED"
              ],
              "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entry that grants rights,\n * `DENIED` - An ACL entry that denies rights"
            },
            "flags": {

```

```

    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "OBJECT_INHERIT",
        "CONTAINER_INHERIT",
        "NO_PROPAGATE_INHERIT",
        "INHERIT_ONLY",
        "INHERITED"
      ],
      "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"
    },
    "trustee": {
      "description": "Trustee for this ACL entry",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ],
          "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
        }
      }
    }
  },

```



```

    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  },
  "rights": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
      ],
      "description": "Rights granted or denied for this ACL entry:\n * `CHANGE_OWNER` - Owner write access,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEN

```


Request

Schema

```
{
  "description": "api_files_create_entry",
  "type": "object",
  "properties": {
    "name": {
      "description": "Name of file to create",
      "type": "string"
    },
    "action": {
      "type": "string",
      "enum": [
        "CREATE_FILE",
        "CREATE_DIRECTORY",
        "CREATE_SYMLINK",
        "CREATE_LINK",
        "RENAME",
        "CREATE_UNIX_FILE"
      ],
      "description": "Operation to perform:\n * `CREATE_DIRECTORY` - API_FILES_CREATE_DIRECTORY,\n * `CREATE_FILE` - API_FILES_CREATE_FILE,\n * `CREATE_LINK` - API_FILES_CREATE_LINK,\n * `CREATE_SYMLINK` - API_FILES_CREATE_SYMLINK,\n * `CREATE_UNIX_FILE` - API_FILES_CREATE_UNIX_FILE,\n * `RENAME` - API_FILES_RENAME"
    },
    "old_path": {
      "description": "Rename source or link target",
      "type": "string"
    },
    "clobber": {
      "description": "When action is RENAME, setting this to true will clobber the destination if it exists.",
      "type": "boolean"
    },
    "symlink_target_type": {
      "type": "string",
      "enum": [
        "FS_FILE_TYPE_UNKNOWN",
        "FS_FILE_TYPE_FILE",
        "FS_FILE_TYPE_DIRECTORY"
      ],
      "description": "The file type of the target to which the symbolic link points. If you don't specify the file type, or if it is FS_FILE_TYPE_UNKNOWN, the effect is the same as running the 'ln -s' command on a Unix NFS client. If the file type is FS_FILE_TYPE_FILE or FS_FILE_TYPE_DIRECTORY, the effect is the same as running th"
    }
  }
}
```

```

e 'mklink' or 'mklink /D' command on a Windows SMB client.:\\n * `FS_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\\n * `FS_FILE_TYPE_FILE` - API_SYMLINK_TARGET_FILE,\\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNOWN"
},
"unix_file_type": {
  "type": "string",
  "enum": [
    "FS_FILE_TYPE_FILE",
    "FS_FILE_TYPE_DIRECTORY",
    "FS_FILE_TYPE_SYMLINK",
    "FS_FILE_TYPE_UNIX_PIPE",
    "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
    "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
    "FS_FILE_TYPE_UNIX_SOCKET"
  ],
  "description": "Required when the action is CREATE_UNIX_FILE. You are given the choice of FS_FILE_TYPE_UNIX_BLOCK_DEVICE, FS_FILE_TYPE_UNIX_CHARACTER_DEVICE, FS_FILE_TYPE_UNIX_PIPE or FS_FILE_TYPE_UNIX_SOCKET:\\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
},
"major_minor_numbers": {
  "description": "When creating a UNIX device file, these are the major and minor numbers",
  "type": "object",
  "properties": {
    "major": {
      "description": "major",
      "type": "number"
    },
    "minor": {
      "description": "minor",
      "type": "number"
    }
  }
}
}
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_attributes",
  "type": "object",
  "properties": {
    "path": {
      "description": "Filesystem path of the object",
      "type": "string"
    },
    "name": {
      "description": "Name of this file",
      "type": "string"
    },
    "num_links": {
      "description": "How many directory entries are associated with this file",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "FS_FILE_TYPE_FILE",
        "FS_FILE_TYPE_DIRECTORY",
        "FS_FILE_TYPE_SYMLINK",
        "FS_FILE_TYPE_UNIX_PIPE",
        "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
        "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
        "FS_FILE_TYPE_UNIX_SOCKET"
      ],
      "description": "Resource type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
    },
    "major_minor_numbers": {
      "description": "The major and minor numbers for UNIX device files",

```

```

    "type": "object",
    "properties": {
      "major": {
        "description": "major",
        "type": "number"
      },
      "minor": {
        "description": "minor",
        "type": "number"
      }
    }
  },
  "symlink_target_type": {
    "type": "string",
    "enum": [
      "FS_FILE_TYPE_UNKNOWN",
      "FS_FILE_TYPE_FILE",
      "FS_FILE_TYPE_DIRECTORY"
    ],
    "description": "The type of the target file if this file is a symlink:\n * `FS_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - API_SYMLINK_TARGET_FILE,\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNOWN"
  },
  "file_number": {
    "description": "Unique ID of this file",
    "type": "string"
  },
  "id": {
    "description": "Unique ID of this file",
    "type": "string"
  },
  "mode": {
    "description": "POSIX-style file mode (octal)",
    "type": "string"
  },
  "owner": {
    "description": "File owner",
    "type": "string"
  },
  "owner_details": {
    "description": "File owner details",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [

```

```

        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
},
"group": {
    "description": "File group",
    "type": "string"
},
"group_details": {
    "description": "File group details",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ],
            "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {

```

```

        "description": "id_value",
        "type": "string"
    }
}
},
"blocks": {
    "description": "Number of blocks used by the file on this cluster",
    "type": "string"
},
"datablocks": {
    "description": "Number of data blocks used by the file on this cluster",
    "type": "string"
},
"metablocks": {
    "description": "Number of meta blocks used by the file on this cluster",
    "type": "string"
},
"logical_datablocks": {
    "description": "Number of data blocks used by the file",
    "type": "string"
},
"size": {
    "description": "File size in bytes",
    "type": "string"
},
"access_time": {
    "description": "Last time content was read, RFC 3339 format",
    "type": "string"
},
"modification_time": {
    "description": "Last time content was modified, RFC 3339 format",
    "type": "string"
},
"change_time": {
    "description": "Last time content or attributes were modified, RFC 3339 format",
    "type": "string"
},
"creation_time": {
    "description": "File creation time, RFC 3339 format",
    "type": "string"
},
"child_count": {
    "description": "Count of children (valid for directories)",
    "type": "number"
},

```



```

"extended_attributes": {
  "description": "SMB extended file attributes",
  "type": "object",
  "properties": {
    "read_only": {
      "description": "read_only",
      "type": "boolean"
    },
    "hidden": {
      "description": "hidden",
      "type": "boolean"
    },
    "system": {
      "description": "system",
      "type": "boolean"
    },
    "archive": {
      "description": "archive",
      "type": "boolean"
    },
    "temporary": {
      "description": "temporary",
      "type": "boolean"
    },
    "compressed": {
      "description": "compressed",
      "type": "boolean"
    },
    "not_content_indexed": {
      "description": "not_content_indexed",
      "type": "boolean"
    },
    "sparse_file": {
      "description": "sparse_file",
      "type": "boolean"
    },
    "offline": {
      "description": "offline",
      "type": "boolean"
    }
  }
},
"directory_entry_hash_policy": {
  "type": "string",
  "enum": [
    "FS_DIRECTORY_HASH_VERSION_LOWER",

```

```

        "FS_DIRECTORY_HASH_VERSION_FOLDED"
    ],
    "description": "Hash policy for directory entries:\n * `FS_DIRECTORY_HASH_VERSION_FOLDED` - FS_DIRECTORY_HASH_VERSION_FOLDED,\n * `FS_DIRECTORY_HASH_VERSION_LOWER` - FS_DIRECTORY_HASH_VERSION_LOWER"
},
    "data_revision": {
        "description": "The revision for changes to the underlying file data.",
        "type": "string"
    },
    "user_metadata_revision": {
        "description": "The revision for changes to the user defined metadata of the file.",
        "type": "string"
    }
}
}

```

files/{ref}/entries/{name}

Endpoint

`/v1/files/{ref}/entries/{name}`

DELETE

Delete the link specified by 'name' in the directory specified by 'ref'. The file system object is deleted if this was its last link. This operation is more convenient than 'DELETE /v1/files/' when the file ID of the directory is known in advance for deleting multiple files in one directory.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>name</code>	Name of the directory entry to be deleted	Yes

Response

Codes

Code	Description
200	Return value on success

files/{ref}/fetch-data

Endpoint

/v1/files/{ref}/fetch-data

POST

[preview] Performs a server-side read of the specified file region to populate cluster caches. Does not return file contents.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_files_fetch_data",
  "type": "object",
  "properties": {
    "offset": {
      "description": "The offset (in bytes) from where to begin fetching data.",
      "type": "string"
    },
    "length": {
      "description": "The maximum number of bytes to fetch. Equals to server target read size by default.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_fetch_data_result",
  "type": "object",
  "properties": {
    "bytes_fetched": {
      "description": "The number of bytes fetched into the cache.",
      "type": "string"
    },
    "next_offset": {
      "description": "The offset (in bytes) to use for the next fetch request. Empty at the end of the file.",
      "type": "string"
    }
  }
}
```

files/{ref}/file-lock

Endpoint

/v1/files/{ref}/file-lock

PATCH

Apply a permanent retention period or removable legal hold preventing deletion or modification of a file. The target file must already exist.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_patch_file_lock",
  "type": "object",
  "properties": {
    "retention_period": {
      "description": "A permanent retention period preventing files from being deleted or modified. The period can only be extended.",
      "type": "string"
    },
    "legal_hold": {
      "description": "A removable lock under which files cannot be deleted or modified.",
      "type": "boolean"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_get_files_attributes",
  "type": "object",
  "properties": {
    "path": {
      "description": "Filesystem path of the object",
      "type": "string"
    },
    "name": {
      "description": "Name of this file",
      "type": "string"
    },
    "num_links": {
      "description": "How many directory entries are associated with this file",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "FS_FILE_TYPE_FILE",
        "FS_FILE_TYPE_DIRECTORY",
        "FS_FILE_TYPE_SYMLINK",
        "FS_FILE_TYPE_UNIX_PIPE",
        "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
        "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
        "FS_FILE_TYPE_UNIX_SOCKET"
      ],
      "description": "Resource type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
    },
    "major_minor_numbers": {
      "description": "The major and minor numbers for UNIX device files",

```

```

"type": "object",
"properties": {
  "major": {
    "description": "major",
    "type": "number"
  },
  "minor": {
    "description": "minor",
    "type": "number"
  }
},
"symlink_target_type": {
  "type": "string",
  "enum": [
    "FS_FILE_TYPE_UNKNOWN",
    "FS_FILE_TYPE_FILE",
    "FS_FILE_TYPE_DIRECTORY"
  ],
  "description": "The type of the target file if this file is a symlink:\n * `FS_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - API_SYMLINK_TARGET_FILE,\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNOWN"
},
"file_number": {
  "description": "Unique ID of this file",
  "type": "string"
},
"id": {
  "description": "Unique ID of this file",
  "type": "string"
},
"mode": {
  "description": "POSIX-style file mode (octal)",
  "type": "string"
},
"owner": {
  "description": "File owner",
  "type": "string"
},
"owner_details": {
  "description": "File owner details",
  "type": "object",
  "properties": {
    "id_type": {
      "type": "string",
      "enum": [

```



```

        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
},
"group": {
    "description": "File group",
    "type": "string"
},
"group_details": {
    "description": "File group details",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ],
            "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {

```

```

        "description": "id_value",
        "type": "string"
    }
},
"blocks": {
    "description": "Number of blocks used by the file on this cluster",
    "type": "string"
},
"datablocks": {
    "description": "Number of data blocks used by the file on this cluster",
    "type": "string"
},
"metablocks": {
    "description": "Number of meta blocks used by the file on this cluster",
    "type": "string"
},
"logical_datablocks": {
    "description": "Number of data blocks used by the file",
    "type": "string"
},
"size": {
    "description": "File size in bytes",
    "type": "string"
},
"access_time": {
    "description": "Last time content was read, RFC 3339 format",
    "type": "string"
},
"modification_time": {
    "description": "Last time content was modified, RFC 3339 format",
    "type": "string"
},
"change_time": {
    "description": "Last time content or attributes were modified, RFC 3339 format",
    "type": "string"
},
"creation_time": {
    "description": "File creation time, RFC 3339 format",
    "type": "string"
},
"child_count": {
    "description": "Count of children (valid for directories)",
    "type": "number"
},

```

```

"extended_attributes": {
  "description": "SMB extended file attributes",
  "type": "object",
  "properties": {
    "read_only": {
      "description": "read_only",
      "type": "boolean"
    },
    "hidden": {
      "description": "hidden",
      "type": "boolean"
    },
    "system": {
      "description": "system",
      "type": "boolean"
    },
    "archive": {
      "description": "archive",
      "type": "boolean"
    },
    "temporary": {
      "description": "temporary",
      "type": "boolean"
    },
    "compressed": {
      "description": "compressed",
      "type": "boolean"
    },
    "not_content_indexed": {
      "description": "not_content_indexed",
      "type": "boolean"
    },
    "sparse_file": {
      "description": "sparse_file",
      "type": "boolean"
    },
    "offline": {
      "description": "offline",
      "type": "boolean"
    }
  }
},
"directory_entry_hash_policy": {
  "type": "string",
  "enum": [
    "FS_DIRECTORY_HASH_VERSION_LOWER",

```

```

        "FS_DIRECTORY_HASH_VERSION_FOLDED"
    ],
    "description": "Hash policy for directory entries:\n * `FS_DIRECTORY_HASH_VERSION_FOLDED` - FS_DIRECTORY_HASH_VERSION_FOLDED,\n * `FS_DIRECTORY_HASH_VERSION_LOWER` - FS_DIRECTORY_HASH_VERSION_LOWER"
},
    "data_revision": {
        "description": "The revision for changes to the underlying file data.",
        "type": "string"
    },
    "user_metadata_revision": {
        "description": "The revision for changes to the user defined metadata of the file.",
        "type": "string"
    },
    "lock": {
        "description": "When requested, the lock applied preventing file modification. Requires READ_ACL to read.",
        "type": "object",
        "properties": {
            "retention_period": {
                "description": "A permanent retention period preventing files from being deleted or modified. The period can only be extended.",
                "type": "string"
            },
            "legal_hold": {
                "description": "A removable lock under which files cannot be deleted or modified.",
                "type": "boolean"
            }
        }
    }
}

```

files/{ref}/info/acl

Endpoint

/v1/files/{ref}/info/acl

GET

Get file access control list (ACL).

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_acl_out",
  "type": "object",
  "properties": {
    "generated": {
      "description": "Set to true if the system has generated an ACL from Unix permissions",
      "type": "boolean"
    },
    "acl": {
      "description": "acl",
      "type": "object",
      "properties": {
```

```

"control": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "PRESENT",
      "DEFAULTED",
      "TRUSTED",
      "AUTO_INHERIT",
      "PROTECTED"
    ],
    "description": "control:\n * `AUTO_INHERIT` - Set whether the ACL was created through inheritance,\n * `DEFAULTED` - Sets whether the ACL was established by default means,\n * `PRESENT` - Set when ACL is present on the object,\n * `PROTECTED` - Protects ACL from inherit operations,\n * `TRUSTED` - Set when ACL is provided by a trusted source"
  },
  "posix_special_permissions": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "STICKY_BIT",
        "SET_GID",
        "SET_UID"
      ],
      "description": "posix_special_permissions:\n * `SET_GID` - SET_GID,\n * `SET_UID` - SET_UID,\n * `STICKY_BIT` - STICKY_BIT"
    },
    "aces": {
      "type": "array",
      "items": {
        "description": "aces",
        "type": "object",
        "properties": {
          "type": {
            "type": "string",
            "enum": [
              "ALLOWED",
              "DENIED"
            ],
            "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entry that grants rights,\n * `DENIED` - An ACL entry that denies rights"
          },

```

```

"flags": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "OBJECT_INHERIT",
      "CONTAINER_INHERIT",
      "NO_PROPAGATE_INHERIT",
      "INHERIT_ONLY",
      "INHERITED"
    ],
    "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"
  },
},
"trustee": {
  "description": "Trustee for this ACL entry",
  "type": "string"
},
"trustee_details": {
  "description": "Trustee details for this ACL entry",
  "type": "object",
  "properties": {
    "id_type": {
      "type": "string",
      "enum": [
        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
      ],
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",

```


Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_files_acl",
  "type": "object",
  "properties": {
    "control": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "PRESENT",
          "DEFAULTED",
          "TRUSTED",
          "AUTO_INHERIT",
          "PROTECTED"
        ]
      },
      "description": "control:\n * `AUTO_INHERIT` - Set whether the ACL was created through inheritance,\n * `DEFAULTED` - Sets whether the ACL was established by default means,\n * `PRESENT` - Set when ACL is present on the object,\n * `PROTECTED` - Protects ACL from inherit operations,\n * `TRUSTED` - Set when ACL is provided by a trusted source"
    },
    "posix_special_permissions": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "STICKY_BIT",
          "SET_GID",
          "SET_UID"
        ]
      }
    }
  }
}
```

```

    ],
    "description": "posix_special_permissions:\n * `SET_GID` - SET_GID,\n * `SE
T_UID` - SET_UID,\n * `STICKY_BIT` - STICKY_BIT"
  }
},
"aces": {
  "type": "array",
  "items": {
    "description": "aces",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entry tha
t grants rights,\n * `DENIED` - An ACL entry that denies rights"
      },
      "flags": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "OBJECT_INHERIT",
            "CONTAINER_INHERIT",
            "NO_PROPAGATE_INHERIT",
            "INHERIT_ONLY",
            "INHERITED"
          ],
          "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT`
- Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicate
s the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doe
sn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent sub
sequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children
inherit as effective ACE. Container objects inherit as inherit-only ACE"
        },
        "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT`
- Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicate
s the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doe
sn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent sub
sequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children
inherit as effective ACE. Container objects inherit as inherit-only ACE"
      }
    },
    "trustee": {
      "description": "Trustee for this ACL entry",
      "type": "string"
    },
    "trustee_details": {
      "description": "Trustee details for this ACL entry",
      "type": "object",

```

```

"properties": {
  "id_type": {
    "type": "string",
    "enum": [
      "LOCAL_USER",
      "LOCAL_GROUP",
      "NFS_GID",
      "NFS_UID",
      "SMB_SID",
      "INTERNAL",
      "QUMULO_OPERATOR",
      "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
  },
  "id_value": {
    "description": "id_value",
    "type": "string"
  }
},
"rights": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
      "DELETE",
      "EXECUTE",
      "MODIFY",
      "EXTEND",
      "DELETE_CHILD",
      "SYNCHRONIZE"
    ],
    "description": "Rights granted or denied for this ACL entry:\n * `CHAN

```



```

        "DEFAULTED",
        "TRUSTED",
        "AUTO_INHERIT",
        "PROTECTED"
    ],
    "description": "control:\n * `AUTO_INHERIT` - Set whether the ACL was created through inheritance,\n * `DEFAULTED` - Sets whether the ACL was established by default means,\n * `PRESENT` - Set when ACL is present on the object,\n * `PROTECTED` - Protects ACL from inherit operations,\n * `TRUSTED` - Set when ACL is provided by a trusted source"
    },
    "posix_special_permissions": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "STICKY_BIT",
                "SET_GID",
                "SET_UID"
            ]
        },
        "description": "posix_special_permissions:\n * `SET_GID` - SET_GID,\n * `SET_UID` - SET_UID,\n * `STICKY_BIT` - STICKY_BIT"
    },
    "aces": {
        "type": "array",
        "items": {
            "description": "aces",
            "type": "object",
            "properties": {
                "type": {
                    "type": "string",
                    "enum": [
                        "ALLOWED",
                        "DENIED"
                    ]
                },
                "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entry that grants rights,\n * `DENIED` - An ACL entry that denies rights"
            },
            "flags": {
                "type": "array",
                "items": {
                    "type": "string",
                    "enum": [
                        "OBJECT_INHERIT",

```

```

        "CONTAINER_INHERIT",
        "NO_PROPAGATE_INHERIT",
        "INHERIT_ONLY",
        "INHERITED"
    ],
    "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"
  },
  "trustee": {
    "description": "Trustee for this ACL entry",
    "type": "string"
  },
  "trustee_details": {
    "description": "Trustee details for this ACL entry",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ]
      },
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  }
},
"rights": {
  "type": "array",

```

```

        "items": {
            "type": "string",
            "enum": [
                "READ",
                "READ_EA",
                "READ_ATTR",
                "READ_ACL",
                "WRITE_EA",
                "WRITE_ATTR",
                "WRITE_ACL",
                "CHANGE_OWNER",
                "WRITE_GROUP",
                "DELETE",
                "EXECUTE",
                "MODIFY",
                "EXTEND",
                "DELETE_CHILD",
                "SYNCHRONIZE"
            ],
            "description": "Rights granted or denied for this ACL entry:\n *
`CHANGE_OWNER` - Owner write access,\n * `DELETE` - Delete access,\n * `DELETE_CHIL
D` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - Fi
le extension access,\n * `MODIFY` - File modification access,\n * `READ` - File rea
d access,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read acces
s,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchron
ize access,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write a
ccess,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group w
rite access"
        }
    }
}

```

files/{ref}/info/acl/explain-posix-mode

Endpoint

/v1/files/{ref}/info/acl/explain-posix-mode

POST

Explain the derived POSIX mode for a file/directory.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_derive_mode_explanation",
  "type": "object",
  "properties": {
    "mode": {
      "description": "The resulting mode",
      "type": "string"
    },
    "owner": {
      "description": "The user that owns the file.",
      "type": "object",
      "properties": {
        "domain": {
```



```

    "type": "string",
    "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
  },
  "auth_id": {
    "description": "auth_id",
    "type": "string"
  },
  "uid": {
    "description": "uid",
    "type": "number"
  },
  "gid": {
    "description": "gid",
    "type": "number"
  },
  "sid": {
    "description": "sid",
    "type": "string"
  },
  "name": {
    "description": "name",
    "type": "string"
  }
}
},
"group_owner": {

```

```

"description": "The group-owner for the file.",
"type": "object",
"properties": {
  "domain": {
    "type": "string",
    "enum": [
      "LOCAL",
      "API_NULL_DOMAIN",
      "WORLD",
      "POSIX_USER",
      "POSIX_GROUP",
      "ACTIVE_DIRECTORY",
      "API_INVALID_DOMAIN",
      "API_RESERVED_DOMAIN",
      "API_INTERNAL_DOMAIN",
      "API_OPERATOR_DOMAIN",
      "API_QUMULO_SUPPORT_DOMAIN",
      "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
  },
  "auth_id": {
    "description": "auth_id",
    "type": "string"
  },
  "uid": {
    "description": "uid",
    "type": "number"
  },
  "gid": {
    "description": "gid",
    "type": "number"
  },
  "sid": {
    "description": "sid",
    "type": "string"
  },
  "name": {
    "description": "name",
    "type": "string"
  }
}

```

```

    }
  },
  "posix_special_permissions": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "STICKY_BIT",
        "SET_GID",
        "SET_UID"
      ],
      "description": "posix_special_permissions:\n * `SET_GID` - SET_GID,\n * `SET_UID` - SET_UID,\n * `STICKY_BIT` - STICKY_BIT"
    }
  },
  "annotated_acl": {
    "type": "array",
    "items": {
      "description": "The explanation of the ACL's contribution to the derived mode at the point of each ACE.",
      "type": "object",
      "properties": {
        "ace": {
          "description": "Exact copy of the FS ACE.",
          "type": "object",
          "properties": {
            "type": {
              "type": "string",
              "enum": [
                "ALLOWED",
                "DENIED"
              ],
              "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entry that grants rights,\n * `DENIED` - An ACL entry that denies rights"
            }
          }
        },
        "flags": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": [
              "OBJECT_INHERIT",
              "CONTAINER_INHERIT",
              "NO_PROPAGATE_INHERIT",
              "INHERIT_ONLY",
              "INHERITED"
            ]
          }
        }
      }
    }
  }
}

```

```

    ],
    "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"
  }
},
"trustee": {
  "description": "Trustee for this ACL entry",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {

```

```

        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE"
        ],
        "description": "Rights granted or denied for this ACL entry:\n *
`CHANGE_OWNER` - Owner write access,\n * `DELETE` - Delete access,\n * `DELETE_CHIL
D` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - Fi
le extension access,\n * `MODIFY` - File modification access,\n * `READ` - File rea
d access,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read acces
s,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchron
ize access,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write a
ccess,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group w
rite access"
    }
}
}

```

```

    },
    "is_inherit_only": {
        "description": "Whether the ACE is inherit-only, and therefore whether we ignore the rights.",
        "type": "boolean"
    },
    "owner_rights": {
        "description": "Owner rights granted by this ACE.",
        "type": "object",
        "properties": {
            "match": {
                "type": "string",
                "enum": [
                    "NONE",
                    "EQUIVALENT",
                    "EVERYONE",
                    "POTENTIALLY_AFFECTED"
                ]
            },
            "description": "Match information for the current ACE trustee, i.e. why the ACE is affecting the mode segment or not.:\\n * `EQUIVALENT` - TRUSTEE_MATCH_EQUIVALENT,\\n * `EVERYONE` - TRUSTEE_MATCH_EVERYONE,\\n * `NONE` - TRUSTEE_MATCH_NONE,\\n * `POTENTIALLY_AFFECTED` - TRUSTEE_MATCH_POTENTIALLY_AFFECTED"
        },
        "newly_allowed": {
            "type": "array",
            "items": {
                "type": "string",
                "enum": [
                    "READ",
                    "READ_EA",
                    "READ_ATTR",
                    "READ_ACL",
                    "WRITE_EA",
                    "WRITE_ATTR",
                    "WRITE_ACL",
                    "CHANGE_OWNER",
                    "WRITE_GROUP",
                    "DELETE",
                    "EXECUTE",
                    "MODIFY",
                    "EXTEND",
                    "DELETE_CHILD",
                    "SYNCHRONIZE"
                ]
            },
            "description": "Rights allowed by the current ACE.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delet

```

e from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - File read access,\n * `READ\_ACL` - ACL read access,\n * `READ\_ATTR` - Attribute read access,\n * `READ\_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE\_ACL` - ACL write access,\n * `WRITE\_ATTR` - Attribute write access,\n * `WRITE\_EA` - Extended attribute write access,\n * `WRITE\_GROUP` - Group write access"

```

    }
  },
  "cumulative_allowed": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
      ],
      "description": "Rights allowed in total so far.: \n * `CHANGE_OWNER` - Owner write access,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - File read access,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
  },
  "newly_denied": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ",

```



```

        "description": "Rights denied in total so far.:\\n * `CHANGE_OWNE
R` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete f
rom directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension
access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n *
`READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_E
A` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n
* `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WR
ITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
  }
},
"group_rights": {
  "description": "Group rights granted by this ACE.",
  "type": "object",
  "properties": {
    "match": {
      "type": "string",
      "enum": [
        "NONE",
        "EQUIVALENT",
        "EVERYONE",
        "POTENTIALLY_AFFECTED"
      ],
      "description": "Match information for the current ACE trustee, i.e.
why the ACE is affecting the mode segment or not.:\\n * `EQUIVALENT` - TRUSTEE_MATC
H_EQUIVALENT,\\n * `EVERYONE` - TRUSTEE_MATCH_EVERYONE,\\n * `NONE` - TRUSTEE_MATCH_NO
NE,\\n * `POTENTIALLY_AFFECTED` - TRUSTEE_MATCH_POTENTIALLY_AFFECTED"
    },
    "newly_allowed": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "READ",
          "READ_EA",
          "READ_ATTR",
          "READ_ACL",
          "WRITE_EA",
          "WRITE_ATTR",
          "WRITE_ACL",
          "CHANGE_OWNER",
          "WRITE_GROUP",
          "DELETE",
          "EXECUTE",
          "MODIFY",

```

```

        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
    ],
    "description": "Rights allowed by the current ACE.:\\n * `CHANGE_OW
NER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delet
e from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extensi
on access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read acces
s,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `R
EAD_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize acces
s,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n
* `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write acces
s"
    }
},
"cumulative_allowed": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE"
        ]
    },
    "description": "Rights allowed in total so far.:\\n * `CHANGE_OWNE
R` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete f
rom directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension
access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n *
`READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_E
A` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n
* `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WR
ITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
},

```

```

    "newly_denied": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "READ",
          "READ_EA",
          "READ_ATTR",
          "READ_ACL",
          "WRITE_EA",
          "WRITE_ATTR",
          "WRITE_ACL",
          "CHANGE_OWNER",
          "WRITE_GROUP",
          "DELETE",
          "EXECUTE",
          "MODIFY",
          "EXTEND",
          "DELETE_CHILD",
          "SYNCHRONIZE"
        ],
        "description": "Rights denied by the current ACE.:\\n * `CHANGE_OWN  

ER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete  

from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extensio  

n access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n  

* `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_E  

A` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n  

* `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WR  

ITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
      }
    },
    "cumulative_denied": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "READ",
          "READ_EA",
          "READ_ATTR",
          "READ_ACL",
          "WRITE_EA",
          "WRITE_ATTR",
          "WRITE_ACL",
          "CHANGE_OWNER",
          "WRITE_GROUP",
          "DELETE",

```

```

        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
    ],
    "description": "Rights denied in total so far.:\\n * `CHANGE_OWNE
R` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete f
rom directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension
access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n *
`READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_E
A` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n
* `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WR
ITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
}
},
"other_rights": {
    "description": "Other rights granted by this ACE.",
    "type": "object",
    "properties": {
        "match": {
            "type": "string",
            "enum": [
                "NONE",
                "EQUIVALENT",
                "EVERYONE",
                "POTENTIALLY_AFFECTED"
            ],
            "description": "Match information for the current ACE trustee, i.e.
why the ACE is affecting the mode segment or not.:\\n * `EQUIVALENT` - TRUSTEE_MATC
H_EQUIVALENT,\\n * `EVERYONE` - TRUSTEE_MATCH_EVERYONE,\\n * `NONE` - TRUSTEE_MATCH_NO
NE,\\n * `POTENTIALLY_AFFECTED` - TRUSTEE_MATCH_POTENTIALLY_AFFECTED"
        },
        "newly_allowed": {
            "type": "array",
            "items": {
                "type": "string",
                "enum": [
                    "READ",
                    "READ_EA",
                    "READ_ATTR",
                    "READ_ACL",
                    "WRITE_EA",
                    "WRITE_ATTR",

```

```

        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
    ],
    "description": "Rights allowed by the current ACE.:\\n * `CHANGE_OW
NER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delet
e from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extensi
on access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read acces
s,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `R
EAD_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize acces
s,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n
* `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write acce
ss"
    }
},
"cumulative_allowed": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE"
        ]
    },
    "description": "Rights allowed in total so far.:\\n * `CHANGE_OWNE
R` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete f
rom directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension
access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n *

```

```

`READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_E
A` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n
* `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WR
ITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
  },
  "newly_denied": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
      ],
    },
    "description": "Rights denied by the current ACE.:\\n * `CHANGE_OWN
ER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete
from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extensio
n access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n
* `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_E
A` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n
* `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WR
ITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
  },
  "cumulative_denied": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",

```


files/{ref}/info/acl/explain-rights

Endpoint

/v1/files/{ref}/info/acl/explain-rights

POST

Explain how rights are granted to a user for a file/directory.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Request

Schema

```
{
  "description": "api_files_effective_rights_post",
  "type": "object",
  "properties": {
    "user": {
      "description": "The user for whom to explain effective rights.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
          ]
        }
      }
    }
  }
}
```



```

        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
},
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"primary_group": {
    "description": "The user's primary group.",
    "type": "object",
    "properties": {
        "domain": {
            "type": "string",
            "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",

```

```

        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
},
"auth_id": {
    "description": "auth_id",
    "type": "string"
},
"uid": {
    "description": "uid",
    "type": "number"
},
"gid": {
    "description": "gid",
    "type": "number"
},
"sid": {
    "description": "sid",
    "type": "string"
},
"name": {
    "description": "name",
    "type": "string"
}
}
},
"auxiliary_identities": {
    "type": "array",
    "items": {
        "description": "Any auxiliary identities for the user, e.g. additional groups or related identities.",
        "type": "object",
        "properties": {

```

```

"domain": {
  "type": "string",
  "enum": [
    "LOCAL",
    "API_NULL_DOMAIN",
    "WORLD",
    "POSIX_USER",
    "POSIX_GROUP",
    "ACTIVE_DIRECTORY",
    "API_INVALID_DOMAIN",
    "API_RESERVED_DOMAIN",
    "API_INTERNAL_DOMAIN",
    "API_OPERATOR_DOMAIN",
    "API_QUMULO_SUPPORT_DOMAIN",
    "API_CREATOR_DOMAIN"
  ],
  "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n *
`API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNA
L_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - AP
I_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPP
ORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DO
MAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSI
X_USER,\n * `WORLD` - WORLD"
},
"auth_id": {
  "description": "auth_id",
  "type": "string"
},
"uid": {
  "description": "uid",
  "type": "number"
},
"gid": {
  "description": "gid",
  "type": "number"
},
"sid": {
  "description": "sid",
  "type": "string"
},
"name": {
  "description": "name",
  "type": "string"
}
}
}

```

```

    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_files_effective_rights_explanation",
  "type": "object",
  "properties": {
    "owner": {
      "description": "The user that owns the file.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ],
          "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
        }
      }
    }
  }
}

```

```

    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  }
},
"group_owner": {
  "description": "The group-owner for the file.",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NUL

```

```

L_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_D
OMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAI
N,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_US
ER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"requestor": {
    "description": "The full identity whose rights are described.",
    "type": "object",
    "properties": {
        "user": {
            "description": "The user for whose rights are being explained.",
            "type": "object",
            "properties": {
                "domain": {
                    "type": "string",
                    "enum": [
                        "LOCAL",
                        "API_NULL_DOMAIN",
                        "WORLD",
                        "POSIX_USER",
                        "POSIX_GROUP",
                        "ACTIVE_DIRECTORY",
                        "API_INVALID_DOMAIN",
                        "API_RESERVED_DOMAIN",

```

```

        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
},
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"primary_group": {
    "description": "The user's primary group.",
    "type": "object",
    "properties": {
        "domain": {
            "type": "string",
            "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",

```

```

        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n
* `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNA
L_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - AP
I_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPP
ORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DO
MAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSI
X_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"auxiliary_identities": {
    "type": "array",
    "items": {
        "description": "Any auxiliary identities for the user, e.g. additional g
roups or related identities.",
        "type": "object",
        "properties": {

```



```

"domain": {
  "type": "string",
  "enum": [
    "LOCAL",
    "API_NULL_DOMAIN",
    "WORLD",
    "POSIX_USER",
    "POSIX_GROUP",
    "ACTIVE_DIRECTORY",
    "API_INVALID_DOMAIN",
    "API_RESERVED_DOMAIN",
    "API_INTERNAL_DOMAIN",
    "API_OPERATOR_DOMAIN",
    "API_QUMULO_SUPPORT_DOMAIN",
    "API_CREATOR_DOMAIN"
  ],
  "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
},
"auth_id": {
  "description": "auth_id",
  "type": "string"
},
"uid": {
  "description": "uid",
  "type": "number"
},
"gid": {
  "description": "gid",
  "type": "number"
},
"sid": {
  "description": "sid",
  "type": "string"
},
"name": {
  "description": "name",
  "type": "string"
}
}
}

```

```

    }
  },
  "admin_priv_rights": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
      ],
      "description": "Rights granted by possessing the administrator privileg
e.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELE
TE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEN
D` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - Fi
le read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read a
ccess,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File sync
hronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute wri
te access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Gro
up write access"
    }
  },
  "read_attr_priv_rights": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",

```

```

        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
    ],
    "description": "Rights granted by possessing the privilege to read attribute s.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
},
"annotated_aces": {
    "type": "array",
    "items": {
        "description": "An ACE-by-ACE explanation of rights granted to the user.",
        "type": "object",
        "properties": {
            "ace": {
                "description": "Exact copy of the FS ACE.",
                "type": "object",
                "properties": {
                    "type": {
                        "type": "string",
                        "enum": [
                            "ALLOWED",
                            "DENIED"
                        ]
                    },
                    "description": "Type of this ACL entry:\\n * `ALLOWED` - An ACL entry that grants rights,\\n * `DENIED` - An ACL entry that denies rights"
                }
            },
            "flags": {
                "type": "array",
                "items": {
                    "type": "string",
                    "enum": [
                        "OBJECT_INHERIT",

```

```

        "CONTAINER_INHERIT",
        "NO_PROPAGATE_INHERIT",
        "INHERIT_ONLY",
        "INHERITED"
    ],
    "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"
}
},
"trustee": {
    "description": "Trustee for this ACL entry",
    "type": "object",
    "properties": {
        "domain": {
            "type": "string",
            "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",
                "API_INVALID_DOMAIN",
                "API_RESERVED_DOMAIN",
                "API_INTERNAL_DOMAIN",
                "API_OPERATOR_DOMAIN",
                "API_QUMULO_SUPPORT_DOMAIN",
                "API_CREATOR_DOMAIN"
            ],
            "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
        },
        "auth_id": {
            "description": "auth_id",
            "type": "string"
        },
        "uid": {

```

```

        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE"
        ],
        "description": "Rights granted or denied for this ACL entry:\n *
`CHANGE_OWNER` - Owner write access,\n * `DELETE` - Delete access,\n * `DELETE_CHIL
D` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - Fi
le extension access,\n * `MODIFY` - File modification access,\n * `READ` - File rea
d access,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read acces
s,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchron
ize access,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write a
ccess,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group w

```

```

rite access"
    }
  }
},
"trustee_matches": {
  "description": "Whether this ACE's trustee matches the user in question.",
  "type": "boolean"
},
"skipped_inherit_only": {
  "description": "Whether this ACE does not affect rights due to being inherit-only.",
  "type": "boolean"
},
"newly_allowed": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
      "DELETE",
      "EXECUTE",
      "MODIFY",
      "EXTEND",
      "DELETE_CHILD",
      "SYNCHRONIZE"
    ]
  },
  "description": "Rights allowed by the current ACE.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
}
},

```

```

"cumulative_allowed": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
      "DELETE",
      "EXECUTE",
      "MODIFY",
      "EXTEND",
      "DELETE_CHILD",
      "SYNCHRONIZE"
    ],
    "description": "Rights allowed in total so far.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
  }
},
"newly_denied": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
      "DELETE",
    ]
  }
}

```

```

        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
    ],
    "description": "Rights denied by the current ACE.:\\n * `CHANGE_OWNER`  

- Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from di  

rectory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension acces  

s,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `REA  

D_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - E  

xtended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRI  

TE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_E  

A` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
},
"cumulative_denied": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE"
        ]
    },
    "description": "Rights denied in total so far.:\\n * `CHANGE_OWNER` - O  

wner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from di  

rectory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension acces  

s,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `REA  

D_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - E  

xtended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRI  

TE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_E  

A` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
}

```



```

    }
  }
},
"rights_from_aces": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
      "DELETE",
      "EXECUTE",
      "MODIFY",
      "EXTEND",
      "DELETE_CHILD",
      "SYNCHRONIZE"
    ],
    "description": "Rights granted by the file or directory's ACEs.:\\n * `CHANG  
E_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - De  
lete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File exte  
nsion access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read acces  
s,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `R  
EAD_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize acces  
s,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n  
* `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write acce  
ss"
  },
  "implicit_owner_rights_suppressed_by_ace": {
    "description": "Whether implicit rights for the owner were suppressed by an AC  
E for the well-known Owner Rights principal.",
    "type": "boolean"
  },
  "implicit_owner_rights": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [

```

```

        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
    ],
    "description": "Rights implicitly granted because the user in question owns
the file or directory.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Dele
te access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execut
e access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification acc
ess,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATT
R` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYN
CHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRIT
E_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write acces
s,\\n * `WRITE_GROUP` - Group write access"
    }
},
"implicit_rights_from_parent": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",

```

```

        "SYNCHRONIZE"
    ],
    "description": "Rights implicitly granted by this file or directory's container.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
},
"implicit_rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE"
        ]
    },
    "description": "Cumulative rights implicitly granted.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
},
"is_read_only": {
    "description": "Whether the file or directory in question is in read-only mode"
}
}

```

```

e.",
  "type": "boolean"
},
"max_rights": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
      "DELETE",
      "EXECUTE",
      "MODIFY",
      "EXTEND",
      "DELETE_CHILD",
      "SYNCHRONIZE"
    ]
  },
  "description": "Maximum rights which may be granted based on share permissions.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
}
},
"effective_rights": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",

```

```

        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
    ],
    "description": "Effective rights granted to the user in question for the file or directory.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
}
}
}

```

files/{ref}/info/acl/explain-set-mode

Endpoint

/v1/files/{ref}/info/acl/explain-set-mode

POST

Explain the effect of setting a POSIX mode on a file/directory.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Request

Schema

```
{
  "description": "api_files_apply_mode_explanation_post",
  "type": "object",
  "properties": {
    "mode": {
      "description": "POSIX mode to explain application of on a file ACL.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

```

{
  "description": "api_files_apply_mode_explanation",
  "type": "object",
  "properties": {
    "owner": {
      "description": "The user that owns the file.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ],
          "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
        },
        "auth_id": {
          "description": "auth_id",
          "type": "string"
        },
        "uid": {
          "description": "uid",
          "type": "number"
        },
        "gid": {
          "description": "gid",
          "type": "number"
        }
      }
    }
  }
}

```

```

    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  },
  "group_owner": {
    "description": "The group-owner for the file.",
    "type": "object",
    "properties": {
      "domain": {
        "type": "string",
        "enum": [
          "LOCAL",
          "API_NULL_DOMAIN",
          "WORLD",
          "POSIX_USER",
          "POSIX_GROUP",
          "ACTIVE_DIRECTORY",
          "API_INVALID_DOMAIN",
          "API_RESERVED_DOMAIN",
          "API_INTERNAL_DOMAIN",
          "API_OPERATOR_DOMAIN",
          "API_QUMULO_SUPPORT_DOMAIN",
          "API_CREATOR_DOMAIN"
        ],
        "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
      },
      "auth_id": {
        "description": "auth_id",
        "type": "string"
      },
      "uid": {
        "description": "uid",
        "type": "number"
      }
    }
  },

```



```

    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  },
  "owner_rights_from_mode": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
      ],
      "description": "The rights granted to the POSIX owner by the requested mode.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
  },

```

```

"group_rights_from_mode": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
      "DELETE",
      "EXECUTE",
      "MODIFY",
      "EXTEND",
      "DELETE_CHILD",
      "SYNCHRONIZE"
    ]
  },
  "description": "The rights granted to the POSIX group by the requested mode.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
}
},
"other_rights_from_mode": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
    ]
  }
}

```

```

        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
    ],
    "description": "The rights granted to the POSIX other by the requested mode.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
},
"max_extra_ace_allow": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE"
        ]
    },
    "description": "The maximum rights that any extra allow ACE can specify.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write a

```

```

ccess,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group w
rite access"
    }
  },
  "max_extra_ace_deny": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
      ],
      "description": "The maximum rights that any extra deny ACE can specify.:\\n
* `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHI
LD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - F
ile extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File rea
d access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read acces
s,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchron
ize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write a
ccess,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group w
rite access"
    }
  },
  "not_produced_by_any_mode": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",

```

```

        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
    ],
    "description": "Rights that are never produced by a POSIX mode bit.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    }
},
"not_visible_in_mode": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE"
        ]
    }
},
    "description": "Rights that will never cause a bit to be set in the displayed mode.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n *

```

```

`EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `REA
D` - File read access,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribut
e read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - F
ile synchronize access,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attri
bute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROU
P` - Group write access"
    }
  },
  "annotated_aces": {
    "type": "array",
    "items": {
      "description": "The annotated steps that would be taken to apply the request
ed mode to the source ACL.",
      "type": "object",
      "properties": {
        "source_ace": {
          "description": "Original ACE that this step affects.",
          "type": "object",
          "properties": {
            "type": {
              "type": "string",
              "enum": [
                "ALLOWED",
                "DENIED"
              ],
            },
            "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entr
y that grants rights,\n * `DENIED` - An ACL entry that denies rights"
          },
        },
        "flags": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": [
              "OBJECT_INHERIT",
              "CONTAINER_INHERIT",
              "NO_PROPAGATE_INHERIT",
              "INHERIT_ONLY",
              "INHERITED"
            ],
          },
          "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHER
IT` - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indic
ates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that
doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent
subsequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container childr
en inherit as effective ACE. Container objects inherit as inherit-only ACE"
        }
      }
    }
  }
}

```

```

},
"trustee": {
  "description": "Trustee for this ACL entry",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {

```

```

        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE"
        ],
        "description": "Rights granted or denied for this ACL entry:\n *
`CHANGE_OWNER` - Owner write access,\n * `DELETE` - Delete access,\n * `DELETE_CHIL
D` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - Fi
le extension access,\n * `MODIFY` - File modification access,\n * `READ` - File rea
d access,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read acces
s,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchron
ize access,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write a
ccess,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group w
rite access"
    }
}
},
"source_trustee_match": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "POSIX_OWNER",
            "POSIX_GROUP_OWNER",

```



```

        "POSIX_OTHERS",
        "NON_POSIX"
    ],
    "description": "Describes which POSIX mode classes the source ACE matches.\n * `NON_POSIX` - SOURCE_TRUSTEE_MATCH_NON_POSIX,\n * `POSIX_GROUP_OWNER` - SOURCE_TRUSTEE_MATCH_POSIX_GROUP_OWNER,\n * `POSIX_OTHERS` - SOURCE_TRUSTEE_MATCH_POSIX_OTHERS,\n * `POSIX_OWNER` - SOURCE_TRUSTEE_MATCH_POSIX_OWNER"
  }
},
"action": {
  "type": "string",
  "enum": [
    "COPY_ACE",
    "MODIFY_ACE",
    "INSERT_ACE",
    "REMOVE_ACE"
  ],
  "description": "The action being performed in this step to affect the ACL.\n * `COPY_ACE` - COPY_ACE,\n * `INSERT_ACE` - INSERT_ACE,\n * `MODIFY_ACE` - MODIFY_ACE,\n * `REMOVE_ACE` - REMOVE_ACE"
},
"reason": {
  "description": "An explanation of why the action is being performed.",
  "type": "string"
},
"rights_removed": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
      "DELETE",
      "EXECUTE",
      "MODIFY",
      "EXTEND",
      "DELETE_CHILD",
      "SYNCHRONIZE"
    ]
  }
},

```

```

        "description": "Any rights that are removed from the source ACE in this step.:\\n * `CHANGE_OWNER` - Owner write access,\\n * `DELETE` - Delete access,\\n * `DELETE_CHILD` - Delete from directory access,\\n * `EXECUTE` - Execute access,\\n * `EXTEND` - File extension access,\\n * `MODIFY` - File modification access,\\n * `READ` - File read access,\\n * `READ_ACL` - ACL read access,\\n * `READ_ATTR` - Attribute read access,\\n * `READ_EA` - Extended attribute read access,\\n * `SYNCHRONIZE` - File synchronize access,\\n * `WRITE_ACL` - ACL write access,\\n * `WRITE_ATTR` - Attribute write access,\\n * `WRITE_EA` - Extended attribute write access,\\n * `WRITE_GROUP` - Group write access"
    },
    "flags_removed": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "OBJECT_INHERIT",
                "CONTAINER_INHERIT",
                "NO_PROPAGATE_INHERIT",
                "INHERIT_ONLY",
                "INHERITED"
            ]
        },
        "description": "Any flags that are removed from the source ACE in this step.:\\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\\n * `INHERITED` - Indicates the ACE was inherited,\\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\\n * `NO_PROPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\\n * `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"
    },
    "flags_added": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "OBJECT_INHERIT",
                "CONTAINER_INHERIT",
                "NO_PROPAGATE_INHERIT",
                "INHERIT_ONLY",
                "INHERITED"
            ]
        },
        "description": "Any flags that are added from the source ACE in this step.:\\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\\n * `INHERITED` - Indicates the ACE was inherited,\\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\\n * `NO_PR

```

OPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\n \* `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"

```

    }
  },
  "result_ace": {
    "description": "The new ACE produced by this step.",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entry that grants rights,\n * `DENIED` - An ACL entry that denies rights"
      },
      "flags": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "OBJECT_INHERIT",
            "CONTAINER_INHERIT",
            "NO_PROPAGATE_INHERIT",
            "INHERIT_ONLY",
            "INHERITED"
          ],
          "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"
        }
      },
      "trustee": {
        "description": "Trustee for this ACL entry",
        "type": "object",
        "properties": {
          "domain": {
            "type": "string",
            "enum": [
              "LOCAL",
              "API_NULL_DOMAIN",

```

```

        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [

```

```

        "READ",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE"
    ],
    "description": "Rights granted or denied for this ACL entry:\n *
`CHANGE_OWNER` - Owner write access,\n * `DELETE` - Delete access,\n * `DELETE_CHIL
D` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - Fi
le extension access,\n * `MODIFY` - File modification access,\n * `READ` - File rea
d access,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read acces
s,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchron
ize access,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write a
ccess,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group w
rite access"
    }
}
}
}
}
},
"initial_acl": {
    "description": "The ACL originally on the file/directory in question.",
    "type": "object",
    "properties": {
        "control": {
            "type": "array",
            "items": {
                "type": "string",
                "enum": [
                    "PRESENT",
                    "DEFAULTED",
                    "TRUSTED",
                    "AUTO_INHERIT",
                    "PROTECTED"
                ]
            }
        }
    }
}

```

```

    ],
    "description": "control:\n * `AUTO_INHERIT` - Set whether the ACL was cr
eated through inheritance,\n * `DEFAULTED` - Sets whether the ACL was established b
y default means,\n * `PRESENT` - Set when ACL is present on the object,\n * `PROTECT
ED` - Protects ACL from inherit operations,\n * `TRUSTED` - Set when ACL is provide
d by a trusted source"
  }
},
"posix_special_permissions": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "STICKY_BIT",
      "SET_GID",
      "SET_UID"
    ],
    "description": "posix_special_permissions:\n * `SET_GID` - SET_GID,\n *
`SET_UID` - SET_UID,\n * `STICKY_BIT` - STICKY_BIT"
  }
},
"aces": {
  "type": "array",
  "items": {
    "description": "aces",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entr
y that grants rights,\n * `DENIED` - An ACL entry that denies rights"
      },
      "flags": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "OBJECT_INHERIT",
            "CONTAINER_INHERIT",
            "NO_PROPAGATE_INHERIT",
            "INHERIT_ONLY",
            "INHERITED"
          ]
        }
      }
    }
  }
}

```

```

    ],
    "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"
  }
},
"trustee": {
  "description": "Trustee for this ACL entry",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {

```

```

        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE"
        ],
        "description": "Rights granted or denied for this ACL entry:\n *
`CHANGE_OWNER` - Owner write access,\n * `DELETE` - Delete access,\n * `DELETE_CHIL
D` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - Fi
le extension access,\n * `MODIFY` - File modification access,\n * `READ` - File rea
d access,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read acces
s,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchron
ize access,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write a
ccess,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group w
rite access"
    }
}
}

```



```

    }
  }
},
"result_acl": {
  "description": "The ACL that would be produced by applying the requested mode.",
  "type": "object",
  "properties": {
    "control": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "PRESENT",
          "DEFAULTED",
          "TRUSTED",
          "AUTO_INHERIT",
          "PROTECTED"
        ]
      },
      "description": "control:\n * `AUTO_INHERIT` - Set whether the ACL was created through inheritance,\n * `DEFAULTED` - Sets whether the ACL was established by default means,\n * `PRESENT` - Set when ACL is present on the object,\n * `PROTECTED` - Protects ACL from inherit operations,\n * `TRUSTED` - Set when ACL is provided by a trusted source"
    },
    "posix_special_permissions": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "STICKY_BIT",
          "SET_GID",
          "SET_UID"
        ]
      },
      "description": "posix_special_permissions:\n * `SET_GID` - SET_GID,\n * `SET_UID` - SET_UID,\n * `STICKY_BIT` - STICKY_BIT"
    },
    "aces": {
      "type": "array",
      "items": {
        "description": "aces",
        "type": "object",
        "properties": {

```

```

"type": {
  "type": "string",
  "enum": [
    "ALLOWED",
    "DENIED"
  ],
  "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entry that grants rights,\n * `DENIED` - An ACL entry that denies rights"
},
"flags": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "OBJECT_INHERIT",
      "CONTAINER_INHERIT",
      "NO_PROPAGATE_INHERIT",
      "INHERIT_ONLY",
      "INHERITED"
    ]
  },
  "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"
},
"trustee": {
  "description": "Trustee for this ACL entry",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",

```

```

        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",

```


files/{ref}/info/attributes

Endpoint

/v1/files/{ref}/info/attributes

GET

Get file attributes.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
<code>retrieve-file-lock</code>	When specified, retrieve the file lock state for this file. Optional because retrieving the file lock requires READ_ACL permissions.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_get_files_attributes",
  "type": "object",
  "properties": {
    "path": {
      "description": "Filesystem path of the object",
      "type": "string"
    },
    "name": {
      "description": "Name of this file",

```

```

    "type": "string"
  },
  "num_links": {
    "description": "How many directory entries are associated with this file",
    "type": "number"
  },
  "type": {
    "type": "string",
    "enum": [
      "FS_FILE_TYPE_FILE",
      "FS_FILE_TYPE_DIRECTORY",
      "FS_FILE_TYPE_SYMLINK",
      "FS_FILE_TYPE_UNIX_PIPE",
      "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
      "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
      "FS_FILE_TYPE_UNIX_SOCKET"
    ],
    "description": "Resource type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
  },
  "major_minor_numbers": {
    "description": "The major and minor numbers for UNIX device files",
    "type": "object",
    "properties": {
      "major": {
        "description": "major",
        "type": "number"
      },
      "minor": {
        "description": "minor",
        "type": "number"
      }
    }
  },
  "symlink_target_type": {
    "type": "string",
    "enum": [
      "FS_FILE_TYPE_UNKNOWN",
      "FS_FILE_TYPE_FILE",
      "FS_FILE_TYPE_DIRECTORY"
    ],
    "description": "The type of the target file if this file is a symlink:\n * `F

```

```

S_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - AP
I_SYMLINK_TARGET_FILE,\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNOWN"
    },
    "file_number": {
      "description": "Unique ID of this file",
      "type": "string"
    },
    },
    "id": {
      "description": "Unique ID of this file",
      "type": "string"
    },
    },
    "mode": {
      "description": "POSIX-style file mode (octal)",
      "type": "string"
    },
    },
    "owner": {
      "description": "File owner",
      "type": "string"
    },
    },
    "owner_details": {
      "description": "File owner details",
      "type": "object",
      "properties": {
        "id_type": {
          "type": "string",
          "enum": [
            "LOCAL_USER",
            "LOCAL_GROUP",
            "NFS_GID",
            "NFS_UID",
            "SMB_SID",
            "INTERNAL",
            "QUMULO_OPERATOR",
            "QUMULO_SUPPORT"
          ],
          "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {
          "description": "id_value",
          "type": "string"
        }
      }
    },
    },
  },
}

```

```

"group": {
  "description": "File group",
  "type": "string"
},
"group_details": {
  "description": "File group details",
  "type": "object",
  "properties": {
    "id_type": {
      "type": "string",
      "enum": [
        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
      ],
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  }
},
"blocks": {
  "description": "Number of blocks used by the file on this cluster",
  "type": "string"
},
"datablocks": {
  "description": "Number of data blocks used by the file on this cluster",
  "type": "string"
},
"metablocks": {
  "description": "Number of meta blocks used by the file on this cluster",
  "type": "string"
},
"logical_datablocks": {
  "description": "Number of data blocks used by the file",
  "type": "string"
}

```



```

},
"size": {
  "description": "File size in bytes",
  "type": "string"
},
"access_time": {
  "description": "Last time content was read, RFC 3339 format",
  "type": "string"
},
"modification_time": {
  "description": "Last time content was modified, RFC 3339 format",
  "type": "string"
},
"change_time": {
  "description": "Last time content or attributes were modified, RFC 3339 format",
  "type": "string"
},
"creation_time": {
  "description": "File creation time, RFC 3339 format",
  "type": "string"
},
"child_count": {
  "description": "Count of children (valid for directories)",
  "type": "number"
},
"extended_attributes": {
  "description": "SMB extended file attributes",
  "type": "object",
  "properties": {
    "read_only": {
      "description": "read_only",
      "type": "boolean"
    },
    "hidden": {
      "description": "hidden",
      "type": "boolean"
    },
    "system": {
      "description": "system",
      "type": "boolean"
    },
    "archive": {
      "description": "archive",
      "type": "boolean"
    }
  }
},

```

```

    "temporary": {
      "description": "temporary",
      "type": "boolean"
    },
    "compressed": {
      "description": "compressed",
      "type": "boolean"
    },
    "not_content_indexed": {
      "description": "not_content_indexed",
      "type": "boolean"
    },
    "sparse_file": {
      "description": "sparse_file",
      "type": "boolean"
    },
    "offline": {
      "description": "offline",
      "type": "boolean"
    }
  }
},
"directory_entry_hash_policy": {
  "type": "string",
  "enum": [
    "FS_DIRECTORY_HASH_VERSION_LOWER",
    "FS_DIRECTORY_HASH_VERSION_FOLDED"
  ],
  "description": "Hash policy for directory entries:\n * `FS_DIRECTORY_HASH_VERSION_FOLDED` - FS_DIRECTORY_HASH_VERSION_FOLDED,\n * `FS_DIRECTORY_HASH_VERSION_LOWER` - FS_DIRECTORY_HASH_VERSION_LOWER"
},
"data_revision": {
  "description": "The revision for changes to the underlying file data.",
  "type": "string"
},
"user_metadata_revision": {
  "description": "The revision for changes to the user defined metadata of the file.",
  "type": "string"
},
"lock": {
  "description": "When requested, the lock applied preventing file modification. Requires READ_ACL to read.",
  "type": "object",
  "properties": {

```

```

    "retention_period": {
      "description": "A permanent retention period preventing files from being d
eleted or modified. The period can only be extended.",
      "type": "string"
    },
    "legal_hold": {
      "description": "A removable lock under which files cannot be deleted or mo
dified.",
      "type": "boolean"
    }
  }
}
}
}

```

PATCH

Update a subset of file attributes. Owner or mode bits change is done POSIX-style; file's ACL is updated to match the requested permissions.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_settable_files_attributes",
  "type": "object",
  "properties": {
    "path": {
      "description": "Filesystem path of the object",
      "type": "string"
    },
  },
}

```

```

"name": {
  "description": "Name of this file",
  "type": "string"
},
"num_links": {
  "description": "How many directory entries are associated with this file",
  "type": "number"
},
"type": {
  "type": "string",
  "enum": [
    "FS_FILE_TYPE_FILE",
    "FS_FILE_TYPE_DIRECTORY",
    "FS_FILE_TYPE_SYMLINK",
    "FS_FILE_TYPE_UNIX_PIPE",
    "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
    "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
    "FS_FILE_TYPE_UNIX_SOCKET"
  ],
  "description": "Resource type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
},
"major_minor_numbers": {
  "description": "The major and minor numbers for UNIX device files",
  "type": "object",
  "properties": {
    "major": {
      "description": "major",
      "type": "number"
    },
    "minor": {
      "description": "minor",
      "type": "number"
    }
  }
},
"symlink_target_type": {
  "type": "string",
  "enum": [
    "FS_FILE_TYPE_UNKNOWN",
    "FS_FILE_TYPE_FILE",
    "FS_FILE_TYPE_DIRECTORY"
  ]
}

```

```

    ],
    "description": "The type of the target file if this file is a symlink:\n * `F
S_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - AP
I_SYMLINK_TARGET_FILE,\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNOWN"
  },
  "file_number": {
    "description": "Unique ID of this file",
    "type": "string"
  },
  "id": {
    "description": "Unique ID of this file",
    "type": "string"
  },
  "mode": {
    "description": "POSIX-style file mode (octal)",
    "type": "string"
  },
  "owner": {
    "description": "File owner",
    "type": "string"
  },
  "owner_details": {
    "description": "File owner details",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ]
      },
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  }
}

```

```

    }
  },
  "group": {
    "description": "File group",
    "type": "string"
  },
  "group_details": {
    "description": "File group details",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ],
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO  
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N  
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO  
RT,\n * `SMB_SID` - SMB_SID"
      },
      "id_value": {
        "description": "id_value",
        "type": "string"
      }
    }
  },
  "blocks": {
    "description": "Number of blocks used by the file on this cluster",
    "type": "string"
  },
  "datablocks": {
    "description": "Number of data blocks used by the file on this cluster",
    "type": "string"
  },
  "metablocks": {
    "description": "Number of meta blocks used by the file on this cluster",
    "type": "string"
  },
  "logical_datablocks": {

```

```

    "description": "Number of data blocks used by the file",
    "type": "string"
  },
  "size": {
    "description": "File size in bytes",
    "type": "string"
  },
  "access_time": {
    "description": "Last time content was read, RFC 3339 format",
    "type": "string"
  },
  "modification_time": {
    "description": "Last time content was modified, RFC 3339 format",
    "type": "string"
  },
  "change_time": {
    "description": "Last time content or attributes were modified, RFC 3339 format",
    "type": "string"
  },
  "creation_time": {
    "description": "File creation time, RFC 3339 format",
    "type": "string"
  },
  "child_count": {
    "description": "Count of children (valid for directories)",
    "type": "number"
  },
  "extended_attributes": {
    "description": "SMB extended file attributes",
    "type": "object",
    "properties": {
      "read_only": {
        "description": "read_only",
        "type": "boolean"
      },
      "hidden": {
        "description": "hidden",
        "type": "boolean"
      },
      "system": {
        "description": "system",
        "type": "boolean"
      },
      "archive": {
        "description": "archive",

```

```

        "type": "boolean"
    },
    "temporary": {
        "description": "temporary",
        "type": "boolean"
    },
    "compressed": {
        "description": "compressed",
        "type": "boolean"
    },
    "not_content_indexed": {
        "description": "not_content_indexed",
        "type": "boolean"
    },
    "sparse_file": {
        "description": "sparse_file",
        "type": "boolean"
    },
    "offline": {
        "description": "offline",
        "type": "boolean"
    }
}
},
"directory_entry_hash_policy": {
    "type": "string",
    "enum": [
        "FS_DIRECTORY_HASH_VERSION_LOWER",
        "FS_DIRECTORY_HASH_VERSION_FOLDED"
    ],
    "description": "Hash policy for directory entries:\n * `FS_DIRECTORY_HASH_VERSION_FOLDED` - FS_DIRECTORY_HASH_VERSION_FOLDED,\n * `FS_DIRECTORY_HASH_VERSION_LOWER` - FS_DIRECTORY_HASH_VERSION_LOWER"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success


```

{
  "description": "api_get_files_attributes",
  "type": "object",
  "properties": {
    "path": {
      "description": "Filesystem path of the object",
      "type": "string"
    },
    "name": {
      "description": "Name of this file",
      "type": "string"
    },
    "num_links": {
      "description": "How many directory entries are associated with this file",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "FS_FILE_TYPE_FILE",
        "FS_FILE_TYPE_DIRECTORY",
        "FS_FILE_TYPE_SYMLINK",
        "FS_FILE_TYPE_UNIX_PIPE",
        "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
        "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
        "FS_FILE_TYPE_UNIX_SOCKET"
      ],
      "description": "Resource type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
    },
    "major_minor_numbers": {
      "description": "The major and minor numbers for UNIX device files",
      "type": "object",
      "properties": {
        "major": {
          "description": "major",
          "type": "number"
        },
        "minor": {
          "description": "minor",

```

```

        "type": "number"
    }
}
},
"symlink_target_type": {
    "type": "string",
    "enum": [
        "FS_FILE_TYPE_UNKNOWN",
        "FS_FILE_TYPE_FILE",
        "FS_FILE_TYPE_DIRECTORY"
    ],
    "description": "The type of the target file if this file is a symlink:\n * `F
S_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - AP
I_SYMLINK_TARGET_FILE,\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNOWN"
},
"file_number": {
    "description": "Unique ID of this file",
    "type": "string"
},
"id": {
    "description": "Unique ID of this file",
    "type": "string"
},
"mode": {
    "description": "POSIX-style file mode (octal)",
    "type": "string"
},
"owner": {
    "description": "File owner",
    "type": "string"
},
"owner_details": {
    "description": "File owner details",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ]
        }
    }
}

```

```

    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
},
"group": {
    "description": "File group",
    "type": "string"
},
"group_details": {
    "description": "File group details",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ],
            "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {
            "description": "id_value",
            "type": "string"
        }
    }
},
"blocks": {
    "description": "Number of blocks used by the file on this cluster",
    "type": "string"
}

```

```

},
"datablocks": {
  "description": "Number of data blocks used by the file on this cluster",
  "type": "string"
},
"metablocks": {
  "description": "Number of meta blocks used by the file on this cluster",
  "type": "string"
},
"logical_datablocks": {
  "description": "Number of data blocks used by the file",
  "type": "string"
},
"size": {
  "description": "File size in bytes",
  "type": "string"
},
"access_time": {
  "description": "Last time content was read, RFC 3339 format",
  "type": "string"
},
"modification_time": {
  "description": "Last time content was modified, RFC 3339 format",
  "type": "string"
},
"change_time": {
  "description": "Last time content or attributes were modified, RFC 3339 format",
  "type": "string"
},
"creation_time": {
  "description": "File creation time, RFC 3339 format",
  "type": "string"
},
"child_count": {
  "description": "Count of children (valid for directories)",
  "type": "number"
},
"extended_attributes": {
  "description": "SMB extended file attributes",
  "type": "object",
  "properties": {
    "read_only": {
      "description": "read_only",
      "type": "boolean"
    }
  }
},

```

```

    "hidden": {
      "description": "hidden",
      "type": "boolean"
    },
    "system": {
      "description": "system",
      "type": "boolean"
    },
    "archive": {
      "description": "archive",
      "type": "boolean"
    },
    "temporary": {
      "description": "temporary",
      "type": "boolean"
    },
    "compressed": {
      "description": "compressed",
      "type": "boolean"
    },
    "not_content_indexed": {
      "description": "not_content_indexed",
      "type": "boolean"
    },
    "sparse_file": {
      "description": "sparse_file",
      "type": "boolean"
    },
    "offline": {
      "description": "offline",
      "type": "boolean"
    }
  }
},
"directory_entry_hash_policy": {
  "type": "string",
  "enum": [
    "FS_DIRECTORY_HASH_VERSION_LOWER",
    "FS_DIRECTORY_HASH_VERSION_FOLDED"
  ],
  "description": "Hash policy for directory entries:\n * `FS_DIRECTORY_HASH_VERSION_FOLDED` - FS_DIRECTORY_HASH_VERSION_FOLDED,\n * `FS_DIRECTORY_HASH_VERSION_LOWER` - FS_DIRECTORY_HASH_VERSION_LOWER"
},
"data_revision": {
  "description": "The revision for changes to the underlying file data.",

```

```

    "type": "string"
  },
  "user_metadata_revision": {
    "description": "The revision for changes to the user defined metadata of the file.",
    "type": "string"
  },
  "lock": {
    "description": "When requested, the lock applied preventing file modification. Requires READ_ACL to read.",
    "type": "object",
    "properties": {
      "retention_period": {
        "description": "A permanent retention period preventing files from being deleted or modified. The period can only be extended.",
        "type": "string"
      },
      "legal_hold": {
        "description": "A removable lock under which files cannot be deleted or modified.",
        "type": "boolean"
      }
    }
  }
}

```

files/{ref}/locks/nfs4/byte-range/

Endpoint

/v1/files/{ref}/locks/nfs4/byte-range/

GET

Return a list of all NFSv4.1 byte range locks currently granted on the specified file.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_nfs4_byte_range_grants",
  "type": "object",
  "properties": {
    "grants": {
      "type": "array",
      "items": {
```

```

"description": "grants",
"type": "object",
"properties": {
  "file_id": {
    "description": "file_id",
    "type": "string"
  },
  "stream_id": {
    "description": "stream_id",
    "type": "string"
  },
  "snapshot_id": {
    "description": "The locked file's snapshot ID. Empty if the file is at the head version (not from a snapshot).",
    "type": "string"
  },
  "mode": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "API_BYTE_RANGE_EXCLUSIVE",
        "API_BYTE_RANGE_SHARED",
        "API_BYTE_RANGE_READ_OP",
        "API_BYTE_RANGE_WRITE_OP"
      ]
    },
    "description": "mode:\n * `API_BYTE_RANGE_EXCLUSIVE` - API_BYTE_RANGE_EXCLUSIVE,\n * `API_BYTE_RANGE_READ_OP` - API_BYTE_RANGE_READ_OP,\n * `API_BYTE_RANGE_SHARED` - API_BYTE_RANGE_SHARED,\n * `API_BYTE_RANGE_WRITE_OP` - API_BYTE_RANGE_WRITE_OP"
  },
  "offset": {
    "description": "offset",
    "type": "string"
  },
  "size": {
    "description": "size",
    "type": "string"
  },
  "owner_id": {
    "description": "The unique identifier for the process that owns the file lock.",
    "type": "string"
  },
  "owner_name": {

```


files/{ref}/locks/nlm/byte-range/

Endpoint

/v1/files/{ref}/locks/nlm/byte-range/

GET

Return a list of all NLM byte range locks currently granted on the specified file.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_byte_range_grants",
  "type": "object",
  "properties": {
    "grants": {
      "type": "array",
      "items": {
```

```

"description": "grants",
"type": "object",
"properties": {
  "file_id": {
    "description": "file_id",
    "type": "string"
  },
  "stream_id": {
    "description": "stream_id",
    "type": "string"
  },
  "snapshot_id": {
    "description": "The locked file's snapshot ID. Empty if the file is at the head version (not from a snapshot).",
    "type": "string"
  },
  "mode": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "API_BYTE_RANGE_EXCLUSIVE",
        "API_BYTE_RANGE_SHARED",
        "API_BYTE_RANGE_READ_OP",
        "API_BYTE_RANGE_WRITE_OP"
      ]
    },
    "description": "mode:\n * `API_BYTE_RANGE_EXCLUSIVE` - API_BYTE_RANGE_EXCLUSIVE,\n * `API_BYTE_RANGE_READ_OP` - API_BYTE_RANGE_READ_OP,\n * `API_BYTE_RANGE_SHARED` - API_BYTE_RANGE_SHARED,\n * `API_BYTE_RANGE_WRITE_OP` - API_BYTE_RANGE_WRITE_OP"
  },
  "offset": {
    "description": "offset",
    "type": "string"
  },
  "size": {
    "description": "size",
    "type": "string"
  },
  "owner_id": {
    "description": "The unique identifier for the process that owns the file lock.",
    "type": "string"
  },
  "owner_name": {

```

```
{
  "description": "The name of the machine that owns the lock.",
  "type": "string"
},
{
  "owner_address": {
    "description": "The IP address to use for acquiring the file lock.",
    "type": "string"
  },
  "node_address": {
    "description": "The IP address of the node that receives the request.",
    "type": "string"
  }
}
}
```

DELETE

Release an arbitrary lock range. This is dangerous, and should only be used after confirming that the owning process has leaked the lock, and only if there is a very good reason why the situation should not be resolved by terminating that process.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the <code>id</code> field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>offset</code>	Offset of the range to release	Yes
<code>size</code>	Size of range to release. Zero releases to the maximum file size.	Yes
<code>owner_id</code>	Opaque, unique identifier for the process that owns the lock. This is the <code>owner_id</code> attribute on entries returned by GET.	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Response

Codes

Code	Description
200	Return value on success

files/{ref}/locks/nlm/byte-range/waiters/

Endpoint

/v1/files/{ref}/locks/nlm/byte-range/waiters/

GET

Return a list of all NLM byte range requests currently waiting on the specified file.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_byte_range_waiters",
  "type": "object",
  "properties": {
    "waiters": {
      "type": "array",
      "items": {
```

```

"description": "waiters",
"type": "object",
"properties": {
  "file_id": {
    "description": "file_id",
    "type": "string"
  },
  "stream_id": {
    "description": "stream_id",
    "type": "string"
  },
  "snapshot_id": {
    "description": "The locked file's snapshot ID. Empty if the file is at the head version (not from a snapshot).",
    "type": "string"
  },
  "mode": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "API_BYTE_RANGE_EXCLUSIVE",
        "API_BYTE_RANGE_SHARED",
        "API_BYTE_RANGE_READ_OP",
        "API_BYTE_RANGE_WRITE_OP"
      ]
    },
    "description": "mode:\n * `API_BYTE_RANGE_EXCLUSIVE` - API_BYTE_RANGE_EXCLUSIVE,\n * `API_BYTE_RANGE_READ_OP` - API_BYTE_RANGE_READ_OP,\n * `API_BYTE_RANGE_SHARED` - API_BYTE_RANGE_SHARED,\n * `API_BYTE_RANGE_WRITE_OP` - API_BYTE_RANGE_WRITE_OP"
  },
  "offset": {
    "description": "offset",
    "type": "string"
  },
  "size": {
    "description": "size",
    "type": "string"
  },
  "owner_id": {
    "description": "The unique identifier for the process that owns the file lock.",
    "type": "string"
  },
  "owner_name": {

```

```
    "description": "The name of the machine that owns the lock.",
    "type": "string"
  },
  "owner_address": {
    "description": "The IP address to use for acquiring the file lock.",
    "type": "string"
  },
  "node_address": {
    "description": "The IP address of the node that receives the request.",
    "type": "string"
  }
}
}
```


files/{ref}/locks/smb/byte-range/

Endpoint

/v1/files/{ref}/locks/smb/byte-range/

GET

Return a list of all SMB byte range locks currently granted on the specified file.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_byte_range_grants",
  "type": "object",
  "properties": {
    "grants": {
      "type": "array",
      "items": {
```

```

"description": "grants",
"type": "object",
"properties": {
  "file_id": {
    "description": "file_id",
    "type": "string"
  },
  "stream_id": {
    "description": "stream_id",
    "type": "string"
  },
  "snapshot_id": {
    "description": "The locked file's snapshot ID. Empty if the file is at the head version (not from a snapshot).",
    "type": "string"
  },
  "mode": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "API_BYTE_RANGE_EXCLUSIVE",
        "API_BYTE_RANGE_SHARED",
        "API_BYTE_RANGE_READ_OP",
        "API_BYTE_RANGE_WRITE_OP"
      ]
    },
    "description": "mode:\n * `API_BYTE_RANGE_EXCLUSIVE` - API_BYTE_RANGE_EXCLUSIVE,\n * `API_BYTE_RANGE_READ_OP` - API_BYTE_RANGE_READ_OP,\n * `API_BYTE_RANGE_SHARED` - API_BYTE_RANGE_SHARED,\n * `API_BYTE_RANGE_WRITE_OP` - API_BYTE_RANGE_WRITE_OP"
  },
  "offset": {
    "description": "offset",
    "type": "string"
  },
  "size": {
    "description": "size",
    "type": "string"
  },
  "owner_id": {
    "description": "The unique identifier for the process that owns the file lock.",
    "type": "string"
  },
  "owner_name": {

```

```
    "description": "The name of the machine that owns the lock.",
    "type": "string"
  },
  "owner_address": {
    "description": "The IP address to use for acquiring the file lock.",
    "type": "string"
  },
  "node_address": {
    "description": "The IP address of the node that receives the request.",
    "type": "string"
  }
}
}
```

files/{ref}/locks/smb/share-mode/

Endpoint

/v1/files/{ref}/locks/smb/share-mode/

GET

Return a list of all SMB share mode locks currently granted on the specified file.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_share_mode_grants",
  "type": "object",
  "properties": {
    "grants": {
      "type": "array",
      "items": {
```

```

"description": "grants",
"type": "object",
"properties": {
  "file_id": {
    "description": "file_id",
    "type": "string"
  },
  "stream_id": {
    "description": "stream_id",
    "type": "string"
  },
  "snapshot_id": {
    "description": "The locked file's snapshot ID. Empty if the file is at the head version (not from a snapshot).",
    "type": "string"
  },
  "mode": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "API_SHARE_MODE_READ",
        "API_SHARE_MODE_WRITE",
        "API_SHARE_MODE_DELETE",
        "API_SHARE_MODE_EXCLUDE_READ",
        "API_SHARE_MODE_EXCLUDE_WRITE",
        "API_SHARE_MODE_EXCLUDE_DELETE"
      ]
    },
    "description": "mode:\n * `API_SHARE_MODE_DELETE` - API_SHARE_MODE_DELETE,\n * `API_SHARE_MODE_EXCLUDE_DELETE` - API_SHARE_MODE_EXCLUDE_DELETE,\n * `API_SHARE_MODE_EXCLUDE_READ` - API_SHARE_MODE_EXCLUDE_READ,\n * `API_SHARE_MODE_EXCLUDE_WRITE` - API_SHARE_MODE_EXCLUDE_WRITE,\n * `API_SHARE_MODE_READ` - API_SHARE_MODE_READ,\n * `API_SHARE_MODE_WRITE` - API_SHARE_MODE_WRITE"
  },
  "owner_id": {
    "description": "The unique identifier for the process that owns the file lock.",
    "type": "string"
  },
  "owner_address": {
    "description": "The IP address to use for acquiring the file lock.",
    "type": "string"
  },
  "node_address": {
    "description": "The IP address of the node that receives the request.",

```

```
    "type": "string"  
  }  
}  
}  
}
```

files/{ref}/notify

Endpoint

/v1/files/{ref}/notify

GET

Streams notifications for file system activity, monitoring only the files in the specified directory by using HTML server-sent events (SSE). The SSE data payload contains JSON-encoded event objects. For example: [{"type": , "path": , "stream_name": }].

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
filter	A list that indicates the types of notification that you want to receive, in CSV format. If you don't provide the list, the system sends every type of notification. The following are available notification types: child_file_added * child_dir_added * child_file_removed * child_dir_re- moved * child_file_moved_from * child_file_moved_to * child_dir_moved_from * child_dir_moved_to * child_btime_changed * child_mtime_changed * child_atime_changed * child_size_changed * child_extra_attrs_changed * child_acl_changed * child_own- er_changed * child_group_changed * child_data_written * child_stream_added * child_stream_removed * child_stream_moved_from * child_stream_moved_to * child_stream_size_changed * child_stream_data_written * self_re- moved	No
recursive	Specifies whether notifications are recursive. A recursive notification emits events for all files in the entire directory tree of the specified di- rectory. A non-recursive notification emits events only for files that are immediately below (but not further down the directory tree) for the specified directory. To configure recursion for notifications, use the /v1/ file-system/settings/notify REST API resource.	No

Response

Codes

Code	Description
200	Return value on success

files/{ref}/punch-hole

Endpoint

/v1/files/{ref}/punch-hole

POST

Create a hole in a region of a file. Destroys all data within the hole so that subsequent reads will return zeroes. Returns the post-operation attributes of the file.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_files_punch_hole",
  "type": "object",
  "properties": {
    "offset": {
      "description": "Offset in bytes specifying the start of the hole to create.",
      "type": "string"
    },
    "size": {
      "description": "Size in bytes of the hole to create.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_attributes",
  "type": "object",
  "properties": {
    "path": {
      "description": "Filesystem path of the object",
      "type": "string"
    },
    "name": {
      "description": "Name of this file",
      "type": "string"
    },
    "num_links": {
      "description": "How many directory entries are associated with this file",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "FS_FILE_TYPE_FILE",
        "FS_FILE_TYPE_DIRECTORY",
        "FS_FILE_TYPE_SYMLINK",
        "FS_FILE_TYPE_UNIX_PIPE",
        "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
        "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
        "FS_FILE_TYPE_UNIX_SOCKET"
      ],
      "description": "Resource type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
    },
    "major_minor_numbers": {
      "description": "The major and minor numbers for UNIX device files",

```

```

    "type": "object",
    "properties": {
      "major": {
        "description": "major",
        "type": "number"
      },
      "minor": {
        "description": "minor",
        "type": "number"
      }
    }
  },
  "symlink_target_type": {
    "type": "string",
    "enum": [
      "FS_FILE_TYPE_UNKNOWN",
      "FS_FILE_TYPE_FILE",
      "FS_FILE_TYPE_DIRECTORY"
    ],
    "description": "The type of the target file if this file is a symlink:\n * `FS_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - API_SYMLINK_TARGET_FILE,\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNOWN"
  },
  "file_number": {
    "description": "Unique ID of this file",
    "type": "string"
  },
  "id": {
    "description": "Unique ID of this file",
    "type": "string"
  },
  "mode": {
    "description": "POSIX-style file mode (octal)",
    "type": "string"
  },
  "owner": {
    "description": "File owner",
    "type": "string"
  },
  "owner_details": {
    "description": "File owner details",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [

```

```

        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
},
"group": {
    "description": "File group",
    "type": "string"
},
"group_details": {
    "description": "File group details",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ],
            "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {

```

```

        "description": "id_value",
        "type": "string"
    }
},
"blocks": {
    "description": "Number of blocks used by the file on this cluster",
    "type": "string"
},
"datablocks": {
    "description": "Number of data blocks used by the file on this cluster",
    "type": "string"
},
"metablocks": {
    "description": "Number of meta blocks used by the file on this cluster",
    "type": "string"
},
"logical_datablocks": {
    "description": "Number of data blocks used by the file",
    "type": "string"
},
"size": {
    "description": "File size in bytes",
    "type": "string"
},
"access_time": {
    "description": "Last time content was read, RFC 3339 format",
    "type": "string"
},
"modification_time": {
    "description": "Last time content was modified, RFC 3339 format",
    "type": "string"
},
"change_time": {
    "description": "Last time content or attributes were modified, RFC 3339 format",
    "type": "string"
},
"creation_time": {
    "description": "File creation time, RFC 3339 format",
    "type": "string"
},
"child_count": {
    "description": "Count of children (valid for directories)",
    "type": "number"
},

```

```

"extended_attributes": {
  "description": "SMB extended file attributes",
  "type": "object",
  "properties": {
    "read_only": {
      "description": "read_only",
      "type": "boolean"
    },
    "hidden": {
      "description": "hidden",
      "type": "boolean"
    },
    "system": {
      "description": "system",
      "type": "boolean"
    },
    "archive": {
      "description": "archive",
      "type": "boolean"
    },
    "temporary": {
      "description": "temporary",
      "type": "boolean"
    },
    "compressed": {
      "description": "compressed",
      "type": "boolean"
    },
    "not_content_indexed": {
      "description": "not_content_indexed",
      "type": "boolean"
    },
    "sparse_file": {
      "description": "sparse_file",
      "type": "boolean"
    },
    "offline": {
      "description": "offline",
      "type": "boolean"
    }
  }
},
"directory_entry_hash_policy": {
  "type": "string",
  "enum": [
    "FS_DIRECTORY_HASH_VERSION_LOWER",

```

```

        "FS_DIRECTORY_HASH_VERSION_FOLDED"
    ],
    "description": "Hash policy for directory entries:\n * `FS_DIRECTORY_HASH_VERSION_FOLDED` - FS_DIRECTORY_HASH_VERSION_FOLDED,\n * `FS_DIRECTORY_HASH_VERSION_LOWER` - FS_DIRECTORY_HASH_VERSION_LOWER"
},
    "data_revision": {
        "description": "The revision for changes to the underlying file data.",
        "type": "string"
    },
    "user_metadata_revision": {
        "description": "The revision for changes to the user defined metadata of the file.",
        "type": "string"
    }
}
}

```

files/{ref}/recursive-aggregates/

Endpoint

/v1/files/{ref}/recursive-aggregates/

GET

Return aggregated data for this directory and its children. It does a breadth-first traversal of directories up to the user-specified limit (see `max_entries` and `max_depth` parameters) or system-imposed limit. Directory entries that are smaller than 10% of the directory's total size are omitted.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the <code>id</code> field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>max-entries</code>	Maximum directory entries we see before breaking out of the tree walk (default: 1000, system limit: 5000)	No
<code>max-depth</code>	Maximum depth to traverse while doing the tree walk (default: 10, system limit: 5000)	No
<code>order-by</code>	Ordering field used for top N selection and sorting (default: <code>total_blocks</code>): <code>* `total_blocks` - total_blocks, * `total_datablocks` - total_datablocks, * `total_directories` - total_directories, * `total_files` - total_files, * `total_metablocks` - total_metablocks, * `total_named_stream_datablocks` - total_named_stream_datablocks, * `total_named_streams` - total_named_streams, * `total_other` - total_other, * `total_symlinks` - total_symlinks</code>	No
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_files_dir_aggregates",
    "type": "object",
    "properties": {
      "path": {
        "description": "path",
        "type": "string"
      },
      "id": {
        "description": "id",
        "type": "string"
      },
      "files": {
        "type": "array",
        "items": {
          "description": "files",
          "type": "object",
          "properties": {
            "name": {
              "description": "Name of this file or directory",
              "type": "string"
            },
            "type": {
              "type": "string",
              "enum": [
                "FS_FILE_TYPE_FILE",
                "FS_FILE_TYPE_DIRECTORY",
                "FS_FILE_TYPE_SYMLINK",
                "FS_FILE_TYPE_UNIX_PIPE",
                "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
                "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
                "FS_FILE_TYPE_UNIX_SOCKET"
              ],
              "description": "type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
            },
            "id": {
              "description": "Unique ID of this file or directory",

```

```

        "type": "string"
    },
    "capacity_usage": {
        "description": "Capacity used by this file, or directory and all its c
children, in bytes",
        "type": "string"
    },
    "data_usage": {
        "description": "Capacity used for data by this file, or directory and
all its children, in bytes",
        "type": "string"
    },
    "meta_usage": {
        "description": "Capacity used for metadata by this file, or directory
and all its children, in bytes",
        "type": "string"
    },
    "num_files": {
        "description": "Total number of files in the directory",
        "type": "string"
    },
    "num_directories": {
        "description": "Total number of directories in the directory",
        "type": "string"
    },
    "num_symlinks": {
        "description": "Total number of symlinks in the directory",
        "type": "string"
    },
    "num_other_objects": {
        "description": "Total number of Unix devices, pipes, and sockets in th
e directory",
        "type": "string"
    },
    "named_stream_data_usage": {
        "description": "Capacity used for data by named streams on this file,
or directory and all its children, in bytes",
        "type": "string"
    },
    "num_named_streams": {
        "description": "Total number of named streams in the directory",
        "type": "string"
    }
}
},
},

```

```

    "total_capacity": {
      "description": "total_capacity",
      "type": "string"
    },
    "total_data": {
      "description": "total_data",
      "type": "string"
    },
    "total_named_stream_data": {
      "description": "total_named_stream_data",
      "type": "string"
    },
    "total_meta": {
      "description": "total_meta",
      "type": "string"
    },
    "total_files": {
      "description": "total_files",
      "type": "string"
    },
    "total_directories": {
      "description": "total_directories",
      "type": "string"
    },
    "total_symlinks": {
      "description": "total_symlinks",
      "type": "string"
    },
    "total_other_objects": {
      "description": "total_other_objects",
      "type": "string"
    },
    "total_named_streams": {
      "description": "total_named_streams",
      "type": "string"
    }
  }
}
}

```

files/{ref}/sample/

Endpoint

/v1/files/{ref}/sample/

GET

Retrieve a random sampling of files, with the probability of being chosen based on by-value property.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
by-value	Weight the sampling by the value specified: capacity (total bytes used for data and metadata), data (total bytes used for data only), file (file count), named_streams (named stream count): * `capacity` - capacity, * `data` - data, * `file` - file, * `named_streams` - named_streams	Yes
limit	Maximum number of entries returned	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_files_aggregates",
    "type": "object",
    "properties": {
      "name": {
        "description": "Name of this file or directory",
```

```

    "type": "string"
  },
  "type": {
    "type": "string",
    "enum": [
      "FS_FILE_TYPE_FILE",
      "FS_FILE_TYPE_DIRECTORY",
      "FS_FILE_TYPE_SYMLINK",
      "FS_FILE_TYPE_UNIX_PIPE",
      "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
      "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
      "FS_FILE_TYPE_UNIX_SOCKET"
    ],
    "description": "type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTOR  
Y,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FIL  
E_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVIC  
E,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET`  
- FS_FILE_TYPE_UNIX_SOCKET"
  },
  "id": {
    "description": "Unique ID of this file or directory",
    "type": "string"
  },
  "capacity_usage": {
    "description": "Capacity used by this file, or directory and all its childre  
n, in bytes",
    "type": "string"
  },
  "data_usage": {
    "description": "Capacity used for data by this file, or directory and all it  
s children, in bytes",
    "type": "string"
  },
  "meta_usage": {
    "description": "Capacity used for metadata by this file, or directory and al  
l its children, in bytes",
    "type": "string"
  },
  "num_files": {
    "description": "Total number of files in the directory",
    "type": "string"
  },
  "num_directories": {
    "description": "Total number of directories in the directory",
    "type": "string"
  }
}

```

```

    },
    "num_symlinks": {
      "description": "Total number of symlinks in the directory",
      "type": "string"
    },
    "num_other_objects": {
      "description": "Total number of Unix devices, pipes, and sockets in the directory",
      "type": "string"
    },
    "named_stream_data_usage": {
      "description": "Capacity used for data by named streams on this file, or directory and all its children, in bytes",
      "type": "string"
    },
    "num_named_streams": {
      "description": "Total number of named streams in the directory",
      "type": "string"
    }
  }
}

```

files/{ref}/streams/

Endpoint

/v1/files/{ref}/streams/

GET

List all named streams on provided object

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_named_stream_attributes",
    "type": "object",
    "properties": {
      "name": {
        "description": "name",
        "type": "string"
      },
      "id": {
        "description": "id",
        "type": "string"
      }
    }
  }
}
```

```

    },
    "size": {
      "description": "Size of the stream in bytes",
      "type": "string"
    },
    "datablocks": {
      "description": "Number of data blocks used by the stream on this cluster",
      "type": "string"
    },
    "logical_datablocks": {
      "description": "Number of data blocks used by the stream",
      "type": "string"
    },
    "data_revision": {
      "description": "Counter that increases with every data change to the stream",
      "type": "string"
    }
  }
}

```

POST

Create a named stream on provided object

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_named_stream_entry",
  "type": "object",

```



```

"properties": {
  "stream_name": {
    "description": "Stream name to be created.",
    "type": "string"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_named_stream_attributes",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "id": {
      "description": "id",
      "type": "string"
    },
    "size": {
      "description": "Size of the stream in bytes",
      "type": "string"
    },
    "datablocks": {
      "description": "Number of data blocks used by the stream on this cluster",
      "type": "string"
    },
    "logical_datablocks": {
      "description": "Number of data blocks used by the stream",
      "type": "string"
    },
    "data_revision": {
      "description": "Counter that increases with every data change to the stream",
      "type": "string"
    }
  }
}

```

```
}  
}  
}
```

files/{ref}/streams/{stream_id}

Endpoint

/v1/files/{ref}/streams/{stream_id}

DELETE

Delete a named stream on provided object

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>stream_id</code>	Stream ID (u64) to be deleted	Yes

Response

Codes

Code	Description
200	Return value on success

files/{ref}/streams/{stream_id}/attributes

Endpoint

/v1/files/{ref}/streams/{stream_id}/attributes

GET

Get Stream attributes.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>stream_id</code>	Stream ID (u64) to get	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_named_stream_attributes",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "id": {
      "description": "id",
```

```

    "type": "string"
  },
  "size": {
    "description": "Size of the stream in bytes",
    "type": "string"
  },
  "datablocks": {
    "description": "Number of data blocks used by the stream on this cluster",
    "type": "string"
  },
  "logical_datablocks": {
    "description": "Number of data blocks used by the stream",
    "type": "string"
  },
  "data_revision": {
    "description": "Counter that increases with every data change to the stream",
    "type": "string"
  }
}
}

```

PATCH

Update a subset of stream attributes

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>stream_id</code>	Stream ID (u64) to get	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_settable_files_attributes",
  "type": "object",
  "properties": {
    "path": {
      "description": "Filesystem path of the object",
      "type": "string"
    },
    "name": {
      "description": "Name of this file",
      "type": "string"
    },
    "num_links": {
      "description": "How many directory entries are associated with this file",
      "type": "number"
    },
    "type": {
      "type": "string",
      "enum": [
        "FS_FILE_TYPE_FILE",
        "FS_FILE_TYPE_DIRECTORY",
        "FS_FILE_TYPE_SYMLINK",
        "FS_FILE_TYPE_UNIX_PIPE",
        "FS_FILE_TYPE_UNIX_CHARACTER_DEVICE",
        "FS_FILE_TYPE_UNIX_BLOCK_DEVICE",
        "FS_FILE_TYPE_UNIX_SOCKET"
      ],
      "description": "Resource type:\n * `FS_FILE_TYPE_DIRECTORY` - FS_FILE_TYPE_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - FS_FILE_TYPE_FILE,\n * `FS_FILE_TYPE_SYMLINK` - FS_FILE_TYPE_SYMLINK,\n * `FS_FILE_TYPE_UNIX_BLOCK_DEVICE` - FS_FILE_TYPE_UNIX_BLOCK_DEVICE,\n * `FS_FILE_TYPE_UNIX_CHARACTER_DEVICE` - FS_FILE_TYPE_UNIX_CHARACTER_DEVICE,\n * `FS_FILE_TYPE_UNIX_PIPE` - FS_FILE_TYPE_UNIX_PIPE,\n * `FS_FILE_TYPE_UNIX_SOCKET` - FS_FILE_TYPE_UNIX_SOCKET"
    },
    "major_minor_numbers": {
      "description": "The major and minor numbers for UNIX device files",
      "type": "object",
      "properties": {
        "major": {
          "description": "major",
          "type": "number"
        },
        "minor": {
```

```

        "description": "minor",
        "type": "number"
    }
}
},
"symlink_target_type": {
    "type": "string",
    "enum": [
        "FS_FILE_TYPE_UNKNOWN",
        "FS_FILE_TYPE_FILE",
        "FS_FILE_TYPE_DIRECTORY"
    ],
    "description": "The type of the target file if this file is a symlink:\n * `F
S_FILE_TYPE_DIRECTORY` - API_SYMLINK_TARGET_DIRECTORY,\n * `FS_FILE_TYPE_FILE` - AP
I_SYMLINK_TARGET_FILE,\n * `FS_FILE_TYPE_UNKNOWN` - API_SYMLINK_TARGET_UNKNOWN"
},
"file_number": {
    "description": "Unique ID of this file",
    "type": "string"
},
"id": {
    "description": "Unique ID of this file",
    "type": "string"
},
"mode": {
    "description": "POSIX-style file mode (octal)",
    "type": "string"
},
"owner": {
    "description": "File owner",
    "type": "string"
},
"owner_details": {
    "description": "File owner details",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
            ]
        }
    }
}

```

```

        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
},
"group": {
    "description": "File group",
    "type": "string"
},
"group_details": {
    "description": "File group details",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ],
            "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LO
CAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - N
FS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPO
RT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {
            "description": "id_value",
            "type": "string"
        }
    }
}
},
"blocks": {
    "description": "Number of blocks used by the file on this cluster",

```



```

    "type": "string"
  },
  "datablocks": {
    "description": "Number of data blocks used by the file on this cluster",
    "type": "string"
  },
  "metablocks": {
    "description": "Number of meta blocks used by the file on this cluster",
    "type": "string"
  },
  "logical_datablocks": {
    "description": "Number of data blocks used by the file",
    "type": "string"
  },
  "size": {
    "description": "File size in bytes",
    "type": "string"
  },
  "access_time": {
    "description": "Last time content was read, RFC 3339 format",
    "type": "string"
  },
  "modification_time": {
    "description": "Last time content was modified, RFC 3339 format",
    "type": "string"
  },
  "change_time": {
    "description": "Last time content or attributes were modified, RFC 3339 format",
    "type": "string"
  },
  "creation_time": {
    "description": "File creation time, RFC 3339 format",
    "type": "string"
  },
  "child_count": {
    "description": "Count of children (valid for directories)",
    "type": "number"
  },
  "extended_attributes": {
    "description": "SMB extended file attributes",
    "type": "object",
    "properties": {
      "read_only": {
        "description": "read_only",
        "type": "boolean"
      }
    }
  }
}

```

```

    },
    "hidden": {
        "description": "hidden",
        "type": "boolean"
    },
    "system": {
        "description": "system",
        "type": "boolean"
    },
    "archive": {
        "description": "archive",
        "type": "boolean"
    },
    "temporary": {
        "description": "temporary",
        "type": "boolean"
    },
    "compressed": {
        "description": "compressed",
        "type": "boolean"
    },
    "not_content_indexed": {
        "description": "not_content_indexed",
        "type": "boolean"
    },
    "sparse_file": {
        "description": "sparse_file",
        "type": "boolean"
    },
    "offline": {
        "description": "offline",
        "type": "boolean"
    }
}
},
"directory_entry_hash_policy": {
    "type": "string",
    "enum": [
        "FS_DIRECTORY_HASH_VERSION_LOWER",
        "FS_DIRECTORY_HASH_VERSION_FOLDED"
    ],
    "description": "Hash policy for directory entries:\n * `FS_DIRECTORY_HASH_VERSION_FOLDED` - FS_DIRECTORY_HASH_VERSION_FOLDED,\n * `FS_DIRECTORY_HASH_VERSION_LOWER` - FS_DIRECTORY_HASH_VERSION_LOWER"
}
}

```

```
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_named_stream_attributes",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "id": {
      "description": "id",
      "type": "string"
    },
    "size": {
      "description": "Size of the stream in bytes",
      "type": "string"
    },
    "datablocks": {
      "description": "Number of data blocks used by the stream on this cluster",
      "type": "string"
    },
    "logical_datablocks": {
      "description": "Number of data blocks used by the stream",
      "type": "string"
    },
    "data_revision": {
      "description": "Counter that increases with every data change to the stream",
      "type": "string"
    }
  }
}
```

files/{ref}/streams/{stream_id}/copy-chunk

Endpoint

/v1/files/{ref}/streams/{stream_id}/copy-chunk

POST

Copies the contents of the source file specified in the body of the request to the destination stream. The stream must already exist.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
stream_id	Stream ID (u64) to be modified	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_files_copy_chunk",
  "type": "object",
  "properties": {
    "source_id": {
      "description": "File ID of the source file. Exactly one of source_id or source_path must be provided.",
      "type": "string"
    },
    "source_path": {
      "description": "Path of the source file. Exactly one of source_id or source_path must be provided.",
      "type": "string"
    },
    "source_stream_id": {
```

```

    "description": "Stream ID of the source file. Defaults to default stream.",
    "type": "string"
  },
  "source_snapshot": {
    "description": "Snapshot ID specifying the version of the file to copy from. Defaults to head version.",
    "type": "number"
  },
  "source_offset": {
    "description": "Specifies the offset in bytes to start copying from. Defaults to 0.",
    "type": "string"
  },
  "target_offset": {
    "description": "Specifies the offset in bytes to start copying to. Defaults to 0.",
    "type": "string"
  },
  "length": {
    "description": "Specifies the maximum length of copy in bytes. Defaults to copy to the end of the source file. The server may not be able to copy the entire length requested. If that is the case, the response body returned can be used as request body for the remaining copy.",
    "type": "string"
  },
  "source_etag": {
    "description": "Expected ETag of the source file returned from /v1/files/{source-id}/info/attributes. If provided, this ETag will be validated against the server to ensure no intermediate change has occurred.",
    "type": "string"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
```

```

"description": "api_files_copy_chunk",
"type": "object",
"properties": {
  "source_id": {
    "description": "File ID of the source file. Exactly one of source_id or source_path must be provided.",
    "type": "string"
  },
  "source_path": {
    "description": "Path of the source file. Exactly one of source_id or source_path must be provided.",
    "type": "string"
  },
  "source_stream_id": {
    "description": "Stream ID of the source file. Defaults to default stream.",
    "type": "string"
  },
  "source_snapshot": {
    "description": "Snapshot ID specifying the version of the file to copy from. Defaults to head version.",
    "type": "number"
  },
  "source_offset": {
    "description": "Specifies the offset in bytes to start copying from. Defaults to 0.",
    "type": "string"
  },
  "target_offset": {
    "description": "Specifies the offset in bytes to start copying to. Defaults to 0.",
    "type": "string"
  },
  "length": {
    "description": "Specifies the maximum length of copy in bytes. Defaults to copy to the end of the source file. The server may not be able to copy the entire length requested. If that is the case, the response body returned can be used as request body for the remaining copy.",
    "type": "string"
  },
  "source_etag": {
    "description": "Expected ETag of the source file returned from /v1/files/{source-id}/info/attributes. If provided, this ETag will be validated against the server to ensure no intermediate change has occurred.",
    "type": "string"
  }
}
}

```

}

files/{ref}/streams/{stream_id}/data

Endpoint

/v1/files/{ref}/streams/{stream_id}/data

GET

Return the contents of the file as an HTTP octet stream. The etag returned by this method represents the whole state of this file. In another word, if you are reading just a portion of the data, etag could be invalid because of other changes happened to the stream, even the specific portion of data you read is still intact.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>stream_id</code>	Stream ID (u64) to be modified	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
<code>offset</code>	Read data from the requested stream starting at the given 64-bit integer offset. If the offset is larger than the size of the stream, the read will succeed and no data will be returned. If not specified the offset will 0.	No
<code>length</code>	Read up to length bytes from the requested stream. If the read extends beyond the end of the stream, the read will return as many bytes as possible, up to length. Will read the whole file if not specified.	No
<code>skip-atime-update</code>	If true, suppress the update of the stream's access time for this read.	No

Response

Codes

Code	Description
------	-------------

200	Return value on success
-----	-------------------------

PUT

Replace the contents of the stream with the body of the request. The target stream must already exist, and the content-type of the request must be Application/Octet-stream.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
stream_id	Stream ID (u64) to be modified	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "type": "object"
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_named_stream_attributes",
  "type": "object",
}
```

```

"properties": {
  "name": {
    "description": "name",
    "type": "string"
  },
  "id": {
    "description": "id",
    "type": "string"
  },
  "size": {
    "description": "Size of the stream in bytes",
    "type": "string"
  },
  "datablocks": {
    "description": "Number of data blocks used by the stream on this cluster",
    "type": "string"
  },
  "logical_datablocks": {
    "description": "Number of data blocks used by the stream",
    "type": "string"
  },
  "data_revision": {
    "description": "Counter that increases with every data change to the stream",
    "type": "string"
  }
}
}

```

PATCH

Set the contents of the stream, at the given offset, to the body of the request. The target stream must already exist, and the Content-Type of the request must be application/octet-stream.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>stream_id</code>	Stream ID (u64) to be modified	Yes

offset	Write the provided data at the given 64-bit integer offset. If the offset is greater than the size of the stream, the stream will be zero-extended up to offset before the data is written. (default: 0)	No
If-Match	ETag for expected version	No

Request

Schema

```
{
  "type": "object"
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_named_stream_attributes",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "id": {
      "description": "id",
      "type": "string"
    },
    "size": {
      "description": "Size of the stream in bytes",
      "type": "string"
    },
    "datablocks": {
      "description": "Number of data blocks used by the stream on this cluster",
      "type": "string"
    }
  }
}
```

```
},
"logical_datablocks": {
  "description": "Number of data blocks used by the stream",
  "type": "string"
},
"data_revision": {
  "description": "Counter that increases with every data change to the stream",
  "type": "string"
}
}
```

files/{ref}/streams/{stream_id}/punch-hole

Endpoint

/v1/files/{ref}/streams/{stream_id}/punch-hole

POST

Create a hole in a region of a stream. Destroys all data within the hole so that subsequent reads will return zeroes. Returns the post-operation attributes of the stream.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
stream_id	Stream ID (u64) to be modified	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_files_punch_hole",
  "type": "object",
  "properties": {
    "offset": {
      "description": "Offset in bytes specifying the start of the hole to create.",
      "type": "string"
    },
    "size": {
      "description": "Size in bytes of the hole to create.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_named_stream_attributes",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "id": {
      "description": "id",
      "type": "string"
    },
    "size": {
      "description": "Size of the stream in bytes",
      "type": "string"
    },
    "datablocks": {
      "description": "Number of data blocks used by the stream on this cluster",
      "type": "string"
    },
    "logical_datablocks": {
      "description": "Number of data blocks used by the stream",
      "type": "string"
    },
    "data_revision": {
      "description": "Counter that increases with every data change to the stream",
      "type": "string"
    }
  }
}
```

files/{ref}/streams/{stream_id}/rename

Endpoint

/v1/files/{ref}/streams/{stream_id}/rename

POST

Rename a stream on provided object

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
stream_id	Stream ID (u64) to be renamed	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_named_stream_entry",
  "type": "object",
  "properties": {
    "stream_name": {
      "description": "Stream name to be created.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
------	-------------

200

Return value on success

Schema

```
{
  "description": "api_named_stream_attributes",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "id": {
      "description": "id",
      "type": "string"
    },
    "size": {
      "description": "Size of the stream in bytes",
      "type": "string"
    },
    "datablocks": {
      "description": "Number of data blocks used by the stream on this cluster",
      "type": "string"
    },
    "logical_datablocks": {
      "description": "Number of data blocks used by the stream",
      "type": "string"
    },
    "data_revision": {
      "description": "Counter that increases with every data change to the stream",
      "type": "string"
    }
  }
}
```


files/{ref}/user-metadata/

Endpoint

/v1/files/{ref}/user-metadata/

GET

Retrieve the Base64-encoded user-defined metadata for the specified file.

Parameters

Name	Description	Required
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>snapshot</code>	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_user_metadata_range_result",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
```

```

    "description": "The list of user metadata entries.",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "GENERIC",
          "S3"
        ],
        "description": "The type of user metadata. Generic user metadata is visible through the S3 api as object tags. S3 metadata is visible to the S3 protocol as object metadata.:\n * `GENERIC` - FS_USER_METADATA_TYPE_GENERIC,\n * `S3` - FS_USER_METADATA_TYPE_S3"
      },
      "key": {
        "description": "The key used to reference the user metadata.",
        "type": "string"
      },
      "value": {
        "description": "The Base64-encoded value that the user-defined metadata entry stores.",
        "type": "string"
      }
    }
  }
}
}
}
}
}
}

```

files/{ref}/user-metadata/{type}/

Endpoint

/v1/files/{ref}/user-metadata/{type}/

GET

Retrieve the user-defined metadata of a specified type for the current file. Values are base 64 encoded.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
type	The user-defined metadata type on which to operate.	Yes
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No
after	Return entries after the given key (keys are returned in the paging object)	No
limit	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_user_metadata_range_result",
  "type": "object",
  "properties": {
```

```

"entries": {
  "type": "array",
  "items": {
    "description": "The list of user metadata entries.",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "GENERIC",
          "S3"
        ],
        "description": "The type of user metadata. Generic user metadata is visible through the S3 api as object tags. S3 metadata is visible to the S3 protocol as object metadata.\n * `GENERIC` - FS_USER_METADATA_TYPE_GENERIC,\n * `S3` - FS_USER_METADATA_TYPE_S3"
      },
      "key": {
        "description": "The key used to reference the user metadata.",
        "type": "string"
      },
      "value": {
        "description": "The Base64-encoded value that the user-defined metadata entry stores.",
        "type": "string"
      }
    }
  }
}

```

files/{ref}/user-metadata/{type}/{key}

Endpoint

/v1/files/{ref}/user-metadata/{type}/{key}

GET

Retrieve the Base64-encoded user-defined metadata value for the current file by using the specified key.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
type	The user-defined metadata type on which to operate.	Yes
key	The user-defined metadata key on which to operate.	Yes
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_user_metadata_value",
  "type": "object",
  "properties": {
    "value": {
      "description": "The Base64-encoded value of the user-defined metadata entry.",
      "type": "string"
    }
  }
}
```

```
}  
}
```

POST

Add a user-defined metadata value to the current file by using the specified key and user-defined metadata type.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
type	The user-defined metadata type on which to operate.	Yes
key	The user-defined metadata key on which to operate.	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{  
  "description": "api_files_user_metadata_value",  
  "type": "object",  
  "properties": {  
    "value": {  
      "description": "The Base64-encoded value of the user-defined metadata entry.",  
      "type": "string"  
    }  
  }  
}
```

Response

Codes

Code	Description
------	-------------

200	Return value on success
-----	-------------------------

PUT

Add or update the user-defined metadata value for the current file by using the specified key.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
type	The user-defined metadata type on which to operate.	Yes
key	The user-defined metadata key on which to operate.	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_files_user_metadata_value",
  "type": "object",
  "properties": {
    "value": {
      "description": "The Base64-encoded value of the user-defined metadata entry.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

DELETE

Delete the user-defined metadata entry for the current file by using the specified key.

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
type	The user-defined metadata type on which to operate.	Yes
key	The user-defined metadata key on which to operate.	Yes
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

files/{ref}/info/acl

Endpoint

/v2/files/{ref}/info/acl

GET

Get file access control list (ACL).

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
snapshot	The snapshot ID that specifies the version of the filesystem to use. If not specified, use the head version.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_acl_v2",
  "type": "object",
  "properties": {
    "control": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "PRESENT",
          "DEFAULTED",
          "TRUSTED",
          "AUTO_INHERIT",

```

```

        "PROTECTED"
    ],
    "description": "control:\n * `AUTO_INHERIT` - Set whether the ACL was created through inheritance,\n * `DEFAULTED` - Sets whether the ACL was established by default means,\n * `PRESENT` - Set when ACL is present on the object,\n * `PROTECTED` - Protects ACL from inherit operations,\n * `TRUSTED` - Set when ACL is provided by a trusted source"
    },
    "posix_special_permissions": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "STICKY_BIT",
                "SET_GID",
                "SET_UID"
            ]
        },
        "description": "posix_special_permissions:\n * `SET_GID` - SET_GID,\n * `SET_UID` - SET_UID,\n * `STICKY_BIT` - STICKY_BIT"
    },
    "aces": {
        "type": "array",
        "items": {
            "description": "aces",
            "type": "object",
            "properties": {
                "type": {
                    "type": "string",
                    "enum": [
                        "ALLOWED",
                        "DENIED"
                    ]
                },
                "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entry that grants rights,\n * `DENIED` - An ACL entry that denies rights"
            }
        },
        "flags": {
            "type": "array",
            "items": {
                "type": "string",
                "enum": [
                    "OBJECT_INHERIT",
                    "CONTAINER_INHERIT",
                    "NO_PROPAGATE_INHERIT",
                    "INHERIT_ONLY",

```

```

        "INHERITED"
    ],
    "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT`\n - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent subsequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"
  }
},
"trustee": {
  "description": "Trustee for this ACL entry",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
    },
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
  },
  "auth_id": {
    "description": "auth_id",
    "type": "string"
  },
  "uid": {
    "description": "uid",
    "type": "number"
  }
},

```

```

        "gid": {
            "description": "gid",
            "type": "number"
        },
        "sid": {
            "description": "sid",
            "type": "string"
        },
        "name": {
            "description": "name",
            "type": "string"
        }
    },
    "rights": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "READ",
                "READ_EA",
                "READ_ATTR",
                "READ_ACL",
                "WRITE_EA",
                "WRITE_ATTR",
                "WRITE_ACL",
                "CHANGE_OWNER",
                "WRITE_GROUP",
                "DELETE",
                "EXECUTE",
                "MODIFY",
                "EXTEND",
                "DELETE_CHILD",
                "SYNCHRONIZE"
            ],
            "description": "Rights granted or denied for this ACL entry:\n * `CHANGE_OWNER` - Owner write access,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - File read access,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
        }
    }
}

```

```

    }
  }
}

```

PUT

Update file access control list (ACL).

Parameters

Name	Description	Required
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_files_acl_v2",
  "type": "object",
  "properties": {
    "control": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "PRESENT",
          "DEFAULTED",
          "TRUSTED",
          "AUTO_INHERIT",
          "PROTECTED"
        ]
      },
      "description": "control:\n * `AUTO_INHERIT` - Set whether the ACL was created through inheritance,\n * `DEFAULTED` - Sets whether the ACL was established by default means,\n * `PRESENT` - Set when ACL is present on the object,\n * `PROTECTED` - Protects ACL from inherit operations,\n * `TRUSTED` - Set when ACL is provided by

```

```

a trusted source"
    }
  },
  "posix_special_permissions": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "STICKY_BIT",
        "SET_GID",
        "SET_UID"
      ],
      "description": "posix_special_permissions:\n * `SET_GID` - SET_GID,\n * `SET_UID` - SET_UID,\n * `STICKY_BIT` - STICKY_BIT"
    }
  },
  "aces": {
    "type": "array",
    "items": {
      "description": "aces",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "ALLOWED",
            "DENIED"
          ],
          "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entry that grants rights,\n * `DENIED` - An ACL entry that denies rights"
        },
        "flags": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": [
              "OBJECT_INHERIT",
              "CONTAINER_INHERIT",
              "NO_PROPAGATE_INHERIT",
              "INHERIT_ONLY",
              "INHERITED"
            ],
            "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT` - Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicates the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doesn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent sub

```

sequent children from inheriting ACE,\n * `OBJECT\_INHERIT` - Non-container children inherit as effective ACE. Container objects inherit as inherit-only ACE"

```
    }
  },
  "trustee": {
    "description": "Trustee for this ACL entry",
    "type": "object",
    "properties": {
      "domain": {
        "type": "string",
        "enum": [
          "LOCAL",
          "API_NULL_DOMAIN",
          "WORLD",
          "POSIX_USER",
          "POSIX_GROUP",
          "ACTIVE_DIRECTORY",
          "API_INVALID_DOMAIN",
          "API_RESERVED_DOMAIN",
          "API_INTERNAL_DOMAIN",
          "API_OPERATOR_DOMAIN",
          "API_QUMULO_SUPPORT_DOMAIN",
          "API_CREATOR_DOMAIN"
        ],
        "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
      },
      "auth_id": {
        "description": "auth_id",
        "type": "string"
      },
      "uid": {
        "description": "uid",
        "type": "number"
      },
      "gid": {
        "description": "gid",
        "type": "number"
      },
      "sid": {
        "description": "sid",
```


Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_files_acl_v2",
  "type": "object",
  "properties": {
    "control": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "PRESENT",
          "DEFAULTED",
          "TRUSTED",
          "AUTO_INHERIT",
          "PROTECTED"
        ]
      },
      "description": "control:\n * `AUTO_INHERIT` - Set whether the ACL was created through inheritance,\n * `DEFAULTED` - Sets whether the ACL was established by default means,\n * `PRESENT` - Set when ACL is present on the object,\n * `PROTECTED` - Protects ACL from inherit operations,\n * `TRUSTED` - Set when ACL is provided by a trusted source"
    },
    "posix_special_permissions": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "STICKY_BIT",
          "SET_GID",
          "SET_UID"
        ]
      },
      "description": "posix_special_permissions:\n * `SET_GID` - SET_GID,\n * `SET_UID` - SET_UID,\n * `STICKY_BIT` - STICKY_BIT"
    },
    "aces": {
```

```

"type": "array",
"items": {
  "description": "aces",
  "type": "object",
  "properties": {
    "type": {
      "type": "string",
      "enum": [
        "ALLOWED",
        "DENIED"
      ],
      "description": "Type of this ACL entry:\n * `ALLOWED` - An ACL entry tha
t grants rights,\n * `DENIED` - An ACL entry that denies rights"
    },
    "flags": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "OBJECT_INHERIT",
          "CONTAINER_INHERIT",
          "NO_PROPAGATE_INHERIT",
          "INHERIT_ONLY",
          "INHERITED"
        ],
        "description": "ACE flags for this ACL entry:\n * `CONTAINER_INHERIT`
- Children that are containers inherit as effective ACE,\n * `INHERITED` - Indicate
s the ACE was inherited,\n * `INHERIT_ONLY` - Indicates an inherit-only ACE that doe
sn't control access to the attached object,\n * `NO_PROPAGATE_INHERIT` - Prevent sub
sequent children from inheriting ACE,\n * `OBJECT_INHERIT` - Non-container children
inherit as effective ACE. Container objects inherit as inherit-only ACE"
      }
    },
    "trustee": {
      "description": "Trustee for this ACL entry",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",

```

```

        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",

```


health/ssd-endurance

Endpoint

/v1/health/ssd-endurance

GET

List all SSD's endurance level

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_ssd_endurance_map",
  "type": "object",
  "properties": {},
  "additionalProperties": {
    "type": "array",
    "items": {
      "description": "api_ssd_endurance_map value",
      "type": "object",
      "properties": {
        "drive_bay": {
          "description": "drive_bay",
          "type": "string"
        },
        "level": {
          "description": "level",
          "type": "string"
        }
      }
    }
  }
}
```

identity/expand

Endpoint

/v1/identity/expand

POST

Find all equivalents and the group membership of the given identity.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_id_to_expand",
  "type": "object",
  "properties": {
    "id": {
      "description": "The identity to expand.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ],
          "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN"
        }
      }
    }
  }
}
```

```

N,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_US
ER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  }
},
"equivalent_ids": {
  "type": "array",
  "items": {
    "description": "Additional identities that should be considered equivalent,
and also expanded.",
    "type": "object",
    "properties": {
      "domain": {
        "type": "string",
        "enum": [
          "LOCAL",
          "API_NULL_DOMAIN",
          "WORLD",
          "POSIX_USER",
          "POSIX_GROUP",
          "ACTIVE_DIRECTORY",
          "API_INVALID_DOMAIN",
          "API_RESERVED_DOMAIN",
          "API_INTERNAL_DOMAIN",
          "API_OPERATOR_DOMAIN",
          "API_QUMULO_SUPPORT_DOMAIN",

```

```

        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n *
`API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNA
L_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - AP
I_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPP
ORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DO
MAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSI
X_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"group_ids": {
    "type": "array",
    "items": {
        "description": "Additional groups that the id should be considered a member
of, and also expanded.",
        "type": "object",
        "properties": {
            "domain": {
                "type": "string",
                "enum": [
                    "LOCAL",
                    "API_NULL_DOMAIN",
                    "WORLD",

```


Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_expanded_id",
  "type": "object",
  "properties": {
    "id": {
      "description": "The identity that was expanded.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ],
          "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
        },
        "auth_id": {
          "description": "auth_id",
          "type": "string"
        }
      }
    }
  }
}
```

```

    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  },
  "type": {
    "type": "string",
    "enum": [
      "UNKNOWN",
      "USER",
      "GROUP"
    ],
    "description": "Whether the expanded identity is a user, group, or indeterminate.\n * `GROUP` - RESOLVED_ID_IS_GROUP,\n * `UNKNOWN` - RESOLVED_ID_IS_UNKNOWN,\n * `USER` - RESOLVED_ID_IS_USER"
  },
  "smb_id": {
    "description": "The equivalent identity that would be shown to SMB clients.",
    "type": "object",
    "properties": {
      "domain": {
        "type": "string",
        "enum": [
          "LOCAL",
          "API_NULL_DOMAIN",
          "WORLD",
          "POSIX_USER",
          "POSIX_GROUP",
          "ACTIVE_DIRECTORY",
          "API_INVALID_DOMAIN",
          "API_RESERVED_DOMAIN",
          "API_INTERNAL_DOMAIN",
          "API_OPERATOR_DOMAIN",

```

```

        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
    }
},
"nfs_id": {
    "description": "The equivalent identity that would be shown to NFS clients.",
    "type": "object",
    "properties": {
        "domain": {
            "type": "string",
            "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",

```

```

        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
  },
  "auth_id": {
    "description": "auth_id",
    "type": "string"
  },
  "uid": {
    "description": "uid",
    "type": "number"
  },
  "gid": {
    "description": "gid",
    "type": "number"
  },
  "sid": {
    "description": "sid",
    "type": "string"
  },
  "name": {
    "description": "name",
    "type": "string"
  }
}
},
"equivalent_ids": {
  "type": "array",
  "items": {
    "description": "Identities that are the same as the expanded ID, and which have the same rights.",
    "type": "object",
    "properties": {
      "domain": {
        "type": "string",

```

```

    "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n *
`API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNA
L_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - AP
I_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPP
ORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DO
MAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSI
X_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"group_ids": {

```

```

"type": "array",
"items": {
  "description": "Groups that the expanded ID is a member of.",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n *  

`API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNA  

L_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - AP  

I_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPP  

ORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DO  

MAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSI  

X_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {

```

```
        "description": "name",  
        "type": "string"  
    }  
    }  
    }  
    }  
}
```


identity/find

Endpoint

/v1/identity/find

POST

Search for identity and populate all fields.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_identity",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
```

```

    "description": "auth_id",
    "type": "string"
  },
  "uid": {
    "description": "uid",
    "type": "number"
  },
  "gid": {
    "description": "gid",
    "type": "number"
  },
  "sid": {
    "description": "sid",
    "type": "string"
  },
  "name": {
    "description": "name",
    "type": "string"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_identity",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",

```

```

        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CR
EATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAI
N,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_D
OMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMA
IN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n
 * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USE
R,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
}

```

Ldap/login-name/{login_name}/gid-numbers

Endpoint

/v1/ldap/login-name/{login_name}/gid-numbers

GET

Query the LDAP server for the gid numbers for all the groups of which the given login name is a member. This returns a vector of results in the case that the given login name maps to multiple uid numbers.

Parameters

Name	Description	Required
<code>login_name</code>	The login name to use to lookup its GID numbers	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_ldap_login_name_to_gid_numbers",
  "type": "object",
  "properties": {
    "login_name": {
      "description": "login_name",
      "type": "string"
    },
    "uid_numbers_to_gid_numbers": {
      "type": "array",
      "items": {
        "description": "uid_numbers_to_gid_numbers",
        "type": "object",
        "properties": {
          "uid_number": {
            "description": "uid_number",
            "type": "number"
          }
        }
      }
    }
  }
}
```

```
    },  
    "gid_numbers": {  
      "type": "array",  
      "items": {  
        "description": "gid_numbers",  
        "type": "number"  
      }  
    }  
  }  
}  
}
```

ldap/login-name/{login_name}/uid-numbers

Endpoint

/v1/ldap/login-name/{login_name}/uid-numbers

GET

Return the UID Numbers of the given login name. This is found by issuing an LDAP query against the LDAP server configured

Parameters

Name	Description	Required
login_name	The login name to use to lookup its UID numbers	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_ldap_login_name_to_uid_numbers",
  "type": "object",
  "properties": {
    "login_name": {
      "description": "login_name",
      "type": "string"
    },
    "uid_numbers": {
      "type": "array",
      "items": {
        "description": "uid_numbers",
        "type": "number"
      }
    }
  }
}
```

Ldap/status

Endpoint

/v1/ldap/status

GET

Get LDAP connection status if applicable.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_ldap_connection_state",
    "type": "object",
    "properties": {
      "node_id": {
        "description": "node_id",
        "type": "number"
      },
      "servers": {
        "type": "array",
        "items": {
          "description": "servers",
          "type": "object",
          "properties": {
            "bind_uri": {
              "description": "bind_uri",
              "type": "string"
            },
            "kdc_address": {
              "description": "kdc_address",
```

```

        "type": "string"
    }
}
},
"bind_domain": {
    "description": "bind_domain",
    "type": "string"
},
"bind_account": {
    "description": "bind_account",
    "type": "string"
},
"base_dn_vec": {
    "type": "array",
    "items": {
        "description": "base_dn_vec",
        "type": "string"
    }
},
"health": {
    "type": "string",
    "enum": [
        "NO_RECENT_ERROR",
        "INTERMITTENT_ERROR",
        "SUSTAINED_ERROR"
    ],
    "description": "health:\n * `INTERMITTENT_ERROR` - LDAP_HEALTH_INTERMITTENT_ERROR,\n * `NO_RECENT_ERROR` - LDAP_HEALTH_NO_RECENT_ERROR,\n * `SUSTAINED_ERROR` - LDAP_HEALTH_SUSTAINED_ERROR"
}
}
}
}

```


Ldap/uid-number/{uid_number}/login-name

Endpoint

/v1/ldap/uid-number/{uid_number}/login-name

GET

Return the login names for the given UID number as found by issuing an LDAP query against the LDAP server configured

Parameters

Name	Description	Required
uid_number	The UID number to use to lookup its login name	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_ldap_uid_number_to_login_names",
  "type": "object",
  "properties": {
    "uid_number": {
      "description": "uid_number",
      "type": "number"
    },
    "login_names": {
      "type": "array",
      "items": {
        "description": "login_names",
        "type": "string"
      }
    }
  }
}
```

Ldap/settings

Endpoint

/v2/ldap/settings

GET

Get settings for LDAP interaction

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_lone_ldap_config_v2",
  "type": "object",
  "properties": {
    "use_ldap": {
      "description": "Top-level LDAP enablement switch, indicating whether Qumulo Co
re should use LDAP or not.",
      "type": "boolean"
    },
    "bind_uri": {
      "description": "LDAP server URIs (for example, ldap://example.com). Separate m
ultiple URIs with commas (,).",
      "type": "string"
    },
    "user": {
      "description": "Binding user's distinguished name. Default is empty, for anyon
mous authentication.",
      "type": "string"
    },
    "password": {
      "description": "Binding password for simple auth. Default is the password tha
t is currently configured.",

```

```

    "type": "string",
    "format": "password"
  },
  "base_distinguished_names": {
    "description": "Distinguished name(s) which will be used as the search base for queries. Multiple DNs may be specified, separated by semi-colons. Example: dc=user s,dc=example,dc=com; dc=robots,dc=example,dc=com",
    "type": "string"
  },
  "ldap_schema": {
    "type": "string",
    "enum": [
      "RFC2307",
      "CUSTOM"
    ],
    "description": "LDAP server schema to use. Default is RFC2307:\n * `CUSTOM` - CUSTOM,\n * `RFC2307` - RFC2307"
  },
  "ldap_schema_description": {
    "description": "An expanded description of the LDAP server schema. Only set this field if setting ldap_schema to CUSTOM.",
    "type": "object",
    "properties": {
      "group_member_attribute": {
        "description": "group_member_attribute",
        "type": "string"
      },
      "user_group_identifier_attribute": {
        "description": "user_group_identifier_attribute",
        "type": "string"
      },
      "login_name_attribute": {
        "description": "login_name_attribute",
        "type": "string"
      },
      "group_name_attribute": {
        "description": "group_name_attribute",
        "type": "string"
      },
      "user_object_class": {
        "description": "user_object_class",
        "type": "string"
      },
      "group_object_class": {
        "description": "group_object_class",
        "type": "string"
      }
    }
  }
}

```

```

    },
    "uid_number_attribute": {
      "description": "uid_number_attribute",
      "type": "string"
    },
    "gid_number_attribute": {
      "description": "gid_number_attribute",
      "type": "string"
    }
  },
  "encrypt_connection": {
    "description": "If true, require to have encrypted connection with LDAP. Default is True.",
    "type": "boolean"
  }
}

```

PUT

Set settings for LDAP interaction

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_ldone_ldap_config_v2",
  "type": "object",
  "properties": {
    "use_ldap": {
      "description": "Top-level LDAP enablement switch, indicating whether Qumulo Core should use LDAP or not.",
      "type": "boolean"
    },
    "bind_uri": {
      "description": "LDAP server URIs (for example, ldap://example.com). Separate multiple URIs with commas (,).",

```

```

    "type": "string"
  },
  "user": {
    "description": "Binding user's distinguished name. Default is empty, for anonymous authentication.",
    "type": "string"
  },
  "password": {
    "description": "Binding password for simple auth. Default is the password that is currently configured.",
    "type": "string",
    "format": "password"
  },
  "base_distinguished_names": {
    "description": "Distinguished name(s) which will be used as the search base for queries. Multiple DN's may be specified, separated by semi-colons. Example: dc=user,dc=example,dc=com; dc=robots,dc=example,dc=com",
    "type": "string"
  },
  "ldap_schema": {
    "type": "string",
    "enum": [
      "RFC2307",
      "CUSTOM"
    ],
    "description": "LDAP server schema to use. Default is RFC2307:\n * `CUSTOM` - CUSTOM,\n * `RFC2307` - RFC2307"
  },
  "ldap_schema_description": {
    "description": "An expanded description of the LDAP server schema. Only set this field if setting ldap_schema to CUSTOM.",
    "type": "object",
    "properties": {
      "group_member_attribute": {
        "description": "group_member_attribute",
        "type": "string"
      },
      "user_group_identifier_attribute": {
        "description": "user_group_identifier_attribute",
        "type": "string"
      },
      "login_name_attribute": {
        "description": "login_name_attribute",
        "type": "string"
      },
      "group_name_attribute": {

```

```

        "description": "group_name_attribute",
        "type": "string"
    },
    "user_object_class": {
        "description": "user_object_class",
        "type": "string"
    },
    "group_object_class": {
        "description": "group_object_class",
        "type": "string"
    },
    "uid_number_attribute": {
        "description": "uid_number_attribute",
        "type": "string"
    },
    "gid_number_attribute": {
        "description": "gid_number_attribute",
        "type": "string"
    }
}
},
"encrypt_connection": {
    "description": "If true, require to have encrypted connection with LDAP. Default is True.",
    "type": "boolean"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
    "description": "api_lone_ldap_config_v2",
    "type": "object",
    "properties": {
        "use_ldap": {
            "description": "Top-level LDAP enablement switch, indicating whether Qumulo Co

```

```

re should use LDAP or not.",
  "type": "boolean"
},
"bind_uri": {
  "description": "LDAP server URIs (for example, ldap://example.com). Separate multiple URIs with commas (,).",
  "type": "string"
},
"user": {
  "description": "Binding user's distinguished name. Default is empty, for anonymous authentication.",
  "type": "string"
},
"password": {
  "description": "Binding password for simple auth. Default is the password that is currently configured.",
  "type": "string",
  "format": "password"
},
"base_distinguished_names": {
  "description": "Distinguished name(s) which will be used as the search base for queries. Multiple DN's may be specified, separated by semi-colons. Example: dc=user,dc=example,dc=com; dc=robots,dc=example,dc=com",
  "type": "string"
},
"ldap_schema": {
  "type": "string",
  "enum": [
    "RFC2307",
    "CUSTOM"
  ],
  "description": "LDAP server schema to use. Default is RFC2307:\n * `CUSTOM` - CUSTOM,\n * `RFC2307` - RFC2307"
},
"ldap_schema_description": {
  "description": "An expanded description of the LDAP server schema. Only set this field if setting ldap_schema to CUSTOM.",
  "type": "object",
  "properties": {
    "group_member_attribute": {
      "description": "group_member_attribute",
      "type": "string"
    },
    "user_group_identifier_attribute": {
      "description": "user_group_identifier_attribute",
      "type": "string"
    }
  }
}

```

```

    },
    "login_name_attribute": {
      "description": "login_name_attribute",
      "type": "string"
    },
    "group_name_attribute": {
      "description": "group_name_attribute",
      "type": "string"
    },
    "user_object_class": {
      "description": "user_object_class",
      "type": "string"
    },
    "group_object_class": {
      "description": "group_object_class",
      "type": "string"
    },
    "uid_number_attribute": {
      "description": "uid_number_attribute",
      "type": "string"
    },
    "gid_number_attribute": {
      "description": "gid_number_attribute",
      "type": "string"
    }
  },
  "encrypt_connection": {
    "description": "If true, require to have encrypted connection with LDAP. Default is True.",
    "type": "boolean"
  }
}

```

PATCH

Partially Set LDAP interaction settings

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_lone_ldap_config_v2",
  "type": "object",
  "properties": {
    "use_ldap": {
      "description": "Top-level LDAP enablement switch, indicating whether Qumulo Core should use LDAP or not.",
      "type": "boolean"
    },
    "bind_uri": {
      "description": "LDAP server URIs (for example, ldap://example.com). Separate multiple URIs with commas (,).",
      "type": "string"
    },
    "user": {
      "description": "Binding user's distinguished name. Default is empty, for anonymous authentication.",
      "type": "string"
    },
    "password": {
      "description": "Binding password for simple auth. Default is the password that is currently configured.",
      "type": "string",
      "format": "password"
    },
    "base_distinguished_names": {
      "description": "Distinguished name(s) which will be used as the search base for queries. Multiple DN's may be specified, separated by semi-colons. Example: dc=users,dc=example,dc=com; dc=robots,dc=example,dc=com",
      "type": "string"
    },
    "ldap_schema": {
      "type": "string",
      "enum": [
        "RFC2307",
        "CUSTOM"
      ],
      "description": "LDAP server schema to use. Default is RFC2307:\n * `CUSTOM` - CUSTOM,\n * `RFC2307` - RFC2307"
    },
    "ldap_schema_description": {
      "description": "An expanded description of the LDAP server schema. Only set this field if setting ldap_schema to CUSTOM."
    }
  }
}
```

```

"type": "object",
"properties": {
  "group_member_attribute": {
    "description": "group_member_attribute",
    "type": "string"
  },
  "user_group_identifier_attribute": {
    "description": "user_group_identifier_attribute",
    "type": "string"
  },
  "login_name_attribute": {
    "description": "login_name_attribute",
    "type": "string"
  },
  "group_name_attribute": {
    "description": "group_name_attribute",
    "type": "string"
  },
  "user_object_class": {
    "description": "user_object_class",
    "type": "string"
  },
  "group_object_class": {
    "description": "group_object_class",
    "type": "string"
  },
  "uid_number_attribute": {
    "description": "uid_number_attribute",
    "type": "string"
  },
  "gid_number_attribute": {
    "description": "gid_number_attribute",
    "type": "string"
  }
},
"encrypt_connection": {
  "description": "If true, require to have encrypted connection with LDAP. Default is True.",
  "type": "boolean"
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_lone_ldap_config_v2",
  "type": "object",
  "properties": {
    "use_ldap": {
      "description": "Top-level LDAP enablement switch, indicating whether Qumulo Core should use LDAP or not.",
      "type": "boolean"
    },
    "bind_uri": {
      "description": "LDAP server URIs (for example, ldap://example.com). Separate multiple URIs with commas (,).",
      "type": "string"
    },
    "user": {
      "description": "Binding user's distinguished name. Default is empty, for anonymous authentication.",
      "type": "string"
    },
    "password": {
      "description": "Binding password for simple auth. Default is the password that is currently configured.",
      "type": "string",
      "format": "password"
    },
    "base_distinguished_names": {
      "description": "Distinguished name(s) which will be used as the search base for queries. Multiple DN's may be specified, separated by semi-colons. Example: dc=user,dc=example,dc=com; dc=robots,dc=example,dc=com",
      "type": "string"
    },
    "ldap_schema": {
      "type": "string",
      "enum": [
        "RFC2307",
        "CUSTOM"
      ]
    }
  }
}
```

```

    ],
    "description": "LDAP server schema to use. Default is RFC2307:\n * `CUSTOM` - CUSTOM,\n * `RFC2307` - RFC2307"
  },
  "ldap_schema_description": {
    "description": "An expanded description of the LDAP server schema. Only set this field if setting ldap_schema to CUSTOM.",
    "type": "object",
    "properties": {
      "group_member_attribute": {
        "description": "group_member_attribute",
        "type": "string"
      },
      "user_group_identifier_attribute": {
        "description": "user_group_identifier_attribute",
        "type": "string"
      },
      "login_name_attribute": {
        "description": "login_name_attribute",
        "type": "string"
      },
      "group_name_attribute": {
        "description": "group_name_attribute",
        "type": "string"
      },
      "user_object_class": {
        "description": "user_object_class",
        "type": "string"
      },
      "group_object_class": {
        "description": "group_object_class",
        "type": "string"
      },
      "uid_number_attribute": {
        "description": "uid_number_attribute",
        "type": "string"
      },
      "gid_number_attribute": {
        "description": "gid_number_attribute",
        "type": "string"
      }
    }
  },
  "encrypt_connection": {
    "description": "If true, require to have encrypted connection with LDAP. Default is True.",

```

```
    "type": "boolean"  
  }  
}  
}
```

license/enforcement

Endpoint

/v1/license/enforcement

GET

[preview] Retrieve the current license and whether it is being enforced.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_license_enforcement",
  "type": "object",
  "properties": {
    "license_is_enforced": {
      "description": "license_is_enforced",
      "type": "boolean"
    }
  }
}
```

license/status

Endpoint

/v1/license/status

GET

[preview] Retrieve the current license and whether it is active.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_license_status",
  "type": "object",
  "properties": {
    "state": {
      "type": "string",
      "enum": [
        "LICENSE_STATE_NONE",
        "LICENSE_STATE_ACTIVE",
        "LICENSE_STATE_EXPIRED"
      ],
      "description": "state:\n * `LICENSE_STATE_ACTIVE` - LICENSE_STATE_ACTIVE,\n * `LICENSE_STATE_EXPIRED` - LICENSE_STATE_EXPIRED,\n * `LICENSE_STATE_NONE` - LICENS\nE_STATE_NONE"
    },
    "license": {
      "description": "license",
      "type": "object",
      "properties": {}
    }
  }
}
```

groups/

Endpoint

/v1/groups/

GET

List all groups. Refer to the 'Modify group' method for a description of the returned fields.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_group",
    "type": "object",
    "properties": {
      "id": {
        "description": "The group's unique id",
        "type": "string"
      },
      "name": {
        "description": "The group name",
        "type": "string"
      },
      "sid": {
        "description": "The group's SID",
        "type": "string"
      },
      "gid": {
        "description": "The group's NFS gid",
        "type": "string"
      }
    }
  }
}
```



```
}  
}  
}
```

POST

Add a group.

Parameters

This resource has no parameters.

Request

Schema

```
{  
  "description": "api_group_post",  
  "type": "object",  
  "properties": {  
    "name": {  
      "description": "The group name",  
      "type": "string"  
    },  
    "gid": {  
      "description": "The group's NFS gid",  
      "type": "string"  
    }  
  }  
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{  
  "description": "api_group",  
  "type": "object",
```

```
"properties": {  
  "id": {  
    "description": "The group's unique id",  
    "type": "string"  
  },  
  "name": {  
    "description": "The group name",  
    "type": "string"  
  },  
  "sid": {  
    "description": "The group's SID",  
    "type": "string"  
  },  
  "gid": {  
    "description": "The group's NFS gid",  
    "type": "string"  
  }  
}
```

groups/{group_id}/members/

Endpoint

/v1/groups/{group_id}/members/

GET

List members of a group, which are among the local users. Refer to the 'Modify user' method for a description of the returned fields.

Parameters

Name	Description	Required
group_id	The group's unique ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_user",
    "type": "object",
    "properties": {
      "id": {
        "description": "The user's unique id",
        "type": "string"
      },
      "name": {
        "description": "The user's account name",
        "type": "string"
      },
      "primary_group": {
        "description": "The unique ID of the user's group",
        "type": "string"
      }
    }
  }
}
```

```

    "sid": {
      "description": "The users's SID",
      "type": "string"
    },
    "uid": {
      "description": "The user's NFS uid",
      "type": "string"
    },
    "home_directory": {
      "description": "The path to the user's home directory",
      "type": "string"
    },
    "can_change_password": {
      "description": "Specifies whether the user can change the password",
      "type": "boolean"
    }
  }
}

```

POST

Add a member to a group. Refer to the 'Modify user' method for a description of the returned fields.

Parameters

Name	Description	Required
<code>group_id</code>	The group's unique ID	Yes

Request

Schema

```

{
  "description": "api_member_auth_id",
  "type": "object",
  "properties": {
    "member_id": {
      "description": "Unique ID of a user",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_user",
  "type": "object",
  "properties": {
    "id": {
      "description": "The user's unique id",
      "type": "string"
    },
    "name": {
      "description": "The user's account name",
      "type": "string"
    },
    "primary_group": {
      "description": "The unique ID of the user's group",
      "type": "string"
    },
    "sid": {
      "description": "The users's SID",
      "type": "string"
    },
    "uid": {
      "description": "The user's NFS uid",
      "type": "string"
    },
    "home_directory": {
      "description": "The path to the user's home directory",
      "type": "string"
    },
    "can_change_password": {
      "description": "Specifies whether the user can change the password",
      "type": "boolean"
    }
  }
}
```

groups/{group_id}/members/{member_id}

Endpoint

/v1/groups/{group_id}/members/{member_id}

DELETE

Remove a member from a group.

Parameters

Name	Description	Required
group_id	The group's unique ID	Yes
member_id	The user's unique ID	Yes

Response

Codes

Code	Description
200	Return value on success

groups/{id}

Endpoint

/v1/groups/{id}

GET

Retrieve the attributes of a group. Refer to the 'Modify group' method for a description of the returned fields.

Parameters

Name	Description	Required
id	The group's unique ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_group",
  "type": "object",
  "properties": {
    "id": {
      "description": "The group's unique id",
      "type": "string"
    },
    "name": {
      "description": "The group name",
      "type": "string"
    },
    "sid": {
      "description": "The group's SID",
      "type": "string"
    },
    "gid": {
      "description": "The group's NFS gid",
```

```
    "type": "string"
  }
}
```

PUT

Modify a group. The 'id' field must match the id in the URI.

Parameters

Name	Description	Required
id	The group's unique ID	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_group_put",
  "type": "object",
  "properties": {
    "id": {
      "description": "The group's unique id",
      "type": "string"
    },
    "name": {
      "description": "The group name",
      "type": "string"
    },
    "gid": {
      "description": "The group's NFS gid",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
------	-------------

200	Return value on success
-----	-------------------------

Schema

```
{
  "description": "api_group",
  "type": "object",
  "properties": {
    "id": {
      "description": "The group's unique id",
      "type": "string"
    },
    "name": {
      "description": "The group name",
      "type": "string"
    },
    "sid": {
      "description": "The group's SID",
      "type": "string"
    },
    "gid": {
      "description": "The group's NFS gid",
      "type": "string"
    }
  }
}
```

DELETE

Delete a group.

Parameters

Name	Description	Required
id	The group's unique ID	Yes

Response

Codes

Code	Description
200	Return value on success

users/

Endpoint

/v1/users/

GET

List all users in the local user database. Refer to the 'Modify user' method for a description of the returned fields.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_user",
    "type": "object",
    "properties": {
      "id": {
        "description": "The user's unique id",
        "type": "string"
      },
      "name": {
        "description": "The user's account name",
        "type": "string"
      },
      "primary_group": {
        "description": "The unique ID of the user's group",
        "type": "string"
      },
      "sid": {
        "description": "The users's SID",
        "type": "string"
      }
    }
  }
}
```

```

    },
    "uid": {
      "description": "The user's NFS uid",
      "type": "string"
    },
    "home_directory": {
      "description": "The path to the user's home directory",
      "type": "string"
    },
    "can_change_password": {
      "description": "Specifies whether the user can change the password",
      "type": "boolean"
    }
  }
}
}

```

POST

Add a user.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "api_user_post",
  "type": "object",
  "properties": {
    "name": {
      "description": "The user's account name",
      "type": "string"
    },
    "primary_group": {
      "description": "The unique ID of the user's group",
      "type": "string"
    },
    "uid": {
      "description": "The user's NFS uid",
      "type": "string"
    },
    "home_directory": {

```

```

    "description": "The user's home directory path",
    "type": "string"
  },
  "password": {
    "description": "The user's password",
    "type": "string",
    "format": "password"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_user",
  "type": "object",
  "properties": {
    "id": {
      "description": "The user's unique id",
      "type": "string"
    },
    "name": {
      "description": "The user's account name",
      "type": "string"
    },
    "primary_group": {
      "description": "The unique ID of the user's group",
      "type": "string"
    },
    "sid": {
      "description": "The users's SID",
      "type": "string"
    },
    "uid": {
      "description": "The user's NFS uid",
      "type": "string"
    },
  },
}

```

```
"home_directory": {  
  "description": "The path to the user's home directory",  
  "type": "string"  
},  
"can_change_password": {  
  "description": "Specifies whether the user can change the password",  
  "type": "boolean"  
}  
}  
}
```

users/{id}

Endpoint

/v1/users/{id}

GET

Retrieve information about a single local user. Refer to the 'Modify user' method for a description of the returned fields.

Parameters

Name	Description	Required
id	The user's unique ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_user",
  "type": "object",
  "properties": {
    "id": {
      "description": "The user's unique id",
      "type": "string"
    },
    "name": {
      "description": "The user's account name",
      "type": "string"
    },
    "primary_group": {
      "description": "The unique ID of the user's group",
      "type": "string"
    },
    "sid": {
      "description": "The users's SID",

```

```

    "type": "string"
  },
  "uid": {
    "description": "The user's NFS uid",
    "type": "string"
  },
  "home_directory": {
    "description": "The path to the user's home directory",
    "type": "string"
  },
  "can_change_password": {
    "description": "Specifies whether the user can change the password",
    "type": "boolean"
  }
}
}

```

PUT

Modify a local user.

Parameters

Name	Description	Required
id	The user's unique ID	Yes
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_user_put",
  "type": "object",
  "properties": {
    "id": {
      "description": "The user's unique ID",
      "type": "string"
    },
    "name": {
      "description": "The user's account name",
      "type": "string"
    }
  }
}

```

```

    "primary_group": {
      "description": "The user group's unique ID",
      "type": "string"
    },
    "uid": {
      "description": "The user's NFS UID",
      "type": "string"
    },
    "home_directory": {
      "description": "The user's home directory path",
      "type": "string"
    },
    "password": {
      "description": "The user's password",
      "type": "string",
      "format": "password"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_user",
  "type": "object",
  "properties": {
    "id": {
      "description": "The user's unique id",
      "type": "string"
    },
    "name": {
      "description": "The user's account name",
      "type": "string"
    },
    "primary_group": {
      "description": "The unique ID of the user's group",
      "type": "string"
    }
  }
}

```



```
    },
    "sid": {
      "description": "The users's SID",
      "type": "string"
    },
    "uid": {
      "description": "The user's NFS uid",
      "type": "string"
    },
    "home_directory": {
      "description": "The path to the user's home directory",
      "type": "string"
    },
    "can_change_password": {
      "description": "Specifies whether the user can change the password",
      "type": "boolean"
    }
  }
}
```

DELETE

Delete a local user.

Parameters

Name	Description	Required
<code>id</code>	The user's unique ID	Yes

Response

Codes

Code	Description
200	Return value on success

users/{id}/groups/

Endpoint

/v1/users/{id}/groups/

GET

Retrieve group membership of a specific user. Refer to the 'Modify group' method for a description of the returned fields. Returns an empty array if the provided user is not a local user.

Parameters

Name	Description	Required
id	The user's unique ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_group",
    "type": "object",
    "properties": {
      "id": {
        "description": "The group's unique id",
        "type": "string"
      },
      "name": {
        "description": "The group name",
        "type": "string"
      },
      "sid": {
        "description": "The group's SID",
        "type": "string"
      }
    }
  }
}
```

```
"gid": {  
  "description": "The group's NFS gid",  
  "type": "string"  
}  
}  
}
```

users/{id}/setpassword

Endpoint

/v1/users/{id}/setpassword

POST

Set a local user's password.

Parameters

Name	Description	Required
id	The user's unique ID	Yes

Request

Schema

```
{
  "description": "new_password",
  "type": "object",
  "properties": {
    "new_password": {
      "description": "new_password",
      "type": "string",
      "format": "password"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

metrics/endpoints/default/data

Endpoint

/v2/metrics/endpoints/default/data

GET

Get all metrics for the cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

support/settings

Endpoint

/v1/support/settings

GET

Get monitoring configuration.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_monitoring_config_get",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    },
    "mq_host": {
      "description": "mq_host",
      "type": "string"
    },
    "mq_port": {
      "description": "mq_port",
      "type": "number"
    },
    "mq_proxy_host": {
      "description": "mq_proxy_host",
      "type": "string"
    },
    "mq_proxy_port": {
      "description": "mq_proxy_port",

```

```
    "type": "number"
  },
  "s3_proxy_host": {
    "description": "s3_proxy_host",
    "type": "string"
  },
  "s3_proxy_port": {
    "description": "s3_proxy_port",
    "type": "number"
  },
  "s3_proxy_disable_https": {
    "description": "s3_proxy_disable_https",
    "type": "boolean"
  },
  "vpn_enabled": {
    "description": "vpn_enabled",
    "type": "boolean"
  },
  "vpn_host": {
    "description": "vpn_host",
    "type": "string"
  },
  "period": {
    "description": "period",
    "type": "number"
  },
  "nexus_enabled": {
    "description": "nexus_enabled",
    "type": "boolean"
  },
  "nexus_host": {
    "description": "nexus_host",
    "type": "string"
  },
  "nexus_port": {
    "description": "nexus_port",
    "type": "number"
  },
  "nexus_interval": {
    "description": "nexus_interval",
    "type": "number"
  },
  "nexus_registration_key": {
    "description": "nexus_registration_key",
    "type": "string"
  },
  },
```

```

    "nexus_secret_created_at": {
      "description": "nexus_secret_created_at",
      "type": "string"
    }
  }
}

```

PUT

Set monitoring configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_monitoring_config_put",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    },
    "mq_host": {
      "description": "mq_host",
      "type": "string"
    },
    "mq_port": {
      "description": "mq_port",
      "type": "number"
    },
    "mq_proxy_host": {
      "description": "mq_proxy_host",
      "type": "string"
    },
    "mq_proxy_port": {
      "description": "mq_proxy_port",
      "type": "number"
    }
  },
}

```



```

"s3_proxy_host": {
  "description": "s3_proxy_host",
  "type": "string"
},
"s3_proxy_port": {
  "description": "s3_proxy_port",
  "type": "number"
},
"s3_proxy_disable_https": {
  "description": "s3_proxy_disable_https",
  "type": "boolean"
},
"vpn_enabled": {
  "description": "vpn_enabled",
  "type": "boolean"
},
"vpn_host": {
  "description": "vpn_host",
  "type": "string"
},
"period": {
  "description": "period",
  "type": "number"
},
"nexus_enabled": {
  "description": "nexus_enabled",
  "type": "boolean"
},
"nexus_host": {
  "description": "nexus_host",
  "type": "string"
},
"nexus_port": {
  "description": "nexus_port",
  "type": "number"
},
"nexus_interval": {
  "description": "nexus_interval",
  "type": "number"
},
"nexus_registration_key": {
  "description": "nexus_registration_key",
  "type": "string"
}
}
}

```

Response

Codes

Code	Description
202	Return value on success

PATCH

Partial set of monitoring configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_monitoring_config_put",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "enabled",
      "type": "boolean"
    },
    "mq_host": {
      "description": "mq_host",
      "type": "string"
    },
    "mq_port": {
      "description": "mq_port",
      "type": "number"
    },
    "mq_proxy_host": {
      "description": "mq_proxy_host",
      "type": "string"
    },
    "mq_proxy_port": {
      "description": "mq_proxy_port",
      "type": "number"
    }
  },
}
```

```

"s3_proxy_host": {
  "description": "s3_proxy_host",
  "type": "string"
},
"s3_proxy_port": {
  "description": "s3_proxy_port",
  "type": "number"
},
"s3_proxy_disable_https": {
  "description": "s3_proxy_disable_https",
  "type": "boolean"
},
"vpn_enabled": {
  "description": "vpn_enabled",
  "type": "boolean"
},
"vpn_host": {
  "description": "vpn_host",
  "type": "string"
},
"period": {
  "description": "period",
  "type": "number"
},
"nexus_enabled": {
  "description": "nexus_enabled",
  "type": "boolean"
},
"nexus_host": {
  "description": "nexus_host",
  "type": "string"
},
"nexus_port": {
  "description": "nexus_port",
  "type": "number"
},
"nexus_interval": {
  "description": "nexus_interval",
  "type": "number"
},
"nexus_registration_key": {
  "description": "nexus_registration_key",
  "type": "string"
}
}
}

```

Response

Codes

Code	Description
202	Return value on success

support/status/

Endpoint

/v1/support/status/

GET

List the monitoring status of all nodes: whether various kinds of monitoring connections are enabled/connected/etc.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_node_monitoring_status",
    "type": "object",
    "properties": {
      "node_id": {
        "description": "Node Id",
        "type": "number"
      },
      "monitoring": {
        "type": "string",
        "enum": [
          "DISABLED",
          "IN_PROGRESS",
          "CONNECTED",
          "ERROR",
          "ERROR_PENDING"
        ],
        "description": "monitoring:\n * `CONNECTED` - Connection successful,\n * `DISABLED` - Service is not enabled,\n * `ERROR` - Connection has been down for 5 minut"
      }
    }
  }
}
```

```

es,\n * `ERROR_PENDING` - Connection error on last attempt,\n * `IN_PROGRESS` - Stat
us has not yet been reported"
    },
    "file_upload": {
      "type": "string",
      "enum": [
        "DISABLED",
        "IN_PROGRESS",
        "CONNECTED",
        "ERROR",
        "ERROR_PENDING"
      ],
      "description": "file_upload:\n * `CONNECTED` - Connection successful,\n * `D
ISABLED` - Service is not enabled,\n * `ERROR` - Connection has been down for 5 minu
tes,\n * `ERROR_PENDING` - Connection error on last attempt,\n * `IN_PROGRESS` - Sta
tus has not yet been reported"
    },
    "vpn_connection": {
      "type": "string",
      "enum": [
        "DISABLED",
        "IN_PROGRESS",
        "CONNECTED",
        "ERROR",
        "ERROR_PENDING"
      ],
      "description": "vpn_connection:\n * `CONNECTED` - Connection successful,\n
 * `DISABLED` - Service is not enabled,\n * `ERROR` - Connection has been down for 5
minutes,\n * `ERROR_PENDING` - Connection error on last attempt,\n * `IN_PROGRESS`
- Status has not yet been reported"
    }
  }
}
}

```

support/vpn-keys

Endpoint

/v1/support/vpn-keys

GET

Get VPN keys.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "vpn_keys",
  "type": "object",
  "properties": {
    "mqvpn_client_cert": {
      "description": "mqvpn_client_cert",
      "type": "string"
    },
    "mqvpn_client_key": {
      "description": "mqvpn_client_key",
      "type": "string"
    },
    "qumulo_ca_cert": {
      "description": "qumulo_ca_cert",
      "type": "string"
    }
  }
}
```

PUT

Set VPN keys.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "vpn_keys",
  "type": "object",
  "properties": {
    "mqvpn_client_crt": {
      "description": "mqvpn_client_crt",
      "type": "string"
    },
    "mqvpn_client_key": {
      "description": "mqvpn_client_key",
      "type": "string"
    },
    "qumulo_ca_crt": {
      "description": "qumulo_ca_crt",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "vpn_keys",
  "type": "object",
  "properties": {
    "mqvpn_client_crt": {
      "description": "mqvpn_client_crt",
      "type": "string"
    },
  },
}
```



```
"mqvpn_client_key": {
  "description": "mqvpn_client_key",
  "type": "string"
},
"qumulo_ca_crt": {
  "description": "qumulo_ca_crt",
  "type": "string"
}
}
```

PATCH

Set VPN keys.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "vpn_keys_patch",
  "type": "object",
  "properties": {
    "mqvpn_client_crt": {
      "description": "mqvpn_client_crt",
      "type": "string"
    },
    "mqvpn_client_key": {
      "description": "mqvpn_client_key",
      "type": "string"
    },
    "qumulo_ca_crt": {
      "description": "qumulo_ca_crt",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "vpn_keys",
  "type": "object",
  "properties": {
    "mqvpn_client.crt": {
      "description": "mqvpn_client.crt",
      "type": "string"
    },
    "mqvpn_client.key": {
      "description": "mqvpn_client.key",
      "type": "string"
    },
    "qumulo_ca.crt": {
      "description": "qumulo_ca.crt",
      "type": "string"
    }
  }
}
```

support/vpn/key/certificate-signing-request

Endpoint

/v1/support/vpn/key/certificate-signing-request

GET

Get a certificate signing request for the generated private key. This returns empty if no private key was generated or if a manual private key is used.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_certificate_signing_request",
  "type": "object",
  "properties": {
    "request": {
      "description": "request",
      "type": "string"
    }
  }
}
```

support/vpn/key/generate

Endpoint

/v1/support/vpn/key/generate

POST

Generate a new VPN private key. If there is an existing private key, this overwrites that key.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

nfs/exports/

Endpoint

/v2/nfs/exports/

GET

This method lists NFS exports. Refer to the 'Modify NFS Export' method for a description of the returned fields.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_nfs_export",
    "type": "object",
    "properties": {
      "id": {
        "description": "The unique ID of the NFS export",
        "type": "string"
      },
      "export_path": {
        "description": "The NFS export path",
        "type": "string"
      },
      "fs_path": {
        "description": "The filesystem path of the exported directory",
        "type": "string"
      },
      "description": {
        "description": "Description of this NFS export",
        "type": "string"
      }
    }
  }
}
```

```

},
"restrictions": {
  "type": "array",
  "items": {
    "description": "An array of NFS host restrictions.",
    "type": "object",
    "properties": {
      "host_restrictions": {
        "type": "array",
        "items": {
          "description": "The list of hosts allowed to connect",
          "type": "string"
        }
      },
    },
    "require_privileged_port": {
      "description": "Require that hosts use a privileged port to use this e
xport.",
      "type": "boolean"
    },
    "read_only": {
      "description": "Sets the NFS export to read-only",
      "type": "boolean"
    },
    "required_authentication_mode": {
      "type": "string",
      "enum": [
        "AUTHENTICATION_MODE_NONE",
        "AUTHENTICATION_MODE_KRB5",
        "AUTHENTICATION_MODE_KRB5I",
        "AUTHENTICATION_MODE_KRB5P"
      ],
      "description": "The authentication mode hosts are required to authenti
cate with:\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the
krb5 security flavor.,\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authentica
te with the krb5i security flavor.,\n * `AUTHENTICATION_MODE_KRB5P` - Require users
to authenticate with the krb5p security flavor.,\n * `AUTHENTICATION_MODE_NONE` - Al
low unauthenticated access."
    },
    "user_mapping": {
      "type": "string",
      "enum": [
        "NFS_MAP_NONE",
        "NFS_MAP_ROOT",
        "NFS_MAP_ALL"
      ],
      "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_AL

```

```

L` - Map all users.,\n * `NFS_MAP_NONE` - Do not map users.,\n * `NFS_MAP_ROOT` - Map root user (uid 0).",
    },
    "map_to_user": {
        "description": "An identity object representing a local user or an NFS user to map (see /users). If map_to_user is an NFS user, then map_to_group with an NFS gid must be given.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",
                    "INTERNAL",
                    "QUMULO_OPERATOR",
                    "QUMULO_SUPPORT"
                ],
                "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID",
            },
            "id_value": {
                "description": "id_value",
                "type": "string"
            }
        }
    },
    "map_to_group": {
        "description": "An identity object representing an NFS group. If given, map_to_user should be an NFS user.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",
                    "INTERNAL",

```

```

        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GRO
UP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NF
S_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QU
MULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
}
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "FILE_IDS",
            "FILE_SIZES",
            "FS_SIZE"
        ],
        "description": "Specify which NFS3 result values should be 32-bit sanitiz
ed on this export. Has no effect on exports used over NFS4.: \n * `FILE_IDS` - Hash hi
gh file ids to 32 bits., \n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit i
n 32 bits., \n * `FS_SIZE` - Clamp available, used and total space reported for the F
S to 4GiB."
    }
},
"tenant_id": {
    "description": "The tenant ID of the tenant that the NFS export is a part o
f",
    "type": "number"
}
}
}
}
}

```

POST

This method adds an NFS export.

Parameters

Name	Description	Required
<code>allow-fs-path-create</code>	Specifies whether the file system path can be created if it does not already exist.	No

Request

Schema

```
{
  "description": "api_nfs_export_post",
  "type": "object",
  "properties": {
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",
      "type": "string"
    },
    "description": {
      "description": "Description of this NFS export",
      "type": "string"
    },
    "restrictions": {
      "type": "array",
      "items": {
        "description": "An array of NFS host restrictions.",
        "type": "object",
        "properties": {
          "host_restrictions": {
            "type": "array",
            "items": {
              "description": "The list of hosts allowed to connect",
              "type": "string"
            }
          },
          "require_privileged_port": {
            "description": "Require that hosts use a privileged port to use this export.",
            "type": "boolean"
          },
          "read_only": {
```

```

        "description": "Sets the NFS export to read-only",
        "type": "boolean"
    },
    "required_authentication_mode": {
        "type": "string",
        "enum": [
            "AUTHENTICATION_MODE_NONE",
            "AUTHENTICATION_MODE_KRB5",
            "AUTHENTICATION_MODE_KRB5I",
            "AUTHENTICATION_MODE_KRB5P"
        ],
        "description": "The authentication mode hosts are required to authentic
te with:\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the kr
b5 security flavor.,\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authentic
e with the krb5i security flavor.,\n * `AUTHENTICATION_MODE_KRB5P` - Require users t
o authenticate with the krb5p security flavor.,\n * `AUTHENTICATION_MODE_NONE` - All
ow unauthenticated access."
    },
    "user_mapping": {
        "type": "string",
        "enum": [
            "NFS_MAP_NONE",
            "NFS_MAP_ROOT",
            "NFS_MAP_ALL"
        ],
        "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL`
- Map all users.,\n * `NFS_MAP_NONE` - Do not map users.,\n * `NFS_MAP_ROOT` - Map r
oot user (uid 0).",
    },
    "map_to_user": {
        "description": "An identity object representing a local user or an NFS u
ser to map (see /users). If map_to_user is an NFS user, then map_to_group with an NF
S gid must be given.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",
                    "INTERNAL",
                    "QUMULO_OPERATOR",
                    "QUMULO_SUPPORT"
                ]
            }
        }
    }
}

```

```

        ],
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
},
"map_to_group": {
    "description": "An identity object representing an NFS group. If given,
map_to_user should be an NFS user.",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ],
            "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {
            "description": "id_value",
            "type": "string"
        }
    }
}
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {

```

```

        "type": "string",
        "enum": [
            "FILE_IDS",
            "FILE_SIZES",
            "FS_SIZE"
        ],
        "description": "Specify which NFS3 result values should be 32-bit sanitized
on this export. Has no effect on exports used over NFS4:\n * `FILE_IDS` - Hash high
file ids to 32 bits.,\n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in 3
2 bits.,\n * `FS_SIZE` - Clamp available, used and total space reported for the FS t
o 4GiB."
    }
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_nfs_export",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    },
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",
      "type": "string"
    },
    "description": {
      "description": "Description of this NFS export",
      "type": "string"
    }
  }
}

```

```

},
"restrictions": {
  "type": "array",
  "items": {
    "description": "An array of NFS host restrictions.",
    "type": "object",
    "properties": {
      "host_restrictions": {
        "type": "array",
        "items": {
          "description": "The list of hosts allowed to connect",
          "type": "string"
        }
      },
    },
    "require_privileged_port": {
      "description": "Require that hosts use a privileged port to use this export.",
      "type": "boolean"
    },
    "read_only": {
      "description": "Sets the NFS export to read-only",
      "type": "boolean"
    },
    "required_authentication_mode": {
      "type": "string",
      "enum": [
        "AUTHENTICATION_MODE_NONE",
        "AUTHENTICATION_MODE_KRB5",
        "AUTHENTICATION_MODE_KRB5I",
        "AUTHENTICATION_MODE_KRB5P"
      ],
      "description": "The authentication mode hosts are required to authenticate with:\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the krb5 security flavor.,\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticate with the krb5i security flavor.,\n * `AUTHENTICATION_MODE_KRB5P` - Require users to authenticate with the krb5p security flavor.,\n * `AUTHENTICATION_MODE_NONE` - Allow unauthenticated access."
    },
    "user_mapping": {
      "type": "string",
      "enum": [
        "NFS_MAP_NONE",
        "NFS_MAP_ROOT",
        "NFS_MAP_ALL"
      ],
      "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL`

```

- Map all users.,\n * `NFS\_MAP\_NONE` - Do not map users.,\n * `NFS\_MAP\_ROOT` - Map root user (uid 0)."

```
    },
    "map_to_user": {
      "description": "An identity object representing a local user or an NFS user to map (see /users). If map_to_user is an NFS user, then map_to_group with an NFS gid must be given.",
      "type": "object",
      "properties": {
        "id_type": {
          "type": "string",
          "enum": [
            "LOCAL_USER",
            "LOCAL_GROUP",
            "NFS_GID",
            "NFS_UID",
            "SMB_SID",
            "INTERNAL",
            "QUMULO_OPERATOR",
            "QUMULO_SUPPORT"
          ],
          "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {
          "description": "id_value",
          "type": "string"
        }
      }
    },
    "map_to_group": {
      "description": "An identity object representing an NFS group. If given, map_to_user should be an NFS user.",
      "type": "object",
      "properties": {
        "id_type": {
          "type": "string",
          "enum": [
            "LOCAL_USER",
            "LOCAL_GROUP",
            "NFS_GID",
            "NFS_UID",
            "SMB_SID",
            "INTERNAL",

```

```

        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU\nP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U\nID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL\nO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
}
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "FILE_IDS",
            "FILE_SIZES",
            "FS_SIZE"
        ],
        "description": "Specify which NFS3 result values should be 32-bit sanitized\non this export. Has no effect on exports used over NFS4.: \n * `FILE_IDS` - Hash hig\nh file ids to 32 bits., \n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in\n32 bits., \n * `FS_SIZE` - Clamp available, used and total space reported for the FS\nto 4GiB."
    }
},
"tenant_id": {
    "description": "The tenant ID of the tenant that the NFS export is a part of",
    "type": "number"
}
}
}

```

nfs/exports/{ref}

Endpoint

/v2/nfs/exports/{ref}

GET

This method retrieves the specified NFS export. Refer to the 'Modify NFS Export' method for a description of the returned fields.

Parameters

Name	Description	Required
ref	A unique identifier of the NFS export, either ID or export path	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_nfs_export",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    },
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",
      "type": "string"
    },
    "description": {
      "description": "Description of this NFS export",

```



```

    "type": "string"
  },
  "restrictions": {
    "type": "array",
    "items": {
      "description": "An array of NFS host restrictions.",
      "type": "object",
      "properties": {
        "host_restrictions": {
          "type": "array",
          "items": {
            "description": "The list of hosts allowed to connect",
            "type": "string"
          }
        }
      }
    },
    "require_privileged_port": {
      "description": "Require that hosts use a privileged port to use this export.",
      "type": "boolean"
    },
    "read_only": {
      "description": "Sets the NFS export to read-only",
      "type": "boolean"
    },
    "required_authentication_mode": {
      "type": "string",
      "enum": [
        "AUTHENTICATION_MODE_NONE",
        "AUTHENTICATION_MODE_KRB5",
        "AUTHENTICATION_MODE_KRB5I",
        "AUTHENTICATION_MODE_KRB5P"
      ],
      "description": "The authentication mode hosts are required to authenticate with.\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the krb5 security flavor.,\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticate with the krb5i security flavor.,\n * `AUTHENTICATION_MODE_KRB5P` - Require users to authenticate with the krb5p security flavor.,\n * `AUTHENTICATION_MODE_NONE` - Allow unauthenticated access."
    },
    "user_mapping": {
      "type": "string",
      "enum": [
        "NFS_MAP_NONE",
        "NFS_MAP_ROOT",
        "NFS_MAP_ALL"
      ]
    }
  }
}

```

```

        "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL`  

- Map all users.,\n * `NFS_MAP_NONE` - Do not map users.,\n * `NFS_MAP_ROOT` - Map root user (uid 0).",
    },
    "map_to_user": {
        "description": "An identity object representing a local user or an NFS user to map (see /users). If map_to_user is an NFS user, then map_to_group with an NFS gid must be given.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",
                    "INTERNAL",
                    "QUMULO_OPERATOR",
                    "QUMULO_SUPPORT"
                ],
                "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID",
            },
            "id_value": {
                "description": "id_value",
                "type": "string"
            }
        }
    },
    "map_to_group": {
        "description": "An identity object representing an NFS group. If given, map_to_user should be an NFS user.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",

```

```

        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU\nP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U\nID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL\nO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "FILE_IDS",
            "FILE_SIZES",
            "FS_SIZE"
        ],
        "description": "Specify which NFS3 result values should be 32-bit sanitized\non this export. Has no effect on exports used over NFS4.:\n * `FILE_IDS` - Hash hig\nh file ids to 32 bits.,\n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in\n32 bits.,\n * `FS_SIZE` - Clamp available, used and total space reported for the FS\nto 4GiB."
    }
},
"tenant_id": {
    "description": "The tenant ID of the tenant that the NFS export is a part of",
    "type": "number"
}
}
}
}

```

PUT

This method sets all attributes of a NFS export.

Parameters

Name	Description	Required
<code>ref</code>	A unique identifier of the NFS export, either ID or export path	Yes
<code>allow-fs-path-create</code>	Specifies whether the file system path can be created if it does not already exist.	No
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_nfs_export",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    },
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",
      "type": "string"
    },
    "description": {
      "description": "Description of this NFS export",
      "type": "string"
    },
    "restrictions": {
      "type": "array",
      "items": {
        "description": "An array of NFS host restrictions.",
        "type": "object",
        "properties": {
          "host_restrictions": {
            "type": "array",
            "items": {
              "description": "The list of hosts allowed to connect",
              "type": "string"
            }
          }
        }
      }
    }
  }
}
```

```

    }
  },
  "require_privileged_port": {
    "description": "Require that hosts use a privileged port to use this export.",
    "type": "boolean"
  },
  "read_only": {
    "description": "Sets the NFS export to read-only",
    "type": "boolean"
  },
  "required_authentication_mode": {
    "type": "string",
    "enum": [
      "AUTHENTICATION_MODE_NONE",
      "AUTHENTICATION_MODE_KRB5",
      "AUTHENTICATION_MODE_KRB5I",
      "AUTHENTICATION_MODE_KRB5P"
    ],
    "description": "The authentication mode hosts are required to authenticate with:\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the krb5 security flavor.,\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticate with the krb5i security flavor.,\n * `AUTHENTICATION_MODE_KRB5P` - Require users to authenticate with the krb5p security flavor.,\n * `AUTHENTICATION_MODE_NONE` - Allow unauthenticated access."
  },
  "user_mapping": {
    "type": "string",
    "enum": [
      "NFS_MAP_NONE",
      "NFS_MAP_ROOT",
      "NFS_MAP_ALL"
    ],
    "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL` - Map all users.,\n * `NFS_MAP_NONE` - Do not map users.,\n * `NFS_MAP_ROOT` - Map root user (uid 0).",
  },
  "map_to_user": {
    "description": "An identity object representing a local user or an NFS user to map (see /users). If map_to_user is an NFS user, then map_to_group with an NFS gid must be given.",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [

```

```

        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
},
"map_to_group": {
    "description": "An identity object representing an NFS group. If given,
map_to_user should be an NFS user.",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ],
            "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {
            "description": "id_value",
            "type": "string"
        }
    }
}

```

```

    }
  }
}
},
"fields_to_present_as_32_bit": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "FILE_IDS",
      "FILE_SIZES",
      "FS_SIZE"
    ],
    "description": "Specify which NFS3 result values should be 32-bit sanitized
on this export. Has no effect on exports used over NFS4.:
\n * `FILE_IDS` - Hash high file ids to 32 bits.
\n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in 32 bits.
\n * `FS_SIZE` - Clamp available, used and total space reported for the FS
to 4GiB."
  }
},
"tenant_id": {
  "description": "The tenant ID of the tenant that the NFS export is a part of",
  "type": "number"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_nfs_export",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    }
  }
}

```

```

},
"export_path": {
  "description": "The NFS export path",
  "type": "string"
},
"fs_path": {
  "description": "The filesystem path of the exported directory",
  "type": "string"
},
"description": {
  "description": "Description of this NFS export",
  "type": "string"
},
"restrictions": {
  "type": "array",
  "items": {
    "description": "An array of NFS host restrictions.",
    "type": "object",
    "properties": {
      "host_restrictions": {
        "type": "array",
        "items": {
          "description": "The list of hosts allowed to connect",
          "type": "string"
        }
      },
      "require_privileged_port": {
        "description": "Require that hosts use a privileged port to use this export.",
        "type": "boolean"
      },
      "read_only": {
        "description": "Sets the NFS export to read-only",
        "type": "boolean"
      },
      "required_authentication_mode": {
        "type": "string",
        "enum": [
          "AUTHENTICATION_MODE_NONE",
          "AUTHENTICATION_MODE_KRB5",
          "AUTHENTICATION_MODE_KRB5I",
          "AUTHENTICATION_MODE_KRB5P"
        ],
        "description": "The authentication mode hosts are required to authenticate with.\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the krb5 security flavor.\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticat

```


e with the krb5i security flavor.,\n * `AUTHENTICATION\_MODE\_KRB5P` - Require users to authenticate with the krb5p security flavor.,\n * `AUTHENTICATION\_MODE\_NONE` - Allow unauthenticated access."

```

    },
    "user_mapping": {
      "type": "string",
      "enum": [
        "NFS_MAP_NONE",
        "NFS_MAP_ROOT",
        "NFS_MAP_ALL"
      ],
      "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL` - Map all users.,\n * `NFS_MAP_NONE` - Do not map users.,\n * `NFS_MAP_ROOT` - Map root user (uid 0).",
    },
    "map_to_user": {
      "description": "An identity object representing a local user or an NFS user to map (see /users). If map_to_user is an NFS user, then map_to_group with an NFS gid must be given.",
      "type": "object",
      "properties": {
        "id_type": {
          "type": "string",
          "enum": [
            "LOCAL_USER",
            "LOCAL_GROUP",
            "NFS_GID",
            "NFS_UID",
            "SMB_SID",
            "INTERNAL",
            "QUMULO_OPERATOR",
            "QUMULO_SUPPORT"
          ],
          "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID",
        },
        "id_value": {
          "description": "id_value",
          "type": "string"
        }
      }
    },
    "map_to_group": {
      "description": "An identity object representing an NFS group. If given,
```

```

map_to_user should be an NFS user.",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ],
            "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {
            "description": "id_value",
            "type": "string"
        }
    }
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "FILE_IDS",
            "FILE_SIZES",
            "FS_SIZE"
        ],
        "description": "Specify which NFS3 result values should be 32-bit sanitized
on this export. Has no effect on exports used over NFS4.: \n * `FILE_IDS` - Hash hig
h file ids to 32 bits., \n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in
32 bits., \n * `FS_SIZE` - Clamp available, used and total space reported for the FS
to 4GiB."
    }
},
"tenant_id": {

```

```
    "description": "The tenant ID of the tenant that the NFS export is a part of",  
    "type": "number"  
  }  
}
```

DELETE

This method deletes an NFS export.

Parameters

Name	Description	Required
ref	A unique identifier of the NFS export, either ID or export path	Yes
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

This method modifies individual attributes of a NFS export.

Parameters

Name	Description	Required
ref	A unique identifier of the NFS export, either ID or export path	Yes
allow-fs-path-create	Specifies whether the file system path can be created if it does not already exist.	No
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_nfs_export_patch",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    },
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",
      "type": "string"
    },
    "description": {
      "description": "Description of this NFS export",
      "type": "string"
    },
    "restrictions": {
      "type": "array",
      "items": {
        "description": "An array of NFS host restrictions.",
        "type": "object",
        "properties": {
          "host_restrictions": {
            "type": "array",
            "items": {
              "description": "The list of hosts allowed to connect",
              "type": "string"
            }
          },
          "require_privileged_port": {
            "description": "Require that hosts use a privileged port to use this export.",
            "type": "boolean"
          },
          "read_only": {
            "description": "Sets the NFS export to read-only",
            "type": "boolean"
          },
          "required_authentication_mode": {
```

```

    "type": "string",
    "enum": [
        "AUTHENTICATION_MODE_NONE",
        "AUTHENTICATION_MODE_KRB5",
        "AUTHENTICATION_MODE_KRB5I",
        "AUTHENTICATION_MODE_KRB5P"
    ],
    "description": "The authentication mode hosts are required to authenticat
te with.:\\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the kr
b5 security flavor.,\\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticat
e with the krb5i security flavor.,\\n * `AUTHENTICATION_MODE_KRB5P` - Require users t
o authenticate with the krb5p security flavor.,\\n * `AUTHENTICATION_MODE_NONE` - All
ow unauthenticated access."
},
    "user_mapping": {
        "type": "string",
        "enum": [
            "NFS_MAP_NONE",
            "NFS_MAP_ROOT",
            "NFS_MAP_ALL"
        ],
        "description": "NFS user mapping (squashing) support:\\n * `NFS_MAP_ALL`
- Map all users.,\\n * `NFS_MAP_NONE` - Do not map users.,\\n * `NFS_MAP_ROOT` - Map r
oot user (uid 0).\"
    },
    "map_to_user": {
        "description": "An identity object representing a local user or an NFS u
ser to map (see /users). If map_to_user is an NFS user, then map_to_group with an NF
S gid must be given.\",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",
                    "INTERNAL",
                    "QUMULO_OPERATOR",
                    "QUMULO_SUPPORT"
                ],
                "description": \"id_type:\\n * `INTERNAL` - INTERNAL,\\n * `LOCAL_GROU
P` - LOCAL_GROUP,\\n * `LOCAL_USER` - LOCAL_USER,\\n * `NFS_GID` - NFS_GID,\\n * `NFS_U
ID` - NFS_UID,\\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\\n * `QUMULO_SUPPORT` - QUMUL

```

```

O_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
},
"map_to_group": {
    "description": "An identity object representing an NFS group. If given,
map_to_user should be an NFS user.",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ],
            "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {
            "description": "id_value",
            "type": "string"
        }
    }
}
}
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "FILE_IDS",
            "FILE_SIZES",

```

```

        "FS_SIZE"
    ],
    "description": "Specify which NFS3 result values should be 32-bit sanitized on this export. Has no effect on exports used over NFS4.:\\n * `FILE_IDS` - Hash high file ids to 32 bits.,\\n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in 32 bits.,\\n * `FS_SIZE` - Clamp available, used and total space reported for the FS to 4GiB."
    }
},
"tenant_id": {
    "description": "The tenant ID of the tenant that the NFS export is a part of",
    "type": "number"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_nfs_export",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    },
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",
      "type": "string"
    },
    "description": {
      "description": "Description of this NFS export",
      "type": "string"
    }
  }
}

```

```

},
"restrictions": {
  "type": "array",
  "items": {
    "description": "An array of NFS host restrictions.",
    "type": "object",
    "properties": {
      "host_restrictions": {
        "type": "array",
        "items": {
          "description": "The list of hosts allowed to connect",
          "type": "string"
        }
      },
    },
    "require_privileged_port": {
      "description": "Require that hosts use a privileged port to use this export.",
      "type": "boolean"
    },
    "read_only": {
      "description": "Sets the NFS export to read-only",
      "type": "boolean"
    },
    "required_authentication_mode": {
      "type": "string",
      "enum": [
        "AUTHENTICATION_MODE_NONE",
        "AUTHENTICATION_MODE_KRB5",
        "AUTHENTICATION_MODE_KRB5I",
        "AUTHENTICATION_MODE_KRB5P"
      ],
      "description": "The authentication mode hosts are required to authenticate with:\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the krb5 security flavor.,\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticate with the krb5i security flavor.,\n * `AUTHENTICATION_MODE_KRB5P` - Require users to authenticate with the krb5p security flavor.,\n * `AUTHENTICATION_MODE_NONE` - Allow unauthenticated access."
    },
    "user_mapping": {
      "type": "string",
      "enum": [
        "NFS_MAP_NONE",
        "NFS_MAP_ROOT",
        "NFS_MAP_ALL"
      ],
      "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL`

```


- Map all users.,\n * `NFS\_MAP\_NONE` - Do not map users.,\n * `NFS\_MAP\_ROOT` - Map root user (uid 0)."

```
    },
    "map_to_user": {
      "description": "An identity object representing a local user or an NFS user to map (see /users). If map_to_user is an NFS user, then map_to_group with an NFS gid must be given.",
      "type": "object",
      "properties": {
        "id_type": {
          "type": "string",
          "enum": [
            "LOCAL_USER",
            "LOCAL_GROUP",
            "NFS_GID",
            "NFS_UID",
            "SMB_SID",
            "INTERNAL",
            "QUMULO_OPERATOR",
            "QUMULO_SUPPORT"
          ],
          "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {
          "description": "id_value",
          "type": "string"
        }
      }
    },
    "map_to_group": {
      "description": "An identity object representing an NFS group. If given, map_to_user should be an NFS user.",
      "type": "object",
      "properties": {
        "id_type": {
          "type": "string",
          "enum": [
            "LOCAL_USER",
            "LOCAL_GROUP",
            "NFS_GID",
            "NFS_UID",
            "SMB_SID",
            "INTERNAL",

```

```

        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU\nP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U\nID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL\nO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
}
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "FILE_IDS",
            "FILE_SIZES",
            "FS_SIZE"
        ],
        "description": "Specify which NFS3 result values should be 32-bit sanitized\non this export. Has no effect on exports used over NFS4.: \n * `FILE_IDS` - Hash hig\nh file ids to 32 bits., \n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in\n32 bits., \n * `FS_SIZE` - Clamp available, used and total space reported for the FS\nto 4GiB."
    }
},
"tenant_id": {
    "description": "The tenant ID of the tenant that the NFS export is a part of",
    "type": "number"
}
}
}

```

nfs/settings

Endpoint

/v2/nfs/settings

GET

Retrieve current NFS server configuration.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",

```

```

    "type": "boolean"
  },
  "idmap_domain": {
    "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
    "type": "string"
  }
}
}

```

PUT

Modify current NFS server configuration.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",
      "type": "boolean"
    }
  },
}

```

```

    "idmap_domain": {
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",
      "type": "boolean"
    },
    "idmap_domain": {
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",

```

```
    "type": "string"
  }
}
```

PATCH

Modify current NFS server configuration.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_nfs_settings_patch",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",
      "type": "boolean"
    },
    "idmap_domain": {
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
      "type": "string"
    }
  }
}
```

```
}  
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{  
  "description": "api_nfs_settings",  
  "type": "object",  
  "properties": {  
    "v4_enabled": {  
      "description": "Whether NFSv4 is enabled",  
      "type": "boolean"  
    },  
    "krb5_enabled": {  
      "description": "Whether Kerberos5 is enabled",  
      "type": "boolean"  
    },  
    "krb5p_enabled": {  
      "description": "Whether Kerberos5p (privacy) is enabled",  
      "type": "boolean"  
    },  
    "krb5i_enabled": {  
      "description": "Whether Kerberos5i (integrity) is enabled",  
      "type": "boolean"  
    },  
    "auth_sys_enabled": {  
      "description": "Whether AUTH_SYS is enabled",  
      "type": "boolean"  
    },  
    "idmap_domain": {  
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",  
      "type": "string"  
    }  
  }  
}
```

nfs/exports/

Endpoint

/v3/nfs/exports/

GET

[preview] This method lists NFS exports. Refer to the 'Modify NFS Export' method for a description of the returned fields.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_nfs_exports_v3",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of NFS exports",
        "type": "object",
        "properties": {
          "id": {
            "description": "The unique ID of the NFS export",
            "type": "string"
          },
          "export_path": {
            "description": "The NFS export path",
            "type": "string"
          },
          "tenant_id": {
            "description": "The tenant ID of the tenant that the NFS export is a part of",

```



```

    "type": "number"
  },
  "fs_path": {
    "description": "The filesystem path of the exported directory",
    "type": "string"
  },
  "description": {
    "description": "Description of this NFS export",
    "type": "string"
  },
  "restrictions": {
    "type": "array",
    "items": {
      "description": "An array of NFS host restrictions.",
      "type": "object",
      "properties": {
        "host_restrictions": {
          "type": "array",
          "items": {
            "description": "The list of hosts allowed to connect",
            "type": "string"
          }
        }
      }
    },
    "require_privileged_port": {
      "description": "Require that hosts use a privileged port to use th
is export.",
      "type": "boolean"
    },
    "read_only": {
      "description": "Sets the NFS export to read-only",
      "type": "boolean"
    },
    "required_authentication_mode": {
      "type": "string",
      "enum": [
        "AUTHENTICATION_MODE_NONE",
        "AUTHENTICATION_MODE_KRB5",
        "AUTHENTICATION_MODE_KRB5I",
        "AUTHENTICATION_MODE_KRB5P"
      ],
      "description": "The authentication mode hosts are required to auth
enticate with.\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with
the krb5 security flavor.\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authen
ticate with the krb5i security flavor.\n * `AUTHENTICATION_MODE_KRB5P` - Require us
ers to authenticate with the krb5p security flavor.\n * `AUTHENTICATION_MODE_NONE`
- Allow unauthenticated access."
    }
  }
}

```

```

    },
    "user_mapping": {
        "type": "string",
        "enum": [
            "NFS_MAP_NONE",
            "NFS_MAP_ROOT",
            "NFS_MAP_ALL"
        ],
        "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL` - Map all users.,\n * `NFS_MAP_NONE` - Do not map users.,\n * `NFS_MAP_ROOT` - Map root user (uid 0).",
    },
    "map_to_user": {
        "description": "An identity object representing a local user or an NFS user to map (see /users). If map_to_user is an NFS user, then map_to_group with an NFS gid must be given.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",
                    "INTERNAL",
                    "QUMULO_OPERATOR",
                    "QUMULO_SUPPORT"
                ],
                "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID",
            },
            "id_value": {
                "description": "id_value",
                "type": "string"
            }
        }
    },
    "map_to_group": {
        "description": "An identity object representing an NFS group. If given, map_to_user should be an NFS user.",
        "type": "object",
        "properties": {

```



```
}
```

POST

[preview] This method adds an NFS export.

Parameters

Name	Description	Required
<code>allow-fs-path-create</code>	Specifies whether the file system path can be created if it does not already exist.	No

Request

Schema

```
{
  "description": "api_nfs_export_post_v3",
  "type": "object",
  "properties": {
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the NFS export is a part of",
      "type": "number"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",
      "type": "string"
    },
    "description": {
      "description": "Description of this NFS export",
      "type": "string"
    },
    "restrictions": {
      "type": "array",
      "items": {
        "description": "An array of NFS host restrictions.",
        "type": "object",
        "properties": {
          "host_restrictions": {
            "type": "array",
```

```

    "items": {
      "description": "The list of hosts allowed to connect",
      "type": "string"
    }
  },
  "require_privileged_port": {
    "description": "Require that hosts use a privileged port to use this export.",
    "type": "boolean"
  },
  "read_only": {
    "description": "Sets the NFS export to read-only",
    "type": "boolean"
  },
  "required_authentication_mode": {
    "type": "string",
    "enum": [
      "AUTHENTICATION_MODE_NONE",
      "AUTHENTICATION_MODE_KRB5",
      "AUTHENTICATION_MODE_KRB5I",
      "AUTHENTICATION_MODE_KRB5P"
    ],
    "description": "The authentication mode hosts are required to authenticate with.:\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the krb5 security flavor.,\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticate with the krb5i security flavor.,\n * `AUTHENTICATION_MODE_KRB5P` - Require users to authenticate with the krb5p security flavor.,\n * `AUTHENTICATION_MODE_NONE` - Allow unauthenticated access."
  },
  "user_mapping": {
    "type": "string",
    "enum": [
      "NFS_MAP_NONE",
      "NFS_MAP_ROOT",
      "NFS_MAP_ALL"
    ],
    "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL` - Map all users.,\n * `NFS_MAP_NONE` - Do not map users.,\n * `NFS_MAP_ROOT` - Map root user (uid 0).\"
  },
  "map_to_user": {
    "description": "An identity object representing a local user or an NFS user to map (see /users). If map_to_user is an NFS user, then map_to_group with an NFS gid must be given.",
    "type": "object",
    "properties": {

```

```

    "id_type": {
      "type": "string",
      "enum": [
        "LOCAL_USER",
        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
      ],
      "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU\nP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U\nID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL\nO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
      "description": "id_value",
      "type": "string"
    }
  },
  "map_to_group": {
    "description": "An identity object representing an NFS group. If given,\nmap_to_user should be an NFS user.",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ],
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU\nP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U\nID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL\nO_SUPPORT,\n * `SMB_SID` - SMB_SID"
      },
      "id_value": {

```

```

        "description": "id_value",
        "type": "string"
    }
}
}
}
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "FILE_IDS",
            "FILE_SIZES",
            "FS_SIZE"
        ],
        "description": "Specify which NFS3 result values should be 32-bit sanitized
on this export. Has no effect on exports used over NFS4:\n * `FILE_IDS` - Hash high
file ids to 32 bits.,\n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in 3
2 bits.,\n * `FS_SIZE` - Clamp available, used and total space reported for the FS t
o 4GiB."
    }
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_nfs_export_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    },
  },
}

```

```

"export_path": {
  "description": "The NFS export path",
  "type": "string"
},
"tenant_id": {
  "description": "The tenant ID of the tenant that the NFS export is a part of",
  "type": "number"
},
"fs_path": {
  "description": "The filesystem path of the exported directory",
  "type": "string"
},
"description": {
  "description": "Description of this NFS export",
  "type": "string"
},
"restrictions": {
  "type": "array",
  "items": {
    "description": "An array of NFS host restrictions.",
    "type": "object",
    "properties": {
      "host_restrictions": {
        "type": "array",
        "items": {
          "description": "The list of hosts allowed to connect",
          "type": "string"
        }
      },
      "require_privileged_port": {
        "description": "Require that hosts use a privileged port to use this export.",
        "type": "boolean"
      },
      "read_only": {
        "description": "Sets the NFS export to read-only",
        "type": "boolean"
      },
      "required_authentication_mode": {
        "type": "string",
        "enum": [
          "AUTHENTICATION_MODE_NONE",
          "AUTHENTICATION_MODE_KRB5",
          "AUTHENTICATION_MODE_KRB5I",
          "AUTHENTICATION_MODE_KRB5P"
        ]
      }
    }
  }
}

```



```

        "description": "The authentication mode hosts are required to authentic
te with.:\\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the kr
b5 security flavor.,\\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticat
e with the krb5i security flavor.,\\n * `AUTHENTICATION_MODE_KRB5P` - Require users t
o authenticate with the krb5p security flavor.,\\n * `AUTHENTICATION_MODE_NONE` - All
ow unauthenticated access."
    },
    "user_mapping": {
        "type": "string",
        "enum": [
            "NFS_MAP_NONE",
            "NFS_MAP_ROOT",
            "NFS_MAP_ALL"
        ],
        "description": "NFS user mapping (squashing) support:\\n * `NFS_MAP_ALL`
- Map all users.,\\n * `NFS_MAP_NONE` - Do not map users.,\\n * `NFS_MAP_ROOT` - Map r
oot user (uid 0).\"
    },
    "map_to_user": {
        "description": "An identity object representing a local user or an NFS u
ser to map (see /users). If map_to_user is an NFS user, then map_to_group with an NF
S gid must be given.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",
                    "INTERNAL",
                    "QUMULO_OPERATOR",
                    "QUMULO_SUPPORT"
                ],
                "description": "id_type:\\n * `INTERNAL` - INTERNAL,\\n * `LOCAL_GROU
P` - LOCAL_GROUP,\\n * `LOCAL_USER` - LOCAL_USER,\\n * `NFS_GID` - NFS_GID,\\n * `NFS_U
ID` - NFS_UID,\\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\\n * `SMB_SID` - SMB_SID\"
            },
            "id_value": {
                "description": "id_value",
                "type": "string"
            }
        }
    }
}

```

```

    },
    "map_to_group": {
      "description": "An identity object representing an NFS group. If given,
map_to_user should be an NFS user.",
      "type": "object",
      "properties": {
        "id_type": {
          "type": "string",
          "enum": [
            "LOCAL_USER",
            "LOCAL_GROUP",
            "NFS_GID",
            "NFS_UID",
            "SMB_SID",
            "INTERNAL",
            "QUMULO_OPERATOR",
            "QUMULO_SUPPORT"
          ],
          "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
        },
        "id_value": {
          "description": "id_value",
          "type": "string"
        }
      }
    }
  },
  "fields_to_present_as_32_bit": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "FILE_IDS",
        "FILE_SIZES",
        "FS_SIZE"
      ],
      "description": "Specify which NFS3 result values should be 32-bit sanitized
on this export. Has no effect on exports used over NFS4.: \n * `FILE_IDS` - Hash hig
h file ids to 32 bits., \n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in
32 bits., \n * `FS_SIZE` - Clamp available, used and total space reported for the FS
to 4GiB."
    }
  }
}

```

```
}  
  }  
}
```

nfs/exports/{export_id}

Endpoint

/v3/nfs/exports/{export_id}

GET

[preview] This method retrieves the specified NFS export. Refer to the 'Modify NFS Export' method for a description of the returned fields.

Parameters

Name	Description	Required
export_id	The unique NFS export ID.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_nfs_export_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    },
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the NFS export is a part of",
      "type": "number"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",

```

```

    "type": "string"
  },
  "description": {
    "description": "Description of this NFS export",
    "type": "string"
  },
  "restrictions": {
    "type": "array",
    "items": {
      "description": "An array of NFS host restrictions.",
      "type": "object",
      "properties": {
        "host_restrictions": {
          "type": "array",
          "items": {
            "description": "The list of hosts allowed to connect",
            "type": "string"
          }
        }
      }
    },
    "require_privileged_port": {
      "description": "Require that hosts use a privileged port to use this export.",
      "type": "boolean"
    },
    "read_only": {
      "description": "Sets the NFS export to read-only",
      "type": "boolean"
    },
    "required_authentication_mode": {
      "type": "string",
      "enum": [
        "AUTHENTICATION_MODE_NONE",
        "AUTHENTICATION_MODE_KRB5",
        "AUTHENTICATION_MODE_KRB5I",
        "AUTHENTICATION_MODE_KRB5P"
      ],
      "description": "The authentication mode hosts are required to authenticate with.\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the krb5 security flavor.,\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticate with the krb5i security flavor.,\n * `AUTHENTICATION_MODE_KRB5P` - Require users to authenticate with the krb5p security flavor.,\n * `AUTHENTICATION_MODE_NONE` - Allow unauthenticated access."
    },
    "user_mapping": {
      "type": "string",
      "enum": [

```

```

        "NFS_MAP_NONE",
        "NFS_MAP_ROOT",
        "NFS_MAP_ALL"
    ],
    "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL` - Map all users.,\n * `NFS_MAP_NONE` - Do not map users.,\n * `NFS_MAP_ROOT` - Map root user (uid 0).",
    },
    "map_to_user": {
        "description": "An identity object representing a local user or an NFS user to map (see /users). If map_to_user is an NFS user, then map_to_group with an NFS gid must be given.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",
                    "INTERNAL",
                    "QUMULO_OPERATOR",
                    "QUMULO_SUPPORT"
                ],
                "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID",
            },
            "id_value": {
                "description": "id_value",
                "type": "string"
            }
        }
    },
    "map_to_group": {
        "description": "An identity object representing an NFS group. If given, map_to_user should be an NFS user.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",

```

```

        "LOCAL_GROUP",
        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU\nP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U\nID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL\nO_SUPPORT,\n * `SMB_SID` - SMB_SID"
},
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
}
},
    "fields_to_present_as_32_bit": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "FILE_IDS",
                "FILE_SIZES",
                "FS_SIZE"
            ]
        },
        "description": "Specify which NFS3 result values should be 32-bit sanitized\non this export. Has no effect on exports used over NFS4.: \n * `FILE_IDS` - Hash hig\nh file ids to 32 bits.,\n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in\n32 bits.,\n * `FS_SIZE` - Clamp available, used and total space reported for the FS\nto 4GiB."
    }
}
}
}
}

```

PUT

[preview] This method sets all attributes of an NFS export.

Parameters

Name	Description	Required
<code>export_id</code>	The unique NFS export ID.	Yes
<code>allow-fs-path-create</code>	Specifies whether the file system path can be created if it does not already exist.	No
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_nfs_export_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    },
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the NFS export is a part of",
      "type": "number"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",
      "type": "string"
    },
    "description": {
      "description": "Description of this NFS export",
      "type": "string"
    },
    "restrictions": {
      "type": "array",
      "items": {
        "description": "An array of NFS host restrictions.",
        "type": "object",
        "properties": {
          "host_restrictions": {
```



```

    "type": "array",
    "items": {
      "description": "The list of hosts allowed to connect",
      "type": "string"
    }
  },
  "require_privileged_port": {
    "description": "Require that hosts use a privileged port to use this exp
ort.",
    "type": "boolean"
  },
  "read_only": {
    "description": "Sets the NFS export to read-only",
    "type": "boolean"
  },
  "required_authentication_mode": {
    "type": "string",
    "enum": [
      "AUTHENTICATION_MODE_NONE",
      "AUTHENTICATION_MODE_KRB5",
      "AUTHENTICATION_MODE_KRB5I",
      "AUTHENTICATION_MODE_KRB5P"
    ],
    "description": "The authentication mode hosts are required to authentica
te with.\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the kr
b5 security flavor.,\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authentica
te with the krb5i security flavor.,\n * `AUTHENTICATION_MODE_KRB5P` - Require users t
o authenticate with the krb5p security flavor.,\n * `AUTHENTICATION_MODE_NONE` - All
ow unauthenticated access."
  },
  "user_mapping": {
    "type": "string",
    "enum": [
      "NFS_MAP_NONE",
      "NFS_MAP_ROOT",
      "NFS_MAP_ALL"
    ],
    "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL`
- Map all users.,\n * `NFS_MAP_NONE` - Do not map users.,\n * `NFS_MAP_ROOT` - Map r
oot user (uid 0).",
  },
  "map_to_user": {
    "description": "An identity object representing a local user or an NFS u
ser to map (see /users). If map_to_user is an NFS user, then map_to_group with an NF
S gid must be given.",
    "type": "object",

```

```

    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ],
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU\nP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U\nID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL\nO_SUPPORT,\n * `SMB_SID` - SMB_SID"
      },
      "id_value": {
        "description": "id_value",
        "type": "string"
      }
    }
  },
  "map_to_group": {
    "description": "An identity object representing an NFS group. If given,\nmap_to_user should be an NFS user.",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ],
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU\nP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U\nID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL\nO_SUPPORT,\n * `SMB_SID` - SMB_SID"
      }
    },

```

```

        "id_value": {
            "description": "id_value",
            "type": "string"
        }
    }
}
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "FILE_IDS",
            "FILE_SIZES",
            "FS_SIZE"
        ],
        "description": "Specify which NFS3 result values should be 32-bit sanitized
on this export. Has no effect on exports used over NFS4.:
\n * `FILE_IDS` - Hash high file ids to 32 bits.
\n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in 32 bits.
\n * `FS_SIZE` - Clamp available, used and total space reported for the FS to 4GiB."
    }
}
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
    "description": "api_nfs_export_v3",
    "type": "object",
    "properties": {
        "id": {
            "description": "The unique ID of the NFS export",
            "type": "string"
        }
    }
}

```

```

},
"export_path": {
  "description": "The NFS export path",
  "type": "string"
},
"tenant_id": {
  "description": "The tenant ID of the tenant that the NFS export is a part of",
  "type": "number"
},
"fs_path": {
  "description": "The filesystem path of the exported directory",
  "type": "string"
},
"description": {
  "description": "Description of this NFS export",
  "type": "string"
},
"restrictions": {
  "type": "array",
  "items": {
    "description": "An array of NFS host restrictions.",
    "type": "object",
    "properties": {
      "host_restrictions": {
        "type": "array",
        "items": {
          "description": "The list of hosts allowed to connect",
          "type": "string"
        }
      },
      "require_privileged_port": {
        "description": "Require that hosts use a privileged port to use this export.",
        "type": "boolean"
      },
      "read_only": {
        "description": "Sets the NFS export to read-only",
        "type": "boolean"
      },
      "required_authentication_mode": {
        "type": "string",
        "enum": [
          "AUTHENTICATION_MODE_NONE",
          "AUTHENTICATION_MODE_KRB5",
          "AUTHENTICATION_MODE_KRB5I",
          "AUTHENTICATION_MODE_KRB5P"
        ]
      }
    }
  }
}

```

```

    ],
    "description": "The authentication mode hosts are required to authenticat
te with.:\\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the kr
b5 security flavor.,\\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticat
e with the krb5i security flavor.,\\n * `AUTHENTICATION_MODE_KRB5P` - Require users t
o authenticate with the krb5p security flavor.,\\n * `AUTHENTICATION_MODE_NONE` - All
ow unauthenticated access."
  },
  "user_mapping": {
    "type": "string",
    "enum": [
      "NFS_MAP_NONE",
      "NFS_MAP_ROOT",
      "NFS_MAP_ALL"
    ],
    "description": "NFS user mapping (squashing) support:\\n * `NFS_MAP_ALL`
- Map all users.,\\n * `NFS_MAP_NONE` - Do not map users.,\\n * `NFS_MAP_ROOT` - Map r
oot user (uid 0).",
  },
  "map_to_user": {
    "description": "An identity object representing a local user or an NFS u
ser to map (see /users). If map_to_user is an NFS user, then map_to_group with an NF
S gid must be given.",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ],
        "description": "id_type:\\n * `INTERNAL` - INTERNAL,\\n * `LOCAL_GROU
P` - LOCAL_GROUP,\\n * `LOCAL_USER` - LOCAL_USER,\\n * `NFS_GID` - NFS_GID,\\n * `NFS_U
ID` - NFS_UID,\\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\\n * `SMB_SID` - SMB_SID",
      },
      "id_value": {
        "description": "id_value",
        "type": "string"
      }
    }
  }
}

```

```

    }
  },
  "map_to_group": {
    "description": "An identity object representing an NFS group. If given,
map_to_user should be an NFS user.",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ],
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
      },
      "id_value": {
        "description": "id_value",
        "type": "string"
      }
    }
  }
}
},
"fields_to_present_as_32_bit": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "FILE_IDS",
      "FILE_SIZES",
      "FS_SIZE"
    ],
    "description": "Specify which NFS3 result values should be 32-bit sanitized
on this export. Has no effect on exports used over NFS4.: \n * `FILE_IDS` - Hash hig
h file ids to 32 bits., \n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in
32 bits., \n * `FS_SIZE` - Clamp available, used and total space reported for the FS

```

```
to 4GiB."
    }
  }
}
```

DELETE

[preview] This method deletes an NFS export.

Parameters

Name	Description	Required
<code>export_id</code>	The unique NFS export ID.	Yes
<code>If-Match</code>	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

[preview] This method modifies individual attributes of an NFS export.

Parameters

Name	Description	Required
<code>export_id</code>	The unique NFS export ID.	Yes
<code>allow-fs-path-create</code>	Specifies whether the file system path can be created if it does not already exist.	No
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_nfs_export_patch_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    },
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the NFS export is a part of",
      "type": "number"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",
      "type": "string"
    },
    "description": {
      "description": "Description of this NFS export",
      "type": "string"
    },
    "restrictions": {
      "type": "array",
      "items": {
        "description": "An array of NFS host restrictions.",
        "type": "object",
        "properties": {
          "host_restrictions": {
            "type": "array",
            "items": {
              "description": "The list of hosts allowed to connect",
              "type": "string"
            }
          },
          "require_privileged_port": {
            "description": "Require that hosts use a privileged port to use this export.",
            "type": "boolean"
          },
          "read_only": {
```



```

    "description": "Sets the NFS export to read-only",
    "type": "boolean"
  },
  "required_authentication_mode": {
    "type": "string",
    "enum": [
      "AUTHENTICATION_MODE_NONE",
      "AUTHENTICATION_MODE_KRB5",
      "AUTHENTICATION_MODE_KRB5I",
      "AUTHENTICATION_MODE_KRB5P"
    ],
    "description": "The authentication mode hosts are required to authenticat
te with.:\\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the kr
b5 security flavor.,\\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticat
e with the krb5i security flavor.,\\n * `AUTHENTICATION_MODE_KRB5P` - Require users t
o authenticate with the krb5p security flavor.,\\n * `AUTHENTICATION_MODE_NONE` - All
ow unauthenticated access."
  },
  "user_mapping": {
    "type": "string",
    "enum": [
      "NFS_MAP_NONE",
      "NFS_MAP_ROOT",
      "NFS_MAP_ALL"
    ],
    "description": "NFS user mapping (squashing) support:\\n * `NFS_MAP_ALL`
- Map all users.,\\n * `NFS_MAP_NONE` - Do not map users.,\\n * `NFS_MAP_ROOT` - Map r
oot user (uid 0).",
  },
  "map_to_user": {
    "description": "An identity object representing a local user or an NFS u
ser to map (see /users). If map_to_user is an NFS user, then map_to_group with an NF
S gid must be given.",
    "type": "object",
    "properties": {
      "id_type": {
        "type": "string",
        "enum": [
          "LOCAL_USER",
          "LOCAL_GROUP",
          "NFS_GID",
          "NFS_UID",
          "SMB_SID",
          "INTERNAL",
          "QUMULO_OPERATOR",
          "QUMULO_SUPPORT"
        ]
      }
    }
  }
}

```

```

        ],
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
},
"map_to_group": {
    "description": "An identity object representing an NFS group. If given,
map_to_user should be an NFS user.",
    "type": "object",
    "properties": {
        "id_type": {
            "type": "string",
            "enum": [
                "LOCAL_USER",
                "LOCAL_GROUP",
                "NFS_GID",
                "NFS_UID",
                "SMB_SID",
                "INTERNAL",
                "QUMULO_OPERATOR",
                "QUMULO_SUPPORT"
            ]
        },
        "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU
P` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U
ID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL
O_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {

```

```

    "type": "string",
    "enum": [
        "FILE_IDS",
        "FILE_SIZES",
        "FS_SIZE"
    ],
    "description": "Specify which NFS3 result values should be 32-bit sanitized
on this export. Has no effect on exports used over NFS4.:\\n * `FILE_IDS` - Hash hig
h file ids to 32 bits.,\\n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in
32 bits.,\\n * `FS_SIZE` - Clamp available, used and total space reported for the FS
to 4GiB."
    }
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_nfs_export_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the NFS export",
      "type": "string"
    },
    "export_path": {
      "description": "The NFS export path",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the NFS export is a part of",
      "type": "number"
    },
    "fs_path": {
      "description": "The filesystem path of the exported directory",
      "type": "string"
    }
  }
}

```

```

},
"description": {
  "description": "Description of this NFS export",
  "type": "string"
},
"restrictions": {
  "type": "array",
  "items": {
    "description": "An array of NFS host restrictions.",
    "type": "object",
    "properties": {
      "host_restrictions": {
        "type": "array",
        "items": {
          "description": "The list of hosts allowed to connect",
          "type": "string"
        }
      }
    }
  },
  "require_privileged_port": {
    "description": "Require that hosts use a privileged port to use this export.",
    "type": "boolean"
  },
  "read_only": {
    "description": "Sets the NFS export to read-only",
    "type": "boolean"
  },
  "required_authentication_mode": {
    "type": "string",
    "enum": [
      "AUTHENTICATION_MODE_NONE",
      "AUTHENTICATION_MODE_KRB5",
      "AUTHENTICATION_MODE_KRB5I",
      "AUTHENTICATION_MODE_KRB5P"
    ],
    "description": "The authentication mode hosts are required to authenticate with.\n * `AUTHENTICATION_MODE_KRB5` - Require users to authenticate with the krb5 security flavor.\n * `AUTHENTICATION_MODE_KRB5I` - Require users to authenticate with the krb5i security flavor.\n * `AUTHENTICATION_MODE_KRB5P` - Require users to authenticate with the krb5p security flavor.\n * `AUTHENTICATION_MODE_NONE` - Allow unauthenticated access."
  },
  "user_mapping": {
    "type": "string",
    "enum": [
      "NFS_MAP_NONE",

```

```

        "NFS_MAP_ROOT",
        "NFS_MAP_ALL"
    ],
    "description": "NFS user mapping (squashing) support:\n * `NFS_MAP_ALL` - Map all users.,\n * `NFS_MAP_NONE` - Do not map users.,\n * `NFS_MAP_ROOT` - Map root user (uid 0).",
    },
    "map_to_user": {
        "description": "An identity object representing a local user or an NFS user to map (see /users). If map_to_user is an NFS user, then map_to_group with an NFS gid must be given.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",
                    "NFS_GID",
                    "NFS_UID",
                    "SMB_SID",
                    "INTERNAL",
                    "QUMULO_OPERATOR",
                    "QUMULO_SUPPORT"
                ],
                "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROUP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_UID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMULO_SUPPORT,\n * `SMB_SID` - SMB_SID",
            },
            "id_value": {
                "description": "id_value",
                "type": "string"
            }
        }
    },
    "map_to_group": {
        "description": "An identity object representing an NFS group. If given, map_to_user should be an NFS user.",
        "type": "object",
        "properties": {
            "id_type": {
                "type": "string",
                "enum": [
                    "LOCAL_USER",
                    "LOCAL_GROUP",

```

```

        "NFS_GID",
        "NFS_UID",
        "SMB_SID",
        "INTERNAL",
        "QUMULO_OPERATOR",
        "QUMULO_SUPPORT"
    ],
    "description": "id_type:\n * `INTERNAL` - INTERNAL,\n * `LOCAL_GROU\nP` - LOCAL_GROUP,\n * `LOCAL_USER` - LOCAL_USER,\n * `NFS_GID` - NFS_GID,\n * `NFS_U\nID` - NFS_UID,\n * `QUMULO_OPERATOR` - QUMULO_OPERATOR,\n * `QUMULO_SUPPORT` - QUMUL\nO_SUPPORT,\n * `SMB_SID` - SMB_SID"
    },
    "id_value": {
        "description": "id_value",
        "type": "string"
    }
}
}
}
},
"fields_to_present_as_32_bit": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "FILE_IDS",
            "FILE_SIZES",
            "FS_SIZE"
        ]
    },
    "description": "Specify which NFS3 result values should be 32-bit sanitized\non this export. Has no effect on exports used over NFS4.: \n * `FILE_IDS` - Hash hig\nh file ids to 32 bits., \n * `FILE_SIZES` - Clamp large file sizes to 4GiB to fit in\n32 bits., \n * `FS_SIZE` - Clamp available, used and total space reported for the FS\nto 4GiB."
}
}
}
}

```

multitenancy/nfs/global-settings

Endpoint

/v1/multitenancy/nfs/global-settings

GET

[preview] Retrieve global NFS configuration.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",

```

```

    "type": "boolean"
  },
  "idmap_domain": {
    "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
    "type": "string"
  }
}
}

```

PUT

[preview] Set global NFS configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {

```



```

    "description": "Whether AUTH_SYS is enabled",
    "type": "boolean"
  },
  "idmap_domain": {
    "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
    "type": "string"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",
      "type": "boolean"
    }
  }
}

```

```

    "idmap_domain": {
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
      "type": "string"
    }
  }
}

```

PATCH

[preview] Modify global NFS configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_nfs_settings_patch",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",
      "type": "boolean"
    }
  }
}

```

```

    },
    "idmap_domain": {
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",
      "type": "boolean"
    },
    "idmap_domain": {
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution."
    }
  }
}

```

```
e must match what idmapd on the clients expects for correct name resolution.",  
    "type": "string"  
  }  
}  
}
```

multitenancy/nfs/settings/

Endpoint

/v1/multitenancy/nfs/settings/

GET

[preview] Retrieve all tenant-specific NFS configurations.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_nfs_settings_map",
  "type": "object",
  "properties": {},
  "additionalProperties": {
    "description": "api_nfs_settings_map value",
    "type": "object",
    "properties": {
      "v4_enabled": {
        "description": "Whether NFSv4 is enabled",
        "type": "boolean"
      },
      "krb5_enabled": {
        "description": "Whether Kerberos5 is enabled",
        "type": "boolean"
      },
      "krb5p_enabled": {
        "description": "Whether Kerberos5p (privacy) is enabled",
        "type": "boolean"
      },
      "krb5i_enabled": {
        "description": "Whether Kerberos5i (integrity) is enabled",

```

```
    "type": "boolean"
  },
  "auth_sys_enabled": {
    "description": "Whether AUTH_SYS is enabled",
    "type": "boolean"
  },
  "idmap_domain": {
    "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
    "type": "string"
  }
}
}
```

multitenancy/nfs/settings/{id}

Endpoint

/v1/multitenancy/nfs/settings/{id}

GET

[preview] Retrieve current tenant-specific NFS configuration.

Parameters

Name	Description	Required
id	The tenant ID of the NFS settings.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    }
  }
}
```

```

    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",
      "type": "boolean"
    },
    "idmap_domain": {
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
      "type": "string"
    }
  }
}

```

PUT

[preview] Set current tenant-specific NFS configuration.

Parameters

Name	Description	Required
<code>id</code>	The tenant ID of the NFS settings.	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```

{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    }
  },
}

```



```

"krb5i_enabled": {
  "description": "Whether Kerberos5i (integrity) is enabled",
  "type": "boolean"
},
"auth_sys_enabled": {
  "description": "Whether AUTH_SYS is enabled",
  "type": "boolean"
},
"idmap_domain": {
  "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
  "type": "string"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    }
  }
}

```

```

    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",
      "type": "boolean"
    },
    "idmap_domain": {
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
      "type": "string"
    }
  }
}

```

DELETE

[preview] Delete current NFS configuration, restoring the global settings for this tenant.

Parameters

Name	Description	Required
<code>id</code>	The tenant ID of the NFS settings.	Yes
<code>If-Match</code>	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

[preview] Modify current tenant-specific NFS configuration.

Parameters

Name	Description	Required
<code>id</code>	The tenant ID of the NFS settings.	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_nfs_settings_patch",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",
      "type": "boolean"
    },
    "idmap_domain": {
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_nfs_settings",
  "type": "object",
  "properties": {
    "v4_enabled": {
      "description": "Whether NFSv4 is enabled",
      "type": "boolean"
    },
    "krb5_enabled": {
      "description": "Whether Kerberos5 is enabled",
      "type": "boolean"
    },
    "krb5p_enabled": {
      "description": "Whether Kerberos5p (privacy) is enabled",
      "type": "boolean"
    },
    "krb5i_enabled": {
      "description": "Whether Kerberos5i (integrity) is enabled",
      "type": "boolean"
    },
    "auth_sys_enabled": {
      "description": "Whether AUTH_SYS is enabled",
      "type": "boolean"
    },
    "idmap_domain": {
      "description": "The domain used for mapping NFSv4 string identities. The value must match what idmapd on the clients expects for correct name resolution.",
      "type": "string"
    }
  }
}
```

network/floating-ip-allocation

Endpoint

/v1/network/floating-ip-allocation

GET

Returns floating IPs per node distribution based on the current network configuration. Returns status code 400 if the server is in DHCP mode.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_node_floating_ips",
    "type": "object",
    "properties": {
      "id": {
        "description": "Node Id",
        "type": "number"
      },
      "floating_addresses": {
        "type": "array",
        "items": {
          "description": "Floating IPv4 or IPv6 addresses in 0.0.0.0 or :: format",
          "type": "string"
        }
      }
    }
  }
}
```

network/settings

Endpoint

/v1/network/settings

GET

Get global networking configuration for the whole cluster. This API is deprecated in favor of /v2/network/interfaces/ and /v2/network/interfaces/1/networks/.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_cluster_network_config_v1",
  "type": "object",
  "properties": {
    "assigned_by": {
      "type": "string",
      "enum": [
        "DHCP",
        "STATIC",
        "LINK_LOCAL",
        "HOST"
      ],
      "description": "How to assign IP address, either DHCP or STATIC:\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
    },
    "ip_ranges": {
      "type": "array",
      "items": {
        "description": "(STATIC only) Comma-separated list of IP ranges",
        "type": "string"
      }
    }
  }
}
```

```

    }
  },
  "floating_ip_ranges": {
    "type": "array",
    "items": {
      "description": "(STATIC only) Comma-separated list of floating IP ranges",
      "type": "string"
    }
  },
  "netmask": {
    "description": "(STATIC only) The IPv4 or IPv6 netmask in 0.0.0.0 or :: format, or the IPv4 or IPv6 subnet CIDR",
    "type": "string"
  },
  "gateway": {
    "description": "(STATIC only) The IPv4 gateway in 0.0.0.0 format",
    "type": "string"
  },
  "gateway_ipv6": {
    "description": "(STATIC only) The IPv6 gateway in :: format",
    "type": "string"
  },
  "dns_servers": {
    "type": "array",
    "items": {
      "description": "(STATIC only) The list of DNS servers",
      "type": "string"
    }
  },
  "dns_search_domains": {
    "type": "array",
    "items": {
      "description": "(STATIC only) The list of DNS search domains",
      "type": "string"
    }
  },
  "mtu": {
    "description": "(STATIC only) The maximum transmission unit (MTU) in bytes",
    "type": "number"
  },
  "bonding_mode": {
    "type": "string",
    "enum": [
      "ACTIVE_BACKUP",
      "IEEE_8023AD"
    ]
  },

```

```

    "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD), if the i
nterface is bonded.:\\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n * `IEEE_802
3AD` - BONDING_MODE_IEEE_8023AD"
  }
}
}

```

PUT

Change networking configuration for the whole cluster. This API is deprecated in favor of `/v2/network/interfaces/` and `/v2/network/interfaces/1/networks/`.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_cluster_network_config_v1",
  "type": "object",
  "properties": {
    "assigned_by": {
      "type": "string",
      "enum": [
        "DHCP",
        "STATIC",
        "LINK_LOCAL",
        "HOST"
      ],
      "description": "How to assign IP address, either DHCP or STATIC:\\n * `DHCP` -
NETWORK_ASSIGNED_BY_DHCP,\\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\\n * `LINK_LOCAL` -
NETWORK_ASSIGNED_BY_LINK_LOCAL,\\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
    },
    "ip_ranges": {
      "type": "array",
      "items": {
        "description": "(STATIC only) Comma-separated list of IP ranges",
        "type": "string"
      }
    }
  },
}

```



```

"floating_ip_ranges": {
  "type": "array",
  "items": {
    "description": "(STATIC only) Comma-separated list of floating IP ranges",
    "type": "string"
  }
},
"netmask": {
  "description": "(STATIC only) The IPv4 or IPv6 netmask in 0.0.0.0 or :: format, or the IPv4 or IPv6 subnet CIDR",
  "type": "string"
},
"gateway": {
  "description": "(STATIC only) The IPv4 gateway in 0.0.0.0 format",
  "type": "string"
},
"gateway_ipv6": {
  "description": "(STATIC only) The IPv6 gateway in :: format",
  "type": "string"
},
"dns_servers": {
  "type": "array",
  "items": {
    "description": "(STATIC only) The list of DNS servers",
    "type": "string"
  }
},
"dns_search_domains": {
  "type": "array",
  "items": {
    "description": "(STATIC only) The list of DNS search domains",
    "type": "string"
  }
},
"mtu": {
  "description": "(STATIC only) The maximum transmission unit (MTU) in bytes",
  "type": "number"
},
"bonding_mode": {
  "type": "string",
  "enum": [
    "ACTIVE_BACKUP",
    "IEEE_8023AD"
  ],
  "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD), if the interface is bonded.: \n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP, \n * `IEEE_802

```

```

3AD` - BONDING_MODE_IEEE_8023AD"
    }
  }
}

```

Response

Codes

Code	Description
202	Return value on success

PATCH

Update networking configuration for the whole cluster. This API is deprecated in favor of `/v2/network/interfaces/` and `/v2/network/interfaces/1/networks/`.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "api_cluster_network_config_v1",
  "type": "object",
  "properties": {
    "assigned_by": {
      "type": "string",
      "enum": [
        "DHCP",
        "STATIC",
        "LINK_LOCAL",
        "HOST"
      ],
    },
    "description": "How to assign IP address, either DHCP or STATIC:\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
  },
  "ip_ranges": {
    "type": "array",
    "items": {
      "description": "(STATIC only) Comma-separated list of IP ranges",
    },
  },
}

```

```

        "type": "string"
    },
    "floating_ip_ranges": {
        "type": "array",
        "items": {
            "description": "(STATIC only) Comma-separated list of floating IP ranges",
            "type": "string"
        }
    },
    "netmask": {
        "description": "(STATIC only) The IPv4 or IPv6 netmask in 0.0.0.0 or :: format, or the IPv4 or IPv6 subnet CIDR",
        "type": "string"
    },
    "gateway": {
        "description": "(STATIC only) The IPv4 gateway in 0.0.0.0 format",
        "type": "string"
    },
    "gateway_ipv6": {
        "description": "(STATIC only) The IPv6 gateway in :: format",
        "type": "string"
    },
    "dns_servers": {
        "type": "array",
        "items": {
            "description": "(STATIC only) The list of DNS servers",
            "type": "string"
        }
    },
    "dns_search_domains": {
        "type": "array",
        "items": {
            "description": "(STATIC only) The list of DNS search domains",
            "type": "string"
        }
    },
    "mtu": {
        "description": "(STATIC only) The maximum transmission unit (MTU) in bytes",
        "type": "number"
    },
    "bonding_mode": {
        "type": "string",
        "enum": [
            "ACTIVE_BACKUP",
            "IEEE_8023AD"
        ]
    }
}

```

```
    ],  
    "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD), if the i  
nterface is bonded.:\\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n * `IEEE_802  
3AD` - BONDING_MODE_IEEE_8023AD"  
  }  
}  
}
```

Response

Codes

Code	Description
202	Return value on success

network/static-ip-allocation

Endpoint

`/v1/network/static-ip-allocation`

GET

Returns total/used/available numbers of IPs based on the current network configuration. Returns status code 400 if the server is in DHCP mode unless the try/floating query parameters are provided.

Parameters

Name	Description	Required
<code>netmask</code>	Netmask to apply to the try and/or floating range arguments, overriding whatever is currently configured. Required if network is currently in DHCP mode.	No
<code>try</code>	Comma-separated static IP range(s) to try. Defaults to currently configured static IP range.	No
<code>floating</code>	Comma-separated floating IP range(s) to try. Defaults to currently configured floating IP range.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_static_ip_allocation_summary",
  "type": "object",
  "properties": {
    "total_ips": {
      "description": "Total number of IP addresses in the given IP ranges",
      "type": "number"
    },
    "used_ips": {
```

```
    "description": "Number of IP addresses currently assigned to nodes",
    "type": "number"
  },
  "available_ips": {
    "description": "Number of IP addresses available; can be negative",
    "type": "number"
  },
  "total_floating_ips": {
    "description": "Total floating ips",
    "type": "number"
  },
  "surplus_floating_ips": {
    "description": "Floating ip count too small or large",
    "type": "number"
  }
}
```

network/status/

Endpoint

/v1/network/status/

GET

This method lists the network status of all nodes. This API is deprecated in favor of /v2/network/interfaces/1/status/.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_network_status_response",
    "type": "object",
    "properties": {
      "id": {
        "description": "Node ID",
        "type": "number"
      },
      "node_name": {
        "description": "Node name",
        "type": "string"
      },
      "update_status": {
        "type": "string",
        "enum": [
          "CHANGES_APPLIED",
          "CHANGES_PENDING",
          "UNAVAILABLE"
        ]
      }
    }
  }
}
```

```

        "description": "update_status:\n * `CHANGES_APPLIED` - UPDATE_STATUS_CHANGE
S_APPLIED,\n * `CHANGES_PENDING` - UPDATE_STATUS_CHANGES_PENDING,\n * `UNAVAILABLE`
- UPDATE_STATUS_UNAVAILABLE"
    },
    "network_status": {
        "description": "network_status",
        "type": "object",
        "properties": {
            "id": {
                "description": "Node Id",
                "type": "number"
            },
            "assigned_by": {
                "type": "string",
                "enum": [
                    "DHCP",
                    "STATIC",
                    "LINK_LOCAL",
                    "HOST"
                ],
                "description": "How to assign IP address, either DHCP or STATIC:\n * `DH
CP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOC
AL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
            },
            "address": {
                "description": "The IPv4 or IPv6 address in 0.0.0.0 or :: format",
                "type": "string"
            },
            "floating_addresses": {
                "type": "array",
                "items": {
                    "description": "Floating IPv4 or IPv6 addresses in 0.0.0.0 or :: forma
t",
                    "type": "string"
                }
            },
            "netmask": {
                "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: format, or th
e IPv4 or IPv6 subnet CIDR",
                "type": "string"
            },
            "gateway": {
                "description": "The IPv4 gateway in 0.0.0.0 format",
                "type": "string"
            },
            "gateway_ipv6": {

```



```

        "description": "The IPv6 gateway in :: format",
        "type": "string"
    },
    "dns_servers": {
        "type": "array",
        "items": {
            "description": "The list of DNS servers",
            "type": "string"
        }
    },
    "dns_search_domains": {
        "type": "array",
        "items": {
            "description": "The list of DNS search domains",
            "type": "string"
        }
    },
    "mtu": {
        "description": "The maximum transmission unit in bytes",
        "type": "number"
    },
    "bonding_mode": {
        "type": "string",
        "enum": [
            "ACTIVE_BACKUP",
            "IEEE_8023AD"
        ],
        "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD), if the interface is bonded.\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\n * `IEEE_8023AD` - BONDING_MODE_8023AD"
    },
    "network_details": {
        "description": "network_details",
        "type": "object",
        "properties": {
            "speed": {
                "description": "Network card speed in Mbps.",
                "type": "number"
            },
            "bytes_sent": {
                "description": "Bytes sent over the interface.",
                "type": "string"
            },
            "bytes_received": {

```


network/status/{id}

Endpoint

/v1/network/status/{id}

GET

This method retrieves the network configuration of the underlying system, including DHCP configuration, and status of any pending changes. This API is deprecated in favor of /v2/network/interfaces/1/status/{node_id}.

Parameters

Name	Description	Required
id	The unique ID of the node	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_network_status_response",
  "type": "object",
  "properties": {
    "id": {
      "description": "Node ID",
      "type": "number"
    },
    "node_name": {
      "description": "Node name",
      "type": "string"
    },
    "update_status": {
      "type": "string",
      "enum": [
        "CHANGES_APPLIED",
        "CHANGES_PENDING"
      ]
    }
  }
}
```

```

        "UNAVAILABLE"
    ],
    "description": "update_status:\n * `CHANGES_APPLIED` - UPDATE_STATUS_CHANGES_A
PPLIED,\n * `CHANGES_PENDING` - UPDATE_STATUS_CHANGES_PENDING,\n * `UNAVAILABLE` - U
PDATE_STATUS_UNAVAILABLE"
},
"network_status": {
    "description": "network_status",
    "type": "object",
    "properties": {
        "id": {
            "description": "Node Id",
            "type": "number"
        },
        "assigned_by": {
            "type": "string",
            "enum": [
                "DHCP",
                "STATIC",
                "LINK_LOCAL",
                "HOST"
            ],
            "description": "How to assign IP address, either DHCP or STATIC:\n * `DHC
P` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCA
L` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
        },
        "address": {
            "description": "The IPv4 or IPv6 address in 0.0.0.0 or :: format",
            "type": "string"
        },
        "floating_addresses": {
            "type": "array",
            "items": {
                "description": "Floating IPv4 or IPv6 addresses in 0.0.0.0 or :: forma
t",
                "type": "string"
            }
        },
        "netmask": {
            "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: format, or the I
Pv4 or IPv6 subnet CIDR",
            "type": "string"
        },
        "gateway": {
            "description": "The IPv4 gateway in 0.0.0.0 format",
            "type": "string"
        }
    }
}

```

```

},
"gateway_ipv6": {
  "description": "The IPv6 gateway in :: format",
  "type": "string"
},
"dns_servers": {
  "type": "array",
  "items": {
    "description": "The list of DNS servers",
    "type": "string"
  }
},
"dns_search_domains": {
  "type": "array",
  "items": {
    "description": "The list of DNS search domains",
    "type": "string"
  }
},
"mtu": {
  "description": "The maximum transmission unit in bytes",
  "type": "number"
},
"bonding_mode": {
  "type": "string",
  "enum": [
    "ACTIVE_BACKUP",
    "IEEE_8023AD"
  ],
  "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD), if the interface is bonded.\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\n * `IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
},
},
"network_details": {
  "description": "network_details",
  "type": "object",
  "properties": {
    "speed": {
      "description": "Network card speed in Mbps.",
      "type": "number"
    },
    "bytes_sent": {
      "description": "Bytes sent over the interface.",
      "type": "string"
    }
  }
}

```

```

    },
    "bytes_received": {
      "description": "Bytes received over the interface.",
      "type": "string"
    },
    },
    "cable_status": {
      "type": "string",
      "enum": [
        "CONNECTED",
        "DISCONNECTED",
        "UNKNOWN"
      ],
      "description": "Whether network card is connected via cable.:\\n * `CONNECTED` - NETWORK_CABLE_CONNECTED,\\n * `DISCONNECTED` - NETWORK_CABLE_DISCONNECTED,\\n * `UNKNOWN` - NETWORK_CABLE_UNKNOWN"
    },
    },
    "interface_status": {
      "type": "string",
      "enum": [
        "UP",
        "DOWN",
        "MISSING",
        "UNKNOWN",
        "NOTPRESENT",
        "LOWERLAYERDOWN",
        "TESTING",
        "DORMANT"
      ],
      "description": "Status of interface connection.:\\n * `DORMANT` - NETWORK_INTERFACE_DORMANT,\\n * `DOWN` - NETWORK_INTERFACE_DOWN,\\n * `LOWERLAYERDOWN` - NETWORK_INTERFACE_LOWER_LAYER_DOWN,\\n * `MISSING` - NETWORK_INTERFACE_MISSING,\\n * `NOTPRESENT` - NETWORK_INTERFACE_NOT_PRESENT,\\n * `TESTING` - NETWORK_INTERFACE_TESTING,\\n * `UNKNOWN` - NETWORK_INTERFACE_UNKNOWN,\\n * `UP` - NETWORK_INTERFACE_UP"
    },
    },
    "mac_address": {
      "description": "MAC address.",
      "type": "string"
    },
    },
    "timestamp": {
      "description": "UNIX epoch timestamp for when the network status was sampled.",
      "type": "string"
    },
  }
}
}

```

}

network/connections/

Endpoint

/v2/network/connections/

GET

Return a list of NFS and SMB protocol connections to each node

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_connection_list_data",
    "type": "object",
    "properties": {
      "id": {
        "description": "id",
        "type": "number"
      },
      "connections": {
        "type": "array",
        "items": {
          "description": "connections",
          "type": "object",
          "properties": {
            "type": {
              "type": "string",
              "enum": [
                "CONNECTION_TYPE_NFS",
                "CONNECTION_TYPE_SMB",
                "CONNECTION_TYPE_FTP"
              ]
            }
          }
        }
      }
    }
  }
}
```


network/interfaces/

Endpoint

/v2/network/interfaces/

GET

Get configurations of all interfaces for the whole cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_interface_config",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier for this interface configuration",
        "type": "number"
      },
      "name": {
        "description": "Name of the configured interface i.e. bond0",
        "type": "string"
      },
      "default_gateway": {
        "description": "Default IPv4 gateway on which all traffic generated from nodes is sent out on this interface",
        "type": "string"
      },
      "default_gateway_ipv6": {
        "description": "Default IPv6 gateway on which all traffic generated from nodes is sent out on this interface",

```

```

        "type": "string"
    },
    "bonding_mode": {
        "type": "string",
        "enum": [
            "ACTIVE_BACKUP",
            "IEEE_8023AD"
        ],
        "description": "Linux bonding mode on this interface, if it is bonded.:\\n *
`ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n * `IEEE_8023AD` - BONDING_MODE_IEE
E_8023AD"
    },
    "mtu": {
        "description": "Maximum transmission unit configuration value",
        "type": "number"
    }
}
}
}

```

network/interfaces/{id}/status/

Endpoint

/v2/network/interfaces/{id}/status/

GET

Retrieve the network statuses of all nodes on the underlying network interface

Parameters

Name	Description	Required
id	The unique ID of the network interface	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_interface_network_statuses",
    "type": "object",
    "properties": {
      "node_id": {
        "description": "Node Id",
        "type": "number"
      },
      "node_name": {
        "description": "Node name",
        "type": "string"
      },
      "update_status": {
        "type": "string",
        "enum": [
          "CHANGES_APPLIED",
          "CHANGES_PENDING",

```

```

        "UNAVAILABLE"
    ],
    "description": "update_status:\n * `CHANGES_APPLIED` - UPDATE_STATUS_CHANGE
S_APPLIED,\n * `CHANGES_PENDING` - UPDATE_STATUS_CHANGES_PENDING,\n * `UNAVAILABLE`
- UPDATE_STATUS_UNAVAILABLE"
},
"interface_details": {
    "description": "interface_details",
    "type": "object",
    "properties": {
        "speed": {
            "description": "Network card speed in Mbps.",
            "type": "number"
        },
        "bytes_sent": {
            "description": "Bytes sent over the interface.",
            "type": "string"
        },
        "bytes_received": {
            "description": "Bytes received over the interface.",
            "type": "string"
        },
        "cable_status": {
            "type": "string",
            "enum": [
                "CONNECTED",
                "DISCONNECTED",
                "UNKNOWN"
            ],
            "description": "Whether network card is connected via cable.:\n * `CONNE
CTED` - NETWORK_CABLE_CONNECTED,\n * `DISCONNECTED` - NETWORK_CABLE_DISCONNECTED,\n
* `UNKNOWN` - NETWORK_CABLE_UNKNOWN"
        },
        "interface_status": {
            "type": "string",
            "enum": [
                "UP",
                "DOWN",
                "MISSING",
                "UNKNOWN",
                "NOTPRESENT",
                "LOWERLAYERDOWN",
                "TESTING",
                "DORMANT"
            ],
            "description": "Status of interface connection.:\n * `DORMANT` - NETWORK

```

```

K_INTERFACE_DORMANT,\n * `DOWN` - NETWORK_INTERFACE_DOWN,\n * `LOWERLAYERDOWN` - NET
WORK_INTERFACE_LOWER_LAYER_DOWN,\n * `MISSING` - NETWORK_INTERFACE_MISSING,\n * `NOT
PRESENT` - NETWORK_INTERFACE_NOT_PRESENT,\n * `TESTING` - NETWORK_INTERFACE_TESTIN
G,\n * `UNKNOWN` - NETWORK_INTERFACE_UNKNOWN,\n * `UP` - NETWORK_INTERFACE_UP"
    },
    "mac_address": {
        "description": "MAC address.",
        "type": "string"
    },
    "timestamp": {
        "description": "UNIX epoch timestamp for when the network status was sam
pled.",
        "type": "string"
    }
},
"interface_status": {
    "description": "interface_status",
    "type": "object",
    "properties": {
        "interface_id": {
            "description": "Unique identifier for this interface configuration.",
            "type": "number"
        },
        "name": {
            "description": "Name of the configured interface i.e. bond0.",
            "type": "string"
        },
        "default_gateway": {
            "description": "IPv4 default gateway on which all traffic generated fro
m nodes is sent out on this interface.",
            "type": "string"
        },
        "default_gateway_ipv6": {
            "description": "IPv6 default gateway on which all traffic generated fro
m nodes is sent out on this interface.",
            "type": "string"
        },
        "bonding_mode": {
            "type": "string",
            "enum": [
                "ACTIVE_BACKUP",
                "IEEE_8023AD"
            ],
            "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD), i
f this interface is bonded.\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\n *

```

```

`IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
    },
    "mtu": {
      "description": "The maximum transmission unit in bytes",
      "type": "number"
    }
  },
  "network_statuses": {
    "type": "array",
    "items": {
      "description": "network_statuses",
      "type": "object",
      "properties": {
        "name": {
          "description": "User-assigned network configuration name",
          "type": "string"
        },
        "assigned_by": {
          "type": "string",
          "enum": [
            "DHCP",
            "STATIC",
            "LINK_LOCAL",
            "HOST"
          ],
          "description": "How to assign IP address, either DHCP, STATIC, or LINK_LOCAL:\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
        },
        "address": {
          "description": "The IPv4 or IPv6 address in 0.0.0.0 or :: format",
          "type": "string"
        },
        "floating_addresses": {
          "type": "array",
          "items": {
            "description": "Floating IPv4 or IPv6 addresses in 0.0.0.0 or :: format",
            "type": "string"
          }
        }
      }
    },
    "dns_servers": {
      "type": "array",
      "items": {

```

```

        "description": "The list of DNS servers",
        "type": "string"
    },
    "dns_search_domains": {
        "type": "array",
        "items": {
            "description": "The list of DNS search domains",
            "type": "string"
        }
    },
    "netmask": {
        "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: format, or the IPv4 or IPv6 subnet CIDR",
        "type": "string"
    },
    "mtu": {
        "description": "The maximum transmission unit in bytes",
        "type": "number"
    },
    "vlan_id": {
        "description": "User-assigned vlan_id tag for network configuration.",
        "type": "number"
    }
},
"aws_status": {
    "description": "AWS Network Status.",
    "type": "object",
    "properties": {
        "eni_id": {
            "description": "ID of the network interface.",
            "type": "string"
        },
        "device_number": {
            "description": "Device number of the interface.",
            "type": "number"
        },
        "private_ipv4_addresses": {
            "type": "array",
            "items": {
                "description": "All private IP addresses associated with the interface.",
                "type": "string"
            }
        }
    }
}

```



```

    },
    "subnet_id": {
      "description": "ID of the subnet for the interface.",
      "type": "string"
    },
    "subnet_mask": {
      "description": "Subnet mask of the interface.",
      "type": "string"
    },
    "vpc_id": {
      "description": "ID of the VPC for the interface.",
      "type": "string"
    },
    "security_groups": {
      "type": "array",
      "items": {
        "description": "Names of the security groups applied.",
        "type": "string"
      }
    }
  },
  "azure_status": {
    "description": "Azure Network Status.",
    "type": "object",
    "properties": {
      "private_ipv4_address": {
        "description": "Private IPv4 address of this instance.",
        "type": "string"
      },
      "network": {
        "description": "Azure network containing this instance.",
        "type": "string"
      },
      "subnet_mask": {
        "description": "Subnet mask of the instance's network.",
        "type": "string"
      }
    }
  },
  "gcp_status": {
    "description": "GCP Network Status.",
    "type": "object",
    "properties": {
      "private_ipv4_address": {
        "description": "Private IPv4 address of this instance.",

```

```
{
  "type": "string",
},
"ip_aliases": {
  "type": "array",
  "items": {
    "description": "List of IP aliases associated with this instance.",
    "type": "string"
  }
},
"network": {
  "description": "GCP network containing this instance.",
  "type": "string"
},
"subnet_mask": {
  "description": "Subnet mask of the instance's network.",
  "type": "string"
}
}
}
```

network/interfaces/{interface_id}

Endpoint

/v2/network/interfaces/{interface_id}

GET

Get configuration of an interface.

Parameters

Name	Description	Required
<code>interface_id</code>	The unique ID of the network interface	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_interface_config",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this interface configuration",
      "type": "number"
    },
    "name": {
      "description": "Name of the configured interface i.e. bond0",
      "type": "string"
    },
    "default_gateway": {
      "description": "Default IPv4 gateway on which all traffic generated from nodes is sent out on this interface",
      "type": "string"
    },
    "default_gateway_ipv6": {
      "description": "Default IPv6 gateway on which all traffic generated from nodes"
    }
  }
}
```

```

s is sent out on this interface",
  "type": "string"
},
"bonding_mode": {
  "type": "string",
  "enum": [
    "ACTIVE_BACKUP",
    "IEEE_8023AD"
  ],
  "description": "Linux bonding mode on this interface, if it is bonded.:\\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n * `IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
},
"mtu": {
  "description": "Maximum transmission unit configuration value",
  "type": "number"
}
}
}

```

PUT

Set configuration of an interface. Changes in interface MTU will be applied to the untagged STATIC network as well as the interface.

Parameters

Name	Description	Required
<code>interface_id</code>	The unique ID of the network interface	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```

{
  "description": "api_interface_config",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this interface configuration",
      "type": "number"
    },
  },
}

```

```

"name": {
  "description": "Name of the configured interface i.e. bond0",
  "type": "string"
},
"default_gateway": {
  "description": "Default IPv4 gateway on which all traffic generated from node
s is sent out on this interface",
  "type": "string"
},
"default_gateway_ipv6": {
  "description": "Default IPv6 gateway on which all traffic generated from node
s is sent out on this interface",
  "type": "string"
},
"bonding_mode": {
  "type": "string",
  "enum": [
    "ACTIVE_BACKUP",
    "IEEE_8023AD"
  ],
  "description": "Linux bonding mode on this interface, if it is bonded.:\\n * `A
CTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n * `IEEE_8023AD` - BONDING_MODE_IEEE_80
23AD"
},
"mtu": {
  "description": "Maximum transmission unit configuration value",
  "type": "number"
}
}
}

```

Response

Codes

Code	Description
202	Return value on success

PATCH

Update a subset of an interface configuration. Changes in interface MTU will be applied to the untagged STATIC network as well as the interface.

Parameters

Name	Description	Required
<code>interface_id</code>	The unique ID of the network interface	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_interface_config",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this interface configuration",
      "type": "number"
    },
    "name": {
      "description": "Name of the configured interface i.e. bond0",
      "type": "string"
    },
    "default_gateway": {
      "description": "Default IPv4 gateway on which all traffic generated from nodes is sent out on this interface",
      "type": "string"
    },
    "default_gateway_ipv6": {
      "description": "Default IPv6 gateway on which all traffic generated from nodes is sent out on this interface",
      "type": "string"
    },
    "bonding_mode": {
      "type": "string",
      "enum": [
        "ACTIVE_BACKUP",
        "IEEE_8023AD"
      ],
      "description": "Linux bonding mode on this interface, if it is bonded.:\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\n * `IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
    },
    "mtu": {
      "description": "Maximum transmission unit configuration value",
```

```
    "type": "number"  
  }  
}  
}
```

Response

Codes

Code	Description
202	Return value on success

network/interfaces/{interface_id}/networks/

Endpoint

/v2/network/interfaces/{interface_id}/networks/

GET

Get configurations of all networks configured on an interface. This will always include at least one network, and exactly one if it is assigned by DHCP. Network 1 is created by default, but it may be removed if other networks are created via static assignment.

Parameters

Name	Description	Required
<code>interface_id</code>	The unique ID of the network interface	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_network_config_v2",
    "type": "object",
    "properties": {
      "name": {
        "description": "name",
        "type": "string"
      },
      "id": {
        "description": "id",
        "type": "number"
      },
      "assigned_by": {
        "type": "string",
        "enum": [
```



```

        "DHCP",
        "STATIC",
        "LINK_LOCAL",
        "HOST"
    ],
    "description": "assigned_by:\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
},
"floating_ip_ranges": {
    "type": "array",
    "items": {
        "description": "floating_ip_ranges",
        "type": "string"
    }
},
"dns_servers": {
    "type": "array",
    "items": {
        "description": "dns_servers",
        "type": "string"
    }
},
"dns_search_domains": {
    "type": "array",
    "items": {
        "description": "dns_search_domains",
        "type": "string"
    }
},
"ip_ranges": {
    "type": "array",
    "items": {
        "description": "ip_ranges",
        "type": "string"
    }
},
"netmask": {
    "description": "netmask",
    "type": "string"
},
"mtu": {
    "description": "mtu",
    "type": "number"
},
"vlan_id": {

```

```

    "description": "User assigned VLAN tag for network configuration. 1-4094 are valid VLAN IDs and 0 is used for untagged networks.",
    "type": "number"
  },
  "tenant_id": {
    "description": "The tenant ID of the tenant that the network is a part of.",
    "type": "number"
  }
}
}
}

```

POST

Add a network configuration to the interface. If the network being added is an untagged STATIC network, the MTU will be computed based on the interface configuration.

Parameters

Name	Description	Required
<code>interface_id</code>	The unique ID of the network interface	Yes

Request

Schema

```

{
  "description": "api_network_config_v2",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "id": {
      "description": "id",
      "type": "number"
    },
    "assigned_by": {
      "type": "string",
      "enum": [
        "DHCP",
        "STATIC",
        "LINK_LOCAL",

```

```

    "HOST"
  ],
  "description": "assigned_by:\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
},
"floating_ip_ranges": {
  "type": "array",
  "items": {
    "description": "floating_ip_ranges",
    "type": "string"
  }
},
"dns_servers": {
  "type": "array",
  "items": {
    "description": "dns_servers",
    "type": "string"
  }
},
"dns_search_domains": {
  "type": "array",
  "items": {
    "description": "dns_search_domains",
    "type": "string"
  }
},
"ip_ranges": {
  "type": "array",
  "items": {
    "description": "ip_ranges",
    "type": "string"
  }
},
"netmask": {
  "description": "netmask",
  "type": "string"
},
"mtu": {
  "description": "mtu",
  "type": "number"
},
"vlan_id": {
  "description": "User assigned VLAN tag for network configuration. 1-4094 are valid VLAN IDs and 0 is used for untagged networks.",
  "type": "number"
}

```

```
    },  
    "tenant_id": {  
      "description": "The tenant ID of the tenant that the network is a part of.",  
      "type": "number"  
    }  
  }  
}
```

Response

Codes

Code	Description
202	Return value on success

network/ interfaces/{interface_id}/networks/{network_id}

Endpoint

/v2/network/interfaces/{interface_id}/networks/{network_id}

GET

Get configuration of a network on an interface.

Parameters

Name	Description	Required
<code>interface_id</code>	The unique ID of the network interface	Yes
<code>network_id</code>	The unique ID of the virtual network	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_network_config_v2",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "id": {
      "description": "id",
      "type": "number"
    },
    "assigned_by": {
      "type": "string",
      "enum": [
```

```

        "DHCP",
        "STATIC",
        "LINK_LOCAL",
        "HOST"
    ],
    "description": "assigned_by:\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
},
"floating_ip_ranges": {
    "type": "array",
    "items": {
        "description": "floating_ip_ranges",
        "type": "string"
    }
},
"dns_servers": {
    "type": "array",
    "items": {
        "description": "dns_servers",
        "type": "string"
    }
},
"dns_search_domains": {
    "type": "array",
    "items": {
        "description": "dns_search_domains",
        "type": "string"
    }
},
"ip_ranges": {
    "type": "array",
    "items": {
        "description": "ip_ranges",
        "type": "string"
    }
},
"netmask": {
    "description": "netmask",
    "type": "string"
},
"mtu": {
    "description": "mtu",
    "type": "number"
},
"vlan_id": {

```

```

    "description": "User assigned VLAN tag for network configuration. 1-4094 are valid VLAN IDs and 0 is used for untagged networks.",
    "type": "number"
  },
  "tenant_id": {
    "description": "The tenant ID of the tenant that the network is a part of.",
    "type": "number"
  }
}
}

```

PUT

Set configuration of a network on an interface. MTU change will not be allowed if the network being updated is an untagged STATIC network. Please modify the interface config instead.

Parameters

Name	Description	Required
interface_id	The unique ID of the network interface	Yes
network_id	The unique ID of the virtual network	Yes
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_network_config_v2",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "id": {
      "description": "id",
      "type": "number"
    },
    "assigned_by": {
      "type": "string",
      "enum": [

```

```

        "DHCP",
        "STATIC",
        "LINK_LOCAL",
        "HOST"
    ],
    "description": "assigned_by:\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
},
"floating_ip_ranges": {
    "type": "array",
    "items": {
        "description": "floating_ip_ranges",
        "type": "string"
    }
},
"dns_servers": {
    "type": "array",
    "items": {
        "description": "dns_servers",
        "type": "string"
    }
},
"dns_search_domains": {
    "type": "array",
    "items": {
        "description": "dns_search_domains",
        "type": "string"
    }
},
"ip_ranges": {
    "type": "array",
    "items": {
        "description": "ip_ranges",
        "type": "string"
    }
},
"netmask": {
    "description": "netmask",
    "type": "string"
},
"mtu": {
    "description": "mtu",
    "type": "number"
},
"vlan_id": {

```



```
    "description": "User assigned VLAN tag for network configuration. 1-4094 are valid VLAN IDs and 0 is used for untagged networks.",
    "type": "number"
  },
  "tenant_id": {
    "description": "The tenant ID of the tenant that the network is a part of.",
    "type": "number"
  }
}
```

Response

Codes

Code	Description
202	Return value on success

DELETE

Delete configuration of a network on an interface.

Parameters

Name	Description	Required
interface_id	The unique ID of the network interface	Yes
network_id	The unique ID of the virtual network	Yes
If-Match	ETag for expected version	No

Response

Codes

Code	Description
202	Return value on success

PATCH

Update a subset of configuration of a network on an interface. MTU change will not be allowed if the network being updated is an untagged STATIC network. Please modify the interface config instead.

Parameters

Name	Description	Required
<code>interface_id</code>	The unique ID of the network interface	Yes
<code>network_id</code>	The unique ID of the virtual network	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_network_config_v2",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "id": {
      "description": "id",
      "type": "number"
    },
    "assigned_by": {
      "type": "string",
      "enum": [
        "DHCP",
        "STATIC",
        "LINK_LOCAL",
        "HOST"
      ],
      "description": "assigned_by:\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
    },
    "floating_ip_ranges": {
      "type": "array",
      "items": {
        "description": "floating_ip_ranges",
        "type": "string"
      }
    },
    "dns_servers": {
```

```

    "type": "array",
    "items": {
      "description": "dns_servers",
      "type": "string"
    }
  },
  "dns_search_domains": {
    "type": "array",
    "items": {
      "description": "dns_search_domains",
      "type": "string"
    }
  },
  "ip_ranges": {
    "type": "array",
    "items": {
      "description": "ip_ranges",
      "type": "string"
    }
  },
  "netmask": {
    "description": "netmask",
    "type": "string"
  },
  "mtu": {
    "description": "mtu",
    "type": "number"
  },
  "vlan_id": {
    "description": "User assigned VLAN tag for network configuration. 1-4094 are valid VLAN IDs and 0 is used for untagged networks.",
    "type": "number"
  },
  "tenant_id": {
    "description": "The tenant ID of the tenant that the network is a part of.",
    "type": "number"
  }
}

```

Response

Codes

Code	Description
------	-------------

202	Return value on success
-----	-------------------------

network/ interfaces/{interface_id}/status/{node_id}

Endpoint

/v2/network/interfaces/{interface_id}/status/{node_id}

GET

Retrieve the network status of a node on the underlying network interface

Parameters

Name	Description	Required
<code>interface_id</code>	The unique ID of the network interface	Yes
<code>node_id</code>	The unique ID of the node	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_interface_network_statuses",
  "type": "object",
  "properties": {
    "node_id": {
      "description": "Node Id",
      "type": "number"
    },
    "node_name": {
      "description": "Node name",
      "type": "string"
    },
    "update_status": {
      "type": "string",
      "enum": [
```

```

        "CHANGES_APPLIED",
        "CHANGES_PENDING",
        "UNAVAILABLE"
    ],
    "description": "update_status:\n * `CHANGES_APPLIED` - UPDATE_STATUS_CHANGES_A
PPLIED,\n * `CHANGES_PENDING` - UPDATE_STATUS_CHANGES_PENDING,\n * `UNAVAILABLE` - U
PDATE_STATUS_UNAVAILABLE"
},
"interface_details": {
    "description": "interface_details",
    "type": "object",
    "properties": {
        "speed": {
            "description": "Network card speed in Mbps.",
            "type": "number"
        },
        "bytes_sent": {
            "description": "Bytes sent over the interface.",
            "type": "string"
        },
        "bytes_received": {
            "description": "Bytes received over the interface.",
            "type": "string"
        },
        "cable_status": {
            "type": "string",
            "enum": [
                "CONNECTED",
                "DISCONNECTED",
                "UNKNOWN"
            ],
            "description": "Whether network card is connected via cable.:\n * `CONNECT
ED` - NETWORK_CABLE_CONNECTED,\n * `DISCONNECTED` - NETWORK_CABLE_DISCONNECTED,\n *
`UNKNOWN` - NETWORK_CABLE_UNKNOWN"
        },
        "interface_status": {
            "type": "string",
            "enum": [
                "UP",
                "DOWN",
                "MISSING",
                "UNKNOWN",
                "NOTPRESENT",
                "LOWERLAYERDOWN",
                "TESTING",
                "DORMANT"
            ]
        }
    }
}

```

```

    ],
    "description": "Status of interface connection.:\\n * `DORMANT` - NETWORK_I
INTERFACE_DORMANT,\\n * `DOWN` - NETWORK_INTERFACE_DOWN,\\n * `LOWERLAYERDOWN` - NETWOR
K_INTERFACE_LOWER_LAYER_DOWN,\\n * `MISSING` - NETWORK_INTERFACE_MISSING,\\n * `NOTPRE
SENT` - NETWORK_INTERFACE_NOT_PRESENT,\\n * `TESTING` - NETWORK_INTERFACE_TESTING,\\n
* `UNKNOWN` - NETWORK_INTERFACE_UNKNOWN,\\n * `UP` - NETWORK_INTERFACE_UP"
  },
  "mac_address": {
    "description": "MAC address.",
    "type": "string"
  },
  "timestamp": {
    "description": "UNIX epoch timestamp for when the network status was sampl
ed.",
    "type": "string"
  }
},
"interface_status": {
  "description": "interface_status",
  "type": "object",
  "properties": {
    "interface_id": {
      "description": "Unique identifier for this interface configuration.",
      "type": "number"
    },
    "name": {
      "description": "Name of the configured interface i.e. bond0.",
      "type": "string"
    },
    "default_gateway": {
      "description": "IPv4 default gateway on which all traffic generated from n
odes is sent out on this interface.",
      "type": "string"
    },
    "default_gateway_ipv6": {
      "description": "IPv6 default gateway on which all traffic generated from n
odes is sent out on this interface.",
      "type": "string"
    },
    "bonding_mode": {
      "type": "string",
      "enum": [
        "ACTIVE_BACKUP",
        "IEEE_8023AD"
      ]
    }
  }
},

```

```

        "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD), if this interface is bonded.:\\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n * `IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
    },
    "mtu": {
        "description": "The maximum transmission unit in bytes",
        "type": "number"
    }
},
"network_statuses": {
    "type": "array",
    "items": {
        "description": "network_statuses",
        "type": "object",
        "properties": {
            "name": {
                "description": "User-assigned network configuration name",
                "type": "string"
            },
            "assigned_by": {
                "type": "string",
                "enum": [
                    "DHCP",
                    "STATIC",
                    "LINK_LOCAL",
                    "HOST"
                ],
                "description": "How to assign IP address, either DHCP, STATIC, or LINK_LOCAL:\\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
            },
            "address": {
                "description": "The IPv4 or IPv6 address in 0.0.0.0 or :: format",
                "type": "string"
            },
            "floating_addresses": {
                "type": "array",
                "items": {
                    "description": "Floating IPv4 or IPv6 addresses in 0.0.0.0 or :: format",
                    "type": "string"
                }
            },
            "dns_servers": {

```



```

        "type": "array",
        "items": {
            "description": "The list of DNS servers",
            "type": "string"
        }
    },
    "dns_search_domains": {
        "type": "array",
        "items": {
            "description": "The list of DNS search domains",
            "type": "string"
        }
    },
    "netmask": {
        "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: format, or the IPv4 or IPv6 subnet CIDR",
        "type": "string"
    },
    "mtu": {
        "description": "The maximum transmission unit in bytes",
        "type": "number"
    },
    "vlan_id": {
        "description": "User-assigned vlan_id tag for network configuration.",
        "type": "number"
    }
}
},
"aws_status": {
    "description": "AWS Network Status.",
    "type": "object",
    "properties": {
        "eni_id": {
            "description": "ID of the network interface.",
            "type": "string"
        },
        "device_number": {
            "description": "Device number of the interface.",
            "type": "number"
        },
        "private_ipv4_addresses": {
            "type": "array",
            "items": {
                "description": "All private IP addresses associated with the interface.",

```

```

        "type": "string"
    }
},
"subnet_id": {
    "description": "ID of the subnet for the interface.",
    "type": "string"
},
"subnet_mask": {
    "description": "Subnet mask of the interface.",
    "type": "string"
},
"vpc_id": {
    "description": "ID of the VPC for the interface.",
    "type": "string"
},
"security_groups": {
    "type": "array",
    "items": {
        "description": "Names of the security groups applied.",
        "type": "string"
    }
}
},
"azure_status": {
    "description": "Azure Network Status.",
    "type": "object",
    "properties": {
        "private_ipv4_address": {
            "description": "Private IPv4 address of this instance.",
            "type": "string"
        },
        "network": {
            "description": "Azure network containing this instance.",
            "type": "string"
        },
        "subnet_mask": {
            "description": "Subnet mask of the instance's network.",
            "type": "string"
        }
    }
},
"gcp_status": {
    "description": "GCP Network Status.",
    "type": "object",
    "properties": {

```

```

    "private_ipv4_address": {
      "description": "Private IPv4 address of this instance.",
      "type": "string"
    },
    "ip_aliases": {
      "type": "array",
      "items": {
        "description": "List of IP aliases associated with this instance.",
        "type": "string"
      }
    },
    "network": {
      "description": "GCP network containing this instance.",
      "type": "string"
    },
    "subnet_mask": {
      "description": "Subnet mask of the instance's network.",
      "type": "string"
    }
  }
}
}
}

```

network

Endpoint

/v3/network

GET

Get the cluster-wide network configuration

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_v3_cluster_network_management",
  "type": "object",
  "properties": {
    "managed_interfaces": {
      "description": "The Linux virtual network interface devices that Qumulo Core creates and manages.",
      "type": "object",
      "properties": {
        "frontend_bond_config": {
          "description": "Bond configuration for frontend interfaces.",
          "type": "object",
          "properties": {
            "interface_name": {
              "description": "Name of the interface i.e. bond0.",
              "type": "string"
            },
            "bonding_mode": {
              "type": "string",
              "enum": [
                "ACTIVE_BACKUP",
                "IEEE_8023AD"
              ]
            }
          }
        }
      }
    }
  }
}
```

```

    ],
    "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD),
if this interface is bonded.:\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\n *
`IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
  },
  "mtu": {
    "description": "Maximum transmission unit configuration value.",
    "type": "number"
  },
  "networks": {
    "type": "array",
    "items": {
      "description": "The ids of the network configurations to apply to th
is interface.",
      "type": "number"
    }
  }
},
"frontend_vlans": {
  "type": "array",
  "items": {
    "description": "VLAN configurations for frontend interfaces.",
    "type": "object",
    "properties": {
      "vlan_id": {
        "description": "User assigned VLAN tag for network configuration.
1-4094 are valid VLAN IDs and 0 is used for untagged networks.",
        "type": "number"
      },
      "mtu": {
        "description": "The maximum transmission unit of this interface.",
        "type": "number"
      },
      "network_id": {
        "description": "The id of the network configuration to apply to thi
s interface.",
        "type": "number"
      },
      "secondary_network_id": {
        "description": "An optional secondary network id to apply to this in
terface.",
        "type": "number"
      }
    }
  }
}

```

```

},
"backend_bond_config": {
  "description": "Optional bond configuration for backend interfaces.",
  "type": "object",
  "properties": {
    "interface_name": {
      "description": "Name of the interface i.e. bond0.",
      "type": "string"
    },
    "bonding_mode": {
      "type": "string",
      "enum": [
        "ACTIVE_BACKUP",
        "IEEE_8023AD"
      ],
      "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD), if this interface is bonded.:\\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n * `IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
    },
    "mtu": {
      "description": "Maximum transmission unit configuration value.",
      "type": "number"
    },
    "networks": {
      "type": "array",
      "items": {
        "description": "The ids of the network configurations to apply to this interface.",
        "type": "number"
      }
    }
  }
},
"frontend_networks": {
  "type": "array",
  "items": {
    "description": "The list of networks applied to interfaces that serve client traffic.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier for this network configuration.",
        "type": "number"
      }
    }
  }
},

```

```

"name": {
  "description": "Unique name for this network configuration.",
  "type": "string"
},
"tenant_id": {
  "description": "The tenant ID of the tenant that the network is a part of.",
  "type": "number"
},
"api_v3_network_addresses": {
  "description": "api_v3_network_addresses",
  "type": "object",
  "properties": {
    "type": {
      "type": "string",
      "enum": [
        "DHCP",
        "STATIC",
        "HOST"
      ],
      "description": "type:\n * `DHCP` - Network uses DHCP for address assignment,\n * `HOST` - Network addresses are managed by the host,\n * `STATIC` - Network uses static address assignment"
    },
    "dhcp_addresses": {
      "description": "Value present when type is API_V3_NETWORK_ADDRESSES_DHCP.",
      "type": "object",
      "properties": {
        "floating_ip_ranges": {
          "type": "array",
          "items": {
            "description": "List of floating IP ranges",
            "type": "string"
          }
        },
        "netmask": {
          "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: format, or subnet CIDR",
          "type": "string"
        }
      }
    },
    "static_addresses": {
      "description": "Value present when type is API_V3_NETWORK_ADDRESSES_STATIC."
    }
  }
}

```

```

    "type": "object",
    "properties": {
      "default_gateway": {
        "description": "Default IPv4 gateway address for this network",
        "type": "string"
      },
      "ip_ranges": {
        "type": "array",
        "items": {
          "description": "List of IP ranges to assign to nodes",
          "type": "string"
        }
      },
      "floating_ip_ranges": {
        "type": "array",
        "items": {
          "description": "List of floating IP",
          "type": "string"
        }
      },
      "netmask": {
        "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: forma
t, or subnet CIDR",
        "type": "string"
      }
    },
    "host_addresses": {
      "description": "Value present when type is API_V3_NETWORK_ADDRESSE
S_HOST.",
      "type": "object",
      "properties": {
        "floating_ip_ranges": {
          "type": "array",
          "items": {
            "description": "List of floating IP ranges",
            "type": "string"
          }
        },
        "netmask": {
          "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: forma
t, or subnet CIDR",
          "type": "string"
        }
      }
    }
  }
}

```


}

PUT

Overwrite the current cluster network configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_v3_cluster_network_management",
  "type": "object",
  "properties": {
    "managed_interfaces": {
      "description": "The Linux virtual network interface devices that Qumulo Core creates and manages.",
      "type": "object",
      "properties": {
        "frontend_bond_config": {
          "description": "Bond configuration for frontend interfaces.",
          "type": "object",
          "properties": {
            "interface_name": {
              "description": "Name of the interface i.e. bond0.",
              "type": "string"
            },
            "bonding_mode": {
              "type": "string",
              "enum": [
                "ACTIVE_BACKUP",
                "IEEE_8023AD"
              ]
            }
          }
        }
      }
    }
  }
}
```

```

        "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD),
if this interface is bonded.:\\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n *
`IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
    },
    "mtu": {
        "description": "Maximum transmission unit configuration value.",
        "type": "number"
    },
    "networks": {
        "type": "array",
        "items": {
            "description": "The ids of the network configurations to apply to th
is interface.",
            "type": "number"
        }
    }
},
"frontend_vlans": {
    "type": "array",
    "items": {
        "description": "VLAN configurations for frontend interfaces.",
        "type": "object",
        "properties": {
            "vlan_id": {
                "description": "User assigned VLAN tag for network configuration.
1-4094 are valid VLAN IDs and 0 is used for untagged networks.",
                "type": "number"
            },
            "mtu": {
                "description": "The maximum transmission unit of this interface.",
                "type": "number"
            },
            "network_id": {
                "description": "The id of the network configuration to apply to thi
s interface.",
                "type": "number"
            },
            "secondary_network_id": {
                "description": "An optional secondary network id to apply to this in
terface.",
                "type": "number"
            }
        }
    }
},
},

```

```

"backend_bond_config": {
  "description": "Optional bond configuration for backend interfaces.",
  "type": "object",
  "properties": {
    "interface_name": {
      "description": "Name of the interface i.e. bond0.",
      "type": "string"
    },
    "bonding_mode": {
      "type": "string",
      "enum": [
        "ACTIVE_BACKUP",
        "IEEE_8023AD"
      ],
      "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD),
if this interface is bonded.:\\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n *
`IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
    },
    "mtu": {
      "description": "Maximum transmission unit configuration value.",
      "type": "number"
    },
    "networks": {
      "type": "array",
      "items": {
        "description": "The ids of the network configurations to apply to th
is interface.",
        "type": "number"
      }
    }
  }
},
"frontend_networks": {
  "type": "array",
  "items": {
    "description": "The list of networks applied to interfaces that serve clien
t traffic.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier for this network configuration.",
        "type": "number"
      },
      "name": {

```

```

        "description": "Unique name for this network configuration.",
        "type": "string"
    },
    "tenant_id": {
        "description": "The tenant ID of the tenant that the network is a part of.",
        "type": "number"
    },
    "api_v3_network_addresses": {
        "description": "api_v3_network_addresses",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "DHCP",
                    "STATIC",
                    "HOST"
                ],
                "description": "type:\n * `DHCP` - Network uses DHCP for address assignment,\n * `HOST` - Network addresses are managed by the host,\n * `STATIC` - Network uses static address assignment"
            },
            "dhcp_addresses": {
                "description": "Value present when type is API_V3_NETWORK_ADDRESSES_DHCP.",
                "type": "object",
                "properties": {
                    "floating_ip_ranges": {
                        "type": "array",
                        "items": {
                            "description": "List of floating IP ranges",
                            "type": "string"
                        }
                    },
                    "netmask": {
                        "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: format, or subnet CIDR",
                        "type": "string"
                    }
                }
            },
            "static_addresses": {
                "description": "Value present when type is API_V3_NETWORK_ADDRESSES_STATIC.",
                "type": "object",

```

```

    "properties": {
      "default_gateway": {
        "description": "Default IPv4 gateway address for this network",
        "type": "string"
      },
      "ip_ranges": {
        "type": "array",
        "items": {
          "description": "List of IP ranges to assign to nodes",
          "type": "string"
        }
      },
      "floating_ip_ranges": {
        "type": "array",
        "items": {
          "description": "List of floating IP",
          "type": "string"
        }
      },
      "netmask": {
        "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: forma
t, or subnet CIDR",
        "type": "string"
      }
    },
    "host_addresses": {
      "description": "Value present when type is API_V3_NETWORK_ADDRESSE
S_HOST.",
      "type": "object",
      "properties": {
        "floating_ip_ranges": {
          "type": "array",
          "items": {
            "description": "List of floating IP ranges",
            "type": "string"
          }
        },
        "netmask": {
          "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: forma
t, or subnet CIDR",
          "type": "string"
        }
      }
    }
  }
}

```

```
}  
  }  
  }  
  }  
}
```

Response

Codes

Code	Description
202	Return value on success

network/backend-interfaces

Endpoint

/v3/network/backend-interfaces

GET

Get the backend interface names for all nodes in the cluster

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "node_id_string_map",
  "type": "object",
  "properties": {},
  "additionalProperties": {
    "description": "node_id_string_map value",
    "type": "string"
  }
}
```

network/frontend-interfaces

Endpoint

/v3/network/frontend-interfaces

GET

Get the frontend interface names for all nodes in the cluster

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "node_id_string_vec_map",
  "type": "object",
  "properties": {},
  "additionalProperties": {
    "type": "array",
    "items": {
      "description": "node_id_string_vec_map value",
      "type": "string"
    }
  }
}
```


network/status

Endpoint

/v3/network/status

GET

Retrieve the network statuses of all nodes in the cluster

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_node_network_status",
    "type": "object",
    "properties": {
      "node_id": {
        "description": "Unique identifier for the node.",
        "type": "number"
      },
      "node_name": {
        "description": "Human-readable name of the node.",
        "type": "string"
      },
      "managed_interface_statuses": {
        "type": "array",
        "items": {
          "description": "Status of all managed network interfaces on this node.",
          "type": "object",
          "properties": {
            "name": {
              "description": "Name of the interface.",

```

```

        "type": "string"
    },
    "status": {
        "type": "string",
        "enum": [
            "APPLIED",
            "PENDING",
            "FAILED"
        ],
        "description": "Current application status of the interface.:\\n * `APPLIED` - APPLICATION_STATUS_APPLIED,\\n * `FAILED` - APPLICATION_STATUS_FAILED,\\n * `PENDING` - APPLICATION_STATUS_PENDING"
    },
    "details": {
        "description": "Additional details about the interface status.",
        "type": "string"
    }
}
},
"network_statuses": {
    "description": "Status of all network configurations on this node.",
    "type": "object",
    "properties": {},
    "additionalProperties": {
        "description": "Status of all network configurations on this node. value",
        "type": "object",
        "properties": {
            "name": {
                "description": "Human readable name of this network configuration.",
                "type": "string"
            },
            "status": {
                "type": "string",
                "enum": [
                    "APPLIED",
                    "PENDING",
                    "FAILED"
                ],
                "description": "Current application status of the network configuration.:\\n * `APPLIED` - APPLICATION_STATUS_APPLIED,\\n * `FAILED` - APPLICATION_STATUS_FAILED,\\n * `PENDING` - APPLICATION_STATUS_PENDING"
            },
            "details": {
                "description": "Additional details about the network configuration status.",

```

```

        "type": "string"
    }
}
},
"devices": {
    "type": "array",
    "items": {
        "description": "All detected network devices on this node.",
        "type": "object",
        "properties": {
            "name": {
                "description": "Name of the network device.",
                "type": "string"
            },
            "permanent_mac_address": {
                "description": "Permanent hardware MAC address of the device.",
                "type": "string"
            },
            "mac_address": {
                "description": "Current MAC address of the device.",
                "type": "string"
            },
            "speed": {
                "description": "Link speed in Mbps.",
                "type": "string"
            },
            "bytes_sent": {
                "description": "Total bytes transmitted on this device.",
                "type": "string"
            },
            "bytes_received": {
                "description": "Total bytes received on this device.",
                "type": "string"
            },
            "cable_status": {
                "type": "string",
                "enum": [
                    "CONNECTED",
                    "DISCONNECTED",
                    "UNKNOWN"
                ],
                "description": "Cable connection status of the device.:\\n * `CONNECTE
D` - NETWORK_CABLE_CONNECTED,\\n * `DISCONNECTED` - NETWORK_CABLE_DISCONNECTED,\\n *
`UNKNOWN` - NETWORK_CABLE_UNKNOWN"
            }
        }
    }
}

```

```

"interface_status": {
  "type": "string",
  "enum": [
    "UP",
    "DOWN",
    "MISSING",
    "UNKNOWN",
    "NOTPRESENT",
    "LOWERLAYERDOWN",
    "TESTING",
    "DORMANT"
  ],
  "description": "Operational status of the network interface.:\\n * `DOR
MANT` - NETWORK_INTERFACE_DORMANT,\\n * `DOWN` - NETWORK_INTERFACE_DOWN,\\n * `LOWERLA
YERDOWN` - NETWORK_INTERFACE_LOWER_LAYER_DOWN,\\n * `MISSING` - NETWORK_INTERFACE_MIS
SING,\\n * `NOTPRESENT` - NETWORK_INTERFACE_NOT_PRESENT,\\n * `TESTING` - NETWORK_INTE
RFACE_TESTING,\\n * `UNKNOWN` - NETWORK_INTERFACE_UNKNOWN,\\n * `UP` - NETWORK_INTERFA
CE_UP"
},
"mtu": {
  "description": "Maximum transmission unit in bytes.",
  "type": "number"
},
"bonding_mode": {
  "type": "string",
  "enum": [
    "ACTIVE_BACKUP",
    "IEEE_8023AD"
  ],
  "description": "Bonding mode if this device is part of a bond.:\\n * `A
CTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n * `IEEE_8023AD` - BONDING_MODE_IEEE_80
23AD"
},
"vlan_id": {
  "description": "VLAN ID if this device is a VLAN interface.",
  "type": "number"
},
"timestamp": {
  "description": "Timestamp when this status was captured.",
  "type": "string"
},
"api_network_specific_fields": {
  "description": "api_network_specific_fields",
  "type": "object",
  "properties": {
    "type": {

```

```

        "type": "string",
        "enum": [
            "FRONTEND",
            "BACKEND",
            "FRONTEND_AND_BACKEND",
            "UNDERLYING",
            "NONE"
        ],
        "description": "use_for:\n * `BACKEND` - USE_FOR_BACKEND,\n * `FRONTEND` - USE_FOR_FRONTEND,\n * `FRONTEND_AND_BACKEND` - USE_FOR_FRONTEND_AND_BACKEND,\n * `NONE` - USE_FOR_NONE,\n * `UNDERLYING` - USE_FOR_UNDERLYING"
    },
    "qumulo_ip_addresses": {
        "type": "array",
        "items": {
            "description": "Value present when type is USE_FOR_FRONTEND, USE_FOR_BACKEND, or USE_FOR_FRONTEND_AND_BACKEND.",
            "type": "object",
            "properties": {
                "network_id": {
                    "description": "Unique identifier for this network configuration",
                    "type": "number"
                },
                "assigned_by": {
                    "type": "string",
                    "enum": [
                        "DHCP",
                        "STATIC",
                        "LINK_LOCAL",
                        "HOST"
                    ],
                    "description": "How networks are assigned: DHCP, STATIC, or HOST:\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
                },
                "netmask": {
                    "description": "The IPv4 or IPv6 netmask",
                    "type": "string"
                },
                "address": {
                    "description": "The IPv4 or IPv6 address assigned to this interface",
                    "type": "string"
                }
            }
        }
    }
}

```

```

        "floating_addresses": {
            "type": "array",
            "items": {
                "description": "Floating IP addresses in 0.0.0.0 or :: for
mat",
                "type": "string"
            }
        },
        "gateway": {
            "description": "Default gateway address for this network",
            "type": "string"
        }
    },
    "host_routable_ip_addresses": {
        "type": "array",
        "items": {
            "description": "Value present when type is USE_FOR_FRONTEND, US
E_FOR_BACKEND, or USE_FOR_FRONTEND_AND_BACKEND.",
            "type": "string"
        }
    },
    "upper_interface_name": {
        "description": "Value present when type is USE_FOR_UNDERLYING.",
        "type": "string"
    },
    "addresses": {
        "type": "array",
        "items": {
            "description": "Value present when type is USE_FOR_NONE.",
            "type": "string"
        }
    }
}
}
}
},
"environment": {
    "description": "Detected network environment settings.",
    "type": "object",
    "properties": {
        "dns_servers": {
            "type": "array",
            "items": {

```

```

        "description": "List of DNS server addresses.",
        "type": "string"
    },
    "dns_search_domains": {
        "type": "array",
        "items": {
            "description": "List of DNS search domains.",
            "type": "string"
        }
    },
    "systemwide_default_gateways": {
        "type": "array",
        "items": {
            "description": "System-wide default gateway addresses.",
            "type": "string"
        }
    }
},
"api_cloud_provider_status": {
    "description": "api_cloud_provider_status",
    "type": "object",
    "properties": {
        "type": {
            "type": "string",
            "enum": [
                "AWS",
                "AZURE",
                "GCP"
            ],
            "description": "type:\n * `AWS` - AWS cloud provider,\n * `AZURE` - Azure cloud provider,\n * `GCP` - GCP cloud provider"
        },
        "aws_status": {
            "description": "Value present when type is API_CLOUD_PROVIDER_STATUS_AWS.",
            "type": "object",
            "properties": {
                "eni_id": {
                    "description": "ID of the network interface.",
                    "type": "string"
                },
                "device_number": {
                    "description": "Device number of the interface.",
                    "type": "number"
                }
            }
        }
    }
}

```

```

    },
    "private_ipv4_addresses": {
      "type": "array",
      "items": {
        "description": "All private IP addresses associated with the inter
face.",
        "type": "string"
      }
    },
    "subnet_id": {
      "description": "ID of the subnet for the interface.",
      "type": "string"
    },
    "subnet_mask": {
      "description": "Subnet mask of the interface.",
      "type": "string"
    },
    "vpc_id": {
      "description": "ID of the VPC for the interface.",
      "type": "string"
    },
    "security_groups": {
      "type": "array",
      "items": {
        "description": "Names of the security groups applied.",
        "type": "string"
      }
    }
  },
  "azure_status": {
    "description": "Value present when type is API_CLOUD_PROVIDER_STATUS_AZU
RE.",
    "type": "object",
    "properties": {
      "private_ipv4_address": {
        "description": "Private IPv4 address of this instance.",
        "type": "string"
      },
      "network": {
        "description": "Azure network containing this instance.",
        "type": "string"
      },
      "subnet_mask": {
        "description": "Subnet mask of the instance's network.",
        "type": "string"
      }
    }
  }
}

```


network/status/{node_id}

Endpoint

/v3/network/status/{node_id}

GET

Retrieve the network status of a node

Parameters

Name	Description	Required
node_id	The unique ID of the node	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_node_network_status",
  "type": "object",
  "properties": {
    "node_id": {
      "description": "Unique identifier for the node.",
      "type": "number"
    },
    "node_name": {
      "description": "Human-readable name of the node.",
      "type": "string"
    },
    "managed_interface_statuses": {
      "type": "array",
      "items": {
        "description": "Status of all managed network interfaces on this node.",
        "type": "object",
        "properties": {
          "name": {
```

```

        "description": "Name of the interface.",
        "type": "string"
    },
    "status": {
        "type": "string",
        "enum": [
            "APPLIED",
            "PENDING",
            "FAILED"
        ],
        "description": "Current application status of the interface.:\\n * `APPLIED` - APPLICATION_STATUS_APPLIED,\\n * `FAILED` - APPLICATION_STATUS_FAILED,\\n * `PENDING` - APPLICATION_STATUS_PENDING"
    },
    "details": {
        "description": "Additional details about the interface status.",
        "type": "string"
    }
}
},
"network_statuses": {
    "description": "Status of all network configurations on this node.",
    "type": "object",
    "properties": {},
    "additionalProperties": {
        "description": "Status of all network configurations on this node. value",
        "type": "object",
        "properties": {
            "name": {
                "description": "Human readable name of this network configuration.",
                "type": "string"
            },
            "status": {
                "type": "string",
                "enum": [
                    "APPLIED",
                    "PENDING",
                    "FAILED"
                ],
                "description": "Current application status of the network configuration.:\\n * `APPLIED` - APPLICATION_STATUS_APPLIED,\\n * `FAILED` - APPLICATION_STATUS_FAILED,\\n * `PENDING` - APPLICATION_STATUS_PENDING"
            },
            "details": {
                "description": "Additional details about the network configuration statu

```

```

s.",
    "type": "string"
  }
}
},
"devices": {
  "type": "array",
  "items": {
    "description": "All detected network devices on this node.",
    "type": "object",
    "properties": {
      "name": {
        "description": "Name of the network device.",
        "type": "string"
      },
      "permanent_mac_address": {
        "description": "Permanent hardware MAC address of the device.",
        "type": "string"
      },
      "mac_address": {
        "description": "Current MAC address of the device.",
        "type": "string"
      },
      "speed": {
        "description": "Link speed in Mbps.",
        "type": "string"
      },
      "bytes_sent": {
        "description": "Total bytes transmitted on this device.",
        "type": "string"
      },
      "bytes_received": {
        "description": "Total bytes received on this device.",
        "type": "string"
      },
      "cable_status": {
        "type": "string",
        "enum": [
          "CONNECTED",
          "DISCONNECTED",
          "UNKNOWN"
        ],
        "description": "Cable connection status of the device.:\\n * `CONNECTED`  

- NETWORK_CABLE_CONNECTED,\\n * `DISCONNECTED` - NETWORK_CABLE_DISCONNECTED,\\n * `UNK  

NOWN` - NETWORK_CABLE_UNKNOWN"
      }
    }
  }
}

```

```

},
"interface_status": {
  "type": "string",
  "enum": [
    "UP",
    "DOWN",
    "MISSING",
    "UNKNOWN",
    "NOTPRESENT",
    "LOWERLAYERDOWN",
    "TESTING",
    "DORMANT"
  ],
  "description": "Operational status of the network interface.:\\n * `DORMANT` - NETWORK_INTERFACE_DORMANT,\\n * `DOWN` - NETWORK_INTERFACE_DOWN,\\n * `LOWERLAYERDOWN` - NETWORK_INTERFACE_LOWER_LAYER_DOWN,\\n * `MISSING` - NETWORK_INTERFACE_MISSING,\\n * `NOTPRESENT` - NETWORK_INTERFACE_NOT_PRESENT,\\n * `TESTING` - NETWORK_INTERFACE_TESTING,\\n * `UNKNOWN` - NETWORK_INTERFACE_UNKNOWN,\\n * `UP` - NETWORK_INTERFACE_UP"
},
"mtu": {
  "description": "Maximum transmission unit in bytes.",
  "type": "number"
},
"bonding_mode": {
  "type": "string",
  "enum": [
    "ACTIVE_BACKUP",
    "IEEE_8023AD"
  ],
  "description": "Bonding mode if this device is part of a bond.:\\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n * `IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
},
"vlan_id": {
  "description": "VLAN ID if this device is a VLAN interface.",
  "type": "number"
},
"timestamp": {
  "description": "Timestamp when this status was captured.",
  "type": "string"
},
"api_network_specific_fields": {
  "description": "api_network_specific_fields",
  "type": "object",
  "properties": {

```

```

"type": {
  "type": "string",
  "enum": [
    "FRONTEND",
    "BACKEND",
    "FRONTEND_AND_BACKEND",
    "UNDERLYING",
    "NONE"
  ],
  "description": "use_for:\n * `BACKEND` - USE_FOR_BACKEND,\n * `FRONTEND` - USE_FOR_FRONTEND,\n * `FRONTEND_AND_BACKEND` - USE_FOR_FRONTEND_AND_BACKEND,\n * `NONE` - USE_FOR_NONE,\n * `UNDERLYING` - USE_FOR_UNDERLYING"
},
"qumulo_ip_addresses": {
  "type": "array",
  "items": {
    "description": "Value present when type is USE_FOR_FRONTEND, USE_FOR_BACKEND, or USE_FOR_FRONTEND_AND_BACKEND.",
    "type": "object",
    "properties": {
      "network_id": {
        "description": "Unique identifier for this network configuration",
        "type": "number"
      },
      "assigned_by": {
        "type": "string",
        "enum": [
          "DHCP",
          "STATIC",
          "LINK_LOCAL",
          "HOST"
        ],
        "description": "How networks are assigned: DHCP, STATIC, or HOST:\n * `DHCP` - NETWORK_ASSIGNED_BY_DHCP,\n * `HOST` - NETWORK_ASSIGNED_BY_HOST,\n * `LINK_LOCAL` - NETWORK_ASSIGNED_BY_LINK_LOCAL,\n * `STATIC` - NETWORK_ASSIGNED_BY_STATIC"
      },
      "netmask": {
        "description": "The IPv4 or IPv6 netmask",
        "type": "string"
      },
      "address": {
        "description": "The IPv4 or IPv6 address assigned to this interface",
        "type": "string"
      }
    }
  }
}

```

```

    },
    "floating_addresses": {
      "type": "array",
      "items": {
        "description": "Floating IP addresses in 0.0.0.0 or :: forma
t",
        "type": "string"
      }
    },
    "gateway": {
      "description": "Default gateway address for this network",
      "type": "string"
    }
  }
},
"host_routable_ip_addresses": {
  "type": "array",
  "items": {
    "description": "Value present when type is USE_FOR_FRONTEND, USE_F
OR_BACKEND, or USE_FOR_FRONTEND_AND_BACKEND.",
    "type": "string"
  }
},
"upper_interface_name": {
  "description": "Value present when type is USE_FOR_UNDERLYING.",
  "type": "string"
},
"addresses": {
  "type": "array",
  "items": {
    "description": "Value present when type is USE_FOR_NONE.",
    "type": "string"
  }
}
}
}
}
},
"environment": {
  "description": "Detected network environment settings.",
  "type": "object",
  "properties": {
    "dns_servers": {
      "type": "array",

```

```

        "items": {
            "description": "List of DNS server addresses.",
            "type": "string"
        }
    },
    "dns_search_domains": {
        "type": "array",
        "items": {
            "description": "List of DNS search domains.",
            "type": "string"
        }
    },
    "systemwide_default_gateways": {
        "type": "array",
        "items": {
            "description": "System-wide default gateway addresses.",
            "type": "string"
        }
    }
},
"api_cloud_provider_status": {
    "description": "api_cloud_provider_status",
    "type": "object",
    "properties": {
        "type": {
            "type": "string",
            "enum": [
                "AWS",
                "AZURE",
                "GCP"
            ],
            "description": "type:\n * `AWS` - AWS cloud provider,\n * `AZURE` - Azure cloud provider,\n * `GCP` - GCP cloud provider"
        },
        "aws_status": {
            "description": "Value present when type is API_CLOUD_PROVIDER_STATUS_AWS.",
            "type": "object",
            "properties": {
                "eni_id": {
                    "description": "ID of the network interface.",
                    "type": "string"
                },
                "device_number": {
                    "description": "Device number of the interface.",

```



```

        "type": "number"
    },
    "private_ipv4_addresses": {
        "type": "array",
        "items": {
            "description": "All private IP addresses associated with the interface.",
            "type": "string"
        }
    },
    "subnet_id": {
        "description": "ID of the subnet for the interface.",
        "type": "string"
    },
    "subnet_mask": {
        "description": "Subnet mask of the interface.",
        "type": "string"
    },
    "vpc_id": {
        "description": "ID of the VPC for the interface.",
        "type": "string"
    },
    "security_groups": {
        "type": "array",
        "items": {
            "description": "Names of the security groups applied.",
            "type": "string"
        }
    }
},
"azure_status": {
    "description": "Value present when type is API_CLOUD_PROVIDER_STATUS_AZURE.",
    "type": "object",
    "properties": {
        "private_ipv4_address": {
            "description": "Private IPv4 address of this instance.",
            "type": "string"
        },
        "network": {
            "description": "Azure network containing this instance.",
            "type": "string"
        },
        "subnet_mask": {
            "description": "Subnet mask of the instance's network.",

```


network/validate

Endpoint

/v3/network/validate

PUT

Validate a new cluster-wide network configuration without writing it to disk

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_v3_cluster_network_management",
  "type": "object",
  "properties": {
    "managed_interfaces": {
      "description": "The Linux virtual network interface devices that Qumulo Core creates and manages.",
      "type": "object",
      "properties": {
        "frontend_bond_config": {
          "description": "Bond configuration for frontend interfaces.",
          "type": "object",
          "properties": {
            "interface_name": {
              "description": "Name of the interface i.e. bond0.",
              "type": "string"
            },
            "bonding_mode": {
              "type": "string",
              "enum": [
                "ACTIVE_BACKUP",
                "IEEE_8023AD"
              ],
              "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD), if this interface is bonded.:\\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n * `IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
            }
          }
        }
      }
    }
  }
}
```

```

    },
    "mtu": {
      "description": "Maximum transmission unit configuration value.",
      "type": "number"
    },
  },
  "networks": {
    "type": "array",
    "items": {
      "description": "The ids of the network configurations to apply to th
is interface.",
      "type": "number"
    }
  }
},
"frontend_vlans": {
  "type": "array",
  "items": {
    "description": "VLAN configurations for frontend interfaces.",
    "type": "object",
    "properties": {
      "vlan_id": {
        "description": "User assigned VLAN tag for network configuration.
1-4094 are valid VLAN IDs and 0 is used for untagged networks.",
        "type": "number"
      },
      "mtu": {
        "description": "The maximum transmission unit of this interface.",
        "type": "number"
      },
      "network_id": {
        "description": "The id of the network configuration to apply to thi
s interface.",
        "type": "number"
      },
      "secondary_network_id": {
        "description": "An optional secondary network id to apply to this in
terface.",
        "type": "number"
      }
    }
  }
},
"backend_bond_config": {
  "description": "Optional bond configuration for backend interfaces.",
  "type": "object",

```

```

    "properties": {
      "interface_name": {
        "description": "Name of the interface i.e. bond0.",
        "type": "string"
      },
      "bonding_mode": {
        "type": "string",
        "enum": [
          "ACTIVE_BACKUP",
          "IEEE_8023AD"
        ],
        "description": "Ethernet bonding mode (ACTIVE_BACKUP or IEEE_8023AD),  
if this interface is bonded.:\\n * `ACTIVE_BACKUP` - BONDING_MODE_ACTIVE_BACKUP,\\n *  
`IEEE_8023AD` - BONDING_MODE_IEEE_8023AD"
      },
      "mtu": {
        "description": "Maximum transmission unit configuration value.",
        "type": "number"
      },
      "networks": {
        "type": "array",
        "items": {
          "description": "The ids of the network configurations to apply to th  
is interface.",
          "type": "number"
        }
      }
    }
  },
  "frontend_networks": {
    "type": "array",
    "items": {
      "description": "The list of networks applied to interfaces that serve clien  
t traffic.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Unique identifier for this network configuration.",
          "type": "number"
        },
        "name": {
          "description": "Unique name for this network configuration.",
          "type": "string"
        }
      }
    }
  }
}

```

```

    "tenant_id": {
      "description": "The tenant ID of the tenant that the network is a part o
f.",
      "type": "number"
    },
    "api_v3_network_addresses": {
      "description": "api_v3_network_addresses",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "DHCP",
            "STATIC",
            "HOST"
          ],
          "description": "type:\n * `DHCP` - Network uses DHCP for address ass
ignment,\n * `HOST` - Network addresses are managed by the host,\n * `STATIC` - Netw
ork uses static address assignment"
        },
        "dhcp_addresses": {
          "description": "Value present when type is API_V3_NETWORK_ADDRESSE
S_DHCP.",
          "type": "object",
          "properties": {
            "floating_ip_ranges": {
              "type": "array",
              "items": {
                "description": "List of floating IP ranges",
                "type": "string"
              }
            },
            "netmask": {
              "description": "The IPv4 or IPv6 netmask in 0.0.0.0 or :: forma
t, or subnet CIDR",
              "type": "string"
            }
          }
        },
        "static_addresses": {
          "description": "Value present when type is API_V3_NETWORK_ADDRESSE
S_STATIC.",
          "type": "object",
          "properties": {
            "default_gateway": {
              "description": "Default IPv4 gateway address for this network",

```



```
}  
}  
}
```

Response

Codes

Code	Description
200	Return value on success

nexus/connection

Endpoint

/v1/nexus/connection

GET

Retrieve current Nexus connection configuration

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "nexus_connection_config",
  "type": "object",
  "properties": {
    "nexus_enabled": {
      "description": "nexus_enabled",
      "type": "boolean"
    },
    "nexus_host": {
      "description": "nexus_host",
      "type": "string"
    },
    "nexus_port": {
      "description": "nexus_port",
      "type": "number"
    },
    "nexus_interval": {
      "description": "nexus_interval",
      "type": "number"
    },
    "nexus_capability_remote_support": {
      "description": "nexus_capability_remote_support",
```

```

    "type": "boolean"
  },
  "nexus_capability_sso": {
    "description": "nexus_capability_sso",
    "type": "boolean"
  }
}
}

```

PUT

Set the Nexus connection configuration

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "nexus_connection_config",
  "type": "object",
  "properties": {
    "nexus_enabled": {
      "description": "nexus_enabled",
      "type": "boolean"
    },
    "nexus_host": {
      "description": "nexus_host",
      "type": "string"
    },
    "nexus_port": {
      "description": "nexus_port",
      "type": "number"
    },
    "nexus_interval": {
      "description": "nexus_interval",
      "type": "number"
    },
    "nexus_capability_remote_support": {
      "description": "nexus_capability_remote_support",

```

```

    "type": "boolean"
  },
  "nexus_capability_sso": {
    "description": "nexus_capability_sso",
    "type": "boolean"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "nexus_connection_config",
  "type": "object",
  "properties": {
    "nexus_enabled": {
      "description": "nexus_enabled",
      "type": "boolean"
    },
    "nexus_host": {
      "description": "nexus_host",
      "type": "string"
    },
    "nexus_port": {
      "description": "nexus_port",
      "type": "number"
    },
    "nexus_interval": {
      "description": "nexus_interval",
      "type": "number"
    },
    "nexus_capability_remote_support": {
      "description": "nexus_capability_remote_support",
      "type": "boolean"
    },
    "nexus_capability_sso": {
      "description": "nexus_capability_sso",

```

```

    "type": "boolean"
  }
}
}

```

PATCH

Partial set of the Nexus connection configuration

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "nexus_connection_config_patch",
  "type": "object",
  "properties": {
    "nexus_enabled": {
      "description": "nexus_enabled",
      "type": "boolean"
    },
    "nexus_host": {
      "description": "nexus_host",
      "type": "string"
    },
    "nexus_port": {
      "description": "nexus_port",
      "type": "number"
    },
    "nexus_interval": {
      "description": "nexus_interval",
      "type": "number"
    },
    "nexus_capability_remote_support": {
      "description": "nexus_capability_remote_support",
      "type": "boolean"
    },
    "nexus_capability_sso": {
      "description": "nexus_capability_sso",

```

```
    "type": "boolean"
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "nexus_connection_config",
  "type": "object",
  "properties": {
    "nexus_enabled": {
      "description": "nexus_enabled",
      "type": "boolean"
    },
    "nexus_host": {
      "description": "nexus_host",
      "type": "string"
    },
    "nexus_port": {
      "description": "nexus_port",
      "type": "number"
    },
    "nexus_interval": {
      "description": "nexus_interval",
      "type": "number"
    },
    "nexus_capability_remote_support": {
      "description": "nexus_capability_remote_support",
      "type": "boolean"
    },
    "nexus_capability_sso": {
      "description": "nexus_capability_sso",
      "type": "boolean"
    }
  }
}
```

nexus/registration

Endpoint

/v1/nexus/registration

GET

Retrieve current Nexus registration status

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "nexus_registration_status",
  "type": "object",
  "properties": {
    "nexus_enabled": {
      "description": "nexus_enabled",
      "type": "boolean"
    },
    "registration_status": {
      "type": "string",
      "enum": [
        "NONE",
        "PENDING_REGISTRATION",
        "ERROR_REGISTERING",
        "REGISTERED"
      ],
      "description": "registration_status:\n * `ERROR_REGISTERING` - ERROR_REGISTERING,\n * `NONE` - NONE,\n * `PENDING_REGISTRATION` - PENDING_REGISTRATION,\n * `REGISTERED` - REGISTERED"
    },
    "secret_created_at": {
      "description": "secret_created_at",
```

```
    "type": "string"
  }
}
```

PUT

Register cluster with Nexus using a join key

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "nexus_registration_put",
  "type": "object",
  "properties": {
    "join_key": {
      "description": "join_key",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "nexus_registration_status",
  "type": "object",
```

```

"properties": {
  "nexus_enabled": {
    "description": "nexus_enabled",
    "type": "boolean"
  },
  "registration_status": {
    "type": "string",
    "enum": [
      "NONE",
      "PENDING_REGISTRATION",
      "ERROR_REGISTERING",
      "REGISTERED"
    ],
    "description": "registration_status:\n * `ERROR_REGISTERING` - ERROR_REGISTERING,\n * `NONE` - NONE,\n * `PENDING_REGISTRATION` - PENDING_REGISTRATION,\n * `REGISTERED` - REGISTERED"
  },
  "secret_created_at": {
    "description": "secret_created_at",
    "type": "string"
  }
}
}

```

DELETE

Forget current Nexus registration secrets

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "nexus_registration_status",
  "type": "object",
  "properties": {
    "nexus_enabled": {
      "description": "nexus_enabled",
      "type": "boolean"
    },
    "registration_status": {
      "type": "string",
      "enum": [
        "NONE",
        "PENDING_REGISTRATION",
        "ERROR_REGISTERING",
        "REGISTERED"
      ],
      "description": "registration_status:\n * `ERROR_REGISTERING` - ERROR_REGISTERING,\n * `NONE` - NONE,\n * `PENDING_REGISTRATION` - PENDING_REGISTRATION,\n * `REGISTERED` - REGISTERED"
    },
    "secret_created_at": {
      "description": "secret_created_at",
      "type": "string"
    }
  }
}
```

nexus/registration/rotate

Endpoint

/v1/nexus/registration/rotate

POST

Manually trigger rotation of the Nexus secret

Parameters

This resource has no parameters.

Response

Codes

Code	Description
202	Return value on success

node/state

Endpoint

/v1/node/state

GET

Retrieves node state of the node that the call was made to.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_node_state",
  "type": "object",
  "properties": {
    "node_id": {
      "description": "node-id of the node responding to the get",
      "type": "number"
    },
    "state": {
      "type": "string",
      "enum": [
        "UNCONFIGURED",
        "STOPPED",
        "PAUSED",
        "ACTIVE",
        "REMOVED"
      ],
      "description": "The state of the node:\n * `ACTIVE` - Configured node part of active quorum,\n * `PAUSED` - Configured node part of paused quorum,\n * `REMOVED` - Configured node that has been removed from its cluster,\n * `STOPPED` - Configured node not part of quorum,\n * `UNCONFIGURED` - Unconfigured node"
    }
  }
}
```

```
"cluster_id": {  
  "description": "Unique identifier of cluster the node belongs to or the empty  
string (') if the node is unconfigured",  
  "type": "string"  
}  
}  
}
```

object-storage/add-uris

Endpoint

/v1/object-storage/add-uris

POST

Add new object storage URIs to the list of object storage URIs which point to the location where the system stores object-backed data. If this endpoint is called with URIs which are already in use, the system adds new URIs to the list of object storage URIs and ignores the existing URIs. Although the system does not rebalance data across URIs, it allocates new space to the least-used URIs.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

Response

Codes

Code	Description
200	Return value on success

object-storage/external-credentials-source

Endpoint

/v1/object-storage/external-credentials-source

GET

Retrieve the opaque name of the external credentials store that may be needed for accessing the configured object storage on some platforms. If no external credentials store is configured, then expect an empty string.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{  
  "type": "string"  
}
```

object-storage/uris

Endpoint

/v1/object-storage/uris

GET

Retrieve the list of object storage URIs which point to the location where the system stores object-backed data.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

object-storage/add-uris

Endpoint

/v2/object-storage/add-uris

POST

Add new object storage URIs and corresponding credentials to the available object storage which points to the location where the system stores object-backed data. If this endpoint is called with URIs or credentials which are already in use, the system ignores them. Although the system does not rebalance data across new URIs, it allocates new space to the least-used URIs.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_object_storage_uris_and_credentials",
  "type": "object",
  "properties": {
    "uris": {
      "type": "array",
      "items": {
        "description": "uris",
        "type": "string"
      }
    },
    "maybe_credentials": {
      "type": "array",
      "items": {
        "description": "maybe_credentials",
        "type": "object",
        "properties": {
          "store_name": {
            "description": "store_name",
            "type": "string"
          },
          "access_key_id": {
            "description": "access_key_id",
            "type": "string"
          }
        }
      }
    }
  }
}
```



```
    "secret_access_key": {  
      "description": "secret_access_key",  
      "type": "string",  
      "format": "password"  
    }  
  }  
}
}
```

Response

Codes

Code	Description
200	Return value on success

replication/source-relationships/

Endpoint

/v2/replication/source-relationships/

GET

List existing replication relationships where this cluster is the source.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_source_relationship",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier of the replication relationship",
        "type": "string"
      },
      "target_address": {
        "description": "The target IP address",
        "type": "string"
      },
      "target_port": {
        "description": "Network port to replicate to on the target",
        "type": "number"
      },
      "source_root_id": {
        "description": "File ID of the source directory",
        "type": "string"
      }
    }
  }
}
```

```

"source_root_read_only": {
  "description": "Whether the source directory is read-only",
  "type": "boolean"
},
"map_local_ids_to_nfs_ids": {
  "description": "Whether to map local user/group identities to their associated NFS UID/GID when replicating them to the target cluster. Replication of local identities fails if this option is false",
  "type": "boolean"
},
"replication_enabled": {
  "description": "Whether automatic replication is enabled",
  "type": "boolean"
},
"replication_mode": {
  "type": "string",
  "enum": [
    "REPLICATION_CONTINUOUS",
    "REPLICATION_SNAPSHOT_POLICY",
    "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
  ],
  "description": "Whether to replicate continuously, replicate snapshots from linked snapshot policies, or both:\n * `REPLICATION_CONTINUOUS` - REPLICATION_CONTINUOUS,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHOT_POLICY,\n * `REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
},
"blackout_window_timezone": {
  "description": "The time zone in which the blackout windows should be interpreted (e.g, America/Los_Angeles or UTC)",
  "type": "string"
},
"blackout_windows": {
  "type": "array",
  "items": {
    "description": "List of blackout windows for the relationship",
    "type": "object",
    "properties": {
      "start_hour": {
        "description": "Hour of day [0, 23] at which the blackout window begins",
        "type": "number"
      },
      "start_minute": {
        "description": "Minute of hour [0, 59] at which the blackout window begins",
        "type": "number"
      }
    }
  }
}

```

```

    },
    "end_hour": {
      "description": "Hour of day [0, 23] at which the blackout window ends",
      "type": "number"
    },
    "end_minute": {
      "description": "Minute of hour [0, 59] at which the blackout window ends",
      "type": "number"
    },
    "on_days": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SUNDAY",
          "MONDAY",
          "TUESDAY",
          "WEDNESDAY",
          "THURSDAY",
          "FRIDAY",
          "SATURDAY"
        ]
      },
      "description": "List of days of the week on which the replication schedule applies. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    }
  }
},
"snapshot_policies": {
  "type": "array",
  "items": {
    "description": "List of snapshot policies linked with the relationship along with the corresponding expiration time of the replicated snapshots on the target for each linked policy",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier for the snapshot policy linked with the relationship",
        "type": "number"
      }
    }
  }
}

```

```

    },
    "target_expiration": {
      "description": "Duration after which to expire snapshots on the target cluster that were replicated from this snapshot policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. 'never' indicates snapshots should never expire and 'same_as_policy' indicates snapshots should expire at the same time as the snapshot policy specifies.",
      "type": "string"
    }
  }
}
}
}
}
}
}
}

```

POST

Create a new replication relationship with this cluster as the source. To begin replication, the corresponding relationship on the target cluster must be authorized using the authorize API.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "api_source_create_request",
  "type": "object",
  "properties": {
    "target_address": {
      "description": "The target IP address",
      "type": "string"
    },
    "target_port": {
      "description": "Network port to replicate to on the target (defaults to 3712)",
      "type": "number"
    },
    "source_root_id": {
      "description": "File ID of the source directory if source_root_path is not provided",

```

```

    "type": "string"
  },
  "source_root_path": {
    "description": "Path to the source directory if source_root_id is not provide
d",
    "type": "string"
  },
  "source_root_read_only": {
    "description": "Whether the source directory is read-only (defaults to fals
e)",
    "type": "boolean"
  },
  "map_local_ids_to_nfs_ids": {
    "description": "Whether to map local user/group identities to their associate
d NFS UID/GID when replicating them to the target cluster. Replication of local iden
tities fails if this option is false (defaults to false)",
    "type": "boolean"
  },
  "target_root_path": {
    "description": "Path to the target directory",
    "type": "string"
  },
  "replication_enabled": {
    "description": "Whether to enable automatic replication (defaults to true)",
    "type": "boolean"
  },
  "replication_mode": {
    "type": "string",
    "enum": [
      "REPLICATION_CONTINUOUS",
      "REPLICATION_SNAPSHOT_POLICY",
      "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
    ],
    "description": "Whether to replicate continuously, replicate snapshots from li
nked snapshot policies, or both (defaults to continuous):\n * `REPLICATION_CONTINUOU
S` - REPLICATION_CONTINUOUS,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHO
T_POLICY,\n * `REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHO
T_POLICY_WITH_CONTINUOUS"
  },
  "blackout_window_timezone": {
    "description": "The time zone in which the blackout windows should be interpre
ted (e.g., America/Los_Angeles or UTC)",
    "type": "string"
  },
  "blackout_windows": {
    "type": "array",

```

```

    "items": {
      "description": "List of blackout windows for the relationship (defaults to empty)",
      "type": "object",
      "properties": {
        "start_hour": {
          "description": "Hour of day [0, 23] at which the blackout window begins",
          "type": "number"
        },
        "start_minute": {
          "description": "Minute of hour [0, 59] at which the blackout window begins",
          "type": "number"
        },
        "end_hour": {
          "description": "Hour of day [0, 23] at which the blackout window ends",
          "type": "number"
        },
        "end_minute": {
          "description": "Minute of hour [0, 59] at which the blackout window ends",
          "type": "number"
        },
        "on_days": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": [
              "SUNDAY",
              "MONDAY",
              "TUESDAY",
              "WEDNESDAY",
              "THURSDAY",
              "FRIDAY",
              "SATURDAY"
            ]
          },
          "description": "List of days of the week on which the replication schedule applies. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
        }
      }
    }
  }
}

```

```

},
"snapshot_policies": {
  "type": "array",
  "items": {
    "description": "List of snapshot policies linked with the relationship along with the corresponding expiration time to live for replicated target snapshots for each linked policy (defaults to empty)",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier for the snapshot policy linked with the relationship",
        "type": "number"
      },
      "target_expiration": {
        "description": "Duration after which to expire snapshots on the target cluster that were replicated from this snapshot policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. 'never' indicates snapshots should never expire and 'same_as_policy' indicates snapshots should expire at the same time as the snapshot policy specifies.",
        "type": "string"
      }
    }
  }
}
}
}
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_source_relationship",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",

```



```

    "type": "string"
  },
  "target_address": {
    "description": "The target IP address",
    "type": "string"
  },
  "target_port": {
    "description": "Network port to replicate to on the target",
    "type": "number"
  },
  "source_root_id": {
    "description": "File ID of the source directory",
    "type": "string"
  },
  "source_root_read_only": {
    "description": "Whether the source directory is read-only",
    "type": "boolean"
  },
  "map_local_ids_to_nfs_ids": {
    "description": "Whether to map local user/group identities to their associated NFS UID/GID when replicating them to the target cluster. Replication of local identities fails if this option is false",
    "type": "boolean"
  },
  "replication_enabled": {
    "description": "Whether automatic replication is enabled",
    "type": "boolean"
  },
  "replication_mode": {
    "type": "string",
    "enum": [
      "REPLICATION_CONTINUOUS",
      "REPLICATION_SNAPSHOT_POLICY",
      "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
    ],
    "description": "Whether to replicate continuously, replicate snapshots from linked snapshot policies, or both:\n * `REPLICATION_CONTINUOUS` - REPLICATION_CONTINUOUS,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHOT_POLICY,\n * `REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
  },
  "blackout_window_timezone": {
    "description": "The time zone in which the blackout windows should be interpreted (e.g, America/Los_Angeles or UTC)",
    "type": "string"
  },
  "blackout_windows": {

```

```

"type": "array",
"items": {
  "description": "List of blackout windows for the relationship",
  "type": "object",
  "properties": {
    "start_hour": {
      "description": "Hour of day [0, 23] at which the blackout window begin
s",
      "type": "number"
    },
    "start_minute": {
      "description": "Minute of hour [0, 59] at which the blackout window begi
ns",
      "type": "number"
    },
    "end_hour": {
      "description": "Hour of day [0, 23] at which the blackout window ends",
      "type": "number"
    },
    "end_minute": {
      "description": "Minute of hour [0, 59] at which the blackout window end
s",
      "type": "number"
    },
    "on_days": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SUNDAY",
          "MONDAY",
          "TUESDAY",
          "WEDNESDAY",
          "THURSDAY",
          "FRIDAY",
          "SATURDAY"
        ],
        "description": "List of days of the week on which the replication sche
dule applies. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can b
e used to specify all days.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATU
RDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` -
TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
      }
    }
  }
}

```

```

    },
    "snapshot_policies": {
      "type": "array",
      "items": {
        "description": "List of snapshot policies linked with the relationship along with the corresponding expiration time of the replicated snapshots on the target for each linked policy",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique identifier for the snapshot policy linked with the relationship",
            "type": "number"
          },
          "target_expiration": {
            "description": "Duration after which to expire snapshots on the target cluster that were replicated from this snapshot policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. 'never' indicates snapshots should never expire and 'same_as_policy' indicates snapshots should expire at the same time as the snapshot policy specifies.",
            "type": "string"
          }
        }
      }
    }
  }
}

```

replication/source-relationships/reverse-target-relationship

Endpoint

`/v2/replication/source-relationships/reverse-target-relationship`

POST

Reverse source and target for the specified replication relationship. This operation is initiated on the target cluster. The previous target directory will be made the new source, and the previous source directory will be made the new target. Any relationship configurations on the source will be retained, and any configurations on the target that have been retained from a previous reversal will be reapplied. To resume replication after reversal, edit any relationship configurations if desired and reconnect the relationship from the new target cluster.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_reverse_request",
  "type": "object",
  "properties": {
    "target_relationship_id": {
      "description": "The identifier of the target relationship to reverse",
      "type": "string"
    },
    "source_address": {
      "description": "The IP address of the source cluster",
      "type": "string"
    },
    "source_port": {
      "description": "Network port of the source cluster (defaults to 3712)",
      "type": "number"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_source_relationship",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "target_address": {
      "description": "The target IP address",
      "type": "string"
    },
    "target_port": {
      "description": "Network port to replicate to on the target",
      "type": "number"
    },
    "source_root_id": {
      "description": "File ID of the source directory",
      "type": "string"
    },
    "source_root_read_only": {
      "description": "Whether the source directory is read-only",
      "type": "boolean"
    },
    "map_local_ids_to_nfs_ids": {
      "description": "Whether to map local user/group identities to their associated NFS UID/GID when replicating them to the target cluster. Replication of local identities fails if this option is false",
      "type": "boolean"
    },
    "replication_enabled": {
      "description": "Whether automatic replication is enabled",
      "type": "boolean"
    },
    "replication_mode": {
      "type": "string",
    }
  }
}
```

```

    "enum": [
      "REPLICATION_CONTINUOUS",
      "REPLICATION_SNAPSHOT_POLICY",
      "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
    ],
    "description": "Whether to replicate continuously, replicate snapshots from linked snapshot policies, or both:\n * `REPLICATION_CONTINUOUS` - REPLICATION_CONTINUOUS,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHOT_POLICY,\n * `REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
  },
  "blackout_window_timezone": {
    "description": "The time zone in which the blackout windows should be interpreted (e.g, America/Los_Angeles or UTC)",
    "type": "string"
  },
  "blackout_windows": {
    "type": "array",
    "items": {
      "description": "List of blackout windows for the relationship",
      "type": "object",
      "properties": {
        "start_hour": {
          "description": "Hour of day [0, 23] at which the blackout window begins",
          "type": "number"
        },
        "start_minute": {
          "description": "Minute of hour [0, 59] at which the blackout window begins",
          "type": "number"
        },
        "end_hour": {
          "description": "Hour of day [0, 23] at which the blackout window ends",
          "type": "number"
        },
        "end_minute": {
          "description": "Minute of hour [0, 59] at which the blackout window ends",
          "type": "number"
        },
        "on_days": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": [
              "SUNDAY",

```

```

        "MONDAY",
        "TUESDAY",
        "WEDNESDAY",
        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
    ],
    "description": "List of days of the week on which the replication sche
dule applies. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can b
e used to specify all days.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATU
RDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` -
TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    }
}
},
"snapshot_policies": {
    "type": "array",
    "items": {
        "description": "List of snapshot policies linked with the relationship along
with the corresponding expiration time of the replicated snapshots on the target f
or each linked policy",
        "type": "object",
        "properties": {
            "id": {
                "description": "Unique identifier for the snapshot policy linked with th
e relationship",
                "type": "number"
            },
            "target_expiration": {
                "description": "Duration after which to expire snapshots on the target c
luster that were replicated from this snapshot policy, in format <quantity><units>,
where <quantity> is a positive integer less than 100 and <units> is one of [months,
weeks, days, hours, minutes], e.g. 5days or 1hours. 'never' indicates snapshots shou
ld never expire and 'same_as_policy' indicates snapshots should expire at the same t
ime as the snapshot policy specifies.",
                "type": "string"
            }
        }
    }
}
}
}
}
}

```

replication/source-relationships/status/

Endpoint

/v2/replication/source-relationships/status/

GET

List statuses for all existing replication relationships where this cluster is the source.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_source_relationship_status",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier of the replication relationship",
        "type": "string"
      },
      "target_address": {
        "description": "The target IP address",
        "type": "string"
      },
      "target_port": {
        "description": "Network port to replicate to on the target",
        "type": "number"
      },
      "source_root_read_only": {
        "description": "Whether the source directory is read-only",
        "type": "boolean"
      }
    }
  }
}
```



```

    "map_local_ids_to_nfs_ids": {
      "description": "Whether to map local user/group identities to their associated NFS UID/GID when replicating them to the target cluster. Replication of local identities fails if this option is False.",
      "type": "boolean"
    },
    "replication_enabled": {
      "description": "Whether automatic replication is enabled",
      "type": "boolean"
    },
    "replication_mode": {
      "type": "string",
      "enum": [
        "REPLICATION_CONTINUOUS",
        "REPLICATION_SNAPSHOT_POLICY",
        "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
      ],
      "description": "Whether to replicate continuously, replicate snapshots from linked snapshot policies, or both:\n * `REPLICATION_CONTINUOUS` - REPLICATION_CONTINUOUS,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHOT_POLICY,\n * `REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
    },
    "blackout_window_timezone": {
      "description": "The time zone in which the blackout windows should be interpreted (e.g, America/Los_Angeles or UTC)",
      "type": "string"
    },
    "blackout_windows": {
      "type": "array",
      "items": {
        "description": "List of blackout windows for the relationship",
        "type": "object",
        "properties": {
          "start_hour": {
            "description": "Hour of day [0, 23] at which the blackout window begins",
            "type": "number"
          },
          "start_minute": {
            "description": "Minute of hour [0, 59] at which the blackout window begins",
            "type": "number"
          },
          "end_hour": {
            "description": "Hour of day [0, 23] at which the blackout window ends",
            "type": "number"
          }
        }
      }
    }
  }

```

```

        "type": "number"
    },
    "end_minute": {
        "description": "Minute of hour [0, 59] at which the blackout window ends",
        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ],
            "description": "List of days of the week on which the replication schedule applies. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
        }
    }
},
"snapshot_policies": {
    "type": "array",
    "items": {
        "description": "List of snapshot policies linked with the relationship along with the corresponding expiration time of the replicated snapshots on the target for each linked policy",
        "type": "object",
        "properties": {
            "id": {
                "description": "Unique identifier for the snapshot policy linked with the relationship",
                "type": "number"
            },
            "target_expiration": {
                "description": "Duration after which to expire snapshots on the target cluster that were replicated from this snapshot policy, in format <quantity><unit>"
            }
        }
    }
}

```

s>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. 'never' indicates snapshots should never expire and 'same_as_policy' indicates snapshots should expire at the same time as the snapshot policy specifies.",

```
    "type": "string"
  }
}
},
"state": {
  "type": "string",
  "enum": [
    "AWAITING_AUTHORIZATION",
    "DISCONNECTED",
    "DISCONNECTING",
    "ENDED",
    "ESTABLISHED",
    "RECONNECTING",
    "REESTABLISHING"
  ],
  "description": "Current state of replication relationship:\n * `AWAITING_AUTHORIZATION` - AWAITING_AUTHORIZATION,\n * `DISCONNECTED` - DISCONNECTED,\n * `DISCONNECTING` - DISCONNECTING,\n * `ENDED` - ENDED,\n * `ESTABLISHED` - ESTABLISHED,\n * `RECONNECTING` - RECONNECTING,\n * `REESTABLISHING` - REESTABLISHING"
},
"end_reason": {
  "description": "If the relationship has ENDED, this states the reason. Otherwise, this field is empty",
  "type": "string"
},
"source_cluster_name": {
  "description": "Name of the source cluster",
  "type": "string"
},
"source_cluster_uuid": {
  "description": "UUID of the source cluster",
  "type": "string"
},
"source_root_path": {
  "description": "Path to the source directory",
  "type": "string"
},
"target_cluster_name": {
  "description": "Name of the target cluster",
  "type": "string"
},
},
```

```

"target_cluster_uuid": {
  "description": "UUID of the target cluster",
  "type": "string"
},
"target_root_path": {
  "description": "Path to the target directory",
  "type": "string"
},
"target_root_read_only": {
  "description": "Whether the target directory is read-only",
  "type": "boolean"
},
"job_state": {
  "type": "string",
  "enum": [
    "REPLICATION_NOT_RUNNING",
    "REPLICATION_RUNNING"
  ],
  "description": "Current state of the job:\n * `REPLICATION_NOT_RUNNING` - REPLICATION_NOT_RUNNING,\n * `REPLICATION_RUNNING` - REPLICATION_RUNNING"
},
"job_start_time": {
  "description": "If the job state is REPLICATION_RUNNING, this is the time th
at the job started, encoded as RFC 3339",
  "type": "string"
},
"recovery_point": {
  "description": "The time that the last successful job started, encoded as RF
C 3339",
  "type": "string"
},
"error_from_last_job": {
  "description": "The error message from the previous job. If the previous jo
b succeeded or no job has ever run, this field will be empty",
  "type": "string"
},
"duration_of_last_job": {
  "description": "The elapsed execution time of the previous job, in nanosecon
ds. If no job has ever run, this field will be null.",
  "type": "object",
  "properties": {
    "nanoseconds": {
      "description": "nanoseconds",
      "type": "string"
    }
  }
}

```

```

    },
    "source_root_id": {
      "description": "File ID of the source directory",
      "type": "string"
    },
    },
    "next_active_time": {
      "description": "The time when the current blackout period ends (in UTC). If
replication is currently enabled and not in a blackout period, this field will be empty",
      "type": "string"
    },
    },
    "replication_job_status": {
      "description": "Information about the progress of a job. This field is null
if there is no job status available.",
      "type": "object",
      "properties": {
        "percent_complete": {
          "description": "Percent of way through the job, computed from a weightin
g of data and files processed",
          "type": "number"
        },
        },
        "estimated_seconds_remaining": {
          "description": "Estimated number of seconds remaining in the job, derive
d from percent_complete. This may be null if there is no estimate.",
          "type": "string"
        },
        },
        "bytes_transferred": {
          "description": "Number of bytes copied",
          "type": "string"
        },
        },
        "bytes_unchanged": {
          "description": "Number of bytes not copied because they didn't change",
          "type": "string"
        },
        },
        "bytes_remaining": {
          "description": "Number of bytes left to be processed in order to complet
e this job",
          "type": "string"
        },
        },
        "bytes_deleted": {
          "description": "Number of bytes deleted",
          "type": "string"
        },
        },
        "bytes_total": {
          "description": "Total number of bytes that will be processed during thi
s job (this will be close but not exact)",

```

```

        "type": "string"
    },
    "files_transferred": {
        "description": "Number of files copied",
        "type": "string"
    },
    "files_unchanged": {
        "description": "Number of files not copied because they didn't change",
        "type": "string"
    },
    "files_remaining": {
        "description": "Number of files left to be processed in order to complete this job",
        "type": "string"
    },
    "files_deleted": {
        "description": "Number of files deleted",
        "type": "string"
    },
    "files_total": {
        "description": "Total number of files that will be processed during this job (this will be close but not exact)",
        "type": "string"
    },
    "throughput_overall": {
        "description": "Overall average throughput in bytes per second of data copied since the beginning of the job",
        "type": "string"
    },
    "throughput_current": {
        "description": "Average throughput in bytes per second of data copied in the last one minute",
        "type": "string"
    }
},
"queued_snapshot_count": {
    "description": "The number of snapshots from linked snapshot policies awaiting replication by this relationship",
    "type": "number"
},
"recovery_point_snapshot": {
    "description": "The snapshot replicated by the last successful job. This field is null if no job has ever run successfully.",
    "type": "object",
    "properties": {

```

```

    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_file_id": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "in_delete": {
      "description": "Whether or not the snapshot is in the process of being deleted",
      "type": "boolean"
    }
  },
  "replicating_snapshot": {
    "description": "The snapshot that is being replicated by the current job. This field is null if no job is in progress.",
    "type": "object",
    "properties": {

```

```

    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_file_id": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "in_delete": {
      "description": "Whether or not the snapshot is in the process of being deleted",
      "type": "boolean"
    }
  }
}
}
}
}
}

```


replication/source-relationships/{id}

Endpoint

/v2/replication/source-relationships/{id}

GET

Get information about the specified replication relationship where this cluster is the source.

Parameters

Name	Description	Required
id	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_source_relationship",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "target_address": {
      "description": "The target IP address",
      "type": "string"
    },
    "target_port": {
      "description": "Network port to replicate to on the target",
      "type": "number"
    },
    "source_root_id": {
      "description": "File ID of the source directory",
      "type": "string"
    }
  }
}
```

```

},
"source_root_read_only": {
  "description": "Whether the source directory is read-only",
  "type": "boolean"
},
"map_local_ids_to_nfs_ids": {
  "description": "Whether to map local user/group identities to their associated NFS UID/GID when replicating them to the target cluster. Replication of local identities fails if this option is false",
  "type": "boolean"
},
"replication_enabled": {
  "description": "Whether automatic replication is enabled",
  "type": "boolean"
},
"replication_mode": {
  "type": "string",
  "enum": [
    "REPLICATION_CONTINUOUS",
    "REPLICATION_SNAPSHOT_POLICY",
    "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
  ],
  "description": "Whether to replicate continuously, replicate snapshots from linked snapshot policies, or both:\n * `REPLICATION_CONTINUOUS` - REPLICATION_CONTINUOUS,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHOT_POLICY,\n * `REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
},
"blackout_window_timezone": {
  "description": "The time zone in which the blackout windows should be interpreted (e.g, America/Los_Angeles or UTC)",
  "type": "string"
},
"blackout_windows": {
  "type": "array",
  "items": {
    "description": "List of blackout windows for the relationship",
    "type": "object",
    "properties": {
      "start_hour": {
        "description": "Hour of day [0, 23] at which the blackout window begins",
        "type": "number"
      },
      "start_minute": {
        "description": "Minute of hour [0, 59] at which the blackout window begins",

```

```

        "type": "number"
    },
    "end_hour": {
        "description": "Hour of day [0, 23] at which the blackout window ends",
        "type": "number"
    },
    "end_minute": {
        "description": "Minute of hour [0, 59] at which the blackout window end
s",
        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ],
            "description": "List of days of the week on which the replication sche
dule applies. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can b
e used to specify all days.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATU
RDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` -
TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
        }
    }
},
"snapshot_policies": {
    "type": "array",
    "items": {
        "description": "List of snapshot policies linked with the relationship alon
g with the corresponding expiration time of the replicated snapshots on the target f
or each linked policy",
        "type": "object",
        "properties": {
            "id": {
                "description": "Unique identifier for the snapshot policy linked with th
e relationship",
                "type": "number"
            }
        }
    }
}

```

```
{
  "target_expiration": {
    "description": "Duration after which to expire snapshots on the target cluster that were replicated from this snapshot policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. 'never' indicates snapshots should never expire and 'same_as_policy' indicates snapshots should expire at the same time as the snapshot policy specifies.",
    "type": "string"
  }
}
```

PUT

Modify an existing replication relationship where this cluster is the source.

Parameters

Name	Description	Required
id	Relationship identifier	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_source_relationship",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "target_address": {
      "description": "The target IP address",
      "type": "string"
    },
    "target_port": {
```

```

    "description": "Network port to replicate to on the target",
    "type": "number"
  },
  "source_root_id": {
    "description": "File ID of the source directory",
    "type": "string"
  },
  "source_root_read_only": {
    "description": "Whether the source directory is read-only",
    "type": "boolean"
  },
  "map_local_ids_to_nfs_ids": {
    "description": "Whether to map local user/group identities to their associated NFS UID/GID when replicating them to the target cluster. Replication of local identities fails if this option is false",
    "type": "boolean"
  },
  "replication_enabled": {
    "description": "Whether automatic replication is enabled",
    "type": "boolean"
  },
  "replication_mode": {
    "type": "string",
    "enum": [
      "REPLICATION_CONTINUOUS",
      "REPLICATION_SNAPSHOT_POLICY",
      "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
    ],
    "description": "Whether to replicate continuously, replicate snapshots from linked snapshot policies, or both:\n * `REPLICATION_CONTINUOUS` - REPLICATION_CONTINUOUS,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHOT_POLICY,\n * `REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
  },
  "blackout_window_timezone": {
    "description": "The time zone in which the blackout windows should be interpreted (e.g, America/Los_Angeles or UTC)",
    "type": "string"
  },
  "blackout_windows": {
    "type": "array",
    "items": {
      "description": "List of blackout windows for the relationship",
      "type": "object",
      "properties": {
        "start_hour": {
          "description": "Hour of day [0, 23] at which the blackout window begin"
        }
      }
    }
  }
}

```

```

s",
    "type": "number"
},
"start_minute": {
    "description": "Minute of hour [0, 59] at which the blackout window begins",
    "type": "number"
},
"end_hour": {
    "description": "Hour of day [0, 23] at which the blackout window ends",
    "type": "number"
},
"end_minute": {
    "description": "Minute of hour [0, 59] at which the blackout window ends",
    "type": "number"
},
"on_days": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "SUNDAY",
            "MONDAY",
            "TUESDAY",
            "WEDNESDAY",
            "THURSDAY",
            "FRIDAY",
            "SATURDAY"
        ]
    },
    "description": "List of days of the week on which the replication schedule applies. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
}
}
},
"snapshot_policies": {
    "type": "array",
    "items": {
        "description": "List of snapshot policies linked with the relationship along with the corresponding expiration time of the replicated snapshots on the target for each linked policy",

```

```

    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier for the snapshot policy linked with the relationship",
        "type": "number"
      },
      "target_expiration": {
        "description": "Duration after which to expire snapshots on the target cluster that were replicated from this snapshot policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. 'never' indicates snapshots should never expire and 'same_as_policy' indicates snapshots should expire at the same time as the snapshot policy specifies.",
        "type": "string"
      }
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_source_relationship",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "target_address": {
      "description": "The target IP address",
      "type": "string"
    },
    "target_port": {

```

```

    "description": "Network port to replicate to on the target",
    "type": "number"
  },
  "source_root_id": {
    "description": "File ID of the source directory",
    "type": "string"
  },
  "source_root_read_only": {
    "description": "Whether the source directory is read-only",
    "type": "boolean"
  },
  "map_local_ids_to_nfs_ids": {
    "description": "Whether to map local user/group identities to their associated NFS UID/GID when replicating them to the target cluster. Replication of local identities fails if this option is false",
    "type": "boolean"
  },
  "replication_enabled": {
    "description": "Whether automatic replication is enabled",
    "type": "boolean"
  },
  "replication_mode": {
    "type": "string",
    "enum": [
      "REPLICATION_CONTINUOUS",
      "REPLICATION_SNAPSHOT_POLICY",
      "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
    ],
    "description": "Whether to replicate continuously, replicate snapshots from linked snapshot policies, or both:\n * `REPLICATION_CONTINUOUS` - REPLICATION_CONTINUOUS,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHOT_POLICY,\n * `REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
  },
  "blackout_window_timezone": {
    "description": "The time zone in which the blackout windows should be interpreted (e.g, America/Los_Angeles or UTC)",
    "type": "string"
  },
  "blackout_windows": {
    "type": "array",
    "items": {
      "description": "List of blackout windows for the relationship",
      "type": "object",
      "properties": {
        "start_hour": {
          "description": "Hour of day [0, 23] at which the blackout window begin"
        }
      }
    }
  }
}

```



```

s",
    "type": "number"
},
"start_minute": {
    "description": "Minute of hour [0, 59] at which the blackout window begins",
    "type": "number"
},
"end_hour": {
    "description": "Hour of day [0, 23] at which the blackout window ends",
    "type": "number"
},
"end_minute": {
    "description": "Minute of hour [0, 59] at which the blackout window ends",
    "type": "number"
},
"on_days": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "SUNDAY",
            "MONDAY",
            "TUESDAY",
            "WEDNESDAY",
            "THURSDAY",
            "FRIDAY",
            "SATURDAY"
        ]
    },
    "description": "List of days of the week on which the replication schedule applies. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
}
}
},
"snapshot_policies": {
    "type": "array",
    "items": {
        "description": "List of snapshot policies linked with the relationship along with the corresponding expiration time of the replicated snapshots on the target for each linked policy",

```

```

    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier for the snapshot policy linked with the relationship",
        "type": "number"
      },
      "target_expiration": {
        "description": "Duration after which to expire snapshots on the target cluster that were replicated from this snapshot policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. 'never' indicates snapshots should never expire and 'same_as_policy' indicates snapshots should expire at the same time as the snapshot policy specifies.",
        "type": "string"
      }
    }
  }
}

```

DELETE

Delete the specified replication relationship where this cluster is the source.

Parameters

Name	Description	Required
id	Relationship identifier	Yes
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

Modify a subset of fields of an existing replication relationship where this cluster is the source.

Parameters

Name	Description	Required
<code>id</code>	Relationship identifier	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_source_relationship",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "target_address": {
      "description": "The target IP address",
      "type": "string"
    },
    "target_port": {
      "description": "Network port to replicate to on the target",
      "type": "number"
    },
    "source_root_id": {
      "description": "File ID of the source directory",
      "type": "string"
    },
    "source_root_read_only": {
      "description": "Whether the source directory is read-only",
      "type": "boolean"
    },
    "map_local_ids_to_nfs_ids": {
      "description": "Whether to map local user/group identities to their associated NFS UID/GID when replicating them to the target cluster. Replication of local identities fails if this option is false",
      "type": "boolean"
    },
    "replication_enabled": {
      "description": "Whether automatic replication is enabled",
      "type": "boolean"
    }
  }
}
```

```

"replication_mode": {
  "type": "string",
  "enum": [
    "REPLICATION_CONTINUOUS",
    "REPLICATION_SNAPSHOT_POLICY",
    "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
  ],
  "description": "Whether to replicate continuously, replicate snapshots from li
nked snapshot policies, or both:\n * `REPLICATION_CONTINUOUS` - REPLICATION_CONTINUO
US,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHOT_POLICY,\n * `REPLICATIO
N_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
},
"blackout_window_timezone": {
  "description": "The time zone in which the blackout windows should be interpre
ted (e.g, America/Los_Angeles or UTC)",
  "type": "string"
},
"blackout_windows": {
  "type": "array",
  "items": {
    "description": "List of blackout windows for the relationship",
    "type": "object",
    "properties": {
      "start_hour": {
        "description": "Hour of day [0, 23] at which the blackout window begin
s",
        "type": "number"
      },
      "start_minute": {
        "description": "Minute of hour [0, 59] at which the blackout window begi
ns",
        "type": "number"
      },
      "end_hour": {
        "description": "Hour of day [0, 23] at which the blackout window ends",
        "type": "number"
      },
      "end_minute": {
        "description": "Minute of hour [0, 59] at which the blackout window end
s",
        "type": "number"
      },
      "on_days": {
        "type": "array",
        "items": {
          "type": "string",

```


Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_source_relationship",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "target_address": {
      "description": "The target IP address",
      "type": "string"
    },
    "target_port": {
      "description": "Network port to replicate to on the target",
      "type": "number"
    },
    "source_root_id": {
      "description": "File ID of the source directory",
      "type": "string"
    },
    "source_root_read_only": {
      "description": "Whether the source directory is read-only",
      "type": "boolean"
    },
    "map_local_ids_to_nfs_ids": {
      "description": "Whether to map local user/group identities to their associated NFS UID/GID when replicating them to the target cluster. Replication of local identities fails if this option is false",
      "type": "boolean"
    },
    "replication_enabled": {
      "description": "Whether automatic replication is enabled",
      "type": "boolean"
    },
    "replication_mode": {
      "type": "string",
    }
  }
}
```

```

    "enum": [
      "REPLICATION_CONTINUOUS",
      "REPLICATION_SNAPSHOT_POLICY",
      "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
    ],
    "description": "Whether to replicate continuously, replicate snapshots from linked snapshot policies, or both:\n * `REPLICATION_CONTINUOUS` - REPLICATION_CONTINUOUS,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHOT_POLICY,\n * `REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS",
  },
  "blackout_window_timezone": {
    "description": "The time zone in which the blackout windows should be interpreted (e.g, America/Los_Angeles or UTC)",
    "type": "string"
  },
  "blackout_windows": {
    "type": "array",
    "items": {
      "description": "List of blackout windows for the relationship",
      "type": "object",
      "properties": {
        "start_hour": {
          "description": "Hour of day [0, 23] at which the blackout window begins",
          "type": "number"
        },
        "start_minute": {
          "description": "Minute of hour [0, 59] at which the blackout window begins",
          "type": "number"
        },
        "end_hour": {
          "description": "Hour of day [0, 23] at which the blackout window ends",
          "type": "number"
        },
        "end_minute": {
          "description": "Minute of hour [0, 59] at which the blackout window ends",
          "type": "number"
        },
        "on_days": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": [
              "SUNDAY",

```


replication/source-relationships/{id}/abort-replication

Endpoint

`/v2/replication/source-relationships/{id}/abort-replication`

POST

Abort any ongoing replication work for the specified replication relationship where this cluster is the source.

Parameters

Name	Description	Required
<code>id</code>	Relationship identifier	Yes
<code>skip-active-policy-snapshot</code>	If set to true and the currently replicating snapshot was created by a policy, the next replication job will use the next queued snapshot instead of retrying the current one. Defaults to false if not specified.	No

Response

Codes

Code	Description
200	Return value on success

replication/source-relationships/{id}/dismiss-error

Endpoint

`/v2/replication/source-relationships/{id}/dismiss-error`

POST

Clear the error associated with this source relationship's last replication attempt, if one exists.

Parameters

Name	Description	Required
<code>id</code>	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

replication/source-relationships/{id}/queued-snapshots/

Endpoint

/v2/replication/source-relationships/{id}/queued-snapshots/

GET

List information for all snapshots awaiting replication by the specified relationship.

Parameters

Name	Description	Required
id	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_queued_replication_snapshots",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of information of snapshots awaiting replication",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique identifier of the snapshot",
            "type": "number"
          },
          "name": {
            "description": "Name of the snapshot",
            "type": "string"
          }
        }
      }
    }
  }
}
```

```

    },
    "timestamp": {
        "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
        "type": "string"
    },
    "directory_name": {
        "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
        "type": "string"
    },
    "source_file_id": {
        "description": "Source directory of the snapshot",
        "type": "string"
    },
    "created_by_policy": {
        "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
        "type": "boolean"
    },
    "in_delete": {
        "description": "Whether or not the snapshot is in the process of being deleted",
        "type": "boolean"
    },
    "expiration": {
        "description": "Time at which snapshot will be expired on the source cluster. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
        "type": "string"
    },
    "target_expiration": {
        "description": "Time at which snapshot will be expired on the target cluster. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
        "type": "string"
    },
    "policy_id": {
        "description": "Unique identifier of the policy that created this snapshot",
        "type": "number"
    }
}

```

```
}  
}  
}
```

replication/source-relationships/{id}/replicate

Endpoint

/v2/replication/source-relationships/{id}/replicate

POST

Replicate from the source to the target of the specified replication relationship where this cluster is the source.

Parameters

Name	Description	Required
id	Relationship identifier	Yes

Response

Codes

Code	Description
202	Return value on success

replication/source-relationships/{id}/status

Endpoint

/v2/replication/source-relationships/{id}/status

GET

Get current status of the specified replication relationship where this cluster is the source.

Parameters

Name	Description	Required
id	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_source_relationship_status",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "target_address": {
      "description": "The target IP address",
      "type": "string"
    },
    "target_port": {
      "description": "Network port to replicate to on the target",
      "type": "number"
    },
    "source_root_read_only": {
      "description": "Whether the source directory is read-only",
      "type": "boolean"
    }
  }
}
```

```

},
"map_local_ids_to_nfs_ids": {
  "description": "Whether to map local user/group identities to their associated NFS UID/GID when replicating them to the target cluster. Replication of local identities fails if this option is False.",
  "type": "boolean"
},
"replication_enabled": {
  "description": "Whether automatic replication is enabled",
  "type": "boolean"
},
"replication_mode": {
  "type": "string",
  "enum": [
    "REPLICATION_CONTINUOUS",
    "REPLICATION_SNAPSHOT_POLICY",
    "REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
  ],
  "description": "Whether to replicate continuously, replicate snapshots from linked snapshot policies, or both:\n * `REPLICATION_CONTINUOUS` - REPLICATION_CONTINUOUS,\n * `REPLICATION_SNAPSHOT_POLICY` - REPLICATION_SNAPSHOT_POLICY,\n * `REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS` - REPLICATION_SNAPSHOT_POLICY_WITH_CONTINUOUS"
},
"blackout_window_timezone": {
  "description": "The time zone in which the blackout windows should be interpreted (e.g, America/Los_Angeles or UTC)",
  "type": "string"
},
"blackout_windows": {
  "type": "array",
  "items": {
    "description": "List of blackout windows for the relationship",
    "type": "object",
    "properties": {
      "start_hour": {
        "description": "Hour of day [0, 23] at which the blackout window begins",
        "type": "number"
      },
      "start_minute": {
        "description": "Minute of hour [0, 59] at which the blackout window begins",
        "type": "number"
      },
      "end_hour": {
        "description": "Hour of day [0, 23] at which the blackout window ends",

```



```

        "type": "number"
    },
    "end_minute": {
        "description": "Minute of hour [0, 59] at which the blackout window ends",
        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ],
            "description": "List of days of the week on which the replication schedule applies. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
        }
    }
},
"snapshot_policies": {
    "type": "array",
    "items": {
        "description": "List of snapshot policies linked with the relationship along with the corresponding expiration time of the replicated snapshots on the target for each linked policy",
        "type": "object",
        "properties": {
            "id": {
                "description": "Unique identifier for the snapshot policy linked with the relationship",
                "type": "number"
            },
            "target_expiration": {
                "description": "Duration after which to expire snapshots on the target cluster that were replicated from this snapshot policy, in format <quantity><units>,"
            }
        }
    }
}

```

where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. 'never' indicates snapshots should never expire and 'same_as_policy' indicates snapshots should expire at the same time as the snapshot policy specifies.",

```
    "type": "string"
  }
}
},
"state": {
  "type": "string",
  "enum": [
    "AWAITING_AUTHORIZATION",
    "DISCONNECTED",
    "DISCONNECTING",
    "ENDED",
    "ESTABLISHED",
    "RECONNECTING",
    "REESTABLISHING"
  ],
  "description": "Current state of replication relationship:\n * `AWAITING_AUTHORIZATION` - AWAITING_AUTHORIZATION,\n * `DISCONNECTED` - DISCONNECTED,\n * `DISCONNECTING` - DISCONNECTING,\n * `ENDED` - ENDED,\n * `ESTABLISHED` - ESTABLISHED,\n * `RECONNECTING` - RECONNECTING,\n * `REESTABLISHING` - REESTABLISHING"
},
"end_reason": {
  "description": "If the relationship has ENDED, this states the reason. Otherwise, this field is empty",
  "type": "string"
},
"source_cluster_name": {
  "description": "Name of the source cluster",
  "type": "string"
},
"source_cluster_uuid": {
  "description": "UUID of the source cluster",
  "type": "string"
},
"source_root_path": {
  "description": "Path to the source directory",
  "type": "string"
},
"target_cluster_name": {
  "description": "Name of the target cluster",
  "type": "string"
},
},
```

```

"target_cluster_uuid": {
  "description": "UUID of the target cluster",
  "type": "string"
},
"target_root_path": {
  "description": "Path to the target directory",
  "type": "string"
},
"target_root_read_only": {
  "description": "Whether the target directory is read-only",
  "type": "boolean"
},
"job_state": {
  "type": "string",
  "enum": [
    "REPLICATION_NOT_RUNNING",
    "REPLICATION_RUNNING"
  ],
  "description": "Current state of the job:\n * `REPLICATION_NOT_RUNNING` - REPLICATION_NOT_RUNNING,\n * `REPLICATION_RUNNING` - REPLICATION_RUNNING"
},
"job_start_time": {
  "description": "If the job state is REPLICATION_RUNNING, this is the time that the job started, encoded as RFC 3339",
  "type": "string"
},
"recovery_point": {
  "description": "The time that the last successful job started, encoded as RFC 3339",
  "type": "string"
},
"error_from_last_job": {
  "description": "The error message from the previous job. If the previous job succeeded or no job has ever run, this field will be empty",
  "type": "string"
},
"duration_of_last_job": {
  "description": "The elapsed execution time of the previous job, in nanoseconds. If no job has ever run, this field will be null.",
  "type": "object",
  "properties": {
    "nanoseconds": {
      "description": "nanoseconds",
      "type": "string"
    }
  }
}

```

```

},
"source_root_id": {
  "description": "File ID of the source directory",
  "type": "string"
},
"next_active_time": {
  "description": "The time when the current blackout period ends (in UTC). If replication is currently enabled and not in a blackout period, this field will be empty",
  "type": "string"
},
"replication_job_status": {
  "description": "Information about the progress of a job. This field is null if there is no job status available.",
  "type": "object",
  "properties": {
    "percent_complete": {
      "description": "Percent of way through the job, computed from a weighting of data and files processed",
      "type": "number"
    },
    "estimated_seconds_remaining": {
      "description": "Estimated number of seconds remaining in the job, derived from percent_complete. This may be null if there is no estimate.",
      "type": "string"
    },
    "bytes_transferred": {
      "description": "Number of bytes copied",
      "type": "string"
    },
    "bytes_unchanged": {
      "description": "Number of bytes not copied because they didn't change",
      "type": "string"
    },
    "bytes_remaining": {
      "description": "Number of bytes left to be processed in order to complete this job",
      "type": "string"
    },
    "bytes_deleted": {
      "description": "Number of bytes deleted",
      "type": "string"
    },
    "bytes_total": {
      "description": "Total number of bytes that will be processed during this job (this will be close but not exact)",

```

```

        "type": "string"
    },
    "files_transferred": {
        "description": "Number of files copied",
        "type": "string"
    },
    "files_unchanged": {
        "description": "Number of files not copied because they didn't change",
        "type": "string"
    },
    "files_remaining": {
        "description": "Number of files left to be processed in order to complete
this job",
        "type": "string"
    },
    "files_deleted": {
        "description": "Number of files deleted",
        "type": "string"
    },
    "files_total": {
        "description": "Total number of files that will be processed during this j
ob (this will be close but not exact)",
        "type": "string"
    },
    "throughput_overall": {
        "description": "Overall average throughput in bytes per second of data cop
ied since the beginning of the job",
        "type": "string"
    },
    "throughput_current": {
        "description": "Average throughput in bytes per second of data copied in t
he last one minute",
        "type": "string"
    }
},
"queued_snapshot_count": {
    "description": "The number of snapshots from linked snapshot policies awaitin
g replication by this relationship",
    "type": "number"
},
"recovery_point_snapshot": {
    "description": "The snapshot replicated by the last successful job. This fiel
d is null if no job has ever run successfully.",
    "type": "object",
    "properties": {

```

```

    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_file_id": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "in_delete": {
      "description": "Whether or not the snapshot is in the process of being deleted",
      "type": "boolean"
    }
  },
  "replicating_snapshot": {
    "description": "The snapshot that is being replicated by the current job. This field is null if no job is in progress.",
    "type": "object",
    "properties": {

```

```

    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_file_id": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "in_delete": {
      "description": "Whether or not the snapshot is in the process of being deleted",
      "type": "boolean"
    }
  }
}
}
}

```

replication/source-relationships/{relationship_id}/queued-snapshots/{snapshot_id}

Endpoint

/v2/replication/source-relationships/{relationship_id}/queued-snapshots/{snapshot_id}

DELETE

Release a snapshot queued for replication from the queue of the specified source replication relationship. This action will permanently remove the snapshot from the relationship's replication queue, but not delete the snapshot from the cluster.

Parameters

Name	Description	Required
<code>relationship_id</code>	Relationship identifier	Yes
<code>snapshot_id</code>	Snapshot identifier	Yes

Response

Codes

Code	Description
200	Return value on success

replication/target-relationships/status/

Endpoint

/v2/replication/target-relationships/status/

GET

List statuses for all existing replication relationships where this cluster is the target.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_target_relationship_status",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier of the replication relationship",
        "type": "string"
      },
      "state": {
        "type": "string",
        "enum": [
          "AWAITING_AUTHORIZATION",
          "DISCONNECTED",
          "DISCONNECTING",
          "ENDED",
          "ESTABLISHED",
          "RECONNECTING",
          "REESTABLISHING"
        ]
      },
      "description": "Current state of replication relationship:\n * `AWAITING_AUT
```

HORIZATION` - AWAITING\_AUTHORIZATION,\n \* `DISCONNECTED` - DISCONNECTED,\n \* `DISCONNECTING` - DISCONNECTING,\n \* `ENDED` - ENDED,\n \* `ESTABLISHED` - ESTABLISHED,\n \* `RECONNECTING` - RECONNECTING,\n \* `REESTABLISHING` - REESTABLISHING"

```
    },
    "end_reason": {
      "description": "If the relationship has ENDED, this states the reason. Otherwise, this field is empty",
      "type": "string"
    },
    "source_cluster_name": {
      "description": "Name of the source cluster",
      "type": "string"
    },
    "source_cluster_uuid": {
      "description": "UUID of the source cluster",
      "type": "string"
    },
    "source_root_path": {
      "description": "Path to the source directory",
      "type": "string"
    },
    "source_root_read_only": {
      "description": "Whether the source directory is read-only",
      "type": "boolean"
    },
    "source_address": {
      "description": "The previously connected source IP address",
      "type": "string"
    },
    "source_port": {
      "description": "Network port previously used to replicate to on the source",
      "type": "number"
    },
    "target_cluster_name": {
      "description": "Name of the target cluster",
      "type": "string"
    },
    "target_cluster_uuid": {
      "description": "UUID of the target cluster",
      "type": "string"
    },
    "target_root_path": {
      "description": "Path to the target directory",
      "type": "string"
    },
    "target_root_read_only": {
```

```

    "description": "Whether the target directory is read-only",
    "type": "boolean"
  },
  "job_state": {
    "type": "string",
    "enum": [
      "REPLICATION_NOT_RUNNING",
      "REPLICATION_RUNNING"
    ],
    "description": "Current state of the job:\n * `REPLICATION_NOT_RUNNING` - REPLICATION_NOT_RUNNING,\n * `REPLICATION_RUNNING` - REPLICATION_RUNNING"
  },
  "job_start_time": {
    "description": "If the job state is REPLICATION_RUNNING, this is the time th
at the job started, encoded as RFC 3339",
    "type": "string"
  },
  "recovery_point": {
    "description": "The time that the last successful job started, encoded as RF
C 3339",
    "type": "string"
  },
  "error_from_last_job": {
    "description": "The error message from the previous job. If the previous jo
b succeeded or no job has ever run, this field will be empty",
    "type": "string"
  },
  "duration_of_last_job": {
    "description": "The elapsed execution time of the previous job, in nanosecon
ds. If no job has ever run, this field will be null.",
    "type": "object",
    "properties": {
      "nanoseconds": {
        "description": "nanoseconds",
        "type": "string"
      }
    }
  },
  "target_root_id": {
    "description": "File ID of the target directory",
    "type": "string"
  },
  "replication_enabled": {
    "description": "Whether automatic replication is enabled",
    "type": "boolean"
  },

```

```

"replication_job_status": {
  "description": "Information about the progress of a job. This field is null
if there is no job status available.",
  "type": "object",
  "properties": {
    "percent_complete": {
      "description": "Percent of way through the job, computed from a weightin
g of data and files processed",
      "type": "number"
    },
    "estimated_seconds_remaining": {
      "description": "Estimated number of seconds remaining in the job, derive
d from percent_complete. This may be null if there is no estimate.",
      "type": "string"
    },
    "bytes_transferred": {
      "description": "Number of bytes copied",
      "type": "string"
    },
    "bytes_unchanged": {
      "description": "Number of bytes not copied because they didn't change",
      "type": "string"
    },
    "bytes_remaining": {
      "description": "Number of bytes left to be processed in order to complet
e this job",
      "type": "string"
    },
    "bytes_deleted": {
      "description": "Number of bytes deleted",
      "type": "string"
    },
    "bytes_total": {
      "description": "Total number of bytes that will be processed during thi
s job (this will be close but not exact)",
      "type": "string"
    },
    "files_transferred": {
      "description": "Number of files copied",
      "type": "string"
    },
    "files_unchanged": {
      "description": "Number of files not copied because they didn't change",
      "type": "string"
    },
    "files_remaining": {

```

```

        "description": "Number of files left to be processed in order to complete this job",
        "type": "string"
    },
    "files_deleted": {
        "description": "Number of files deleted",
        "type": "string"
    },
    "files_total": {
        "description": "Total number of files that will be processed during this job (this will be close but not exact)",
        "type": "string"
    },
    "throughput_overall": {
        "description": "Overall average throughput in bytes per second of data copied since the beginning of the job",
        "type": "string"
    },
    "throughput_current": {
        "description": "Average throughput in bytes per second of data copied in the last one minute",
        "type": "string"
    }
},
"recovery_point_snapshot": {
    "description": "The snapshot that the last successful job replicated. If no replication job has ever run successfully, this field is set to null.",
    "type": "object",
    "properties": {
        "id": {
            "description": "Unique identifier of the snapshot",
            "type": "number"
        },
        "name": {
            "description": "Name of the snapshot",
            "type": "string"
        },
        "timestamp": {
            "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
            "type": "string"
        },
        "directory_name": {
            "description": "Snapshot directory name, as would be seen in the .snapshot directory"
        }
    }
}

```

```

ot directory over SMB or NFS.",
    "type": "string"
},
"source_file_id": {
    "description": "Source directory of the snapshot",
    "type": "string"
},
"created_by_policy": {
    "description": "This snapshot was created by a policy. The name of that
policy will be stored in the name field in place of a user-defined name.",
    "type": "boolean"
},
"expiration": {
    "description": "Time at which snapshot will be expired. Empty string if
no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 860
1. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
},
"in_delete": {
    "description": "Whether or not the snapshot is in the process of being d
eleted",
    "type": "boolean"
}
},
"lock_key": {
    "description": "The key that locks the policy-created snapshots for the spec
ified target replication relationship. If set to null, the system does not lock the
snapshots that the specified target replication relationship creates. Only snapshot
s created by a policy will be locked. Unless you configure an expiration on the snap
shot policy on the target cluster, the system does not lock snapshots. If you revers
e the relationship (switch the source and the target), the new target does not use t
his lock key. To enable snapshot locking, you must configure the new target separate
ly. However, if you revert the reversed relationship (return the source and target t
o their original assignments), the system preserves the original target replication
relationship lock key. Unless you reverse the relationship, you cannot disable or de
lete a lock key while a target replication relationship uses the key. If you disabl
e or delete a lock key while the relationship is reversed and you then revert the re
versal, the original source-target relationship has no lock key until you configure
a new one.",
    "type": "string"
}
}
}
}

```

replication/target-relationships/{id}/authorize

Endpoint

/v2/replication/target-relationships/{id}/authorize

POST

Authorize the specified replication relationship, establishing this cluster as the target of replication.

Parameters

Name	Description	Required
id	Relationship identifier	Yes
allow-non-empty-directory	Specifies whether the replication relationship may be authorized when the target directory is not empty. If set to true, existing data in the target directory that does not match the source directory will be overwritten or deleted. Defaults to false if not specified.	No
allow-fs-path-create	Specifies whether the target directory may be created with inherited permissions if the directory does not already exist. Defaults to false if not specified.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_target_relationship_status",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    }
  }
}
```

```

},
"state": {
  "type": "string",
  "enum": [
    "AWAITING_AUTHORIZATION",
    "DISCONNECTED",
    "DISCONNECTING",
    "ENDED",
    "ESTABLISHED",
    "RECONNECTING",
    "REESTABLISHING"
  ],
  "description": "Current state of replication relationship:\n * `AWAITING_AUTHORIZATION` - AWAITING_AUTHORIZATION,\n * `DISCONNECTED` - DISCONNECTED,\n * `DISCONNECTING` - DISCONNECTING,\n * `ENDED` - ENDED,\n * `ESTABLISHED` - ESTABLISHED,\n * `RECONNECTING` - RECONNECTING,\n * `REESTABLISHING` - REESTABLISHING"
},
"end_reason": {
  "description": "If the relationship has ENDED, this states the reason. Otherwise, this field is empty",
  "type": "string"
},
"source_cluster_name": {
  "description": "Name of the source cluster",
  "type": "string"
},
"source_cluster_uuid": {
  "description": "UUID of the source cluster",
  "type": "string"
},
"source_root_path": {
  "description": "Path to the source directory",
  "type": "string"
},
"source_root_read_only": {
  "description": "Whether the source directory is read-only",
  "type": "boolean"
},
"source_address": {
  "description": "The previously connected source IP address",
  "type": "string"
},
"source_port": {
  "description": "Network port previously used to replicate to on the source",
  "type": "number"
},
},

```



```

"target_cluster_name": {
  "description": "Name of the target cluster",
  "type": "string"
},
"target_cluster_uuid": {
  "description": "UUID of the target cluster",
  "type": "string"
},
"target_root_path": {
  "description": "Path to the target directory",
  "type": "string"
},
"target_root_read_only": {
  "description": "Whether the target directory is read-only",
  "type": "boolean"
},
"job_state": {
  "type": "string",
  "enum": [
    "REPLICATION_NOT_RUNNING",
    "REPLICATION_RUNNING"
  ],
  "description": "Current state of the job:\n * `REPLICATION_NOT_RUNNING` - REPLICATION_NOT_RUNNING,\n * `REPLICATION_RUNNING` - REPLICATION_RUNNING"
},
"job_start_time": {
  "description": "If the job state is REPLICATION_RUNNING, this is the time that the job started, encoded as RFC 3339",
  "type": "string"
},
"recovery_point": {
  "description": "The time that the last successful job started, encoded as RFC 3339",
  "type": "string"
},
"error_from_last_job": {
  "description": "The error message from the previous job. If the previous job succeeded or no job has ever run, this field will be empty",
  "type": "string"
},
"duration_of_last_job": {
  "description": "The elapsed execution time of the previous job, in nanoseconds. If no job has ever run, this field will be null.",
  "type": "object",
  "properties": {
    "nanoseconds": {

```

```

        "description": "nanoseconds",
        "type": "string"
    }
},
"target_root_id": {
    "description": "File ID of the target directory",
    "type": "string"
},
"replication_enabled": {
    "description": "Whether automatic replication is enabled",
    "type": "boolean"
},
"replication_job_status": {
    "description": "Information about the progress of a job. This field is null i
f there is no job status available.",
    "type": "object",
    "properties": {
        "percent_complete": {
            "description": "Percent of way through the job, computed from a weighting
of data and files processed",
            "type": "number"
        },
        "estimated_seconds_remaining": {
            "description": "Estimated number of seconds remaining in the job, derived
from percent_complete. This may be null if there is no estimate.",
            "type": "string"
        },
        "bytes_transferred": {
            "description": "Number of bytes copied",
            "type": "string"
        },
        "bytes_unchanged": {
            "description": "Number of bytes not copied because they didn't change",
            "type": "string"
        },
        "bytes_remaining": {
            "description": "Number of bytes left to be processed in order to complete
this job",
            "type": "string"
        },
        "bytes_deleted": {
            "description": "Number of bytes deleted",
            "type": "string"
        },
        "bytes_total": {

```

```

        "description": "Total number of bytes that will be processed during this job (this will be close but not exact)",
        "type": "string"
    },
    "files_transferred": {
        "description": "Number of files copied",
        "type": "string"
    },
    "files_unchanged": {
        "description": "Number of files not copied because they didn't change",
        "type": "string"
    },
    "files_remaining": {
        "description": "Number of files left to be processed in order to complete this job",
        "type": "string"
    },
    "files_deleted": {
        "description": "Number of files deleted",
        "type": "string"
    },
    "files_total": {
        "description": "Total number of files that will be processed during this job (this will be close but not exact)",
        "type": "string"
    },
    "throughput_overall": {
        "description": "Overall average throughput in bytes per second of data copied since the beginning of the job",
        "type": "string"
    },
    "throughput_current": {
        "description": "Average throughput in bytes per second of data copied in the last one minute",
        "type": "string"
    }
},
"recovery_point_snapshot": {
    "description": "The snapshot that the last successful job replicated. If no replication job has ever run successfully, this field is set to null.",
    "type": "object",
    "properties": {
        "id": {
            "description": "Unique identifier of the snapshot",
            "type": "number"
        }
    }
}

```

```

    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_file_id": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "in_delete": {
      "description": "Whether or not the snapshot is in the process of being deleted",
      "type": "boolean"
    }
  }
},
"lock_key": {
  "description": "The key that locks the policy-created snapshots for the specified target replication relationship. If set to null, the system does not lock the snapshots that the specified target replication relationship creates. Only snapshots created by a policy will be locked. Unless you configure an expiration on the snapshot policy on the target cluster, the system does not lock snapshots. If you reverse the relationship (switch the source and the target), the new target does not use this lock key. To enable snapshot locking, you must configure the new target separately."
}

```

y. However, if you revert the reversed relationship (return the source and target to their original assignments), the system preserves the original target replication relationship lock key. Unless you reverse the relationship, you cannot disable or delete a lock key while a target replication relationship uses the key. If you disable or delete a lock key while the relationship is reversed and you then revert the reversal, the original source-target relationship has no lock key until you configure a new one.",

```
    "type": "string"
  }
}
```

replication/target-relationships/{id}/delete

Endpoint

/v2/replication/target-relationships/{id}/delete

POST

Delete the specified replication relationship where this cluster is the target.

Parameters

Name	Description	Required
<code>id</code>	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

replication/target-relationships/{id}/dismiss-error

Endpoint

/v2/replication/target-relationships/{id}/dismiss-error

POST

Clear the error associated with this target relationship's last replication attempt, if one exists.

Parameters

Name	Description	Required
id	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

replication/target-relationships/{id}/lock

Endpoint

/v2/replication/target-relationships/{id}/lock

POST

Set or clear the snapshot lock key ID for snapshots that this target replication relationship creates. Changing the lock key applies only to snapshots that the system takes after you make a configuration change.

Parameters

Name	Description	Required
id	Relationship identifier	Yes

Request

Schema

```
{
  "description": "api_target_relationship_lock",
  "type": "object",
  "properties": {
    "lock_key_ref": {
      "description": "The key that locks the policy-created snapshots for the specified target replication relationship. If set to null, the system does not lock the snapshots that the specified target replication relationship creates. Only snapshots created by a policy will be locked. Unless you configure an expiration on the snapshot policy on the target cluster, the system does not lock snapshots. If you reverse the relationship (switch the source and the target), the new target does not use this lock key. To enable snapshot locking, you must configure the new target separately. However, if you revert the reversed relationship (return the source and target to their original assignments), the system preserves the original target replication relationship lock key. Unless you reverse the relationship, you cannot disable or delete a lock key while a target replication relationship uses the key. If you disable or delete a lock key while the relationship is reversed and you then revert the reversal, the original source-target relationship has no lock key until you configure a new one.",
      "type": "string"
    }
  }
}
```


Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_target_relationship_lock",
  "type": "object",
  "properties": {
    "lock_key_ref": {
      "description": "The key that locks the policy-created snapshots for the specified target replication relationship. If set to null, the system does not lock the snapshots that the specified target replication relationship creates. Only snapshots created by a policy will be locked. Unless you configure an expiration on the snapshot policy on the target cluster, the system does not lock snapshots. If you reverse the relationship (switch the source and the target), the new target does not use this lock key. To enable snapshot locking, you must configure the new target separately. However, if you revert the reversed relationship (return the source and target to their original assignments), the system preserves the original target replication relationship lock key. Unless you reverse the relationship, you cannot disable or delete a lock key while a target replication relationship uses the key. If you disable or delete a lock key while the relationship is reversed and you then revert the reversal, the original source-target relationship has no lock key until you configure a new one.",
      "type": "string"
    }
  }
}
```

replication/target-relationships/{id}/make-writable

Endpoint

`/v2/replication/target-relationships/{id}/make-writable`

POST

Revert target directory to the latest recovery point to ensure that it is in a point-in-time consistent state. Then disconnect the specified target replication relationship, breaking the relationship with the source and making the target directory writable. The revert action may take some time to complete. If the relationship is later reconnected, any changes made to the target directory since the relationship was disconnected will be reverted upon reconnecting.

Parameters

Name	Description	Required
<code>id</code>	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_target_relationship_status",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "state": {
      "type": "string",
      "enum": [
        "AWAITING_AUTHORIZATION",
        "DISCONNECTED"
      ]
    }
  }
}
```

```

        "DISCONNECTING",
        "ENDED",
        "ESTABLISHED",
        "RECONNECTING",
        "REESTABLISHING"
    ],
    "description": "Current state of replication relationship:\n * `AWAITING_AUTHORIZATION` - AWAITING_AUTHORIZATION,\n * `DISCONNECTED` - DISCONNECTED,\n * `DISCONNECTING` - DISCONNECTING,\n * `ENDED` - ENDED,\n * `ESTABLISHED` - ESTABLISHED,\n * `RECONNECTING` - RECONNECTING,\n * `REESTABLISHING` - REESTABLISHING"
},
"end_reason": {
    "description": "If the relationship has ENDED, this states the reason. Otherwise, this field is empty",
    "type": "string"
},
"source_cluster_name": {
    "description": "Name of the source cluster",
    "type": "string"
},
"source_cluster_uuid": {
    "description": "UUID of the source cluster",
    "type": "string"
},
"source_root_path": {
    "description": "Path to the source directory",
    "type": "string"
},
"source_root_read_only": {
    "description": "Whether the source directory is read-only",
    "type": "boolean"
},
"source_address": {
    "description": "The previously connected source IP address",
    "type": "string"
},
"source_port": {
    "description": "Network port previously used to replicate to on the source",
    "type": "number"
},
"target_cluster_name": {
    "description": "Name of the target cluster",
    "type": "string"
},
"target_cluster_uuid": {
    "description": "UUID of the target cluster",

```

```

    "type": "string"
  },
  "target_root_path": {
    "description": "Path to the target directory",
    "type": "string"
  },
  "target_root_read_only": {
    "description": "Whether the target directory is read-only",
    "type": "boolean"
  },
  "job_state": {
    "type": "string",
    "enum": [
      "REPLICATION_NOT_RUNNING",
      "REPLICATION_RUNNING"
    ],
    "description": "Current state of the job:\n * `REPLICATION_NOT_RUNNING` - REPLICATION_NOT_RUNNING,\n * `REPLICATION_RUNNING` - REPLICATION_RUNNING"
  },
  "job_start_time": {
    "description": "If the job state is REPLICATION_RUNNING, this is the time that the job started, encoded as RFC 3339",
    "type": "string"
  },
  "recovery_point": {
    "description": "The time that the last successful job started, encoded as RFC 3339",
    "type": "string"
  },
  "error_from_last_job": {
    "description": "The error message from the previous job. If the previous job succeeded or no job has ever run, this field will be empty",
    "type": "string"
  },
  "duration_of_last_job": {
    "description": "The elapsed execution time of the previous job, in nanoseconds. If no job has ever run, this field will be null.",
    "type": "object",
    "properties": {
      "nanoseconds": {
        "description": "nanoseconds",
        "type": "string"
      }
    }
  },
  "target_root_id": {

```

```

    "description": "File ID of the target directory",
    "type": "string"
  },
  "replication_enabled": {
    "description": "Whether automatic replication is enabled",
    "type": "boolean"
  },
  "replication_job_status": {
    "description": "Information about the progress of a job. This field is null i
f there is no job status available.",
    "type": "object",
    "properties": {
      "percent_complete": {
        "description": "Percent of way through the job, computed from a weighting
of data and files processed",
        "type": "number"
      },
      "estimated_seconds_remaining": {
        "description": "Estimated number of seconds remaining in the job, derived
from percent_complete. This may be null if there is no estimate.",
        "type": "string"
      },
      "bytes_transferred": {
        "description": "Number of bytes copied",
        "type": "string"
      },
      "bytes_unchanged": {
        "description": "Number of bytes not copied because they didn't change",
        "type": "string"
      },
      "bytes_remaining": {
        "description": "Number of bytes left to be processed in order to complete
this job",
        "type": "string"
      },
      "bytes_deleted": {
        "description": "Number of bytes deleted",
        "type": "string"
      },
      "bytes_total": {
        "description": "Total number of bytes that will be processed during this j
ob (this will be close but not exact)",
        "type": "string"
      },
      "files_transferred": {
        "description": "Number of files copied",

```

```

        "type": "string"
    },
    "files_unchanged": {
        "description": "Number of files not copied because they didn't change",
        "type": "string"
    },
    "files_remaining": {
        "description": "Number of files left to be processed in order to complete
this job",
        "type": "string"
    },
    "files_deleted": {
        "description": "Number of files deleted",
        "type": "string"
    },
    "files_total": {
        "description": "Total number of files that will be processed during this j
ob (this will be close but not exact)",
        "type": "string"
    },
    "throughput_overall": {
        "description": "Overall average throughput in bytes per second of data cop
ied since the beginning of the job",
        "type": "string"
    },
    "throughput_current": {
        "description": "Average throughput in bytes per second of data copied in t
he last one minute",
        "type": "string"
    }
}
},
"recovery_point_snapshot": {
    "description": "The snapshot that the last successful job replicated. If no re
plication job has ever run successfully, this field is set to null.",
    "type": "object",
    "properties": {
        "id": {
            "description": "Unique identifier of the snapshot",
            "type": "number"
        },
        "name": {
            "description": "Name of the snapshot",
            "type": "string"
        },
        "timestamp": {

```

```

        "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
        "type": "string"
    },
    "directory_name": {
        "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
        "type": "string"
    },
    "source_file_id": {
        "description": "Source directory of the snapshot",
        "type": "string"
    },
    "created_by_policy": {
        "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
        "type": "boolean"
    },
    "expiration": {
        "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
        "type": "string"
    },
    "in_delete": {
        "description": "Whether or not the snapshot is in the process of being deleted",
        "type": "boolean"
    }
}
},
"lock_key": {
    "description": "The key that locks the policy-created snapshots for the specified target replication relationship. If set to null, the system does not lock the snapshots that the specified target replication relationship creates. Only snapshots created by a policy will be locked. Unless you configure an expiration on the snapshot policy on the target cluster, the system does not lock snapshots. If you reverse the relationship (switch the source and the target), the new target does not use this lock key. To enable snapshot locking, you must configure the new target separately. However, if you revert the reversed relationship (return the source and target to their original assignments), the system preserves the original target replication relationship lock key. Unless you reverse the relationship, you cannot disable or delete a lock key while a target replication relationship uses the key. If you disable or delete a lock key while the relationship is reversed and you then revert the reversal, the original source-target relationship has no lock key until you configure

```

```
a new one.",  
  "type": "string"  
}  
}  
}
```


replication/target-relationships/{id}/reconnect

Endpoint

/v2/replication/target-relationships/{id}/reconnect

POST

Make the target directory read-only and revert any changes made to the target directory since the latest recovery point. Then reconnect the specified target replication relationship with its source directory. The revert action may take some time to complete before replication is resumed.

Parameters

Name	Description	Required
id	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_target_relationship_status",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "state": {
      "type": "string",
      "enum": [
        "AWAITING_AUTHORIZATION",
        "DISCONNECTED",
        "DISCONNECTING",
        "ENDED"
      ]
    }
  }
}
```

```

        "ESTABLISHED",
        "RECONNECTING",
        "REESTABLISHING"
    ],
    "description": "Current state of replication relationship:\n * `AWAITING_AUTHORIZATION` - AWAITING_AUTHORIZATION,\n * `DISCONNECTED` - DISCONNECTED,\n * `DISCONNECTING` - DISCONNECTING,\n * `ENDED` - ENDED,\n * `ESTABLISHED` - ESTABLISHED,\n * `RECONNECTING` - RECONNECTING,\n * `REESTABLISHING` - REESTABLISHING"
},
"end_reason": {
    "description": "If the relationship has ENDED, this states the reason. Otherwise, this field is empty",
    "type": "string"
},
"source_cluster_name": {
    "description": "Name of the source cluster",
    "type": "string"
},
"source_cluster_uuid": {
    "description": "UUID of the source cluster",
    "type": "string"
},
"source_root_path": {
    "description": "Path to the source directory",
    "type": "string"
},
"source_root_read_only": {
    "description": "Whether the source directory is read-only",
    "type": "boolean"
},
"source_address": {
    "description": "The previously connected source IP address",
    "type": "string"
},
"source_port": {
    "description": "Network port previously used to replicate to on the source",
    "type": "number"
},
"target_cluster_name": {
    "description": "Name of the target cluster",
    "type": "string"
},
"target_cluster_uuid": {
    "description": "UUID of the target cluster",
    "type": "string"
},
},

```

```

"target_root_path": {
  "description": "Path to the target directory",
  "type": "string"
},
"target_root_read_only": {
  "description": "Whether the target directory is read-only",
  "type": "boolean"
},
"job_state": {
  "type": "string",
  "enum": [
    "REPLICATION_NOT_RUNNING",
    "REPLICATION_RUNNING"
  ],
  "description": "Current state of the job:\n * `REPLICATION_NOT_RUNNING` - REPLICATION_NOT_RUNNING,\n * `REPLICATION_RUNNING` - REPLICATION_RUNNING"
},
"job_start_time": {
  "description": "If the job state is REPLICATION_RUNNING, this is the time that the job started, encoded as RFC 3339",
  "type": "string"
},
"recovery_point": {
  "description": "The time that the last successful job started, encoded as RFC 3339",
  "type": "string"
},
"error_from_last_job": {
  "description": "The error message from the previous job. If the previous job succeeded or no job has ever run, this field will be empty",
  "type": "string"
},
"duration_of_last_job": {
  "description": "The elapsed execution time of the previous job, in nanoseconds. If no job has ever run, this field will be null.",
  "type": "object",
  "properties": {
    "nanoseconds": {
      "description": "nanoseconds",
      "type": "string"
    }
  }
},
"target_root_id": {
  "description": "File ID of the target directory",
  "type": "string"
}

```

```

},
"replication_enabled": {
  "description": "Whether automatic replication is enabled",
  "type": "boolean"
},
"replication_job_status": {
  "description": "Information about the progress of a job. This field is null if there is no job status available.",
  "type": "object",
  "properties": {
    "percent_complete": {
      "description": "Percent of way through the job, computed from a weighting of data and files processed",
      "type": "number"
    },
    "estimated_seconds_remaining": {
      "description": "Estimated number of seconds remaining in the job, derived from percent_complete. This may be null if there is no estimate.",
      "type": "string"
    },
    "bytes_transferred": {
      "description": "Number of bytes copied",
      "type": "string"
    },
    "bytes_unchanged": {
      "description": "Number of bytes not copied because they didn't change",
      "type": "string"
    },
    "bytes_remaining": {
      "description": "Number of bytes left to be processed in order to complete this job",
      "type": "string"
    },
    "bytes_deleted": {
      "description": "Number of bytes deleted",
      "type": "string"
    },
    "bytes_total": {
      "description": "Total number of bytes that will be processed during this job (this will be close but not exact)",
      "type": "string"
    },
    "files_transferred": {
      "description": "Number of files copied",
      "type": "string"
    }
  }
},

```

```

    "files_unchanged": {
      "description": "Number of files not copied because they didn't change",
      "type": "string"
    },
    "files_remaining": {
      "description": "Number of files left to be processed in order to complete
this job",
      "type": "string"
    },
    "files_deleted": {
      "description": "Number of files deleted",
      "type": "string"
    },
    "files_total": {
      "description": "Total number of files that will be processed during this j
ob (this will be close but not exact)",
      "type": "string"
    },
    "throughput_overall": {
      "description": "Overall average throughput in bytes per second of data cop
ied since the beginning of the job",
      "type": "string"
    },
    "throughput_current": {
      "description": "Average throughput in bytes per second of data copied in t
he last one minute",
      "type": "string"
    }
  },
  "recovery_point_snapshot": {
    "description": "The snapshot that the last successful job replicated. If no re
plication job has ever run successfully, this field is set to null.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier of the snapshot",
        "type": "number"
      },
      "name": {
        "description": "Name of the snapshot",
        "type": "string"
      },
      "timestamp": {
        "description": "Creation timestamp of the snapshot, encoded as RFC 3339, w
hich is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt,

```

```

section 5.6 for ABNF.",
    "type": "string"
},
"directory_name": {
    "description": "Snapshot directory name, as would be seen in the .snapsho
t directory over SMB or NFS.",
    "type": "string"
},
"source_file_id": {
    "description": "Source directory of the snapshot",
    "type": "string"
},
"created_by_policy": {
    "description": "This snapshot was created by a policy. The name of that po
lcy will be stored in the name field in place of a user-defined name.",
    "type": "boolean"
},
"expiration": {
    "description": "Time at which snapshot will be expired. Empty string if n
o expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 860
1. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
},
"in_delete": {
    "description": "Whether or not the snapshot is in the process of being del
eted",
    "type": "boolean"
}
},
"lock_key": {
    "description": "The key that locks the policy-created snapshots for the specif
ied target replication relationship. If set to null, the system does not lock the sn
apshots that the specified target replication relationship creates. Only snapshots c
reated by a policy will be locked. Unless you configure an expiration on the snapsho
t policy on the target cluster, the system does not lock snapshots. If you reverse t
he relationship (switch the source and the target), the new target does not use thi
s lock key. To enable snapshot locking, you must configure the new target separatel
y. However, if you revert the reversed relationship (return the source and target t
o their original assignments), the system preserves the original target replication
relationship lock key. Unless you reverse the relationship, you cannot disable or de
lete a lock key while a target replication relationship uses the key. If you disabl
e or delete a lock key while the relationship is reversed and you then revert the re
versal, the original source-target relationship has no lock key until you configure
a new one.",
    "type": "string"
}
}

```

```
}  
}  
}
```

replication/target-relationships/{id}/status

Endpoint

/v2/replication/target-relationships/{id}/status

GET

Get current status of the specified replication relationship where this cluster is the target.

Parameters

Name	Description	Required
id	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_target_relationship_status",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "state": {
      "type": "string",
      "enum": [
        "AWAITING_AUTHORIZATION",
        "DISCONNECTED",
        "DISCONNECTING",
        "ENDED",
        "ESTABLISHED",
        "RECONNECTING",
        "REESTABLISHING"
      ]
    }
  }
}
```



```

    "description": "Current state of replication relationship:\n * `AWAITING_AUTHORIZATION` - AWAITING_AUTHORIZATION,\n * `DISCONNECTED` - DISCONNECTED,\n * `DISCONNECTING` - DISCONNECTING,\n * `ENDED` - ENDED,\n * `ESTABLISHED` - ESTABLISHED,\n * `RECONNECTING` - RECONNECTING,\n * `REESTABLISHING` - REESTABLISHING"
  },
  "end_reason": {
    "description": "If the relationship has ENDED, this states the reason. Otherwise, this field is empty",
    "type": "string"
  },
  "source_cluster_name": {
    "description": "Name of the source cluster",
    "type": "string"
  },
  "source_cluster_uuid": {
    "description": "UUID of the source cluster",
    "type": "string"
  },
  "source_root_path": {
    "description": "Path to the source directory",
    "type": "string"
  },
  "source_root_read_only": {
    "description": "Whether the source directory is read-only",
    "type": "boolean"
  },
  "source_address": {
    "description": "The previously connected source IP address",
    "type": "string"
  },
  "source_port": {
    "description": "Network port previously used to replicate to on the source",
    "type": "number"
  },
  "target_cluster_name": {
    "description": "Name of the target cluster",
    "type": "string"
  },
  "target_cluster_uuid": {
    "description": "UUID of the target cluster",
    "type": "string"
  },
  "target_root_path": {
    "description": "Path to the target directory",
    "type": "string"
  },
},

```

```

"target_root_read_only": {
  "description": "Whether the target directory is read-only",
  "type": "boolean"
},
"job_state": {
  "type": "string",
  "enum": [
    "REPLICATION_NOT_RUNNING",
    "REPLICATION_RUNNING"
  ],
  "description": "Current state of the job:\n * `REPLICATION_NOT_RUNNING` - REPLICATION_NOT_RUNNING,\n * `REPLICATION_RUNNING` - REPLICATION_RUNNING"
},
"job_start_time": {
  "description": "If the job state is REPLICATION_RUNNING, this is the time that the job started, encoded as RFC 3339",
  "type": "string"
},
"recovery_point": {
  "description": "The time that the last successful job started, encoded as RFC 3339",
  "type": "string"
},
"error_from_last_job": {
  "description": "The error message from the previous job. If the previous job succeeded or no job has ever run, this field will be empty",
  "type": "string"
},
"duration_of_last_job": {
  "description": "The elapsed execution time of the previous job, in nanoseconds. If no job has ever run, this field will be null.",
  "type": "object",
  "properties": {
    "nanoseconds": {
      "description": "nanoseconds",
      "type": "string"
    }
  }
},
"target_root_id": {
  "description": "File ID of the target directory",
  "type": "string"
},
"replication_enabled": {
  "description": "Whether automatic replication is enabled",
  "type": "boolean"
}

```

```

},
"replication_job_status": {
  "description": "Information about the progress of a job. This field is null i
f there is no job status available.",
  "type": "object",
  "properties": {
    "percent_complete": {
      "description": "Percent of way through the job, computed from a weighting
of data and files processed",
      "type": "number"
    },
    "estimated_seconds_remaining": {
      "description": "Estimated number of seconds remaining in the job, derived
from percent_complete. This may be null if there is no estimate.",
      "type": "string"
    },
    "bytes_transferred": {
      "description": "Number of bytes copied",
      "type": "string"
    },
    "bytes_unchanged": {
      "description": "Number of bytes not copied because they didn't change",
      "type": "string"
    },
    "bytes_remaining": {
      "description": "Number of bytes left to be processed in order to complete
this job",
      "type": "string"
    },
    "bytes_deleted": {
      "description": "Number of bytes deleted",
      "type": "string"
    },
    "bytes_total": {
      "description": "Total number of bytes that will be processed during this j
ob (this will be close but not exact)",
      "type": "string"
    },
    "files_transferred": {
      "description": "Number of files copied",
      "type": "string"
    },
    "files_unchanged": {
      "description": "Number of files not copied because they didn't change",
      "type": "string"
    }
  }
},

```

```

    "files_remaining": {
      "description": "Number of files left to be processed in order to complete
this job",
      "type": "string"
    },
    "files_deleted": {
      "description": "Number of files deleted",
      "type": "string"
    },
    "files_total": {
      "description": "Total number of files that will be processed during this j
ob (this will be close but not exact)",
      "type": "string"
    },
    "throughput_overall": {
      "description": "Overall average throughput in bytes per second of data cop
ied since the beginning of the job",
      "type": "string"
    },
    "throughput_current": {
      "description": "Average throughput in bytes per second of data copied in t
he last one minute",
      "type": "string"
    }
  },
  "recovery_point_snapshot": {
    "description": "The snapshot that the last successful job replicated. If no re
plication job has ever run successfully, this field is set to null.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier of the snapshot",
        "type": "number"
      },
      "name": {
        "description": "Name of the snapshot",
        "type": "string"
      },
      "timestamp": {
        "description": "Creation timestamp of the snapshot, encoded as RFC 3339, w
hich is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt,
section 5.6 for ABNF.",
        "type": "string"
      },
      "directory_name": {

```

```

        "description": "Snapshot directory name, as would be seen in the .snapsho
t directory over SMB or NFS.",
        "type": "string"
    },
    "source_file_id": {
        "description": "Source directory of the snapshot",
        "type": "string"
    },
    "created_by_policy": {
        "description": "This snapshot was created by a policy. The name of that po
licy will be stored in the name field in place of a user-defined name.",
        "type": "boolean"
    },
    "expiration": {
        "description": "Time at which snapshot will be expired. Empty string if n
o expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 860
1. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
        "type": "string"
    },
    "in_delete": {
        "description": "Whether or not the snapshot is in the process of being del
eted",
        "type": "boolean"
    }
}
},
"lock_key": {
    "description": "The key that locks the policy-created snapshots for the specif
ied target replication relationship. If set to null, the system does not lock the sn
apshots that the specified target replication relationship creates. Only snapshots c
reated by a policy will be locked. Unless you configure an expiration on the snapsho
t policy on the target cluster, the system does not lock snapshots. If you reverse t
he relationship (switch the source and the target), the new target does not use thi
s lock key. To enable snapshot locking, you must configure the new target separatel
y. However, if you revert the reversed relationship (return the source and target t
o their original assignments), the system preserves the original target replication
relationship lock key. Unless you reverse the relationship, you cannot disable or de
lete a lock key while a target replication relationship uses the key. If you disabl
e or delete a lock key while the relationship is reversed and you then revert the re
versal, the original source-target relationship has no lock key until you configure
a new one.",
    "type": "string"
}
}
}

```

replication/object-relationships/

Endpoint

/v3/replication/object-relationships/

GET

List existing object replication relationships.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_object_relationship_v3",
    "type": "object",
    "properties": {
      "id": {
        "description": "Unique identifier of the replication relationship",
        "type": "string"
      },
      "direction": {
        "type": "string",
        "enum": [
          "COPY_TO_OBJECT",
          "COPY_FROM_OBJECT"
        ],
        "description": "The object relationship can either copy data to or from the object store:\n * `COPY_FROM_OBJECT` - COPY_FROM_OBJECT,\n * `COPY_TO_OBJECT` - COPY_TO_OBJECT"
      },
      "local_directory_id": {
        "description": "File ID of the qumulo directory",

```

```

    "type": "string"
  },
  "object_store_address": {
    "description": "S3-compatible server address",
    "type": "string"
  },
  "port": {
    "description": "HTTPS port to use when communicating with the object store",
    "type": "number"
  },
  "ca_certificate": {
    "description": "Public certificate of the certificate authority to trust for connections to the object store, in PEM format. If empty, the built-in trusted public CAs are used.",
    "type": "string"
  },
  "bucket": {
    "description": "Bucket in the object store to use",
    "type": "string"
  },
  "bucket_style": {
    "type": "string",
    "enum": [
      "BUCKET_STYLE_PATH",
      "BUCKET_STYLE_VIRTUAL_HOSTED"
    ],
    "description": "Addressing style for requests to the bucket. BUCKET_STYLE_PATH indicates path-style addressing while BUCKET_STYLE_VIRTUAL_HOSTED indicates virtual hosted-style.\n * `BUCKET_STYLE_PATH` - BUCKET_STYLE_PATH,\n * `BUCKET_STYLE_VIRTUAL_HOSTED` - BUCKET_STYLE_VIRTUAL_HOSTED"
  },
  "object_folder": {
    "description": "Folder in the object store bucket to use",
    "type": "string"
  },
  "region": {
    "description": "Region the bucket is located in",
    "type": "string"
  },
  "access_key_id": {
    "description": "Access key ID to use when communicating with the object store",
    "type": "string"
  }
}

```

```
}
```

POST

Create a new object replication relationship. Replication will automatically start after the relationship is created.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_object_create_request_v3",
  "type": "object",
  "properties": {
    "direction": {
      "type": "string",
      "enum": [
        "COPY_TO_OBJECT",
        "COPY_FROM_OBJECT"
      ],
      "description": "Whether data is to be copied to, or from, the object store:\n * `COPY_FROM_OBJECT` - COPY_FROM_OBJECT,\n * `COPY_TO_OBJECT` - COPY_TO_OBJECT"
    },
    "local_directory_id": {
      "description": "File ID of the qumulo directory if local_directory_path is not provided",
      "type": "string"
    },
    "local_directory_path": {
      "description": "Path of the qumulo directory if local_directory_id is not provided",
      "type": "string"
    },
    "object_store_address": {
      "description": "S3-compatible server address. For Amazon S3, use s3.<region>.amazonaws.com (e.g., s3.us-west-2.amazonaws.com).",
      "type": "string"
    },
    "port": {
      "description": "HTTPS port to use when communicating with the object store (default: 443)",

```



```

    "type": "number"
  },
  "ca_certificate": {
    "description": "Public certificate of the certificate authority to trust for c
onnections to the object store, in PEM format (defaults to built-in trusted public C
As)",
    "type": "string"
  },
  "bucket": {
    "description": "Bucket in the object store to use for this relationship",
    "type": "string"
  },
  "bucket_style": {
    "type": "string",
    "enum": [
      "BUCKET_STYLE_PATH",
      "BUCKET_STYLE_VIRTUAL_HOSTED"
    ],
    "description": "Addressing style for requests to the bucket. Set to BUCKET_STY
LE_PATH for path-style addressing or BUCKET_STYLE_VIRTUAL_HOSTED for virtual hosted-
style (the default). For Amazon S3, virtual hosted-style is recommended as path-styl
e is deprecated. Bucket names containing dots ('.') or characters that are not vali
d in domain names may require path-style. The object_store_address should not includ
e the bucket name, regardless of addressing style.:\\n * `BUCKET_STYLE_PATH` - BUCKE
T_STYLE_PATH,\\n * `BUCKET_STYLE_VIRTUAL_HOSTED` - BUCKET_STYLE_VIRTUAL_HOSTED"
  },
  "object_folder": {
    "description": "Folder to use in the object store bucket. A slash separator i
s automatically used to specify a 'folder' in a bucket. For example, a folder of 'ex
ample' and a file path (relative to the directory_path) of 'dir/file' will result i
n key 'example/dir/file'. Use empty value '' or '/' to replicate with the root of th
e bucket.",
    "type": "string"
  },
  "region": {
    "description": "Region the bucket is located in",
    "type": "string"
  },
  "access_key_id": {
    "description": "Access key ID to use when communicating with the object stor
e",
    "type": "string"
  },
  "secret_access_key": {
    "description": "Secret access key to use when communicating with the object st
ore",

```

```

    "type": "string",
    "format": "password"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_object_relationship_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "direction": {
      "type": "string",
      "enum": [
        "COPY_TO_OBJECT",
        "COPY_FROM_OBJECT"
      ],
      "description": "The object relationship can either copy data to or from the object store:\n * `COPY_FROM_OBJECT` - COPY_FROM_OBJECT,\n * `COPY_TO_OBJECT` - COPY_TO_OBJECT"
    },
    "local_directory_id": {
      "description": "File ID of the qumulo directory",
      "type": "string"
    },
    "object_store_address": {
      "description": "S3-compatible server address",
      "type": "string"
    },
    "port": {
      "description": "HTTPS port to use when communicating with the object store",
      "type": "number"
    }
  }
}

```

```

    },
    "ca_certificate": {
      "description": "Public certificate of the certificate authority to trust for c
onnections to the object store, in PEM format. If empty, the built-in trusted publi
c CAs are used.",
      "type": "string"
    },
    "bucket": {
      "description": "Bucket in the object store to use",
      "type": "string"
    },
    "bucket_style": {
      "type": "string",
      "enum": [
        "BUCKET_STYLE_PATH",
        "BUCKET_STYLE_VIRTUAL_HOSTED"
      ],
      "description": "Addressing style for requests to the bucket. BUCKET_STYLE_PAT
H indicates path-style addressing while BUCKET_STYLE_VIRTUAL_HOSTED indicates virtua
l hosted-style.:\\n * `BUCKET_STYLE_PATH` - BUCKET_STYLE_PATH,\\n * `BUCKET_STYLE_VIRT
UAL_HOSTED` - BUCKET_STYLE_VIRTUAL_HOSTED"
    },
    "object_folder": {
      "description": "Folder in the object store bucket to use",
      "type": "string"
    },
    "region": {
      "description": "Region the bucket is located in",
      "type": "string"
    },
    "access_key_id": {
      "description": "Access key ID to use when communicating with the object stor
e",
      "type": "string"
    }
  }
}

```

replication/object-relationships/status/

Endpoint

`/v3/replication/object-relationships/status/`

GET

List statuses for all existing object replication relationships.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

replication/object-relationships/{id}

Endpoint

/v3/replication/object-relationships/{id}

GET

Get information about the specified object replication relationship.

Parameters

Name	Description	Required
id	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_object_relationship_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the replication relationship",
      "type": "string"
    },
    "direction": {
      "type": "string",
      "enum": [
        "COPY_TO_OBJECT",
        "COPY_FROM_OBJECT"
      ],
      "description": "The object relationship can either copy data to or from the object store:\n * `COPY_FROM_OBJECT` - COPY_FROM_OBJECT,\n * `COPY_TO_OBJECT` - COPY_TO_OBJECT"
    },
    "local_directory_id": {
```

```

    "description": "File ID of the qumulo directory",
    "type": "string"
  },
  "object_store_address": {
    "description": "S3-compatible server address",
    "type": "string"
  },
  "port": {
    "description": "HTTPS port to use when communicating with the object store",
    "type": "number"
  },
  "ca_certificate": {
    "description": "Public certificate of the certificate authority to trust for connections to the object store, in PEM format. If empty, the built-in trusted public CAs are used.",
    "type": "string"
  },
  "bucket": {
    "description": "Bucket in the object store to use",
    "type": "string"
  },
  "bucket_style": {
    "type": "string",
    "enum": [
      "BUCKET_STYLE_PATH",
      "BUCKET_STYLE_VIRTUAL_HOSTED"
    ],
    "description": "Addressing style for requests to the bucket. BUCKET_STYLE_PATH indicates path-style addressing while BUCKET_STYLE_VIRTUAL_HOSTED indicates virtual hosted-style.\n * `BUCKET_STYLE_PATH` - BUCKET_STYLE_PATH,\n * `BUCKET_STYLE_VIRTUAL_HOSTED` - BUCKET_STYLE_VIRTUAL_HOSTED"
  },
  "object_folder": {
    "description": "Folder in the object store bucket to use",
    "type": "string"
  },
  "region": {
    "description": "Region the bucket is located in",
    "type": "string"
  },
  "access_key_id": {
    "description": "Access key ID to use when communicating with the object store",
    "type": "string"
  }
}

```

```
}
```

DELETE

Delete the specified object replication relationship, which must not be running a job.

Parameters

Name	Description	Required
id	Relationship identifier	Yes
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

replication/object-relationships/{id}/abort-replication

Endpoint

`/v3/replication/object-relationships/{id}/abort-replication`

POST

Abort any ongoing replication job for the specified object replication relationship.

Parameters

Name	Description	Required
<code>id</code>	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

replication/object-relationships/{id}/replicate

Endpoint

`/v3/replication/object-relationships/{id}/replicate`

POST

Start a new replication job for the specified object relationship

Parameters

Name	Description	Required
<code>id</code>	Relationship identifier	Yes

Response

Codes

Code	Description
202	Return value on success

replication/object-relationships/{id}/status

Endpoint

`/v3/replication/object-relationships/{id}/status`

GET

Get the status of an existing object replication relationship.

Parameters

Name	Description	Required
<code>id</code>	Relationship identifier	Yes

Response

Codes

Code	Description
200	Return value on success

auth/privileges/

Endpoint

/v1/auth/privileges/

GET

Get information about all privileges.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "string_string_map",
  "type": "object",
  "properties": {},
  "additionalProperties": {
    "description": "string_string_map value",
    "type": "string"
  }
}
```

auth/roles/

Endpoint

/v1/auth/roles/

GET

List all roles.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "role_model_map",
  "type": "object",
  "properties": {},
  "additionalProperties": {
    "description": "role_model_map value",
    "type": "object",
    "properties": {
      "description": {
        "description": "Description of the role",
        "type": "string"
      },
      "privileges": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "PRIVILEGE_AD_READ",
            "PRIVILEGE_AD_USE",
            "PRIVILEGE_AD_WRITE",
            "PRIVILEGE_ANALYTICS_READ",
            "PRIVILEGE_AUDIT_READ",

```

```
"PRIVILEGE_AUDIT_WRITE",
"PRIVILEGE_AUTH_CACHE_READ",
"PRIVILEGE_AUTH_CACHE_WRITE",
"PRIVILEGE_CLUSTER_READ",
"PRIVILEGE_CLUSTER_WRITE",
"PRIVILEGE_DEBUG",
"PRIVILEGE_DNS_READ",
"PRIVILEGE_DNS_USE",
"PRIVILEGE_DNS_WRITE",
"PRIVILEGE_FILE_FULL_ACCESS",
"PRIVILEGE_FS_ATTRIBUTES_READ",
"PRIVILEGE_FS_DELETE_TREE_READ",
"PRIVILEGE_FS_DELETE_TREE_WRITE",
"PRIVILEGE_FS_LOCK_READ",
"PRIVILEGE_FS_LOCK_WRITE",
"PRIVILEGE_FS_SETTINGS_READ",
"PRIVILEGE_FS_SETTINGS_WRITE",
"PRIVILEGE_FTP_READ",
"PRIVILEGE_FTP_WRITE",
"PRIVILEGE_IDENTITY_MAPPING_READ",
"PRIVILEGE_IDENTITY_MAPPING_WRITE",
"PRIVILEGE_IDENTITY_READ",
"PRIVILEGE_IDENTITY_WRITE",
"PRIVILEGE_KERBEROS_KEYTAB_READ",
"PRIVILEGE_KERBEROS_KEYTAB_WRITE",
"PRIVILEGE_KERBEROS_SETTINGS_READ",
"PRIVILEGE_KERBEROS_SETTINGS_WRITE",
"PRIVILEGE_KV_READ",
"PRIVILEGE_LDAP_READ",
"PRIVILEGE_LDAP_USE",
"PRIVILEGE_LDAP_WRITE",
"PRIVILEGE_LOCAL_GROUP_READ",
"PRIVILEGE_LOCAL_GROUP_WRITE",
"PRIVILEGE_LOCAL_USER_READ",
"PRIVILEGE_LOCAL_USER_WRITE",
"PRIVILEGE_METRICS_READ",
"PRIVILEGE_NETWORK_IP_ALLOCATION_READ",
"PRIVILEGE_NETWORK_READ",
"PRIVILEGE_NETWORK_WRITE",
"PRIVILEGE_NFS_EXPORT_READ",
"PRIVILEGE_NFS_EXPORT_WRITE",
"PRIVILEGE_POWER_CYCLE",
"PRIVILEGE_QUOTA_READ",
"PRIVILEGE_QUOTA_WRITE",
"PRIVILEGE_RECONCILER_READ",
"PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP",
```

```
"PRIVILEGE_REPLICATION_SOURCE_READ",  
"PRIVILEGE_REPLICATION_SOURCE_WRITE",  
"PRIVILEGE_REPLICATION_TARGET_READ",  
"PRIVILEGE_REPLICATION_TARGET_WRITE",  
"PRIVILEGE_ROLE_READ",  
"PRIVILEGE_ROLE_WRITE",  
"PRIVILEGE_SMB_SHARE_READ",  
"PRIVILEGE_SMB_SHARE_WRITE",  
"PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ",  
"PRIVILEGE_SNAPSHOT_DIFFERENCE_READ",  
"PRIVILEGE_SNAPSHOT_POLICY_READ",  
"PRIVILEGE_SNAPSHOT_POLICY_WRITE",  
"PRIVILEGE_SNAPSHOT_READ",  
"PRIVILEGE_SNAPSHOT_WRITE",  
"PRIVILEGE_SUPPORT_READ",  
"PRIVILEGE_SUPPORT_WRITE",  
"PRIVILEGE_TEST_ONLY",  
"PRIVILEGE_TIME_READ",  
"PRIVILEGE_TIME_WRITE",  
"PRIVILEGE_UNCONFIGURED_NODE_READ",  
"PRIVILEGE_UPGRADE_READ",  
"PRIVILEGE_UPGRADE_WRITE",  
"PRIVILEGE_SMB_FILE_HANDLE_READ",  
"PRIVILEGE_SMB_FILE_HANDLE_WRITE",  
"PRIVILEGE_SMB_SESSION_READ",  
"PRIVILEGE_SMB_SESSION_WRITE",  
"PRIVILEGE_REPLICATION_OBJECT_READ",  
"PRIVILEGE_REPLICATION_OBJECT_WRITE",  
"PRIVILEGE_ENCRYPTION_WRITE",  
"PRIVILEGE_ENCRYPTION_READ",  
"PRIVILEGE_NFS_SETTINGS_READ",  
"PRIVILEGE_NFS_SETTINGS_WRITE",  
"PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE",  
"PRIVILEGE_SERVICE_PUBLIC_KEYS_READ",  
"PRIVILEGE_METRICS_CONFIG_READ",  
"PRIVILEGE_METRICS_CONFIG_WRITE",  
"PRIVILEGE_REBOOT_USE",  
"PRIVILEGE_REBOOT_READ",  
"PRIVILEGE_CHECKSUMMING_READ",  
"PRIVILEGE_S3_SETTINGS_READ",  
"PRIVILEGE_S3_SETTINGS_WRITE",  
"PRIVILEGE_WEB_UI_SETTINGS_WRITE",  
"PRIVILEGE_S3_CREDENTIALS_READ",  
"PRIVILEGE_S3_CREDENTIALS_WRITE",  
"PRIVILEGE_TENANT_READ",  
"PRIVILEGE_TENANT_WRITE",
```

```

"PRIVILEGE_SAML_SETTINGS_READ",
"PRIVILEGE_SAML_SETTINGS_WRITE",
"PRIVILEGE_S3_BUCKETS_READ",
"PRIVILEGE_S3_BUCKETS_WRITE",
"PRIVILEGE_ACCESS_TOKENS_READ",
"PRIVILEGE_ACCESS_TOKENS_WRITE",
"PRIVILEGE_S3_UPLOADS_READ",
"PRIVILEGE_S3_UPLOADS_WRITE",
"PRIVILEGE_SNAPSHOT_LOCK",
"PRIVILEGE_FS_KEY_MANAGEMENT_WRITE",
"PRIVILEGE_FS_KEY_MANAGEMENT_READ",
"PRIVILEGE_IDENTITY_CONFIG_WRITE",
"PRIVILEGE_IDENTITY_CONFIG_READ",
"PRIVILEGE_FILE_READ_ACCESS",
"PRIVILEGE_PORTAL_SPOKE_READ",
"PRIVILEGE_PORTAL_SPOKE_WRITE",
"PRIVILEGE_PORTAL_SPOKE_EVICT",
"PRIVILEGE_PORTAL_HUB_READ",
"PRIVILEGE_PORTAL_HUB_WRITE",
"PRIVILEGE_PORTAL_GLOBAL_READ",
"PRIVILEGE_FS_FILE_LOCK_WRITE",
"PRIVILEGE_LICENSE_READ",
"PRIVILEGE_CAPACITY_READ",
"PRIVILEGE_CAPACITY_WRITE",
"PRIVILEGE_OBJECT_STORAGE_URI_READ",
"PRIVILEGE_OBJECT_STORAGE_URI_WRITE",
"PRIVILEGE_DISK_ERROR_WRITE",
"PRIVILEGE_DISK_ERROR_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE"

```

```
],
```

```

"description": "Privileges the role has been granted:\n * `PRIVILEGE_ACCESS_TOKENS_READ` - View any access tokens present in the system,\n * `PRIVILEGE_ACCESS_TOKENS_WRITE` - Create or delete access tokens for any user in the system,\n * `PRIVILEGE_AD_READ` - Read Qumulo Active Directory settings,\n * `PRIVILEGE_AD_USE` - Use Qumulo's APIs for performing queries against Active Directory,\n * `PRIVILEGE_AD_WRITE` - Modify Qumulo Active Directory settings,\n * `PRIVILEGE_ANALYTICS_READ` - Read cluster analytics,\n * `PRIVILEGE_AUDIT_READ` - Read audit settings,\n * `PRIVILEGE_AUDIT_WRITE` - Modify audit settings,\n * `PRIVILEGE_AUTH_CACHE_READ` - Internal-Only: Read authentication cache settings,\n * `PRIVILEGE_AUTH_CACHE_WRITE` - Internal-Only: Modify authentication cache settings,\n * `PRIVILEGE_CAPACITY_READ` - View the capacity clamp value.,\n * `PRIVILEGE_CAPACITY_WRITE` - Set the capacity clamp value.,\n * `PRIVILEGE_CHECKSUMMING_READ` - View the status of checksumming,\n * `PRIVILEGE_CLUSTER_READ` - View nodes, disks, protection status, and SSL certificate,\n * `PRIVILEGE_CLUSTER_WRITE` - Modify cluster settings and disk/identify LEDs,\n * `PRIVILEGE_DEBUG` - Internal-Only: Perform debug operations on the cluster

```

r,\n * `PRIVILEGE\_DISK\_ERROR\_READ` - Internal-Only: Read disk error threshold and status.,\n * `PRIVILEGE\_DISK\_ERROR\_WRITE` - Internal-Only: Modify disk error threshold and revive rejected disks.,\n * `PRIVILEGE\_DNS\_READ` - Read DNS settings,\n * `PRIVILEGE\_DNS\_USE` - Perform DNS lookups,\n * `PRIVILEGE\_DNS\_WRITE` - Modify DNS settings,\n * `PRIVILEGE\_ENCRYPTION\_READ` - View the status of at-rest-encryption,\n * `PRIVILEGE\_ENCRYPTION\_WRITE` - Rotate encryption keys for clusters with at-rest-encryption,\n * `PRIVILEGE\_FILE\_FULL\_ACCESS` - Provides full access to all files regardless of permissions,\n * `PRIVILEGE\_FILE\_READ\_ACCESS` - Provides read access to all files regardless of permissions,\n * `PRIVILEGE\_FS\_ATTRIBUTES\_READ` - Read file system statistics,\n * `PRIVILEGE\_FS\_DELETE\_TREE\_READ` - View the status of directory tree delete operations,\n * `PRIVILEGE\_FS\_DELETE\_TREE\_WRITE` - Use directory tree delete API. Granting this privilege allows the deletion of any file or directory on the cluster. File and directory permissions are not taken into account. Not required for `rm -r`.,\n * `PRIVILEGE\_FS\_FILE\_LOCK\_WRITE` - Set or extend file lock retention periods and legal holds.,\n * `PRIVILEGE\_FS\_KEY\_MANAGEMENT\_READ` - Read and list public keys for various FS security features.,\n * `PRIVILEGE\_FS\_KEY\_MANAGEMENT\_WRITE` - Create and manage public keys for various FS security features.,\n * `PRIVILEGE\_FS\_LOCK\_READ` - View NLM and SMB locks and waiters,\n * `PRIVILEGE\_FS\_LOCK\_WRITE` - Release NLM and SMB locks,\n * `PRIVILEGE\_FS\_SETTINGS\_READ` - View file system permissions settings,\n * `PRIVILEGE\_FS\_SETTINGS\_WRITE` - Modify file system permissions mode,\n * `PRIVILEGE\_FTP\_READ` - View FTP status and settings,\n * `PRIVILEGE\_FTP\_WRITE` - Modify FTP status and settings,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_READ` - Read and list identity configurations.,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_WRITE` - Modify identity configurations.,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_READ` - Get AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_WRITE` - Set AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_READ` - Use Qumulo's identity lookup and translation APIs,\n * `PRIVILEGE\_IDENTITY\_WRITE` - Modify identity attributes and clear authentication cache,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_READ` - View Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_WRITE` - Modify Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_READ` - Read Kerberos settings,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_WRITE` - Modify Kerberos settings,\n * `PRIVILEGE\_KV\_READ` - DEPRECATED: Read and delete KV store entries for all users,\n * `PRIVILEGE\_LDAP\_READ` - View LDAP settings,\n * `PRIVILEGE\_LDAP\_USE` - Use Qumulo's APIs for performing LDAP queries,\n * `PRIVILEGE\_LDAP\_WRITE` - Modify LDAP settings,\n * `PRIVILEGE\_LICENSE\_READ` - Get the cluster's license status.,\n * `PRIVILEGE\_LOCAL\_GROUP\_READ` - View local groups and members,\n * `PRIVILEGE\_LOCAL\_GROUP\_WRITE` - Modify local groups and membership,\n * `PRIVILEGE\_LOCAL\_USER\_READ` - Get information about local users,\n * `PRIVILEGE\_LOCAL\_USER\_WRITE` - Create and modify all local users,\n * `PRIVILEGE\_METRICS\_CONFIG\_READ` - View metrics configuration,\n * `PRIVILEGE\_METRICS\_CONFIG\_WRITE` - Modify metrics configuration,\n * `PRIVILEGE\_METRICS\_READ` - Get all metrics,\n * `PRIVILEGE\_NETWORK\_IP\_ALLOCATION\_READ` - View network IP address allocations,\n * `PRIVILEGE\_NETWORK\_READ` - Read network status and settings,\n * `PRIVILEGE\_NETWORK\_WRITE` - Modify network configuration,\n * `PRIVILEGE\_NFS\_EXPORT\_READ` - View configuration of NFS exports,\n * `PRIVILEGE\_NFS\_EXPORT\_WRITE` - Create, modify, and delete NFS exports,\n * `PRIVILEGE\_NFS\_SETTINGS\_READ` - Internal-Only: View NFS server settings,\n * `PRIVILEGE\_NFS\_SETTINGS\_WRITE` - Internal-Only: Modify NFS server settings,\n * `PRIVILEGE_OBJECT_ST

ORAGE_CONFIG_READ` - Read object storage config, including store URIs and credential s.,\n \* `PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE` - Write object storage config, inclu ding store URIs and credentials.,\n \* `PRIVILEGE_OBJECT_STORAGE_URIS_READ` - View th e object storage URIs.,\n \* `PRIVILEGE_OBJECT_STORAGE_URIS_WRITE` - Add new object s torage URIs.,\n \* `PRIVILEGE_PORTAL_GLOBAL_READ` - View global portal settings and s tatus,\n \* `PRIVILEGE_PORTAL_HUB_READ` - View hub portal relationship status and con figuration,\n \* `PRIVILEGE_PORTAL_HUB_WRITE` - Authorize, modify, and delete hub por tal relationships. Granting this privilege allows authorizing proposed relationship s. Depending on existing file and directory permissions, this privilege can allow re mote access to local data under the hub root directory.,\n \* `PRIVILEGE_PORTAL_SPOK E_EVICT` - Remove cached files and directories from a spoke portal. Qumulo Core reca ches the removed files or directories upon access.,\n \* `PRIVILEGE_PORTAL_SPOKE_REA D` - View spoke portal relationship status and configuration,\n \* `PRIVILEGE_PORTA L_SPOKE_WRITE` - Create, modify, and delete spoke portal relationships. Granting thi s privilege allows creating spoke portal root directories. Depending on existing fil e permissions, this privilege can allow local access to remote files and directorie s.,\n \* `PRIVILEGE_POWER_CYCLE` - Shutdown and reboot nodes,\n \* `PRIVILEGE_QUOTA_RE AD` - View all file system quotas,\n \* `PRIVILEGE_QUOTA_WRITE` - Create, modify, an d delete file system quotas,\n \* `PRIVILEGE_REBOOT_READ` - View Reboot Status,\n \* `PRIVILEGE_REBOOT_USE` - Perform Reboots,\n \* `PRIVILEGE_RECONCILER_READ` - View rec onciler status and metrics,\n \* `PRIVILEGE_REPLICATION_OBJECT_READ` - View object st ore relationship settings and status,\n \* `PRIVILEGE_REPLICATION_OBJECT_WRITE` - Cre ate, modify, and delete object store relationships. Granting this privilege allows o verwriting existing data, replicating, and potentially accessing any data on the clu ster regardless of file and directory permissions.,\n \* `PRIVILEGE_REPLICATION_REVER SE_RELATIONSHIP` - Reverse a source and target relationship,\n \* `PRIVILEGE_REPLICAT ION_SOURCE_READ` - View source relationship settings and status,\n \* `PRIVILEGE_REPL ICATION_SOURCE_WRITE` - Create, modify, and delete source relationships. Granting th is privilege allows replicating and potentially accessing any data on the cluster re gardless of file and directory permissions.,\n \* `PRIVILEGE_REPLICATION_TARGET_REA D` - View target relationship settings and status,\n \* `PRIVILEGE_REPLICATION_TARGE T_WRITE` - Create, modify, and delete target relationships. Granting this privilege allows overwriting any data on the cluster regardless of file and directory permissi ons.,\n \* `PRIVILEGE_ROLE_READ` - View roles and assignments,\n \* `PRIVILEGE_ROLE_WR ITE` - Create and modify roles and assignments,\n \* `PRIVILEGE_S3_BUCKETS_READ` - Vi ew all S3 buckets and bucket policies present in the system,\n \* `PRIVILEGE_S3_BUCKE TS_WRITE` - Create or delete any S3 bucket in the system, and create, delete, or mod ify policies for any S3 bucket in the system. Subject to having sufficient FS permis sions.,\n \* `PRIVILEGE_S3_CREDENTIALS_READ` - View any S3 access key present in the system,\n \* `PRIVILEGE_S3_CREDENTIALS_WRITE` - Create or delete S3 access keys for a ny user in the system,\n \* `PRIVILEGE_S3_SETTINGS_READ` - View S3 server setting s,\n \* `PRIVILEGE_S3_SETTINGS_WRITE` - Modify S3 server settings,\n \* `PRIVILEGE_S 3_UPLOADS_READ` - View all S3 uploads present in the system. This will override a bu cket policy that denies the user this permission.,\n \* `PRIVILEGE_S3_UPLOADS_WRITE` - Abort S3 uploads in the system. This will override a bucket policy that denies th e user this permission.,\n \* `PRIVILEGE_SAML_SETTINGS_READ` - View SAML integration

```

settings,\n * `PRIVILEGE_SAML_SETTINGS_WRITE` - Modify SAML integration settings,\n
* `PRIVILEGE_SERVICE_PUBLIC_KEYS_READ` - Internal-Only: Read public keys,\n * `PRIVI
LEGE_SERVICE_PUBLIC_KEYS_WRITE` - Internal-Only: Write public keys,\n * `PRIVILEGE_S
MB_FILE_HANDLE_READ` - List open SMB file handles,\n * `PRIVILEGE_SMB_FILE_HANDLE_WR
ITE` - Force close an open SMB file handle,\n * `PRIVILEGE_SMB_SESSION_READ` - List
logged on SMB sessions,\n * `PRIVILEGE_SMB_SESSION_WRITE` - Force close a logged on
SMB session,\n * `PRIVILEGE_SMB_SHARE_READ` - View configuration of SMB shares and S
MB server settings,\n * `PRIVILEGE_SMB_SHARE_WRITE` - Create, modify, and delete SM
B shares and SMB server settings,\n * `PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_RE
AD` - Recalculate capacity usage of snapshots,\n * `PRIVILEGE_SNAPSHOT_DIFFERENCE_RE
AD` - View the changes between snapshots,\n * `PRIVILEGE_SNAPSHOT_LOCK` - Lock or un
lock snapshots. Configure snapshot policies to lock or unlock snapshots.,\n * `PRIVI
LEGE_SNAPSHOT_POLICY_READ` - View snapshot policies and status,\n * `PRIVILEGE_SNAPS
HOT_POLICY_WRITE` - Create, modify, and delete snapshot policies,\n * `PRIVILEGE_SNA
PSHOT_READ` - List snapshots and view their status and cached capacity. Does not aff
ect the visibility of the virtual `.snapshot` directories,\n * `PRIVILEGE_SNAPSHOT_W
RITE` - Create, modify, and delete snapshots,\n * `PRIVILEGE_SUPPORT_READ` - View su
pport configuration and status,\n * `PRIVILEGE_SUPPORT_WRITE` - Modify cloud-based m
onitoring and remote management,\n * `PRIVILEGE_TENANT_READ` - View any tenant infor
mation,\n * `PRIVILEGE_TENANT_WRITE` - Create, edit or delete tenants,\n * `PRIVILEG
E_TEST_ONLY` - Test only actions,\n * `PRIVILEGE_TIME_READ` - View time and time set
tings,\n * `PRIVILEGE_TIME_WRITE` - Modify time settings,\n * `PRIVILEGE_UNCONFIGURE
D_NODE_READ` - List unconfigured Qumulo nodes,\n * `PRIVILEGE_UPGRADE_READ` - View u
pgrade configuration and status,\n * `PRIVILEGE_UPGRADE_WRITE` - Perform upgrade
s,\n * `PRIVILEGE_WEB_UI_SETTINGS_WRITE` - Modify web UI settings"
    }
  }
}
}
}

```

POST

Create a new role.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "named_role_model",
  "type": "object",

```

```

"properties": {
  "name": {
    "description": "Name of the role. Role names are case-insensitive and may not
contain whitespace.",
    "type": "string"
  },
  "description": {
    "description": "Description of the role",
    "type": "string"
  },
  "privileges": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "PRIVILEGE_AD_READ",
        "PRIVILEGE_AD_USE",
        "PRIVILEGE_AD_WRITE",
        "PRIVILEGE_ANALYTICS_READ",
        "PRIVILEGE_AUDIT_READ",
        "PRIVILEGE_AUDIT_WRITE",
        "PRIVILEGE_AUTH_CACHE_READ",
        "PRIVILEGE_AUTH_CACHE_WRITE",
        "PRIVILEGE_CLUSTER_READ",
        "PRIVILEGE_CLUSTER_WRITE",
        "PRIVILEGE_DEBUG",
        "PRIVILEGE_DNS_READ",
        "PRIVILEGE_DNS_USE",
        "PRIVILEGE_DNS_WRITE",
        "PRIVILEGE_FILE_FULL_ACCESS",
        "PRIVILEGE_FS_ATTRIBUTES_READ",
        "PRIVILEGE_FS_DELETE_TREE_READ",
        "PRIVILEGE_FS_DELETE_TREE_WRITE",
        "PRIVILEGE_FS_LOCK_READ",
        "PRIVILEGE_FS_LOCK_WRITE",
        "PRIVILEGE_FS_SETTINGS_READ",
        "PRIVILEGE_FS_SETTINGS_WRITE",
        "PRIVILEGE_FTP_READ",
        "PRIVILEGE_FTP_WRITE",
        "PRIVILEGE_IDENTITY_MAPPING_READ",
        "PRIVILEGE_IDENTITY_MAPPING_WRITE",
        "PRIVILEGE_IDENTITY_READ",
        "PRIVILEGE_IDENTITY_WRITE",
        "PRIVILEGE_KERBEROS_KEYTAB_READ",
        "PRIVILEGE_KERBEROS_KEYTAB_WRITE",
        "PRIVILEGE_KERBEROS_SETTINGS_READ",

```

```
"PRIVILEGE_KERBEROS_SETTINGS_WRITE",
"PRIVILEGE_KV_READ",
"PRIVILEGE_LDAP_READ",
"PRIVILEGE_LDAP_USE",
"PRIVILEGE_LDAP_WRITE",
"PRIVILEGE_LOCAL_GROUP_READ",
"PRIVILEGE_LOCAL_GROUP_WRITE",
"PRIVILEGE_LOCAL_USER_READ",
"PRIVILEGE_LOCAL_USER_WRITE",
"PRIVILEGE_METRICS_READ",
"PRIVILEGE_NETWORK_IP_ALLOCATION_READ",
"PRIVILEGE_NETWORK_READ",
"PRIVILEGE_NETWORK_WRITE",
"PRIVILEGE_NFS_EXPORT_READ",
"PRIVILEGE_NFS_EXPORT_WRITE",
"PRIVILEGE_POWER_CYCLE",
"PRIVILEGE_QUOTA_READ",
"PRIVILEGE_QUOTA_WRITE",
"PRIVILEGE_RECONCILER_READ",
"PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP",
"PRIVILEGE_REPLICATION_SOURCE_READ",
"PRIVILEGE_REPLICATION_SOURCE_WRITE",
"PRIVILEGE_REPLICATION_TARGET_READ",
"PRIVILEGE_REPLICATION_TARGET_WRITE",
"PRIVILEGE_ROLE_READ",
"PRIVILEGE_ROLE_WRITE",
"PRIVILEGE_SMB_SHARE_READ",
"PRIVILEGE_SMB_SHARE_WRITE",
"PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ",
"PRIVILEGE_SNAPSHOT_DIFFERENCE_READ",
"PRIVILEGE_SNAPSHOT_POLICY_READ",
"PRIVILEGE_SNAPSHOT_POLICY_WRITE",
"PRIVILEGE_SNAPSHOT_READ",
"PRIVILEGE_SNAPSHOT_WRITE",
"PRIVILEGE_SUPPORT_READ",
"PRIVILEGE_SUPPORT_WRITE",
"PRIVILEGE_TEST_ONLY",
"PRIVILEGE_TIME_READ",
"PRIVILEGE_TIME_WRITE",
"PRIVILEGE_UNCONFIGURED_NODE_READ",
"PRIVILEGE_UPGRADE_READ",
"PRIVILEGE_UPGRADE_WRITE",
"PRIVILEGE_SMB_FILE_HANDLE_READ",
"PRIVILEGE_SMB_FILE_HANDLE_WRITE",
"PRIVILEGE_SMB_SESSION_READ",
"PRIVILEGE_SMB_SESSION_WRITE",
```

"PRIVILEGE_REPLICATION_OBJECT_READ",
"PRIVILEGE_REPLICATION_OBJECT_WRITE",
"PRIVILEGE_ENCRYPTION_WRITE",
"PRIVILEGE_ENCRYPTION_READ",
"PRIVILEGE_NFS_SETTINGS_READ",
"PRIVILEGE_NFS_SETTINGS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_READ",
"PRIVILEGE_METRICS_CONFIG_READ",
"PRIVILEGE_METRICS_CONFIG_WRITE",
"PRIVILEGE_REBOOT_USE",
"PRIVILEGE_REBOOT_READ",
"PRIVILEGE_CHECKSUMMING_READ",
"PRIVILEGE_S3_SETTINGS_READ",
"PRIVILEGE_S3_SETTINGS_WRITE",
"PRIVILEGE_WEB_UI_SETTINGS_WRITE",
"PRIVILEGE_S3_CREDENTIALS_READ",
"PRIVILEGE_S3_CREDENTIALS_WRITE",
"PRIVILEGE_TENANT_READ",
"PRIVILEGE_TENANT_WRITE",
"PRIVILEGE_SAML_SETTINGS_READ",
"PRIVILEGE_SAML_SETTINGS_WRITE",
"PRIVILEGE_S3_BUCKETS_READ",
"PRIVILEGE_S3_BUCKETS_WRITE",
"PRIVILEGE_ACCESS_TOKENS_READ",
"PRIVILEGE_ACCESS_TOKENS_WRITE",
"PRIVILEGE_S3_UPLOADS_READ",
"PRIVILEGE_S3_UPLOADS_WRITE",
"PRIVILEGE_SNAPSHOT_LOCK",
"PRIVILEGE_FS_KEY_MANAGEMENT_WRITE",
"PRIVILEGE_FS_KEY_MANAGEMENT_READ",
"PRIVILEGE_IDENTITY_CONFIG_WRITE",
"PRIVILEGE_IDENTITY_CONFIG_READ",
"PRIVILEGE_FILE_READ_ACCESS",
"PRIVILEGE_PORTAL_SPOKE_READ",
"PRIVILEGE_PORTAL_SPOKE_WRITE",
"PRIVILEGE_PORTAL_SPOKE_EVICT",
"PRIVILEGE_PORTAL_HUB_READ",
"PRIVILEGE_PORTAL_HUB_WRITE",
"PRIVILEGE_PORTAL_GLOBAL_READ",
"PRIVILEGE_FS_FILE_LOCK_WRITE",
"PRIVILEGE_LICENSE_READ",
"PRIVILEGE_CAPACITY_READ",
"PRIVILEGE_CAPACITY_WRITE",
"PRIVILEGE_OBJECT_STORAGE_URI_READ",
"PRIVILEGE_OBJECT_STORAGE_URI_WRITE",

```

        "PRIVILEGE_DISK_ERROR_WRITE",
        "PRIVILEGE_DISK_ERROR_READ",
        "PRIVILEGE_OBJECT_STORAGE_CONFIG_READ",
        "PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE"
    ],
    "description": "Privileges the role has been granted:\n * `PRIVILEGE_ACCESS_TOKENS_READ` - View any access tokens present in the system,\n * `PRIVILEGE_ACCESS_TOKENS_WRITE` - Create or delete access tokens for any user in the system,\n * `PRIVILEGE_AD_READ` - Read Qumulo Active Directory settings,\n * `PRIVILEGE_AD_USE` - Use Qumulo's APIs for performing queries against Active Directory,\n * `PRIVILEGE_AD_WRITE` - Modify Qumulo Active Directory settings,\n * `PRIVILEGE_ANALYTICS_READ` - Read cluster analytics,\n * `PRIVILEGE_AUDIT_READ` - Read audit settings,\n * `PRIVILEGE_AUDIT_WRITE` - Modify audit settings,\n * `PRIVILEGE_AUTH_CACHE_READ` - Internal-Only: Read authentication cache settings,\n * `PRIVILEGE_AUTH_CACHE_WRITE` - Internal-Only: Modify authentication cache settings,\n * `PRIVILEGE_CAPACITY_READ` - View the capacity clamp value.,\n * `PRIVILEGE_CAPACITY_WRITE` - Set the capacity clamp value.,\n * `PRIVILEGE_CHECKSUMMING_READ` - View the status of checksumming,\n * `PRIVILEGE_CLUSTER_READ` - View nodes, disks, protection status, and SSL certificate,\n * `PRIVILEGE_CLUSTER_WRITE` - Modify cluster settings and disk/identify LEDs,\n * `PRIVILEGE_DEBUG` - Internal-Only: Perform debug operations on the cluster,\n * `PRIVILEGE_DISK_ERROR_READ` - Internal-Only: Read disk error threshold and status.,\n * `PRIVILEGE_DISK_ERROR_WRITE` - Internal-Only: Modify disk error threshold and revive rejected disks.,\n * `PRIVILEGE_DNS_READ` - Read DNS settings,\n * `PRIVILEGE_DNS_USE` - Perform DNS lookups,\n * `PRIVILEGE_DNS_WRITE` - Modify DNS settings,\n * `PRIVILEGE_ENCRYPTION_READ` - View the status of at-rest-encryption,\n * `PRIVILEGE_ENCRYPTION_WRITE` - Rotate encryption keys for clusters with at-rest-encryption,\n * `PRIVILEGE_FILE_FULL_ACCESS` - Provides full access to all files regardless of permissions,\n * `PRIVILEGE_FILE_READ_ACCESS` - Provides read access to all files regardless of permissions,\n * `PRIVILEGE_FS_ATTRIBUTES_READ` - Read file system statistics,\n * `PRIVILEGE_FS_DELETE_TREE_READ` - View the status of directory tree delete operations,\n * `PRIVILEGE_FS_DELETE_TREE_WRITE` - Use directory tree delete API. Granting this privilege allows the deletion of any file or directory on the cluster. File and directory permissions are not taken into account. Not required for `rm -r`.,\n * `PRIVILEGE_FS_FILE_LOCK_WRITE` - Set or extend file lock retention periods and legal holds.,\n * `PRIVILEGE_FS_KEY_MANAGEMENT_READ` - Read and list public keys for various FS security features.,\n * `PRIVILEGE_FS_KEY_MANAGEMENT_WRITE` - Create and manage public keys for various FS security features.,\n * `PRIVILEGE_FS_LOCK_READ` - View NLN and SMB locks and waiters,\n * `PRIVILEGE_FS_LOCK_WRITE` - Release NLN and SMB locks,\n * `PRIVILEGE_FS_SETTINGS_READ` - View file system permissions settings,\n * `PRIVILEGE_FS_SETTINGS_WRITE` - Modify file system permissions mode,\n * `PRIVILEGE_FTP_READ` - View FTP status and settings,\n * `PRIVILEGE_FTP_WRITE` - Modify FTP status and settings,\n * `PRIVILEGE_IDENTITY_CONFIG_READ` - Read and list identity configurations.,\n * `PRIVILEGE_IDENTITY_CONFIG_WRITE` - Modify identity configurations.,\n * `PRIVILEGE_IDENTITY_MAPPING_READ` - Get AD/LDAP User Defined Mappings,\n * `PRIVILEGE_IDENTITY_MAPPING_WRITE` - Set AD/LDAP User Defined Mappings,\n * `PRIVILEGE_IDENTITY_READ` - Use Qumulo's identity lookup and translation AP

```

Is,\n * `PRIVILEGE\_IDENTITY\_WRITE` - Modify identity attributes and clear authentication cache,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_READ` - View Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_WRITE` - Modify Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_READ` - Read Kerberos settings,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_WRITE` - Modify Kerberos settings,\n * `PRIVILEGE\_KV\_READ` - DEPRECATED: Read and delete KV store entries for all users,\n * `PRIVILEGE\_LDAP\_READ` - View LDAP settings,\n * `PRIVILEGE\_LDAP\_USE` - Use Qumulo's APIs for performing LDAP queries,\n * `PRIVILEGE\_LDAP\_WRITE` - Modify LDAP settings,\n * `PRIVILEGE\_LICENSE\_READ` - Get the cluster's license status.,\n * `PRIVILEGE\_LOCAL\_GROUP\_READ` - View local groups and members,\n * `PRIVILEGE\_LOCAL\_GROUP\_WRITE` - Modify local groups and membership,\n * `PRIVILEGE\_LOCAL\_USER\_READ` - Get information about local users,\n * `PRIVILEGE\_LOCAL\_USER\_WRITE` - Create and modify all local users,\n * `PRIVILEGE\_METRICS\_CONFIG\_READ` - View metrics configuration,\n * `PRIVILEGE\_METRICS\_CONFIG\_WRITE` - Modify metrics configuration,\n * `PRIVILEGE\_METRICS\_READ` - Get all metrics,\n * `PRIVILEGE\_NETWORK\_IP\_ALLOCATION\_READ` - View network IP address allocations,\n * `PRIVILEGE\_NETWORK\_READ` - Read network status and settings,\n * `PRIVILEGE\_NETWORK\_WRITE` - Modify network configuration,\n * `PRIVILEGE\_NFS\_EXPORT\_READ` - View configuration of NFS exports,\n * `PRIVILEGE\_NFS\_EXPORT\_WRITE` - Create, modify, and delete NFS exports,\n * `PRIVILEGE\_NFS\_SETTINGS\_READ` - Internal-Only: View NFS server settings,\n * `PRIVILEGE\_NFS\_SETTINGS\_WRITE` - Internal-Only: Modify NFS server settings,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_READ` - Read object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_WRITE` - Write object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_READ` - View the object storage URIs.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_WRITE` - Add new object storage URIs.,\n * `PRIVILEGE\_PORTAL\_GLOBAL\_READ` - View global portal settings and status,\n * `PRIVILEGE\_PORTAL\_HUB\_READ` - View hub portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_HUB\_WRITE` - Authorize, modify, and delete hub portal relationships. Granting this privilege allows authorizing proposed relationships. Depending on existing file and directory permissions, this privilege can allow remote access to local data under the hub root directory.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_EVICT` - Remove cached files and directories from a spoke portal. Qumulo Core recaches the removed files or directories upon access.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_READ` - View spoke portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_SPOKE\_WRITE` - Create, modify, and delete spoke portal relationships. Granting this privilege allows creating spoke portal root directories. Depending on existing file permissions, this privilege can allow local access to remote files and directories.,\n * `PRIVILEGE\_POWER\_CYCLE` - Shutdown and reboot nodes,\n * `PRIVILEGE\_QUOTA\_READ` - View all file system quotas,\n * `PRIVILEGE\_QUOTA\_WRITE` - Create, modify, and delete file system quotas,\n * `PRIVILEGE\_REBOOT\_READ` - View Reboot Status,\n * `PRIVILEGE\_REBOOT\_USE` - Perform Reboots,\n * `PRIVILEGE\_RECONCILER\_READ` - View reconciler status and metrics,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_READ` - View object store relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_WRITE` - Create, modify, and delete object store relationships. Granting this privilege allows overwriting existing data, replicating, and potentially accessing any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_REPLICATION\_REVERSE\_RELATIONSHIP` - Reverse a source and target relationship,\n * `PRIVILEGE_REPLICAT


```

ION_SOURCE_READ` - View source relationship settings and status,\n * `PRIVILEGE_REPL
ICATION_SOURCE_WRITE` - Create, modify, and delete source relationships. Granting th
is privilege allows replicating and potentially accessing any data on the cluster re
gardless of file and directory permissions.,\n * `PRIVILEGE_REPLICATION_TARGET_REA
D` - View target relationship settings and status,\n * `PRIVILEGE_REPLICATION_TARGE
T_WRITE` - Create, modify, and delete target relationships. Granting this privilege
allows overwriting any data on the cluster regardless of file and directory permissi
ons.,\n * `PRIVILEGE_ROLE_READ` - View roles and assignments,\n * `PRIVILEGE_ROLE_W
RITE` - Create and modify roles and assignments,\n * `PRIVILEGE_S3_BUCKETS_READ` - Vi
ew all S3 buckets and bucket policies present in the system,\n * `PRIVILEGE_S3_BUCKE
TS_WRITE` - Create or delete any S3 bucket in the system, and create, delete, or mod
ify policies for any S3 bucket in the system. Subject to having sufficient FS permis
sions.,\n * `PRIVILEGE_S3_CREDENTIALS_READ` - View any S3 access key present in the
system,\n * `PRIVILEGE_S3_CREDENTIALS_WRITE` - Create or delete S3 access keys for a
ny user in the system,\n * `PRIVILEGE_S3_SETTINGS_READ` - View S3 server setting
s,\n * `PRIVILEGE_S3_SETTINGS_WRITE` - Modify S3 server settings,\n * `PRIVILEGE_S
3_UPLOADS_READ` - View all S3 uploads present in the system. This will override a bu
cket policy that denies the user this permission.,\n * `PRIVILEGE_S3_UPLOADS_WRITE`
- Abort S3 uploads in the system. This will override a bucket policy that denies th
e user this permission.,\n * `PRIVILEGE_SAML_SETTINGS_READ` - View SAML integration
settings,\n * `PRIVILEGE_SAML_SETTINGS_WRITE` - Modify SAML integration settings,\n
* `PRIVILEGE_SERVICE_PUBLIC_KEYS_READ` - Internal-Only: Read public keys,\n * `PRIV
ILEGE_SERVICE_PUBLIC_KEYS_WRITE` - Internal-Only: Write public keys,\n * `PRIVILEGE_S
MB_FILE_HANDLE_READ` - List open SMB file handles,\n * `PRIVILEGE_SMB_FILE_HANDLE_W
RITE` - Force close an open SMB file handle,\n * `PRIVILEGE_SMB_SESSION_READ` - List
logged on SMB sessions,\n * `PRIVILEGE_SMB_SESSION_WRITE` - Force close a logged on
SMB session,\n * `PRIVILEGE_SMB_SHARE_READ` - View configuration of SMB shares and S
MB server settings,\n * `PRIVILEGE_SMB_SHARE_WRITE` - Create, modify, and delete SM
B shares and SMB server settings,\n * `PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_R
EAD` - Recalculate capacity usage of snapshots,\n * `PRIVILEGE_SNAPSHOT_DIFFERENCE_R
EAD` - View the changes between snapshots,\n * `PRIVILEGE_SNAPSHOT_LOCK` - Lock or un
lock snapshots. Configure snapshot policies to lock or unlock snapshots.,\n * `PRIV
ILEGE_SNAPSHOT_POLICY_READ` - View snapshot policies and status,\n * `PRIVILEGE_SNA
PSHOT_POLICY_WRITE` - Create, modify, and delete snapshot policies,\n * `PRIVILEGE_SNA
PSHOT_READ` - List snapshots and view their status and cached capacity. Does not aff
ect the visibility of the virtual `.snapshot` directories,\n * `PRIVILEGE_SNAPSHOT_W
RITE` - Create, modify, and delete snapshots,\n * `PRIVILEGE_SUPPORT_READ` - View su
pport configuration and status,\n * `PRIVILEGE_SUPPORT_WRITE` - Modify cloud-based m
onitoring and remote management,\n * `PRIVILEGE_TENANT_READ` - View any tenant infor
mation,\n * `PRIVILEGE_TENANT_WRITE` - Create, edit or delete tenants,\n * `PRIVILEG
E_TEST_ONLY` - Test only actions,\n * `PRIVILEGE_TIME_READ` - View time and time set
tings,\n * `PRIVILEGE_TIME_WRITE` - Modify time settings,\n * `PRIVILEGE_UNCONFIGURE
D_NODE_READ` - List unconfigured Qumulo nodes,\n * `PRIVILEGE_UPGRADE_READ` - View u
pgrade configuration and status,\n * `PRIVILEGE_UPGRADE_WRITE` - Perform upgrade
s,\n * `PRIVILEGE_WEB_UI_SETTINGS_WRITE` - Modify web UI settings"
}

```



```
}  
}  
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{  
  "description": "named_role_model",  
  "type": "object",  
  "properties": {  
    "name": {  
      "description": "Name of the role. Role names are case-insensitive and may not  
contain whitespace.",  
      "type": "string"  
    },  
    "description": {  
      "description": "Description of the role",  
      "type": "string"  
    },  
    "privileges": {  
      "type": "array",  
      "items": {  
        "type": "string",  
        "enum": [  
          "PRIVILEGE_AD_READ",  
          "PRIVILEGE_AD_USE",  
          "PRIVILEGE_AD_WRITE",  
          "PRIVILEGE_ANALYTICS_READ",  
          "PRIVILEGE_AUDIT_READ",  
          "PRIVILEGE_AUDIT_WRITE",  
          "PRIVILEGE_AUTH_CACHE_READ",  
          "PRIVILEGE_AUTH_CACHE_WRITE",  
          "PRIVILEGE_CLUSTER_READ",  
          "PRIVILEGE_CLUSTER_WRITE",  
          "PRIVILEGE_DEBUG",  
          "PRIVILEGE_DNS_READ",  
          "PRIVILEGE_DNS_USE",  
        ]  
      }  
    }  
  }  
}
```

```
"PRIVILEGE_DNS_WRITE",
"PRIVILEGE_FILE_FULL_ACCESS",
"PRIVILEGE_FS_ATTRIBUTES_READ",
"PRIVILEGE_FS_DELETE_TREE_READ",
"PRIVILEGE_FS_DELETE_TREE_WRITE",
"PRIVILEGE_FS_LOCK_READ",
"PRIVILEGE_FS_LOCK_WRITE",
"PRIVILEGE_FS_SETTINGS_READ",
"PRIVILEGE_FS_SETTINGS_WRITE",
"PRIVILEGE_FTP_READ",
"PRIVILEGE_FTP_WRITE",
"PRIVILEGE_IDENTITY_MAPPING_READ",
"PRIVILEGE_IDENTITY_MAPPING_WRITE",
"PRIVILEGE_IDENTITY_READ",
"PRIVILEGE_IDENTITY_WRITE",
"PRIVILEGE_KERBEROS_KEYTAB_READ",
"PRIVILEGE_KERBEROS_KEYTAB_WRITE",
"PRIVILEGE_KERBEROS_SETTINGS_READ",
"PRIVILEGE_KERBEROS_SETTINGS_WRITE",
"PRIVILEGE_KV_READ",
"PRIVILEGE_LDAP_READ",
"PRIVILEGE_LDAP_USE",
"PRIVILEGE_LDAP_WRITE",
"PRIVILEGE_LOCAL_GROUP_READ",
"PRIVILEGE_LOCAL_GROUP_WRITE",
"PRIVILEGE_LOCAL_USER_READ",
"PRIVILEGE_LOCAL_USER_WRITE",
"PRIVILEGE_METRICS_READ",
"PRIVILEGE_NETWORK_IP_ALLOCATION_READ",
"PRIVILEGE_NETWORK_READ",
"PRIVILEGE_NETWORK_WRITE",
"PRIVILEGE_NFS_EXPORT_READ",
"PRIVILEGE_NFS_EXPORT_WRITE",
"PRIVILEGE_POWER_CYCLE",
"PRIVILEGE_QUOTA_READ",
"PRIVILEGE_QUOTA_WRITE",
"PRIVILEGE_RECONCILER_READ",
"PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP",
"PRIVILEGE_REPLICATION_SOURCE_READ",
"PRIVILEGE_REPLICATION_SOURCE_WRITE",
"PRIVILEGE_REPLICATION_TARGET_READ",
"PRIVILEGE_REPLICATION_TARGET_WRITE",
"PRIVILEGE_ROLE_READ",
"PRIVILEGE_ROLE_WRITE",
"PRIVILEGE_SMB_SHARE_READ",
"PRIVILEGE_SMB_SHARE_WRITE",
```

"PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ",
"PRIVILEGE_SNAPSHOT_DIFFERENCE_READ",
"PRIVILEGE_SNAPSHOT_POLICY_READ",
"PRIVILEGE_SNAPSHOT_POLICY_WRITE",
"PRIVILEGE_SNAPSHOT_READ",
"PRIVILEGE_SNAPSHOT_WRITE",
"PRIVILEGE_SUPPORT_READ",
"PRIVILEGE_SUPPORT_WRITE",
"PRIVILEGE_TEST_ONLY",
"PRIVILEGE_TIME_READ",
"PRIVILEGE_TIME_WRITE",
"PRIVILEGE_UNCONFIGURED_NODE_READ",
"PRIVILEGE_UPGRADE_READ",
"PRIVILEGE_UPGRADE_WRITE",
"PRIVILEGE_SMB_FILE_HANDLE_READ",
"PRIVILEGE_SMB_FILE_HANDLE_WRITE",
"PRIVILEGE_SMB_SESSION_READ",
"PRIVILEGE_SMB_SESSION_WRITE",
"PRIVILEGE_REPLICATION_OBJECT_READ",
"PRIVILEGE_REPLICATION_OBJECT_WRITE",
"PRIVILEGE_ENCRYPTION_WRITE",
"PRIVILEGE_ENCRYPTION_READ",
"PRIVILEGE_NFS_SETTINGS_READ",
"PRIVILEGE_NFS_SETTINGS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_READ",
"PRIVILEGE_METRICS_CONFIG_READ",
"PRIVILEGE_METRICS_CONFIG_WRITE",
"PRIVILEGE_REBOOT_USE",
"PRIVILEGE_REBOOT_READ",
"PRIVILEGE_CHECKSUMMING_READ",
"PRIVILEGE_S3_SETTINGS_READ",
"PRIVILEGE_S3_SETTINGS_WRITE",
"PRIVILEGE_WEB_UI_SETTINGS_WRITE",
"PRIVILEGE_S3_CREDENTIALS_READ",
"PRIVILEGE_S3_CREDENTIALS_WRITE",
"PRIVILEGE_TENANT_READ",
"PRIVILEGE_TENANT_WRITE",
"PRIVILEGE_SAML_SETTINGS_READ",
"PRIVILEGE_SAML_SETTINGS_WRITE",
"PRIVILEGE_S3_BUCKETS_READ",
"PRIVILEGE_S3_BUCKETS_WRITE",
"PRIVILEGE_ACCESS_TOKENS_READ",
"PRIVILEGE_ACCESS_TOKENS_WRITE",
"PRIVILEGE_S3_UPLOADS_READ",
"PRIVILEGE_S3_UPLOADS_WRITE",

```

"PRIVILEGE_SNAPSHOT_LOCK",
"PRIVILEGE_FS_KEY_MANAGEMENT_WRITE",
"PRIVILEGE_FS_KEY_MANAGEMENT_READ",
"PRIVILEGE_IDENTITY_CONFIG_WRITE",
"PRIVILEGE_IDENTITY_CONFIG_READ",
"PRIVILEGE_FILE_READ_ACCESS",
"PRIVILEGE_PORTAL_SPOKE_READ",
"PRIVILEGE_PORTAL_SPOKE_WRITE",
"PRIVILEGE_PORTAL_SPOKE_EVICT",
"PRIVILEGE_PORTAL_HUB_READ",
"PRIVILEGE_PORTAL_HUB_WRITE",
"PRIVILEGE_PORTAL_GLOBAL_READ",
"PRIVILEGE_FS_FILE_LOCK_WRITE",
"PRIVILEGE_LICENSE_READ",
"PRIVILEGE_CAPACITY_READ",
"PRIVILEGE_CAPACITY_WRITE",
"PRIVILEGE_OBJECT_STORAGE_URIS_READ",
"PRIVILEGE_OBJECT_STORAGE_URIS_WRITE",
"PRIVILEGE_DISK_ERROR_WRITE",
"PRIVILEGE_DISK_ERROR_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE"
],
"description": "Privileges the role has been granted:\n * `PRIVILEGE_ACCESS_TOKENS_READ` - View any access tokens present in the system,\n * `PRIVILEGE_ACCESS_TOKENS_WRITE` - Create or delete access tokens for any user in the system,\n * `PRIVILEGE_AD_READ` - Read Qumulo Active Directory settings,\n * `PRIVILEGE_AD_USE` - Use Qumulo's APIs for performing queries against Active Directory,\n * `PRIVILEGE_AD_WRITE` - Modify Qumulo Active Directory settings,\n * `PRIVILEGE_ANALYTICS_READ` - Read cluster analytics,\n * `PRIVILEGE_AUDIT_READ` - Read audit settings,\n * `PRIVILEGE_AUDIT_WRITE` - Modify audit settings,\n * `PRIVILEGE_AUTH_CACHE_READ` - Internal-Only: Read authentication cache settings,\n * `PRIVILEGE_AUTH_CACHE_WRITE` - Internal-Only: Modify authentication cache settings,\n * `PRIVILEGE_CAPACITY_READ` - View the capacity clamp value.,\n * `PRIVILEGE_CAPACITY_WRITE` - Set the capacity clamp value.,\n * `PRIVILEGE_CHECKSUMMING_READ` - View the status of checksumming,\n * `PRIVILEGE_CLUSTER_READ` - View nodes, disks, protection status, and SSL certificate,\n * `PRIVILEGE_CLUSTER_WRITE` - Modify cluster settings and disk/identify LEDs,\n * `PRIVILEGE_DEBUG` - Internal-Only: Perform debug operations on the cluster,\n * `PRIVILEGE_DISK_ERROR_READ` - Internal-Only: Read disk error threshold and status.,\n * `PRIVILEGE_DISK_ERROR_WRITE` - Internal-Only: Modify disk error threshold and revive rejected disks.,\n * `PRIVILEGE_DNS_READ` - Read DNS settings,\n * `PRIVILEGE_DNS_USE` - Perform DNS lookups,\n * `PRIVILEGE_DNS_WRITE` - Modify DNS settings,\n * `PRIVILEGE_ENCRYPTION_READ` - View the status of at-rest-encryption,\n * `PRIVILEGE_ENCRYPTION_WRITE` - Rotate encryption keys for clusters with at-rest-encryption,\n * `PRIVILEGE_FILE_FULL_ACCESS` - Provides full access to all files regardless of permissions,\n * `PRIVILEGE_FILE_READ_ACCESS` - Provides read access to all files

```

es regardless of permissions,\n * `PRIVILEGE\_FS\_ATTRIBUTES\_READ` - Read file system statistics,\n * `PRIVILEGE\_FS\_DELETE\_TREE\_READ` - View the status of directory tree delete operations,\n * `PRIVILEGE\_FS\_DELETE\_TREE\_WRITE` - Use directory tree delete API. Granting this privilege allows the deletion of any file or directory on the cluster. File and directory permissions are not taken into account. Not required for `rm -r`.,\n * `PRIVILEGE\_FS\_FILE\_LOCK\_WRITE` - Set or extend file lock retention periods and legal holds.,\n * `PRIVILEGE\_FS\_KEY\_MANAGEMENT\_READ` - Read and list public keys for various FS security features.,\n * `PRIVILEGE\_FS\_KEY\_MANAGEMENT\_WRITE` - Create and manage public keys for various FS security features.,\n * `PRIVILEGE\_FS\_LOCK\_READ` - View NLN and SMB locks and waiters,\n * `PRIVILEGE\_FS\_LOCK\_WRITE` - Release NLN and SMB locks,\n * `PRIVILEGE\_FS\_SETTINGS\_READ` - View file system permissions settings,\n * `PRIVILEGE\_FS\_SETTINGS\_WRITE` - Modify file system permissions mode,\n * `PRIVILEGE\_FTP\_READ` - View FTP status and settings,\n * `PRIVILEGE\_FTP\_WRITE` - Modify FTP status and settings,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_READ` - Read and list identity configurations.,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_WRITE` - Modify identity configurations.,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_READ` - Get AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_WRITE` - Set AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_READ` - Use Qumulo's identity lookup and translation APIs,\n * `PRIVILEGE\_IDENTITY\_WRITE` - Modify identity attributes and clear authentication cache,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_READ` - View Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_WRITE` - Modify Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_READ` - Read Kerberos settings,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_WRITE` - Modify Kerberos settings,\n * `PRIVILEGE\_KV\_READ` - DEPRECATED: Read and delete KV store entries for all users,\n * `PRIVILEGE\_LDAP\_READ` - View LDAP settings,\n * `PRIVILEGE\_LDAP\_USE` - Use Qumulo's APIs for performing LDAP queries,\n * `PRIVILEGE\_LDAP\_WRITE` - Modify LDAP settings,\n * `PRIVILEGE\_LICENSE\_READ` - Get the cluster's license status.,\n * `PRIVILEGE\_LOCAL\_GROUP\_READ` - View local groups and members,\n * `PRIVILEGE\_LOCAL\_GROUP\_WRITE` - Modify local groups and membership,\n * `PRIVILEGE\_LOCAL\_USER\_READ` - Get information about local users,\n * `PRIVILEGE\_LOCAL\_USER\_WRITE` - Create and modify all local users,\n * `PRIVILEGE\_METRICS\_CONFIG\_READ` - View metrics configuration,\n * `PRIVILEGE\_METRICS\_CONFIG\_WRITE` - Modify metrics configuration,\n * `PRIVILEGE\_METRICS\_READ` - Get all metrics,\n * `PRIVILEGE\_NETWORK\_IP\_ALLOCATION\_READ` - View network IP address allocations,\n * `PRIVILEGE\_NETWORK\_READ` - Read network status and settings,\n * `PRIVILEGE\_NETWORK\_WRITE` - Modify network configuration,\n * `PRIVILEGE\_NFS\_EXPORT\_READ` - View configuration of NFS exports,\n * `PRIVILEGE\_NFS\_EXPORT\_WRITE` - Create, modify, and delete NFS exports,\n * `PRIVILEGE\_NFS\_SETTINGS\_READ` - Internal-Only: View NFS server settings,\n * `PRIVILEGE\_NFS\_SETTINGS\_WRITE` - Internal-Only: Modify NFS server settings,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_READ` - Read object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_WRITE` - Write object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_READ` - View the object storage URIs.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_WRITE` - Add new object storage URIs.,\n * `PRIVILEGE\_PORTAL\_GLOBAL\_READ` - View global portal settings and status,\n * `PRIVILEGE\_PORTAL\_HUB\_READ` - View hub portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_HUB\_WRITE` - Authorize, modify, and delete hub portal relationships. Granting this privilege allows authorizing proposed relationship

s. Depending on existing file and directory permissions, this privilege can allow remote access to local data under the hub root directory.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_EVICT` - Remove cached files and directories from a spoke portal. Qumulo Core recaches the removed files or directories upon access.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_READ` - View spoke portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_SPOKE\_WRITE` - Create, modify, and delete spoke portal relationships. Granting this privilege allows creating spoke portal root directories. Depending on existing file permissions, this privilege can allow local access to remote files and directories.,\n * `PRIVILEGE\_POWER\_CYCLE` - Shutdown and reboot nodes,\n * `PRIVILEGE\_QUOTA\_READ` - View all file system quotas,\n * `PRIVILEGE\_QUOTA\_WRITE` - Create, modify, and delete file system quotas,\n * `PRIVILEGE\_REBOOT\_READ` - View Reboot Status,\n * `PRIVILEGE\_REBOOT\_USE` - Perform Reboots,\n * `PRIVILEGE\_RECONCILER\_READ` - View reconciler status and metrics,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_READ` - View object store relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_WRITE` - Create, modify, and delete object store relationships. Granting this privilege allows overwriting existing data, replicating, and potentially accessing any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_REPLICATION\_REVERSE\_RELATIONSHIP` - Reverse a source and target relationship,\n * `PRIVILEGE\_REPLICATION\_SOURCE\_READ` - View source relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_SOURCE\_WRITE` - Create, modify, and delete source relationships. Granting this privilege allows replicating and potentially accessing any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_REPLICATION\_TARGET\_READ` - View target relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_TARGET\_WRITE` - Create, modify, and delete target relationships. Granting this privilege allows overwriting any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_ROLE\_READ` - View roles and assignments,\n * `PRIVILEGE\_ROLE\_WRITE` - Create and modify roles and assignments,\n * `PRIVILEGE\_S3\_BUCKETS\_READ` - View all S3 buckets and bucket policies present in the system,\n * `PRIVILEGE\_S3\_BUCKETS\_WRITE` - Create or delete any S3 bucket in the system, and create, delete, or modify policies for any S3 bucket in the system. Subject to having sufficient FS permissions.,\n * `PRIVILEGE\_S3\_CREDENTIALS\_READ` - View any S3 access key present in the system,\n * `PRIVILEGE\_S3\_CREDENTIALS\_WRITE` - Create or delete S3 access keys for any user in the system,\n * `PRIVILEGE\_S3\_SETTINGS\_READ` - View S3 server settings,\n * `PRIVILEGE\_S3\_SETTINGS\_WRITE` - Modify S3 server settings,\n * `PRIVILEGE\_S3\_UPLOADS\_READ` - View all S3 uploads present in the system. This will override a bucket policy that denies the user this permission.,\n * `PRIVILEGE\_S3\_UPLOADS\_WRITE` - Abort S3 uploads in the system. This will override a bucket policy that denies the user this permission.,\n * `PRIVILEGE\_SAML\_SETTINGS\_READ` - View SAML integration settings,\n * `PRIVILEGE\_SAML\_SETTINGS\_WRITE` - Modify SAML integration settings,\n * `PRIVILEGE\_SERVICE\_PUBLIC\_KEYS\_READ` - Internal-Only: Read public keys,\n * `PRIVILEGE\_SERVICE\_PUBLIC\_KEYS\_WRITE` - Internal-Only: Write public keys,\n * `PRIVILEGE\_SMB\_FILE\_HANDLE\_READ` - List open SMB file handles,\n * `PRIVILEGE\_SMB\_FILE\_HANDLE\_WRITE` - Force close an open SMB file handle,\n * `PRIVILEGE\_SMB\_SESSION\_READ` - List logged on SMB sessions,\n * `PRIVILEGE\_SMB\_SESSION\_WRITE` - Force close a logged on SMB session,\n * `PRIVILEGE\_SMB\_SHARE\_READ` - View configuration of SMB shares and SMB server settings,\n * `PRIVILEGE\_SMB\_SHARE\_WRITE` - Create, modify, and delete SM

```

B shares and SMB server settings,\n * `PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ` - Recalculate capacity usage of snapshots,\n * `PRIVILEGE_SNAPSHOT_DIFFERENCE_READ` - View the changes between snapshots,\n * `PRIVILEGE_SNAPSHOT_LOCK` - Lock or unlock snapshots. Configure snapshot policies to lock or unlock snapshots.,\n * `PRIVILEGE_SNAPSHOT_POLICY_READ` - View snapshot policies and status,\n * `PRIVILEGE_SNAPSHOT_POLICY_WRITE` - Create, modify, and delete snapshot policies,\n * `PRIVILEGE_SNAPSHOT_READ` - List snapshots and view their status and cached capacity. Does not affect the visibility of the virtual `.snapshot` directories,\n * `PRIVILEGE_SNAPSHOT_WRITE` - Create, modify, and delete snapshots,\n * `PRIVILEGE_SUPPORT_READ` - View support configuration and status,\n * `PRIVILEGE_SUPPORT_WRITE` - Modify cloud-based monitoring and remote management,\n * `PRIVILEGE_TENANT_READ` - View any tenant information,\n * `PRIVILEGE_TENANT_WRITE` - Create, edit or delete tenants,\n * `PRIVILEGE_TEST_ONLY` - Test only actions,\n * `PRIVILEGE_TIME_READ` - View time and time settings,\n * `PRIVILEGE_TIME_WRITE` - Modify time settings,\n * `PRIVILEGE_UNCONFIGURE_NODE_READ` - List unconfigured Qumulo nodes,\n * `PRIVILEGE_UPGRADE_READ` - View upgrade configuration and status,\n * `PRIVILEGE_UPGRADE_WRITE` - Perform upgrades,\n * `PRIVILEGE_WEB_UI_SETTINGS_WRITE` - Modify web UI settings"
    }
  }
}

```

auth/roles/{role_name}

Endpoint

/v1/auth/roles/{role_name}

GET

Retrieve information about the role.

Parameters

Name	Description	Required
role_name	The name of the role (This page URL-encodes the name for you)	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "role_model",
  "type": "object",
  "properties": {
    "description": {
      "description": "Description of the role",
      "type": "string"
    },
    "privileges": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "PRIVILEGE_AD_READ",
          "PRIVILEGE_AD_USE",
          "PRIVILEGE_AD_WRITE",
          "PRIVILEGE_ANALYTICS_READ",
          "PRIVILEGE_AUDIT_READ",
          "PRIVILEGE_AUDIT_WRITE",

```



```
"PRIVILEGE_AUTH_CACHE_READ",
"PRIVILEGE_AUTH_CACHE_WRITE",
"PRIVILEGE_CLUSTER_READ",
"PRIVILEGE_CLUSTER_WRITE",
"PRIVILEGE_DEBUG",
"PRIVILEGE_DNS_READ",
"PRIVILEGE_DNS_USE",
"PRIVILEGE_DNS_WRITE",
"PRIVILEGE_FILE_FULL_ACCESS",
"PRIVILEGE_FS_ATTRIBUTES_READ",
"PRIVILEGE_FS_DELETE_TREE_READ",
"PRIVILEGE_FS_DELETE_TREE_WRITE",
"PRIVILEGE_FS_LOCK_READ",
"PRIVILEGE_FS_LOCK_WRITE",
"PRIVILEGE_FS_SETTINGS_READ",
"PRIVILEGE_FS_SETTINGS_WRITE",
"PRIVILEGE_FTP_READ",
"PRIVILEGE_FTP_WRITE",
"PRIVILEGE_IDENTITY_MAPPING_READ",
"PRIVILEGE_IDENTITY_MAPPING_WRITE",
"PRIVILEGE_IDENTITY_READ",
"PRIVILEGE_IDENTITY_WRITE",
"PRIVILEGE_KERBEROS_KEYTAB_READ",
"PRIVILEGE_KERBEROS_KEYTAB_WRITE",
"PRIVILEGE_KERBEROS_SETTINGS_READ",
"PRIVILEGE_KERBEROS_SETTINGS_WRITE",
"PRIVILEGE_KV_READ",
"PRIVILEGE_LDAP_READ",
"PRIVILEGE_LDAP_USE",
"PRIVILEGE_LDAP_WRITE",
"PRIVILEGE_LOCAL_GROUP_READ",
"PRIVILEGE_LOCAL_GROUP_WRITE",
"PRIVILEGE_LOCAL_USER_READ",
"PRIVILEGE_LOCAL_USER_WRITE",
"PRIVILEGE_METRICS_READ",
"PRIVILEGE_NETWORK_IP_ALLOCATION_READ",
"PRIVILEGE_NETWORK_READ",
"PRIVILEGE_NETWORK_WRITE",
"PRIVILEGE_NFS_EXPORT_READ",
"PRIVILEGE_NFS_EXPORT_WRITE",
"PRIVILEGE_POWER_CYCLE",
"PRIVILEGE_QUOTA_READ",
"PRIVILEGE_QUOTA_WRITE",
"PRIVILEGE_RECONCILER_READ",
"PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP",
"PRIVILEGE_REPLICATION_SOURCE_READ",
```

"PRIVILEGE_REPLICATION_SOURCE_WRITE",
"PRIVILEGE_REPLICATION_TARGET_READ",
"PRIVILEGE_REPLICATION_TARGET_WRITE",
"PRIVILEGE_ROLE_READ",
"PRIVILEGE_ROLE_WRITE",
"PRIVILEGE_SMB_SHARE_READ",
"PRIVILEGE_SMB_SHARE_WRITE",
"PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ",
"PRIVILEGE_SNAPSHOT_DIFFERENCE_READ",
"PRIVILEGE_SNAPSHOT_POLICY_READ",
"PRIVILEGE_SNAPSHOT_POLICY_WRITE",
"PRIVILEGE_SNAPSHOT_READ",
"PRIVILEGE_SNAPSHOT_WRITE",
"PRIVILEGE_SUPPORT_READ",
"PRIVILEGE_SUPPORT_WRITE",
"PRIVILEGE_TEST_ONLY",
"PRIVILEGE_TIME_READ",
"PRIVILEGE_TIME_WRITE",
"PRIVILEGE_UNCONFIGURED_NODE_READ",
"PRIVILEGE_UPGRADE_READ",
"PRIVILEGE_UPGRADE_WRITE",
"PRIVILEGE_SMB_FILE_HANDLE_READ",
"PRIVILEGE_SMB_FILE_HANDLE_WRITE",
"PRIVILEGE_SMB_SESSION_READ",
"PRIVILEGE_SMB_SESSION_WRITE",
"PRIVILEGE_REPLICATION_OBJECT_READ",
"PRIVILEGE_REPLICATION_OBJECT_WRITE",
"PRIVILEGE_ENCRYPTION_WRITE",
"PRIVILEGE_ENCRYPTION_READ",
"PRIVILEGE_NFS_SETTINGS_READ",
"PRIVILEGE_NFS_SETTINGS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_READ",
"PRIVILEGE_METRICS_CONFIG_READ",
"PRIVILEGE_METRICS_CONFIG_WRITE",
"PRIVILEGE_REBOOT_USE",
"PRIVILEGE_REBOOT_READ",
"PRIVILEGE_CHECKSUMMING_READ",
"PRIVILEGE_S3_SETTINGS_READ",
"PRIVILEGE_S3_SETTINGS_WRITE",
"PRIVILEGE_WEB_UI_SETTINGS_WRITE",
"PRIVILEGE_S3_CREDENTIALS_READ",
"PRIVILEGE_S3_CREDENTIALS_WRITE",
"PRIVILEGE_TENANT_READ",
"PRIVILEGE_TENANT_WRITE",
"PRIVILEGE_SAML_SETTINGS_READ",

```

"PRIVILEGE_SAML_SETTINGS_WRITE",
"PRIVILEGE_S3_BUCKETS_READ",
"PRIVILEGE_S3_BUCKETS_WRITE",
"PRIVILEGE_ACCESS_TOKENS_READ",
"PRIVILEGE_ACCESS_TOKENS_WRITE",
"PRIVILEGE_S3_UPLOADS_READ",
"PRIVILEGE_S3_UPLOADS_WRITE",
"PRIVILEGE_SNAPSHOT_LOCK",
"PRIVILEGE_FS_KEY_MANAGEMENT_WRITE",
"PRIVILEGE_FS_KEY_MANAGEMENT_READ",
"PRIVILEGE_IDENTITY_CONFIG_WRITE",
"PRIVILEGE_IDENTITY_CONFIG_READ",
"PRIVILEGE_FILE_READ_ACCESS",
"PRIVILEGE_PORTAL_SPOKE_READ",
"PRIVILEGE_PORTAL_SPOKE_WRITE",
"PRIVILEGE_PORTAL_SPOKE_EVICT",
"PRIVILEGE_PORTAL_HUB_READ",
"PRIVILEGE_PORTAL_HUB_WRITE",
"PRIVILEGE_PORTAL_GLOBAL_READ",
"PRIVILEGE_FS_FILE_LOCK_WRITE",
"PRIVILEGE_LICENSE_READ",
"PRIVILEGE_CAPACITY_READ",
"PRIVILEGE_CAPACITY_WRITE",
"PRIVILEGE_OBJECT_STORAGE_URIS_READ",
"PRIVILEGE_OBJECT_STORAGE_URIS_WRITE",
"PRIVILEGE_DISK_ERROR_WRITE",
"PRIVILEGE_DISK_ERROR_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE"
],
"description": "Privileges the role has been granted:\n * `PRIVILEGE_ACCESS_TOKENS_READ` - View any access tokens present in the system,\n * `PRIVILEGE_ACCESS_TOKENS_WRITE` - Create or delete access tokens for any user in the system,\n * `PRIVILEGE_AD_READ` - Read Qumulo Active Directory settings,\n * `PRIVILEGE_AD_USE` - Use Qumulo's APIs for performing queries against Active Directory,\n * `PRIVILEGE_AD_WRITE` - Modify Qumulo Active Directory settings,\n * `PRIVILEGE_ANALYTICS_READ` - Read cluster analytics,\n * `PRIVILEGE_AUDIT_READ` - Read audit settings,\n * `PRIVILEGE_AUDIT_WRITE` - Modify audit settings,\n * `PRIVILEGE_AUTH_CACHE_READ` - Internal-Only: Read authentication cache settings,\n * `PRIVILEGE_AUTH_CACHE_WRITE` - Internal-Only: Modify authentication cache settings,\n * `PRIVILEGE_CAPACITY_READ` - View the capacity clamp value.,\n * `PRIVILEGE_CAPACITY_WRITE` - Set the capacity clamp value.,\n * `PRIVILEGE_CHECKSUMMING_READ` - View the status of checksumming,\n * `PRIVILEGE_CLUSTER_READ` - View nodes, disks, protection status, and SSL certificate,\n * `PRIVILEGE_CLUSTER_WRITE` - Modify cluster settings and disk/identify LEDs,\n * `PRIVILEGE_DEBUG` - Internal-Only: Perform debug operations on the cluster,\n * `PRIVILEGE_DISK_ERROR_READ` - Internal-Only: Read disk error threshold and st

```

atus.,\n * `PRIVILEGE\_DISK\_ERROR\_WRITE` - Internal-Only: Modify disk error threshold and revive rejected disks.,\n * `PRIVILEGE\_DNS\_READ` - Read DNS settings,\n * `PRIVILEGE\_DNS\_USE` - Perform DNS lookups,\n * `PRIVILEGE\_DNS\_WRITE` - Modify DNS settings,\n * `PRIVILEGE\_ENCRYPTION\_READ` - View the status of at-rest-encryption,\n * `PRIVILEGE\_ENCRYPTION\_WRITE` - Rotate encryption keys for clusters with at-rest-encryption,\n * `PRIVILEGE\_FILE\_FULL\_ACCESS` - Provides full access to all files regardless of permissions,\n * `PRIVILEGE\_FILE\_READ\_ACCESS` - Provides read access to all files regardless of permissions,\n * `PRIVILEGE\_FS\_ATTRIBUTES\_READ` - Read file system statistics,\n * `PRIVILEGE\_FS\_DELETE\_TREE\_READ` - View the status of directory tree delete operations,\n * `PRIVILEGE\_FS\_DELETE\_TREE\_WRITE` - Use directory tree delete API. Granting this privilege allows the deletion of any file or directory on the cluster. File and directory permissions are not taken into account. Not required for `rm -r`.,\n * `PRIVILEGE\_FS\_FILE\_LOCK\_WRITE` - Set or extend file lock retention periods and legal holds.,\n * `PRIVILEGE\_FS\_KEY\_MANAGEMENT\_READ` - Read and list public keys for various FS security features.,\n * `PRIVILEGE\_FS\_KEY\_MANAGEMENT\_WRITE` - Create and manage public keys for various FS security features.,\n * `PRIVILEGE\_FS\_LOCK\_READ` - View NLM and SMB locks and waiters,\n * `PRIVILEGE\_FS\_LOCK\_WRITE` - Release NLM and SMB locks,\n * `PRIVILEGE\_FS\_SETTINGS\_READ` - View file system permissions settings,\n * `PRIVILEGE\_FS\_SETTINGS\_WRITE` - Modify file system permissions mode,\n * `PRIVILEGE\_FTP\_READ` - View FTP status and settings,\n * `PRIVILEGE\_FTP\_WRITE` - Modify FTP status and settings,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_READ` - Read and list identity configurations.,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_WRITE` - Modify identity configurations.,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_READ` - Get AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_WRITE` - Set AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_READ` - Use Qumulo's identity lookup and translation APIs,\n * `PRIVILEGE\_IDENTITY\_WRITE` - Modify identity attributes and clear authentication cache,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_READ` - View Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_WRITE` - Modify Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_READ` - Read Kerberos settings,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_WRITE` - Modify Kerberos settings,\n * `PRIVILEGE\_KV\_READ` - DEPRECATED: Read and delete KV store entries for all users,\n * `PRIVILEGE\_LDAP\_READ` - View LDAP settings,\n * `PRIVILEGE\_LDAP\_USE` - Use Qumulo's APIs for performing LDAP queries,\n * `PRIVILEGE\_LDAP\_WRITE` - Modify LDAP settings,\n * `PRIVILEGE\_LICENSE\_READ` - Get the cluster's license status.,\n * `PRIVILEGE\_LOCAL\_GROUP\_READ` - View local groups and members,\n * `PRIVILEGE\_LOCAL\_GROUP\_WRITE` - Modify local groups and membership,\n * `PRIVILEGE\_LOCAL\_USER\_READ` - Get information about local users,\n * `PRIVILEGE\_LOCAL\_USER\_WRITE` - Create and modify all local users,\n * `PRIVILEGE\_METRICS\_CONFIG\_READ` - View metrics configuration,\n * `PRIVILEGE\_METRICS\_CONFIG\_WRITE` - Modify metrics configuration,\n * `PRIVILEGE\_METRICS\_READ` - Get all metrics,\n * `PRIVILEGE\_NETWORK\_IP\_ALLOCATION\_READ` - View network IP address allocations,\n * `PRIVILEGE\_NETWORK\_READ` - Read network status and settings,\n * `PRIVILEGE\_NETWORK\_WRITE` - Modify network configuration,\n * `PRIVILEGE\_NFS\_EXPORT\_READ` - View configuration of NFS exports,\n * `PRIVILEGE\_NFS\_EXPORT\_WRITE` - Create, modify, and delete NFS exports,\n * `PRIVILEGE\_NFS\_SETTINGS\_READ` - Internal-Only: View NFS server settings,\n * `PRIVILEGE\_NFS\_SETTINGS\_WRITE` - Internal-Only: Modify NFS server settings,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_READ` - Read object storage config, including store URIs and credential

s.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_WRITE` - Write object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_READ` - View the object storage URIs.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_WRITE` - Add new object storage URIs.,\n * `PRIVILEGE\_PORTAL\_GLOBAL\_READ` - View global portal settings and status,\n * `PRIVILEGE\_PORTAL\_HUB\_READ` - View hub portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_HUB\_WRITE` - Authorize, modify, and delete hub portal relationships. Granting this privilege allows authorizing proposed relationships. Depending on existing file and directory permissions, this privilege can allow remote access to local data under the hub root directory.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_EVICT` - Remove cached files and directories from a spoke portal. Qumulo Core recaches the removed files or directories upon access.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_READ` - View spoke portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_SPOKE\_WRITE` - Create, modify, and delete spoke portal relationships. Granting this privilege allows creating spoke portal root directories. Depending on existing file permissions, this privilege can allow local access to remote files and directories.,\n * `PRIVILEGE\_POWER\_CYCLE` - Shutdown and reboot nodes,\n * `PRIVILEGE\_QUOTA\_READ` - View all file system quotas,\n * `PRIVILEGE\_QUOTA\_WRITE` - Create, modify, and delete file system quotas,\n * `PRIVILEGE\_REBOOT\_READ` - View Reboot Status,\n * `PRIVILEGE\_REBOOT\_USE` - Perform Reboots,\n * `PRIVILEGE\_RECONCILER\_READ` - View reconciler status and metrics,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_READ` - View object store relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_WRITE` - Create, modify, and delete object store relationships. Granting this privilege allows overwriting existing data, replicating, and potentially accessing any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_REPLICATION\_REVERSE\_RELATIONSHIP` - Reverse a source and target relationship,\n * `PRIVILEGE\_REPLICATION\_SOURCE\_READ` - View source relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_SOURCE\_WRITE` - Create, modify, and delete source relationships. Granting this privilege allows replicating and potentially accessing any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_REPLICATION\_TARGET\_READ` - View target relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_TARGET\_WRITE` - Create, modify, and delete target relationships. Granting this privilege allows overwriting any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_ROLE\_READ` - View roles and assignments,\n * `PRIVILEGE\_ROLE\_WRITE` - Create and modify roles and assignments,\n * `PRIVILEGE\_S3\_BUCKETS\_READ` - View all S3 buckets and bucket policies present in the system,\n * `PRIVILEGE\_S3\_BUCKETS\_WRITE` - Create or delete any S3 bucket in the system, and create, delete, or modify policies for any S3 bucket in the system. Subject to having sufficient FS permissions.,\n * `PRIVILEGE\_S3\_CREDENTIALS\_READ` - View any S3 access key present in the system,\n * `PRIVILEGE\_S3\_CREDENTIALS\_WRITE` - Create or delete S3 access keys for any user in the system,\n * `PRIVILEGE\_S3\_SETTINGS\_READ` - View S3 server settings,\n * `PRIVILEGE\_S3\_SETTINGS\_WRITE` - Modify S3 server settings,\n * `PRIVILEGE\_S3\_UPLOADS\_READ` - View all S3 uploads present in the system. This will override a bucket policy that denies the user this permission.,\n * `PRIVILEGE\_S3\_UPLOADS\_WRITE` - Abort S3 uploads in the system. This will override a bucket policy that denies the user this permission.,\n * `PRIVILEGE\_SAML\_SETTINGS\_READ` - View SAML integration settings,\n * `PRIVILEGE\_SAML\_SETTINGS\_WRITE` - Modify SAML integration settings,\n

```

* `PRIVILEGE_SERVICE_PUBLIC_KEYS_READ` - Internal-Only: Read public keys,\n * `PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE` - Internal-Only: Write public keys,\n * `PRIVILEGE_SMB_FILE_HANDLE_READ` - List open SMB file handles,\n * `PRIVILEGE_SMB_FILE_HANDLE_WRITE` - Force close an open SMB file handle,\n * `PRIVILEGE_SMB_SESSION_READ` - List logged on SMB sessions,\n * `PRIVILEGE_SMB_SESSION_WRITE` - Force close a logged on SMB session,\n * `PRIVILEGE_SMB_SHARE_READ` - View configuration of SMB shares and SMB server settings,\n * `PRIVILEGE_SMB_SHARE_WRITE` - Create, modify, and delete SMB shares and SMB server settings,\n * `PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ` - Recalculate capacity usage of snapshots,\n * `PRIVILEGE_SNAPSHOT_DIFFERENCE_READ` - View the changes between snapshots,\n * `PRIVILEGE_SNAPSHOT_LOCK` - Lock or unlock snapshots. Configure snapshot policies to lock or unlock snapshots.,\n * `PRIVILEGE_SNAPSHOT_POLICY_READ` - View snapshot policies and status,\n * `PRIVILEGE_SNAPSHOT_POLICY_WRITE` - Create, modify, and delete snapshot policies,\n * `PRIVILEGE_SNAPSHOT_READ` - List snapshots and view their status and cached capacity. Does not affect the visibility of the virtual `.snapshot` directories,\n * `PRIVILEGE_SNAPSHOT_WRITE` - Create, modify, and delete snapshots,\n * `PRIVILEGE_SUPPORT_READ` - View support configuration and status,\n * `PRIVILEGE_SUPPORT_WRITE` - Modify cloud-based monitoring and remote management,\n * `PRIVILEGE_TENANT_READ` - View any tenant information,\n * `PRIVILEGE_TENANT_WRITE` - Create, edit or delete tenants,\n * `PRIVILEGE_TEST_ONLY` - Test only actions,\n * `PRIVILEGE_TIME_READ` - View time and time settings,\n * `PRIVILEGE_TIME_WRITE` - Modify time settings,\n * `PRIVILEGE_UNCONFIGURED_NODE_READ` - List unconfigured Qumulo nodes,\n * `PRIVILEGE_UPGRADE_READ` - View upgrade configuration and status,\n * `PRIVILEGE_UPGRADE_WRITE` - Perform upgrades,\n * `PRIVILEGE_WEB_UI_SETTINGS_WRITE` - Modify web UI settings"
    }
  }
}

```

PUT

Modify a role.

Parameters

Name	Description	Required
<code>role_name</code>	The name of the role (This page URL-encodes the name for you)	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "role_model",
  "type": "object",
  "properties": {
    "description": {
      "description": "Description of the role",
      "type": "string"
    },
    "privileges": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "PRIVILEGE_AD_READ",
          "PRIVILEGE_AD_USE",
          "PRIVILEGE_AD_WRITE",
          "PRIVILEGE_ANALYTICS_READ",
          "PRIVILEGE_AUDIT_READ",
          "PRIVILEGE_AUDIT_WRITE",
          "PRIVILEGE_AUTH_CACHE_READ",
          "PRIVILEGE_AUTH_CACHE_WRITE",
          "PRIVILEGE_CLUSTER_READ",
          "PRIVILEGE_CLUSTER_WRITE",
          "PRIVILEGE_DEBUG",
          "PRIVILEGE_DNS_READ",
          "PRIVILEGE_DNS_USE",
          "PRIVILEGE_DNS_WRITE",
          "PRIVILEGE_FILE_FULL_ACCESS",
          "PRIVILEGE_FS_ATTRIBUTES_READ",
          "PRIVILEGE_FS_DELETE_TREE_READ",
          "PRIVILEGE_FS_DELETE_TREE_WRITE",
          "PRIVILEGE_FS_LOCK_READ",
          "PRIVILEGE_FS_LOCK_WRITE",
          "PRIVILEGE_FS_SETTINGS_READ",
          "PRIVILEGE_FS_SETTINGS_WRITE",
          "PRIVILEGE_FTP_READ",
          "PRIVILEGE_FTP_WRITE",
          "PRIVILEGE_IDENTITY_MAPPING_READ",
          "PRIVILEGE_IDENTITY_MAPPING_WRITE",
          "PRIVILEGE_IDENTITY_READ",
          "PRIVILEGE_IDENTITY_WRITE",
          "PRIVILEGE_KERBEROS_KEYTAB_READ",
          "PRIVILEGE_KERBEROS_KEYTAB_WRITE",

```

```
"PRIVILEGE_KERBEROS_SETTINGS_READ",
"PRIVILEGE_KERBEROS_SETTINGS_WRITE",
"PRIVILEGE_KV_READ",
"PRIVILEGE_LDAP_READ",
"PRIVILEGE_LDAP_USE",
"PRIVILEGE_LDAP_WRITE",
"PRIVILEGE_LOCAL_GROUP_READ",
"PRIVILEGE_LOCAL_GROUP_WRITE",
"PRIVILEGE_LOCAL_USER_READ",
"PRIVILEGE_LOCAL_USER_WRITE",
"PRIVILEGE_METRICS_READ",
"PRIVILEGE_NETWORK_IP_ALLOCATION_READ",
"PRIVILEGE_NETWORK_READ",
"PRIVILEGE_NETWORK_WRITE",
"PRIVILEGE_NFS_EXPORT_READ",
"PRIVILEGE_NFS_EXPORT_WRITE",
"PRIVILEGE_POWER_CYCLE",
"PRIVILEGE_QUOTA_READ",
"PRIVILEGE_QUOTA_WRITE",
"PRIVILEGE_RECONCILER_READ",
"PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP",
"PRIVILEGE_REPLICATION_SOURCE_READ",
"PRIVILEGE_REPLICATION_SOURCE_WRITE",
"PRIVILEGE_REPLICATION_TARGET_READ",
"PRIVILEGE_REPLICATION_TARGET_WRITE",
"PRIVILEGE_ROLE_READ",
"PRIVILEGE_ROLE_WRITE",
"PRIVILEGE_SMB_SHARE_READ",
"PRIVILEGE_SMB_SHARE_WRITE",
"PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ",
"PRIVILEGE_SNAPSHOT_DIFFERENCE_READ",
"PRIVILEGE_SNAPSHOT_POLICY_READ",
"PRIVILEGE_SNAPSHOT_POLICY_WRITE",
"PRIVILEGE_SNAPSHOT_READ",
"PRIVILEGE_SNAPSHOT_WRITE",
"PRIVILEGE_SUPPORT_READ",
"PRIVILEGE_SUPPORT_WRITE",
"PRIVILEGE_TEST_ONLY",
"PRIVILEGE_TIME_READ",
"PRIVILEGE_TIME_WRITE",
"PRIVILEGE_UNCONFIGURED_NODE_READ",
"PRIVILEGE_UPGRADE_READ",
"PRIVILEGE_UPGRADE_WRITE",
"PRIVILEGE_SMB_FILE_HANDLE_READ",
"PRIVILEGE_SMB_FILE_HANDLE_WRITE",
"PRIVILEGE_SMB_SESSION_READ",
```


"PRIVILEGE_SMB_SESSION_WRITE",
"PRIVILEGE_REPLICATION_OBJECT_READ",
"PRIVILEGE_REPLICATION_OBJECT_WRITE",
"PRIVILEGE_ENCRYPTION_WRITE",
"PRIVILEGE_ENCRYPTION_READ",
"PRIVILEGE_NFS_SETTINGS_READ",
"PRIVILEGE_NFS_SETTINGS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_READ",
"PRIVILEGE_METRICS_CONFIG_READ",
"PRIVILEGE_METRICS_CONFIG_WRITE",
"PRIVILEGE_REBOOT_USE",
"PRIVILEGE_REBOOT_READ",
"PRIVILEGE_CHECKSUMMING_READ",
"PRIVILEGE_S3_SETTINGS_READ",
"PRIVILEGE_S3_SETTINGS_WRITE",
"PRIVILEGE_WEB_UI_SETTINGS_WRITE",
"PRIVILEGE_S3_CREDENTIALS_READ",
"PRIVILEGE_S3_CREDENTIALS_WRITE",
"PRIVILEGE_TENANT_READ",
"PRIVILEGE_TENANT_WRITE",
"PRIVILEGE_SAML_SETTINGS_READ",
"PRIVILEGE_SAML_SETTINGS_WRITE",
"PRIVILEGE_S3_BUCKETS_READ",
"PRIVILEGE_S3_BUCKETS_WRITE",
"PRIVILEGE_ACCESS_TOKENS_READ",
"PRIVILEGE_ACCESS_TOKENS_WRITE",
"PRIVILEGE_S3_UPLOADS_READ",
"PRIVILEGE_S3_UPLOADS_WRITE",
"PRIVILEGE_SNAPSHOT_LOCK",
"PRIVILEGE_FS_KEY_MANAGEMENT_WRITE",
"PRIVILEGE_FS_KEY_MANAGEMENT_READ",
"PRIVILEGE_IDENTITY_CONFIG_WRITE",
"PRIVILEGE_IDENTITY_CONFIG_READ",
"PRIVILEGE_FILE_READ_ACCESS",
"PRIVILEGE_PORTAL_SPOKE_READ",
"PRIVILEGE_PORTAL_SPOKE_WRITE",
"PRIVILEGE_PORTAL_SPOKE_EVICT",
"PRIVILEGE_PORTAL_HUB_READ",
"PRIVILEGE_PORTAL_HUB_WRITE",
"PRIVILEGE_PORTAL_GLOBAL_READ",
"PRIVILEGE_FS_FILE_LOCK_WRITE",
"PRIVILEGE_LICENSE_READ",
"PRIVILEGE_CAPACITY_READ",
"PRIVILEGE_CAPACITY_WRITE",
"PRIVILEGE_OBJECT_STORAGE_URIS_READ",

```

"PRIVILEGE_OBJECT_STORAGE_URI_WRITE",
"PRIVILEGE_DISK_ERROR_WRITE",
"PRIVILEGE_DISK_ERROR_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE"
],
"description": "Privileges the role has been granted:\n * `PRIVILEGE_ACCESS_TOKENS_READ` - View any access tokens present in the system,\n * `PRIVILEGE_ACCESS_TOKENS_WRITE` - Create or delete access tokens for any user in the system,\n * `PRIVILEGE_AD_READ` - Read Qumulo Active Directory settings,\n * `PRIVILEGE_AD_USE` - Use Qumulo's APIs for performing queries against Active Directory,\n * `PRIVILEGE_AD_WRITE` - Modify Qumulo Active Directory settings,\n * `PRIVILEGE_ANALYTICS_READ` - Read cluster analytics,\n * `PRIVILEGE_AUDIT_READ` - Read audit settings,\n * `PRIVILEGE_AUDIT_WRITE` - Modify audit settings,\n * `PRIVILEGE_AUTH_CACHE_READ` - Internal-Only: Read authentication cache settings,\n * `PRIVILEGE_AUTH_CACHE_WRITE` - Internal-Only: Modify authentication cache settings,\n * `PRIVILEGE_CAPACITY_READ` - View the capacity clamp value.,\n * `PRIVILEGE_CAPACITY_WRITE` - Set the capacity clamp value.,\n * `PRIVILEGE_CHECKSUMMING_READ` - View the status of checksumming,\n * `PRIVILEGE_CLUSTER_READ` - View nodes, disks, protection status, and SSL certificate,\n * `PRIVILEGE_CLUSTER_WRITE` - Modify cluster settings and disk/identify LEDs,\n * `PRIVILEGE_DEBUG` - Internal-Only: Perform debug operations on the cluster,\n * `PRIVILEGE_DISK_ERROR_READ` - Internal-Only: Read disk error threshold and status.,\n * `PRIVILEGE_DISK_ERROR_WRITE` - Internal-Only: Modify disk error threshold and revive rejected disks.,\n * `PRIVILEGE_DNS_READ` - Read DNS settings,\n * `PRIVILEGE_DNS_USE` - Perform DNS lookups,\n * `PRIVILEGE_DNS_WRITE` - Modify DNS settings,\n * `PRIVILEGE_ENCRYPTION_READ` - View the status of at-rest-encryption,\n * `PRIVILEGE_ENCRYPTION_WRITE` - Rotate encryption keys for clusters with at-rest-encryption,\n * `PRIVILEGE_FILE_FULL_ACCESS` - Provides full access to all files regardless of permissions,\n * `PRIVILEGE_FILE_READ_ACCESS` - Provides read access to all files regardless of permissions,\n * `PRIVILEGE_FS_ATTRIBUTES_READ` - Read file system statistics,\n * `PRIVILEGE_FS_DELETE_TREE_READ` - View the status of directory tree delete operations,\n * `PRIVILEGE_FS_DELETE_TREE_WRITE` - Use directory tree delete API. Granting this privilege allows the deletion of any file or directory on the cluster. File and directory permissions are not taken into account. Not required for `rm -r`.,\n * `PRIVILEGE_FS_FILE_LOCK_WRITE` - Set or extend file lock retention periods and legal holds.,\n * `PRIVILEGE_FS_KEY_MANAGEMENT_READ` - Read and list public keys for various FS security features.,\n * `PRIVILEGE_FS_KEY_MANAGEMENT_WRITE` - Create and manage public keys for various FS security features.,\n * `PRIVILEGE_FS_LOCK_READ` - View NLM and SMB locks and waiters,\n * `PRIVILEGE_FS_LOCK_WRITE` - Release NLM and SMB locks,\n * `PRIVILEGE_FS_SETTINGS_READ` - View file system permissions settings,\n * `PRIVILEGE_FS_SETTINGS_WRITE` - Modify file system permissions mode,\n * `PRIVILEGE_FTP_READ` - View FTP status and settings,\n * `PRIVILEGE_FTP_WRITE` - Modify FTP status and settings,\n * `PRIVILEGE_IDENTITY_CONFIG_READ` - Read and list identity configurations.,\n * `PRIVILEGE_IDENTITY_CONFIG_WRITE` - Modify identity configurations.,\n * `PRIVILEGE_IDENTITY_MAPPING_READ` - Get AD/LDAP User Defined Mappings,\n * `PRIVILEGE_IDENTITY_MAPPING_WRITE` - Set AD/LDAP User Defined Mappings

```

ngs,\n * `PRIVILEGE\_IDENTITY\_READ` - Use Qumulo's identity lookup and translation APIs,\n * `PRIVILEGE\_IDENTITY\_WRITE` - Modify identity attributes and clear authentication cache,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_READ` - View Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_WRITE` - Modify Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_READ` - Read Kerberos settings,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_WRITE` - Modify Kerberos settings,\n * `PRIVILEGE\_KV\_READ` - DEPRECATED: Read and delete KV store entries for all users,\n * `PRIVILEGE\_LDAP\_READ` - View LDAP settings,\n * `PRIVILEGE\_LDAP\_USE` - Use Qumulo's APIs for performing LDAP queries,\n * `PRIVILEGE\_LDAP\_WRITE` - Modify LDAP settings,\n * `PRIVILEGE\_LICENSE\_READ` - Get the cluster's license status.,\n * `PRIVILEGE\_LOCAL\_GROUP\_READ` - View local groups and members,\n * `PRIVILEGE\_LOCAL\_GROUP\_WRITE` - Modify local groups and membership,\n * `PRIVILEGE\_LOCAL\_USER\_READ` - Get information about local users,\n * `PRIVILEGE\_LOCAL\_USER\_WRITE` - Create and modify all local users,\n * `PRIVILEGE\_METRICS\_CONFIG\_READ` - View metrics configuration,\n * `PRIVILEGE\_METRICS\_CONFIG\_WRITE` - Modify metrics configuration,\n * `PRIVILEGE\_METRICS\_READ` - Get all metrics,\n * `PRIVILEGE\_NETWORK\_IP\_ALLOCATION\_READ` - View network IP address allocations,\n * `PRIVILEGE\_NETWORK\_READ` - Read network status and settings,\n * `PRIVILEGE\_NETWORK\_WRITE` - Modify network configuration,\n * `PRIVILEGE\_NFS\_EXPORT\_READ` - View configuration of NFS exports,\n * `PRIVILEGE\_NFS\_EXPORT\_WRITE` - Create, modify, and delete NFS exports,\n * `PRIVILEGE\_NFS\_SETTINGS\_READ` - Internal-Only: View NFS server settings,\n * `PRIVILEGE\_NFS\_SETTINGS\_WRITE` - Internal-Only: Modify NFS server settings,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_READ` - Read object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_WRITE` - Write object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_READ` - View the object storage URIs.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_WRITE` - Add new object storage URIs.,\n * `PRIVILEGE\_PORTAL\_GLOBAL\_READ` - View global portal settings and status,\n * `PRIVILEGE\_PORTAL\_HUB\_READ` - View hub portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_HUB\_WRITE` - Authorize, modify, and delete hub portal relationships. Granting this privilege allows authorizing proposed relationships. Depending on existing file and directory permissions, this privilege can allow remote access to local data under the hub root directory.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_EVICT` - Remove cached files and directories from a spoke portal. Qumulo Core caches the removed files or directories upon access.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_READ` - View spoke portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_SPOKE\_WRITE` - Create, modify, and delete spoke portal relationships. Granting this privilege allows creating spoke portal root directories. Depending on existing file permissions, this privilege can allow local access to remote files and directories.,\n * `PRIVILEGE\_POWER\_CYCLE` - Shutdown and reboot nodes,\n * `PRIVILEGE\_QUOTA\_READ` - View all file system quotas,\n * `PRIVILEGE\_QUOTA\_WRITE` - Create, modify, and delete file system quotas,\n * `PRIVILEGE\_REBOOT\_READ` - View Reboot Status,\n * `PRIVILEGE\_REBOOT\_USE` - Perform Reboots,\n * `PRIVILEGE\_RECONCILER\_READ` - View reconciler status and metrics,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_READ` - View object store relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_WRITE` - Create, modify, and delete object store relationships. Granting this privilege allows overwriting existing data, replicating, and potentially accessing any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE_REPLICATION_REVER

SE_RELATIONSHIP` - Reverse a source and target relationship,\n \* `PRIVILEGE_REPLICATION_SOURCE_READ` - View source relationship settings and status,\n \* `PRIVILEGE_REPLICATION_SOURCE_WRITE` - Create, modify, and delete source relationships. Granting this privilege allows replicating and potentially accessing any data on the cluster regardless of file and directory permissions.,\n \* `PRIVILEGE_REPLICATION_TARGET_READ` - View target relationship settings and status,\n \* `PRIVILEGE_REPLICATION_TARGET_WRITE` - Create, modify, and delete target relationships. Granting this privilege allows overwriting any data on the cluster regardless of file and directory permissions.,\n \* `PRIVILEGE_ROLE_READ` - View roles and assignments,\n \* `PRIVILEGE_ROLE_WRITE` - Create and modify roles and assignments,\n \* `PRIVILEGE_S3_BUCKETS_READ` - View all S3 buckets and bucket policies present in the system,\n \* `PRIVILEGE_S3_BUCKETS_WRITE` - Create or delete any S3 bucket in the system, and create, delete, or modify policies for any S3 bucket in the system. Subject to having sufficient FS permissions.,\n \* `PRIVILEGE_S3_CREDENTIALS_READ` - View any S3 access key present in the system,\n \* `PRIVILEGE_S3_CREDENTIALS_WRITE` - Create or delete S3 access keys for any user in the system,\n \* `PRIVILEGE_S3_SETTINGS_READ` - View S3 server settings,\n \* `PRIVILEGE_S3_SETTINGS_WRITE` - Modify S3 server settings,\n \* `PRIVILEGE_S3_UPLOADS_READ` - View all S3 uploads present in the system. This will override a bucket policy that denies the user this permission.,\n \* `PRIVILEGE_S3_UPLOADS_WRITE` - Abort S3 uploads in the system. This will override a bucket policy that denies the user this permission.,\n \* `PRIVILEGE_SAML_SETTINGS_READ` - View SAML integration settings,\n \* `PRIVILEGE_SAML_SETTINGS_WRITE` - Modify SAML integration settings,\n \* `PRIVILEGE_SERVICE_PUBLIC_KEYS_READ` - Internal-Only: Read public keys,\n \* `PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE` - Internal-Only: Write public keys,\n \* `PRIVILEGE_SMB_FILE_HANDLE_READ` - List open SMB file handles,\n \* `PRIVILEGE_SMB_FILE_HANDLE_WRITE` - Force close an open SMB file handle,\n \* `PRIVILEGE_SMB_SESSION_READ` - List logged on SMB sessions,\n \* `PRIVILEGE_SMB_SESSION_WRITE` - Force close a logged on SMB session,\n \* `PRIVILEGE_SMB_SHARE_READ` - View configuration of SMB shares and SMB server settings,\n \* `PRIVILEGE_SMB_SHARE_WRITE` - Create, modify, and delete SMB shares and SMB server settings,\n \* `PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ` - Recalculate capacity usage of snapshots,\n \* `PRIVILEGE_SNAPSHOT_DIFFERENCE_READ` - View the changes between snapshots,\n \* `PRIVILEGE_SNAPSHOT_LOCK` - Lock or unlock snapshots. Configure snapshot policies to lock or unlock snapshots.,\n \* `PRIVILEGE_SNAPSHOT_POLICY_READ` - View snapshot policies and status,\n \* `PRIVILEGE_SNAPSHOT_POLICY_WRITE` - Create, modify, and delete snapshot policies,\n \* `PRIVILEGE_SNAPSHOT_READ` - List snapshots and view their status and cached capacity. Does not affect the visibility of the virtual `.snapshot` directories,\n \* `PRIVILEGE_SNAPSHOT_WRITE` - Create, modify, and delete snapshots,\n \* `PRIVILEGE_SUPPORT_READ` - View support configuration and status,\n \* `PRIVILEGE_SUPPORT_WRITE` - Modify cloud-based monitoring and remote management,\n \* `PRIVILEGE_TENANT_READ` - View any tenant information,\n \* `PRIVILEGE_TENANT_WRITE` - Create, edit or delete tenants,\n \* `PRIVILEGE_TEST_ONLY` - Test only actions,\n \* `PRIVILEGE_TIME_READ` - View time and time settings,\n \* `PRIVILEGE_TIME_WRITE` - Modify time settings,\n \* `PRIVILEGE_UNCONFIGURE_D_NODE_READ` - List unconfigured Qumulo nodes,\n \* `PRIVILEGE_UPGRADE_READ` - View upgrade configuration and status,\n \* `PRIVILEGE_UPGRADE_WRITE` - Perform upgrades,\n \* `PRIVILEGE_WEB_UI_SETTINGS_WRITE` - Modify web UI settings"

"PRIVILEGE_FS_DELETE_TREE_WRITE",
"PRIVILEGE_FS_LOCK_READ",
"PRIVILEGE_FS_LOCK_WRITE",
"PRIVILEGE_FS_SETTINGS_READ",
"PRIVILEGE_FS_SETTINGS_WRITE",
"PRIVILEGE_FTP_READ",
"PRIVILEGE_FTP_WRITE",
"PRIVILEGE_IDENTITY_MAPPING_READ",
"PRIVILEGE_IDENTITY_MAPPING_WRITE",
"PRIVILEGE_IDENTITY_READ",
"PRIVILEGE_IDENTITY_WRITE",
"PRIVILEGE_KERBEROS_KEYTAB_READ",
"PRIVILEGE_KERBEROS_KEYTAB_WRITE",
"PRIVILEGE_KERBEROS_SETTINGS_READ",
"PRIVILEGE_KERBEROS_SETTINGS_WRITE",
"PRIVILEGE_KV_READ",
"PRIVILEGE_LDAP_READ",
"PRIVILEGE_LDAP_USE",
"PRIVILEGE_LDAP_WRITE",
"PRIVILEGE_LOCAL_GROUP_READ",
"PRIVILEGE_LOCAL_GROUP_WRITE",
"PRIVILEGE_LOCAL_USER_READ",
"PRIVILEGE_LOCAL_USER_WRITE",
"PRIVILEGE_METRICS_READ",
"PRIVILEGE_NETWORK_IP_ALLOCATION_READ",
"PRIVILEGE_NETWORK_READ",
"PRIVILEGE_NETWORK_WRITE",
"PRIVILEGE_NFS_EXPORT_READ",
"PRIVILEGE_NFS_EXPORT_WRITE",
"PRIVILEGE_POWER_CYCLE",
"PRIVILEGE_QUOTA_READ",
"PRIVILEGE_QUOTA_WRITE",
"PRIVILEGE_RECONCILER_READ",
"PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP",
"PRIVILEGE_REPLICATION_SOURCE_READ",
"PRIVILEGE_REPLICATION_SOURCE_WRITE",
"PRIVILEGE_REPLICATION_TARGET_READ",
"PRIVILEGE_REPLICATION_TARGET_WRITE",
"PRIVILEGE_ROLE_READ",
"PRIVILEGE_ROLE_WRITE",
"PRIVILEGE_SMB_SHARE_READ",
"PRIVILEGE_SMB_SHARE_WRITE",
"PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ",
"PRIVILEGE_SNAPSHOT_DIFFERENCE_READ",
"PRIVILEGE_SNAPSHOT_POLICY_READ",
"PRIVILEGE_SNAPSHOT_POLICY_WRITE",

```
"PRIVILEGE_SNAPSHOT_READ",  
"PRIVILEGE_SNAPSHOT_WRITE",  
"PRIVILEGE_SUPPORT_READ",  
"PRIVILEGE_SUPPORT_WRITE",  
"PRIVILEGE_TEST_ONLY",  
"PRIVILEGE_TIME_READ",  
"PRIVILEGE_TIME_WRITE",  
"PRIVILEGE_UNCONFIGURED_NODE_READ",  
"PRIVILEGE_UPGRADE_READ",  
"PRIVILEGE_UPGRADE_WRITE",  
"PRIVILEGE_SMB_FILE_HANDLE_READ",  
"PRIVILEGE_SMB_FILE_HANDLE_WRITE",  
"PRIVILEGE_SMB_SESSION_READ",  
"PRIVILEGE_SMB_SESSION_WRITE",  
"PRIVILEGE_REPLICATION_OBJECT_READ",  
"PRIVILEGE_REPLICATION_OBJECT_WRITE",  
"PRIVILEGE_ENCRYPTION_WRITE",  
"PRIVILEGE_ENCRYPTION_READ",  
"PRIVILEGE_NFS_SETTINGS_READ",  
"PRIVILEGE_NFS_SETTINGS_WRITE",  
"PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE",  
"PRIVILEGE_SERVICE_PUBLIC_KEYS_READ",  
"PRIVILEGE_METRICS_CONFIG_READ",  
"PRIVILEGE_METRICS_CONFIG_WRITE",  
"PRIVILEGE_REBOOT_USE",  
"PRIVILEGE_REBOOT_READ",  
"PRIVILEGE_CHECKSUMMING_READ",  
"PRIVILEGE_S3_SETTINGS_READ",  
"PRIVILEGE_S3_SETTINGS_WRITE",  
"PRIVILEGE_WEB_UI_SETTINGS_WRITE",  
"PRIVILEGE_S3_CREDENTIALS_READ",  
"PRIVILEGE_S3_CREDENTIALS_WRITE",  
"PRIVILEGE_TENANT_READ",  
"PRIVILEGE_TENANT_WRITE",  
"PRIVILEGE_SAML_SETTINGS_READ",  
"PRIVILEGE_SAML_SETTINGS_WRITE",  
"PRIVILEGE_S3_BUCKETS_READ",  
"PRIVILEGE_S3_BUCKETS_WRITE",  
"PRIVILEGE_ACCESS_TOKENS_READ",  
"PRIVILEGE_ACCESS_TOKENS_WRITE",  
"PRIVILEGE_S3_UPLOADS_READ",  
"PRIVILEGE_S3_UPLOADS_WRITE",  
"PRIVILEGE_SNAPSHOT_LOCK",  
"PRIVILEGE_FS_KEY_MANAGEMENT_WRITE",  
"PRIVILEGE_FS_KEY_MANAGEMENT_READ",  
"PRIVILEGE_IDENTITY_CONFIG_WRITE",
```



```

"PRIVILEGE_IDENTITY_CONFIG_READ",
"PRIVILEGE_FILE_READ_ACCESS",
"PRIVILEGE_PORTAL_SPOKE_READ",
"PRIVILEGE_PORTAL_SPOKE_WRITE",
"PRIVILEGE_PORTAL_SPOKE_EVICT",
"PRIVILEGE_PORTAL_HUB_READ",
"PRIVILEGE_PORTAL_HUB_WRITE",
"PRIVILEGE_PORTAL_GLOBAL_READ",
"PRIVILEGE_FS_FILE_LOCK_WRITE",
"PRIVILEGE_LICENSE_READ",
"PRIVILEGE_CAPACITY_READ",
"PRIVILEGE_CAPACITY_WRITE",
"PRIVILEGE_OBJECT_STORAGE_URI_READ",
"PRIVILEGE_OBJECT_STORAGE_URI_WRITE",
"PRIVILEGE_DISK_ERROR_WRITE",
"PRIVILEGE_DISK_ERROR_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE"
],
"description": "Privileges the role has been granted:\n * `PRIVILEGE_ACCESS_TOKENS_READ` - View any access tokens present in the system,\n * `PRIVILEGE_ACCESS_TOKENS_WRITE` - Create or delete access tokens for any user in the system,\n * `PRIVILEGE_AD_READ` - Read Qumulo Active Directory settings,\n * `PRIVILEGE_AD_USE` - Use Qumulo's APIs for performing queries against Active Directory,\n * `PRIVILEGE_AD_WRITE` - Modify Qumulo Active Directory settings,\n * `PRIVILEGE_ANALYTICS_READ` - Read cluster analytics,\n * `PRIVILEGE_AUDIT_READ` - Read audit settings,\n * `PRIVILEGE_AUDIT_WRITE` - Modify audit settings,\n * `PRIVILEGE_AUTH_CACHE_READ` - Internal-Only: Read authentication cache settings,\n * `PRIVILEGE_AUTH_CACHE_WRITE` - Internal-Only: Modify authentication cache settings,\n * `PRIVILEGE_CAPACITY_READ` - View the capacity clamp value.,\n * `PRIVILEGE_CAPACITY_WRITE` - Set the capacity clamp value.,\n * `PRIVILEGE_CHECKSUMMING_READ` - View the status of checksumming,\n * `PRIVILEGE_CLUSTER_READ` - View nodes, disks, protection status, and SSL certificate,\n * `PRIVILEGE_CLUSTER_WRITE` - Modify cluster settings and disk/identify LEDs,\n * `PRIVILEGE_DEBUG` - Internal-Only: Perform debug operations on the cluster,\n * `PRIVILEGE_DISK_ERROR_READ` - Internal-Only: Read disk error threshold and status.,\n * `PRIVILEGE_DISK_ERROR_WRITE` - Internal-Only: Modify disk error threshold and revive rejected disks.,\n * `PRIVILEGE_DNS_READ` - Read DNS settings,\n * `PRIVILEGE_DNS_USE` - Perform DNS lookups,\n * `PRIVILEGE_DNS_WRITE` - Modify DNS settings,\n * `PRIVILEGE_ENCRYPTION_READ` - View the status of at-rest-encryption,\n * `PRIVILEGE_ENCRYPTION_WRITE` - Rotate encryption keys for clusters with at-rest-encryption,\n * `PRIVILEGE_FILE_FULL_ACCESS` - Provides full access to all files regardless of permissions,\n * `PRIVILEGE_FILE_READ_ACCESS` - Provides read access to all files regardless of permissions,\n * `PRIVILEGE_FS_ATTRIBUTES_READ` - Read file system statistics,\n * `PRIVILEGE_FS_DELETE_TREE_READ` - View the status of directory tree delete operations,\n * `PRIVILEGE_FS_DELETE_TREE_WRITE` - Use directory tree delete API. Granting this privilege allows the deletion of any file or directory on the clu

```


ster. File and directory permissions are not taken into account. Not required for `rm -r`.,\n * `PRIVILEGE\_FS\_FILE\_LOCK\_WRITE` - Set or extend file lock retention periods and legal holds.,\n * `PRIVILEGE\_FS\_KEY\_MANAGEMENT\_READ` - Read and list public keys for various FS security features.,\n * `PRIVILEGE\_FS\_KEY\_MANAGEMENT\_WRITE` - Create and manage public keys for various FS security features.,\n * `PRIVILEGE\_FS\_LOCK\_READ` - View NLN and SMB locks and waiters,\n * `PRIVILEGE\_FS\_LOCK\_WRITE` - Release NLN and SMB locks,\n * `PRIVILEGE\_FS\_SETTINGS\_READ` - View file system permissions settings,\n * `PRIVILEGE\_FS\_SETTINGS\_WRITE` - Modify file system permissions mode,\n * `PRIVILEGE\_FTP\_READ` - View FTP status and settings,\n * `PRIVILEGE\_FTP\_WRITE` - Modify FTP status and settings,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_READ` - Read and list identity configurations.,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_WRITE` - Modify identity configurations.,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_READ` - Get AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_WRITE` - Set AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_READ` - Use Qumulo's identity lookup and translation APIs,\n * `PRIVILEGE\_IDENTITY\_WRITE` - Modify identity attributes and clear authentication cache,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_READ` - View Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_WRITE` - Modify Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_READ` - Read Kerberos settings,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_WRITE` - Modify Kerberos settings,\n * `PRIVILEGE\_KV\_READ` - DEPRECATED: Read and delete KV store entries for all users,\n * `PRIVILEGE\_LDAP\_READ` - View LDAP settings,\n * `PRIVILEGE\_LDAP\_USE` - Use Qumulo's APIs for performing LDAP queries,\n * `PRIVILEGE\_LDAP\_WRITE` - Modify LDAP settings,\n * `PRIVILEGE\_LICENSE\_READ` - Get the cluster's license status.,\n * `PRIVILEGE\_LOCAL\_GROUP\_READ` - View local groups and members,\n * `PRIVILEGE\_LOCAL\_GROUP\_WRITE` - Modify local groups and membership,\n * `PRIVILEGE\_LOCAL\_USER\_READ` - Get information about local users,\n * `PRIVILEGE\_LOCAL\_USER\_WRITE` - Create and modify all local users,\n * `PRIVILEGE\_METRICS\_CONFIG\_READ` - View metrics configuration,\n * `PRIVILEGE\_METRICS\_CONFIG\_WRITE` - Modify metrics configuration,\n * `PRIVILEGE\_METRICS\_READ` - Get all metrics,\n * `PRIVILEGE\_NETWORK\_IP\_ALLOCATION\_READ` - View network IP address allocations,\n * `PRIVILEGE\_NETWORK\_READ` - Read network status and settings,\n * `PRIVILEGE\_NETWORK\_WRITE` - Modify network configuration,\n * `PRIVILEGE\_NFS\_EXPORT\_READ` - View configuration of NFS exports,\n * `PRIVILEGE\_NFS\_EXPORT\_WRITE` - Create, modify, and delete NFS exports,\n * `PRIVILEGE\_NFS\_SETTINGS\_READ` - Internal-Only: View NFS server settings,\n * `PRIVILEGE\_NFS\_SETTINGS\_WRITE` - Internal-Only: Modify NFS server settings,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_READ` - Read object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_WRITE` - Write object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_READ` - View the object storage URIs.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_WRITE` - Add new object storage URIs.,\n * `PRIVILEGE\_PORTAL\_GLOBAL\_READ` - View global portal settings and status,\n * `PRIVILEGE\_PORTAL\_HUB\_READ` - View hub portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_HUB\_WRITE` - Authorize, modify, and delete hub portal relationships. Granting this privilege allows authorizing proposed relationships. Depending on existing file and directory permissions, this privilege can allow remote access to local data under the hub root directory.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_EVICT` - Remove cached files and directories from a spoke portal. Qumulo Core caches the removed files or directories upon access.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_READ`

D` - View spoke portal relationship status and configuration,\n \* `PRIVILEGE_PORTAL_SPOKE_WRITE` - Create, modify, and delete spoke portal relationships. Granting this privilege allows creating spoke portal root directories. Depending on existing file permissions, this privilege can allow local access to remote files and directories.,\n \* `PRIVILEGE_POWER_CYCLE` - Shutdown and reboot nodes,\n \* `PRIVILEGE_QUOTA_READ` - View all file system quotas,\n \* `PRIVILEGE_QUOTA_WRITE` - Create, modify, and delete file system quotas,\n \* `PRIVILEGE_REBOOT_READ` - View Reboot Status,\n \* `PRIVILEGE_REBOOT_USE` - Perform Reboots,\n \* `PRIVILEGE_RECONCILER_READ` - View reconciler status and metrics,\n \* `PRIVILEGE_REPLICATION_OBJECT_READ` - View object store relationship settings and status,\n \* `PRIVILEGE_REPLICATION_OBJECT_WRITE` - Create, modify, and delete object store relationships. Granting this privilege allows overwriting existing data, replicating, and potentially accessing any data on the cluster regardless of file and directory permissions.,\n \* `PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP` - Reverse a source and target relationship,\n \* `PRIVILEGE_REPLICATION_SOURCE_READ` - View source relationship settings and status,\n \* `PRIVILEGE_REPLICATION_SOURCE_WRITE` - Create, modify, and delete source relationships. Granting this privilege allows replicating and potentially accessing any data on the cluster regardless of file and directory permissions.,\n \* `PRIVILEGE_REPLICATION_TARGET_READ` - View target relationship settings and status,\n \* `PRIVILEGE_REPLICATION_TARGET_WRITE` - Create, modify, and delete target relationships. Granting this privilege allows overwriting any data on the cluster regardless of file and directory permissions.,\n \* `PRIVILEGE_ROLE_READ` - View roles and assignments,\n \* `PRIVILEGE_ROLE_WRITE` - Create and modify roles and assignments,\n \* `PRIVILEGE_S3_BUCKETS_READ` - View all S3 buckets and bucket policies present in the system,\n \* `PRIVILEGE_S3_BUCKETS_WRITE` - Create or delete any S3 bucket in the system, and create, delete, or modify policies for any S3 bucket in the system. Subject to having sufficient FS permissions.,\n \* `PRIVILEGE_S3_CREDENTIALS_READ` - View any S3 access key present in the system,\n \* `PRIVILEGE_S3_CREDENTIALS_WRITE` - Create or delete S3 access keys for any user in the system,\n \* `PRIVILEGE_S3_SETTINGS_READ` - View S3 server settings,\n \* `PRIVILEGE_S3_SETTINGS_WRITE` - Modify S3 server settings,\n \* `PRIVILEGE_S3_UPLOADS_READ` - View all S3 uploads present in the system. This will override a bucket policy that denies the user this permission.,\n \* `PRIVILEGE_S3_UPLOADS_WRITE` - Abort S3 uploads in the system. This will override a bucket policy that denies the user this permission.,\n \* `PRIVILEGE_SAML_SETTINGS_READ` - View SAML integration settings,\n \* `PRIVILEGE_SAML_SETTINGS_WRITE` - Modify SAML integration settings,\n \* `PRIVILEGE_SERVICE_PUBLIC_KEYS_READ` - Internal-Only: Read public keys,\n \* `PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE` - Internal-Only: Write public keys,\n \* `PRIVILEGE_SMB_FILE_HANDLE_READ` - List open SMB file handles,\n \* `PRIVILEGE_SMB_FILE_HANDLE_WRITE` - Force close an open SMB file handle,\n \* `PRIVILEGE_SMB_SESSION_READ` - List logged on SMB sessions,\n \* `PRIVILEGE_SMB_SESSION_WRITE` - Force close a logged on SMB session,\n \* `PRIVILEGE_SMB_SHARE_READ` - View configuration of SMB shares and SMB server settings,\n \* `PRIVILEGE_SMB_SHARE_WRITE` - Create, modify, and delete SMB shares and SMB server settings,\n \* `PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ` - Recalculate capacity usage of snapshots,\n \* `PRIVILEGE_SNAPSHOT_DIFFERENCE_READ` - View the changes between snapshots,\n \* `PRIVILEGE_SNAPSHOT_LOCK` - Lock or unlock snapshots. Configure snapshot policies to lock or unlock snapshots.,\n \* `PRIVI

```

LEGE_SNAPSHOT_POLICY_READ` - View snapshot policies and status,\n * `PRIVILEGE_SNAPS
HOT_POLICY_WRITE` - Create, modify, and delete snapshot policies,\n * `PRIVILEGE_SNA
PSHOT_READ` - List snapshots and view their status and cached capacity. Does not aff
ect the visibility of the virtual `.snapshot` directories,\n * `PRIVILEGE_SNAPSHOT_W
RITE` - Create, modify, and delete snapshots,\n * `PRIVILEGE_SUPPORT_READ` - View su
pport configuration and status,\n * `PRIVILEGE_SUPPORT_WRITE` - Modify cloud-based m
onitoring and remote management,\n * `PRIVILEGE_TENANT_READ` - View any tenant infor
mation,\n * `PRIVILEGE_TENANT_WRITE` - Create, edit or delete tenants,\n * `PRIVILEG
E_TEST_ONLY` - Test only actions,\n * `PRIVILEGE_TIME_READ` - View time and time set
tings,\n * `PRIVILEGE_TIME_WRITE` - Modify time settings,\n * `PRIVILEGE_UNCONFIGURE
D_NODE_READ` - List unconfigured Qumulo nodes,\n * `PRIVILEGE_UPGRADE_READ` - View u
pgrade configuration and status,\n * `PRIVILEGE_UPGRADE_WRITE` - Perform upgrade
s,\n * `PRIVILEGE_WEB_UI_SETTINGS_WRITE` - Modify web UI settings"
    }
  }
}
}

```

DELETE

Delete a role.

Parameters

Name	Description	Required
<code>role_name</code>	The name of the role (This page URL-encodes the name for you)	Yes
<code>If-Match</code>	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

Modify fields on a role.

Parameters

Name	Description	Required
------	-------------	----------

role_name	The name of the role (This page URL-encodes the name for you)	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "role_model_delta",
  "type": "object",
  "properties": {
    "description": {
      "description": "Description of the role",
      "type": "string"
    },
    "privileges": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "PRIVILEGE_AD_READ",
          "PRIVILEGE_AD_USE",
          "PRIVILEGE_AD_WRITE",
          "PRIVILEGE_ANALYTICS_READ",
          "PRIVILEGE_AUDIT_READ",
          "PRIVILEGE_AUDIT_WRITE",
          "PRIVILEGE_AUTH_CACHE_READ",
          "PRIVILEGE_AUTH_CACHE_WRITE",
          "PRIVILEGE_CLUSTER_READ",
          "PRIVILEGE_CLUSTER_WRITE",
          "PRIVILEGE_DEBUG",
          "PRIVILEGE_DNS_READ",
          "PRIVILEGE_DNS_USE",
          "PRIVILEGE_DNS_WRITE",
          "PRIVILEGE_FILE_FULL_ACCESS",
          "PRIVILEGE_FS_ATTRIBUTES_READ",
          "PRIVILEGE_FS_DELETE_TREE_READ",
          "PRIVILEGE_FS_DELETE_TREE_WRITE",
          "PRIVILEGE_FS_LOCK_READ",
          "PRIVILEGE_FS_LOCK_WRITE",
          "PRIVILEGE_FS_SETTINGS_READ",
          "PRIVILEGE_FS_SETTINGS_WRITE",
          "PRIVILEGE_FTP_READ",
          "PRIVILEGE_FTP_WRITE",
          "PRIVILEGE_IDENTITY_MAPPING_READ",

```

```
"PRIVILEGE_IDENTITY_MAPPING_WRITE",
"PRIVILEGE_IDENTITY_READ",
"PRIVILEGE_IDENTITY_WRITE",
"PRIVILEGE_KERBEROS_KEYTAB_READ",
"PRIVILEGE_KERBEROS_KEYTAB_WRITE",
"PRIVILEGE_KERBEROS_SETTINGS_READ",
"PRIVILEGE_KERBEROS_SETTINGS_WRITE",
"PRIVILEGE_KV_READ",
"PRIVILEGE_LDAP_READ",
"PRIVILEGE_LDAP_USE",
"PRIVILEGE_LDAP_WRITE",
"PRIVILEGE_LOCAL_GROUP_READ",
"PRIVILEGE_LOCAL_GROUP_WRITE",
"PRIVILEGE_LOCAL_USER_READ",
"PRIVILEGE_LOCAL_USER_WRITE",
"PRIVILEGE_METRICS_READ",
"PRIVILEGE_NETWORK_IP_ALLOCATION_READ",
"PRIVILEGE_NETWORK_READ",
"PRIVILEGE_NETWORK_WRITE",
"PRIVILEGE_NFS_EXPORT_READ",
"PRIVILEGE_NFS_EXPORT_WRITE",
"PRIVILEGE_POWER_CYCLE",
"PRIVILEGE_QUOTA_READ",
"PRIVILEGE_QUOTA_WRITE",
"PRIVILEGE_RECONCILER_READ",
"PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP",
"PRIVILEGE_REPLICATION_SOURCE_READ",
"PRIVILEGE_REPLICATION_SOURCE_WRITE",
"PRIVILEGE_REPLICATION_TARGET_READ",
"PRIVILEGE_REPLICATION_TARGET_WRITE",
"PRIVILEGE_ROLE_READ",
"PRIVILEGE_ROLE_WRITE",
"PRIVILEGE_SMB_SHARE_READ",
"PRIVILEGE_SMB_SHARE_WRITE",
"PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ",
"PRIVILEGE_SNAPSHOT_DIFFERENCE_READ",
"PRIVILEGE_SNAPSHOT_POLICY_READ",
"PRIVILEGE_SNAPSHOT_POLICY_WRITE",
"PRIVILEGE_SNAPSHOT_READ",
"PRIVILEGE_SNAPSHOT_WRITE",
"PRIVILEGE_SUPPORT_READ",
"PRIVILEGE_SUPPORT_WRITE",
"PRIVILEGE_TEST_ONLY",
"PRIVILEGE_TIME_READ",
"PRIVILEGE_TIME_WRITE",
"PRIVILEGE_UNCONFIGURED_NODE_READ",
```

"PRIVILEGE_UPGRADE_READ",
"PRIVILEGE_UPGRADE_WRITE",
"PRIVILEGE_SMB_FILE_HANDLE_READ",
"PRIVILEGE_SMB_FILE_HANDLE_WRITE",
"PRIVILEGE_SMB_SESSION_READ",
"PRIVILEGE_SMB_SESSION_WRITE",
"PRIVILEGE_REPLICATION_OBJECT_READ",
"PRIVILEGE_REPLICATION_OBJECT_WRITE",
"PRIVILEGE_ENCRYPTION_WRITE",
"PRIVILEGE_ENCRYPTION_READ",
"PRIVILEGE_NFS_SETTINGS_READ",
"PRIVILEGE_NFS_SETTINGS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_READ",
"PRIVILEGE_METRICS_CONFIG_READ",
"PRIVILEGE_METRICS_CONFIG_WRITE",
"PRIVILEGE_REBOOT_USE",
"PRIVILEGE_REBOOT_READ",
"PRIVILEGE_CHECKSUMMING_READ",
"PRIVILEGE_S3_SETTINGS_READ",
"PRIVILEGE_S3_SETTINGS_WRITE",
"PRIVILEGE_WEB_UI_SETTINGS_WRITE",
"PRIVILEGE_S3_CREDENTIALS_READ",
"PRIVILEGE_S3_CREDENTIALS_WRITE",
"PRIVILEGE_TENANT_READ",
"PRIVILEGE_TENANT_WRITE",
"PRIVILEGE_SAML_SETTINGS_READ",
"PRIVILEGE_SAML_SETTINGS_WRITE",
"PRIVILEGE_S3_BUCKETS_READ",
"PRIVILEGE_S3_BUCKETS_WRITE",
"PRIVILEGE_ACCESS_TOKENS_READ",
"PRIVILEGE_ACCESS_TOKENS_WRITE",
"PRIVILEGE_S3_UPLOADS_READ",
"PRIVILEGE_S3_UPLOADS_WRITE",
"PRIVILEGE_SNAPSHOT_LOCK",
"PRIVILEGE_FS_KEY_MANAGEMENT_WRITE",
"PRIVILEGE_FS_KEY_MANAGEMENT_READ",
"PRIVILEGE_IDENTITY_CONFIG_WRITE",
"PRIVILEGE_IDENTITY_CONFIG_READ",
"PRIVILEGE_FILE_READ_ACCESS",
"PRIVILEGE_PORTAL_SPOKE_READ",
"PRIVILEGE_PORTAL_SPOKE_WRITE",
"PRIVILEGE_PORTAL_SPOKE_EVICT",
"PRIVILEGE_PORTAL_HUB_READ",
"PRIVILEGE_PORTAL_HUB_WRITE",
"PRIVILEGE_PORTAL_GLOBAL_READ",

```

"PRIVILEGE_FS_FILE_LOCK_WRITE",
"PRIVILEGE_LICENSE_READ",
"PRIVILEGE_CAPACITY_READ",
"PRIVILEGE_CAPACITY_WRITE",
"PRIVILEGE_OBJECT_STORAGE_URIS_READ",
"PRIVILEGE_OBJECT_STORAGE_URIS_WRITE",
"PRIVILEGE_DISK_ERROR_WRITE",
"PRIVILEGE_DISK_ERROR_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE"
],
"description": "Privileges the role has been granted:\n * `PRIVILEGE_ACCESS_TOKENS_READ` - View any access tokens present in the system,\n * `PRIVILEGE_ACCESS_TOKENS_WRITE` - Create or delete access tokens for any user in the system,\n * `PRIVILEGE_AD_READ` - Read Qumulo Active Directory settings,\n * `PRIVILEGE_AD_USE` - Use Qumulo's APIs for performing queries against Active Directory,\n * `PRIVILEGE_AD_WRITE` - Modify Qumulo Active Directory settings,\n * `PRIVILEGE_ANALYTICS_READ` - Read cluster analytics,\n * `PRIVILEGE_AUDIT_READ` - Read audit settings,\n * `PRIVILEGE_AUDIT_WRITE` - Modify audit settings,\n * `PRIVILEGE_AUTH_CACHE_READ` - Internal-Only: Read authentication cache settings,\n * `PRIVILEGE_AUTH_CACHE_WRITE` - Internal-Only: Modify authentication cache settings,\n * `PRIVILEGE_CAPACITY_READ` - View the capacity clamp value.,\n * `PRIVILEGE_CAPACITY_WRITE` - Set the capacity clamp value.,\n * `PRIVILEGE_CHECKSUMMING_READ` - View the status of checksumming,\n * `PRIVILEGE_CLUSTER_READ` - View nodes, disks, protection status, and SSL certificate,\n * `PRIVILEGE_CLUSTER_WRITE` - Modify cluster settings and disk/identify LEDs,\n * `PRIVILEGE_DEBUG` - Internal-Only: Perform debug operations on the cluster,\n * `PRIVILEGE_DISK_ERROR_READ` - Internal-Only: Read disk error threshold and status.,\n * `PRIVILEGE_DISK_ERROR_WRITE` - Internal-Only: Modify disk error threshold and revive rejected disks.,\n * `PRIVILEGE_DNS_READ` - Read DNS settings,\n * `PRIVILEGE_DNS_USE` - Perform DNS lookups,\n * `PRIVILEGE_DNS_WRITE` - Modify DNS settings,\n * `PRIVILEGE_ENCRYPTION_READ` - View the status of at-rest-encryption,\n * `PRIVILEGE_ENCRYPTION_WRITE` - Rotate encryption keys for clusters with at-rest-encryption,\n * `PRIVILEGE_FILE_FULL_ACCESS` - Provides full access to all files regardless of permissions,\n * `PRIVILEGE_FILE_READ_ACCESS` - Provides read access to all files regardless of permissions,\n * `PRIVILEGE_FS_ATTRIBUTES_READ` - Read file system statistics,\n * `PRIVILEGE_FS_DELETE_TREE_READ` - View the status of directory tree delete operations,\n * `PRIVILEGE_FS_DELETE_TREE_WRITE` - Use directory tree delete API. Granting this privilege allows the deletion of any file or directory on the cluster. File and directory permissions are not taken into account. Not required for `rm -r`.,\n * `PRIVILEGE_FS_FILE_LOCK_WRITE` - Set or extend file lock retention periods and legal holds.,\n * `PRIVILEGE_FS_KEY_MANAGEMENT_READ` - Read and list public keys for various FS security features.,\n * `PRIVILEGE_FS_KEY_MANAGEMENT_WRITE` - Create and manage public keys for various FS security features.,\n * `PRIVILEGE_FS_LOCK_READ` - View NLN and SMB locks and waiters,\n * `PRIVILEGE_FS_LOCK_WRITE` - Release NLN and SMB locks,\n * `PRIVILEGE_FS_SETTINGS_READ` - View file system permissions settings,\n * `PRIVILEGE_FS_SETTINGS_WRITE` - Modify file system permissions mod

```


e,\n * `PRIVILEGE\_FTP\_READ` - View FTP status and settings,\n * `PRIVILEGE\_FTP\_WRITE` - Modify FTP status and settings,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_READ` - Read and list identity configurations.,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_WRITE` - Modify identity configurations.,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_READ` - Get AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_WRITE` - Set AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_READ` - Use Qumulo's identity lookup and translation APIs,\n * `PRIVILEGE\_IDENTITY\_WRITE` - Modify identity attributes and clear authentication cache,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_READ` - View Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_WRITE` - Modify Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_SETTING\_READ` - Read Kerberos settings,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_WRITE` - Modify Kerberos settings,\n * `PRIVILEGE\_KV\_READ` - DEPRECATED: Read and delete KV store entries for all users,\n * `PRIVILEGE\_LDAP\_READ` - View LDAP settings,\n * `PRIVILEGE\_LDAP\_USE` - Use Qumulo's APIs for performing LDAP queries,\n * `PRIVILEGE\_LDAP\_WRITE` - Modify LDAP settings,\n * `PRIVILEGE\_LICENSE\_READ` - Get the cluster's license status.,\n * `PRIVILEGE\_LOCAL\_GROUP\_READ` - View local groups and members,\n * `PRIVILEGE\_LOCAL\_GROUP\_WRITE` - Modify local groups and membership,\n * `PRIVILEGE\_LOCAL\_USER\_READ` - Get information about local users,\n * `PRIVILEGE\_LOCAL\_USER\_WRITE` - Create and modify all local users,\n * `PRIVILEGE\_METRICS\_CONFIG\_READ` - View metrics configuration,\n * `PRIVILEGE\_METRICS\_CONFIG\_WRITE` - Modify metrics configuration,\n * `PRIVILEGE\_METRICS\_READ` - Get all metrics,\n * `PRIVILEGE\_NETWORK\_IP\_ALLOCATION\_READ` - View network IP address allocations,\n * `PRIVILEGE\_NETWORK\_READ` - Read network status and settings,\n * `PRIVILEGE\_NETWORK\_WRITE` - Modify network configuration,\n * `PRIVILEGE\_NFS\_EXPORT\_READ` - View configuration of NFS exports,\n * `PRIVILEGE\_NFS\_EXPORT\_WRITE` - Create, modify, and delete NFS exports,\n * `PRIVILEGE\_NFS\_SETTINGS\_READ` - Internal-Only: View NFS server settings,\n * `PRIVILEGE\_NFS\_SETTINGS\_WRITE` - Internal-Only: Modify NFS server settings,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_READ` - Read object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_WRITE` - Write object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_READ` - View the object storage URIs.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_WRITE` - Add new object storage URIs.,\n * `PRIVILEGE\_PORTAL\_GLOBAL\_READ` - View global portal settings and status,\n * `PRIVILEGE\_PORTAL\_HUB\_READ` - View hub portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_HUB\_WRITE` - Authorize, modify, and delete hub portal relationships. Granting this privilege allows authorizing proposed relationships. Depending on existing file and directory permissions, this privilege can allow remote access to local data under the hub root directory.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_EVICT` - Remove cached files and directories from a spoke portal. Qumulo Core recaches the removed files or directories upon access.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_READ` - View spoke portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_SPOKE\_WRITE` - Create, modify, and delete spoke portal relationships. Granting this privilege allows creating spoke portal root directories. Depending on existing file permissions, this privilege can allow local access to remote files and directories.,\n * `PRIVILEGE\_POWER\_CYCLE` - Shutdown and reboot nodes,\n * `PRIVILEGE\_QUOTA\_READ` - View all file system quotas,\n * `PRIVILEGE\_QUOTA\_WRITE` - Create, modify, and delete file system quotas,\n * `PRIVILEGE\_REBOOT\_READ` - View Reboot Status,\n * `PRIVILEGE\_REBOOT\_USE` - Perform Reboots,\n * `PRIVILEGE\_RECONCILER\_READ` - View rec

onciler status and metrics,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_READ` - View object store relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_WRITE` - Create, modify, and delete object store relationships. Granting this privilege allows overwriting existing data, replicating, and potentially accessing any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_REPLICATION\_REVERSE\_RELATIONSHIP` - Reverse a source and target relationship,\n * `PRIVILEGE\_REPLICATION\_SOURCE\_READ` - View source relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_SOURCE\_WRITE` - Create, modify, and delete source relationships. Granting this privilege allows replicating and potentially accessing any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_REPLICATION\_TARGET\_READ` - View target relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_TARGET\_WRITE` - Create, modify, and delete target relationships. Granting this privilege allows overwriting any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_ROLE\_READ` - View roles and assignments,\n * `PRIVILEGE\_ROLE\_WRITE` - Create and modify roles and assignments,\n * `PRIVILEGE\_S3\_BUCKETS\_READ` - View all S3 buckets and bucket policies present in the system,\n * `PRIVILEGE\_S3\_BUCKETS\_WRITE` - Create or delete any S3 bucket in the system, and create, delete, or modify policies for any S3 bucket in the system. Subject to having sufficient FS permissions.,\n * `PRIVILEGE\_S3\_CREDENTIALS\_READ` - View any S3 access key present in the system,\n * `PRIVILEGE\_S3\_CREDENTIALS\_WRITE` - Create or delete S3 access keys for any user in the system,\n * `PRIVILEGE\_S3\_SETTINGS\_READ` - View S3 server settings,\n * `PRIVILEGE\_S3\_SETTINGS\_WRITE` - Modify S3 server settings,\n * `PRIVILEGE\_S3\_UPLOADS\_READ` - View all S3 uploads present in the system. This will override a bucket policy that denies the user this permission.,\n * `PRIVILEGE\_S3\_UPLOADS\_WRITE` - Abort S3 uploads in the system. This will override a bucket policy that denies the user this permission.,\n * `PRIVILEGE\_SAML\_SETTINGS\_READ` - View SAML integration settings,\n * `PRIVILEGE\_SAML\_SETTINGS\_WRITE` - Modify SAML integration settings,\n * `PRIVILEGE\_SERVICE\_PUBLIC\_KEYS\_READ` - Internal-Only: Read public keys,\n * `PRIVILEGE\_SERVICE\_PUBLIC\_KEYS\_WRITE` - Internal-Only: Write public keys,\n * `PRIVILEGE\_SMB\_FILE\_HANDLE\_READ` - List open SMB file handles,\n * `PRIVILEGE\_SMB\_FILE\_HANDLE\_WRITE` - Force close an open SMB file handle,\n * `PRIVILEGE\_SMB\_SESSION\_READ` - List logged on SMB sessions,\n * `PRIVILEGE\_SMB\_SESSION\_WRITE` - Force close a logged on SMB session,\n * `PRIVILEGE\_SMB\_SHARE\_READ` - View configuration of SMB shares and SMB server settings,\n * `PRIVILEGE\_SMB\_SHARE\_WRITE` - Create, modify, and delete SMB shares and SMB server settings,\n * `PRIVILEGE\_SNAPSHOT\_CALCULATE\_USED\_CAPACITY\_READ` - Recalculate capacity usage of snapshots,\n * `PRIVILEGE\_SNAPSHOT\_DIFFERENCE\_READ` - View the changes between snapshots,\n * `PRIVILEGE\_SNAPSHOT\_LOCK` - Lock or unlock snapshots. Configure snapshot policies to lock or unlock snapshots.,\n * `PRIVILEGE\_SNAPSHOT\_POLICY\_READ` - View snapshot policies and status,\n * `PRIVILEGE\_SNAPSHOT\_POLICY\_WRITE` - Create, modify, and delete snapshot policies,\n * `PRIVILEGE\_SNAPSHOT\_READ` - List snapshots and view their status and cached capacity. Does not affect the visibility of the virtual `.snapshot` directories,\n * `PRIVILEGE\_SNAPSHOT\_WRITE` - Create, modify, and delete snapshots,\n * `PRIVILEGE\_SUPPORT\_READ` - View support configuration and status,\n * `PRIVILEGE\_SUPPORT\_WRITE` - Modify cloud-based monitoring and remote management,\n * `PRIVILEGE\_TENANT\_READ` - View any tenant information,\n * `PRIVILEGE\_TENANT\_WRITE` - Create, edit or delete tenants,\n * `PRIVILEGE

```

E_TEST_ONLY` - Test only actions,\n * `PRIVILEGE_TIME_READ` - View time and time set
tings,\n * `PRIVILEGE_TIME_WRITE` - Modify time settings,\n * `PRIVILEGE_UNCONFIGURE
D_NODE_READ` - List unconfigured Qumulo nodes,\n * `PRIVILEGE_UPGRADE_READ` - View u
pgrade configuration and status,\n * `PRIVILEGE_UPGRADE_WRITE` - Perform upgrade
s,\n * `PRIVILEGE_WEB_UI_SETTINGS_WRITE` - Modify web UI settings"
    }
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "role_model",
  "type": "object",
  "properties": {
    "description": {
      "description": "Description of the role",
      "type": "string"
    },
    "privileges": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "PRIVILEGE_AD_READ",
          "PRIVILEGE_AD_USE",
          "PRIVILEGE_AD_WRITE",
          "PRIVILEGE_ANALYTICS_READ",
          "PRIVILEGE_AUDIT_READ",
          "PRIVILEGE_AUDIT_WRITE",
          "PRIVILEGE_AUTH_CACHE_READ",
          "PRIVILEGE_AUTH_CACHE_WRITE",
          "PRIVILEGE_CLUSTER_READ",
          "PRIVILEGE_CLUSTER_WRITE",
          "PRIVILEGE_DEBUG",
          "PRIVILEGE_DNS_READ",

```

```
"PRIVILEGE_DNS_USE",  
"PRIVILEGE_DNS_WRITE",  
"PRIVILEGE_FILE_FULL_ACCESS",  
"PRIVILEGE_FS_ATTRIBUTES_READ",  
"PRIVILEGE_FS_DELETE_TREE_READ",  
"PRIVILEGE_FS_DELETE_TREE_WRITE",  
"PRIVILEGE_FS_LOCK_READ",  
"PRIVILEGE_FS_LOCK_WRITE",  
"PRIVILEGE_FS_SETTINGS_READ",  
"PRIVILEGE_FS_SETTINGS_WRITE",  
"PRIVILEGE_FTP_READ",  
"PRIVILEGE_FTP_WRITE",  
"PRIVILEGE_IDENTITY_MAPPING_READ",  
"PRIVILEGE_IDENTITY_MAPPING_WRITE",  
"PRIVILEGE_IDENTITY_READ",  
"PRIVILEGE_IDENTITY_WRITE",  
"PRIVILEGE_KERBEROS_KEYTAB_READ",  
"PRIVILEGE_KERBEROS_KEYTAB_WRITE",  
"PRIVILEGE_KERBEROS_SETTINGS_READ",  
"PRIVILEGE_KERBEROS_SETTINGS_WRITE",  
"PRIVILEGE_KV_READ",  
"PRIVILEGE_LDAP_READ",  
"PRIVILEGE_LDAP_USE",  
"PRIVILEGE_LDAP_WRITE",  
"PRIVILEGE_LOCAL_GROUP_READ",  
"PRIVILEGE_LOCAL_GROUP_WRITE",  
"PRIVILEGE_LOCAL_USER_READ",  
"PRIVILEGE_LOCAL_USER_WRITE",  
"PRIVILEGE_METRICS_READ",  
"PRIVILEGE_NETWORK_IP_ALLOCATION_READ",  
"PRIVILEGE_NETWORK_READ",  
"PRIVILEGE_NETWORK_WRITE",  
"PRIVILEGE_NFS_EXPORT_READ",  
"PRIVILEGE_NFS_EXPORT_WRITE",  
"PRIVILEGE_POWER_CYCLE",  
"PRIVILEGE_QUOTA_READ",  
"PRIVILEGE_QUOTA_WRITE",  
"PRIVILEGE_RECONCILER_READ",  
"PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP",  
"PRIVILEGE_REPLICATION_SOURCE_READ",  
"PRIVILEGE_REPLICATION_SOURCE_WRITE",  
"PRIVILEGE_REPLICATION_TARGET_READ",  
"PRIVILEGE_REPLICATION_TARGET_WRITE",  
"PRIVILEGE_ROLE_READ",  
"PRIVILEGE_ROLE_WRITE",  
"PRIVILEGE_SMB_SHARE_READ",
```

"PRIVILEGE_SMB_SHARE_WRITE",
"PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ",
"PRIVILEGE_SNAPSHOT_DIFFERENCE_READ",
"PRIVILEGE_SNAPSHOT_POLICY_READ",
"PRIVILEGE_SNAPSHOT_POLICY_WRITE",
"PRIVILEGE_SNAPSHOT_READ",
"PRIVILEGE_SNAPSHOT_WRITE",
"PRIVILEGE_SUPPORT_READ",
"PRIVILEGE_SUPPORT_WRITE",
"PRIVILEGE_TEST_ONLY",
"PRIVILEGE_TIME_READ",
"PRIVILEGE_TIME_WRITE",
"PRIVILEGE_UNCONFIGURED_NODE_READ",
"PRIVILEGE_UPGRADE_READ",
"PRIVILEGE_UPGRADE_WRITE",
"PRIVILEGE_SMB_FILE_HANDLE_READ",
"PRIVILEGE_SMB_FILE_HANDLE_WRITE",
"PRIVILEGE_SMB_SESSION_READ",
"PRIVILEGE_SMB_SESSION_WRITE",
"PRIVILEGE_REPLICATION_OBJECT_READ",
"PRIVILEGE_REPLICATION_OBJECT_WRITE",
"PRIVILEGE_ENCRYPTION_WRITE",
"PRIVILEGE_ENCRYPTION_READ",
"PRIVILEGE_NFS_SETTINGS_READ",
"PRIVILEGE_NFS_SETTINGS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_READ",
"PRIVILEGE_METRICS_CONFIG_READ",
"PRIVILEGE_METRICS_CONFIG_WRITE",
"PRIVILEGE_REBOOT_USE",
"PRIVILEGE_REBOOT_READ",
"PRIVILEGE_CHECKSUMMING_READ",
"PRIVILEGE_S3_SETTINGS_READ",
"PRIVILEGE_S3_SETTINGS_WRITE",
"PRIVILEGE_WEB_UI_SETTINGS_WRITE",
"PRIVILEGE_S3_CREDENTIALS_READ",
"PRIVILEGE_S3_CREDENTIALS_WRITE",
"PRIVILEGE_TENANT_READ",
"PRIVILEGE_TENANT_WRITE",
"PRIVILEGE_SAML_SETTINGS_READ",
"PRIVILEGE_SAML_SETTINGS_WRITE",
"PRIVILEGE_S3_BUCKETS_READ",
"PRIVILEGE_S3_BUCKETS_WRITE",
"PRIVILEGE_ACCESS_TOKENS_READ",
"PRIVILEGE_ACCESS_TOKENS_WRITE",
"PRIVILEGE_S3_UPLOADS_READ",

```

"PRIVILEGE_S3_UPLOADS_WRITE",
"PRIVILEGE_SNAPSHOT_LOCK",
"PRIVILEGE_FS_KEY_MANAGEMENT_WRITE",
"PRIVILEGE_FS_KEY_MANAGEMENT_READ",
"PRIVILEGE_IDENTITY_CONFIG_WRITE",
"PRIVILEGE_IDENTITY_CONFIG_READ",
"PRIVILEGE_FILE_READ_ACCESS",
"PRIVILEGE_PORTAL_SPOKE_READ",
"PRIVILEGE_PORTAL_SPOKE_WRITE",
"PRIVILEGE_PORTAL_SPOKE_EVICT",
"PRIVILEGE_PORTAL_HUB_READ",
"PRIVILEGE_PORTAL_HUB_WRITE",
"PRIVILEGE_PORTAL_GLOBAL_READ",
"PRIVILEGE_FS_FILE_LOCK_WRITE",
"PRIVILEGE_LICENSE_READ",
"PRIVILEGE_CAPACITY_READ",
"PRIVILEGE_CAPACITY_WRITE",
"PRIVILEGE_OBJECT_STORAGE_URIS_READ",
"PRIVILEGE_OBJECT_STORAGE_URIS_WRITE",
"PRIVILEGE_DISK_ERROR_WRITE",
"PRIVILEGE_DISK_ERROR_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_READ",
"PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE"
],
"description": "Privileges the role has been granted:\n * `PRIVILEGE_ACCESS_TOKENS_READ` - View any access tokens present in the system,\n * `PRIVILEGE_ACCESS_TOKENS_WRITE` - Create or delete access tokens for any user in the system,\n * `PRIVILEGE_AD_READ` - Read Qumulo Active Directory settings,\n * `PRIVILEGE_AD_USE` - Use Qumulo's APIs for performing queries against Active Directory,\n * `PRIVILEGE_AD_WRITE` - Modify Qumulo Active Directory settings,\n * `PRIVILEGE_ANALYTICS_READ` - Read cluster analytics,\n * `PRIVILEGE_AUDIT_READ` - Read audit settings,\n * `PRIVILEGE_AUDIT_WRITE` - Modify audit settings,\n * `PRIVILEGE_AUTH_CACHE_READ` - Internal-Only: Read authentication cache settings,\n * `PRIVILEGE_AUTH_CACHE_WRITE` - Internal-Only: Modify authentication cache settings,\n * `PRIVILEGE_CAPACITY_READ` - View the capacity clamp value.,\n * `PRIVILEGE_CAPACITY_WRITE` - Set the capacity clamp value.,\n * `PRIVILEGE_CHECKSUMMING_READ` - View the status of checksumming,\n * `PRIVILEGE_CLUSTER_READ` - View nodes, disks, protection status, and SSL certificate,\n * `PRIVILEGE_CLUSTER_WRITE` - Modify cluster settings and disk/identify LEDs,\n * `PRIVILEGE_DEBUG` - Internal-Only: Perform debug operations on the cluster,\n * `PRIVILEGE_DISK_ERROR_READ` - Internal-Only: Read disk error threshold and status.,\n * `PRIVILEGE_DISK_ERROR_WRITE` - Internal-Only: Modify disk error threshold and revive rejected disks.,\n * `PRIVILEGE_DNS_READ` - Read DNS settings,\n * `PRIVILEGE_DNS_USE` - Perform DNS lookups,\n * `PRIVILEGE_DNS_WRITE` - Modify DNS settings,\n * `PRIVILEGE_ENCRYPTION_READ` - View the status of at-rest-encryption,\n * `PRIVILEGE_ENCRYPTION_WRITE` - Rotate encryption keys for clusters with at-rest-encryption,\n * `PRIVILEGE_FILE_FULL_ACCESS` - Provides full access to all files regardless

```

s of permissions,\n * `PRIVILEGE\_FILE\_READ\_ACCESS` - Provides read access to all files regardless of permissions,\n * `PRIVILEGE\_FS\_ATTRIBUTES\_READ` - Read file system statistics,\n * `PRIVILEGE\_FS\_DELETE\_TREE\_READ` - View the status of directory tree delete operations,\n * `PRIVILEGE\_FS\_DELETE\_TREE\_WRITE` - Use directory tree delete API. Granting this privilege allows the deletion of any file or directory on the cluster. File and directory permissions are not taken into account. Not required for `rm -r`.,\n * `PRIVILEGE\_FS\_FILE\_LOCK\_WRITE` - Set or extend file lock retention periods and legal holds.,\n * `PRIVILEGE\_FS\_KEY\_MANAGEMENT\_READ` - Read and list public keys for various FS security features.,\n * `PRIVILEGE\_FS\_KEY\_MANAGEMENT\_WRITE` - Create and manage public keys for various FS security features.,\n * `PRIVILEGE\_FS\_LOCK\_READ` - View NLM and SMB locks and waiters,\n * `PRIVILEGE\_FS\_LOCK\_WRITE` - Release NLM and SMB locks,\n * `PRIVILEGE\_FS\_SETTINGS\_READ` - View file system permissions settings,\n * `PRIVILEGE\_FS\_SETTINGS\_WRITE` - Modify file system permissions mode,\n * `PRIVILEGE\_FTP\_READ` - View FTP status and settings,\n * `PRIVILEGE\_FTP\_WRITE` - Modify FTP status and settings,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_READ` - Read and list identity configurations.,\n * `PRIVILEGE\_IDENTITY\_CONFIG\_WRITE` - Modify identity configurations.,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_READ` - Get AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_MAPPING\_WRITE` - Set AD/LDAP User Defined Mappings,\n * `PRIVILEGE\_IDENTITY\_READ` - Use Qumulo's identity lookup and translation APIs,\n * `PRIVILEGE\_IDENTITY\_WRITE` - Modify identity attributes and clear authentication cache,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_READ` - View Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_KEYTAB\_WRITE` - Modify Kerberos keytab,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_READ` - Read Kerberos settings,\n * `PRIVILEGE\_KERBEROS\_SETTINGS\_WRITE` - Modify Kerberos settings,\n * `PRIVILEGE\_KV\_READ` - DEPRECATED: Read and delete KV store entries for all users,\n * `PRIVILEGE\_LDAP\_READ` - View LDAP settings,\n * `PRIVILEGE\_LDAP\_USE` - Use Qumulo's APIs for performing LDAP queries,\n * `PRIVILEGE\_LDAP\_WRITE` - Modify LDAP settings,\n * `PRIVILEGE\_LICENSE\_READ` - Get the cluster's license status.,\n * `PRIVILEGE\_LOCAL\_GROUP\_READ` - View local groups and members,\n * `PRIVILEGE\_LOCAL\_GROUP\_WRITE` - Modify local groups and membership,\n * `PRIVILEGE\_LOCAL\_USER\_READ` - Get information about local users,\n * `PRIVILEGE\_LOCAL\_USER\_WRITE` - Create and modify all local users,\n * `PRIVILEGE\_METRICS\_CONFIG\_READ` - View metrics configuration,\n * `PRIVILEGE\_METRICS\_CONFIG\_WRITE` - Modify metrics configuration,\n * `PRIVILEGE\_METRICS\_READ` - Get all metrics,\n * `PRIVILEGE\_NETWORK\_IP\_ALLOCATION\_READ` - View network IP address allocations,\n * `PRIVILEGE\_NETWORK\_READ` - Read network status and settings,\n * `PRIVILEGE\_NETWORK\_WRITE` - Modify network configuration,\n * `PRIVILEGE\_NFS\_EXPORT\_READ` - View configuration of NFS exports,\n * `PRIVILEGE\_NFS\_EXPORT\_WRITE` - Create, modify, and delete NFS exports,\n * `PRIVILEGE\_NFS\_SETTINGS\_READ` - Internal-Only: View NFS server settings,\n * `PRIVILEGE\_NFS\_SETTINGS\_WRITE` - Internal-Only: Modify NFS server settings,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_READ` - Read object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_CONFIG\_WRITE` - Write object storage config, including store URIs and credentials.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_READ` - View the object storage URIs.,\n * `PRIVILEGE\_OBJECT\_STORAGE\_URIS\_WRITE` - Add new object storage URIs.,\n * `PRIVILEGE\_PORTAL\_GLOBAL\_READ` - View global portal settings and status,\n * `PRIVILEGE\_PORTAL\_HUB\_READ` - View hub portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_HUB\_WRITE` - Authorize, modify, and delete hub por

tal relationships. Granting this privilege allows authorizing proposed relationships. Depending on existing file and directory permissions, this privilege can allow remote access to local data under the hub root directory.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_EVICT` - Remove cached files and directories from a spoke portal. Qumulo Core recaches the removed files or directories upon access.,\n * `PRIVILEGE\_PORTAL\_SPOKE\_READ` - View spoke portal relationship status and configuration,\n * `PRIVILEGE\_PORTAL\_SPOKE\_WRITE` - Create, modify, and delete spoke portal relationships. Granting this privilege allows creating spoke portal root directories. Depending on existing file permissions, this privilege can allow local access to remote files and directories.,\n * `PRIVILEGE\_POWER\_CYCLE` - Shutdown and reboot nodes,\n * `PRIVILEGE\_QUOTA\_READ` - View all file system quotas,\n * `PRIVILEGE\_QUOTA\_WRITE` - Create, modify, and delete file system quotas,\n * `PRIVILEGE\_REBOOT\_READ` - View Reboot Status,\n * `PRIVILEGE\_REBOOT\_USE` - Perform Reboots,\n * `PRIVILEGE\_RECONCILER\_READ` - View reconciler status and metrics,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_READ` - View object store relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_OBJECT\_WRITE` - Create, modify, and delete object store relationships. Granting this privilege allows overwriting existing data, replicating, and potentially accessing any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_REPLICATION\_REVERSE\_RELATIONSHIP` - Reverse a source and target relationship,\n * `PRIVILEGE\_REPLICATION\_SOURCE\_READ` - View source relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_SOURCE\_WRITE` - Create, modify, and delete source relationships. Granting this privilege allows replicating and potentially accessing any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_REPLICATION\_TARGET\_READ` - View target relationship settings and status,\n * `PRIVILEGE\_REPLICATION\_TARGET\_WRITE` - Create, modify, and delete target relationships. Granting this privilege allows overwriting any data on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE\_ROLE\_READ` - View roles and assignments,\n * `PRIVILEGE\_ROLE\_WRITE` - Create and modify roles and assignments,\n * `PRIVILEGE\_S3\_BUCKETS\_READ` - View all S3 buckets and bucket policies present in the system,\n * `PRIVILEGE\_S3\_BUCKETS\_WRITE` - Create or delete any S3 bucket in the system, and create, delete, or modify policies for any S3 bucket in the system. Subject to having sufficient FS permissions.,\n * `PRIVILEGE\_S3\_CREDENTIALS\_READ` - View any S3 access key present in the system,\n * `PRIVILEGE\_S3\_CREDENTIALS\_WRITE` - Create or delete S3 access keys for any user in the system,\n * `PRIVILEGE\_S3\_SETTINGS\_READ` - View S3 server settings,\n * `PRIVILEGE\_S3\_SETTINGS\_WRITE` - Modify S3 server settings,\n * `PRIVILEGE\_S3\_UPLOADS\_READ` - View all S3 uploads present in the system. This will override a bucket policy that denies the user this permission.,\n * `PRIVILEGE\_S3\_UPLOADS\_WRITE` - Abort S3 uploads in the system. This will override a bucket policy that denies the user this permission.,\n * `PRIVILEGE\_SAML\_SETTINGS\_READ` - View SAML integration settings,\n * `PRIVILEGE\_SAML\_SETTINGS\_WRITE` - Modify SAML integration settings,\n * `PRIVILEGE\_SERVICE\_PUBLIC\_KEYS\_READ` - Internal-Only: Read public keys,\n * `PRIVILEGE\_SERVICE\_PUBLIC\_KEYS\_WRITE` - Internal-Only: Write public keys,\n * `PRIVILEGE\_SMB\_FILE\_HANDLE\_READ` - List open SMB file handles,\n * `PRIVILEGE\_SMB\_FILE\_HANDLE\_WRITE` - Force close an open SMB file handle,\n * `PRIVILEGE\_SMB\_SESSION\_READ` - List logged on SMB sessions,\n * `PRIVILEGE\_SMB\_SESSION\_WRITE` - Force close a logged on SMB session,\n * `PRIVILEGE\_SMB\_SHARE\_READ` - View configuration of SMB shares and S


```

MB server settings,\n * `PRIVILEGE_SMB_SHARE_WRITE` - Create, modify, and delete SM
B shares and SMB server settings,\n * `PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_RE
AD` - Recalculate capacity usage of snapshots,\n * `PRIVILEGE_SNAPSHOT_DIFFERENCE_RE
AD` - View the changes between snapshots,\n * `PRIVILEGE_SNAPSHOT_LOCK` - Lock or un
lock snapshots. Configure snapshot policies to lock or unlock snapshots.,\n * `PRIVI
LEGE_SNAPSHOT_POLICY_READ` - View snapshot policies and status,\n * `PRIVILEGE_SNAPS
HOT_POLICY_WRITE` - Create, modify, and delete snapshot policies,\n * `PRIVILEGE_SNA
PSHOT_READ` - List snapshots and view their status and cached capacity. Does not aff
ect the visibility of the virtual `.snapshot` directories,\n * `PRIVILEGE_SNAPSHOT_W
RITE` - Create, modify, and delete snapshots,\n * `PRIVILEGE_SUPPORT_READ` - View su
pport configuration and status,\n * `PRIVILEGE_SUPPORT_WRITE` - Modify cloud-based m
onitoring and remote management,\n * `PRIVILEGE_TENANT_READ` - View any tenant infor
mation,\n * `PRIVILEGE_TENANT_WRITE` - Create, edit or delete tenants,\n * `PRIVILEG
E_TEST_ONLY` - Test only actions,\n * `PRIVILEGE_TIME_READ` - View time and time set
tings,\n * `PRIVILEGE_TIME_WRITE` - Modify time settings,\n * `PRIVILEGE_UNCONFIGURE
D_NODE_READ` - List unconfigured Qumulo nodes,\n * `PRIVILEGE_UPGRADE_READ` - View u
pgrade configuration and status,\n * `PRIVILEGE_UPGRADE_WRITE` - Perform upgrade
s,\n * `PRIVILEGE_WEB_UI_SETTINGS_WRITE` - Modify web UI settings"
    }
  }
}

```


auth/roles/{role_name}/members

Endpoint

/v1/auth/roles/{role_name}/members

GET

List all members of a role.

Parameters

Name	Description	Required
<code>role_name</code>	The name of the role (This page URL-encodes the name for you)	Yes
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "members_model",
  "type": "object",
  "properties": {
    "members": {
      "description": "Members of the role",
      "type": "object",
      "properties": {},
      "additionalProperties": {
        "description": "Members of the role value",
        "type": "object",
        "properties": {
```

```

"domain": {
  "type": "string",
  "enum": [
    "LOCAL",
    "API_NULL_DOMAIN",
    "WORLD",
    "POSIX_USER",
    "POSIX_GROUP",
    "ACTIVE_DIRECTORY",
    "API_INVALID_DOMAIN",
    "API_RESERVED_DOMAIN",
    "API_INTERNAL_DOMAIN",
    "API_OPERATOR_DOMAIN",
    "API_QUMULO_SUPPORT_DOMAIN",
    "API_CREATOR_DOMAIN"
  ],
  "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n *
`API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNA
L_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - AP
I_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPP
ORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DO
MAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSI
X_USER,\n * `WORLD` - WORLD"
},
"auth_id": {
  "description": "auth_id",
  "type": "string"
},
"uid": {
  "description": "uid",
  "type": "number"
},
"gid": {
  "description": "gid",
  "type": "number"
},
"sid": {
  "description": "sid",
  "type": "string"
},
"name": {
  "description": "name",
  "type": "string"
}
}
}

```

```

    }
  }
}

```

POST

Assign a member to a role

Parameters

Name	Description	Required
<code>role_name</code>	The name of the role (This page URL-encodes the name for you)	Yes

Request

Schema

```

{
  "description": "api_identity",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    }
  }
}

```

```

    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_identity",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",

```

```

        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
},
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
}

```

auth/ roles/{role_name}/members/{member_id}

Endpoint

/v1/auth/roles/{role_name}/members/{member_id}

GET

Get information about the member of the role.

Parameters

Name	Description	Required
role_name	The name of the role (This page URL-encodes the name for you)	Yes
member_id	The member's unique ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_identity",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
      ]
    }
  }
}
```

```

        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
}

```

DELETE

Remove a member from a role

Parameters

Name	Description	Required
<code>role_name</code>	The name of the role (This page URL-encodes the name for you)	Yes

<code>member_id</code>	The member's unique ID	Yes
------------------------	------------------------	-----

Response

Codes

Code	Description
200	Return value on success

s3/access-keys/

Endpoint

/v1/s3/access-keys/

GET

List all S3 access keys present in the system or for a specified user. Privilege S3_CREDENTIALS_READ is required to list keys other than for yourself.

Parameters

Name	Description	Required
<code>user</code>	Filters access keys by the given user identity if specified.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_key_description_list_model",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "entries",
        "type": "object",
        "properties": {
          "access_key_id": {
            "description": "The access key ID of the S3 credentials to use in signed requests.",

```

```

    "type": "string"
  },
  "owner": {
    "description": "The system identity that the requests with the current c
redentials use for file system operations.",
    "type": "object",
    "properties": {
      "domain": {
        "type": "string",
        "enum": [
          "LOCAL",
          "API_NULL_DOMAIN",
          "WORLD",
          "POSIX_USER",
          "POSIX_GROUP",
          "ACTIVE_DIRECTORY",
          "API_INVALID_DOMAIN",
          "API_RESERVED_DOMAIN",
          "API_INTERNAL_DOMAIN",
          "API_OPERATOR_DOMAIN",
          "API_QUMULO_SUPPORT_DOMAIN",
          "API_CREATOR_DOMAIN"
        ],
        "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
      },
      "auth_id": {
        "description": "auth_id",
        "type": "string"
      },
      "uid": {
        "description": "uid",
        "type": "number"
      },
      "gid": {
        "description": "gid",
        "type": "number"
      },
      "sid": {
        "description": "sid",
        "type": "string"
      }
    }
  }
}

```

```

    },
    "name": {
      "description": "name",
      "type": "string"
    }
  },
  "creation_time": {
    "description": "The creation time of the current credentials.",
    "type": "string"
  }
}
}
}
}
}
}
}
}
}
}

```

POST

Create a new S3 access key for the provided user identity. To add a new key, a user must have fewer than two keys. Privilege S3_CREDENTIALS_WRITE is required to create a key for a user other than yourself.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "api_key_creation_options",
  "type": "object",
  "properties": {
    "user": {
      "description": "user",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",

```

```

        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
},
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_created_key",
  "type": "object",
  "properties": {
    "access_key_id": {
      "description": "The access key ID of the S3 credentials to use in signed requests.",
      "type": "string"
    },
    "owner": {
      "description": "The system identity which the requests with the current credentials use for file system operations.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ],
          "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER"
        }
      }
    }
  }
}
```

```

ER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  },
  "secret_access_key": {
    "description": "The secret access key to use as the signing key in requests th
at use the current credentials.",
    "type": "string"
  },
  "creation_time": {
    "description": "The creation time of the current credentials.",
    "type": "string"
  }
}
}

```

s3/access-keys/{id}

Endpoint

/v1/s3/access-keys/{id}

DELETE

Delete the key identified by the given Access Key ID the current user. Access is revoked immediately. Privilege S3_CREDENTIALS_WRITE is required to delete a key for a user other than yourself.

Parameters

Name	Description	Required
id	Access Key ID	Yes

Response

Codes

Code	Description
200	Return value on success

s3/buckets/

Endpoint

/v1/s3/buckets/

GET

List all S3 buckets present in the system.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_bucket_description_list_model",
  "type": "object",
  "properties": {
    "buckets": {
      "type": "array",
      "items": {
        "description": "buckets",
        "type": "object",
        "properties": {
          "name": {
            "description": "The name of the S3 bucket.",
            "type": "string"
          },
          "creation_time": {
            "description": "The creation time of the S3 bucket.",
            "type": "string"
          },
          "path": {
            "description": "The bucket root directory of the S3 bucket.",
            "type": "string"
          }
        }
      }
    }
  }
}
```



```

    "anonymous_access_enabled": {
      "description": "Deprecated. To configure anonymous access for an S3 bucket, use the qq s3_set_bucket policy command with an Allow statement that targets the local:guest account.",
      "type": "boolean"
    },
    "versioning": {
      "description": "The versioning state of the current S3 bucket: Unversioned, Enabled, or Suspended.",
      "type": "string"
    },
    "lock_config": {
      "description": "The Object Lock configuration for the S3 bucket.",
      "type": "object",
      "properties": {
        "enabled": {
          "description": "Specifies whether Object Lock is enabled for the S3 bucket.",
          "type": "boolean"
        },
        "default_retention": {
          "description": "The default retention period for the S3 bucket.",
          "type": "object",
          "properties": {
            "units": {
              "description": "The units of the retention, either DAYS or YEARS",
              "type": "string"
            },
            "value": {
              "description": "The number of either DAYS or YEARS in the retention period",
              "type": "number"
            }
          }
        }
      }
    }
  }
}

```

POST

Create a new S3 bucket.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_bucket_options",
  "type": "object",
  "properties": {
    "name": {
      "description": "name",
      "type": "string"
    },
    "path": {
      "description": "The absolute path to the directory to use as bucket root directory. The caller must have permission to look up this directory.",
      "type": "string"
    },
    "create_fs_path": {
      "description": "Specifies whether to create the bucket root if it doesn't exist.",
      "type": "boolean"
    },
    "object_lock_enabled": {
      "description": "Specifies whether to enable object locking.",
      "type": "boolean"
    },
    "private": {
      "description": "Specifies whether to create a private S3 bucket. By default, Qumulo Core creates the bucket without a policy, allowing all S3 API users to perform S3 object read and write operations and the S3 bucket's creator and users with RBAC permissions to perform S3 bucket write operations. When enabled, Qumulo Core applies a policy that restricts both S3 object and S3 bucket operations to the S3 bucket's creator and users with RBAC permissions. ",
      "type": "boolean"
    }
  }
}
```

Response

Codes

Code	Description
------	-------------

200	Return value on success
-----	-------------------------

Schema

```
{
  "description": "api_bucket_description",
  "type": "object",
  "properties": {
    "name": {
      "description": "The name of the S3 bucket.",
      "type": "string"
    },
    "creation_time": {
      "description": "The creation time of the S3 bucket.",
      "type": "string"
    },
    "path": {
      "description": "The bucket root directory of the S3 bucket.",
      "type": "string"
    },
    "anonymous_access_enabled": {
      "description": "Deprecated. To configure anonymous access for an S3 bucket, use the qq s3_set_bucket policy command with an Allow statement that targets the local:guest account.",
      "type": "boolean"
    },
    "versioning": {
      "description": "The versioning state of the current S3 bucket: Unversioned, Enabled, or Suspended.",
      "type": "string"
    },
    "lock_config": {
      "description": "The Object Lock configuration for the S3 bucket.",
      "type": "object",
      "properties": {
        "enabled": {
          "description": "Specifies whether Object Lock is enabled for the S3 bucket.",
          "type": "boolean"
        }
      }
    },
    "default_retention": {
      "description": "The default retention period for the S3 bucket.",
      "type": "object",
      "properties": {
        "units": {
```


s3/buckets/{name}

Endpoint

/v1/s3/buckets/{name}

DELETE

Delete an existing S3 bucket.

Parameters

Name	Description	Required
name	Bucket name	Yes
delete-root-dir	If set to true, the root directory of the bucket will also be unlinked. Otherwise the root directory is not unlinked.	Yes

Response

Codes

Code	Description
200	Return value on success

PATCH

Modify the versioning status or lock configuration for the specified S3 bucket

Parameters

Name	Description	Required
name	Bucket name	Yes

Request

Schema

```
{
  "description": "api_bucket_patch",
  "type": "object",
  "properties": {
```

```

"anonymous_access_enabled": {
  "description": "[Deprecated] Use bucket policies to enable anonymous access",
  "type": "boolean"
},
"versioning": {
  "description": "The versioning state of the S3 bucket: Unversioned, Enabled, or Suspended. Note: These values are case sensitive.",
  "type": "string"
},
"lock_config": {
  "description": "The lock configuration of the S3 bucket.",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "Specifies whether Object Lock is enabled for the S3 bucket.",
      "type": "boolean"
    },
    "default_retention": {
      "description": "The default retention period for the S3 bucket.",
      "type": "object",
      "properties": {
        "units": {
          "description": "The units of the retention, either DAYS or YEARS",
          "type": "string"
        },
        "value": {
          "description": "The number of either DAYS or YEARS in the retention period",
          "type": "number"
        }
      }
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_bucket_description",
  "type": "object",
  "properties": {
    "name": {
      "description": "The name of the S3 bucket.",
      "type": "string"
    },
    "creation_time": {
      "description": "The creation time of the S3 bucket.",
      "type": "string"
    },
    "path": {
      "description": "The bucket root directory of the S3 bucket.",
      "type": "string"
    },
    "anonymous_access_enabled": {
      "description": "Deprecated. To configure anonymous access for an S3 bucket, use the qq s3_set_bucket policy command with an Allow statement that targets the local:guest account.",
      "type": "boolean"
    },
    "versioning": {
      "description": "The versioning state of the current S3 bucket: Unversioned, Enabled, or Suspended.",
      "type": "string"
    },
    "lock_config": {
      "description": "The Object Lock configuration for the S3 bucket.",
      "type": "object",
      "properties": {
        "enabled": {
          "description": "Specifies whether Object Lock is enabled for the S3 bucket.",
          "type": "boolean"
        }
      }
    },
    "default_retention": {
      "description": "The default retention period for the S3 bucket.",
      "type": "object",
      "properties": {
        "units": {
          "description": "The units of the retention, either DAYS or YEARS",
          "type": "string"
        }
      }
    }
  }
}
```

```
        "value": {
          "description": "The number of either DAYS or YEARS in the retention pe
riod",
          "type": "number"
        }
      }
    }
  }
}
```


s3/buckets/{name}/policy

Endpoint

/v1/s3/buckets/{name}/policy

GET

Gets the policy on an S3 bucket.

Parameters

Name	Description	Required
name	Bucket name	Yes

Response

Codes

Code	Description
200	Return value on success

PUT

Sets the policy on an S3 bucket. The format of the bucket policy can be found here: <https://docs.qumulo.com/administrator-guide/s3-api/creating-managing-s3-buckets.html>

Parameters

Name	Description	Required
name	Bucket name	Yes
allow-remove-self	If set to true, the user is able to set a bucket policy that removes their access to set bucket policies on this bucket, otherwise they cannot. If not present, removing self permissions will be denied.	No
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

s3/buckets/{name}/policy/explain-access

Endpoint

/v1/s3/buckets/{name}/policy/explain-access

POST

Explains the access of an identity due to the bucket policy.

Parameters

Name	Description	Required
name	Bucket name	Yes

Request

Schema

```
{
  "description": "api_bucket_policy_access_explanation_options",
  "type": "object",
  "properties": {
    "identity": {
      "description": "The identity to explain bucket access for, if None then return access for an anonymous user.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ]
        },
        "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `AP
```

```

I_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOM
AIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NUL
L_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_D
OMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAI
N,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_US
ER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  }
}
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_bucket_policy_access_explanation",
  "type": "object",

```

```

"properties": {
  "allowed_actions": {
    "type": "array",
    "items": {
      "description": "The complete set of API actions that the user is permitted to perform on the specified bucket.",
      "type": "string"
    }
  },
  "identity": {
    "description": "The identity the explanation pertains to.",
    "type": "object",
    "properties": {
      "domain": {
        "type": "string",
        "enum": [
          "LOCAL",
          "API_NULL_DOMAIN",
          "WORLD",
          "POSIX_USER",
          "POSIX_GROUP",
          "ACTIVE_DIRECTORY",
          "API_INVALID_DOMAIN",
          "API_RESERVED_DOMAIN",
          "API_INTERNAL_DOMAIN",
          "API_OPERATOR_DOMAIN",
          "API_QUMULO_SUPPORT_DOMAIN",
          "API_CREATOR_DOMAIN"
        ],
        "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
      },
      "auth_id": {
        "description": "auth_id",
        "type": "string"
      },
      "uid": {
        "description": "uid",
        "type": "number"
      },
      "gid": {

```


s3/buckets/{name}/uploads/

Endpoint

/v1/s3/buckets/{name}/uploads/

GET

List all in-progress S3 uploads for a specific bucket.

Parameters

Name	Description	Required
name	Bucket name	Yes
after	Return entries after the given key (keys are returned in the paging object)	No
limit	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_upload_description_list_model",
  "type": "object",
  "properties": {
    "uploads": {
      "type": "array",
      "items": {
        "description": "uploads",
        "type": "object",
        "properties": {
          "id": {
            "description": "The ID of the S3 upload.",
            "type": "string"
          }
        }
      }
    }
  }
}
```

```

    "key": {
      "description": "The key for which the system initiates the upload.",
      "type": "string"
    },
    "bucket": {
      "description": "The name of the S3 bucket to which the upload belongs.",
      "type": "string"
    },
    "initiator": {
      "description": "The system identity that represents the user who initiated the upload.",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ],
          "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
        },
        "auth_id": {
          "description": "auth_id",
          "type": "string"
        },
        "uid": {
          "description": "uid",
          "type": "number"
        },
        "gid": {

```



```

        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
},
"initiated": {
    "description": "The time at which the upload was initiated.",
    "type": "string"
},
"last_modified": {
    "description": "The time at which the upload was modified last.",
    "type": "string"
},
"total_blocks": {
    "description": "The total number of blocks (data and meta blocks) that t
he upload has used.",
    "type": "string"
},
"datablocks": {
    "description": "The number of data blocks that the upload has used.",
    "type": "string"
},
"metablocks": {
    "description": "The number of meta blocks that the upload has used.",
    "type": "string"
},
"completing": {
    "description": "The upload is in progress.",
    "type": "boolean"
},
"system_initiated": {
    "description": "The system has initiated the current upload as part of
a different request.",
    "type": "boolean"
}
}
}
}

```

```
}  
}
```

s3/buckets/{name}/uploads/{id}

Endpoint

/v1/s3/buckets/{name}/uploads/{id}

DELETE

Aborts an in-progress upload and releases all allocated storage.

Parameters

Name	Description	Required
name	Bucket name	Yes
id	Upload ID	Yes

Response

Codes

Code	Description
200	Return value on success

s3/settings

Endpoint

/v1/s3/settings

GET

Retrieve the current S3 server settings.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_v1_s3_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, allows the cluster to make S3 connections.",
      "type": "boolean"
    },
    "base_path": {
      "description": "The default bucket directory prefix for all S3 buckets created without an explicitly specified path, for example, by using the CreateBucket API action. You must specify this directory as an absolute path.",
      "type": "string"
    },
    "multipart_upload_expiry_interval": {
      "description": "The time period during which the system permits a multipart upload to remain unmodified. When this time period elapses, the system considers the multipart upload stale and cleans it up automatically. Specify the time period in the <quantity><units> format (for example, 5days). Quantity must be a positive integer less than 100 and units must be one of the following: months, weeks, days, or hours. To disable automatic multipart upload cleanup, specify never for quantity and do not specify any units.",
      "type": "string"
    }
  }
}
```

```

    "type": "string"
  },
  "secure": {
    "description": "If you specify true, the S3 server accepts only HTTP connections. By default, the S3 server accepts only HTTP connections.",
    "type": "boolean"
  }
}
}

```

PATCH

Modify the current S3 server settings.

Parameters

This resource has no parameters.

Request

Schema

```

{
  "description": "api_v1_s3_config_patch",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, allows the cluster to make S3 connections.",
      "type": "boolean"
    },
    "base_path": {
      "description": "The default bucket directory prefix for all S3 buckets created without an explicitly specified path, for example, by using the CreateBucket API action. You must specify this directory as an absolute path.",
      "type": "string"
    },
    "multipart_upload_expiry_interval": {
      "description": "The time period during which the system permits a multipart upload to remain unmodified. When this time period elapses, the system considers the multipart upload stale and cleans it up automatically. Specify the time period in the <quantity><units> format (for example, 5days). Quantity must be a positive integer less than 100 and units must be one of the following: months, weeks, days, or hours. To disable automatic multipart upload cleanup, specify never for quantity and do not specify any units.",
      "type": "string"
    }
  }
}

```

```

    "secure": {
      "description": "If you specify true, the S3 server accepts only HTTP connections. By default, the S3 server accepts only HTTP connections.",
      "type": "boolean"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_v1_s3_config",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, allows the cluster to make S3 connections.",
      "type": "boolean"
    },
    "base_path": {
      "description": "The default bucket directory prefix for all S3 buckets created without an explicitly specified path, for example, by using the CreateBucket API action. You must specify this directory as an absolute path.",
      "type": "string"
    },
    "multipart_upload_expiry_interval": {
      "description": "The time period during which the system permits a multipart upload to remain unmodified. When this time period elapses, the system considers the multipart upload stale and cleans it up automatically. Specify the time period in the <quantity><units> format (for example, 5days). Quantity must be a positive integer less than 100 and units must be one of the following: months, weeks, days, or hours. To disable automatic multipart upload cleanup, specify never for quantity and do not specify any units.",
      "type": "string"
    },
    "secure": {
      "description": "If you specify true, the S3 server accepts only HTTP connections. By default, the S3 server accepts only HTTP connections.",

```

```
    "type": "boolean"  
  }  
}  
}
```

saml/settings

Endpoint

/v1/saml/settings

GET

Retrieve the current SAML integration settings.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_v1_saml_settings",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, the cluster accepts SAML authentication. It is necessary first to create a SAML integration for the cluster with a third-party SSO service (that will act as a SAML Identity Provider) and obtain IdP SSO URL and X.509 certificate. Use https://cluster-fqdn/saml for the Service Provider endpoint when creating the SAML integration. The cluster must be joined to an Active Directory domain, and the SSO service must be connected to the same domain.",
      "type": "boolean"
    },
    "idp_sso_url": {
      "description": "IdP SSO URL. The cluster will send a SAML authentication request to this URL to ask for a Single Sign-On from the Identity Provider. ",
      "type": "string"
    },
    "idp_certificate": {
      "description": "IdP X.509 certificate in PEM format. The cluster will use it to validate the SAML Response received from the Identity Provider before granting the user from the response a bearer token to access the cluster.",
      "type": "string"
    }
  }
}
```



```

    "type": "string"
  },
  "idp_entity_id": {
    "description": "IdP entity ID. Must be a URI provided by the IdP. The cluster will use it to prepare correctly-formed SAML requests to the IdP and to verify that received SAML responses came from that IdP.",
    "type": "string"
  },
  "cluster_dns_name": {
    "description": "DNS name of the cluster. Must be of the form `cluster.domain.com`. The cluster uses this to correctly redirect authentication flows back to itself when the user attempts to log in to the Identity Provider.",
    "type": "string"
  },
  "require_sso": {
    "description": "If set, requires SSO for Active Directory (AD) users to be able to manage this cluster. The cluster rejects password-based authentication from AD users of the Web UI, qql CLI, and REST API. This setting does not restrict access over file protocols such as SMB.",
    "type": "boolean"
  }
}

```

PUT

Set the SAML integration settings.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_v1_saml_settings",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, the cluster accepts SAML authentication. It is necessary first to create a SAML integration for the cluster with a third-party SSO s

```

ervice (that will act as a SAML Identity Provider) and obtain IdP SSO URL and X.509 certificate. Use <https://cluster-fqdn/saml> for the Service Provider endpoint when creating the SAML integration. The cluster must be joined to an Active Directory domain, and the SSO service must be connected to the same domain.",

```
"type": "boolean"
},
"idp_sso_url": {
  "description": "IdP SSO URL. The cluster will send a SAML authentication request to this URL to ask for a Single Sign-On from the Identity Provider. ",
  "type": "string"
},
"idp_certificate": {
  "description": "IdP X.509 certificate in PEM format. The cluster will use it to validate the SAML Response received from the Identity Provider before granting the user from the response a bearer token to access the cluster.",
  "type": "string"
},
"idp_entity_id": {
  "description": "IdP entity ID. Must be a URI provided by the IdP. The cluster will use it to prepare correctly-formed SAML requests to the IdP and to verify that received SAML responses came from that IdP.",
  "type": "string"
},
"cluster_dns_name": {
  "description": "DNS name of the cluster. Must be of the form `cluster.domain.com`. The cluster uses this to correctly redirect authentication flows back to itself when the user attempts to log in to the Identity Provider.",
  "type": "string"
},
"require_sso": {
  "description": "If set, requires SSO for Active Directory (AD) users to be able to manage this cluster. The cluster rejects password-based authentication from AD users of the Web UI, qql CLI, and REST API. This setting does not restrict access over file protocols such as SMB.",
  "type": "boolean"
}
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_v1_saml_settings",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, the cluster accepts SAML authentication. It is necessary first to create a SAML integration for the cluster with a third-party SSO service (that will act as a SAML Identity Provider) and obtain IdP SSO URL and X.509 certificate. Use https://cluster-fqdn/saml for the Service Provider endpoint when creating the SAML integration. The cluster must be joined to an Active Directory domain, and the SSO service must be connected to the same domain.",
      "type": "boolean"
    },
    "idp_sso_url": {
      "description": "IdP SSO URL. The cluster will send a SAML authentication request to this URL to ask for a Single Sign-On from the Identity Provider. ",
      "type": "string"
    },
    "idp_certificate": {
      "description": "IdP X.509 certificate in PEM format. The cluster will use it to validate the SAML Response received from the Identity Provider before granting the user from the response a bearer token to access the cluster.",
      "type": "string"
    },
    "idp_entity_id": {
      "description": "IdP entity ID. Must be a URI provided by the IdP. The cluster will use it to prepare correctly-formed SAML requests to the IdP and to verify that received SAML responses came from that IdP.",
      "type": "string"
    },
    "cluster_dns_name": {
      "description": "DNS name of the cluster. Must be of the form `cluster.domain.com`. The cluster uses this to correctly redirect authentication flows back to itself when the user attempts to log in to the Identity Provider.",
      "type": "string"
    },
    "require_sso": {
      "description": "If set, requires SSO for Active Directory (AD) users to be able to manage this cluster. The cluster rejects password-based authentication from AD users of the Web UI, qq CLI, and REST API. This setting does not restrict access over file protocols such as SMB.",
      "type": "boolean"
    }
  }
}
```

```
}
```

PATCH

Modify the SAML integration settings.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_v1_saml_settings_patch",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, the cluster accepts SAML authentication. It is necessary first to create a SAML integration for the cluster with a third-party SSO service (that will act as a SAML Identity Provider) and obtain IdP SSO URL and X.509 certificate. Use https://cluster-fqdn/saml for the Service Provider endpoint when creating the SAML integration. The cluster must be joined to an Active Directory domain, and the SSO service must be connected to the same domain.",
      "type": "boolean"
    },
    "idp_sso_url": {
      "description": "IdP SSO URL. The cluster will send a SAML authentication request to this URL to ask for a Single Sign-On from the Identity Provider. ",
      "type": "string"
    },
    "idp_certificate": {
      "description": "IdP X.509 certificate in PEM format. The cluster will use it to validate the SAML Response received from the Identity Provider before granting the user from the response a bearer token to access the cluster.",
      "type": "string"
    },
    "idp_entity_id": {
      "description": "IdP entity ID. Must be a URI provided by the IdP. The cluster will use it to prepare correctly-formed SAML requests to the IdP and to verify that received SAML responses came from that IdP.",
      "type": "string"
    }
  }
}
```

```

    },
    "cluster_dns_name": {
      "description": "DNS name of the cluster. Must be of the form `cluster.domain.com`. The cluster uses this to correctly redirect authentication flows back to itself when the user attempts to log in to the Identity Provider.",
      "type": "string"
    },
    "require_sso": {
      "description": "If set, requires SSO for Active Directory (AD) users to be able to manage this cluster. The cluster rejects password-based authentication from AD users of the Web UI, qql CLI, and REST API. This setting does not restrict access over file protocols such as SMB.",
      "type": "boolean"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_v1_saml_settings",
  "type": "object",
  "properties": {
    "enabled": {
      "description": "When enabled, the cluster accepts SAML authentication. It is necessary first to create a SAML integration for the cluster with a third-party SSO service (that will act as a SAML Identity Provider) and obtain IdP SSO URL and X.509 certificate. Use https://cluster-fqdn/saml for the Service Provider endpoint when creating the SAML integration. The cluster must be joined to an Active Directory domain, and the SSO service must be connected to the same domain.",
      "type": "boolean"
    },
    "idp_sso_url": {
      "description": "IdP SSO URL. The cluster will send a SAML authentication request to this URL to ask for a Single Sign-On from the Identity Provider. ",
      "type": "string"
    }
  },
}

```

```

    "idp_certificate": {
      "description": "IdP X.509 certificate in PEM format. The cluster will use it to validate the SAML Response received from the Identity Provider before granting the user from the response a bearer token to access the cluster.",
      "type": "string"
    },
    "idp_entity_id": {
      "description": "IdP entity ID. Must be a URI provided by the IdP. The cluster will use it to prepare correctly-formed SAML requests to the IdP and to verify that received SAML responses came from that IdP.",
      "type": "string"
    },
    "cluster_dns_name": {
      "description": "DNS name of the cluster. Must be of the form `cluster.domain.com`. The cluster uses this to correctly redirect authentication flows back to itself when the user attempts to log in to the Identity Provider.",
      "type": "string"
    },
    "require_sso": {
      "description": "If set, requires SSO for Active Directory (AD) users to be able to manage this cluster. The cluster rejects password-based authentication from AD users of the Web UI, qql CLI, and REST API. This setting does not restrict access over file protocols such as SMB.",
      "type": "boolean"
    }
  }
}

```

smb/files/

Endpoint

/v1/smb/files/

GET

Enumerate open file handles

Parameters

Name	Description	Required
<code>file_number</code>	File ID. Limits result to handles on the specified file.	No
<code>resolve_paths</code>	Includes the paths to each file in the results. Resolving many paths can be slow.	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_files_get_response",
  "type": "object",
  "properties": {
    "file_handles": {
      "type": "array",
      "items": {
        "description": "file_handles",
        "type": "object",

```

```

"properties": {
  "file_number": {
    "description": "file_number",
    "type": "string"
  },
  "handle_info": {
    "description": "handle_info",
    "type": "object",
    "properties": {
      "location": {
        "description": "location",
        "type": "string"
      },
      "version": {
        "description": "version",
        "type": "number"
      },
      "num_byte_range_locks": {
        "description": "num_byte_range_locks",
        "type": "number"
      },
      "num_notify_watches": {
        "description": "num_notify_watches",
        "type": "string"
      },
      "access_mask": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "MS_ACCESS_FILE_READ_DATA",
            "MS_ACCESS_FILE_WRITE_DATA",
            "MS_ACCESS_FILE_APPEND_DATA",
            "MS_ACCESS_FILE_EXECUTE",
            "MS_ACCESS_FILE_READ_EA",
            "MS_ACCESS_FILE_WRITE_EA",
            "MS_ACCESS_FILE_DELETE_CHILD",
            "MS_ACCESS_FILE_READ_ATTRIBUTES",
            "MS_ACCESS_FILE_WRITE_ATTRIBUTES",
            "MS_ACCESS_OBJECT_SPECIFIC_9",
            "MS_ACCESS_OBJECT_SPECIFIC_10",
            "MS_ACCESS_OBJECT_SPECIFIC_11",
            "MS_ACCESS_OBJECT_SPECIFIC_12",
            "MS_ACCESS_OBJECT_SPECIFIC_13",
            "MS_ACCESS_OBJECT_SPECIFIC_14",
            "MS_ACCESS_OBJECT_SPECIFIC_15",

```



```

        "MS_ACCESS_DELETE",
        "MS_ACCESS_READ_CONTROL",
        "MS_ACCESS_WRITE_DAC",
        "MS_ACCESS_WRITE_OWNER",
        "MS_ACCESS_SYNCHRONIZE",
        "MS_ACCESS_SYSTEM_SECURITY",
        "MS_ACCESS_MAXIMUM_ALLOWED",
        "MS_ACCESS_GENERIC_ALL",
        "MS_ACCESS_GENERIC_EXECUTE",
        "MS_ACCESS_GENERIC_WRITE",
        "MS_ACCESS_GENERIC_READ"
    ],
    "description": "access_mask:\n * `MS_ACCESS_DELETE` - MS_ACCESS_DELETE,\n * `MS_ACCESS_FILE_APPEND_DATA` - MS_ACCESS_FILE_APPEND_DATA,\n * `MS_ACCESS_FILE_DELETE_CHILD` - MS_ACCESS_FILE_DELETE_CHILD,\n * `MS_ACCESS_FILE_EXECUTE` - MS_ACCESS_FILE_EXECUTE,\n * `MS_ACCESS_FILE_READ_ATTRIBUTES` - MS_ACCESS_FILE_READ_ATTRIBUTES,\n * `MS_ACCESS_FILE_READ_DATA` - MS_ACCESS_FILE_READ_DATA,\n * `MS_ACCESS_FILE_READ_EA` - MS_ACCESS_FILE_READ_EA,\n * `MS_ACCESS_FILE_WRITE_ATTRIBUTES` - MS_ACCESS_FILE_WRITE_ATTRIBUTES,\n * `MS_ACCESS_FILE_WRITE_DATA` - MS_ACCESS_FILE_WRITE_DATA,\n * `MS_ACCESS_FILE_WRITE_EA` - MS_ACCESS_FILE_WRITE_EA,\n * `MS_ACCESS_GENERIC_ALL` - MS_ACCESS_GENERIC_ALL,\n * `MS_ACCESS_GENERIC_EXECUTE` - MS_ACCESS_GENERIC_EXECUTE,\n * `MS_ACCESS_GENERIC_READ` - MS_ACCESS_GENERIC_READ,\n * `MS_ACCESS_GENERIC_WRITE` - MS_ACCESS_GENERIC_WRITE,\n * `MS_ACCESS_MAXIMUM_ALLOWED` - MS_ACCESS_MAXIMUM_ALLOWED,\n * `MS_ACCESS_OBJECT_SPECIFIC_10` - MS_ACCESS_OBJECT_SPECIFIC_10,\n * `MS_ACCESS_OBJECT_SPECIFIC_11` - MS_ACCESS_OBJECT_SPECIFIC_11,\n * `MS_ACCESS_OBJECT_SPECIFIC_12` - MS_ACCESS_OBJECT_SPECIFIC_12,\n * `MS_ACCESS_OBJECT_SPECIFIC_13` - MS_ACCESS_OBJECT_SPECIFIC_13,\n * `MS_ACCESS_OBJECT_SPECIFIC_14` - MS_ACCESS_OBJECT_SPECIFIC_14,\n * `MS_ACCESS_OBJECT_SPECIFIC_15` - MS_ACCESS_OBJECT_SPECIFIC_15,\n * `MS_ACCESS_OBJECT_SPECIFIC_9` - MS_ACCESS_OBJECT_SPECIFIC_9,\n * `MS_ACCESS_READ_CONTROL` - MS_ACCESS_READ_CONTROL,\n * `MS_ACCESS_SYNCHRONIZE` - MS_ACCESS_SYNCHRONIZE,\n * `MS_ACCESS_SYSTEM_SECURITY` - MS_ACCESS_SYSTEM_SECURITY,\n * `MS_ACCESS_WRITE_DAC` - MS_ACCESS_WRITE_DAC,\n * `MS_ACCESS_WRITE_OWNER` - MS_ACCESS_WRITE_OWNER"
    },
    "owner": {
        "description": "owner",
        "type": "string"
    },
    "path": {
        "description": "path",
        "type": "string"
    }
}
}
}
}

```

```
}  
}  
}
```

smb/files/close

Endpoint

/v1/smb/files/close

POST

The request body must contain a list of file handles to close, as returned from GET /v1/smb/files. Fields other than 'location' are ignored.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_smb2_close_file_handle",
    "type": "object",
    "properties": {
      "handle_info": {
        "description": "handle_info",
        "type": "object",
        "properties": {
          "location": {
            "description": "location",
            "type": "string"
          }
        }
      }
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_smb2_file_close_result",
    "type": "object",
    "properties": {
      "error_message": {
        "description": "error_message",
        "type": "string"
      }
    }
  }
}
```

multitenancy/smb/global-settings

Endpoint

/v1/multitenancy/smb/global-settings

GET

[preview] Retrieve global SMB configuration.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SMB2_DIALECT_2_002",

```

```

        "SMB2_DIALECT_2_1",
        "SMB2_DIALECT_3_0",
        "SMB2_DIALECT_3_11"
    ],
    "description": "supported_dialects:\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
  },
  },
  "hide_shares_from_unauthorized_users": {
    "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
    "type": "boolean"
  },
  "hide_shares_from_unauthorized_hosts": {
    "description": "If share permissions deny a connected host access to a share, that share will not be visible in the share listing.",
    "type": "boolean"
  },
  "snapshot_directory_mode": {
    "type": "string",
    "enum": [
      "VISIBLE",
      "HIDDEN",
      "DISABLED"
    ],
    "description": "Whether the special .snapshot directory should be visible or accessible.:\n * `DISABLED` - .snapshot directories will not be accessible via SMB.,\n * `HIDDEN` - .snapshot directories will not be visible in directory listings, but may be opened by name.,\n * `VISIBLE` - A .snapshot directory will be visible when listing the root directory of a SMB share."
  },
  "bypass_traverse_checking": {
    "description": "Skip directory traversal checking for all users.",
    "type": "boolean"
  },
  "signing_required": {
    "description": "Requires messages from non-guest users to be signed.",
    "type": "boolean"
  }
}
}

```

PUT

[preview] Set global SMB configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SMB2_DIALECT_2_002",
          "SMB2_DIALECT_2_1",
          "SMB2_DIALECT_3_0",
          "SMB2_DIALECT_3_11"
        ],
        "description": "supported_dialects:\\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
      }
    },
    "hide_shares_from_unauthorized_users": {
      "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    }
  }
}
```

```

"hide_shares_from_unauthorized_hosts": {
  "description": "If share permissions deny a connected host access to a share,
that share will not be visible in the share listing.",
  "type": "boolean"
},
"snapshot_directory_mode": {
  "type": "string",
  "enum": [
    "VISIBLE",
    "HIDDEN",
    "DISABLED"
  ],
  "description": "Whether the special .snapshot directory should be visible or a
ccessible.:\\n * `DISABLED` - .snapshot directories will not be accessible via SM
B.,\\n * `HIDDEN` - .snapshot directories will not be visible in directory listings,
but may be opened by name.,\\n * `VISIBLE` - A .snapshot directory will be visible wh
en listing the root directory of a SMB share."
},
"bypass_traverse_checking": {
  "description": "Skip directory traversal checking for all users.",
  "type": "boolean"
},
"signing_required": {
  "description": "Requires messages from non-guest users to be signed.",
  "type": "boolean"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",

```



```

    "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
    ],
    "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
},
"supported_dialects": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "SMB2_DIALECT_2_002",
            "SMB2_DIALECT_2_1",
            "SMB2_DIALECT_3_0",
            "SMB2_DIALECT_3_11"
        ]
    },
    "description": "supported_dialects:\\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
},
"hide_shares_from_unauthorized_users": {
    "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
    "type": "boolean"
},
"hide_shares_from_unauthorized_hosts": {
    "description": "If share permissions deny a connected host access to a share, that share will not be visible in the share listing.",
    "type": "boolean"
},
"snapshot_directory_mode": {
    "type": "string",
    "enum": [
        "VISIBLE",
        "HIDDEN",
        "DISABLED"
    ],
    "description": "Whether the special .snapshot directory should be visible or accessible.:\\n * `DISABLED` - .snapshot directories will not be accessible via SMB.,\\n * `HIDDEN` - .snapshot directories will not be visible in directory listings, but may be opened by name.,\\n * `VISIBLE` - A .snapshot directory will be visible wh

```

```

en listing the root directory of a SMB share."
    },
    "bypass_traverse_checking": {
      "description": "Skip directory traversal checking for all users.",
      "type": "boolean"
    },
    "signing_required": {
      "description": "Requires messages from non-guest users to be signed.",
      "type": "boolean"
    }
  }
}

```

PATCH

[preview] Modify global SMB configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_smb_settings_patch",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",

```

```

    "items": {
      "type": "string",
      "enum": [
        "SMB2_DIALECT_2_002",
        "SMB2_DIALECT_2_1",
        "SMB2_DIALECT_3_0",
        "SMB2_DIALECT_3_11"
      ],
      "description": "supported_dialects:\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
    },
    "hide_shares_from_unauthorized_users": {
      "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "hide_shares_from_unauthorized_hosts": {
      "description": "If share permissions deny a connected host access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "snapshot_directory_mode": {
      "type": "string",
      "enum": [
        "VISIBLE",
        "HIDDEN",
        "DISABLED"
      ],
      "description": "Whether the special .snapshot directory should be visible or accessible.\n * `DISABLED` - .snapshot directories will not be accessible via SMB.,\n * `HIDDEN` - .snapshot directories will not be visible in directory listings, but may be opened by name.,\n * `VISIBLE` - A .snapshot directory will be visible when listing the root directory of a SMB share."
    },
    "bypass_traverse_checking": {
      "description": "Skip directory traversal checking for all users.",
      "type": "boolean"
    },
    "signing_required": {
      "description": "Requires messages from non-guest users to be signed.",
      "type": "boolean"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SMB2_DIALECT_2_002",
          "SMB2_DIALECT_2_1",
          "SMB2_DIALECT_3_0",
          "SMB2_DIALECT_3_11"
        ],
        "description": "supported_dialects:\\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
      }
    },
    "hide_shares_from_unauthorized_users": {
      "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    }
  }
}
```

```

    "hide_shares_from_unauthorized_hosts": {
      "description": "If share permissions deny a connected host access to a share,
that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "snapshot_directory_mode": {
      "type": "string",
      "enum": [
        "VISIBLE",
        "HIDDEN",
        "DISABLED"
      ],
      "description": "Whether the special .snapshot directory should be visible or a
ccessible.:\\n * `DISABLED` - .snapshot directories will not be accessible via SM
B.,\\n * `HIDDEN` - .snapshot directories will not be visible in directory listings,
but may be opened by name.,\\n * `VISIBLE` - A .snapshot directory will be visible wh
en listing the root directory of a SMB share."
    },
    "bypass_traverse_checking": {
      "description": "Skip directory traversal checking for all users.",
      "type": "boolean"
    },
    "signing_required": {
      "description": "Requires messages from non-guest users to be signed.",
      "type": "boolean"
    }
  }
}

```

multitenancy/smb/settings/

Endpoint

/v1/multitenancy/smb/settings/

GET

[preview] Retrieve all tenant-specific SMB configurations.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_settings_map",
  "type": "object",
  "properties": {},
  "additionalProperties": {
    "description": "api_smb_settings_map value",
    "type": "object",
    "properties": {
      "session_encryption": {
        "type": "string",
        "enum": [
          "NONE",
          "PREFERRED",
          "REQUIRED"
        ],
        "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
      },
      "supported_dialects": {
        "type": "array",
```

```

    "items": {
      "type": "string",
      "enum": [
        "SMB2_DIALECT_2_002",
        "SMB2_DIALECT_2_1",
        "SMB2_DIALECT_3_0",
        "SMB2_DIALECT_3_11"
      ],
      "description": "supported_dialects:\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
    },
    "hide_shares_from_unauthorized_users": {
      "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "hide_shares_from_unauthorized_hosts": {
      "description": "If share permissions deny a connected host access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "snapshot_directory_mode": {
      "type": "string",
      "enum": [
        "VISIBLE",
        "HIDDEN",
        "DISABLED"
      ],
      "description": "Whether the special .snapshot directory should be visible or accessible.:\n * `DISABLED` - .snapshot directories will not be accessible via SMB.,\n * `HIDDEN` - .snapshot directories will not be visible in directory listings, but may be opened by name.,\n * `VISIBLE` - A .snapshot directory will be visible when listing the root directory of a SMB share."
    },
    "bypass_traverse_checking": {
      "description": "Skip directory traversal checking for all users.",
      "type": "boolean"
    },
    "signing_required": {
      "description": "Requires messages from non-guest users to be signed.",
      "type": "boolean"
    }
  }
}

```

}

multitenancy/smb/settings/{id}

Endpoint

/v1/multitenancy/smb/settings/{id}

GET

[preview] Retrieve current tenant-specific SMB configuration.

Parameters

Name	Description	Required
id	The tenant ID of the SMB settings.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",
      "items": {
```

```

    "type": "string",
    "enum": [
        "SMB2_DIALECT_2_002",
        "SMB2_DIALECT_2_1",
        "SMB2_DIALECT_3_0",
        "SMB2_DIALECT_3_11"
    ],
    "description": "supported_dialects:\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
  },
  "hide_shares_from_unauthorized_users": {
    "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
    "type": "boolean"
  },
  "hide_shares_from_unauthorized_hosts": {
    "description": "If share permissions deny a connected host access to a share, that share will not be visible in the share listing.",
    "type": "boolean"
  },
  "snapshot_directory_mode": {
    "type": "string",
    "enum": [
        "VISIBLE",
        "HIDDEN",
        "DISABLED"
    ],
    "description": "Whether the special .snapshot directory should be visible or accessible.\n * `DISABLED` - .snapshot directories will not be accessible via SMB.,\n * `HIDDEN` - .snapshot directories will not be visible in directory listings, but may be opened by name.,\n * `VISIBLE` - A .snapshot directory will be visible when listing the root directory of a SMB share."
  },
  "bypass_traverse_checking": {
    "description": "Skip directory traversal checking for all users.",
    "type": "boolean"
  },
  "signing_required": {
    "description": "Requires messages from non-guest users to be signed.",
    "type": "boolean"
  }
}

```

PUT

[preview] Set current tenant-specific SMB configuration.

Parameters

Name	Description	Required
<code>id</code>	The tenant ID of the SMB settings.	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SMB2_DIALECT_2_002",
          "SMB2_DIALECT_2_1",
          "SMB2_DIALECT_3_0",
          "SMB2_DIALECT_3_11"
        ],
        "description": "supported_dialects:\\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
      }
    }
  }
}
```

```

    },
    "hide_shares_from_unauthorized_users": {
      "description": "If share permissions deny a logged in user access to a share,
that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "hide_shares_from_unauthorized_hosts": {
      "description": "If share permissions deny a connected host access to a share,
that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "snapshot_directory_mode": {
      "type": "string",
      "enum": [
        "VISIBLE",
        "HIDDEN",
        "DISABLED"
      ],
      "description": "Whether the special .snapshot directory should be visible or a
ccessible.:\\n * `DISABLED` - .snapshot directories will not be accessible via SM
B.,\\n * `HIDDEN` - .snapshot directories will not be visible in directory listings,
but may be opened by name.,\\n * `VISIBLE` - A .snapshot directory will be visible wh
en listing the root directory of a SMB share."
    },
    "bypass_traverse_checking": {
      "description": "Skip directory traversal checking for all users.",
      "type": "boolean"
    },
    "signing_required": {
      "description": "Requires messages from non-guest users to be signed.",
      "type": "boolean"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SMB2_DIALECT_2_002",
          "SMB2_DIALECT_2_1",
          "SMB2_DIALECT_3_0",
          "SMB2_DIALECT_3_11"
        ],
        "description": "supported_dialects:\\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
      }
    },
    "hide_shares_from_unauthorized_users": {
      "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "hide_shares_from_unauthorized_hosts": {
      "description": "If share permissions deny a connected host access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "snapshot_directory_mode": {
      "type": "string",
      "enum": [
```

```

        "VISIBLE",
        "HIDDEN",
        "DISABLED"
    ],
    "description": "Whether the special .snapshot directory should be visible or a ccessible.:\\n * `DISABLED` - .snapshot directories will not be accessible via SMB.,\\n * `HIDDEN` - .snapshot directories will not be visible in directory listings, but may be opened by name.,\\n * `VISIBLE` - A .snapshot directory will be visible wh en listing the root directory of a SMB share."
  },
  "bypass_traverse_checking": {
    "description": "Skip directory traversal checking for all users.",
    "type": "boolean"
  },
  "signing_required": {
    "description": "Requires messages from non-guest users to be signed.",
    "type": "boolean"
  }
}
}

```

DELETE

[preview] Delete current SMB configuration, restoring the global settings for this tenant.

Parameters

Name	Description	Required
id	The tenant ID of the SMB settings.	Yes
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

[preview] Modify current tenant-specific SMB configuration.

Parameters

Name	Description	Required
<code>id</code>	The tenant ID of the SMB settings.	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_smb_settings_patch",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SMB2_DIALECT_2_002",
          "SMB2_DIALECT_2_1",
          "SMB2_DIALECT_3_0",
          "SMB2_DIALECT_3_11"
        ]
      },
      "description": "supported_dialects:\\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
    },
    "hide_shares_from_unauthorized_users": {
      "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing."
    }
  }
}
```

```

    "type": "boolean"
  },
  "hide_shares_from_unauthorized_hosts": {
    "description": "If share permissions deny a connected host access to a share,
that share will not be visible in the share listing.",
    "type": "boolean"
  },
  "snapshot_directory_mode": {
    "type": "string",
    "enum": [
      "VISIBLE",
      "HIDDEN",
      "DISABLED"
    ],
    "description": "Whether the special .snapshot directory should be visible or a
ccessible.:\\n * `DISABLED` - .snapshot directories will not be accessible via SM
B.,\\n * `HIDDEN` - .snapshot directories will not be visible in directory listings,
but may be opened by name.,\\n * `VISIBLE` - A .snapshot directory will be visible wh
en listing the root directory of a SMB share."
  },
  "bypass_traverse_checking": {
    "description": "Skip directory traversal checking for all users.",
    "type": "boolean"
  },
  "signing_required": {
    "description": "Requires messages from non-guest users to be signed.",
    "type": "boolean"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {

```



```

"session_encryption": {
  "type": "string",
  "enum": [
    "NONE",
    "PREFERRED",
    "REQUIRED"
  ],
  "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
},
"supported_dialects": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "SMB2_DIALECT_2_002",
      "SMB2_DIALECT_2_1",
      "SMB2_DIALECT_3_0",
      "SMB2_DIALECT_3_11"
    ]
  },
  "description": "supported_dialects:\\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
},
"hide_shares_from_unauthorized_users": {
  "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
  "type": "boolean"
},
"hide_shares_from_unauthorized_hosts": {
  "description": "If share permissions deny a connected host access to a share, that share will not be visible in the share listing.",
  "type": "boolean"
},
"snapshot_directory_mode": {
  "type": "string",
  "enum": [
    "VISIBLE",
    "HIDDEN",
    "DISABLED"
  ],
  "description": "Whether the special .snapshot directory should be visible or accessible.:\\n * `DISABLED` - .snapshot directories will not be accessible via SM

```

B.,\n * `HIDDEN` - .snapshot directories will not be visible in directory listings, but may be opened by name.,\n * `VISIBLE` - A .snapshot directory will be visible when listing the root directory of a SMB share."

```
    },
    "bypass_traverse_checking": {
      "description": "Skip directory traversal checking for all users.",
      "type": "boolean"
    },
    "signing_required": {
      "description": "Requires messages from non-guest users to be signed.",
      "type": "boolean"
    }
  }
}
```

smb/settings

Endpoint

/v1/smb/settings

GET

Get settings for the SMB Server.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SMB2_DIALECT_2_002",

```

```

        "SMB2_DIALECT_2_1",
        "SMB2_DIALECT_3_0",
        "SMB2_DIALECT_3_11"
    ],
    "description": "supported_dialects:\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
    }
},
"hide_shares_from_unauthorized_users": {
    "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
    "type": "boolean"
},
"hide_shares_from_unauthorized_hosts": {
    "description": "If share permissions deny a connected host access to a share, that share will not be visible in the share listing.",
    "type": "boolean"
},
"snapshot_directory_mode": {
    "type": "string",
    "enum": [
        "VISIBLE",
        "HIDDEN",
        "DISABLED"
    ],
    "description": "Whether the special .snapshot directory should be visible or accessible.:\n * `DISABLED` - .snapshot directories will not be accessible via SMB.,\n * `HIDDEN` - .snapshot directories will not be visible in directory listings, but may be opened by name.,\n * `VISIBLE` - A .snapshot directory will be visible when listing the root directory of a SMB share."
},
"bypass_traverse_checking": {
    "description": "Skip directory traversal checking for all users.",
    "type": "boolean"
},
"signing_required": {
    "description": "Requires messages from non-guest users to be signed.",
    "type": "boolean"
}
}
}

```

PUT

Set settings for the SMB Server.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SMB2_DIALECT_2_002",
          "SMB2_DIALECT_2_1",
          "SMB2_DIALECT_3_0",
          "SMB2_DIALECT_3_11"
        ],
        "description": "supported_dialects:\\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
      }
    },
    "hide_shares_from_unauthorized_users": {
      "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    }
  }
}
```

```

"hide_shares_from_unauthorized_hosts": {
  "description": "If share permissions deny a connected host access to a share,
that share will not be visible in the share listing.",
  "type": "boolean"
},
"snapshot_directory_mode": {
  "type": "string",
  "enum": [
    "VISIBLE",
    "HIDDEN",
    "DISABLED"
  ],
  "description": "Whether the special .snapshot directory should be visible or a
ccessible.:\\n * `DISABLED` - .snapshot directories will not be accessible via SM
B.,\\n * `HIDDEN` - .snapshot directories will not be visible in directory listings,
but may be opened by name.,\\n * `VISIBLE` - A .snapshot directory will be visible wh
en listing the root directory of a SMB share."
},
"bypass_traverse_checking": {
  "description": "Skip directory traversal checking for all users.",
  "type": "boolean"
},
"signing_required": {
  "description": "Requires messages from non-guest users to be signed.",
  "type": "boolean"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",

```

```

    "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
    ],
    "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
},
"supported_dialects": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "SMB2_DIALECT_2_002",
            "SMB2_DIALECT_2_1",
            "SMB2_DIALECT_3_0",
            "SMB2_DIALECT_3_11"
        ]
    },
    "description": "supported_dialects:\\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
},
"hide_shares_from_unauthorized_users": {
    "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
    "type": "boolean"
},
"hide_shares_from_unauthorized_hosts": {
    "description": "If share permissions deny a connected host access to a share, that share will not be visible in the share listing.",
    "type": "boolean"
},
"snapshot_directory_mode": {
    "type": "string",
    "enum": [
        "VISIBLE",
        "HIDDEN",
        "DISABLED"
    ],
    "description": "Whether the special .snapshot directory should be visible or accessible.:\\n * `DISABLED` - .snapshot directories will not be accessible via SMB.,\\n * `HIDDEN` - .snapshot directories will not be visible in directory listings, but may be opened by name.,\\n * `VISIBLE` - A .snapshot directory will be visible wh

```

```

en listing the root directory of a SMB share."
    },
    "bypass_traverse_checking": {
      "description": "Skip directory traversal checking for all users.",
      "type": "boolean"
    },
    "signing_required": {
      "description": "Requires messages from non-guest users to be signed.",
      "type": "boolean"
    }
  }
}

```

PATCH

Partially set settings for the SMB Server.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_smb_settings_patch",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",

```



```

    "items": {
      "type": "string",
      "enum": [
        "SMB2_DIALECT_2_002",
        "SMB2_DIALECT_2_1",
        "SMB2_DIALECT_3_0",
        "SMB2_DIALECT_3_11"
      ],
      "description": "supported_dialects:\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
    },
    "hide_shares_from_unauthorized_users": {
      "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "hide_shares_from_unauthorized_hosts": {
      "description": "If share permissions deny a connected host access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "snapshot_directory_mode": {
      "type": "string",
      "enum": [
        "VISIBLE",
        "HIDDEN",
        "DISABLED"
      ],
      "description": "Whether the special .snapshot directory should be visible or accessible.:\n * `DISABLED` - .snapshot directories will not be accessible via SMB.,\n * `HIDDEN` - .snapshot directories will not be visible in directory listings, but may be opened by name.,\n * `VISIBLE` - A .snapshot directory will be visible when listing the root directory of a SMB share."
    },
    "bypass_traverse_checking": {
      "description": "Skip directory traversal checking for all users.",
      "type": "boolean"
    },
    "signing_required": {
      "description": "Requires messages from non-guest users to be signed.",
      "type": "boolean"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_settings",
  "type": "object",
  "properties": {
    "session_encryption": {
      "type": "string",
      "enum": [
        "NONE",
        "PREFERRED",
        "REQUIRED"
      ],
      "description": "Session-level encryption setting.:\\n * `NONE` - Do not instruct clients to encrypt SMB traffic.,\\n * `PREFERRED` - Instruct clients to encrypt SMB traffic if they support encryption.,\\n * `REQUIRED` - Always instruct clients to encrypt SMB traffic. Reject clients who do not support encryption."
    },
    "supported_dialects": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SMB2_DIALECT_2_002",
          "SMB2_DIALECT_2_1",
          "SMB2_DIALECT_3_0",
          "SMB2_DIALECT_3_11"
        ],
        "description": "supported_dialects:\\n * `SMB2_DIALECT_2_002` - API_SMB2_DIALECT_2_002,\\n * `SMB2_DIALECT_2_1` - API_SMB2_DIALECT_2_1,\\n * `SMB2_DIALECT_3_0` - API_SMB2_DIALECT_3_0,\\n * `SMB2_DIALECT_3_11` - API_SMB2_DIALECT_3_11"
      }
    },
    "hide_shares_from_unauthorized_users": {
      "description": "If share permissions deny a logged in user access to a share, that share will not be visible in the share listing.",
      "type": "boolean"
    }
  }
}
```

```

    "hide_shares_from_unauthorized_hosts": {
      "description": "If share permissions deny a connected host access to a share,
that share will not be visible in the share listing.",
      "type": "boolean"
    },
    "snapshot_directory_mode": {
      "type": "string",
      "enum": [
        "VISIBLE",
        "HIDDEN",
        "DISABLED"
      ],
      "description": "Whether the special .snapshot directory should be visible or a
ccessible.:\\n * `DISABLED` - .snapshot directories will not be accessible via SM
B.,\\n * `HIDDEN` - .snapshot directories will not be visible in directory listings,
but may be opened by name.,\\n * `VISIBLE` - A .snapshot directory will be visible wh
en listing the root directory of a SMB share."
    },
    "bypass_traverse_checking": {
      "description": "Skip directory traversal checking for all users.",
      "type": "boolean"
    },
    "signing_required": {
      "description": "Requires messages from non-guest users to be signed.",
      "type": "boolean"
    }
  }
}

```

smb/sessions/

Endpoint

/v1/smb/sessions/

GET

Enumerate open sessions

Parameters

Name	Description	Required
<code>identity</code>	List only sessions matching a user identity in the form of: [1] A name or a SID optionally qualified with a domain prefix (e.g local:name, S-1-1-0, name, world:Everyone, ldap_user:name, or ad:name), or [2] An ID type (e.g. uid:1001, auth_id:513, SID:S-1-1-0.).	No
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_sessions_get_response",
  "type": "object",
  "properties": {
    "session_infos": {
      "type": "array",
      "items": {
        "description": "session_infos",
        "type": "object",
        "properties": {
```

```

"location": {
  "description": "location",
  "type": "string"
},
"tenant_id": {
  "description": "tenant_id",
  "type": "number"
},
"originator": {
  "description": "originator",
  "type": "string"
},
"server_address": {
  "description": "server_address",
  "type": "string"
},
"user": {
  "description": "user",
  "type": "object",
  "properties": {
    "domain": {
      "type": "string",
      "enum": [
        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
      ],
      "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",

```

```

        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
},
"num_opens": {
    "description": "num_opens",
    "type": "number"
},
"time_open": {
    "description": "time_open",
    "type": "object",
    "properties": {
        "nanoseconds": {
            "description": "nanoseconds",
            "type": "string"
        }
    }
},
"time_idle": {
    "description": "time_idle",
    "type": "object",
    "properties": {
        "nanoseconds": {
            "description": "nanoseconds",
            "type": "string"
        }
    }
},
"is_guest": {
    "description": "is_guest",

```

```
    "type": "boolean"
  },
  "is_encrypted": {
    "description": "is_encrypted",
    "type": "boolean"
  },
  "share_names": {
    "type": "array",
    "items": {
      "description": "share_names",
      "type": "string"
    }
  }
}
}
```

smb/sessions/close

Endpoint

/v1/smb/sessions/close

POST

The request body must contain a list of sessions to close, as returned from GET /v1/smb/sessions.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_smb_session_info",
    "type": "object",
    "properties": {
      "location": {
        "description": "location",
        "type": "string"
      },
      "tenant_id": {
        "description": "tenant_id",
        "type": "number"
      },
      "originator": {
        "description": "originator",
        "type": "string"
      },
      "server_address": {
        "description": "server_address",
        "type": "string"
      },
      "user": {
        "description": "user",
        "type": "object",
        "properties": {
          "domain": {
            "type": "string",
            "enum": [
```



```

        "LOCAL",
        "API_NULL_DOMAIN",
        "WORLD",
        "POSIX_USER",
        "POSIX_GROUP",
        "ACTIVE_DIRECTORY",
        "API_INVALID_DOMAIN",
        "API_RESERVED_DOMAIN",
        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n *
`API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNA
L_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - AP
I_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPP
ORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DO
MAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSI
X_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
    }
},
"num_opens": {
    "description": "num_opens",
    "type": "number"
}

```

```

},
"time_open": {
  "description": "time_open",
  "type": "object",
  "properties": {
    "nanoseconds": {
      "description": "nanoseconds",
      "type": "string"
    }
  }
},
"time_idle": {
  "description": "time_idle",
  "type": "object",
  "properties": {
    "nanoseconds": {
      "description": "nanoseconds",
      "type": "string"
    }
  }
},
"is_guest": {
  "description": "is_guest",
  "type": "boolean"
},
"is_encrypted": {
  "description": "is_encrypted",
  "type": "boolean"
},
"share_names": {
  "type": "array",
  "items": {
    "description": "share_names",
    "type": "string"
  }
}
}
}
}

```

Response

Codes

Code	Description
------	-------------

200	Return value on success
-----	-------------------------

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_smb2_session_close_result",
    "type": "object",
    "properties": {
      "error_message": {
        "description": "error_message",
        "type": "string"
      }
    }
  }
}
```

smb/shares/

Endpoint

/v1/smb/shares/

GET

List all SMB shares. Refer to the 'Modify SMB share' method for a description of the returned fields.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_smb_share",
    "type": "object",
    "properties": {
      "id": {
        "description": "The unique ID of the SMB share",
        "type": "string"
      },
      "share_name": {
        "description": "The SMB share name",
        "type": "string"
      },
      "fs_path": {
        "description": "The filesystem path to SMB share",
        "type": "string"
      },
      "description": {
        "description": "Description of this SMB share",
        "type": "string"
      }
    }
  }
}
```

```

    },
    "read_only": {
      "description": "Sets the SMB share to read-only",
      "type": "boolean"
    },
    "allow_guest_access": {
      "description": "Allows guest access to this SMB share",
      "type": "boolean"
    },
    "access_based_enumeration_enabled": {
      "description": "Enable Access-based Enumeration on this SMB share",
      "type": "boolean"
    },
    "default_file_create_mode": {
      "description": "Default POSIX file create mode bits on this SMB share (octal, default 0644 if this field is empty)",
      "type": "string"
    },
    "default_directory_create_mode": {
      "description": "Default POSIX directory create mode bits on this SMB share (octal, default 0755 if this field is empty)",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the SMB share is a part of",
      "type": "number"
    }
  }
}

```

POST

Add an SMB share with given options.

Parameters

Name	Description	Required
<code>allow-fs-path-create</code>	Specifies whether the file system path can be created if it does not already exist.	No

Request

Schema

```
{
  "description": "api_smb_share_post",
  "type": "object",
  "properties": {
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",
      "type": "string"
    },
    "read_only": {
      "description": "Sets the SMB share to read-only",
      "type": "boolean"
    },
    "allow_guest_access": {
      "description": "Allows guest access to this SMB share",
      "type": "boolean"
    },
    "access_based_enumeration_enabled": {
      "description": "Enable Access-based Enumeration on this SMB share",
      "type": "boolean"
    },
    "default_file_create_mode": {
      "description": "Default POSIX file create mode bits on this SMB share (octal, default 0644 if this field is empty)",
      "type": "string"
    },
    "default_directory_create_mode": {
      "description": "Default POSIX directory create mode bits on this SMB share (octal, default 0755 if this field is empty)",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_share",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",
      "type": "string"
    },
    "read_only": {
      "description": "Sets the SMB share to read-only",
      "type": "boolean"
    },
    "allow_guest_access": {
      "description": "Allows guest access to this SMB share",
      "type": "boolean"
    },
    "access_based_enumeration_enabled": {
      "description": "Enable Access-based Enumeration on this SMB share",
      "type": "boolean"
    },
    "default_file_create_mode": {
      "description": "Default POSIX file create mode bits on this SMB share (octal, default 0644 if this field is empty)",
      "type": "string"
    }
  }
}
```

```
    },  
    "default_directory_create_mode": {  
      "description": "Default POSIX directory create mode bits on this SMB share (oc  
tal, default 0755 if this field is empty)",  
      "type": "string"  
    },  
    "tenant_id": {  
      "description": "The tenant ID of the tenant that the SMB share is a part of",  
      "type": "number"  
    }  
  }  
}
```


smb/shares/{id}

Endpoint

/v1/smb/shares/{id}

GET

Retrieve the specified SMB share. Refer to the 'Modify SMB share' method for a description of the returned fields.

Parameters

Name	Description	Required
id	The unique ID of the SMB share	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_share",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",

```

```

    "type": "string"
  },
  "read_only": {
    "description": "Sets the SMB share to read-only",
    "type": "boolean"
  },
  "allow_guest_access": {
    "description": "Allows guest access to this SMB share",
    "type": "boolean"
  },
  "access_based_enumeration_enabled": {
    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
  },
  "default_file_create_mode": {
    "description": "Default POSIX file create mode bits on this SMB share (octal, default 0644 if this field is empty)",
    "type": "string"
  },
  "default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (octal, default 0755 if this field is empty)",
    "type": "string"
  },
  "tenant_id": {
    "description": "The tenant ID of the tenant that the SMB share is a part of",
    "type": "number"
  }
}

```

PUT

Modify an SMB share's options.

Parameters

Name	Description	Required
<code>id</code>	The unique ID of the SMB share	Yes
<code>allow-fs-path-create</code>	Specifies whether the file system path can be created if it does not already exist.	No
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_smb_share",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",
      "type": "string"
    },
    "read_only": {
      "description": "Sets the SMB share to read-only",
      "type": "boolean"
    },
    "allow_guest_access": {
      "description": "Allows guest access to this SMB share",
      "type": "boolean"
    },
    "access_based_enumeration_enabled": {
      "description": "Enable Access-based Enumeration on this SMB share",
      "type": "boolean"
    },
    "default_file_create_mode": {
      "description": "Default POSIX file create mode bits on this SMB share (octal, default 0644 if this field is empty)",
      "type": "string"
    },
    "default_directory_create_mode": {
      "description": "Default POSIX directory create mode bits on this SMB share (octal, default 0755 if this field is empty)",
      "type": "string"
    },
    "tenant_id": {
```

```
    "description": "The tenant ID of the tenant that the SMB share is a part of",
    "type": "number"
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_share",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",
      "type": "string"
    },
    "read_only": {
      "description": "Sets the SMB share to read-only",
      "type": "boolean"
    },
    "allow_guest_access": {
      "description": "Allows guest access to this SMB share",
      "type": "boolean"
    },
    "access_based_enumeration_enabled": {
```

```

    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
  },
  "default_file_create_mode": {
    "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
    "type": "string"
  },
  "default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (oc
tal, default 0755 if this field is empty)",
    "type": "string"
  },
  "tenant_id": {
    "description": "The tenant ID of the tenant that the SMB share is a part of",
    "type": "number"
  }
}
}

```

DELETE

Delete an SMB share. Not undoable.

Parameters

Name	Description	Required
id	The unique ID of the SMB share	Yes
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

smb/shares/

Endpoint

/v2/smb/shares/

GET

List all SMB shares. Refer to the 'Modify SMB Share' method for a description of the returned fields.

Parameters

Name	Description	Required
<code>populate-trustee-names</code>	Populate trustee names in the response. By default, trustee names are not returned.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "description": "api_smb_share_v2",
    "type": "object",
    "properties": {
      "id": {
        "description": "The unique ID of the SMB share",
        "type": "string"
      },
      "share_name": {
        "description": "The SMB share name",
        "type": "string"
      },
      "fs_path": {
        "description": "The filesystem path to SMB share",
        "type": "string"
      }
    }
  }
}
```

```

},
"description": {
  "description": "Description of this SMB share",
  "type": "string"
},
"permissions": {
  "type": "array",
  "items": {
    "description": "The access control list (ACL) for this SMB share",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
      },
      "trustee": {
        "description": "User/group to apply the permissions entry to",
        "type": "object",
        "properties": {
          "domain": {
            "type": "string",
            "enum": [
              "LOCAL",
              "API_NULL_DOMAIN",
              "WORLD",
              "POSIX_USER",
              "POSIX_GROUP",
              "ACTIVE_DIRECTORY",
              "API_INVALID_DOMAIN",
              "API_RESERVED_DOMAIN",
              "API_INTERNAL_DOMAIN",
              "API_OPERATOR_DOMAIN",
              "API_QUMULO_SUPPORT_DOMAIN",
              "API_CREATOR_DOMAIN"
            ],
            "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN"
          }
        }
      }
    }
  }
}

```

```

VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  }
},
"rights": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ_DATA",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
      "DELETE",
      "EXECUTE",
      "MODIFY",
      "EXTEND",
      "DELETE_CHILD",
      "SYNCHRONIZE",
      "READ",

```



```

        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"network_permissions": {
    "type": "array",
    "items": {
        "description": "The network access control list (ACL) for this SMB share. If not specified, the default is to allow any host.",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "ALLOWED",
                    "DENIED"
                ],
                "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
            },
            "address_ranges": {
                "type": "array",
                "items": {
                    "description": "IP address ranges to apply permissions to. Empty means all hosts.",
                    "type": "string"
                }
            },
            "rights": {
                "type": "array",
                "items": {

```

```

        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE",
            "READ",
            "WRITE",
            "CHANGE_PERMISSIONS"
        ],
        "description": "Rights pertaining to the permissions entry:\n * `CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"access_based_enumeration_enabled": {
    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
},
"default_file_create_mode": {
    "description": "Default POSIX file create mode bits on this SMB share (octal, default 0644 if this field is empty)",
    "type": "string"
},
"default_directory_create_mode": {

```

```

    "description": "Default POSIX directory create mode bits on this SMB share
(octal, default 0755 if this field is empty)",
    "type": "string"
  },
  "bytes_per_sector": {
    "description": "SMB bytes per sector reported to clients. We do not support
values other than 512. If specified for put or patch, this must be 512.",
    "type": "string"
  },
  "require_encryption": {
    "description": "Require all traffic to this share to be encrypted. Clients w
ithout encryption capabilities will not be able to connect. Default is false if thi
s field is empty.",
    "type": "boolean"
  },
  "tenant_id": {
    "description": "The tenant ID of the tenant that the SMB share is a part o
f",
    "type": "number"
  }
}

```

POST

Add an SMB share with given options.

Parameters

Name	Description	Required
<code>allow-fs-path-create</code>	Specifies whether the file system path can be created if it does not already exist.	No

Request

Schema

```

{
  "description": "api_smb_share_post_v2",
  "type": "object",
  "properties": {
    "share_name": {
      "description": "The SMB share name",

```

```

    "type": "string"
  },
  "fs_path": {
    "description": "The filesystem path to SMB share",
    "type": "string"
  },
  "description": {
    "description": "Description of this SMB share",
    "type": "string"
  },
  "permissions": {
    "type": "array",
    "items": {
      "description": "The access control list (ACL) for this SMB share",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "ALLOWED",
            "DENIED"
          ],
          "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
        },
        "trustee": {
          "description": "User/group to apply the permissions entry to",
          "type": "object",
          "properties": {
            "domain": {
              "type": "string",
              "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",
                "API_INVALID_DOMAIN",
                "API_RESERVED_DOMAIN",
                "API_INTERNAL_DOMAIN",
                "API_OPERATOR_DOMAIN",
                "API_QUMULO_SUPPORT_DOMAIN",
                "API_CREATOR_DOMAIN"
              ]
            }
          }
        }
      }
    }
  }
}

```

```

        "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",

```

```

        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"network_permissions": {
    "type": "array",
    "items": {
        "description": "The network access control list (ACL) for this SMB share. If not specified, the default is to allow any host.",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "ALLOWED",
                    "DENIED"
                ]
            },
            "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
        },
        "address_ranges": {
            "type": "array",
            "items": {
                "description": "IP address ranges to apply permissions to. Empty means all hosts.",
                "type": "string"
            }
        }
    }
}

```

```

    }
  },
  "rights": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ_DATA",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
      ],
      "description": "Rights pertaining to the permissions entry:\n * `CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
  }
},
  "access_based_enumeration_enabled": {
    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
  },
  "default_file_create_mode": {

```

```

    "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
    "type": "string"
  },
  "default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (oc
tal, default 0755 if this field is empty)",
    "type": "string"
  },
  "bytes_per_sector": {
    "description": "SMB bytes per sector reported to clients. We do not support va
lues other than 512. If specified, this must be 512.",
    "type": "string"
  },
  "require_encryption": {
    "description": "Require all traffic to this share to be encrypted. Clients wit
hout encryption capabilities will not be able to connect. Default is false if this f
ield is empty.",
    "type": "boolean"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_smb_share_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    }
  },
}

```



```

"fs_path": {
  "description": "The filesystem path to SMB share",
  "type": "string"
},
"description": {
  "description": "Description of this SMB share",
  "type": "string"
},
"permissions": {
  "type": "array",
  "items": {
    "description": "The access control list (ACL) for this SMB share",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
      },
      "trustee": {
        "description": "User/group to apply the permissions entry to",
        "type": "object",
        "properties": {
          "domain": {
            "type": "string",
            "enum": [
              "LOCAL",
              "API_NULL_DOMAIN",
              "WORLD",
              "POSIX_USER",
              "POSIX_GROUP",
              "ACTIVE_DIRECTORY",
              "API_INVALID_DOMAIN",
              "API_RESERVED_DOMAIN",
              "API_INTERNAL_DOMAIN",
              "API_OPERATOR_DOMAIN",
              "API_QUMULO_SUPPORT_DOMAIN",
              "API_CREATOR_DOMAIN"
            ],
            "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN

```

```

TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",

```

```

        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"network_permissions": {
    "type": "array",
    "items": {
        "description": "The network access control list (ACL) for this SMB share. I
f not specified, the default is to allow any host.",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "ALLOWED",
                    "DENIED"
                ],
            },
            "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLO
WED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The p
ermissions entry rights are denied to the trustee"
        },
        "address_ranges": {
            "type": "array",
            "items": {
                "description": "IP address ranges to apply permissions to. Empty mean
s all hosts.",
                "type": "string"
            }
        }
    },
}

```

```

    "rights": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "READ_DATA",
          "READ_EA",
          "READ_ATTR",
          "READ_ACL",
          "WRITE_EA",
          "WRITE_ATTR",
          "WRITE_ACL",
          "CHANGE_OWNER",
          "WRITE_GROUP",
          "DELETE",
          "EXECUTE",
          "MODIFY",
          "EXTEND",
          "DELETE_CHILD",
          "SYNCHRONIZE",
          "READ",
          "WRITE",
          "CHANGE_PERMISSIONS"
        ],
        "description": "Rights pertaining to the permissions entry:\n * `CHANG\nE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio\nns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d\nirectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces\ns,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE\nAD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`\n- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ\nE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A\nCL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende\n d attribute write access,\n * `WRITE_GROUP` - Group write access"
      },
      "description": "Rights pertaining to the permissions entry:\n * `CHANG\nE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio\nns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d\nirectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces\ns,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE\nAD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`\n- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ\nE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A\nCL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende\n d attribute write access,\n * `WRITE_GROUP` - Group write access"
    },
    "access_based_enumeration_enabled": {
      "description": "Enable Access-based Enumeration on this SMB share",
      "type": "boolean"
    },
    "default_file_create_mode": {
      "description": "Default POSIX file create mode bits on this SMB share (octal,\ndefault 0644 if this field is empty)",

```

```

    "type": "string"
  },
  "default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (octal, default 0755 if this field is empty)",
    "type": "string"
  },
  "bytes_per_sector": {
    "description": "SMB bytes per sector reported to clients. We do not support values other than 512. If specified for put or patch, this must be 512.",
    "type": "string"
  },
  "require_encryption": {
    "description": "Require all traffic to this share to be encrypted. Clients without encryption capabilities will not be able to connect. Default is false if this field is empty.",
    "type": "boolean"
  },
  "tenant_id": {
    "description": "The tenant ID of the tenant that the SMB share is a part of",
    "type": "number"
  }
}
}

```

smb/shares/{ref}

Endpoint

/v2/smb/shares/{ref}

GET

Retrieve the specified SMB share. Refer to the 'Modify SMB Share' method for a description of the returned fields.

Parameters

Name	Description	Required
ref	A unique identifier of the SMB share, either share ID or name	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_share_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",

```

```

    "type": "string"
  },
  "permissions": {
    "type": "array",
    "items": {
      "description": "The access control list (ACL) for this SMB share",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "ALLOWED",
            "DENIED"
          ],
          "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
        },
        "trustee": {
          "description": "User/group to apply the permissions entry to",
          "type": "object",
          "properties": {
            "domain": {
              "type": "string",
              "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",
                "API_INVALID_DOMAIN",
                "API_RESERVED_DOMAIN",
                "API_INTERNAL_DOMAIN",
                "API_OPERATOR_DOMAIN",
                "API_QUMULO_SUPPORT_DOMAIN",
                "API_CREATOR_DOMAIN"
              ],
              "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
            }
          }
        }
      }
    }
  },

```

```

    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  },
  "rights": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ_DATA",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
      ]
    }
  },

```



```

        "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
  }
},
"network_permissions": {
  "type": "array",
  "items": {
    "description": "The network access control list (ACL) for this SMB share. I
f not specified, the default is to allow any host.",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLO
WED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The p
ermissions entry rights are denied to the trustee"
      },
      "address_ranges": {
        "type": "array",
        "items": {
          "description": "IP address ranges to apply permissions to. Empty mean
s all hosts.",
          "type": "string"
        }
      },
      "rights": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "READ_DATA",

```

```

        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
}
},
"access_based_enumeration_enabled": {
    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
},
"default_file_create_mode": {
    "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
    "type": "string"
},
"default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (oc
tal, default 0755 if this field is empty)",
    "type": "string"
}

```

```

    },
    "bytes_per_sector": {
      "description": "SMB bytes per sector reported to clients. We do not support values other than 512. If specified for put or patch, this must be 512.",
      "type": "string"
    },
    "require_encryption": {
      "description": "Require all traffic to this share to be encrypted. Clients without encryption capabilities will not be able to connect. Default is false if this field is empty.",
      "type": "boolean"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the SMB share is a part of",
      "type": "number"
    }
  }
}

```

PUT

Modify an SMB share's options.

Parameters

Name	Description	Required
ref	A unique identifier of the SMB share, either share ID or name	Yes
allow-fs-path-create	Specifies whether the file system path can be created if it does not already exist.	No
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_smb_share_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    }
  }
}

```

```

},
"share_name": {
  "description": "The SMB share name",
  "type": "string"
},
"fs_path": {
  "description": "The filesystem path to SMB share",
  "type": "string"
},
"description": {
  "description": "Description of this SMB share",
  "type": "string"
},
"permissions": {
  "type": "array",
  "items": {
    "description": "The access control list (ACL) for this SMB share",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
      },
      "trustee": {
        "description": "User/group to apply the permissions entry to",
        "type": "object",
        "properties": {
          "domain": {
            "type": "string",
            "enum": [
              "LOCAL",
              "API_NULL_DOMAIN",
              "WORLD",
              "POSIX_USER",
              "POSIX_GROUP",
              "ACTIVE_DIRECTORY",
              "API_INVALID_DOMAIN",
              "API_RESERVED_DOMAIN",
              "API_INTERNAL_DOMAIN",
              "API_OPERATOR_DOMAIN",
            ]
          }
        }
      }
    }
  }
}

```

```

        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",

```

```

        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
}
},
"network_permissions": {
    "type": "array",
    "items": {
        "description": "The network access control list (ACL) for this SMB share. I
f not specified, the default is to allow any host.",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "ALLOWED",
                    "DENIED"
                ],
                "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLO
WED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The p
ermissions entry rights are denied to the trustee"
            },
            "address_ranges": {
                "type": "array",
                "items": {

```

```

        "description": "IP address ranges to apply permissions to. Empty means all hosts.",
        "type": "string"
    },
    "rights": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "READ_DATA",
                "READ_EA",
                "READ_ATTR",
                "READ_ACL",
                "WRITE_EA",
                "WRITE_ATTR",
                "WRITE_ACL",
                "CHANGE_OWNER",
                "WRITE_GROUP",
                "DELETE",
                "EXECUTE",
                "MODIFY",
                "EXTEND",
                "DELETE_CHILD",
                "SYNCHRONIZE",
                "READ",
                "WRITE",
                "CHANGE_PERMISSIONS"
            ]
        },
        "description": "Rights pertaining to the permissions entry:\n * `CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
},
    "access_based_enumeration_enabled": {
        "description": "Enable Access-based Enumeration on this SMB share",

```

```

    "type": "boolean"
  },
  "default_file_create_mode": {
    "description": "Default POSIX file create mode bits on this SMB share (octal, default 0644 if this field is empty)",
    "type": "string"
  },
  "default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (octal, default 0755 if this field is empty)",
    "type": "string"
  },
  "bytes_per_sector": {
    "description": "SMB bytes per sector reported to clients. We do not support values other than 512. If specified for put or patch, this must be 512.",
    "type": "string"
  },
  "require_encryption": {
    "description": "Require all traffic to this share to be encrypted. Clients without encryption capabilities will not be able to connect. Default is false if this field is empty.",
    "type": "boolean"
  },
  "tenant_id": {
    "description": "The tenant ID of the tenant that the SMB share is a part of",
    "type": "number"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_smb_share_v2",
  "type": "object",
  "properties": {
    "id": {

```



```

    "description": "The unique ID of the SMB share",
    "type": "string"
  },
  "share_name": {
    "description": "The SMB share name",
    "type": "string"
  },
  "fs_path": {
    "description": "The filesystem path to SMB share",
    "type": "string"
  },
  "description": {
    "description": "Description of this SMB share",
    "type": "string"
  },
  "permissions": {
    "type": "array",
    "items": {
      "description": "The access control list (ACL) for this SMB share",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "ALLOWED",
            "DENIED"
          ],
          "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
        },
        "trustee": {
          "description": "User/group to apply the permissions entry to",
          "type": "object",
          "properties": {
            "domain": {
              "type": "string",
              "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",
                "API_INVALID_DOMAIN",
                "API_RESERVED_DOMAIN",

```

```

        "API_INTERNAL_DOMAIN",
        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",

```

```

        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"network_permissions": {
    "type": "array",
    "items": {
        "description": "The network access control list (ACL) for this SMB share. If not specified, the default is to allow any host.",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "ALLOWED",
                    "DENIED"
                ],
            },
            "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
        },
        "address_ranges": {

```

```

        "type": "array",
        "items": {
            "description": "IP address ranges to apply permissions to. Empty means all hosts.",
            "type": "string"
        }
    },
    "rights": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "READ_DATA",
                "READ_EA",
                "READ_ATTR",
                "READ_ACL",
                "WRITE_EA",
                "WRITE_ATTR",
                "WRITE_ACL",
                "CHANGE_OWNER",
                "WRITE_GROUP",
                "DELETE",
                "EXECUTE",
                "MODIFY",
                "EXTEND",
                "DELETE_CHILD",
                "SYNCHRONIZE",
                "READ",
                "WRITE",
                "CHANGE_PERMISSIONS"
            ],
            "description": "Rights pertaining to the permissions entry:\n * `CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
        }
    }
}
},
},
},

```

```

"access_based_enumeration_enabled": {
  "description": "Enable Access-based Enumeration on this SMB share",
  "type": "boolean"
},
"default_file_create_mode": {
  "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
  "type": "string"
},
"default_directory_create_mode": {
  "description": "Default POSIX directory create mode bits on this SMB share (oc
tal, default 0755 if this field is empty)",
  "type": "string"
},
"bytes_per_sector": {
  "description": "SMB bytes per sector reported to clients. We do not support va
lues other than 512. If specified for put or patch, this must be 512.",
  "type": "string"
},
"require_encryption": {
  "description": "Require all traffic to this share to be encrypted. Clients wit
hout encryption capabilities will not be able to connect. Default is false if this f
ield is empty.",
  "type": "boolean"
},
"tenant_id": {
  "description": "The tenant ID of the tenant that the SMB share is a part of",
  "type": "number"
}
}
}

```

DELETE

Delete an SMB share. Not undoable.

Parameters

Name	Description	Required
ref	A unique identifier of the SMB share, either share ID or name	Yes
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

Modify select fields in an SMB share.

Parameters

Name	Description	Required
ref	A unique identifier of the SMB share, either share ID or name	Yes
allow-fs-path-create	Specifies whether the file system path can be created if it does not already exist.	No
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_smb_share_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",
      "type": "string"
    }
  }
}
```

```

},
"permissions": {
  "type": "array",
  "items": {
    "description": "The access control list (ACL) for this SMB share",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
      },
      "trustee": {
        "description": "User/group to apply the permissions entry to",
        "type": "object",
        "properties": {
          "domain": {
            "type": "string",
            "enum": [
              "LOCAL",
              "API_NULL_DOMAIN",
              "WORLD",
              "POSIX_USER",
              "POSIX_GROUP",
              "ACTIVE_DIRECTORY",
              "API_INVALID_DOMAIN",
              "API_RESERVED_DOMAIN",
              "API_INTERNAL_DOMAIN",
              "API_OPERATOR_DOMAIN",
              "API_QUMULO_SUPPORT_DOMAIN",
              "API_CREATOR_DOMAIN"
            ],
            "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
          },
          "auth_id": {

```

```

        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE",
            "READ",
            "WRITE",
            "CHANGE_PERMISSIONS"
        ]
    },
    "description": "Rights pertaining to the permissions entry:\n * `CHANG

```


E_OWNER` - Owner write access,\n \* `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n \* `DELETE` - Delete access,\n \* `DELETE_CHILD` - Delete from directory access,\n \* `EXECUTE` - Execute access,\n \* `EXTEND` - File extension access,\n \* `MODIFY` - File modification access,\n \* `READ` - Read access rights,\n \* `READ_ACL` - ACL read access,\n \* `READ_ATTR` - Attribute read access,\n \* `READ_DATA` - File read access,\n \* `READ_EA` - Extended attribute read access,\n \* `SYNCHRONIZE` - File synchronize access,\n \* `WRITE` - Write access rights,\n \* `WRITE_ACL` - ACL write access,\n \* `WRITE_ATTR` - Attribute write access,\n \* `WRITE_EA` - Extended attribute write access,\n \* `WRITE_GROUP` - Group write access"

```

    }
  }
}
},
"network_permissions": {
  "type": "array",
  "items": {
    "description": "The network access control list (ACL) for this SMB share. If not specified, the default is to allow any host.",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
      },
      "address_ranges": {
        "type": "array",
        "items": {
          "description": "IP address ranges to apply permissions to. Empty means all hosts.",
          "type": "string"
        }
      },
      "rights": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "READ_DATA",
            "READ_EA",

```

```

        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
}
},
"access_based_enumeration_enabled": {
    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
},
"default_file_create_mode": {
    "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
    "type": "string"
},
"default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (oc
tal, default 0755 if this field is empty)",
    "type": "string"
},
},

```

```

    "bytes_per_sector": {
      "description": "SMB bytes per sector reported to clients. We do not support values other than 512. If specified for put or patch, this must be 512.",
      "type": "string"
    },
    "require_encryption": {
      "description": "Require all traffic to this share to be encrypted. Clients without encryption capabilities will not be able to connect. Default is false if this field is empty.",
      "type": "boolean"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the SMB share is a part of",
      "type": "number"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_smb_share_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {

```

```

    "description": "Description of this SMB share",
    "type": "string"
  },
  "permissions": {
    "type": "array",
    "items": {
      "description": "The access control list (ACL) for this SMB share",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "ALLOWED",
            "DENIED"
          ],
          "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
        },
        "trustee": {
          "description": "User/group to apply the permissions entry to",
          "type": "object",
          "properties": {
            "domain": {
              "type": "string",
              "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",
                "API_INVALID_DOMAIN",
                "API_RESERVED_DOMAIN",
                "API_INTERNAL_DOMAIN",
                "API_OPERATOR_DOMAIN",
                "API_QUMULO_SUPPORT_DOMAIN",
                "API_CREATOR_DOMAIN"
              ],
              "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
            }
          }
        }
      }
    }
  }
}

```

```

    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE",
            "READ",
            "WRITE",
            "CHANGE_PERMISSIONS"
        ]
    }
}

```

```

    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
  }
},
"network_permissions": {
  "type": "array",
  "items": {
    "description": "The network access control list (ACL) for this SMB share. I
f not specified, the default is to allow any host.",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLO
WED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The p
ermissions entry rights are denied to the trustee"
      },
      "address_ranges": {
        "type": "array",
        "items": {
          "description": "IP address ranges to apply permissions to. Empty mean
s all hosts.",
          "type": "string"
        }
      },
      "rights": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [

```

```

        "READ_DATA",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"access_based_enumeration_enabled": {
    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
},
"default_file_create_mode": {
    "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
    "type": "string"
},
"default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (oc
tal, default 0755 if this field is empty)",

```

```

    "type": "string"
  },
  "bytes_per_sector": {
    "description": "SMB bytes per sector reported to clients. We do not support va
lues other than 512. If specified for put or patch, this must be 512.",
    "type": "string"
  },
  "require_encryption": {
    "description": "Require all traffic to this share to be encrypted. Clients wit
hout encryption capabilities will not be able to connect. Default is false if this f
ield is empty.",
    "type": "boolean"
  },
  "tenant_id": {
    "description": "The tenant ID of the tenant that the SMB share is a part of",
    "type": "number"
  }
}

```


smb/shares/

Endpoint

/v3/smb/shares/

GET

[preview] List all SMB shares. Refer to the 'Modify SMB Share' method for a description of the returned fields.

Parameters

Name	Description	Required
populate-trustee-names	Populate trustee names in the response. By default, trustee names are not returned.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_shares_v3",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of SMB shares",
        "type": "object",
        "properties": {
          "id": {
            "description": "The unique ID of the SMB share",
            "type": "string"
          },
          "share_name": {
            "description": "The SMB share name",
            "type": "string"
          }
        }
      }
    }
  }
}
```

```

    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the SMB share is a part of",
      "type": "number"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",
      "type": "string"
    },
    "permissions": {
      "type": "array",
      "items": {
        "description": "The access control list (ACL) for this SMB share",
        "type": "object",
        "properties": {
          "type": {
            "type": "string",
            "enum": [
              "ALLOWED",
              "DENIED"
            ],
            "description": "Type of permissions entry (ALLOWED or DENIED):\n
* `ALLOWED` - The permissions entry rights are allowed to the trustee,\n
* `DENIED` - The permissions entry rights are denied to the trustee"
          },
          "trustee": {
            "description": "User/group to apply the permissions entry to",
            "type": "object",
            "properties": {
              "domain": {
                "type": "string",
                "enum": [
                  "LOCAL",
                  "API_NULL_DOMAIN",
                  "WORLD",
                  "POSIX_USER",
                  "POSIX_GROUP",
                  "ACTIVE_DIRECTORY",
                  "API_INVALID_DOMAIN",
                  "API_RESERVED_DOMAIN",
                  "API_INTERNAL_DOMAIN",

```

```

        "API_OPERATOR_DOMAIN",
        "API_QUMULO_SUPPORT_DOMAIN",
        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
},
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",

```

```

        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n *
`CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change per
missions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete
from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extensio
n access,\n * `MODIFY` - File modification access,\n * `READ` - Read access right
s,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `R
EAD_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `S
YNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRIT
E_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_E
A` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"network_permissions": {
    "type": "array",
    "items": {
        "description": "The network access control list (ACL) for this SMB sha
re. If not specified, the default is to allow any host.",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "ALLOWED",
                    "DENIED"
                ],
            },
            "description": "Type of permissions entry (ALLOWED or DENIED):\n
* `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED`
- The permissions entry rights are denied to the trustee"
        },
        "address_ranges": {
            "type": "array",

```

```

        "items": {
            "description": "IP address ranges to apply permissions to. Empty means all hosts.",
            "type": "string"
        }
    },
    "rights": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "READ_DATA",
                "READ_EA",
                "READ_ATTR",
                "READ_ACL",
                "WRITE_EA",
                "WRITE_ATTR",
                "WRITE_ACL",
                "CHANGE_OWNER",
                "WRITE_GROUP",
                "DELETE",
                "EXECUTE",
                "MODIFY",
                "EXTEND",
                "DELETE_CHILD",
                "SYNCHRONIZE",
                "READ",
                "WRITE",
                "CHANGE_PERMISSIONS"
            ],
            "description": "Rights pertaining to the permissions entry:\n *
`CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change per
missions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete
from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extensio
n access,\n * `MODIFY` - File modification access,\n * `READ` - Read access right
s,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `R
EAD_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `S
YNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRIT
E_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_E
A` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
        }
    }
}
}
},
"access_based_enumeration_enabled": {

```

```

        "description": "Enable Access-based Enumeration on this SMB share",
        "type": "boolean"
    },
    "default_file_create_mode": {
        "description": "Default POSIX file create mode bits on this SMB share (octal, default 0644 if this field is empty)",
        "type": "string"
    },
    "default_directory_create_mode": {
        "description": "Default POSIX directory create mode bits on this SMB share (octal, default 0755 if this field is empty)",
        "type": "string"
    },
    "require_encryption": {
        "description": "Require all traffic to this share to be encrypted. Clients without encryption capabilities will not be able to connect. Default is false if this field is empty.",
        "type": "boolean"
    },
    "allow_fs_path_create": {
        "description": "If true, the server will create the file system path for the share if it does not already exist. If false, the file system path must already exist. Default is false if this field is empty.",
        "type": "boolean"
    },
    "expand_fs_path_variables": {
        "description": "If true, the server will expand %U variables in the file system path to username. Default is false if this field is empty.",
        "type": "boolean"
    },
    "offline_files_caching_mode": {
        "type": "string",
        "enum": [
            "NO_CACHING",
            "MANUAL_CACHING",
            "AUTOMATIC_CACHING"
        ],
        "description": "Offline-files caching mode advertised to SMB clients: \\\"no_caching\\\" (no caching, the default), \\\"manual_caching\\\" (cache files the user designates as offline-available), or \\\"automatic_caching\\\" (cache files as they are opened).:\\n * `AUTOMATIC_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_AUTOMATIC_CACHING,\\n * `MANUAL_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_MANUAL_CACHING,\\n * `NO_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_NO_CACHING"
    }
}
}

```

POST

[preview] Add an SMB share with given options.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_smb_share_post_v3",
  "type": "object",
  "properties": {
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the SMB share is a part of",
      "type": "number"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",
      "type": "string"
    },
    "permissions": {
      "type": "array",
      "items": {
        "description": "The access control list (ACL) for this SMB share",
        "type": "object",
        "properties": {
          "type": {
            "type": "string",
            "enum": [
              "ALLOWED",

```

```

        "DENIED"
    ],
    "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
},
"trustee": {
    "description": "User/group to apply the permissions entry to",
    "type": "object",
    "properties": {
        "domain": {
            "type": "string",
            "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",
                "API_INVALID_DOMAIN",
                "API_RESERVED_DOMAIN",
                "API_INTERNAL_DOMAIN",
                "API_OPERATOR_DOMAIN",
                "API_QUMULO_SUPPORT_DOMAIN",
                "API_CREATOR_DOMAIN"
            ],
            "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
        },
        "auth_id": {
            "description": "auth_id",
            "type": "string"
        },
        "uid": {
            "description": "uid",
            "type": "number"
        },
        "gid": {
            "description": "gid",
            "type": "number"
        }
    }
},

```



```

        "sid": {
            "description": "sid",
            "type": "string"
        },
        "name": {
            "description": "name",
            "type": "string"
        }
    },
    "rights": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "READ_DATA",
                "READ_EA",
                "READ_ATTR",
                "READ_ACL",
                "WRITE_EA",
                "WRITE_ATTR",
                "WRITE_ACL",
                "CHANGE_OWNER",
                "WRITE_GROUP",
                "DELETE",
                "EXECUTE",
                "MODIFY",
                "EXTEND",
                "DELETE_CHILD",
                "SYNCHRONIZE",
                "READ",
                "WRITE",
                "CHANGE_PERMISSIONS"
            ],
            "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
        }
    }
}

```

```

    }
  },
  "network_permissions": {
    "type": "array",
    "items": {
      "description": "The network access control list (ACL) for this SMB share. If not specified, the default is to allow any host.",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "ALLOWED",
            "DENIED"
          ],
          "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
        },
        "address_ranges": {
          "type": "array",
          "items": {
            "description": "IP address ranges to apply permissions to. Empty means all hosts.",
            "type": "string"
          }
        }
      }
    },
    "rights": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "READ_DATA",
          "READ_EA",
          "READ_ATTR",
          "READ_ACL",
          "WRITE_EA",
          "WRITE_ATTR",
          "WRITE_ACL",
          "CHANGE_OWNER",
          "WRITE_GROUP",
          "DELETE",
          "EXECUTE",
          "MODIFY",
          "EXTEND",

```



```

    },
    "expand_fs_path_variables": {
        "description": "If true, the server will expand %U variables in the share file system path to username. Default is false if this field is empty.",
        "type": "boolean"
    },
    "offline_files_caching_mode": {
        "type": "string",
        "enum": [
            "NO_CACHING",
            "MANUAL_CACHING",
            "AUTOMATIC_CACHING"
        ],
        "description": "Offline-files caching mode advertised to SMB clients: \"no_caching\" (no caching, the default), \"manual_caching\" (cache files the user designates as offline-available), or \"automatic_caching\" (cache files as they are opened).:\n * `AUTOMATIC_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_AUTOMATIC_CACHING,\n * `MANUAL_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_MANUAL_CACHING,\n * `NO_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_NO_CACHING"
    }
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_smb_share_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    }
  },
}

```

```

"tenant_id": {
  "description": "The tenant ID of the tenant that the SMB share is a part of",
  "type": "number"
},
"fs_path": {
  "description": "The filesystem path to SMB share",
  "type": "string"
},
"description": {
  "description": "Description of this SMB share",
  "type": "string"
},
"permissions": {
  "type": "array",
  "items": {
    "description": "The access control list (ACL) for this SMB share",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
      },
      "trustee": {
        "description": "User/group to apply the permissions entry to",
        "type": "object",
        "properties": {
          "domain": {
            "type": "string",
            "enum": [
              "LOCAL",
              "API_NULL_DOMAIN",
              "WORLD",
              "POSIX_USER",
              "POSIX_GROUP",
              "ACTIVE_DIRECTORY",
              "API_INVALID_DOMAIN",
              "API_RESERVED_DOMAIN",
              "API_INTERNAL_DOMAIN",
              "API_OPERATOR_DOMAIN",
              "API_QUMULO_SUPPORT_DOMAIN",
            ]
          }
        }
      }
    }
  }
}

```

```

        "API_CREATOR_DOMAIN"
    ],
    "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",

```

```

        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"network_permissions": {
    "type": "array",
    "items": {
        "description": "The network access control list (ACL) for this SMB share. If not specified, the default is to allow any host.",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "ALLOWED",
                    "DENIED"
                ],
                "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
            },
            "address_ranges": {
                "type": "array",
                "items": {
                    "description": "IP address ranges to apply permissions to. Empty mean

```

```

s all hosts.",
    "type": "string"
  }
},
"rights": {
  "type": "array",
  "items": {
    "type": "string",
    "enum": [
      "READ_DATA",
      "READ_EA",
      "READ_ATTR",
      "READ_ACL",
      "WRITE_EA",
      "WRITE_ATTR",
      "WRITE_ACL",
      "CHANGE_OWNER",
      "WRITE_GROUP",
      "DELETE",
      "EXECUTE",
      "MODIFY",
      "EXTEND",
      "DELETE_CHILD",
      "SYNCHRONIZE",
      "READ",
      "WRITE",
      "CHANGE_PERMISSIONS"
    ]
  },
  "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
}
}
}
},
"access_based_enumeration_enabled": {
  "description": "Enable Access-based Enumeration on this SMB share",
  "type": "boolean"
}

```



```

    },
    "default_file_create_mode": {
        "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
        "type": "string"
    },
    "default_directory_create_mode": {
        "description": "Default POSIX directory create mode bits on this SMB share (oc
tal, default 0755 if this field is empty)",
        "type": "string"
    },
    "require_encryption": {
        "description": "Require all traffic to this share to be encrypted. Clients wit
hout encryption capabilities will not be able to connect. Default is false if this f
ield is empty.",
        "type": "boolean"
    },
    "allow_fs_path_create": {
        "description": "If true, the server will create the file system path for the s
hare if it does not already exist. If false, the file system path must already exis
t. Default is false if this field is empty.",
        "type": "boolean"
    },
    "expand_fs_path_variables": {
        "description": "If true, the server will expand %U variables in the file syste
m path to username. Default is false if this field is empty.",
        "type": "boolean"
    },
    "offline_files_caching_mode": {
        "type": "string",
        "enum": [
            "NO_CACHING",
            "MANUAL_CACHING",
            "AUTOMATIC_CACHING"
        ],
        "description": "Offline-files caching mode advertised to SMB clients: \"no_cac
hing\" (no caching, the default), \"manual_caching\" (cache files the user designate
s as offline-available), or \"automatic_caching\" (cache files as they are opene
d).:\n * `AUTOMATIC_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_AUTOMATIC_CACHING,\n
* `MANUAL_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_MANUAL_CACHING,\n * `NO_CACHIN
G` - SMB_OFFLINE_FILES_CACHING_MODE_NO_CACHING"
    }
}
}

```

smb/shares/{share_id}

Endpoint

/v3/smb/shares/{share_id}

GET

[preview] Retrieve the specified SMB share. Refer to the 'Modify SMB Share' method for a description of the returned fields.

Parameters

Name	Description	Required
share_id	The unique ID of the SMB share.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_share_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the SMB share is a part of",
      "type": "number"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",

```

```

    "type": "string"
  },
  "description": {
    "description": "Description of this SMB share",
    "type": "string"
  },
  "permissions": {
    "type": "array",
    "items": {
      "description": "The access control list (ACL) for this SMB share",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "ALLOWED",
            "DENIED"
          ],
          "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
        },
        "trustee": {
          "description": "User/group to apply the permissions entry to",
          "type": "object",
          "properties": {
            "domain": {
              "type": "string",
              "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",
                "API_INVALID_DOMAIN",
                "API_RESERVED_DOMAIN",
                "API_INTERNAL_DOMAIN",
                "API_OPERATOR_DOMAIN",
                "API_QUMULO_SUPPORT_DOMAIN",
                "API_CREATOR_DOMAIN"
              ],
              "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN"
            }
          }
        }
      }
    }
  }
}

```

```

O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
      "description": "auth_id",
      "type": "string"
    },
    "uid": {
      "description": "uid",
      "type": "number"
    },
    "gid": {
      "description": "gid",
      "type": "number"
    },
    "sid": {
      "description": "sid",
      "type": "string"
    },
    "name": {
      "description": "name",
      "type": "string"
    }
  },
  "rights": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ_DATA",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",

```

```

        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
}
},
"network_permissions": {
    "type": "array",
    "items": {
        "description": "The network access control list (ACL) for this SMB share. I
f not specified, the default is to allow any host.",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "ALLOWED",
                    "DENIED"
                ],
                "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLO
WED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The p
ermissions entry rights are denied to the trustee"
            },
            "address_ranges": {
                "type": "array",
                "items": {
                    "description": "IP address ranges to apply permissions to. Empty mean
s all hosts.",
                    "type": "string"
                }
            },
            "rights": {
                "type": "array",

```

```

    "items": {
      "type": "string",
      "enum": [
        "READ_DATA",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
      ],
      "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
  }
}
},
"access_based_enumeration_enabled": {
  "description": "Enable Access-based Enumeration on this SMB share",
  "type": "boolean"
},
"default_file_create_mode": {
  "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
  "type": "string"
},

```

```

"default_directory_create_mode": {
  "description": "Default POSIX directory create mode bits on this SMB share (octal, default 0755 if this field is empty)",
  "type": "string"
},
"require_encryption": {
  "description": "Require all traffic to this share to be encrypted. Clients without encryption capabilities will not be able to connect. Default is false if this field is empty.",
  "type": "boolean"
},
"allow_fs_path_create": {
  "description": "If true, the server will create the file system path for the share if it does not already exist. If false, the file system path must already exist. Default is false if this field is empty.",
  "type": "boolean"
},
"expand_fs_path_variables": {
  "description": "If true, the server will expand %U variables in the file system path to username. Default is false if this field is empty.",
  "type": "boolean"
},
"offline_files_caching_mode": {
  "type": "string",
  "enum": [
    "NO_CACHING",
    "MANUAL_CACHING",
    "AUTOMATIC_CACHING"
  ],
  "description": "Offline-files caching mode advertised to SMB clients: \"no_caching\" (no caching, the default), \"manual_caching\" (cache files the user designates as offline-available), or \"automatic_caching\" (cache files as they are opened).:\n * `AUTOMATIC_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_AUTOMATIC_CACHING,\n * `MANUAL_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_MANUAL_CACHING,\n * `NO_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_NO_CACHING"
}
}
}

```

PUT

[preview] Modify an SMB share's options.

Parameters

Name	Description	Required
------	-------------	----------

share_id	The unique ID of the SMB share.	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_smb_share_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the SMB share is a part of",
      "type": "number"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",
      "type": "string"
    },
    "permissions": {
      "type": "array",
      "items": {
        "description": "The access control list (ACL) for this SMB share",
        "type": "object",
        "properties": {
          "type": {
            "type": "string",
            "enum": [
              "ALLOWED",
              "DENIED"
            ]
          },
          "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The p
```


permissions entry rights are denied to the trustee"

```
    },
    "trustee": {
      "description": "User/group to apply the permissions entry to",
      "type": "object",
      "properties": {
        "domain": {
          "type": "string",
          "enum": [
            "LOCAL",
            "API_NULL_DOMAIN",
            "WORLD",
            "POSIX_USER",
            "POSIX_GROUP",
            "ACTIVE_DIRECTORY",
            "API_INVALID_DOMAIN",
            "API_RESERVED_DOMAIN",
            "API_INTERNAL_DOMAIN",
            "API_OPERATOR_DOMAIN",
            "API_QUMULO_SUPPORT_DOMAIN",
            "API_CREATOR_DOMAIN"
          ],
          "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR  
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN  
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`  
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL  
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER  
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`  
- POSIX_USER,\n * `WORLD` - WORLD"
        },
        "auth_id": {
          "description": "auth_id",
          "type": "string"
        },
        "uid": {
          "description": "uid",
          "type": "number"
        },
        "gid": {
          "description": "gid",
          "type": "number"
        },
        "sid": {
          "description": "sid",
          "type": "string"
        }
      }
    },
```

```

        "name": {
            "description": "name",
            "type": "string"
        }
    },
    "rights": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "READ_DATA",
                "READ_EA",
                "READ_ATTR",
                "READ_ACL",
                "WRITE_EA",
                "WRITE_ATTR",
                "WRITE_ACL",
                "CHANGE_OWNER",
                "WRITE_GROUP",
                "DELETE",
                "EXECUTE",
                "MODIFY",
                "EXTEND",
                "DELETE_CHILD",
                "SYNCHRONIZE",
                "READ",
                "WRITE",
                "CHANGE_PERMISSIONS"
            ],
            "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
        }
    }
}
},
"network_permissions": {

```

```

"type": "array",
"items": {
  "description": "The network access control list (ACL) for this SMB share. If not specified, the default is to allow any host.",
  "type": "object",
  "properties": {
    "type": {
      "type": "string",
      "enum": [
        "ALLOWED",
        "DENIED"
      ],
      "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
    },
    "address_ranges": {
      "type": "array",
      "items": {
        "description": "IP address ranges to apply permissions to. Empty means all hosts.",
        "type": "string"
      }
    },
    "rights": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "READ_DATA",
          "READ_EA",
          "READ_ATTR",
          "READ_ACL",
          "WRITE_EA",
          "WRITE_ATTR",
          "WRITE_ACL",
          "CHANGE_OWNER",
          "WRITE_GROUP",
          "DELETE",
          "EXECUTE",
          "MODIFY",
          "EXTEND",
          "DELETE_CHILD",
          "SYNCHRONIZE",
          "READ",
          "WRITE",

```

```

        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"access_based_enumeration_enabled": {
    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
},
"default_file_create_mode": {
    "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
    "type": "string"
},
"default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (oc
tal, default 0755 if this field is empty)",
    "type": "string"
},
"require_encryption": {
    "description": "Require all traffic to this share to be encrypted. Clients wit
hout encryption capabilities will not be able to connect. Default is false if this f
ield is empty.",
    "type": "boolean"
},
"allow_fs_path_create": {
    "description": "If true, the server will create the file system path for the s
hare if it does not already exist. If false, the file system path must already exis
t. Default is false if this field is empty.",
    "type": "boolean"
},
"expand_fs_path_variables": {
    "description": "If true, the server will expand %U variables in the file syste
m path to username. Default is false if this field is empty.",

```

```

    "type": "boolean"
  },
  "offline_files_caching_mode": {
    "type": "string",
    "enum": [
      "NO_CACHING",
      "MANUAL_CACHING",
      "AUTOMATIC_CACHING"
    ],
    "description": "Offline-files caching mode advertised to SMB clients: \"no_caching\" (no caching, the default), \"manual_caching\" (cache files the user designates as offline-available), or \"automatic_caching\" (cache files as they are opened).:\n * `AUTOMATIC_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_AUTOMATIC_CACHING,\n * `MANUAL_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_MANUAL_CACHING,\n * `NO_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_NO_CACHING"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_smb_share_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the SMB share is a part of",
      "type": "number"
    }
  }
}

```

```

"fs_path": {
  "description": "The filesystem path to SMB share",
  "type": "string"
},
"description": {
  "description": "Description of this SMB share",
  "type": "string"
},
"permissions": {
  "type": "array",
  "items": {
    "description": "The access control list (ACL) for this SMB share",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
      },
      "trustee": {
        "description": "User/group to apply the permissions entry to",
        "type": "object",
        "properties": {
          "domain": {
            "type": "string",
            "enum": [
              "LOCAL",
              "API_NULL_DOMAIN",
              "WORLD",
              "POSIX_USER",
              "POSIX_GROUP",
              "ACTIVE_DIRECTORY",
              "API_INVALID_DOMAIN",
              "API_RESERVED_DOMAIN",
              "API_INTERNAL_DOMAIN",
              "API_OPERATOR_DOMAIN",
              "API_QUMULO_SUPPORT_DOMAIN",
              "API_CREATOR_DOMAIN"
            ],
            "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN

```

```

TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",

```

```

        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"network_permissions": {
    "type": "array",
    "items": {
        "description": "The network access control list (ACL) for this SMB share. I
f not specified, the default is to allow any host.",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "ALLOWED",
                    "DENIED"
                ],
            },
            "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLO
WED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The p
ermissions entry rights are denied to the trustee"
        },
        "address_ranges": {
            "type": "array",
            "items": {
                "description": "IP address ranges to apply permissions to. Empty mean
s all hosts.",
                "type": "string"
            }
        }
    },
}

```



```

    "rights": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "READ_DATA",
          "READ_EA",
          "READ_ATTR",
          "READ_ACL",
          "WRITE_EA",
          "WRITE_ATTR",
          "WRITE_ACL",
          "CHANGE_OWNER",
          "WRITE_GROUP",
          "DELETE",
          "EXECUTE",
          "MODIFY",
          "EXTEND",
          "DELETE_CHILD",
          "SYNCHRONIZE",
          "READ",
          "WRITE",
          "CHANGE_PERMISSIONS"
        ],
        "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
      }
    }
  },
  "access_based_enumeration_enabled": {
    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
  },
  "default_file_create_mode": {
    "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",

```

```

    "type": "string"
  },
  "default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (octal, default 0755 if this field is empty)",
    "type": "string"
  },
  "require_encryption": {
    "description": "Require all traffic to this share to be encrypted. Clients without encryption capabilities will not be able to connect. Default is false if this field is empty.",
    "type": "boolean"
  },
  "allow_fs_path_create": {
    "description": "If true, the server will create the file system path for the share if it does not already exist. If false, the file system path must already exist. Default is false if this field is empty.",
    "type": "boolean"
  },
  "expand_fs_path_variables": {
    "description": "If true, the server will expand %U variables in the file system path to username. Default is false if this field is empty.",
    "type": "boolean"
  },
  "offline_files_caching_mode": {
    "type": "string",
    "enum": [
      "NO_CACHING",
      "MANUAL_CACHING",
      "AUTOMATIC_CACHING"
    ],
    "description": "Offline-files caching mode advertised to SMB clients: \"no_caching\" (no caching, the default), \"manual_caching\" (cache files the user designates as offline-available), or \"automatic_caching\" (cache files as they are opened).:\n * `AUTOMATIC_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_AUTOMATIC_CACHING,\n * `MANUAL_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_MANUAL_CACHING,\n * `NO_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_NO_CACHING"
  }
}
}

```

DELETE

[preview] Delete an SMB share. Not undoable.

Parameters

Name	Description	Required
<code>share_id</code>	The unique ID of the SMB share.	Yes
<code>If-Match</code>	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

[preview] Modify select fields in an SMB share.

Parameters

Name	Description	Required
<code>share_id</code>	The unique ID of the SMB share.	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_smb_share_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the SMB share is a part of",
```

```

    "type": "number"
  },
  "fs_path": {
    "description": "The filesystem path to SMB share",
    "type": "string"
  },
  "description": {
    "description": "Description of this SMB share",
    "type": "string"
  },
  "permissions": {
    "type": "array",
    "items": {
      "description": "The access control list (ACL) for this SMB share",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "ALLOWED",
            "DENIED"
          ],
          "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
        },
        "trustee": {
          "description": "User/group to apply the permissions entry to",
          "type": "object",
          "properties": {
            "domain": {
              "type": "string",
              "enum": [
                "LOCAL",
                "API_NULL_DOMAIN",
                "WORLD",
                "POSIX_USER",
                "POSIX_GROUP",
                "ACTIVE_DIRECTORY",
                "API_INVALID_DOMAIN",
                "API_RESERVED_DOMAIN",
                "API_INTERNAL_DOMAIN",
                "API_OPERATOR_DOMAIN",
                "API_QUMULO_SUPPORT_DOMAIN",
                "API_CREATOR_DOMAIN"
              ]
            }
          }
        }
      }
    }
  }
}

```

```

        "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTOR
Y,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_IN
TERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN`
- API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMUL
O_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESER
VED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER`
- POSIX_USER,\n * `WORLD` - WORLD"
    },
    "auth_id": {
        "description": "auth_id",
        "type": "string"
    },
    "uid": {
        "description": "uid",
        "type": "number"
    },
    "gid": {
        "description": "gid",
        "type": "number"
    },
    "sid": {
        "description": "sid",
        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",

```

```

        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
},
"network_permissions": {
    "type": "array",
    "items": {
        "description": "The network access control list (ACL) for this SMB share. If not specified, the default is to allow any host.",
        "type": "object",
        "properties": {
            "type": {
                "type": "string",
                "enum": [
                    "ALLOWED",
                    "DENIED"
                ]
            },
            "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
        },
        "address_ranges": {
            "type": "array",
            "items": {
                "description": "IP address ranges to apply permissions to. Empty means all hosts.",
                "type": "string"
            }
        }
    }
}

```

```

    }
  },
  "rights": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ_DATA",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",
        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
      ],
      "description": "Rights pertaining to the permissions entry:\n * `CHANGE_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissions on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from directory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension access,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `READ_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA` - File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZE` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - ACL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extended attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
  }
},
  "access_based_enumeration_enabled": {
    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
  },
  "default_file_create_mode": {

```

```

    "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
    "type": "string"
},
"default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (oc
tal, default 0755 if this field is empty)",
    "type": "string"
},
"require_encryption": {
    "description": "Require all traffic to this share to be encrypted. Clients wit
hout encryption capabilities will not be able to connect. Default is false if this f
ield is empty.",
    "type": "boolean"
},
"allow_fs_path_create": {
    "description": "If true, the server will create the file system path for the s
hare if it does not already exist. If false, the file system path must already exis
t. Default is false if this field is empty.",
    "type": "boolean"
},
"expand_fs_path_variables": {
    "description": "If true, the server will expand %U variables in the file syste
m path to username. Default is false if this field is empty.",
    "type": "boolean"
},
"offline_files_caching_mode": {
    "type": "string",
    "enum": [
        "NO_CACHING",
        "MANUAL_CACHING",
        "AUTOMATIC_CACHING"
    ],
    "description": "Offline-files caching mode advertised to SMB clients: \"no_cac
hing\" (no caching, the default), \"manual_caching\" (cache files the user designate
s as offline-available), or \"automatic_caching\" (cache files as they are opene
d).:\n * `AUTOMATIC_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_AUTOMATIC_CACHING,\n
* `MANUAL_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_MANUAL_CACHING,\n * `NO_CACHIN
G` - SMB_OFFLINE_FILES_CACHING_MODE_NO_CACHING"
}
}
}

```


Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_smb_share_v3",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique ID of the SMB share",
      "type": "string"
    },
    "share_name": {
      "description": "The SMB share name",
      "type": "string"
    },
    "tenant_id": {
      "description": "The tenant ID of the tenant that the SMB share is a part of",
      "type": "number"
    },
    "fs_path": {
      "description": "The filesystem path to SMB share",
      "type": "string"
    },
    "description": {
      "description": "Description of this SMB share",
      "type": "string"
    },
    "permissions": {
      "type": "array",
      "items": {
        "description": "The access control list (ACL) for this SMB share",
        "type": "object",
        "properties": {
          "type": {
            "type": "string",
            "enum": [
              "ALLOWED",
              "DENIED"
            ]
          }
        }
      }
    }
  }
}
```

```

        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
    },
    "trustee": {
        "description": "User/group to apply the permissions entry to",
        "type": "object",
        "properties": {
            "domain": {
                "type": "string",
                "enum": [
                    "LOCAL",
                    "API_NULL_DOMAIN",
                    "WORLD",
                    "POSIX_USER",
                    "POSIX_GROUP",
                    "ACTIVE_DIRECTORY",
                    "API_INVALID_DOMAIN",
                    "API_RESERVED_DOMAIN",
                    "API_INTERNAL_DOMAIN",
                    "API_OPERATOR_DOMAIN",
                    "API_QUMULO_SUPPORT_DOMAIN",
                    "API_CREATOR_DOMAIN"
                ],
                "description": "domain:\n * `ACTIVE_DIRECTORY` - ACTIVE_DIRECTORY,\n * `API_CREATOR_DOMAIN` - API_CREATOR_DOMAIN,\n * `API_INTERNAL_DOMAIN` - API_INTERNAL_DOMAIN,\n * `API_INVALID_DOMAIN` - API_INVALID_DOMAIN,\n * `API_NULL_DOMAIN` - API_NULL_DOMAIN,\n * `API_OPERATOR_DOMAIN` - API_OPERATOR_DOMAIN,\n * `API_QUMULO_SUPPORT_DOMAIN` - API_QUMULO_SUPPORT_DOMAIN,\n * `API_RESERVED_DOMAIN` - API_RESERVED_DOMAIN,\n * `LOCAL` - LOCAL,\n * `POSIX_GROUP` - POSIX_GROUP,\n * `POSIX_USER` - POSIX_USER,\n * `WORLD` - WORLD"
            },
            "auth_id": {
                "description": "auth_id",
                "type": "string"
            },
            "uid": {
                "description": "uid",
                "type": "number"
            },
            "gid": {
                "description": "gid",
                "type": "number"
            },
            "sid": {
                "description": "sid",

```

```

        "type": "string"
    },
    "name": {
        "description": "name",
        "type": "string"
    }
}
},
"rights": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "READ_DATA",
            "READ_EA",
            "READ_ATTR",
            "READ_ACL",
            "WRITE_EA",
            "WRITE_ATTR",
            "WRITE_ACL",
            "CHANGE_OWNER",
            "WRITE_GROUP",
            "DELETE",
            "EXECUTE",
            "MODIFY",
            "EXTEND",
            "DELETE_CHILD",
            "SYNCHRONIZE",
            "READ",
            "WRITE",
            "CHANGE_PERMISSIONS"
        ],
        "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
}
}

```

```

},
"network_permissions": {
  "type": "array",
  "items": {
    "description": "The network access control list (ACL) for this SMB share. If not specified, the default is to allow any host.",
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "enum": [
          "ALLOWED",
          "DENIED"
        ],
        "description": "Type of permissions entry (ALLOWED or DENIED):\n * `ALLOWED` - The permissions entry rights are allowed to the trustee,\n * `DENIED` - The permissions entry rights are denied to the trustee"
      },
      "address_ranges": {
        "type": "array",
        "items": {
          "description": "IP address ranges to apply permissions to. Empty means all hosts.",
          "type": "string"
        }
      }
    }
  },
  "rights": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "READ_DATA",
        "READ_EA",
        "READ_ATTR",
        "READ_ACL",
        "WRITE_EA",
        "WRITE_ATTR",
        "WRITE_ACL",
        "CHANGE_OWNER",
        "WRITE_GROUP",
        "DELETE",
        "EXECUTE",
        "MODIFY",
        "EXTEND",
        "DELETE_CHILD",
        "SYNCHRONIZE",

```

```

        "READ",
        "WRITE",
        "CHANGE_PERMISSIONS"
    ],
    "description": "Rights pertaining to the permissions entry:\n * `CHANG
E_OWNER` - Owner write access,\n * `CHANGE_PERMISSIONS` - Rights to change permissio
ns on file objects,\n * `DELETE` - Delete access,\n * `DELETE_CHILD` - Delete from d
irectory access,\n * `EXECUTE` - Execute access,\n * `EXTEND` - File extension acces
s,\n * `MODIFY` - File modification access,\n * `READ` - Read access rights,\n * `RE
AD_ACL` - ACL read access,\n * `READ_ATTR` - Attribute read access,\n * `READ_DATA`
- File read access,\n * `READ_EA` - Extended attribute read access,\n * `SYNCHRONIZ
E` - File synchronize access,\n * `WRITE` - Write access rights,\n * `WRITE_ACL` - A
CL write access,\n * `WRITE_ATTR` - Attribute write access,\n * `WRITE_EA` - Extende
d attribute write access,\n * `WRITE_GROUP` - Group write access"
    }
}
}
},
"access_based_enumeration_enabled": {
    "description": "Enable Access-based Enumeration on this SMB share",
    "type": "boolean"
},
"default_file_create_mode": {
    "description": "Default POSIX file create mode bits on this SMB share (octal,
default 0644 if this field is empty)",
    "type": "string"
},
"default_directory_create_mode": {
    "description": "Default POSIX directory create mode bits on this SMB share (oc
tal, default 0755 if this field is empty)",
    "type": "string"
},
"require_encryption": {
    "description": "Require all traffic to this share to be encrypted. Clients wit
hout encryption capabilities will not be able to connect. Default is false if this f
ield is empty.",
    "type": "boolean"
},
"allow_fs_path_create": {
    "description": "If true, the server will create the file system path for the s
hare if it does not already exist. If false, the file system path must already exist.
Default is false if this field is empty.",
    "type": "boolean"
},
"expand_fs_path_variables": {

```

```

    "description": "If true, the server will expand %U variables in the file system path to username. Default is false if this field is empty.",
    "type": "boolean"
  },
  "offline_files_caching_mode": {
    "type": "string",
    "enum": [
      "NO_CACHING",
      "MANUAL_CACHING",
      "AUTOMATIC_CACHING"
    ],
    "description": "Offline-files caching mode advertised to SMB clients: \"no_caching\" (no caching, the default), \"manual_caching\" (cache files the user designates as offline-available), or \"automatic_caching\" (cache files as they are opened).:\n * `AUTOMATIC_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_AUTOMATIC_CACHING,\n * `MANUAL_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_MANUAL_CACHING,\n * `NO_CACHING` - SMB_OFFLINE_FILES_CACHING_MODE_NO_CACHING"
  }
}

```

session/change-password

Endpoint

/v1/session/change-password

POST

Change the password for the logged in user.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "password_change",
  "type": "object",
  "properties": {
    "old_password": {
      "description": "The current password",
      "type": "string",
      "format": "password"
    },
    "new_password": {
      "description": "The new password",
      "type": "string",
      "format": "password"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

session/login

Endpoint

/v1/session/login

POST

Authenticate the user. To authenticate subsequent requests, provide the bearer token from the response in the Authorization header.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "login",
  "type": "object",
  "properties": {
    "username": {
      "description": "The username to authenticate with",
      "type": "string"
    },
    "password": {
      "description": "The password to authenticate with",
      "type": "string",
      "format": "password"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "credentials",
  "type": "object",
  "properties": {
    "bearer_token": {
      "description": "bearer_token",
      "type": "string"
    }
  }
}
```

session/retrieve-saml-login

Endpoint

/v1/session/retrieve-saml-login

POST

This API resource supports the `qq sso_login` command. Check the status of the in-progress SAML single sign-on (SSO) authentication process that `start-saml-login` begins. When a user completes the authentication process, return the `bearer_token` with which a user can perform subsequent API requests. When the caller retrieves the `bearer_token`, future calls with the same `saml_login_id` return the 404 Not Found error. If authentication for `login_id` is pending, instruct the caller to check again later by returning an empty `bearer_token`. If the `login_id` has expired within the 5-minute limit, return the 401 Unauthorized error. If the caller has already retrieved the login-id, return the 404 Not Found error. If the provided verification code mismatches with the expected code, return the 400 Bad Request error.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "saml_login_verification",
  "type": "object",
  "properties": {
    "login_id": {
      "description": "A unique, Qumulo-generated login_id associated with a SAML SSO authentication session.",
      "type": "string"
    },
    "verification_code": {
      "description": "A one-time security code that helps ensure that the SAML SSO authentication session is user-initiated.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "credentials",
  "type": "object",
  "properties": {
    "bearer_token": {
      "description": "bearer_token",
      "type": "string"
    }
  }
}
```

session/roles

Endpoint

/v1/session/roles

GET

Retrieve a list of all the roles assigned to the current user, including those assigned to a group to which the current user belongs.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

session/start-saml-login

Endpoint

/v1/session/start-saml-login

POST

This API resource supports the `qq sso_login` command. Begin an interactive SAML single sign-on (SSO) authentication process for the cluster. Return the `login_id` and `login_url` strings required for the user to complete the authentication process. If SSO is not enabled on the cluster, return `saml_not_configured_error`. To complete in-browser authentication, the caller must pass the `login_url` parameter to the user. The caller must use the `login_id` parameter to poll the `retrieve-saml-login` API for SAML SSO credentials until the user completes the authentication process in the browser, or until the 5-minute limit elapses.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_saml_login_info",
  "type": "object",
  "properties": {
    "login_id": {
      "description": "The unique identifier for the pending login. Use the login_id with the check-saml-login API.",
      "type": "string"
    },
    "login_url": {
      "description": "The login URL to present to the user. To complete the authentication process, the user must open the login URL in a browser.",
      "type": "string"
    }
  }
}
```

}

session/who-am-i

Endpoint

/v1/session/who-am-i

GET

Retrieve information about the currently logged in user.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_user_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The user's unique id",
      "type": "string"
    },
    "name": {
      "description": "The user's account name",
      "type": "string"
    },
    "primary_group": {
      "description": "The unique ID of the user's group",
      "type": "string"
    },
    "sid": {
      "description": "The users's SID",
      "type": "string"
    },
    "uid": {
      "description": "The user's NFS uid",

```

```

    "type": "string"
  },
  "home_directory": {
    "description": "The path to the user's home directory",
    "type": "string"
  },
  "can_change_password": {
    "description": "Specifies whether the user can change the password",
    "type": "boolean"
  },
  "privileges": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "PRIVILEGE_AD_READ",
        "PRIVILEGE_AD_USE",
        "PRIVILEGE_AD_WRITE",
        "PRIVILEGE_ANALYTICS_READ",
        "PRIVILEGE_AUDIT_READ",
        "PRIVILEGE_AUDIT_WRITE",
        "PRIVILEGE_AUTH_CACHE_READ",
        "PRIVILEGE_AUTH_CACHE_WRITE",
        "PRIVILEGE_CLUSTER_READ",
        "PRIVILEGE_CLUSTER_WRITE",
        "PRIVILEGE_DEBUG",
        "PRIVILEGE_DNS_READ",
        "PRIVILEGE_DNS_USE",
        "PRIVILEGE_DNS_WRITE",
        "PRIVILEGE_FILE_FULL_ACCESS",
        "PRIVILEGE_FS_ATTRIBUTES_READ",
        "PRIVILEGE_FS_DELETE_TREE_READ",
        "PRIVILEGE_FS_DELETE_TREE_WRITE",
        "PRIVILEGE_FS_LOCK_READ",
        "PRIVILEGE_FS_LOCK_WRITE",
        "PRIVILEGE_FS_SETTINGS_READ",
        "PRIVILEGE_FS_SETTINGS_WRITE",
        "PRIVILEGE_FTP_READ",
        "PRIVILEGE_FTP_WRITE",
        "PRIVILEGE_IDENTITY_MAPPING_READ",
        "PRIVILEGE_IDENTITY_MAPPING_WRITE",
        "PRIVILEGE_IDENTITY_READ",
        "PRIVILEGE_IDENTITY_WRITE",
        "PRIVILEGE_KERBEROS_KEYTAB_READ",
        "PRIVILEGE_KERBEROS_KEYTAB_WRITE",
        "PRIVILEGE_KERBEROS_SETTINGS_READ",

```



```
"PRIVILEGE_KERBEROS_SETTINGS_WRITE",
"PRIVILEGE_KV_READ",
"PRIVILEGE_LDAP_READ",
"PRIVILEGE_LDAP_USE",
"PRIVILEGE_LDAP_WRITE",
"PRIVILEGE_LOCAL_GROUP_READ",
"PRIVILEGE_LOCAL_GROUP_WRITE",
"PRIVILEGE_LOCAL_USER_READ",
"PRIVILEGE_LOCAL_USER_WRITE",
"PRIVILEGE_METRICS_READ",
"PRIVILEGE_NETWORK_IP_ALLOCATION_READ",
"PRIVILEGE_NETWORK_READ",
"PRIVILEGE_NETWORK_WRITE",
"PRIVILEGE_NFS_EXPORT_READ",
"PRIVILEGE_NFS_EXPORT_WRITE",
"PRIVILEGE_POWER_CYCLE",
"PRIVILEGE_QUOTA_READ",
"PRIVILEGE_QUOTA_WRITE",
"PRIVILEGE_RECONCILER_READ",
"PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP",
"PRIVILEGE_REPLICATION_SOURCE_READ",
"PRIVILEGE_REPLICATION_SOURCE_WRITE",
"PRIVILEGE_REPLICATION_TARGET_READ",
"PRIVILEGE_REPLICATION_TARGET_WRITE",
"PRIVILEGE_ROLE_READ",
"PRIVILEGE_ROLE_WRITE",
"PRIVILEGE_SMB_SHARE_READ",
"PRIVILEGE_SMB_SHARE_WRITE",
"PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ",
"PRIVILEGE_SNAPSHOT_DIFFERENCE_READ",
"PRIVILEGE_SNAPSHOT_POLICY_READ",
"PRIVILEGE_SNAPSHOT_POLICY_WRITE",
"PRIVILEGE_SNAPSHOT_READ",
"PRIVILEGE_SNAPSHOT_WRITE",
"PRIVILEGE_SUPPORT_READ",
"PRIVILEGE_SUPPORT_WRITE",
"PRIVILEGE_TEST_ONLY",
"PRIVILEGE_TIME_READ",
"PRIVILEGE_TIME_WRITE",
"PRIVILEGE_UNCONFIGURED_NODE_READ",
"PRIVILEGE_UPGRADE_READ",
"PRIVILEGE_UPGRADE_WRITE",
"PRIVILEGE_SMB_FILE_HANDLE_READ",
"PRIVILEGE_SMB_FILE_HANDLE_WRITE",
"PRIVILEGE_SMB_SESSION_READ",
"PRIVILEGE_SMB_SESSION_WRITE",
```

"PRIVILEGE_REPLICATION_OBJECT_READ",
"PRIVILEGE_REPLICATION_OBJECT_WRITE",
"PRIVILEGE_ENCRYPTION_WRITE",
"PRIVILEGE_ENCRYPTION_READ",
"PRIVILEGE_NFS_SETTINGS_READ",
"PRIVILEGE_NFS_SETTINGS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_WRITE",
"PRIVILEGE_SERVICE_PUBLIC_KEYS_READ",
"PRIVILEGE_METRICS_CONFIG_READ",
"PRIVILEGE_METRICS_CONFIG_WRITE",
"PRIVILEGE_REBOOT_USE",
"PRIVILEGE_REBOOT_READ",
"PRIVILEGE_CHECKSUMMING_READ",
"PRIVILEGE_S3_SETTINGS_READ",
"PRIVILEGE_S3_SETTINGS_WRITE",
"PRIVILEGE_WEB_UI_SETTINGS_WRITE",
"PRIVILEGE_S3_CREDENTIALS_READ",
"PRIVILEGE_S3_CREDENTIALS_WRITE",
"PRIVILEGE_TENANT_READ",
"PRIVILEGE_TENANT_WRITE",
"PRIVILEGE_SAML_SETTINGS_READ",
"PRIVILEGE_SAML_SETTINGS_WRITE",
"PRIVILEGE_S3_BUCKETS_READ",
"PRIVILEGE_S3_BUCKETS_WRITE",
"PRIVILEGE_ACCESS_TOKENS_READ",
"PRIVILEGE_ACCESS_TOKENS_WRITE",
"PRIVILEGE_S3_UPLOADS_READ",
"PRIVILEGE_S3_UPLOADS_WRITE",
"PRIVILEGE_SNAPSHOT_LOCK",
"PRIVILEGE_FS_KEY_MANAGEMENT_WRITE",
"PRIVILEGE_FS_KEY_MANAGEMENT_READ",
"PRIVILEGE_IDENTITY_CONFIG_WRITE",
"PRIVILEGE_IDENTITY_CONFIG_READ",
"PRIVILEGE_FILE_READ_ACCESS",
"PRIVILEGE_PORTAL_SPOKE_READ",
"PRIVILEGE_PORTAL_SPOKE_WRITE",
"PRIVILEGE_PORTAL_SPOKE_EVICT",
"PRIVILEGE_PORTAL_HUB_READ",
"PRIVILEGE_PORTAL_HUB_WRITE",
"PRIVILEGE_PORTAL_GLOBAL_READ",
"PRIVILEGE_FS_FILE_LOCK_WRITE",
"PRIVILEGE_LICENSE_READ",
"PRIVILEGE_CAPACITY_READ",
"PRIVILEGE_CAPACITY_WRITE",
"PRIVILEGE_OBJECT_STORAGE_URI_READ",
"PRIVILEGE_OBJECT_STORAGE_URI_WRITE",

```

        "PRIVILEGE_DISK_ERROR_WRITE",
        "PRIVILEGE_DISK_ERROR_READ",
        "PRIVILEGE_OBJECT_STORAGE_CONFIG_READ",
        "PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE"
    ],
    "description": "The user's privileges:\n * `PRIVILEGE_ACCESS_TOKENS_READ` -
View any access tokens present in the system,\n * `PRIVILEGE_ACCESS_TOKENS_WRITE` -
Create or delete access tokens for any user in the system,\n * `PRIVILEGE_AD_READ`
- Read Qumulo Active Directory settings,\n * `PRIVILEGE_AD_USE` - Use Qumulo's APIs
for performing queries against Active Directory,\n * `PRIVILEGE_AD_WRITE` - Modify Q
umulo Active Directory settings,\n * `PRIVILEGE_ANALYTICS_READ` - Read cluster analy
tics,\n * `PRIVILEGE_AUDIT_READ` - Read audit settings,\n * `PRIVILEGE_AUDIT_WRITE`
- Modify audit settings,\n * `PRIVILEGE_AUTH_CACHE_READ` - Internal-Only: Read authe
ntication cache settings,\n * `PRIVILEGE_AUTH_CACHE_WRITE` - Internal-Only: Modify a
uthentication cache settings,\n * `PRIVILEGE_CAPACITY_READ` - View the capacity clam
p value.,\n * `PRIVILEGE_CAPACITY_WRITE` - Set the capacity clamp value.,\n * `PRIVI
LEGE_CHECKSUMMING_READ` - View the status of checksumming,\n * `PRIVILEGE_CLUSTER_RE
AD` - View nodes, disks, protection status, and SSL certificate,\n * `PRIVILEGE_CLUS
TER_WRITE` - Modify cluster settings and disk/identify LEDs,\n * `PRIVILEGE_DEBUG`
- Internal-Only: Perform debug operations on the cluster,\n * `PRIVILEGE_DISK_ERRO
R_READ` - Internal-Only: Read disk error threshold and status.,\n * `PRIVILEGE_DIS
K_ERROR_WRITE` - Internal-Only: Modify disk error threshold and revive rejected disk
s.,\n * `PRIVILEGE_DNS_READ` - Read DNS settings,\n * `PRIVILEGE_DNS_USE` - Perform
DNS lookups,\n * `PRIVILEGE_DNS_WRITE` - Modify DNS settings,\n * `PRIVILEGE_ENCRYPT
ION_READ` - View the status of at-rest-encryption,\n * `PRIVILEGE_ENCRYPTION_WRITE`
- Rotate encryption keys for clusters with at-rest-encryption,\n * `PRIVILEGE_FILE_F
ULL_ACCESS` - Provides full access to all files regardless of permissions,\n * `PRIV
ILEGE_FILE_READ_ACCESS` - Provides read access to all files regardless of permission
s,\n * `PRIVILEGE_FS_ATTRIBUTES_READ` - Read file system statistics,\n * `PRIVILEG
E_FS_DELETE_TREE_READ` - View the status of directory tree delete operations,\n * `P
RIVILEGE_FS_DELETE_TREE_WRITE` - Use directory tree delete API. Granting this privil
ege allows the deletion of any file or directory on the cluster. File and directory
permissions are not taken into account. Not required for `rm -r`.,\n * `PRIVILEGE_F
S_FILE_LOCK_WRITE` - Set or extend file lock retention periods and legal holds.,\n
* `PRIVILEGE_FS_KEY_MANAGEMENT_READ` - Read and list public keys for various FS secu
rity features.,\n * `PRIVILEGE_FS_KEY_MANAGEMENT_WRITE` - Create and manage public k
eys for various FS security features.,\n * `PRIVILEGE_FS_LOCK_READ` - View NLN and S
MB locks and waiters,\n * `PRIVILEGE_FS_LOCK_WRITE` - Release NLN and SMB locks,\n
* `PRIVILEGE_FS_SETTINGS_READ` - View file system permissions settings,\n * `PRIVILE
GE_FS_SETTINGS_WRITE` - Modify file system permissions mode,\n * `PRIVILEGE_FTP_REA
D` - View FTP status and settings,\n * `PRIVILEGE_FTP_WRITE` - Modify FTP status an
d settings,\n * `PRIVILEGE_IDENTITY_CONFIG_READ` - Read and list identity configurat
ions.,\n * `PRIVILEGE_IDENTITY_CONFIG_WRITE` - Modify identity configurations.,\n *
`PRIVILEGE_IDENTITY_MAPPING_READ` - Get AD/LDAP User Defined Mappings,\n * `PRIVILEG
E_IDENTITY_MAPPING_WRITE` - Set AD/LDAP User Defined Mappings,\n * `PRIVILEGE_IDENTI
TY_READ` - Use Qumulo's identity lookup and translation APIs,\n * `PRIVILEGE_IDENTIT

```

Y_WRITE` - Modify identity attributes and clear authentication cache,\n \* `PRIVILEGE_KERBEROS_KEYTAB_READ` - View Kerberos keytab,\n \* `PRIVILEGE_KERBEROS_KEYTAB_WRITE` - Modify Kerberos keytab,\n \* `PRIVILEGE_KERBEROS_SETTINGS_READ` - Read Kerberos settings,\n \* `PRIVILEGE_KERBEROS_SETTINGS_WRITE` - Modify Kerberos settings,\n \* `PRIVILEGE_KV_READ` - DEPRECATED: Read and delete KV store entries for all users,\n \* `PRIVILEGE_LDAP_READ` - View LDAP settings,\n \* `PRIVILEGE_LDAP_USE` - Use Qumulo's APIs for performing LDAP queries,\n \* `PRIVILEGE_LDAP_WRITE` - Modify LDAP settings,\n \* `PRIVILEGE_LICENSE_READ` - Get the cluster's license status.,\n \* `PRIVILEGE_LOCAL_GROUP_READ` - View local groups and members,\n \* `PRIVILEGE_LOCAL_GROUP_WRITE` - Modify local groups and membership,\n \* `PRIVILEGE_LOCAL_USER_READ` - Get information about local users,\n \* `PRIVILEGE_LOCAL_USER_WRITE` - Create and modify all local users,\n \* `PRIVILEGE_METRICS_CONFIG_READ` - View metrics configuration,\n \* `PRIVILEGE_METRICS_CONFIG_WRITE` - Modify metrics configuration,\n \* `PRIVILEGE_METRICS_READ` - Get all metrics,\n \* `PRIVILEGE_NETWORK_IP_ALLOCATION_READ` - View network IP address allocations,\n \* `PRIVILEGE_NETWORK_READ` - Read network status and settings,\n \* `PRIVILEGE_NETWORK_WRITE` - Modify network configuration,\n \* `PRIVILEGE_NFS_EXPORT_READ` - View configuration of NFS exports,\n \* `PRIVILEGE_NFS_EXPORT_WRITE` - Create, modify, and delete NFS exports,\n \* `PRIVILEGE_NFS_SETTINGS_READ` - Internal-Only: View NFS server settings,\n \* `PRIVILEGE_NFS_SETTINGS_WRITE` - Internal-Only: Modify NFS server settings,\n \* `PRIVILEGE_OBJECT_STORAGE_CONFIG_READ` - Read object storage config, including store URIs and credentials.,\n \* `PRIVILEGE_OBJECT_STORAGE_CONFIG_WRITE` - Write object storage config, including store URIs and credentials.,\n \* `PRIVILEGE_OBJECT_STORAGE_URIS_READ` - View the object storage URIs.,\n \* `PRIVILEGE_OBJECT_STORAGE_URIS_WRITE` - Add new object storage URIs.,\n \* `PRIVILEGE_PORTAL_GLOBAL_READ` - View global portal settings and status,\n \* `PRIVILEGE_PORTAL_HUB_READ` - View hub portal relationship status and configuration,\n \* `PRIVILEGE_PORTAL_HUB_WRITE` - Authorize, modify, and delete hub portal relationships. Granting this privilege allows authorizing proposed relationships. Depending on existing file and directory permissions, this privilege can allow remote access to local data under the hub root directory.,\n \* `PRIVILEGE_PORTAL_SPOKE_EVICT` - Remove cached files and directories from a spoke portal. Qumulo Core recaches the removed files or directories upon access.,\n \* `PRIVILEGE_PORTAL_SPOKE_READ` - View spoke portal relationship status and configuration,\n \* `PRIVILEGE_PORTAL_SPOKE_WRITE` - Create, modify, and delete spoke portal relationships. Granting this privilege allows creating spoke portal root directories. Depending on existing file permissions, this privilege can allow local access to remote files and directories.,\n \* `PRIVILEGE_POWER_CYCLE` - Shutdown and reboot nodes,\n \* `PRIVILEGE_QUOTA_READ` - View all file system quotas,\n \* `PRIVILEGE_QUOTA_WRITE` - Create, modify, and delete file system quotas,\n \* `PRIVILEGE_REBOOT_READ` - View Reboot Status,\n \* `PRIVILEGE_REBOOT_USE` - Perform Reboots,\n \* `PRIVILEGE_RECONCILER_READ` - View reconciler status and metrics,\n \* `PRIVILEGE_REPLICATION_OBJECT_READ` - View object store relationship settings and status,\n \* `PRIVILEGE_REPLICATION_OBJECT_WRITE` - Create, modify, and delete object store relationships. Granting this privilege allows overwriting existing data, replicating, and potentially accessing any data on the cluster regardless of file and directory permissions.,\n \* `PRIVILEGE_REPLICATION_REVERSE_RELATIONSHIP` - Reverse a source and target relationship,\n \* `PRIVILEGE_REPLICATION_SOURCE_READ` - Vie

```

w source relationship settings and status,\n * `PRIVILEGE_REPLICATION_SOURCE_WRITE`
- Create, modify, and delete source relationships. Granting this privilege allows re
plicating and potentially accessing any data on the cluster regardless of file and d
irectory permissions.,\n * `PRIVILEGE_REPLICATION_TARGET_READ` - View target relatio
nship settings and status,\n * `PRIVILEGE_REPLICATION_TARGET_WRITE` - Create, modif
y, and delete target relationships. Granting this privilege allows overwriting any d
ata on the cluster regardless of file and directory permissions.,\n * `PRIVILEGE_ROL
E_READ` - View roles and assignments,\n * `PRIVILEGE_ROLE_WRITE` - Create and modif
y roles and assignments,\n * `PRIVILEGE_S3_BUCKETS_READ` - View all S3 buckets and b
ucket policies present in the system,\n * `PRIVILEGE_S3_BUCKETS_WRITE` - Create or d
elete any S3 bucket in the system, and create, delete, or modify policies for any S
3 bucket in the system. Subject to having sufficient FS permissions.,\n * `PRIVILEG
E_S3_CREDENTIALS_READ` - View any S3 access key present in the system,\n * `PRIVILEG
E_S3_CREDENTIALS_WRITE` - Create or delete S3 access keys for any user in the syste
m,\n * `PRIVILEGE_S3_SETTINGS_READ` - View S3 server settings,\n * `PRIVILEGE_S3_SET
TINGS_WRITE` - Modify S3 server settings,\n * `PRIVILEGE_S3_UPLOADS_READ` - View al
l S3 uploads present in the system. This will override a bucket policy that denies t
he user this permission.,\n * `PRIVILEGE_S3_UPLOADS_WRITE` - Abort S3 uploads in th
e system. This will override a bucket policy that denies the user this permissio
n.,\n * `PRIVILEGE_SAML_SETTINGS_READ` - View SAML integration settings,\n * `PRIVIL
EGE_SAML_SETTINGS_WRITE` - Modify SAML integration settings,\n * `PRIVILEGE_SERVIC
E_PUBLIC_KEYS_READ` - Internal-Only: Read public keys,\n * `PRIVILEGE_SERVICE_PUBLI
C_KEYS_WRITE` - Internal-Only: Write public keys,\n * `PRIVILEGE_SMB_FILE_HANDLE_REA
D` - List open SMB file handles,\n * `PRIVILEGE_SMB_FILE_HANDLE_WRITE` - Force clos
e an open SMB file handle,\n * `PRIVILEGE_SMB_SESSION_READ` - List logged on SMB ses
sions,\n * `PRIVILEGE_SMB_SESSION_WRITE` - Force close a logged on SMB session,\n *
`PRIVILEGE_SMB_SHARE_READ` - View configuration of SMB shares and SMB server setting
s,\n * `PRIVILEGE_SMB_SHARE_WRITE` - Create, modify, and delete SMB shares and SMB s
erver settings,\n * `PRIVILEGE_SNAPSHOT_CALCULATE_USED_CAPACITY_READ` - Recalculate
capacity usage of snapshots,\n * `PRIVILEGE_SNAPSHOT_DIFFERENCE_READ` - View the cha
nges between snapshots,\n * `PRIVILEGE_SNAPSHOT_LOCK` - Lock or unlock snapshots. Co
nfigure snapshot policies to lock or unlock snapshots.,\n * `PRIVILEGE_SNAPSHOT_POLI
CY_READ` - View snapshot policies and status,\n * `PRIVILEGE_SNAPSHOT_POLICY_WRITE`
- Create, modify, and delete snapshot policies,\n * `PRIVILEGE_SNAPSHOT_READ` - Lis
t snapshots and view their status and cached capacity. Does not affect the visibilit
y of the virtual `.snapshot` directories,\n * `PRIVILEGE_SNAPSHOT_WRITE` - Create, m
odify, and delete snapshots,\n * `PRIVILEGE_SUPPORT_READ` - View support configurati
on and status,\n * `PRIVILEGE_SUPPORT_WRITE` - Modify cloud-based monitoring and rem
ote management,\n * `PRIVILEGE_TENANT_READ` - View any tenant information,\n * `PRIV
ILEGE_TENANT_WRITE` - Create, edit or delete tenants,\n * `PRIVILEGE_TEST_ONLY` - Te
st only actions,\n * `PRIVILEGE_TIME_READ` - View time and time settings,\n * `PRIVI
LEGE_TIME_WRITE` - Modify time settings,\n * `PRIVILEGE_UNCONFIGURED_NODE_READ` - Li
st unconfigured Qumulo nodes,\n * `PRIVILEGE_UPGRADE_READ` - View upgrade configurat
ion and status,\n * `PRIVILEGE_UPGRADE_WRITE` - Perform upgrades,\n * `PRIVILEGE_WE
B_UI_SETTINGS_WRITE` - Modify web UI settings"
}

```

```
    },  
    "access_token_id": {  
      "description": "The user's access token ID. Only present when access token authentication is used.",  
      "type": "string"  
    }  
  }  
}
```

shutdown/container-restart

Endpoint

`/v1/shutdown/container-restart`

POST

Restart the Qumulo Core container on every node in the cluster.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
202	Return value on success

shutdown/container-restart/{node_id}

Endpoint

/v1/shutdown/container-restart/{node_id}

POST

Restart the Qumulo Core container on a particular node.

Parameters

Name	Description	Required
<code>node_id</code>	URI parameter node_id	Yes

Response

Codes

Code	Description
200	Return value on success

shutdown/halt

Endpoint

`/v1/shutdown/halt`

POST

Shut down every node in the cluster and power off.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

shutdown/halt/{node_id}

Endpoint

/v1/shutdown/halt/{node_id}

POST

Shut down a single node.

Parameters

Name	Description	Required
<code>node_id</code>	URI parameter node_id	Yes

Response

Codes

Code	Description
200	Return value on success

shutdown/reboot/pause

Endpoint

/v1/shutdown/reboot/pause

POST

Pause an in progress reboot cycle.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

shutdown/reboot/resume

Endpoint

/v1/shutdown/reboot/resume

POST

Resume a paused reboot cycle.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

shutdown/reboot/start

Endpoint

/v1/shutdown/reboot/start

POST

Start a reboot cycle with the Reboot Manager system.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_reboot_start_options",
  "type": "object",
  "properties": {
    "is_rolling": {
      "description": "If true, kick off a rolling reboot, otherwise do it concurrently. Defaults to false",
      "type": "boolean"
    },
    "num_nodes_to_reboot": {
      "description": "If the number of nodes to reboot is configured and rolling reboot is enabled, your cluster reboots the specified number of nodes at a time. The number of nodes must be greater than 0 and less than or equal to the number of node failures that your cluster permits. By default, the value is the number of permitted node failures minus 1 (1 node minimum).",
      "type": "number"
    }
  }
}
```

Response

Codes

Code	Description
202	Return value on success

shutdown/reboot/status

Endpoint

/v1/shutdown/reboot/status

GET

Retrieve the current status of the reboot manager.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "reboot_status",
  "type": "object",
  "properties": {
    "state": {
      "type": "string",
      "enum": [
        "REBOOT_IDLE",
        "REBOOT_IN_PROGRESS",
        "REBOOT_PAUSED",
        "REBOOT_PAUSED_DUE_TO_ERROR"
      ],
      "description": "state:\n * `REBOOT_IDLE` - REBOOT_IDLE,\n * `REBOOT_IN_PROGRESS` - REBOOT_IN_PROGRESS,\n * `REBOOT_PAUSED` - REBOOT_PAUSED,\n * `REBOOT_PAUSED_DUE_TO_ERROR` - REBOOT_PAUSED_DUE_TO_ERROR"
    },
    "rolling": {
      "description": "rolling",
      "type": "boolean"
    },
    "upgrade_initiated": {
      "description": "upgrade_initiated",
```

```
    "type": "boolean"
  },
  "total_node_count": {
    "description": "total_node_count",
    "type": "number"
  },
  "rebooted_node_count": {
    "description": "rebooted_node_count",
    "type": "number"
  },
  "error_message": {
    "description": "error_message",
    "type": "string"
  }
}
```

shutdown/reboot/{node_id}

Endpoint

/v1/shutdown/reboot/{node_id}

POST

Reboot a single node.

Parameters

Name	Description	Required
<code>node_id</code>	URI parameter node_id	Yes

Response

Codes

Code	Description
200	Return value on success

snapshots/

Endpoint

/v1/snapshots/

GET

Returns information about all snapshots.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshots_v1",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of snapshot information",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique identifier of the snapshot",
            "type": "number"
          },
          "name": {
            "description": "Name of the snapshot",
            "type": "string"
          },
          "timestamp": {
            "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",

```

```

    "type": "string"
  },
  "directory_name": {
    "description": "Snapshot directory name, as would be seen in the .snapsh
ot directory over SMB or NFS.",
    "type": "string"
  },
  "source_path": {
    "description": "Source directory of the snapshot",
    "type": "string"
  },
  "created_by_policy": {
    "description": "This snapshot was created by a policy. The name of that
policy will be stored in the name field in place of a user-defined name.",
    "type": "boolean"
  },
  "expiration": {
    "description": "Time at which snapshot will be expired. Empty string if
no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 860
1. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  }
}
}
}
}
}
}

```

POST

Creates a new snapshot and returns its details.

Parameters

Name	Description	Required
<code>expiration-time-to-live</code>	Duration after which to expire the snapshot, in format <code><value><unit></code> , where <code><value></code> is a positive integer less than 1000 and is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates the snapshot should never expire. Defaults to never if not specified.	No

Request

Schema

```
{
  "description": "api_snapshot_create_v1",
  "type": "object",
  "properties": {
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, whic
```

h is a normalized subset of ISO 8601. See <http://tools.ietf.org/rfc/rfc3339.txt>, section 5.6 for ABNF.",

```
    "type": "string"
  },
  "directory_name": {
    "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
    "type": "string"
  },
  "source_path": {
    "description": "Source directory of the snapshot",
    "type": "string"
  },
  "created_by_policy": {
    "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
    "type": "boolean"
  },
  "expiration": {
    "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  }
}
```

snapshots/policies/

Endpoint

/v1/snapshots/policies/

GET

Returns information about all snapshot policies.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshots_policies_v1",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of snapshot policy information",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique identifier for the snapshot policy",
            "type": "number"
          },
          "name": {
            "description": "Name of the snapshot policy",
            "type": "string"
          },
          "source_file_ids": {
            "type": "array",
            "items": {
              "description": "File ID of the directory on which to take snapshots un
```

```

der the policy. The array must contain exactly one file ID and cannot be modified af
ter policy creation.",
    "type": "string"
  }
},
"schedules": {
  "type": "array",
  "items": {
    "description": "Schedule by which to take snapshots for the policy. Th
e array must contain exactly one schedule.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Identifier for the snapshot policy's schedule. Onl
y unique within the scope of a snapshot policy.",
        "type": "number"
      },
      "creation_schedule": {
        "description": "Structure defining when to take snapshots",
        "type": "object",
        "properties": {
          "timezone": {
            "description": "The time zone in which the schedule should be
interpreted (e.g. America/Los_Angeles or UTC).",
            "type": "string"
          },
          "frequency": {
            "type": "string",
            "enum": [
              "SCHEDULE_MONTHLY",
              "SCHEDULE_DAILY_OR_WEEKLY",
              "SCHEDULE_HOURLY_OR_LESS"
            ],
            "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, o
r HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDU
LE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SC
HEDULE_MONTHLY` - SCHEDULE_MONTHLY"
          },
          "hour": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hou
r of day [0, 23] at which to take snapshot",
            "type": "number"
          },
          "minute": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minu
te of hour [0, 59] at which to take snapshot",

```

```

        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ]
        },
        "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour

```

```
[0, 59] for end of window during which to take snapshots",
    "type": "number"
  },
  "fire_every_interval": {
    "type": "string",
    "enum": [
      "FIRE_IN_MINUTES",
      "FIRE_IN_HOURS"
    ],
    "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
  },
  "fire_every": {
    "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
    "type": "number"
  }
},
"expiration_time_to_live": {
  "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
  "type": "string"
}
}
}
},
"enabled": {
  "description": "Whether snapshot taking is enabled for this policy (defaults to true)",
  "type": "boolean"
}
}
}
}
}
```

POST

Creates a new snapshot policy and returns its details.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_snapshots_policy_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for the snapshot policy",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot policy",
      "type": "string"
    },
    "source_file_ids": {
      "type": "array",
      "items": {
        "description": "File ID of the directory on which to take snapshots under the policy. The array must contain exactly one file ID and cannot be modified after policy creation.",
        "type": "string"
      }
    },
    "schedules": {
      "type": "array",
      "items": {
        "description": "Schedule by which to take snapshots for the policy. The array must contain exactly one schedule.",
        "type": "object",
        "properties": {
          "id": {
            "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
            "type": "number"
          },
          "creation_schedule": {
            "description": "Structure defining when to take snapshots",
            "type": "object",
            "properties": {
              "timezone": {
                "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
                "type": "string"
              },
              "frequency": {
```

```

        "type": "string",
        "enum": [
            "SCHEDULE_MONTHLY",
            "SCHEDULE_DAILY_OR_WEEKLY",
            "SCHEDULE_HOURLY_OR_LESS"
        ],
        "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
    },
    "hour": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
        "type": "number"
    },
    "minute": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ],
        },
        "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\n * `FRIDAY` - FRIDAY,\n * `MONDAY` - MONDAY,\n * `SATURDAY` - SATURDAY,\n * `SUNDAY` - SUNDAY,\n * `THURSDAY` - THURSDAY,\n * `TUESDAY` - TUESDAY,\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
    },

```

```

        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
        "type": "number"
    }
}

"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1 hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}

```

```

    }
  },
  "enabled": {
    "description": "Whether snapshot taking is enabled for this policy (defaults to true)",
    "type": "boolean"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshots_policy_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for the snapshot policy",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot policy",
      "type": "string"
    },
    "source_file_ids": {
      "type": "array",
      "items": {
        "description": "File ID of the directory on which to take snapshots under the policy. The array must contain exactly one file ID and cannot be modified after policy creation.",
        "type": "string"
      }
    },
    "schedules": {
      "type": "array",
      "items": {

```

```

    "description": "Schedule by which to take snapshots for the policy. The array must contain exactly one schedule.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
        "type": "number"
      },
      "creation_schedule": {
        "description": "Structure defining when to take snapshots",
        "type": "object",
        "properties": {
          "timezone": {
            "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
            "type": "string"
          },
          "frequency": {
            "type": "string",
            "enum": [
              "SCHEDULE_MONTHLY",
              "SCHEDULE_DAILY_OR_WEEKLY",
              "SCHEDULE_HOURLY_OR_LESS"
            ],
            "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
          },
          "hour": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
            "type": "number"
          },
          "minute": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
            "type": "number"
          },
          "on_days": {
            "type": "array",
            "items": {
              "type": "string",
              "enum": [
                "SUNDAY",

```

```

        "MONDAY",
        "TUESDAY",
        "WEDNESDAY",
        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
    ],
    "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
  },
  "day_of_month": {
    "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
    "type": "number"
  },
  "window_start_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
    "type": "number"
  },
  "window_start_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
    "type": "number"
  },
  "window_end_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
    "type": "number"
  },
  "window_end_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
    "type": "number"
  },
  "fire_every_interval": {
    "type": "string",
    "enum": [
      "FIRE_IN_MINUTES",
      "FIRE_IN_HOURS"
    ]
  }
}

```

```

    ],
    "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
  },
  "fire_every": {
    "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
    "type": "number"
  }
},
"expiration_time_to_live": {
  "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1 hours. Empty string or never indicates snapshots should never expire.",
  "type": "string"
}
},
"enabled": {
  "description": "Whether snapshot taking is enabled for this policy (defaults to true)",
  "type": "boolean"
}
}
}

```

snapshots/policies/status/

Endpoint

/v1/snapshots/policies/status/

GET

Returns status information about all snapshot policies.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "snapshots_api_policy_statuses_v1",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of snapshot policy statuses",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique identifier for the snapshot policy",
            "type": "number"
          },
          "name": {
            "description": "Name of the snapshot policy",
            "type": "string"
          },
          "schedules": {
            "type": "array",
            "items": {
              "description": "Schedule by which to take snapshots for the policy. Th
```



```

e array contains exactly one schedule.",
    "type": "object",
    "properties": {
        "id": {
            "description": "Identifier for the snapshot policy's schedule. Only
unique within the scope of a snapshot policy.",
            "type": "number"
        },
        "creation_schedule": {
            "description": "Structure defining when to take snapshots",
            "type": "object",
            "properties": {
                "timezone": {
                    "description": "The time zone in which the schedule should be
interpreted (e.g. America/Los_Angeles or UTC).",
                    "type": "string"
                },
                "frequency": {
                    "type": "string",
                    "enum": [
                        "SCHEDULE_MONTHLY",
                        "SCHEDULE_DAILY_OR_WEEKLY",
                        "SCHEDULE_HOURLY_OR_LESS"
                    ],
                    "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, o
r HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDU
LE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SC
HEDULE_MONTHLY` - SCHEDULE_MONTHLY"
                },
                "hour": {
                    "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hou
r of day [0, 23] at which to take snapshot",
                    "type": "number"
                },
                "minute": {
                    "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minu
te of hour [0, 59] at which to take snapshot",
                    "type": "number"
                },
                "on_days": {
                    "type": "array",
                    "items": {
                        "type": "string",
                        "enum": [
                            "SUNDAY",
                            "MONDAY",

```

```

        "TUESDAY",
        "WEDNESDAY",
        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
    ],
    "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ]
    }
],

```

```

        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
        "type": "number"
    }
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Whether snapshot taking is enabled for this policy (defaults to true)",
    "type": "boolean"
},
"source_files": {
    "type": "array",
    "items": {
        "description": "Status of the source directory for the policy. The array contains exactly one status.",
        "type": "object",
        "properties": {
            "source_file_id": {
                "description": "File ID of the snapshot source directory",
                "type": "string"
            },
            "source_file_path": {
                "description": "File path of the snapshot source directory, if available",
                "type": "string"
            },
            "deleted": {
                "description": "True if the source directory is deleted",
                "type": "boolean"
            }
        }
    }
}

```

```

    }
  },
  "owners": {
    "type": "array",
    "items": {
      "description": "Owners of this snapshot policy. The policy can only be modified but not deleted while the list is non-empty.",
      "type": "object",
      "properties": {
        "id": {
          "description": "id",
          "type": "string"
        }
      }
    }
  }
}

```

snapshots/policies/status/{id}

Endpoint

/v1/snapshots/policies/status/{id}

GET

Returns status information about a specific snapshot policy.

Parameters

Name	Description	Required
id	Policy identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "snapshots_api_policy_status_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for the snapshot policy",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot policy",
      "type": "string"
    },
    "schedules": {
      "type": "array",
      "items": {
        "description": "Schedule by which to take snapshots for the policy. The array contains exactly one schedule.",
        "type": "object",
        "properties": {
```

```

    "id": {
      "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
      "type": "number"
    },
    "creation_schedule": {
      "description": "Structure defining when to take snapshots",
      "type": "object",
      "properties": {
        "timezone": {
          "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
          "type": "string"
        },
        "frequency": {
          "type": "string",
          "enum": [
            "SCHEDULE_MONTHLY",
            "SCHEDULE_DAILY_OR_WEEKLY",
            "SCHEDULE_HOURLY_OR_LESS"
          ],
          "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
        },
        "hour": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
          "type": "number"
        },
        "minute": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
          "type": "number"
        },
        "on_days": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": [
              "SUNDAY",
              "MONDAY",
              "TUESDAY",
              "WEDNESDAY",
              "THURSDAY",

```

```

        "FRIDAY",
        "SATURDAY"
    ],
    "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    }
}

```

```

    },
    "fire_every": {
      "description": "For HOURLY_OR_LESS frequency: value for interval
[1, 99] at which to take snapshot during specified window",
      "type": "number"
    }
  },
  "expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by thi
s policy, in format <quantity><units>, where <quantity> is a positive integer less t
han 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1
hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
  }
},
"enabled": {
  "description": "Whether snapshot taking is enabled for this policy (defaults t
o true)",
  "type": "boolean"
},
"source_files": {
  "type": "array",
  "items": {
    "description": "Status of the source directory for the policy. The array con
tains exactly one status.",
    "type": "object",
    "properties": {
      "source_file_id": {
        "description": "File ID of the snapshot source directory",
        "type": "string"
      },
      "source_file_path": {
        "description": "File path of the snapshot source directory, if availabl
e",
        "type": "string"
      },
      "deleted": {
        "description": "True if the source directory is deleted",
        "type": "boolean"
      }
    }
  }
}
},
},

```



```
"owners": {  
  "type": "array",  
  "items": {  
    "description": "Owners of this snapshot policy. The policy can only be modified but not deleted while the list is non-empty.",  
    "type": "object",  
    "properties": {  
      "id": {  
        "description": "id",  
        "type": "string"  
      }  
    }  
  }  
}
```

snapshots/policies/{id}

Endpoint

/v1/snapshots/policies/{id}

GET

Returns information about a specific snapshot policy.

Parameters

Name	Description	Required
id	Policy identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshots_policy_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for the snapshot policy",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot policy",
      "type": "string"
    },
    "source_file_ids": {
      "type": "array",
      "items": {
        "description": "File ID of the directory on which to take snapshots under the policy. The array must contain exactly one file ID and cannot be modified after policy creation.",
        "type": "string"
      }
    }
  }
}
```

```

    }
  },
  "schedules": {
    "type": "array",
    "items": {
      "description": "Schedule by which to take snapshots for the policy. The array must contain exactly one schedule.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
          "type": "number"
        },
        "creation_schedule": {
          "description": "Structure defining when to take snapshots",
          "type": "object",
          "properties": {
            "timezone": {
              "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
              "type": "string"
            },
            "frequency": {
              "type": "string",
              "enum": [
                "SCHEDULE_MONTHLY",
                "SCHEDULE_DAILY_OR_WEEKLY",
                "SCHEDULE_HOURLY_OR_LESS"
              ],
              "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
            },
            "hour": {
              "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
              "type": "number"
            },
            "minute": {
              "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
              "type": "number"
            },
            "on_days": {

```

```

    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "SUNDAY",
        "MONDAY",
        "TUESDAY",
        "WEDNESDAY",
        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
      ],
      "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
      "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
      "type": "number"
    },
    "window_start_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_start_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_end_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
      "type": "number"
    },
    "window_end_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
      "type": "number"
    },
  },

```

```

    "fire_every_interval": {
      "type": "string",
      "enum": [
        "FIRE_IN_MINUTES",
        "FIRE_IN_HOURS"
      ],
      "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
      "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
      "type": "number"
    }
  },
  "expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1 hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
  }
}
},
"enabled": {
  "description": "Whether snapshot taking is enabled for this policy (defaults to true)",
  "type": "boolean"
}
}
}

```

PUT

Modifies a snapshot policy.

Parameters

Name	Description	Required
id	Policy identifier	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_snapshots_policy_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for the snapshot policy",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot policy",
      "type": "string"
    },
    "source_file_ids": {
      "type": "array",
      "items": {
        "description": "File ID of the directory on which to take snapshots under the policy. The array must contain exactly one file ID and cannot be modified after policy creation.",
        "type": "string"
      }
    },
    "schedules": {
      "type": "array",
      "items": {
        "description": "Schedule by which to take snapshots for the policy. The array must contain exactly one schedule.",
        "type": "object",
        "properties": {
          "id": {
            "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
            "type": "number"
          },
          "creation_schedule": {
            "description": "Structure defining when to take snapshots",
            "type": "object",
            "properties": {
              "timezone": {
                "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
                "type": "string"
              },
              "frequency": {
```

```

        "type": "string",
        "enum": [
            "SCHEDULE_MONTHLY",
            "SCHEDULE_DAILY_OR_WEEKLY",
            "SCHEDULE_HOURLY_OR_LESS"
        ],
        "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
    },
    "hour": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
        "type": "number"
    },
    "minute": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ],
            "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\n * `FRIDAY` - FRIDAY,\n * `MONDAY` - MONDAY,\n * `SATURDAY` - SATURDAY,\n * `SUNDAY` - SUNDAY,\n * `THURSDAY` - THURSDAY,\n * `TUESDAY` - TUESDAY,\n * `WEDNESDAY` - WEDNESDAY"
        }
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",

```

```

        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
        "type": "number"
    }
}

"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1 hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}

```



```

    }
  },
  "enabled": {
    "description": "Whether snapshot taking is enabled for this policy (defaults to true)",
    "type": "boolean"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshots_policy_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for the snapshot policy",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot policy",
      "type": "string"
    },
    "source_file_ids": {
      "type": "array",
      "items": {
        "description": "File ID of the directory on which to take snapshots under the policy. The array must contain exactly one file ID and cannot be modified after policy creation.",
        "type": "string"
      }
    },
    "schedules": {
      "type": "array",
      "items": {

```

```

    "description": "Schedule by which to take snapshots for the policy. The array must contain exactly one schedule.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
        "type": "number"
      },
      "creation_schedule": {
        "description": "Structure defining when to take snapshots",
        "type": "object",
        "properties": {
          "timezone": {
            "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
            "type": "string"
          },
          "frequency": {
            "type": "string",
            "enum": [
              "SCHEDULE_MONTHLY",
              "SCHEDULE_DAILY_OR_WEEKLY",
              "SCHEDULE_HOURLY_OR_LESS"
            ],
            "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
          },
          "hour": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
            "type": "number"
          },
          "minute": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
            "type": "number"
          },
          "on_days": {
            "type": "array",
            "items": {
              "type": "string",
              "enum": [
                "SUNDAY",

```

```

        "MONDAY",
        "TUESDAY",
        "WEDNESDAY",
        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
    ],
    "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ]
    }
}

```

```

    ],
    "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
  },
  "fire_every": {
    "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
    "type": "number"
  }
},
"expiration_time_to_live": {
  "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1 hours. Empty string or never indicates snapshots should never expire.",
  "type": "string"
}
}
},
"enabled": {
  "description": "Whether snapshot taking is enabled for this policy (defaults to true)",
  "type": "boolean"
}
}
}

```

DELETE

Deletes a snapshot policy.

Parameters

Name	Description	Required
<code>id</code>	Policy identifier	Yes

Response

Codes

Code	Description
------	-------------

200	Return value on success
-----	-------------------------

PATCH

Modifies a snapshot policy.

Parameters

Name	Description	Required
id	Policy identifier	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_snapshots_policy_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for the snapshot policy",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot policy",
      "type": "string"
    },
    "source_file_ids": {
      "type": "array",
      "items": {
        "description": "File ID of the directory on which to take snapshots under the policy. The array must contain exactly one file ID and cannot be modified after policy creation.",
        "type": "string"
      }
    },
    "schedules": {
      "type": "array",
      "items": {
        "description": "Schedule by which to take snapshots for the policy. The array must contain exactly one schedule.",
        "type": "object",

```

```

"properties": {
  "id": {
    "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
    "type": "number"
  },
  "creation_schedule": {
    "description": "Structure defining when to take snapshots",
    "type": "object",
    "properties": {
      "timezone": {
        "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
        "type": "string"
      },
      "frequency": {
        "type": "string",
        "enum": [
          "SCHEDULE_MONTHLY",
          "SCHEDULE_DAILY_OR_WEEKLY",
          "SCHEDULE_HOURLY_OR_LESS"
        ],
        "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
      },
      "hour": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
        "type": "number"
      },
      "minute": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
        "type": "number"
      },
      "on_days": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "SUNDAY",
            "MONDAY",
            "TUESDAY",
            "WEDNESDAY",

```

```

        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
    ],
    "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\\n * `FIRE_IN_HOUR

```

```

S` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
      "description": "For HOURLY_OR_LESS frequency: value for interval
[1, 99] at which to take snapshot during specified window",
      "type": "number"
    }
  },
  "expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by thi
s policy, in format <quantity><units>, where <quantity> is a positive integer less t
han 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1
hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
  }
},
"enabled": {
  "description": "Whether snapshot taking is enabled for this policy (defaults t
o true)",
  "type": "boolean"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshots_policy_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for the snapshot policy",
      "type": "number"
    },
  },
}

```



```

"name": {
  "description": "Name of the snapshot policy",
  "type": "string"
},
"source_file_ids": {
  "type": "array",
  "items": {
    "description": "File ID of the directory on which to take snapshots under the policy. The array must contain exactly one file ID and cannot be modified after policy creation.",
    "type": "string"
  }
},
"schedules": {
  "type": "array",
  "items": {
    "description": "Schedule by which to take snapshots for the policy. The array must contain exactly one schedule.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
        "type": "number"
      },
      "creation_schedule": {
        "description": "Structure defining when to take snapshots",
        "type": "object",
        "properties": {
          "timezone": {
            "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
            "type": "string"
          },
          "frequency": {
            "type": "string",
            "enum": [
              "SCHEDULE_MONTHLY",
              "SCHEDULE_DAILY_OR_WEEKLY",
              "SCHEDULE_HOURLY_OR_LESS"
            ],
            "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
          }
        }
      }
    }
  }
}

```

```

    "hour": {
      "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
      "type": "number"
    },
    "minute": {
      "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
      "type": "number"
    },
    "on_days": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SUNDAY",
          "MONDAY",
          "TUESDAY",
          "WEDNESDAY",
          "THURSDAY",
          "FRIDAY",
          "SATURDAY"
        ]
      },
      "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
      "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
      "type": "number"
    },
    "window_start_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_start_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
      "type": "number"
    }
  }

```

```

    },
    "window_end_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots",
      "type": "number"
    },
    "window_end_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
      "type": "number"
    },
    "fire_every_interval": {
      "type": "string",
      "enum": [
        "FIRE_IN_MINUTES",
        "FIRE_IN_HOURS"
      ],
      "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
      "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
      "type": "number"
    }
  },
  "expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1 hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
  }
},
"enabled": {
  "description": "Whether snapshot taking is enabled for this policy (defaults to true)",
  "type": "boolean"
}
}

```

snapshots/total-used-capacity

Endpoint

/v1/snapshots/total-used-capacity

GET

Returns approximate amount of space that would be reclaimed if all snapshots were deleted.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_capacity_used",
  "type": "object",
  "properties": {
    "bytes": {
      "description": "bytes",
      "type": "string"
    }
  }
}
```

snapshots/{id}

Endpoint

/v1/snapshots/{id}

GET

Returns information about a specific snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
```

```

    "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
    "type": "string"
  },
  "source_path": {
    "description": "Source directory of the snapshot",
    "type": "string"
  },
  "created_by_policy": {
    "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
    "type": "boolean"
  },
  "expiration": {
    "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  }
}
}

```

PUT

Modifies a snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_snapshot_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    }
  }
}

```

```

    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_path": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
```

```

"description": "api_snapshot_info_v1",
"type": "object",
"properties": {
  "id": {
    "description": "Unique identifier of the snapshot",
    "type": "number"
  },
  "name": {
    "description": "Name of the snapshot",
    "type": "string"
  },
  "timestamp": {
    "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  },
  "directory_name": {
    "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
    "type": "string"
  },
  "source_path": {
    "description": "Source directory of the snapshot",
    "type": "string"
  },
  "created_by_policy": {
    "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
    "type": "boolean"
  },
  "expiration": {
    "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  }
}
}

```

DELETE

Deletes a snapshot.

Parameters

Name	Description	Required
<code>id</code>	Snapshot identifier	Yes

Response

Codes

Code	Description
200	Return value on success

PATCH

Modifies a snapshot.

Parameters

Name	Description	Required
<code>id</code>	Snapshot identifier	Yes
<code>expiration-time-to-live</code>	Duration after which to expire the snapshot, in format , where is a positive integer less than 1000 and is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates the snapshot should never expire. Defaults to never if not specified.	No
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_snapshot_info_v1",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    }
  }
}
```

```

    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_path": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshot_info_v1",
  "type": "object",
  "properties": {
    "id": {

```

```

    "description": "Unique identifier of the snapshot",
    "type": "number"
  },
  "name": {
    "description": "Name of the snapshot",
    "type": "string"
  },
  "timestamp": {
    "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  },
  "directory_name": {
    "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
    "type": "string"
  },
  "source_path": {
    "description": "Source directory of the snapshot",
    "type": "string"
  },
  "created_by_policy": {
    "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
    "type": "boolean"
  },
  "expiration": {
    "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  }
}

```

snapshots/

Endpoint

/v2/snapshots/

GET

Returns information about all snapshots.

Parameters

Name	Description	Required
<code>include-in-delete</code>	Specifies whether or not to include snapshots that are currently being deleted. Defaults to false if not specified.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshots_v2",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of snapshot information",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique identifier of the snapshot",
            "type": "number"
          },
          "name": {
            "description": "Name of the snapshot",
            "type": "string"
          }
        }
      }
    }
  }
}
```

```

    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_file_id": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "in_delete": {
      "description": "Whether or not the snapshot is in the process of being deleted",
      "type": "boolean"
    }
  }
}

```

POST

Creates a new snapshot and returns its details.

Parameters

Name	Description	Required
------	-------------	----------

expiration-time-to-live	Duration after which to expire the snapshot, in format , where is a positive integer less than 1000 and is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates the snapshot should never expire. Defaults to never if not specified.	No
--------------------------------	--	----

Request

Schema

```
{
  "description": "api_snapshot_create_v2",
  "type": "object",
  "properties": {
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "source_file_id": {
      "description": "ID of directory to snapshot.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_info_v2",
  "type": "object",
  "properties": {
```

```

    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_file_id": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "in_delete": {
      "description": "Whether or not the snapshot is in the process of being deleted",
      "type": "boolean"
    }
  }
}

```

snapshots/policies/

Endpoint

/v2/snapshots/policies/

GET

Returns information about all snapshot policies.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_policies_v2",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of snapshot policy information",
        "type": "object",
        "properties": {
          "id": {
            "description": "The unique identifier for the snapshot policy.",
            "type": "number"
          },
          "policy_name": {
            "description": "The snapshot policy name.",
            "type": "string"
          },
          "snapshot_name_template": {
            "description": "The naming template for the snapshots that this policy creates.",
            "type": "string"
          }
        }
      }
    }
  }
}
```



```

    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
          "type": "number"
        },
        "creation_schedule": {
          "description": "Structure defining when to take snapshots",
          "type": "object",
          "properties": {
            "timezone": {
              "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
              "type": "string"
            },
            "frequency": {
              "type": "string",
              "enum": [
                "SCHEDULE_MONTHLY",
                "SCHEDULE_DAILY_OR_WEEKLY",
                "SCHEDULE_HOURLY_OR_LESS"
              ],
              "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
            },
            "hour": {
              "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
              "type": "number"
            },
            "minute": {
              "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
              "type": "number"
            }
          }
        }
      }
    }
  }

```

```

    },
    "on_days": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SUNDAY",
          "MONDAY",
          "TUESDAY",
          "WEDNESDAY",
          "THURSDAY",
          "FRIDAY",
          "SATURDAY"
        ]
      },
      "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    }
  },
  "day_of_month": {
    "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
    "type": "number"
  },
  "window_start_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
    "type": "number"
  },
  "window_start_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
    "type": "number"
  },
  "window_end_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
    "type": "number"
  },
  "window_end_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",

```

```

        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
        "type": "number"
    }
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this policy.",
    "type": "boolean"
}
}
}
}
}
}
}
}

```

POST

Creates a new snapshot policy and returns its information.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_snapshot_policy_create_v2",
  "type": "object",
  "properties": {
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for snapshots that this policy creates. If null, Qumulo Core chooses {ID}_{Policy} or {ID}_{Policy}_{Directory}.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
          "type": "number"
        },
        "creation_schedule": {
          "description": "Structure defining when to take snapshots",
          "type": "object",
          "properties": {
            "timezone": {
              "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
              "type": "string"
            },
            "frequency": {
              "type": "string",
              "enum": [
                "SCHEDULE_MONTHLY",
                "SCHEDULE_DAILY_OR_WEEKLY",
                "SCHEDULE_HOURLY_OR_LESS"
              ]
            }
          }
        }
      }
    }
  }
}
```

```

    ],
    "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
  },
  "hour": {
    "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
    "type": "number"
  },
  "minute": {
    "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
    "type": "number"
  },
  "on_days": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "SUNDAY",
        "MONDAY",
        "TUESDAY",
        "WEDNESDAY",
        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
      ]
    }
  },
  "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\n * `FRIDAY` - FRIDAY,\n * `MONDAY` - MONDAY,\n * `SATURDAY` - SATURDAY,\n * `SUNDAY` - SUNDAY,\n * `THURSDAY` - THURSDAY,\n * `TUESDAY` - TUESDAY,\n * `WEDNESDAY` - WEDNESDAY"
  },
  "day_of_month": {
    "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
    "type": "number"
  },
  "window_start_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",

```

```

        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f
or start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for
end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f
or end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINU
TES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOUR
S` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 9
9] at which to take snapshot during specified window",
        "type": "number"
    }
}
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this p
olicy, in format <quantity><units>, where <quantity> is a positive integer less tha
n 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1ho
urs. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Specifies whether snapshot taking is enabled for this policy
(defaults to true).",

```

```

    "type": "boolean"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshot_policy_info_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",

```

```

    "type": "number"
  },
  "creation_schedule": {
    "description": "Structure defining when to take snapshots",
    "type": "object",
    "properties": {
      "timezone": {
        "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
        "type": "string"
      },
      "frequency": {
        "type": "string",
        "enum": [
          "SCHEDULE_MONTHLY",
          "SCHEDULE_DAILY_OR_WEEKLY",
          "SCHEDULE_HOURLY_OR_LESS"
        ],
        "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
      },
      "hour": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
        "type": "number"
      },
      "minute": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
        "type": "number"
      },
      "on_days": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "SUNDAY",
            "MONDAY",
            "TUESDAY",
            "WEDNESDAY",
            "THURSDAY",
            "FRIDAY",
            "SATURDAY"
          ]
        }
      }
    }
  }
}

```



```

        "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 9

```

```

9] at which to take snapshot during specified window",
    "type": "number"
  }
},
"expiration_time_to_live": {
  "description": "Duration after which to expire snapshots created by this p
olicy, in format <quantity><units>, where <quantity> is a positive integer less tha
n 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1ho
urs. Empty string or never indicates snapshots should never expire.",
  "type": "string"
}
},
"enabled": {
  "description": "Specifies whether taking snapshots is enabled for this polic
y.",
  "type": "boolean"
}
}

```

snapshots/policies/status/

Endpoint

/v2/snapshots/policies/status/

GET

Returns status information about all snapshot policies. A policy status includes non-configurable policy information.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "snapshots_api_policy_statuses_v2",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "The list of snapshot policy statuses.",
        "type": "object",
        "properties": {
          "id": {
            "description": "The unique identifier for the snapshot policy.",
            "type": "number"
          },
          "policy_name": {
            "description": "The snapshot policy name.",
            "type": "string"
          },
          "snapshot_name_template": {
            "description": "The naming template for the snapshots that this policy c
reated.",

```

```

    "type": "string"
  },
  "source_file_id": {
    "description": "The source file ID of the directory to snapshot under the policy.",
    "type": "string"
  },
  "source_file_path": {
    "description": "The snapshot source directory (if available).",
    "type": "string"
  },
  "schedule": {
    "description": "The schedule according to which to take snapshots for the policy.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
        "type": "number"
      },
      "creation_schedule": {
        "description": "Structure defining when to take snapshots",
        "type": "object",
        "properties": {
          "timezone": {
            "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
            "type": "string"
          },
          "frequency": {
            "type": "string",
            "enum": [
              "SCHEDULE_MONTHLY",
              "SCHEDULE_DAILY_OR_WEEKLY",
              "SCHEDULE_HOURLY_OR_LESS"
            ],
            "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
          },
          "hour": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
            "type": "number"
          }
        }
      }
    }
  }
}

```

```

    },
    "minute": {
      "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
      "type": "number"
    },
    "on_days": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SUNDAY",
          "MONDAY",
          "TUESDAY",
          "WEDNESDAY",
          "THURSDAY",
          "FRIDAY",
          "SATURDAY"
        ]
      },
      "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
      "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
      "type": "number"
    },
    "window_start_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_start_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_end_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",

```

```

        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour
[0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
        "type": "number"
    }
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this policy.",
    "type": "boolean"
},
"owners": {
    "type": "array",
    "items": {
        "description": "The snapshot policy's owners. While there are entries on this list, the policy can't be deleted or modified.",
        "type": "object",
        "properties": {
            "id": {

```

```
        "description": "id",  
        "type": "string"  
    }  
    }  
    }  
    }  
    }  
    }  
    }  
    }  
    }  
    }
```

snapshots/policies/status/{id}

Endpoint

/v2/snapshots/policies/status/{id}

GET

Returns status information about a specific snapshot policy.

Parameters

Name	Description	Required
id	Policy identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "snapshots_api_policy_status_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy."
    }
  }
}
```



```

icy.",
  "type": "string"
},
"source_file_path": {
  "description": "The snapshot source directory (if available).",
  "type": "string"
},
"schedule": {
  "description": "The schedule according to which to take snapshots for the policy.",
  "type": "object",
  "properties": {
    "id": {
      "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
      "type": "number"
    },
    "creation_schedule": {
      "description": "Structure defining when to take snapshots",
      "type": "object",
      "properties": {
        "timezone": {
          "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
          "type": "string"
        },
        "frequency": {
          "type": "string",
          "enum": [
            "SCHEDULE_MONTHLY",
            "SCHEDULE_DAILY_OR_WEEKLY",
            "SCHEDULE_HOURLY_OR_LESS"
          ],
          "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
        },
        "hour": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
          "type": "number"
        },
        "minute": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",

```

```

        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ],
            "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
        }
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f

```

```

or end of window during which to take snapshots",
    "type": "number"
},
"fire_every_interval": {
    "type": "string",
    "enum": [
        "FIRE_IN_MINUTES",
        "FIRE_IN_HOURS"
    ],
    "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
},
"fire_every": {
    "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
    "type": "number"
}
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this policy.",
    "type": "boolean"
},
"owners": {
    "type": "array",
    "items": {
        "description": "The snapshot policy's owners. While there are entries on this list, the policy can't be deleted or modified.",
        "type": "object",
        "properties": {
            "id": {
                "description": "id",
                "type": "string"
            }
        }
    }
}

```

```
}  
}  
}
```

snapshots/policies/{id}

Endpoint

/v2/snapshots/policies/{id}

GET

Returns information about a specific snapshot policy.

Parameters

Name	Description	Required
id	Snapshot Policy Identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_policy_info_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy."
    }
  }
}
```

```

icy.",
  "type": "string"
},
"schedule": {
  "description": "The schedule according to which to take snapshots under this policy.",
  "type": "object",
  "properties": {
    "id": {
      "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
      "type": "number"
    },
    "creation_schedule": {
      "description": "Structure defining when to take snapshots",
      "type": "object",
      "properties": {
        "timezone": {
          "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
          "type": "string"
        },
        "frequency": {
          "type": "string",
          "enum": [
            "SCHEDULE_MONTHLY",
            "SCHEDULE_DAILY_OR_WEEKLY",
            "SCHEDULE_HOURLY_OR_LESS"
          ],
          "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
        },
        "hour": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
          "type": "number"
        },
        "minute": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
          "type": "number"
        },
        "on_days": {
          "type": "array",

```

```

    "items": {
      "type": "string",
      "enum": [
        "SUNDAY",
        "MONDAY",
        "TUESDAY",
        "WEDNESDAY",
        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
      ],
      "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
      "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
      "type": "number"
    },
    "window_start_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_start_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_end_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
      "type": "number"
    },
    "window_end_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
      "type": "number"
    },
    "fire_every_interval": {

```

```

        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
        "type": "number"
    }
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this policy.",
    "type": "boolean"
}
}
}

```

PUT

Modifies a snapshot policy.

Parameters

Name	Description	Required
id	Snapshot Policy Identifier	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_snapshot_policy_info_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
          "type": "number"
        },
        "creation_schedule": {
          "description": "Structure defining when to take snapshots",
          "type": "object",
          "properties": {
            "timezone": {
              "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
              "type": "string"
            },
            "frequency": {
              "type": "string",
            }
          }
        }
      }
    }
  }
}
```

```

    "enum": [
        "SCHEDULE_MONTHLY",
        "SCHEDULE_DAILY_OR_WEEKLY",
        "SCHEDULE_HOURLY_OR_LESS"
    ],
    "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY",
    },
    "hour": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
        "type": "number"
    },
    "minute": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ],
            "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\n * `FRIDAY` - FRIDAY,\n * `MONDAY` - MONDAY,\n * `SATURDAY` - SATURDAY,\n * `SUNDAY` - SUNDAY,\n * `THURSDAY` - THURSDAY,\n * `TUESDAY` - TUESDAY,\n * `WEDNESDAY` - WEDNESDAY"
        }
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    }
}

```

```

    },
    "window_start_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for
start of window during which to take snapshots",
      "type": "number"
    },
    "window_start_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f
or start of window during which to take snapshots",
      "type": "number"
    },
    "window_end_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for
end of window during which to take snapshots)",
      "type": "number"
    },
    "window_end_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f
or end of window during which to take snapshots",
      "type": "number"
    },
    "fire_every_interval": {
      "type": "string",
      "enum": [
        "FIRE_IN_MINUTES",
        "FIRE_IN_HOURS"
      ],
      "description": "For HOURLY_OR_LESS frequency: units for interval (MINU
TES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOU
RS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
      "description": "For HOURLY_OR_LESS frequency: value for interval [1, 9
9] at which to take snapshot during specified window",
      "type": "number"
    }
  },
  "expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this p
olicy, in format <quantity><units>, where <quantity> is a positive integer less tha
n 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1ho
urs. Empty string or never indicates snapshots should never expire.",
    "type": "string"
  }
}

```

```

    },
    "enabled": {
      "description": "Specifies whether taking snapshots is enabled for this policy.",
      "type": "boolean"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshot_policy_info_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",

```

```

"properties": {
  "id": {
    "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
    "type": "number"
  },
  "creation_schedule": {
    "description": "Structure defining when to take snapshots",
    "type": "object",
    "properties": {
      "timezone": {
        "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
        "type": "string"
      },
      "frequency": {
        "type": "string",
        "enum": [
          "SCHEDULE_MONTHLY",
          "SCHEDULE_DAILY_OR_WEEKLY",
          "SCHEDULE_HOURLY_OR_LESS"
        ],
        "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
      },
      "hour": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
        "type": "number"
      },
      "minute": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
        "type": "number"
      },
      "on_days": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "SUNDAY",
            "MONDAY",
            "TUESDAY",
            "WEDNESDAY",

```

```

        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
    ],
    "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\\n * `FIRE_IN_HOUR

```

```

S` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
      "description": "For HOURLY_OR_LESS frequency: value for interval [1, 9
9] at which to take snapshot during specified window",
      "type": "number"
    }
  },
  "expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this p
olicy, in format <quantity><units>, where <quantity> is a positive integer less tha
n 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1ho
urs. Empty string or never indicates snapshots should never expire.",
    "type": "string"
  }
},
"enabled": {
  "description": "Specifies whether taking snapshots is enabled for this polic
y.",
  "type": "boolean"
}
}
}

```

DELETE

Deletes a snapshot policy.

Parameters

Name	Description	Required
id	Snapshot Policy Identifier	Yes
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

Modifies a snapshot policy.

Parameters

Name	Description	Required
<code>id</code>	Snapshot Policy Identifier	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_snapshot_policy_info_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",

```



```

    "type": "number"
  },
  "creation_schedule": {
    "description": "Structure defining when to take snapshots",
    "type": "object",
    "properties": {
      "timezone": {
        "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
        "type": "string"
      },
      "frequency": {
        "type": "string",
        "enum": [
          "SCHEDULE_MONTHLY",
          "SCHEDULE_DAILY_OR_WEEKLY",
          "SCHEDULE_HOURLY_OR_LESS"
        ],
        "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
      },
      "hour": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
        "type": "number"
      },
      "minute": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
        "type": "number"
      },
      "on_days": {
        "type": "array",
        "items": {
          "type": "string",
          "enum": [
            "SUNDAY",
            "MONDAY",
            "TUESDAY",
            "WEDNESDAY",
            "THURSDAY",
            "FRIDAY",
            "SATURDAY"
          ]
        }
      }
    }
  }
}

```

```

        "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 9

```

```

9] at which to take snapshot during specified window",
    "type": "number"
  }
},
"expiration_time_to_live": {
  "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
  "type": "string"
}
},
"enabled": {
  "description": "Specifies whether taking snapshots is enabled for this policy.",
  "type": "boolean"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshot_policy_info_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {

```

```

    "description": "The naming template for the snapshots that this policy creates.",
    "type": "string"
  },
  "source_file_id": {
    "description": "The source file ID of the directory to snapshot under this policy.",
    "type": "string"
  },
  "schedule": {
    "description": "The schedule according to which to take snapshots under this policy.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
        "type": "number"
      },
      "creation_schedule": {
        "description": "Structure defining when to take snapshots",
        "type": "object",
        "properties": {
          "timezone": {
            "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
            "type": "string"
          },
          "frequency": {
            "type": "string",
            "enum": [
              "SCHEDULE_MONTHLY",
              "SCHEDULE_DAILY_OR_WEEKLY",
              "SCHEDULE_HOURLY_OR_LESS"
            ],
            "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
          },
          "hour": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
            "type": "number"
          },
          "minute": {

```

```

        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ]
        },
        "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\\n * `FRIDAY` - FRIDAY,\\n * `MONDAY` - MONDAY,\\n * `SATURDAY` - SATURDAY,\\n * `SUNDAY` - SUNDAY,\\n * `THURSDAY` - THURSDAY,\\n * `TUESDAY` - TUESDAY,\\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },

```

```

        "window_end_minute": {
            "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f
or end of window during which to take snapshots",
            "type": "number"
        },
        "fire_every_interval": {
            "type": "string",
            "enum": [
                "FIRE_IN_MINUTES",
                "FIRE_IN_HOURS"
            ],
            "description": "For HOURLY_OR_LESS frequency: units for interval (MINU
TES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOUR
S` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
        },
        "fire_every": {
            "description": "For HOURLY_OR_LESS frequency: value for interval [1, 9
9] at which to take snapshot during specified window",
            "type": "number"
        }
    },
    "expiration_time_to_live": {
        "description": "Duration after which to expire snapshots created by this p
olicy, in format <quantity><units>, where <quantity> is a positive integer less tha
n 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1ho
urs. Empty string or never indicates snapshots should never expire.",
        "type": "string"
    }
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this polic
y.",
    "type": "boolean"
}
}

```

snapshots/status/

Endpoint

/v2/snapshots/status/

GET

Returns the status on all snapshots.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_statuses_v2",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of snapshot status information",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique identifier of the snapshot",
            "type": "number"
          },
          "name": {
            "description": "Name of the snapshot",
            "type": "string"
          },
          "timestamp": {
            "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
            "type": "string"
          }
        }
      }
    }
  }
}
```

```

        "type": "string"
    },
    "directory_name": {
        "description": "Snapshot directory name, as would be seen in the .snapsh
ot directory over SMB or NFS.",
        "type": "string"
    },
    "source_file_id": {
        "description": "File ID of the snapshot source directory",
        "type": "string"
    },
    "source_file_path": {
        "description": "File path of the snapshot source directory",
        "type": "string"
    },
    "created_by_policy": {
        "description": "This snapshot was created by a policy. The name of that
policy will be stored in the name field in place of a user-defined name.",
        "type": "boolean"
    },
    "expiration": {
        "description": "Time at which snapshot will be expired. Empty string if
no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 860
1. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
        "type": "string"
    },
    "owners": {
        "type": "array",
        "items": {
            "description": "Owners of this snapshot. The snapshot cannot be delete
d or modified while the list is non-empty.",
            "type": "object",
            "properties": {
                "id": {
                    "description": "id",
                    "type": "string"
                }
            }
        }
    }
}

```


snapshots/status/{id}

Endpoint

/v2/snapshots/status/{id}

GET

Returns the status on a snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_status_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
```

```

    "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
    "type": "string"
  },
  "source_file_id": {
    "description": "File ID of the snapshot source directory",
    "type": "string"
  },
  "source_file_path": {
    "description": "File path of the snapshot source directory",
    "type": "string"
  },
  "created_by_policy": {
    "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
    "type": "boolean"
  },
  "expiration": {
    "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  },
  "owners": {
    "type": "array",
    "items": {
      "description": "Owners of this snapshot. The snapshot cannot be deleted or modified while the list is non-empty.",
      "type": "object",
      "properties": {
        "id": {
          "description": "id",
          "type": "string"
        }
      }
    }
  }
}

```

snapshots/{id}

Endpoint

/v2/snapshots/{id}

GET

Returns information about a specific snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_info_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
```

```

    "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
    "type": "string"
  },
  "source_file_id": {
    "description": "Source directory of the snapshot",
    "type": "string"
  },
  "created_by_policy": {
    "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
    "type": "boolean"
  },
  "expiration": {
    "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  },
  "in_delete": {
    "description": "Whether or not the snapshot is in the process of being deleted",
    "type": "boolean"
  }
}

```

PUT

Modifies a snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_snapshot_info_v2",

```

```

"type": "object",
"properties": {
  "id": {
    "description": "Unique identifier of the snapshot",
    "type": "number"
  },
  "name": {
    "description": "Name of the snapshot",
    "type": "string"
  },
  "timestamp": {
    "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  },
  "directory_name": {
    "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
    "type": "string"
  },
  "source_file_id": {
    "description": "Source directory of the snapshot",
    "type": "string"
  },
  "created_by_policy": {
    "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
    "type": "boolean"
  },
  "expiration": {
    "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
    "type": "string"
  },
  "in_delete": {
    "description": "Whether or not the snapshot is in the process of being deleted",
    "type": "boolean"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_info_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_file_id": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    }
  }
}
```

```

    "type": "string"
  },
  "in_delete": {
    "description": "Whether or not the snapshot is in the process of being delete
d",
    "type": "boolean"
  }
}
}
}

```

DELETE

Deletes a snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes

Response

Codes

Code	Description
200	Return value on success

PATCH

Modifies a snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes
expiration-time-to-live	Duration after which to expire the snapshot, in format , where is a positive integer less than 1000 and is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates the snapshot should never expire. Defaults to never if not specified.	No
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_snapshot_info_v2",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier of the snapshot",
      "type": "number"
    },
    "name": {
      "description": "Name of the snapshot",
      "type": "string"
    },
    "timestamp": {
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "directory_name": {
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "source_file_id": {
      "description": "Source directory of the snapshot",
      "type": "string"
    },
    "created_by_policy": {
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",
      "type": "boolean"
    },
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "in_delete": {
      "description": "Whether or not the snapshot is in the process of being deleted",
      "type": "boolean"
    }
  }
}
```



```
}  
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{  
  "description": "api_snapshot_info_v2",  
  "type": "object",  
  "properties": {  
    "id": {  
      "description": "Unique identifier of the snapshot",  
      "type": "number"  
    },  
    "name": {  
      "description": "Name of the snapshot",  
      "type": "string"  
    },  
    "timestamp": {  
      "description": "Creation timestamp of the snapshot, encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",  
      "type": "string"  
    },  
    "directory_name": {  
      "description": "Snapshot directory name, as would be seen in the .snapshot directory over SMB or NFS.",  
      "type": "string"  
    },  
    "source_file_id": {  
      "description": "Source directory of the snapshot",  
      "type": "string"  
    },  
    "created_by_policy": {  
      "description": "This snapshot was created by a policy. The name of that policy will be stored in the name field in place of a user-defined name.",  
      "type": "boolean"  
    },  
  },  
}
```

```
    "expiration": {
      "description": "Time at which snapshot will be expired. Empty string if no expiration time set. Encoded as RFC 3339, which is a normalized subset of ISO 8601. See http://tools.ietf.org/rfc/rfc3339.txt, section 5.6 for ABNF.",
      "type": "string"
    },
    "in_delete": {
      "description": "Whether or not the snapshot is in the process of being deleted",
      "type": "boolean"
    }
  }
}
```

snapshots/{newer_id}/changes-since/{older_id}

Endpoint

/v2/snapshots/{newer_id}/changes-since/{older_id}

GET

Returns a list of changed files and directories between two snapshots.

Parameters

Name	Description	Required
<code>newer_id</code>	Newer snapshot	Yes
<code>older_id</code>	Older snapshot	Yes
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_tree_diff",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
```

```

    "description": "entries",
    "type": "object",
    "properties": {
      "op": {
        "type": "string",
        "enum": [
          "CREATE",
          "MODIFY",
          "DELETE"
        ],
        "description": "op:\n * `CREATE` - API_SNAPSHOT_TREE_DIFF_OP_CREATE,\n * `DELETE` - API_SNAPSHOT_TREE_DIFF_OP_DELETE,\n * `MODIFY` - API_SNAPSHOT_TREE_DIF\nF_OP_MODIFY"
      },
      "path": {
        "description": "path",
        "type": "string"
      }
    }
  }
}
}
}
}

```

snapshots/{newer_id}/changes-since/{older_id}/files/{ref}

Endpoint

/v2/snapshots/{newer_id}/changes-since/{older_id}/files/{ref}

GET

Returns the byte ranges of a file whose contents differ between two snapshots. Each entry's `type` field reports what's in the newer snapshot at that range: DATA or HOLE.

Parameters

Name	Description	Required
newer_id	Newer snapshot	Yes
older_id	Older snapshot	Yes
ref	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
after	Return entries after the given key (keys are returned in the paging object)	No
limit	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_file_diff_v2",
```

```

"type": "object",
"properties": {
  "entries": {
    "type": "array",
    "items": {
      "description": "entries",
      "type": "object",
      "properties": {
        "type": {
          "type": "string",
          "enum": [
            "FILE_REGION_DATA",
            "FILE_REGION_HOLE"
          ],
          "description": "The type of content in the changed region of the file i
n the newer snapshot. The region may contain either data a hole.:\\n * `FILE_REGION_D
ATA` - FILE_REGION_DATA,\\n * `FILE_REGION_HOLE` - FILE_REGION_HOLE"
        },
        "offset": {
          "description": "The starting offset of the changed region in bytes.",
          "type": "string"
        },
        "size": {
          "description": "The size of the changed region in bytes.",
          "type": "string"
        }
      }
    }
  }
}

```

snapshots/

Endpoint

/v3/snapshots/

GET

Returns information about all snapshots.

Parameters

Name	Description	Required
filter	Filter the list of snapshots to exclude snapshots in process of being deleted, or include only snapshots in process of being deleted. By default, includes all snapshots.: * `all` - all, * `exclude_in_delete` - exclude_in_delete, * `only_in_delete` - only_in_delete	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshots",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of snapshot information",
        "type": "object",
        "properties": {
          "id": {
            "description": "The unique snapshot identifier.",
            "type": "number"
          },
          "name": {
            "description": "The snapshot name as it appears in the .snapshot directo
```

```
ry over SMB or NFS.",
    "type": "string"
},
"timestamp": {
    "description": "The snapshot creation timestamp, encoded as RFC 3339, a normalized subset of ISO 8601.",
    "type": "string"
},
"source_file_id": {
    "description": "The source file ID of the directory for the snapshot.",
    "type": "string"
},
"policy_id": {
    "description": "The policy ID from which this snapshot was created, or null if this snapshot was created manually.",
    "type": "number"
},
"expiration": {
    "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
    "type": "string"
},
"in_delete": {
    "description": "Specifies whether the snapshot is in the process of being deleted.",
    "type": "boolean"
}
}
}
}
```

POST

Creates a new snapshot and returns snapshot information.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_snapshot_create",
  "type": "object",
  "properties": {
    "name_suffix": {
      "description": "The snapshot name. Qumulo Core prepends the snapshot ID to the name. If not provided, Qumulo Core uses the value OnDemand.",
      "type": "string"
    },
    "expiration": {
      "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The ID of the directory to snapshot.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique snapshot identifier.",
      "type": "number"
    },
    "name": {
      "description": "The snapshot name as it appears in the .snapshot directory over"
    }
  }
}
```

```

r SMB or NFS.",
  "type": "string"
},
"timestamp": {
  "description": "The snapshot creation timestamp, encoded as RFC 3339, a normalized subset of ISO 8601.",
  "type": "string"
},
"source_file_id": {
  "description": "The source file ID of the directory for the snapshot.",
  "type": "string"
},
"policy_id": {
  "description": "The policy ID from which this snapshot was created, or null if this snapshot was created manually.",
  "type": "number"
},
"expiration": {
  "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
  "type": "string"
},
"in_delete": {
  "description": "Specifies whether the snapshot is in the process of being deleted.",
  "type": "boolean"
}
}
}

```

snapshots/policies/

Endpoint

/v3/snapshots/policies/

GET

Returns information about all snapshot policies.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_policies",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of snapshot policy information",
        "type": "object",
        "properties": {
          "id": {
            "description": "The unique identifier for the snapshot policy.",
            "type": "number"
          },
          "policy_name": {
            "description": "The snapshot policy name.",
            "type": "string"
          },
          "snapshot_name_template": {
            "description": "The naming template for the snapshots that this policy creates.",
            "type": "string"
          }
        }
      }
    }
  }
}
```

```

    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
          "type": "number"
        },
        "creation_schedule": {
          "description": "Structure defining when to take snapshots",
          "type": "object",
          "properties": {
            "timezone": {
              "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
              "type": "string"
            },
            "frequency": {
              "type": "string",
              "enum": [
                "SCHEDULE_MONTHLY",
                "SCHEDULE_DAILY_OR_WEEKLY",
                "SCHEDULE_HOURLY_OR_LESS"
              ],
              "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
            },
            "hour": {
              "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
              "type": "number"
            },
            "minute": {
              "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
              "type": "number"
            }
          }
        }
      }
    }
  }

```

```

    },
    "on_days": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SUNDAY",
          "MONDAY",
          "TUESDAY",
          "WEDNESDAY",
          "THURSDAY",
          "FRIDAY",
          "SATURDAY"
        ]
      },
      "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    }
  },
  "day_of_month": {
    "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
    "type": "number"
  },
  "window_start_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
    "type": "number"
  },
  "window_start_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
    "type": "number"
  },
  "window_end_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
    "type": "number"
  },
  "window_end_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",

```


Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_snapshot_policy_create",
  "type": "object",
  "properties": {
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates. If set to null, Qumulo Core uses {ID}_{Policy} for root directories and {ID}_{Policy}_{Directory} for all other directory types.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
          "type": "number"
        },
        "creation_schedule": {
          "description": "Structure defining when to take snapshots",
          "type": "object",
          "properties": {
            "timezone": {
              "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
              "type": "string"
            },
            "frequency": {
```

```

        "type": "string",
        "enum": [
            "SCHEDULE_MONTHLY",
            "SCHEDULE_DAILY_OR_WEEKLY",
            "SCHEDULE_HOURLY_OR_LESS"
        ],
        "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
    },
    "hour": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
        "type": "number"
    },
    "minute": {
        "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ],
        },
        "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\n * `FRIDAY` - FRIDAY,\n * `MONDAY` - MONDAY,\n * `SATURDAY` - SATURDAY,\n * `SUNDAY` - SUNDAY,\n * `THURSDAY` - THURSDAY,\n * `TUESDAY` - TUESDAY,\n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
    },

```



```

        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for
start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f
or start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for
end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f
or end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINU
TES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOU
RS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 9
9] at which to take snapshot during specified window",
        "type": "number"
    }
}
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this p
olicy, in format <quantity><units>, where <quantity> is a positive integer less tha
n 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1ho
urs. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
}

```

```

    }
  },
  "enabled": {
    "description": "Specifies whether snapshot taking is enabled for this policy. Taking snapshots is enabled by default.",
    "type": "boolean"
  },
  "lock_key_ref": {
    "description": "If not set to null, the system uses the specified identifier to create locked snapshots under this policy.",
    "type": "string"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshot_policy_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",

```

```

    "type": "string"
  },
  "schedule": {
    "description": "The schedule according to which to take snapshots under this p
olicy.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Identifier for the snapshot policy's schedule. Only uniqu
e within the scope of a snapshot policy.",
        "type": "number"
      },
      "creation_schedule": {
        "description": "Structure defining when to take snapshots",
        "type": "object",
        "properties": {
          "timezone": {
            "description": "The time zone in which the schedule should be interpre
ted (e.g. America/Los_Angeles or UTC).",
            "type": "string"
          },
          "frequency": {
            "type": "string",
            "enum": [
              "SCHEDULE_MONTHLY",
              "SCHEDULE_DAILY_OR_WEEKLY",
              "SCHEDULE_HOURLY_OR_LESS"
            ],
            "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURL
Y_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAIL
Y_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDUL
E_MONTHLY` - SCHEDULE_MONTHLY"
          },
          "hour": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day
[0, 23] at which to take snapshot",
            "type": "number"
          },
          "minute": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of ho
ur [0, 59] at which to take snapshot",
            "type": "number"
          },
          "on_days": {
            "type": "array",
            "items": {

```

```

        "type": "string",
        "enum": [
            "SUNDAY",
            "MONDAY",
            "TUESDAY",
            "WEDNESDAY",
            "THURSDAY",
            "FRIDAY",
            "SATURDAY"
        ],
        "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",

```

```

        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
        "type": "number"
    }
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this policy.",
    "type": "boolean"
},
"lock_key_ref": {
    "description": "If non-empty, snapshots taken for this policy will be locked with the given id.",
    "type": "string"
}
}
}

```

snapshots/policies/status/

Endpoint

/v3/snapshots/policies/status/

GET

Returns status information about all snapshot policies. A policy status includes non-configurable policy information.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "snapshots_api_policy_statuses",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "The list of snapshot policy statuses.",
        "type": "object",
        "properties": {
          "id": {
            "description": "The unique identifier for the snapshot policy.",
            "type": "number"
          },
          "policy_name": {
            "description": "The snapshot policy name.",
            "type": "string"
          },
          "snapshot_name_template": {
            "description": "The naming template for the snapshots that this policy c
reated.",

```

```

    "type": "string"
  },
  "source_file_id": {
    "description": "The source file ID of the directory to snapshot under the policy.",
    "type": "string"
  },
  "source_file_path": {
    "description": "The snapshot source directory (if available).",
    "type": "string"
  },
  "schedule": {
    "description": "The schedule according to which to take snapshots for the policy.",
    "type": "object",
    "properties": {
      "id": {
        "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
        "type": "number"
      },
      "creation_schedule": {
        "description": "Structure defining when to take snapshots",
        "type": "object",
        "properties": {
          "timezone": {
            "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
            "type": "string"
          },
          "frequency": {
            "type": "string",
            "enum": [
              "SCHEDULE_MONTHLY",
              "SCHEDULE_DAILY_OR_WEEKLY",
              "SCHEDULE_HOURLY_OR_LESS"
            ],
            "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
          },
          "hour": {
            "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
            "type": "number"
          }
        }
      }
    }
  }
}

```

```

    },
    "minute": {
      "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
      "type": "number"
    },
    "on_days": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SUNDAY",
          "MONDAY",
          "TUESDAY",
          "WEDNESDAY",
          "THURSDAY",
          "FRIDAY",
          "SATURDAY"
        ]
      },
      "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
      "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
      "type": "number"
    },
    "window_start_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_start_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_end_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",

```



```

        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour
[0, 59] for end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
        "type": "number"
    }
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this policy.",
    "type": "boolean"
},
"lock_key": {
    "description": "If not set to null, the system uses the specified identifier to create locked snapshots under this policy.",
    "type": "string"
},
"owners": {
    "type": "array",
    "items": {

```

```
        "description": "The snapshot policy's owners. While there are entries  
on this list, the policy can't be deleted or modified.",  
        "type": "object",  
        "properties": {  
            "id": {  
                "description": "id",  
                "type": "string"  
            }  
        }  
    }  
}  
}  
}  
}  
}  
}  
}
```

snapshots/policies/status/{id}

Endpoint

/v3/snapshots/policies/status/{id}

GET

Returns status information about a specific snapshot policy.

Parameters

Name	Description	Required
id	Policy identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "snapshots_api_policy_status",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy."
    }
  }
}
```

```

icy.",
  "type": "string"
},
"source_file_path": {
  "description": "The snapshot source directory (if available).",
  "type": "string"
},
"schedule": {
  "description": "The schedule according to which to take snapshots for the policy.",
  "type": "object",
  "properties": {
    "id": {
      "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
      "type": "number"
    },
    "creation_schedule": {
      "description": "Structure defining when to take snapshots",
      "type": "object",
      "properties": {
        "timezone": {
          "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
          "type": "string"
        },
        "frequency": {
          "type": "string",
          "enum": [
            "SCHEDULE_MONTHLY",
            "SCHEDULE_DAILY_OR_WEEKLY",
            "SCHEDULE_HOURLY_OR_LESS"
          ],
          "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
        },
        "hour": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
          "type": "number"
        },
        "minute": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",

```

```

        "type": "number"
    },
    "on_days": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "SUNDAY",
                "MONDAY",
                "TUESDAY",
                "WEDNESDAY",
                "THURSDAY",
                "FRIDAY",
                "SATURDAY"
            ],
            "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
        }
    },
    "day_of_month": {
        "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
        "type": "number"
    },
    "window_start_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_start_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
        "type": "number"
    },
    "window_end_hour": {
        "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
        "type": "number"
    },
    "window_end_minute": {
        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f

```

```

or end of window during which to take snapshots",
    "type": "number"
},
"fire_every_interval": {
    "type": "string",
    "enum": [
        "FIRE_IN_MINUTES",
        "FIRE_IN_HOURS"
    ],
    "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
},
"fire_every": {
    "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
    "type": "number"
}
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this policy.",
    "type": "boolean"
},
"lock_key": {
    "description": "If not set to null, the system uses the specified identifier to create locked snapshots under this policy.",
    "type": "string"
},
"owners": {
    "type": "array",
    "items": {
        "description": "The snapshot policy's owners. While there are entries on this list, the policy can't be deleted or modified.",
        "type": "object",
        "properties": {

```

```
    "id": {  
      "description": "id",  
      "type": "string"  
    }  
  }  
}  
}
```

snapshots/policies/{id}

Endpoint

/v3/snapshots/policies/{id}

GET

Returns information about a specific snapshot policy.

Parameters

Name	Description	Required
id	Snapshot Policy Identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_policy_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy."
    }
  }
}
```



```

icy.",
  "type": "string"
},
"schedule": {
  "description": "The schedule according to which to take snapshots under this policy.",
  "type": "object",
  "properties": {
    "id": {
      "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
      "type": "number"
    },
    "creation_schedule": {
      "description": "Structure defining when to take snapshots",
      "type": "object",
      "properties": {
        "timezone": {
          "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
          "type": "string"
        },
        "frequency": {
          "type": "string",
          "enum": [
            "SCHEDULE_MONTHLY",
            "SCHEDULE_DAILY_OR_WEEKLY",
            "SCHEDULE_HOURLY_OR_LESS"
          ],
          "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
        },
        "hour": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
          "type": "number"
        },
        "minute": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
          "type": "number"
        },
        "on_days": {
          "type": "array",

```

```

    "items": {
      "type": "string",
      "enum": [
        "SUNDAY",
        "MONDAY",
        "TUESDAY",
        "WEDNESDAY",
        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
      ],
      "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    },
    "day_of_month": {
      "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
      "type": "number"
    },
    "window_start_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_start_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_end_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
      "type": "number"
    },
    "window_end_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
      "type": "number"
    },
    "fire_every_interval": {

```

```

        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
        "type": "number"
    }
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this policy.",
    "type": "boolean"
},
"lock_key_ref": {
    "description": "If non-empty, snapshots taken for this policy will be locked with the given id.",
    "type": "string"
}
}
}

```

PUT

Modifies a snapshot policy.

Parameters

Name	Description	Required
------	-------------	----------

id	Snapshot Policy Identifier	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_snapshot_policy_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
          "type": "number"
        },
        "creation_schedule": {
          "description": "Structure defining when to take snapshots",
          "type": "object",
          "properties": {
            "timezone": {
              "description": "The time zone in which the schedule should be interpreted"
            }
          }
        }
      }
    }
  }
}
```

```

ted (e.g. America/Los_Angeles or UTC).",
    "type": "string"
  },
  "frequency": {
    "type": "string",
    "enum": [
      "SCHEDULE_MONTHLY",
      "SCHEDULE_DAILY_OR_WEEKLY",
      "SCHEDULE_HOURLY_OR_LESS"
    ],
    "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
  },
  "hour": {
    "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
    "type": "number"
  },
  "minute": {
    "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
    "type": "number"
  },
  "on_days": {
    "type": "array",
    "items": {
      "type": "string",
      "enum": [
        "SUNDAY",
        "MONDAY",
        "TUESDAY",
        "WEDNESDAY",
        "THURSDAY",
        "FRIDAY",
        "SATURDAY"
      ],
      "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\n * `FRIDAY` - FRIDAY,\n * `MONDAY` - MONDAY,\n * `SATURDAY` - SATURDAY,\n * `SUNDAY` - SUNDAY,\n * `THURSDAY` - THURSDAY,\n * `TUESDAY` - TUESDAY,\n * `WEDNESDAY` - WEDNESDAY"
    }
  }
}

```

```

    },
    "day_of_month": {
      "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
      "type": "number"
    },
    "window_start_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_start_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
      "type": "number"
    },
    "window_end_hour": {
      "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
      "type": "number"
    },
    "window_end_minute": {
      "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",
      "type": "number"
    },
    "fire_every_interval": {
      "type": "string",
      "enum": [
        "FIRE_IN_MINUTES",
        "FIRE_IN_HOURS"
      ],
      "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
      "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
      "type": "number"
    }
  },
  "expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than"
  }
}

```

```

n 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
  }
},
"enabled": {
  "description": "Specifies whether taking snapshots is enabled for this policy.",
  "type": "boolean"
},
"lock_key_ref": {
  "description": "If non-empty, snapshots taken for this policy will be locked with the given id.",
  "type": "string"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshot_policy_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    }
  }
}

```

```

    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
          "type": "number"
        },
        "creation_schedule": {
          "description": "Structure defining when to take snapshots",
          "type": "object",
          "properties": {
            "timezone": {
              "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
              "type": "string"
            },
            "frequency": {
              "type": "string",
              "enum": [
                "SCHEDULE_MONTHLY",
                "SCHEDULE_DAILY_OR_WEEKLY",
                "SCHEDULE_HOURLY_OR_LESS"
              ],
              "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
            },
            "hour": {
              "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
              "type": "number"
            },
            "minute": {
              "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
              "type": "number"
            }
          }
        }
      }
    }
  }

```



```

    },
    "on_days": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SUNDAY",
          "MONDAY",
          "TUESDAY",
          "WEDNESDAY",
          "THURSDAY",
          "FRIDAY",
          "SATURDAY"
        ]
      },
      "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    }
  },
  "day_of_month": {
    "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
    "type": "number"
  },
  "window_start_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
    "type": "number"
  },
  "window_start_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
    "type": "number"
  },
  "window_end_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
    "type": "number"
  },
  "window_end_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for end of window during which to take snapshots",

```

```

        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINUTES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOURS` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 99] at which to take snapshot during specified window",
        "type": "number"
    }
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this policy, in format <quantity><units>, where <quantity> is a positive integer less than 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1hours. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this policy.",
    "type": "boolean"
},
"lock_key_ref": {
    "description": "If non-empty, snapshots taken for this policy will be locked with the given id.",
    "type": "string"
}
}
}

```

DELETE

Deletes a snapshot policy.

Parameters

Name	Description	Required
<code>id</code>	Snapshot Policy Identifier	Yes
<code>If-Match</code>	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

Modifies a snapshot policy.

Parameters

Name	Description	Required
<code>id</code>	Snapshot Policy Identifier	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_snapshot_policy_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy create
```

```

s.",
  "type": "string"
},
"source_file_id": {
  "description": "The source file ID of the directory to snapshot under this policy.",
  "type": "string"
},
"schedule": {
  "description": "The schedule according to which to take snapshots under this policy.",
  "type": "object",
  "properties": {
    "id": {
      "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
      "type": "number"
    },
    "creation_schedule": {
      "description": "Structure defining when to take snapshots",
      "type": "object",
      "properties": {
        "timezone": {
          "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
          "type": "string"
        },
        "frequency": {
          "type": "string",
          "enum": [
            "SCHEDULE_MONTHLY",
            "SCHEDULE_DAILY_OR_WEEKLY",
            "SCHEDULE_HOURLY_OR_LESS"
          ],
          "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
        },
        "hour": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
          "type": "number"
        },
        "minute": {
          "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of ho

```

```

ur [0, 59] at which to take snapshot",
    "type": "number"
},
"on_days": {
    "type": "array",
    "items": {
        "type": "string",
        "enum": [
            "SUNDAY",
            "MONDAY",
            "TUESDAY",
            "WEDNESDAY",
            "THURSDAY",
            "FRIDAY",
            "SATURDAY"
        ],
        "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.: \n * `FRIDAY` - FRIDAY, \n * `MONDAY` - MONDAY, \n * `SATURDAY` - SATURDAY, \n * `SUNDAY` - SUNDAY, \n * `THURSDAY` - THURSDAY, \n * `TUESDAY` - TUESDAY, \n * `WEDNESDAY` - WEDNESDAY"
    }
},
"day_of_month": {
    "description": "For MONTHLY frequency: day of month on which to take snapshot. [1, 27] for specific day, 128 for last day of month.",
    "type": "number"
},
"window_start_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for start of window during which to take snapshots",
    "type": "number"
},
"window_start_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] for start of window during which to take snapshots",
    "type": "number"
},
"window_end_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for end of window during which to take snapshots)",
    "type": "number"
},
"window_end_minute": {

```

```

        "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f
or end of window during which to take snapshots",
        "type": "number"
    },
    "fire_every_interval": {
        "type": "string",
        "enum": [
            "FIRE_IN_MINUTES",
            "FIRE_IN_HOURS"
        ],
        "description": "For HOURLY_OR_LESS frequency: units for interval (MINU
TES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOU
R` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
    },
    "fire_every": {
        "description": "For HOURLY_OR_LESS frequency: value for interval [1, 9
9] at which to take snapshot during specified window",
        "type": "number"
    }
},
"expiration_time_to_live": {
    "description": "Duration after which to expire snapshots created by this p
olicy, in format <quantity><units>, where <quantity> is a positive integer less tha
n 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1ho
urs. Empty string or never indicates snapshots should never expire.",
    "type": "string"
}
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this polic
y.",
    "type": "boolean"
},
"lock_key_ref": {
    "description": "If non-empty, snapshots taken for this policy will be locked w
ith the given id.",
    "type": "string"
}
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_policy_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique identifier for the snapshot policy.",
      "type": "number"
    },
    "policy_name": {
      "description": "The snapshot policy name.",
      "type": "string"
    },
    "snapshot_name_template": {
      "description": "The naming template for the snapshots that this policy creates.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory to snapshot under this policy.",
      "type": "string"
    },
    "schedule": {
      "description": "The schedule according to which to take snapshots under this policy.",
      "type": "object",
      "properties": {
        "id": {
          "description": "Identifier for the snapshot policy's schedule. Only unique within the scope of a snapshot policy.",
          "type": "number"
        },
        "creation_schedule": {
          "description": "Structure defining when to take snapshots",
          "type": "object",
          "properties": {
```

```

    "timezone": {
      "description": "The time zone in which the schedule should be interpreted (e.g. America/Los_Angeles or UTC).",
      "type": "string"
    },
    "frequency": {
      "type": "string",
      "enum": [
        "SCHEDULE_MONTHLY",
        "SCHEDULE_DAILY_OR_WEEKLY",
        "SCHEDULE_HOURLY_OR_LESS"
      ],
      "description": "Coarse frequency (MONTHLY, DAILY_OR_WEEKLY, or HOURLY_OR_LESS) at which to take snapshot:\n * `SCHEDULE_DAILY_OR_WEEKLY` - SCHEDULE_DAILY_OR_WEEKLY,\n * `SCHEDULE_HOURLY_OR_LESS` - SCHEDULE_HOURLY_OR_LESS,\n * `SCHEDULE_MONTHLY` - SCHEDULE_MONTHLY"
    },
    "hour": {
      "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: Hour of day [0, 23] at which to take snapshot",
      "type": "number"
    },
    "minute": {
      "description": "For MONTHLY or DAILY_OR_WEEKLY frequency: minute of hour [0, 59] at which to take snapshot",
      "type": "number"
    },
    "on_days": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": [
          "SUNDAY",
          "MONDAY",
          "TUESDAY",
          "WEDNESDAY",
          "THURSDAY",
          "FRIDAY",
          "SATURDAY"
        ],
        "description": "For DAILY_OR_WEEKLY or HOURLY_OR_LESS frequency: list of days of the week on which to take snapshots. Choose from SUN, MON, TUE, WED, THU, FRI, and/or SAT. EVERY_DAY can be used to specify all days. For MONTHLY frequency: LAST_DAY_OF_MONTH indicates that the snapshot should be taken only on the last day of the month.:\n * `FRIDAY` - FRIDAY,\n * `MONDAY` - MONDAY,\n * `SATURDAY` - SATURDAY,\n * `SUNDAY` - SUNDAY,\n * `THURSDAY` - THURSDAY,\n * `TUESDAY` - TUESDAY,\n"
      }
    }
  }

```



```

* `WEDNESDAY` - WEDNESDAY"
    }
  },
  "day_of_month": {
    "description": "For MONTHLY frequency: day of month on which to take s
napshot. [1, 27] for specific day, 128 for last day of month.",
    "type": "number"
  },
  "window_start_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for
start of window during which to take snapshots",
    "type": "number"
  },
  "window_start_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f
or start of window during which to take snapshots",
    "type": "number"
  },
  "window_end_hour": {
    "description": "For HOURLY_OR_LESS frequency: hour of day [0, 23] for
end of window during which to take snapshots)",
    "type": "number"
  },
  "window_end_minute": {
    "description": "For HOURLY_OR_LESS frequency: minute of hour [0, 59] f
or end of window during which to take snapshots",
    "type": "number"
  },
  "fire_every_interval": {
    "type": "string",
    "enum": [
      "FIRE_IN_MINUTES",
      "FIRE_IN_HOURS"
    ],
    "description": "For HOURLY_OR_LESS frequency: units for interval (MINU
TES or HOURS) at which to take snapshot during specified window:\n * `FIRE_IN_HOU
R S` - FIRE_IN_HOURS,\n * `FIRE_IN_MINUTES` - FIRE_IN_MINUTES"
  },
  "fire_every": {
    "description": "For HOURLY_OR_LESS frequency: value for interval [1, 9
9] at which to take snapshot during specified window",
    "type": "number"
  }
},
"expiration_time_to_live": {

```

```

        "description": "Duration after which to expire snapshots created by this p
olicy, in format <quantity><units>, where <quantity> is a positive integer less tha
n 100 and <units> is one of [months, weeks, days, hours, minutes], e.g. 5days or 1ho
urs. Empty string or never indicates snapshots should never expire.",
        "type": "string"
    }
},
"enabled": {
    "description": "Specifies whether taking snapshots is enabled for this polic
y.",
    "type": "boolean"
},
"lock_key_ref": {
    "description": "If non-empty, snapshots taken for this policy will be locked w
ith the given id.",
    "type": "string"
}
}
}

```

snapshots/status/

Endpoint

/v3/snapshots/status/

GET

Returns the statuses for all snapshots. Each snapshot's status includes additional non-configurable information about a snapshot.

Parameters

Name	Description	Required
<code>filter</code>	Filter the list of snapshots to exclude snapshots in process of being deleted, or include only snapshots in process of being deleted. By default, includes all snapshots.: * <code>`all`</code> - all, * <code>`exclude_in_delete`</code> - exclude_in_delete, * <code>`only_in_delete`</code> - only_in_delete	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_statuses",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of snapshot statuses",
        "type": "object",
        "properties": {
          "id": {
            "description": "The unique snapshot identifier.",
            "type": "number"
          },
          "name": {
```

```

        "description": "The snapshot name as it appears in the .snapshot directory over SMB or NFS.",
        "type": "string"
    },
    "timestamp": {
        "description": "The snapshot creation timestamp, encoded as RFC 3339, a normalized subset of ISO 8601.",
        "type": "string"
    },
    "source_file_id": {
        "description": "The source file ID of the directory for the snapshot.",
        "type": "string"
    },
    "source_file_path": {
        "description": "The snapshot source directory (if available).",
        "type": "string"
    },
    "policy_id": {
        "description": "The policy ID from which this snapshot was created, or null if this snapshot was created manually.",
        "type": "number"
    },
    "policy_name": {
        "description": "The policy name from which this snapshot was created, or null if this snapshot was created manually or its policy was deleted.",
        "type": "string"
    },
    "expiration": {
        "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
        "type": "string"
    },
    "owners": {
        "type": "array",
        "items": {
            "description": "This snapshot's owners. While there are entries on this list, the snapshot can't be deleted or modified.",
            "type": "object",
            "properties": {
                "id": {
                    "description": "id",
                    "type": "string"
                }
            }
        }
    }
}

```


snapshots/status/{id}

Endpoint

/v3/snapshots/status/{id}

GET

Returns the status for a specific snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_status",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique snapshot identifier.",
      "type": "number"
    },
    "name": {
      "description": "The snapshot name as it appears in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "timestamp": {
      "description": "The snapshot creation timestamp, encoded as RFC 3339, a normalized subset of ISO 8601.",
      "type": "string"
    },
    "source_file_id": {
```

```

    "description": "The source file ID of the directory for the snapshot.",
    "type": "string"
  },
  "source_file_path": {
    "description": "The snapshot source directory (if available).",
    "type": "string"
  },
  "policy_id": {
    "description": "The policy ID from which this snapshot was created, or null if this snapshot was created manually.",
    "type": "number"
  },
  "policy_name": {
    "description": "The policy name from which this snapshot was created, or null if this snapshot was created manually or its policy was deleted.",
    "type": "string"
  },
  "expiration": {
    "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
    "type": "string"
  },
  "owners": {
    "type": "array",
    "items": {
      "description": "This snapshot's owners. While there are entries on this list, the snapshot can't be deleted or modified.",
      "type": "object",
      "properties": {
        "id": {
          "description": "id",
          "type": "string"
        }
      }
    }
  },
  "in_delete": {
    "description": "Specifies whether the snapshot is in the process of being deleted.",
    "type": "boolean"
  },
  "lock_key": {
    "description": "The key that the snapshot is locked with. If set to null, the system does not create locked snapshots under this policy.",
    "type": "string"
  }
}

```

```
}  
}
```


snapshots/{id}

Endpoint

/v3/snapshots/{id}

GET

Returns information about a specific snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique snapshot identifier.",
      "type": "number"
    },
    "name": {
      "description": "The snapshot name as it appears in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "timestamp": {
      "description": "The snapshot creation timestamp, encoded as RFC 3339, a normalized subset of ISO 8601.",
      "type": "string"
    },
    "source_file_id": {
```

```

    "description": "The source file ID of the directory for the snapshot.",
    "type": "string"
  },
  "policy_id": {
    "description": "The policy ID from which this snapshot was created, or null if this snapshot was created manually.",
    "type": "number"
  },
  "expiration": {
    "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
    "type": "string"
  },
  "in_delete": {
    "description": "Specifies whether the snapshot is in the process of being deleted.",
    "type": "boolean"
  }
}

```

PUT

Modifies a snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_snapshot_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique snapshot identifier.",
      "type": "number"
    },
  },
}

```

```

    "name": {
      "description": "The snapshot name as it appears in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "timestamp": {
      "description": "The snapshot creation timestamp, encoded as RFC 3339, a normalized subset of ISO 8601.",
      "type": "string"
    },
    "source_file_id": {
      "description": "The source file ID of the directory for the snapshot.",
      "type": "string"
    },
    "policy_id": {
      "description": "The policy ID from which this snapshot was created, or null if this snapshot was created manually.",
      "type": "number"
    },
    "expiration": {
      "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
      "type": "string"
    },
    "in_delete": {
      "description": "Specifies whether the snapshot is in the process of being deleted.",
      "type": "boolean"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshot_info",
  "type": "object",

```

```

"properties": {
  "id": {
    "description": "The unique snapshot identifier.",
    "type": "number"
  },
  "name": {
    "description": "The snapshot name as it appears in the .snapshot directory over SMB or NFS.",
    "type": "string"
  },
  "timestamp": {
    "description": "The snapshot creation timestamp, encoded as RFC 3339, a normalized subset of ISO 8601.",
    "type": "string"
  },
  "source_file_id": {
    "description": "The source file ID of the directory for the snapshot.",
    "type": "string"
  },
  "policy_id": {
    "description": "The policy ID from which this snapshot was created, or null if this snapshot was created manually.",
    "type": "number"
  },
  "expiration": {
    "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
    "type": "string"
  },
  "in_delete": {
    "description": "Specifies whether the snapshot is in the process of being deleted.",
    "type": "boolean"
  }
}
}

```

DELETE

Deletes a snapshot.

Parameters

Name	Description	Required
<code>id</code>	Snapshot identifier	Yes

If-Match	ETag for expected version	No
----------	---------------------------	----

Response

Codes

Code	Description
202	Return value on success

PATCH

Modifies a snapshot.

Parameters

Name	Description	Required
id	Snapshot identifier	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_snapshot_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique snapshot identifier.",
      "type": "number"
    },
    "name": {
      "description": "The snapshot name as it appears in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "timestamp": {
      "description": "The snapshot creation timestamp, encoded as RFC 3339, a normalized subset of ISO 8601.",
      "type": "string"
    },
    "source_file_id": {
```

```

    "description": "The source file ID of the directory for the snapshot.",
    "type": "string"
  },
  "policy_id": {
    "description": "The policy ID from which this snapshot was created, or null if this snapshot was created manually.",
    "type": "number"
  },
  "expiration": {
    "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
    "type": "string"
  },
  "in_delete": {
    "description": "Specifies whether the snapshot is in the process of being deleted.",
    "type": "boolean"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_snapshot_info",
  "type": "object",
  "properties": {
    "id": {
      "description": "The unique snapshot identifier.",
      "type": "number"
    },
    "name": {
      "description": "The snapshot name as it appears in the .snapshot directory over SMB or NFS.",
      "type": "string"
    },
    "timestamp": {

```

```

    "description": "The snapshot creation timestamp, encoded as RFC 3339, a normalized subset of ISO 8601.",
    "type": "string"
  },
  "source_file_id": {
    "description": "The source file ID of the directory for the snapshot.",
    "type": "string"
  },
  "policy_id": {
    "description": "The policy ID from which this snapshot was created, or null if this snapshot was created manually.",
    "type": "number"
  },
  "expiration": {
    "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
    "type": "string"
  },
  "in_delete": {
    "description": "Specifies whether the snapshot is in the process of being deleted.",
    "type": "boolean"
  }
}

```

snapshots/{id}/lock

Endpoint

/v3/snapshots/{id}/lock

POST

Lock the specified snapshot. The only modification you can make to a locked snapshot is extending its expiration time.

Parameters

Name	Description	Required
id	The snapshot identifier.	Yes

Request

Schema

```
{
  "description": "api_snapshot_lock",
  "type": "object",
  "properties": {
    "lock_key_ref": {
      "description": "lock_key_ref",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_lock",
```



```
"type": "object",  
"properties": {  
  "lock_key_ref": {  
    "description": "lock_key_ref",  
    "type": "string"  
  }  
}  
}
```

snapshots/{id}/unlock

Endpoint

/v3/snapshots/{id}/unlock

POST

Unlock the specified snapshot. After you unlock a snapshot, you can modify it.

Parameters

Name	Description	Required
id	The snapshot identifier.	Yes

Request

Schema

```
{
  "description": "api_snapshot_unlock",
  "type": "object",
  "properties": {
    "signature": {
      "description": "signature",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

snapshots/{id}/unlock-challenge

Endpoint

/v3/snapshots/{id}/unlock-challenge

GET

Generate a snapshot unlock challenge to provide in the subsequent unlock call.

Parameters

Name	Description	Required
id	The snapshot identifier.	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_unlock_challenge",
  "type": "object",
  "properties": {
    "challenge": {
      "description": "challenge",
      "type": "string"
    }
  }
}
```

snapshots/{newer_id}/changes-since/{older_id}/files/{ref}

Endpoint

/v3/snapshots/{newer_id}/changes-since/{older_id}/files/{ref}

GET

Returns the operations that transform the older snapshot's file contents into the newer snapshot's, at byte-range granularity. Each entry's `op` field is CREATE, MODIFY, or DELETE.

Parameters

Name	Description	Required
<code>newer_id</code>	Newer snapshot	Yes
<code>older_id</code>	Older snapshot	Yes
<code>ref</code>	The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.	Yes
<code>after</code>	Return entries after the given key (keys are returned in the paging object)	No
<code>limit</code>	Return no more than this many entries; the system may choose a smaller limit.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{  
  "description": "api_snapshot_file_diff_v3",  
}
```

```

"type": "object",
"properties": {
  "entries": {
    "type": "array",
    "items": {
      "description": "entries",
      "type": "object",
      "properties": {
        "op": {
          "type": "string",
          "enum": [
            "CREATE",
            "MODIFY",
            "DELETE"
          ],
          "description": "The type of change in the region of the file in the newer snapshot. The region may have been created, modified, or deleted compared to the older snapshot.:\\n * `CREATE` - SNAPSHOT_FILE_DIFF_OPERATION_CREATE,\\n * `DELETE` - SNAPSHOT_FILE_DIFF_OPERATION_DELETE,\\n * `MODIFY` - SNAPSHOT_FILE_DIFF_OPERATION_MODIFY"
        },
        "offset": {
          "description": "The starting offset of the changed region in bytes.",
          "type": "string"
        },
        "size": {
          "description": "The size of the changed region in bytes.",
          "type": "string"
        }
      }
    }
  }
}

```

/v4/snapshots/status/

Endpoint

/v4/snapshots/status/

GET

Returns the information for every snapshot. If a snapshot was created from a snapshot policy, returns information about the policy.

Parameters

Name	Description	Required
<code>filter</code>	Filter the list of snapshots to exclude any combination of snapshots in process of being deleted, snapshots not in process of being deleted, locked snapshots, and unlocked snapshots. By default, includes all snapshots.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_snapshot_statuses",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of snapshot statuses",
        "type": "object",
        "properties": {
          "id": {
            "description": "The unique snapshot identifier.",
            "type": "number"
          },
          "name": {
```

```

        "description": "The snapshot name as it appears in the .snapshot directory over SMB or NFS.",
        "type": "string"
    },
    "timestamp": {
        "description": "The snapshot creation timestamp, encoded as RFC 3339, a normalized subset of ISO 8601.",
        "type": "string"
    },
    "source_file_id": {
        "description": "The source file ID of the directory for the snapshot.",
        "type": "string"
    },
    "source_file_path": {
        "description": "The snapshot source directory (if available).",
        "type": "string"
    },
    "policy_id": {
        "description": "The policy ID from which this snapshot was created, or null if this snapshot was created manually.",
        "type": "number"
    },
    "policy_name": {
        "description": "The policy name from which this snapshot was created, or null if this snapshot was created manually or its policy was deleted.",
        "type": "string"
    },
    "expiration": {
        "description": "The snapshot expiration time, encoded as RFC 3339, a normalized subset of ISO 8601. If expiration time is null, the snapshot never expires.",
        "type": "string"
    },
    "owners": {
        "type": "array",
        "items": {
            "description": "This snapshot's owners. While there are entries on this list, the snapshot can't be deleted or modified.",
            "type": "object",
            "properties": {
                "id": {
                    "description": "id",
                    "type": "string"
                }
            }
        }
    }
}

```

```

    },
    "in_delete": {
      "description": "Specifies whether the snapshot is in the process of being deleted.",
      "type": "boolean"
    },
    "lock_key": {
      "description": "The key that the snapshot is locked with. If set to null, the system does not create locked snapshots under this policy.",
      "type": "string"
    }
  }
}
}
}
}
}

```


multitenancy/tenants/

Endpoint

/v1/multitenancy/tenants/

GET

[preview] Get configurations of all tenants.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_tenant_configs",
  "type": "object",
  "properties": {
    "entries": {
      "type": "array",
      "items": {
        "description": "List of tenant configs",
        "type": "object",
        "properties": {
          "id": {
            "description": "Unique identifier for this tenant configuration.",
            "type": "number"
          },
          "name": {
            "description": "Unique name of the tenant chosen by the user.",
            "type": "string"
          },
          "web_ui_enabled": {
            "description": "Web UI is accessible from this tenant.",
            "type": "boolean"
          }
        }
      }
    }
  }
}
```

```

    "rest_api_enabled": {
      "description": "Rest API is accessible from this tenant.",
      "type": "boolean"
    },
    "ssh_enabled": {
      "description": "SSH is accessible from this tenant.",
      "type": "boolean"
    },
    "replication_enabled": {
      "description": "Replication is accessible from this tenant.",
      "type": "boolean"
    },
    "nfs_enabled": {
      "description": "NFS is accessible from this tenant.",
      "type": "boolean"
    },
    "smb_enabled": {
      "description": "SMB is accessible from this tenant.",
      "type": "boolean"
    },
    "networks": {
      "type": "array",
      "items": {
        "description": "List of network IDs associated with this tenant.",
        "type": "number"
      }
    },
    "identity_config_id": {
      "description": "Unique identifier for the identity configuration to use
for this tenant.",
      "type": "number"
    }
  }
}
}
}
}
}

```

POST

[preview] Create a tenant.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_tenant_config_post",
  "type": "object",
  "properties": {
    "name": {
      "description": "Unique name of the tenant chosen by the user.",
      "type": "string"
    },
    "web_ui_enabled": {
      "description": "Web UI is accessible from this tenant. Defaults to false.",
      "type": "boolean"
    },
    "rest_api_enabled": {
      "description": "Rest API is accessible from this tenant. Defaults to false.",
      "type": "boolean"
    },
    "ssh_enabled": {
      "description": "SSH is accessible from this tenant. Defaults to false.",
      "type": "boolean"
    },
    "replication_enabled": {
      "description": "Replication is accessible from this tenant. Defaults to false.",
      "type": "boolean"
    },
    "nfs_enabled": {
      "description": "NFS is accessible from this tenant. Defaults to false.",
      "type": "boolean"
    },
    "smb_enabled": {
      "description": "SMB is accessible from this tenant. Defaults to false.",
      "type": "boolean"
    },
    "networks": {
      "type": "array",
      "items": {
        "description": "List of network IDs associated with this tenant. Defaults to empty.",
        "type": "number"
      }
    },
    "identity_config_id": {
      "description": "Unique identifier for the identity configuration to use for th
```

```
is tenant.",
  "type": "number"
}
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_tenant_config",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this tenant configuration.",
      "type": "number"
    },
    "name": {
      "description": "Unique name of the tenant chosen by the user.",
      "type": "string"
    },
    "web_ui_enabled": {
      "description": "Web UI is accessible from this tenant.",
      "type": "boolean"
    },
    "rest_api_enabled": {
      "description": "Rest API is accessible from this tenant.",
      "type": "boolean"
    },
    "ssh_enabled": {
      "description": "SSH is accessible from this tenant.",
      "type": "boolean"
    },
    "replication_enabled": {
      "description": "Replication is accessible from this tenant.",
      "type": "boolean"
    },
    "nfs_enabled": {
```

```
    "description": "NFS is accessible from this tenant.",
    "type": "boolean"
  },
  "smb_enabled": {
    "description": "SMB is accessible from this tenant.",
    "type": "boolean"
  },
  "networks": {
    "type": "array",
    "items": {
      "description": "List of network IDs associated with this tenant.",
      "type": "number"
    }
  },
  "identity_config_id": {
    "description": "Unique identifier for the identity configuration to use for this tenant.",
    "type": "number"
  }
}
```

multitenancy/tenants/{tenant_id}

Endpoint

/v1/multitenancy/tenants/{tenant_id}

GET

[preview] Get configuration of a tenant.

Parameters

Name	Description	Required
tenant_id	The unique ID of the tenant	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_tenant_config",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this tenant configuration.",
      "type": "number"
    },
    "name": {
      "description": "Unique name of the tenant chosen by the user.",
      "type": "string"
    },
    "web_ui_enabled": {
      "description": "Web UI is accessible from this tenant.",
      "type": "boolean"
    },
    "rest_api_enabled": {
      "description": "Rest API is accessible from this tenant.",
      "type": "boolean"
    }
  }
}
```

```

},
"ssh_enabled": {
  "description": "SSH is accessible from this tenant.",
  "type": "boolean"
},
"replication_enabled": {
  "description": "Replication is accessible from this tenant.",
  "type": "boolean"
},
"nfs_enabled": {
  "description": "NFS is accessible from this tenant.",
  "type": "boolean"
},
"smb_enabled": {
  "description": "SMB is accessible from this tenant.",
  "type": "boolean"
},
"networks": {
  "type": "array",
  "items": {
    "description": "List of network IDs associated with this tenant.",
    "type": "number"
  }
},
"identity_config_id": {
  "description": "Unique identifier for the identity configuration to use for th
is tenant.",
  "type": "number"
}
}
}

```

PUT

[preview] Set configuration of a tenant.

Parameters

Name	Description	Required
tenant_id	The unique ID of the tenant	Yes
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "api_tenant_config",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this tenant configuration.",
      "type": "number"
    },
    "name": {
      "description": "Unique name of the tenant chosen by the user.",
      "type": "string"
    },
    "web_ui_enabled": {
      "description": "Web UI is accessible from this tenant.",
      "type": "boolean"
    },
    "rest_api_enabled": {
      "description": "Rest API is accessible from this tenant.",
      "type": "boolean"
    },
    "ssh_enabled": {
      "description": "SSH is accessible from this tenant.",
      "type": "boolean"
    },
    "replication_enabled": {
      "description": "Replication is accessible from this tenant.",
      "type": "boolean"
    },
    "nfs_enabled": {
      "description": "NFS is accessible from this tenant.",
      "type": "boolean"
    },
    "smb_enabled": {
      "description": "SMB is accessible from this tenant.",
      "type": "boolean"
    },
    "networks": {
      "type": "array",
      "items": {
        "description": "List of network IDs associated with this tenant.",
        "type": "number"
      }
    }
  },
}
```



```

    "identity_config_id": {
      "description": "Unique identifier for the identity configuration to use for this tenant.",
      "type": "number"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_tenant_config",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this tenant configuration.",
      "type": "number"
    },
    "name": {
      "description": "Unique name of the tenant chosen by the user.",
      "type": "string"
    },
    "web_ui_enabled": {
      "description": "Web UI is accessible from this tenant.",
      "type": "boolean"
    },
    "rest_api_enabled": {
      "description": "Rest API is accessible from this tenant.",
      "type": "boolean"
    },
    "ssh_enabled": {
      "description": "SSH is accessible from this tenant.",
      "type": "boolean"
    },
    "replication_enabled": {
      "description": "Replication is accessible from this tenant.",
      "type": "boolean"
    }
  }
}

```

```

    },
    "nfs_enabled": {
      "description": "NFS is accessible from this tenant.",
      "type": "boolean"
    },
    "smb_enabled": {
      "description": "SMB is accessible from this tenant.",
      "type": "boolean"
    },
    "networks": {
      "type": "array",
      "items": {
        "description": "List of network IDs associated with this tenant.",
        "type": "number"
      }
    },
    "identity_config_id": {
      "description": "Unique identifier for the identity configuration to use for th
is tenant.",
      "type": "number"
    }
  }
}

```

DELETE

[preview] Delete configuration of a tenant.

Parameters

Name	Description	Required
tenant_id	The unique ID of the tenant	Yes
If-Match	ETag for expected version	No

Response

Codes

Code	Description
200	Return value on success

PATCH

[preview] Update the configuration of a tenant.

Parameters

Name	Description	Required
<code>tenant_id</code>	The unique ID of the tenant	Yes
<code>If-Match</code>	ETag for expected version	No

Request

Schema

```
{
  "description": "api_tenant_config_patch",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this tenant configuration.",
      "type": "number"
    },
    "name": {
      "description": "Unique name of the tenant chosen by the user.",
      "type": "string"
    },
    "web_ui_enabled": {
      "description": "Web UI is accessible from this tenant.",
      "type": "boolean"
    },
    "rest_api_enabled": {
      "description": "Rest API is accessible from this tenant.",
      "type": "boolean"
    },
    "ssh_enabled": {
      "description": "SSH is accessible from this tenant.",
      "type": "boolean"
    },
    "replication_enabled": {
      "description": "Replication is accessible from this tenant.",
      "type": "boolean"
    },
    "nfs_enabled": {
      "description": "NFS is accessible from this tenant.",
      "type": "boolean"
    },
    "smb_enabled": {
      "description": "SMB is accessible from this tenant.",

```

```

    "type": "boolean"
  },
  "networks": {
    "type": "array",
    "items": {
      "description": "List of network IDs associated with this tenant.",
      "type": "number"
    }
  },
  "identity_config_id": {
    "description": "Unique identifier for the identity configuration to use for this tenant.",
    "type": "number"
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_tenant_config",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for this tenant configuration.",
      "type": "number"
    },
    "name": {
      "description": "Unique name of the tenant chosen by the user.",
      "type": "string"
    },
    "web_ui_enabled": {
      "description": "Web UI is accessible from this tenant.",
      "type": "boolean"
    },
    "rest_api_enabled": {
      "description": "Rest API is accessible from this tenant.",

```

```

    "type": "boolean"
  },
  "ssh_enabled": {
    "description": "SSH is accessible from this tenant.",
    "type": "boolean"
  },
  "replication_enabled": {
    "description": "Replication is accessible from this tenant.",
    "type": "boolean"
  },
  "nfs_enabled": {
    "description": "NFS is accessible from this tenant.",
    "type": "boolean"
  },
  "smb_enabled": {
    "description": "SMB is accessible from this tenant.",
    "type": "boolean"
  },
  "networks": {
    "type": "array",
    "items": {
      "description": "List of network IDs associated with this tenant.",
      "type": "number"
    }
  },
  "identity_config_id": {
    "description": "Unique identifier for the identity configuration to use for th
is tenant.",
    "type": "number"
  }
}

```

time/settings

Endpoint

/v1/time/settings

GET

Retrieve the server's time-management configuration. Refer to the 'Set Time Configuration' method for a description of the returned fields.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "conf_time_state",
  "type": "object",
  "properties": {
    "use_ad_for_primary": {
      "description": "Whether to use the Active Directory controller as the primary NTP server",
      "type": "boolean"
    },
    "ntp_servers": {
      "type": "array",
      "items": {
        "description": "List of NTP servers",
        "type": "string"
      }
    }
  }
}
```

PUT

Set the server's time-management configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "conf_time_state",
  "type": "object",
  "properties": {
    "use_ad_for_primary": {
      "description": "Whether to use the Active Directory controller as the primary NTP server",
      "type": "boolean"
    },
    "ntp_servers": {
      "type": "array",
      "items": {
        "description": "List of NTP servers",
        "type": "string"
      }
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "conf_time_state",
  "type": "object",
  "properties": {
    "use_ad_for_primary": {
      "description": "Whether to use the Active Directory controller as the primary
```

```

NTP server",
  "type": "boolean"
},
"ntp_servers": {
  "type": "array",
  "items": {
    "description": "List of NTP servers",
    "type": "string"
  }
}
}
}

```

PATCH

Set just the provided components of the server's time-management configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "conf_time_state_patch",
  "type": "object",
  "properties": {
    "use_ad_for_primary": {
      "description": "Whether to use the Active Directory controller as the primary
NTP server",
      "type": "boolean"
    },
    "ntp_servers": {
      "type": "array",
      "items": {
        "description": "List of NTP servers",
        "type": "string"
      }
    }
  }
}

```


Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "conf_time_state",
  "type": "object",
  "properties": {
    "use_ad_for_primary": {
      "description": "Whether to use the Active Directory controller as the primary NTP server",
      "type": "boolean"
    },
    "ntp_servers": {
      "type": "array",
      "items": {
        "description": "List of NTP servers",
        "type": "string"
      }
    }
  }
}
```

time/status

Endpoint

/v1/time/status

GET

Retrieve the time status of the underlying system

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "time_status_response",
  "type": "object",
  "properties": {
    "config": {
      "description": "config",
      "type": "object",
      "properties": {
        "use_ad_for_primary": {
          "description": "Whether to use the Active Directory controller as the primary NTP server",
          "type": "boolean"
        },
        "ntp_servers": {
          "type": "array",
          "items": {
            "description": "List of NTP servers",
            "type": "string"
          }
        }
      }
    }
  }
},
```

```

    "time": {
      "description": "time",
      "type": "string"
    },
    "status": {
      "type": "string",
      "enum": [
        "TIME_NOT_SYNCHRONIZING",
        "TIME_SYNCHRONIZING"
      ],
      "description": "status:\n * `TIME_NOT_SYNCHRONIZING` - TIME_NOT_SYNCHRONIZIN
G,\n * `TIME_SYNCHRONIZING` - TIME_SYNCHRONIZING"
    }
  }
}

```

time/timezones

Endpoint

`/v1/time/timezones`

GET

Get a list of all time zones supported by Qumulo Core

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

time/default-settings

Endpoint

/v2/time/default-settings

GET

Retrieve the current cluster's default time sync configuration.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_time_config_v2",
  "type": "object",
  "properties": {
    "source": {
      "type": "string",
      "enum": [
        "API_TIME_SOURCE_NTP",
        "API_TIME_SOURCE_HYPERVISOR"
      ],
      "description": "The time source type: For ANQ, must be the hypervisor-provide d time source. For all platforms other than CNQ on Azure, must be an NTP server. Fo r CNQ on Azure, can be either an NTP server or the hypervisor-provided time sourc e.:\\n * `API_TIME_SOURCE_HYPERVISOR` - API_TIME_SOURCE_HYPERVISOR,\\n * `API_TIME_SOU RCE_NTP` - API_TIME_SOURCE_NTP"
    },
    "use_ad_for_primary": {
      "description": "Use AD as the primary time source",
      "type": "boolean"
    },
    "ntp_servers": {
      "type": "array",
```

```
    "items": {  
      "description": "List of NTP servers",  
      "type": "string"  
    }  
  }  
}
```

time/settings

Endpoint

/v2/time/settings

GET

Retrieve this cluster's time-management configuration. Refer to the 'Set Time Configuration' method for a description of the returned fields.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_time_config_v2",
  "type": "object",
  "properties": {
    "source": {
      "type": "string",
      "enum": [
        "API_TIME_SOURCE_NTP",
        "API_TIME_SOURCE_HYPERVISOR"
      ],
      "description": "The time source type: For ANQ, must be the hypervisor-provide d time source. For all platforms other than CNQ on Azure, must be an NTP server. Fo r CNQ on Azure, can be either an NTP server or the hypervisor-provided time sourc e.:\\n * `API_TIME_SOURCE_HYPERVISOR` - API_TIME_SOURCE_HYPERVISOR,\\n * `API_TIME_SOU RCE_NTP` - API_TIME_SOURCE_NTP"
    },
    "use_ad_for_primary": {
      "description": "Use AD as the primary time source",
      "type": "boolean"
    },
    "ntp_servers": {
```

```

    "type": "array",
    "items": {
      "description": "List of NTP servers",
      "type": "string"
    }
  }
}
}

```

PUT

Set this cluster's time-management configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```

{
  "description": "api_time_config_v2",
  "type": "object",
  "properties": {
    "source": {
      "type": "string",
      "enum": [
        "API_TIME_SOURCE_NTP",
        "API_TIME_SOURCE_HYPERVISOR"
      ],
      "description": "The time source type: For ANQ, must be the hypervisor-provide  
d time source. For all platforms other than CNQ on Azure, must be an NTP server. Fo  
r CNQ on Azure, can be either an NTP server or the hypervisor-provided time sourc  
e.:\\n * `API_TIME_SOURCE_HYPERVISOR` - API_TIME_SOURCE_HYPERVISOR,\\n * `API_TIME_SOU  
RCE_NTP` - API_TIME_SOURCE_NTP"
    },
    "use_ad_for_primary": {
      "description": "Use AD as the primary time source",
      "type": "boolean"
    },
    "ntp_servers": {
      "type": "array",

```



```

    "items": {
      "description": "List of NTP servers",
      "type": "string"
    }
  }
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "api_time_config_v2",
  "type": "object",
  "properties": {
    "source": {
      "type": "string",
      "enum": [
        "API_TIME_SOURCE_NTP",
        "API_TIME_SOURCE_HYPERVISOR"
      ],
      "description": "The time source type: For ANQ, must be the hypervisor-provide  
d time source. For all platforms other than CNQ on Azure, must be an NTP server. Fo  
r CNQ on Azure, can be either an NTP server or the hypervisor-provided time sourc  
e.:\\n * `API_TIME_SOURCE_HYPERVISOR` - API_TIME_SOURCE_HYPERVISOR,\\n * `API_TIME_SOU  
RCE_NTP` - API_TIME_SOURCE_NTP"
    },
    "use_ad_for_primary": {
      "description": "Use AD as the primary time source",
      "type": "boolean"
    },
    "ntp_servers": {
      "type": "array",
      "items": {
        "description": "List of NTP servers",
        "type": "string"
      }
    }
  }
}

```

```
}  
}
```

PATCH

Set just the provided components of this cluster's time-management configuration.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{  
  "description": "api_time_config_v2_patch",  
  "type": "object",  
  "properties": {  
    "source": {  
      "type": "string",  
      "enum": [  
        "API_TIME_SOURCE_NTP",  
        "API_TIME_SOURCE_HYPERVISOR"  
      ],  
      "description": "The time source type: For ANQ, must be the hypervisor-provide  
d time source. For all platforms other than CNQ on Azure, must be an NTP server. Fo  
r CNQ on Azure, can be either an NTP server or the hypervisor-provided time sourc  
e.:\\n * `API_TIME_SOURCE_HYPERVISOR` - API_TIME_SOURCE_HYPERVISOR,\\n * `API_TIME_SOU  
RCE_NTP` - API_TIME_SOURCE_NTP"  
    },  
    "use_ad_for_primary": {  
      "description": "Use AD as the primary time source",  
      "type": "boolean"  
    },  
    "ntp_servers": {  
      "type": "array",  
      "items": {  
        "description": "List of NTP servers",  
        "type": "string"  
      }  
    }  
  }  
}
```

```
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_time_config_v2",
  "type": "object",
  "properties": {
    "source": {
      "type": "string",
      "enum": [
        "API_TIME_SOURCE_NTP",
        "API_TIME_SOURCE_HYPERVISOR"
      ],
      "description": "The time source type: For ANQ, must be the hypervisor-provide  
d time source. For all platforms other than CNQ on Azure, must be an NTP server. Fo  
r CNQ on Azure, can be either an NTP server or the hypervisor-provided time sourc  
e.:\\n * `API_TIME_SOURCE_HYPERVISOR` - API_TIME_SOURCE_HYPERVISOR,\\n * `API_TIME_SOU  
RCE_NTP` - API_TIME_SOURCE_NTP"
    },
    "use_ad_for_primary": {
      "description": "Use AD as the primary time source",
      "type": "boolean"
    },
    "ntp_servers": {
      "type": "array",
      "items": {
        "description": "List of NTP servers",
        "type": "string"
      }
    }
  }
}
```

time/status

Endpoint

/v2/time/status

GET

Retrieve the time status of the underlying system

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_time_status_v2",
  "type": "object",
  "properties": {
    "config": {
      "description": "config",
      "type": "object",
      "properties": {
        "source": {
          "type": "string",
          "enum": [
            "API_TIME_SOURCE_NTP",
            "API_TIME_SOURCE_HYPERVISOR"
          ],
          "description": "The time source type: For ANQ, must be the hypervisor-provided time source. For all platforms other than CNQ on Azure, must be an NTP server. For CNQ on Azure, can be either an NTP server or the hypervisor-provided time source. e.:\\n * `API_TIME_SOURCE_HYPERVISOR` - API_TIME_SOURCE_HYPERVISOR,\\n * `API_TIME_SOURCE_NTP` - API_TIME_SOURCE_NTP"
        },
        "use_ad_for_primary": {
          "description": "Use AD as the primary time source",

```

```

        "type": "boolean"
    },
    "ntp_servers": {
        "type": "array",
        "items": {
            "description": "List of NTP servers",
            "type": "string"
        }
    }
},
"time": {
    "description": "time",
    "type": "string"
},
"node_statuses": {
    "type": "array",
    "items": {
        "description": "node_statuses",
        "type": "object",
        "properties": {
            "node_id": {
                "description": "node_id",
                "type": "number"
            },
            "status": {
                "type": "string",
                "enum": [
                    "TIME_NOT_SYNCHRONIZING",
                    "TIME_SYNCHRONIZING"
                ],
                "description": "status:\n * `TIME_NOT_SYNCHRONIZING` - TIME_NOT_SYNCHRONIZING,\n * `TIME_SYNCHRONIZING` - TIME_SYNCHRONIZING"
            }
        }
    }
}
}
}
}
}

```

time/timezones

Endpoint

/v2/time/timezones

GET

Get a list of all time zones supported by Qumulo Core

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "type": "array",
  "items": {
    "type": "string"
  }
}
```

tree-delete/jobs/

Endpoint

/v1/tree-delete/jobs/

GET

Get status of all directory-tree deletion jobs.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "tree_delete_jobs_response",
  "type": "object",
  "properties": {
    "jobs": {
      "type": "array",
      "items": {
        "description": "jobs",
        "type": "object",
        "properties": {
          "id": {
            "description": "The ID of the directory being deleted.",
            "type": "string"
          },
          "create_time": {
            "description": "The time the job was created. It may not have started at that time if the system was processing other jobs.",
            "type": "string"
          },
          "mode": {
            "type": "string",
            "enum": [
```

```

        "PLACE"
    ],
    "description": "The tree delete mode this job is running in.:\n * `PLAC
E` - TREE_DELETE_IN_PLACE"
},
    "initial_path": {
        "description": "The path of the directory at the time the job was starte
d.",
        "type": "string"
    },
    "initial_capacity": {
        "description": "Initial bytes (data and metadata) used by the tree bein
g deleted.",
        "type": "string"
    },
    "initial_directories": {
        "description": "Initial number of directories in the tree being delete
d.",
        "type": "string"
    },
    "initial_files": {
        "description": "Initial number of non-directory files in the tree being
deleted.",
        "type": "string"
    },
    "remaining_capacity": {
        "description": "Remaining bytes (data and metadata) used by the tree bei
ng deleted.",
        "type": "string"
    },
    "remaining_directories": {
        "description": "Remaining number of directories in the tree being delete
d.",
        "type": "string"
    },
    "remaining_files": {
        "description": "Remaining number of non-directory files in the tree bein
g deleted.",
        "type": "string"
    },
    "last_error_message": {
        "description": "The message from the last error that caused this job to
be aborted.",
        "type": "string"
    }
}

```



```
}
  }
}
}
```

POST

Start unlinking this directory and all its contents.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "tree_delete_job_post",
  "type": "object",
  "properties": {
    "id": {
      "description": "The file ID or the absolute path to the file system object. File IDs can be found in the id field of responses of APIs that return file attributes. You must URL-encode the paths. The APIs & Tools page in the Qumulo Core Web UI URL-encodes the paths.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
202	Return value on success

tree-delete/jobs/restart/{id}

Endpoint

`/v1/tree-delete/jobs/restart/{id}`

POST

Restart execution of a directory tree deletion job that has hit an error on a filelock.

Parameters

Name	Description	Required
<code>id</code>	Job ID	Yes

Response

Codes

Code	Description
202	Return value on success

tree-delete/jobs/{id}

Endpoint

/v1/tree-delete/jobs/{id}

GET

Get status of directory-tree deletion on the specified directory. If the job has finished, returns 404. Also returns 404 if there was never a job on the given object

Parameters

Name	Description	Required
id	Job ID	Yes

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "tree_delete_job_status",
  "type": "object",
  "properties": {
    "id": {
      "description": "The ID of the directory being deleted.",
      "type": "string"
    },
    "create_time": {
      "description": "The time the job was created. It may not have started at that time if the system was processing other jobs.",
      "type": "string"
    },
    "mode": {
      "type": "string",
      "enum": [
        "PLACE"
      ]
    }
  }
}
```

```

    "description": "The tree delete mode this job is running in.:\\n * `PLACE` - TREE_DELETE_IN_PLACE"
  },
  "initial_path": {
    "description": "The path of the directory at the time the job was started.",
    "type": "string"
  },
  "initial_capacity": {
    "description": "Initial bytes (data and metadata) used by the tree being deleted.",
    "type": "string"
  },
  "initial_directories": {
    "description": "Initial number of directories in the tree being deleted.",
    "type": "string"
  },
  "initial_files": {
    "description": "Initial number of non-directory files in the tree being deleted.",
    "type": "string"
  },
  "remaining_capacity": {
    "description": "Remaining bytes (data and metadata) used by the tree being deleted.",
    "type": "string"
  },
  "remaining_directories": {
    "description": "Remaining number of directories in the tree being deleted.",
    "type": "string"
  },
  "remaining_files": {
    "description": "Remaining number of non-directory files in the tree being deleted.",
    "type": "string"
  },
  "last_error_message": {
    "description": "The message from the last error that caused this job to be aborted.",
    "type": "string"
  }
}

```

DELETE

Cancel directory-tree deletion on the specified directory. If the job has finished, returns 404. Also returns 404 if there was never a job on the given object

Parameters

Name	Description	Required
id	Job ID	Yes

Response

Codes

Code	Description
200	Return value on success

node/state

Endpoint

/v1/node/state

GET

Retrieves node state of the node that the call was made to.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_node_state",
  "type": "object",
  "properties": {
    "node_id": {
      "description": "node-id of the node responding to the get",
      "type": "number"
    },
    "state": {
      "type": "string",
      "enum": [
        "UNCONFIGURED",
        "STOPPED",
        "PAUSED",
        "ACTIVE",
        "REMOVED"
      ],
      "description": "The state of the node:\n * `ACTIVE` - Configured node part of active quorum,\n * `PAUSED` - Configured node part of paused quorum,\n * `REMOVED` - Configured node that has been removed from its cluster,\n * `STOPPED` - Configured node not part of quorum,\n * `UNCONFIGURED` - Unconfigured node"
    }
  }
}
```

```
"cluster_id": {  
  "description": "Unique identifier of cluster the node belongs to or the empty  
string (') if the node is unconfigured",  
  "type": "string"  
}  
}  
}
```

unconfigured/nodes/

Endpoint

/v1/unconfigured/nodes/

GET

List the unconfigured nodes discovered on the local network.

Parameters

Name	Description	Required
<code>include-incompatibles</code>	Include incompatible unconfigured nodes in the discover response. Defaults to false.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_unconfigured_nodes_response",
  "type": "object",
  "properties": {
    "nodes": {
      "type": "array",
      "items": {
        "description": "nodes",
        "type": "object",
        "properties": {
          "uuid": {
            "description": "Unique node identifier",
            "type": "string"
          },
          "label": {
            "description": "Physically identifiable label assigned to the hardware",
            "type": "string"
          }
        }
      }
    }
  }
}
```



```

"serial_number": {
  "description": "Node serial number",
  "type": "string"
},
"model_number": {
  "description": "Node model number",
  "type": "string"
},
"capacity_in_bytes": {
  "description": "Raw capacity of the node",
  "type": "string"
},
"disk_info": {
  "description": "Node disk info",
  "type": "object",
  "properties": {
    "slot_counts": {
      "description": "slot_counts",
      "type": "object",
      "properties": {
        "hdds": {
          "description": "hdds",
          "type": "number"
        },
        "ssds": {
          "description": "ssds",
          "type": "number"
        }
      }
    }
  },
  "ssd_partition_size": {
    "description": "ssd_partition_size",
    "type": "string"
  },
  "hdd_partition_size": {
    "description": "hdd_partition_size",
    "type": "string"
  }
},
"node_version": {
  "description": "Version",
  "type": "object",
  "properties": {
    "revision_id": {
      "description": "revision_id",

```

```

        "type": "string"
    },
    "build_id": {
        "description": "build_id",
        "type": "string"
    },
    "flavor": {
        "description": "flavor",
        "type": "string"
    },
    "build_date": {
        "description": "build_date",
        "type": "string"
    }
}
}
}
},
"current_node_uuid": {
    "description": "UUID of the current node",
    "type": "string"
}
}
}

```

unconfigured/nodes/

Endpoint

/v1/unconfigured/nodes/

GET

List the unconfigured nodes discovered on the local network.

Parameters

Name	Description	Required
<code>include-incompatibles</code>	Include incompatible unconfigured nodes in the discover response. Defaults to false.	No

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_unconfigured_nodes_response",
  "type": "object",
  "properties": {
    "nodes": {
      "type": "array",
      "items": {
        "description": "nodes",
        "type": "object",
        "properties": {
          "uuid": {
            "description": "Unique node identifier",
            "type": "string"
          },
          "label": {
            "description": "Physically identifiable label assigned to the hardware",
            "type": "string"
          }
        }
      }
    }
  }
}
```

```

"serial_number": {
  "description": "Node serial number",
  "type": "string"
},
"model_number": {
  "description": "Node model number",
  "type": "string"
},
"capacity_in_bytes": {
  "description": "Raw capacity of the node",
  "type": "string"
},
"disk_info": {
  "description": "Node disk info",
  "type": "object",
  "properties": {
    "slot_counts": {
      "description": "slot_counts",
      "type": "object",
      "properties": {
        "hdds": {
          "description": "hdds",
          "type": "number"
        },
        "ssds": {
          "description": "ssds",
          "type": "number"
        }
      }
    }
  },
  "ssd_partition_size": {
    "description": "ssd_partition_size",
    "type": "string"
  },
  "hdd_partition_size": {
    "description": "hdd_partition_size",
    "type": "string"
  }
},
"node_version": {
  "description": "Version",
  "type": "object",
  "properties": {
    "revision_id": {
      "description": "revision_id",

```

```

        "type": "string"
    },
    "build_id": {
        "description": "build_id",
        "type": "string"
    },
    "flavor": {
        "description": "flavor",
        "type": "string"
    },
    "build_date": {
        "description": "build_date",
        "type": "string"
    }
}
}
}
},
"current_node_uuid": {
    "description": "UUID of the current node",
    "type": "string"
}
}
}

```

version

Endpoint

/v1/version

GET

Retrieve the version of the appliance.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_version_info",
  "type": "object",
  "properties": {
    "revision_id": {
      "description": "revision_id",
      "type": "string"
    },
    "build_id": {
      "description": "build_id",
      "type": "string"
    },
    "flavor": {
      "description": "flavor",
      "type": "string"
    },
    "build_date": {
      "description": "build_date",
      "type": "string"
    }
  }
}
```

upgrade/blocked

Endpoint

/v2/upgrade/blocked

GET

Check if upgrade is currently blocked.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_upgrade_blocked_response",
  "type": "object",
  "properties": {
    "is_blocked": {
      "description": "is_blocked",
      "type": "boolean"
    },
    "cluster_degraded": {
      "description": "cluster_degraded",
      "type": "boolean"
    },
    "blocked_reason": {
      "description": "blocked_reason",
      "type": "string"
    }
  }
}
```

upgrade/commit

Endpoint

`/v2/upgrade/commit`

POST

Commit a prepared upgrade.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
202	Return value on success

upgrade/prepare

Endpoint

/v2/upgrade/prepare

POST

Prepare for upgrade.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_upgrade_prepare_request",
  "type": "object",
  "properties": {
    "image_path": {
      "description": "Path to image to install",
      "type": "string"
    },
    "auto_commit": {
      "description": "If true, the system will automatically commit when prepare is complete",
      "type": "boolean"
    },
    "do_rolling_reboot": {
      "description": "If true, do a rolling reboot after the upgrade is committed if doing a full platform upgrade",
      "type": "boolean"
    },
    "num_nodes_to_reboot": {
      "description": "If the number of nodes to reboot is configured and rolling reboot is enabled, your cluster reboots the specified number of nodes at a time. The number of nodes must be greater than 0 and less than or equal to the number of node failures that your cluster permits. By default, the value is the number of permitted node failures minus 1 (1 node minimum).",
      "type": "number"
    }
  }
}
```

Response

Codes

Code	Description
202	Return value on success

upgrade/status

Endpoint

/v2/upgrade/status

GET

Retrieve the current status of the upgrade system. This API is deprecated in favor of /v3/upgrade/status.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "upgrade_status",
  "type": "object",
  "properties": {
    "state": {
      "type": "string",
      "enum": [
        "UPGRADE_STATE_IDLE",
        "UPGRADE_STATE_PREPARING",
        "UPGRADE_STATE_PREPARED",
        "UPGRADE_STATE_COMMITTING",
        "UPGRADE_STATE_COMMITTED",
        "UPGRADE_STATE_REBOOTING"
      ],
      "description": "state:\n * `UPGRADE_STATE_COMMITTED` - UPGRADE_STATE_COMMITTE\nD,\n * `UPGRADE_STATE_COMMITTING` - UPGRADE_STATE_COMMITTING,\n * `UPGRADE_STATE_IDL\nE` - UPGRADE_STATE_IDLE,\n * `UPGRADE_STATE_PREPARED` - UPGRADE_STATE_PREPARED,\n * `UPGRADE_STATE_PREPARING` - UPGRADE_STATE_PREPARING,\n * `UPGRADE_STATE_REBOOTING`\n - UPGRADE_STATE_REBOOTING"
    },
    "progress": {
```

```

    "description": "progress",
    "type": "number"
  },
  "settings": {
    "description": "settings",
    "type": "object",
    "properties": {
      "install_path": {
        "description": "install_path",
        "type": "string"
      },
      "target_version": {
        "description": "target_version",
        "type": "string"
      },
      "upgrade_type": {
        "type": "string",
        "enum": [
          "SOFTWARE_ONLY",
          "SOFTWARE_AND_PLATFORM"
        ],
        "description": "upgrade_type:\n * `SOFTWARE_AND_PLATFORM` - SOFTWARE_AND_P
PLATFORM,\n * `SOFTWARE_ONLY` - SOFTWARE_ONLY"
      },
      "auto_commit": {
        "description": "auto_commit",
        "type": "boolean"
      },
      "do_rolling_reboot": {
        "description": "do_rolling_reboot",
        "type": "boolean"
      },
      "num_nodes_to_reboot": {
        "description": "num_nodes_to_reboot",
        "type": "number"
      }
    }
  },
  "error_info": {
    "description": "error_info",
    "type": "string"
  }
}

```

upgrade/verify-image

Endpoint

/v2/upgrade/verify-image

POST

Verify that the given image can be used to upgrade the cluster and retrieve details about the upgrade that will occur.

Parameters

This resource has no parameters.

Request

Schema

```
{
  "description": "api_verify_request",
  "type": "object",
  "properties": {
    "image_path": {
      "description": "image_path",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "upgrade_verify_result",
  "type": "object",
  "properties": {
    "target_version": {
```

```

    "description": "target_version",
    "type": "string"
  },
  "upgrade_type": {
    "type": "string",
    "enum": [
      "SOFTWARE_ONLY",
      "SOFTWARE_AND_PLATFORM"
    ],
    "description": "upgrade_type:\n * `SOFTWARE_AND_PLATFORM` - SOFTWARE_AND_PLATF
ORM,\n * `SOFTWARE_ONLY` - SOFTWARE_ONLY"
  },
  "error": {
    "description": "error",
    "type": "string"
  },
  "error_class": {
    "description": "error_class",
    "type": "string"
  }
}

```

upgrade/status

Endpoint

/v3/upgrade/status

GET

Retrieve the current status of the upgrade system.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "upgrade_status",
  "type": "object",
  "properties": {
    "state": {
      "type": "string",
      "enum": [
        "UPGRADE_STATE_IDLE",
        "UPGRADE_STATE_PREPARING",
        "UPGRADE_STATE_PREPARED",
        "UPGRADE_STATE_COMMITTING",
        "UPGRADE_STATE_COMMITTED",
        "UPGRADE_STATE_REBOOTING"
      ],
      "description": "state:\n * `UPGRADE_STATE_COMMITTED` - UPGRADE_STATE_COMMITTE\nD,\n * `UPGRADE_STATE_COMMITTING` - UPGRADE_STATE_COMMITTING,\n * `UPGRADE_STATE_IDL\nE` - UPGRADE_STATE_IDLE,\n * `UPGRADE_STATE_PREPARED` - UPGRADE_STATE_PREPARED,\n * `UPGRADE_STATE_PREPARING` - UPGRADE_STATE_PREPARING,\n * `UPGRADE_STATE_REBOOTING`\n - UPGRADE_STATE_REBOOTING"
    },
    "progress": {
      "description": "progress",

```

```

    "type": "number"
  },
  "settings": {
    "description": "settings",
    "type": "object",
    "properties": {
      "install_path": {
        "description": "install_path",
        "type": "string"
      },
      "target_version": {
        "description": "target_version",
        "type": "string"
      },
      "upgrade_type": {
        "type": "string",
        "enum": [
          "SOFTWARE_ONLY",
          "SOFTWARE_AND_PLATFORM"
        ],
        "description": "upgrade_type:\n * `SOFTWARE_AND_PLATFORM` - SOFTWARE_AND_P
PLATFORM,\n * `SOFTWARE_ONLY` - SOFTWARE_ONLY"
      },
      "auto_commit": {
        "description": "auto_commit",
        "type": "boolean"
      },
      "do_rolling_reboot": {
        "description": "do_rolling_reboot",
        "type": "boolean"
      },
      "num_nodes_to_reboot": {
        "description": "num_nodes_to_reboot",
        "type": "number"
      }
    }
  },
  "error_info": {
    "description": "error_info",
    "type": "string"
  }
}

```


version

Endpoint

/v1/version

GET

Retrieve the version of the appliance.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "api_version_info",
  "type": "object",
  "properties": {
    "revision_id": {
      "description": "revision_id",
      "type": "string"
    },
    "build_id": {
      "description": "build_id",
      "type": "string"
    },
    "flavor": {
      "description": "flavor",
      "type": "string"
    },
    "build_date": {
      "description": "build_date",
      "type": "string"
    }
  }
}
```

web-ui/settings

Endpoint

/v1/web-ui/settings

GET

Return settings (such as the inactivity timeout) that the Web UI uses. Because the Web UI can apply these settings before the user logs in, this method doesn't require authentication.

Parameters

This resource has no parameters.

Response

Codes

Code	Description
200	Return value on success

Schema

```
{
  "description": "web_ui_settings",
  "type": "object",
  "properties": {
    "inactivity_timeout": {
      "description": "When set, the Web UI logs out users after they are inactive for the specified time duration.",
      "type": "object",
      "properties": {
        "nanoseconds": {
          "description": "nanoseconds",
          "type": "string"
        }
      }
    },
    "login_banner": {
      "description": "When set, the Web UI shows a banner with the specified Markdown string on the login screen.",
      "type": "string"
    }
  }
}
```

```
}
```

PUT

Replace all the settings that the Web UI uses. These settings take effect immediately for new UI sessions.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
  "description": "web_ui_settings",
  "type": "object",
  "properties": {
    "inactivity_timeout": {
      "description": "When set, the Web UI logs out users after they are inactive for the specified time duration.",
      "type": "object",
      "properties": {
        "nanoseconds": {
          "description": "nanoseconds",
          "type": "string"
        }
      }
    },
    "login_banner": {
      "description": "When set, the Web UI shows a banner with the specified Markdown string on the login screen.",
      "type": "string"
    }
  }
}
```

Response

Codes

Code	Description
------	-------------

200	Return value on success
-----	-------------------------

Schema

```
{
  "description": "web_ui_settings",
  "type": "object",
  "properties": {
    "inactivity_timeout": {
      "description": "When set, the Web UI logs out users after they are inactive for the specified time duration.",
      "type": "object",
      "properties": {
        "nanoseconds": {
          "description": "nanoseconds",
          "type": "string"
        }
      }
    },
    "login_banner": {
      "description": "When set, the Web UI shows a banner with the specified Markdown string on the login screen.",
      "type": "string"
    }
  }
}
```

PATCH

Replace individual Web UI settings. These settings take effect immediately for new Web UI sessions.

Parameters

Name	Description	Required
If-Match	ETag for expected version	No

Request

Schema

```
{
```

```

"description": "web_ui_settings_patch",
"type": "object",
"properties": {
  "inactivity_timeout": {
    "description": "When set, the Web UI logs out users after they are inactive for the specified time duration.",
    "type": "object",
    "properties": {
      "nanoseconds": {
        "description": "nanoseconds",
        "type": "string"
      }
    }
  },
  "login_banner": {
    "description": "When set, the Web UI shows a banner with the specified Markdown string on the login screen.",
    "type": "string"
  }
}
}

```

Response

Codes

Code	Description
200	Return value on success

Schema

```

{
  "description": "web_ui_settings",
  "type": "object",
  "properties": {
    "inactivity_timeout": {
      "description": "When set, the Web UI logs out users after they are inactive for the specified time duration.",
      "type": "object",
      "properties": {
        "nanoseconds": {
          "description": "nanoseconds",
          "type": "string"
        }
      }
    }
  }
}

```

```
    }  
  },  
  "login_banner": {  
    "description": "When set, the Web UI shows a banner with the specified Markdow  
n string on the login screen.",  
    "type": "string"  
  }  
}  
}
```