




ggpedigree: Visualizing Pedigrees with ‘ggplot2’ and ‘plotly’

S. Mason Garrison ¹✉

¹ Department of Psychology, Wake Forest University, North Carolina, USA ✉ Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright,
and release the work under a
Creative Commons Attribution 4.0
International License ([CC BY 4.0](#)).

Summary

Pedigree diagrams underpin research and practice across genetics, animal breeding, genealogy, forensics, and counseling. They help medical geneticists trace the inheritance of Mendelian diseases and identify at-risk relatives; enable dairy breeders to plan matings that improve milk yield; support genealogists in reconstructing ancestry; assist forensic scientists in establishing familial connections in criminal investigations; and facilitate family therapists and counselors in understanding their clients’ relationships (McGoldrick, Gerson, & Petry, 2020). Early R tools such as kinship2 (Sinnwell, Therneau, & Schaid, 2014) plot simple nuclear families effectively, but they do not scale to today’s pedigrees that can exceed 1,000s of individuals. As datasets have grown, researchers now work with increasingly complex family structures, including large-scale plant breeding pedigrees (Shaw, Graham, Kennedy, Milne, & Marshall, 2014), web-based pedigree management systems (Ranaweera, Makalic, Hopper, & Bickerstaffe, 2018), interactive pedigree editors (Carver et al., 2018), and behavior genetic studies of extended family structures (Garrison et al., 2023; Hunter, Garrison, Burt, & Rodgers, 2021). That complexity exposes the limitations of existing tools, which often struggle with large and complex datasets. ggpedigree addresses this need by combining a vectorised layout algorithm, ggplot2 output, and optional plotly interactivity.

Statement of need

Pedigree visualization has traditionally relied on proprietary software (e.g., Progeny, GenoPro, Pedigree Viewer) or R packages like kinship2 (Sinnwell et al., 2014), pedtools (Vigeland, 2021a), or pedtricks (J. Martin, Wolak, Johnston, & Morrissey, 2025). While these tools are functional for many use cases, their limitations become pronounced when working with complex, modern pedigree datasets or when more detailed customization is required. Most R packages focus on base graphics or simple ggplot2 implementations.

Existing R solutions face three main challenges. First, current solutions are often poorly integrated with tidyverse workflows and do not expose the full theming and layering capabilities familiar to ggplot2 users (Wickham, 2016). In animal-focused workflows, rapid rendering seems to take precedence over aesthetic flexibility. I suspect that this is because users tend to work with more uniform data and fewer phenotypes. By contrast, human-focused workflows—particularly in behavior genetics and genetic epidemiology (Garrison et al., 2023; Lyu et al., 2025; McArdle & McDonald, 1984)—require closer integration with tidyverse pipelines and more flexible plotting systems to accommodate complex pedigree structures and harmonization of phenotypes across data sources. In other words, the needs are different.

Second, most R-based tools offer no interactivity. Static graphics are often sufficient for publication, but interactivity improves exploration and communication during model development or data cleaning. A notable exception is pedtools (Vigeland, 2021b), which offers a sister shiny

41 app, QuickPed (Vigeland, 2022). While the R ecosystem includes libraries, like plotly, that
42 support interactive plotting, these features have yet to be integrated into pedigree functions.

43 Third, scalability and extensibility remain limited across existing tools. Several R packages
44 attempt to address these challenges with built-in pedigree plotting functions. kinship2
45 (Sinnwell et al., 2014) remains widely used but produces static base graphics and relies on non-
46 vectorized recursive layout functions that do not scale well to large families. A partial ggplot2
47 implementation exists in a modernized kinship2 (called Pedexplorer, Le Nézet, Sinnwell,
48 Letko, André, & Quignon, 2025), but is non-vectorized and incompatible with other ggplot2
49 layers. pedtricks, a revival of pedantics (Morrissey & Wilson, 2010), provides a ggplot2-
50 based implementation for large animal pedigrees but lacks extensibility and interactivity. The
51 geneHapR (Zhang, Jia, & Diao, 2023) package focuses on haplotype visualization rather than
52 general pedigree structure. The pedgene package (Schaid & Sinnwell, 2024) offers some
53 plotting functions but is primarily designed for association testing. The pedigreejs package
54 (Carver et al., 2018) provides an interactive pedigree editor but does not integrate with R or
55 ggplot2, limiting its utility for R users.

56 None of these packages offers the combination of modern ggplot2 integration, interactive
57 capabilities, and extensibility that ggpedigree provides. ggpedigree addresses these limitations
58 by providing a comprehensive visualization framework built on modern R graphics infrastructure.
59 It leverages the extensive customization capabilities of ggplot2 while adding specialized
60 functionality for pedigree-specific visualization challenges.

61 Software Architecture

62 ggpedigree is built on a modular architecture that separates data processing, layout calculation,
63 and visualization layers. The core workflow involves: (1) data standardization and family
64 structure analysis using BGmisc functions, (2) coordinate calculation using algorithms adapted
65 from kinship2, (3) relationship connection mapping, and (4) layer-based plot construction
66 using ggplot2 geometry functions. This design allows users to customize any aspect of the
67 visualization while maintaining computational efficiency for large pedigrees. The package
68 integrates tightly with the broader R ecosystem, particularly the tidyverse (Wickham et al.,
69 2019) and BGmisc (Garrison, S. M., Hunter, Michael D., Lyu, X., Trattner, J. D., & Burt,
70 S. A., 2024). All functions return standard R objects (ggplot or plotly) that can be further
71 customized.

72 Features

73 I describe the main features of the ggpedigree package below. More detailed descriptions of
74 features and usage is available in the [package vignettes](#), including examples of how to create
75 static and interactive pedigree plots, customize aesthetics, and visualize relatedness matrices.
76 Additional example data include squirrel data from the Kluane Red Squirrel Project (McFarlane
77 et al., 2014, 2015) and Targaryen family data from the Song of Ice and Fire universe (G. R. R.
78 Martin, 1997, 2018).


- 79 ■ Data Standardization and Family Structure Analysis: ggPedigree() integrates with
80 BGmisc functions like ped2fam() to organize individuals by family, recodeSex() to
81 standardize sex coding, and checkParentIDs() to validate pedigree structures. The
82 function handles consanguineous relationships and individuals appearing in multiple
83 pedigree positions.
- 84 ■ Coordinate Calculation: calculateCoordinates() computes optimal positioning for indi-
85 viduals using algorithms adapted from kinship2::align.pedigree, with enhancements
86 for large multi-generational pedigrees and complex family structures. These steps are
87 vectorized as much as possible to ensure computational efficiency and compatibility with
88 ggplot2.

- 89 ■ Relationship Connection Mapping: `calculateConnections()` generates connection paths
90 between family members, mapping parent-child, sibling, spousal, and twin relationships.
91 The function determines midpoints for line intersections and handles overlapping con-
92 nections with specialized curved segments. These calculations are optimized for large
93 datasets by using vectorized operations rather than the loop-based approaches used in
94 `kinship2`.
- 95 ■ Layer-based Plot Construction: `ggPedigree()` constructs plots using `ggplot2` geometry
96 functions, returning standard `ggplot2` objects that integrate with existing R workflows.
97 `ggPedigreeInteractive()` extends plots into interactive `plotly` widgets. A config system
98 allows customization of over 100 aesthetic and layout parameters.
- 99 ■ Individual Highlighting: Advanced functionality to highlight specific individuals and their
100 relatives based on additive genetic, mitochondrial, or other relationship matrices.
- 101 ■ Specific Visualization Functions: `ggPedigree()` creates static pedigree plots using
102 `ggplot2`. `ggPedigreeInteractive()` generates interactive pedigree plots using `plotly`.
103 `ggRelatednessMatrix()` creates customizable heatmaps for relatedness matrices with
104 support for hierarchical clustering, and seamless integration with `BGmisc` relatedness
105 calculations. `ggPhenotypeByDegree()` visualizes phenotypic correlations as a function
106 of genetic relatedness, including confidence intervals and statistical summaries for
107 quantitative genetic analysis.


108 Code example

109 This example shows how to use `ggpedigree` to visualize a pedigree. The potter dataset
110 includes several wizarding families from the Harry Potter series.

```
ggPedigree(potter,
  famID = "famID",
  personID = "personID"
)
```



111
112 I demonstrate several advanced features by restyling the figure from (Hunter et al., 2025), to
113 follow the Wake Forest brand identity guidelines; source code is in the appendix.



I have combined two figures using patchwork (Pedersen, 2025): panel (a) highlights unique mitochondrial lines in the Dursley and Evans families, while panel (b) shows the full pedigree with Molly Weasley's mitochondrial descendants in gold.

Collectively, these tools provide a valuable resource for behavior geneticists and others who work with extended family data. They were developed as part of a grant and have been used in several ongoing projects, presentations (Garrison, 2024; Hunter, Garrison, Lyu, Good, & Burt, 2024), and forthcoming papers (Burt et al., 2025; Hunter et al., 2025; Lyu et al., 2025).

Availability

The ggpedigree package is open-source and available on both GitHub at <https://github.com/R-Computing-Lab/ggpedigree> and the Comprehensive R Archive Network (CRAN) at <https://cran.r-project.org/package=ggpedigree>. It is licensed under the GNU General Public License.

Acknowledgments

The current research is supported by the National Institute on Aging (NIA), RF1-AG073189. The author would like to thank Michael Hunter for his enthusiasm for the development of this package.

References

- Burt, S. A., Garrison, S. M., Lyu, X., Rodgers, J. L., Carroll, S. L., Smith, K. R., & Hunter, M. D. (2025). Contributions of inherited mtDNA to longevity: Evidence from extended pedigrees with 176 million kinship pairs. *eBioMedicine*, 119, 105911. doi:<https://doi.org/10.1016/j.ebiom.2025.105911>
- Carver, T., Cunningham, A. P., Babb de Villiers, C., Lee, A., Hartley, S., Tischkowitz, M., Walter, F. M., et al. (2018). Pedigreejs: A web-based graphical pedigree editor. *Bioinformatics*, 34(6), 1069–1071. doi:[10.1093/bioinformatics/btx705](https://doi.org/10.1093/bioinformatics/btx705)

- 139 Garrison, S. M. (2024). Charting new paths in behavior genetics: Developing a comprehensive
140 r visualization atlas. *Behavior Genetics* (Vol. 54, p. 488488). doi:[10.1007/s10519-024-](https://doi.org/10.1007/s10519-024-10197-8)
141 [10197-8](https://doi.org/10.1007/s10519-024-10197-8)
- 142 Garrison, S. M., Hunter, Michael D., Lyu, X., Trattner, J. D., & Burt, S. A. (2024). BGmisc:
143 An r package for extended behavior genetics analysis. *Journal of Open Source Software*,
144 9(94). doi:[10.21105/joss.06203](https://doi.org/10.21105/joss.06203)
- 145 Garrison, S. M., Lyu, X., Hunter, M. D., Rodgers, J. L., Smith, K. R., Coon, H., & Burt, S.
146 A. (2023). Analyzing extended cousin similarity to unravel the mystery of mtDNA and
147 longevity. *Behavior Genetics*. doi:[10.1007/s10519-023-10156-9](https://doi.org/10.1007/s10519-023-10156-9)
- 148 Hunter, M. D., Garrison, S. M., Burt, S. A., & Rodgers, J. L. (2021). The Analytic Identification
149 of Variance Component Models Common to Behavior Genetics. *Behavior Genetics*, 51(4),
150 425–437. doi:[10.1007/s10519-021-10055-x](https://doi.org/10.1007/s10519-021-10055-x)
- 151 Hunter, M. D., Garrison, S. M., Lyu, X., Good, R., & Burt, S. A. (2024). Tools for
152 biometric modeling in large population databases. *Behavior Genetics* (Vol. 54, p. 531531).
153 doi:[10.1007/s10519-024-10197-8](https://doi.org/10.1007/s10519-024-10197-8)
- 154 Hunter, M. D., Garrison, S. M., Lyu, X., Good, R., Carroll, S. L., & Burt, S. A. (2025). *Tracing*
155 *the right path: Determination of large pedigree segmentation and relatedness. Revise and*
156 *Resubmit at Behavior Genetics*.
- 157 Le Nézet, L., Sinnwell, J., Letko, A., André, C., & Quignon, P. (2025). Pedixplorer: A
158 bioconductor package to streamline pedigree design and visualization. *Bioinformatics*,
159 41(6), btaf329. doi:[10.1093/bioinformatics/btaf329](https://doi.org/10.1093/bioinformatics/btaf329)
- 160 Lyu, X., Hunter, M. D., Burt, S. A., Good, R., Carroll, S. L., & Garrison, S. M. (2025).
161 Detecting mtDNA effects with an extended pedigree model: An analysis of statistical power
162 and estimation bias. *Behavior Genetics*. doi:[10.1007/s10519-025-10225-1](https://doi.org/10.1007/s10519-025-10225-1)
- 163 Martin, G. R. R. (1997). *A game of thrones* (Vol. 1). Bantam.
- 164 Martin, G. R. R. (2018). *Fire & blood: 300 years before a game of thrones*. New York:
165 Random House Worlds.
- 166 Martin, J., Wolak, M., Johnston, S., & Morrissey, M. (2025). *Pedtricks: Visualize, summarize*
167 *and simulate data from pedigrees*. doi:[10.32614/CRAN.package.pedtricks](https://doi.org/10.32614/CRAN.package.pedtricks)
- 168 McArdle, J. J., & McDonald, R. P. (1984). Some algebraic properties of the reticular action
169 model for moment structures. *British Journal of Mathematical and Statistical Psychology*,
170 37, 234–251. doi:[10.1111/j.2044-8317.1984.tb00802.x](https://doi.org/10.1111/j.2044-8317.1984.tb00802.x)
- 171 McFarlane, S. E., Boutin, S., Humphries, M. M., McAdam, A. G., Gorrell, J. C., & Colt-
172 man, D. W. (2015, January 21). Data from: Very low levels of direct additive ge-
173 netic variance in fitness and fitness components in a red squirrel population. Dryad.
174 doi:[10.5061/DRYAD.N5Q05](https://doi.org/10.5061/DRYAD.N5Q05)
- 175 McFarlane, S. E., Gorrell, J. C., Coltman, D. W., Humphries, M. M., Boutin, S., & McAdam,
176 A. G. (2014). Very low levels of direct additive genetic variance in fitness and fitness
177 components in a red squirrel population. *Ecology and Evolution*, 4(10), 1729–1738.
178 doi:[10.1002/ece3.982](https://doi.org/10.1002/ece3.982)
- 179 McGoldrick, M., Gerson, R., & Petry, S. (2020). *Genograms: Assessment and Treatment*.
180 Erscheinungsort nicht ermittelbar: W. W. Norton & Company.
- 181 Morrissey, M. B., & Wilson, A. J. (2010). pedantics: an r package for pedigree-based genetic
182 simulation and pedigree manipulation, characterization and viewing. *Molecular Ecology*
183 *Resources*, 10(4), 711–719. doi:[10.1111/j.1755-0998.2009.02817.x](https://doi.org/10.1111/j.1755-0998.2009.02817.x)
- 184 Pedersen, T. L. (2025). *Patchwork: The composer of plots*. doi:[10.32614/CRAN.pack-](https://doi.org/10.32614/CRAN.package.patchwork)
185 [age.patchwork](https://doi.org/10.32614/CRAN.package.patchwork)

- 186 Ranaweera, T., Makalic, E., Hopper, J. L., & Bickerstaffe, A. (2018). An open-source,
187 integrated pedigree data management and visualization tool for genetic epidemiology.
188 *International Journal of Epidemiology*, 47(4), 1034–1039. doi:[10.1093/ije/dyy049](https://doi.org/10.1093/ije/dyy049)
- 189 Schaid, D., & Sinnwell, J. (2024). Pedgene: Gene-level variant association tests for pedigree
190 data. doi:[10.32614/CRAN.package.pedgene](https://doi.org/10.32614/CRAN.package.pedgene)
- 191 Shaw, P. D., Graham, M., Kennedy, J., Milne, I., & Marshall, D. F. (2014). Helium: Visualiza-
192 tion of large scale plant pedigrees. *BMC Bioinformatics*, 15(1), 259. doi:[10.1186/1471-](https://doi.org/10.1186/1471-2105-15-259)
193 [2105-15-259](https://doi.org/10.1186/1471-2105-15-259)
- 194 Sinnwell, J. P., Therneau, T. M., & Schaid, D. J. (2014). The kinship2 r package for pedigree
195 data. *Human Heredity*, 78, 91–93. doi:[10.1159/000363105](https://doi.org/10.1159/000363105)
- 196 Vigeland, M. D. (2021b). *Pedigree analysis in r*. London: Academic Press, an imprint of
197 Elsevier. Retrieved from [https://shop.elsevier.com/books/pedigree-analysis-in-r/vigeland/](https://shop.elsevier.com/books/pedigree-analysis-in-r/vigeland/978-0-12-824430-2)
198 [978-0-12-824430-2](https://shop.elsevier.com/books/pedigree-analysis-in-r/vigeland/978-0-12-824430-2)
- 199 Vigeland, M. D. (2021a). *Pedigree analysis in {r}*. doi:[10.32614/CRAN.package.pedtools](https://doi.org/10.32614/CRAN.package.pedtools)
- 200 Vigeland, M. D. (2022). QuickPed: An online tool for drawing pedigrees and analysing
201 relatedness. *BMC Bioinformatics*, 23(1), 220. doi:[10.1186/s12859-022-04759-y](https://doi.org/10.1186/s12859-022-04759-y)
- 202 Wickham, H. (2016). *ggplot2*. Use R! Cham: Springer International Publishing.
203 doi:[10.1007/978-3-319-24277-4](https://doi.org/10.1007/978-3-319-24277-4)
- 204 Wickham, H., Averick, M., Bryan, J., Chang, W., McGowan, L., François, R., Grolemond, G.,
205 et al. (2019). Welcome to the tidyverse. *Journal of Open Source Software*, 4(43), 1686.
206 doi:[10.21105/joss.01686](https://doi.org/10.21105/joss.01686)
- 207 Zhang, R., Jia, G., & Diao, X. (2023). geneHapR: An r package for gene haplotypic statistics
208 and visualization. *BMC Bioinformatics*, 24(1), 199. doi:[10.1186/s12859-023-05318-9](https://doi.org/10.1186/s12859-023-05318-9)