

# <sup>1</sup> `ggpedigree`: Visualizing Pedigrees with ‘`ggplot2`’ and <sup>2</sup> ‘`plotly`’

<sup>3</sup> **S. Mason Garrison**  

<sup>4</sup> 1 Department of Psychology, Wake Forest University, North Carolina, USA  Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

---

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## <sup>5</sup> Summary

Pedigree diagrams underpin research and practice across genetics, animal breeding, genealogy, forensics, and counseling. They help medical geneticists trace the inheritance of Mendelian diseases and identify at-risk relatives; enable dairy breeders to plan matings that improve milk yield; support genealogists in reconstructing ancestry; assist forensic scientists in establishing familial connections in criminal investigations; and facilitate family therapists and counselors in understanding their clients’ relationships (McGoldrick, Gerson, & Petry, 2020). Early R tools such as `kinship2` (Sinnwell, Therneau, & Schaid, 2014) plot simple nuclear families effectively, but they do not scale to today’s pedigrees that can exceed 1,000s of individuals. As datasets have grown, researchers now work with increasingly complex family structures, including large-scale plant breeding pedigrees (Shaw, Graham, Kennedy, Milne, & Marshall, 2014), web-based pedigree management systems (Ranaweera, Makalic, Hopper, & Bickerstaffe, 2018), interactive pedigree editors (Carver et al., 2018), and behavior genetic studies of extended family structures (Garrison et al., 2023; Hunter, Garrison, Burt, & Rodgers, 2021). That complexity exposes the limitations of existing tools, which often struggle with large and complex datasets. `ggpedigree` addresses this need by combining a vectorised layout algorithm, `ggplot2` output, and optional `plotly` interactivity.

## <sup>22</sup> Statement of need

Pedigree visualization has traditionally relied on proprietary software (e.g., Progeny, GenoPro, Pedigree Viewer) or R packages like `kinship2` (Sinnwell et al., 2014), `pedtools` (Vigeland, 2021a), or `pedtricks` (J. Martin, Wolak, Johnston, & Morrissey, 2025). While these tools are functional for many use cases, their limitations become pronounced when working with complex, modern pedigree datasets or when more detailed customization is required. Most R packages focus on base graphics or simple `ggplot2` implementations.

Existing R solutions face three main challenges. First, current solutions are often poorly integrated with tidyverse workflows and do not expose the full theming and layering capabilities familiar to `ggplot2` users (Wickham, 2016). In animal-focused workflows, rapid rendering seems to takes precedence over aesthetic flexibility. I suspect that this is because users tend to work with more uniform data and fewer phenotypes. By contrast, human-focused workflows—particularly in behavior genetics and genetic epidemiology (Garrison et al., 2023; Lyu et al., 2025; McArdle & McDonald, 1984)—require closer integration with tidyverse pipelines and more flexible plotting systems to accommodate complex pedigree structures and harmonization of phenotypes across data sources. In other words, the needs are different.

Second, most R-based tools offer no interactivity. Static graphics are often sufficient for publication, but interactivity improves exploration and communication during model development or data cleaning. A notable exception is `pedtools` (Vigeland, 2021b), which offers a sister shiny

41 app, QuickPed ([Vigeland, 2022](#)). While the R ecosystem includes libraries, like `plotly`, that  
42 support interactive plotting, these features have yet to be integrated into pedigree functions.

43 Third, scalability and extensibility remain limited across existing tools. Several R packages  
44 attempt to address these challenges with built-in pedigree plotting functions. `kinship2`  
45 ([Sinnwell et al., 2014](#)) remains widely used but produces static base graphics and relies on non-  
46 vectorized recursive layout functions that do not scale well to large families. A partial `ggplot2`  
47 implementation exists in a modernized `kinship2` (called `Pedixplorer`, [Le Nézet, Sinnwell,  
48 Letko, André, & Quignon, 2025](#)), but is non-vectorized and incompatible with other `ggplot2`  
49 layers. `pedtricks`, a revival of `pedantics` ([Morrissey & Wilson, 2010](#)), provides a `ggplot2`-  
50 based implementation for large animal pedigrees but lacks extensibility and interactivity. The  
51 `geneHapR` ([Zhang, Jia, & Diao, 2023](#)) package focuses on haplotype visualization rather than  
52 general pedigree structure. The `pedgene` package ([Schaid & Sinnwell, 2024](#)) offers some  
53 plotting functions but is primarily designed for association testing. The `pedigreejs` package  
54 ([Carver et al., 2018](#)) provides an interactive pedigree editor but does not integrate with R or  
55 `ggplot2`, limiting its utility for R users.

56 None of these packages offers the combination of modern `ggplot2` integration, interactive  
57 capabilities, and extensibility that `ggpeditree` provides. `ggpeditree` addresses these limitations  
58 by providing a comprehensive visualization framework built on modern R graphics infrastructure.  
59 It leverages the extensive customization capabilities of `ggplot2` while adding specialized  
60 functionality for pedigree-specific visualization challenges.

## 61 Software Architecture

62 `ggpeditree` is built on a modular architecture that separates data processing, layout calculation,  
63 and visualization layers. The core workflow involves: (1) data standardization and family  
64 structure analysis using `BGmisc` functions, (2) coordinate calculation using algorithms adapted  
65 from `kinship2`, (3) relationship connection mapping, and (4) layer-based plot construction  
66 using `ggplot2` geometry functions. This design allows users to customize any aspect of the  
67 visualization while maintaining computational efficiency for large pedigrees. The package  
68 integrates tightly with the broader R ecosystem, particularly the `tidyverse` ([Wickham et al.,  
69 2019](#)) and `BGmisc` ([Garrison, S. M., Hunter, Michael D., Lyu, X., Trattner, J. D., & Burt,  
70 S. A., 2024](#)). All functions return standard R objects (`ggplot` or `plotly`) that can be further  
71 customized.

## 72 Features

73 I describe the main features of the `ggpeditree` package below. More detailed descriptions of  
74 features and usage is available in the [package vignettes](#), including examples of how to create  
75 static and interactive pedigree plots, customize aesthetics, and visualize relatedness matrices.  
76 Additional example data include squirrel data from the Kluane Red Squirrel Project ([McFarlane  
77 et al., 2014, 2015](#)) and Targaryen family data from the Song of Ice and Fire universe ([G. R. R.  
78 Martin, 1997, 2018](#)).


- 79     ▪ Data Standardization and Family Structure Analysis: `ggPedigree()` integrates with  
80         `BGmisc` functions like `ped2fam()` to organize individuals by family, `recodeSex()` to  
81         standardize sex coding, and `checkParentIDs()` to validate pedigree structures. The  
82         function handles consanguineous relationships and individuals appearing in multiple  
83         pedigree positions.
- 84     ▪ Coordinate Calculation: `calculateCoordinates()` computes optimal positioning for indi-  
85         viduals using algorithms adapted from `kinship2::align_pedigree`, with enhancements  
86         for large multi-generational pedigrees and complex family structures. These steps are  
87         vectorized as much as possible to ensure computational efficiency and compatibility with  
88         `ggplot2`.

- 89     ▪ Relationship Connection Mapping: `calculateConnections()` generates connection paths
- 90        between family members, mapping parent-child, sibling, spousal, and twin relationships.
- 91        The function determines midpoints for line intersections and handles overlapping con-
- 92        nections with specialized curved segments. These calculations are optimized for large
- 93        datasets by using vectorized operations rather than the loop-based approaches used in
- 94        `kinship2`.
- 95     ▪ Layer-based Plot Construction: `ggPedigree()` constructs plots using `ggplot2` geometry
- 96        functions, returning standard `ggplot2` objects that integrate with existing R workflows.
- 97        `ggPedigreeInteractive()` extends plots into interactive `plotly` widgets. A config system
- 98        allows customization of over 100 aesthetic and layout parameters.
- 99     ▪ Individual Highlighting: Advanced functionality to highlight specific individuals and their
- 100        relatives based on additive genetic, mitochondrial, or other relationship matrices.
- 101    ▪ Specific Visualization Functions: `ggPedigree()` creates static pedigree plots using
- 102        `ggplot2`. `ggPedigreeInteractive()` generates interactive pedigree plots using `plotly`.
- 103        `ggRelatednessMatrix()` creates customizable heatmaps for relatedness matrices with
- 104        support for hierarchical clustering, and seamless integration with `BGmisc` relatedness
- 105        calculations. `ggPhenotypeByDegree()` visualizes phenotypic correlations as a function
- 106        of genetic relatedness, including confidence intervals and statistical summaries for
- 107        quantitative genetic analysis.

#### 108    Code example


109    This example shows how to use `ggpedigree` to visualize a pedigree. The `potter` dataset  
 110    includes several wizarding families from the Harry Potter series.

```
109 ggPedigree(potter,
110   famID = "famID",
111   personID = "personID"
112 )
113
114
```



111    This code produces the following pedigree plot:

112    I demonstrate several advanced features by restyling a figure from ([Hunter et al., 2025](#)), to  
 113    follow the Wake Forest brand identity guidelines. The source code for transforming these  
 114    potter data is available in the package documentation on . The resulting figure appears below:



115

116 I have combined two figures using patchwork (Pedersen, 2025): panel (a) highlights unique  
 117 mitochondrial lines in the Dursley and Evans families, while panel (b) shows the full pedigree  
 118 with Molly Weasley's mitochondrial descendants in gold.

119 Collectively, these tools provide a valuable resource for behavior geneticists and others who  
 120 work with extended family data. They were developed as part of a grant and have been used  
 121 in several ongoing projects, presentations (Garrison, 2024; Hunter, Garrison, Lyu, Good, &  
 122 Burt, 2024), and forthcoming papers (Burt et al., 2025; Hunter et al., 2025; Lyu et al., 2025).

## 123 Availability

124 The `ggpedigree` package is open-source and available on both GitHub at <https://github.com/R-Computing-Lab/ggpedigree> and the Comprehensive R Archive Network (CRAN) at  
 125 <https://cran.r-project.org/package=ggpedigree>. It is licensed under the GNU General Public  
 126 License.  
 127

## 128 Acknowledgments

129 The current research is supported by the National Institute on Aging (NIA), RF1-AG073189.  
 130 The author would like to thank Michael Hunter for his enthusiasm for the development of this  
 131 package.

## 132 References

- 133 Burt, S. A., Garrison, S. M., Lyu, X., Rodgers, J. L., Carroll, S. L., Smith, K. R., &  
 134 Hunter, M. D. (2025). Contributions of inherited mtDNA to longevity: Evidence from  
 135 extended pedigrees with 176 million kinship pairs. *eBioMedicine*, 119, 105911. doi:<https://doi.org/10.1016/j.ebiom.2025.105911>
- 136
- 137 Carver, T., Cunningham, A. P., Babb de Villiers, C., Lee, A., Hartley, S., Tischkowitz,  
 138 M., Walter, F. M., et al. (2018). Pedigreejs: A web-based graphical pedigree editor.  
 139 *Bioinformatics*, 34(6), 1069–1071. doi:[10.1093/bioinformatics/btx705](https://doi.org/10.1093/bioinformatics/btx705)

- 140 Garrison, S. M. (2024). Charting new paths in behavior genetics: Developing a comprehensive  
141 r visualization atlas. *Behavior Genetics* (Vol. 54, p. 488488). doi:[10.1007/s10519-024-10197-8](https://doi.org/10.1007/s10519-024-10197-8)
- 143 Garrison, S. M., Hunter, Michael D., Lyu, X., Trattner, J. D., & Burt, S. A. (2024). BGmisc:  
144 An r package for extended behavior genetics analysis. *Journal of Open Source Software*,  
145 9(94). doi:[10.21105/joss.06203](https://doi.org/10.21105/joss.06203)
- 146 Garrison, S. M., Lyu, X., Hunter, M. D., Rodgers, J. L., Smith, K. R., Coon, H., & Burt, S.  
147 A. (2023). Analyzing extended cousin similarity to unravel the mystery of mtDNA and  
148 longevity. *Behavior Genetics*. doi:[10.1007/s10519-023-10156-9](https://doi.org/10.1007/s10519-023-10156-9)
- 149 Hunter, M. D., Garrison, S. M., Burt, S. A., & Rodgers, J. L. (2021). The Analytic Identification  
150 of Variance Component Models Common to Behavior Genetics. *Behavior Genetics*, 51(4),  
151 425–437. doi:[10.1007/s10519-021-10055-x](https://doi.org/10.1007/s10519-021-10055-x)
- 152 Hunter, M. D., Garrison, S. M., Lyu, X., Good, R., & Burt, S. A. (2024). Tools for  
153 biometric modeling in large population databases. *Behavior Genetics* (Vol. 54, p. 531531).  
154 doi:[10.1007/s10519-024-10197-8](https://doi.org/10.1007/s10519-024-10197-8)
- 155 Hunter, M. D., Garrison, S. M., Lyu, X., Good, R., Carroll, S. L., & Burt, S. A. (2025). *Tracing  
156 the right path: Determination of large pedigree segmentation and relatedness. Revise and  
157 Resubmit at Behavior Genetics.*
- 158 Le Nézet, L., Sinnwell, J., Letko, A., André, C., & Quignon, P. (2025). Pedixplorer: A  
159 bioconductor package to streamline pedigree design and visualization. *Bioinformatics*,  
160 41(6), btaf329. doi:[10.1093/bioinformatics/btaf329](https://doi.org/10.1093/bioinformatics/btaf329)
- 161 Lyu, X., Hunter, M. D., Burt, S. A., Good, R., Carroll, S. L., & Garrison, S. M. (2025).  
162 Detecting mtDNA effects with an extended pedigree model: An analysis of statistical power  
163 and estimation bias. *Behavior Genetics*. doi:[10.1007/s10519-025-10225-1](https://doi.org/10.1007/s10519-025-10225-1)
- 164 Martin, G. R. R. (1997). *A game of thrones* (Vol. 1). Bantam.
- 165 Martin, G. R. R. (2018). *Fire & blood: 300 years before a game of thrones*. New York:  
166 Random House Worlds.
- 167 Martin, J., Wolak, M., Johnston, S., & Morrissey, M. (2025). Pedtricks: Visualize, summarize  
168 and simulate data from pedigrees. doi:[10.32614/CRAN.package.pedtricks](https://CRAN.R-project.org/package=pedtricks)
- 169 McArdle, J. J., & McDonald, R. P. (1984). Some algebraic properties of the reticular action  
170 model for moment structures. *British Journal of Mathematical and Statistical Psychology*,  
171 37, 234–251. doi:[10.1111/j.2044-8317.1984.tb00802.x](https://doi.org/10.1111/j.2044-8317.1984.tb00802.x)
- 172 McFarlane, S. E., Boutin, S., Humphries, M. M., McAdam, A. G., Gorrell, J. C., & Coltmann,  
173 D. W. (2015, January 21). Data from: Very low levels of direct additive genetic  
174 variance in fitness and fitness components in a red squirrel population. Dryad.  
175 doi:[10.5061/DRYAD.N5Q05](https://doi.org/10.5061/DRYAD.N5Q05)
- 176 McFarlane, S. E., Gorrell, J. C., Coltmann, D. W., Humphries, M. M., Boutin, S., & McAdam,  
177 A. G. (2014). Very low levels of direct additive genetic variance in fitness and fitness  
178 components in a red squirrel population. *Ecology and Evolution*, 4(10), 1729–1738.  
179 doi:[10.1002/ece3.982](https://doi.org/10.1002/ece3.982)
- 180 McGoldrick, M., Gerson, R., & Petry, S. (2020). *Genograms: Assessment and Treatment*.  
181 Erscheinungsort nicht ermittelbar: W. W. Norton & Company.
- 182 Morrissey, M. B., & Wilson, A. J. (2010). pedantics: an r package for pedigree-based genetic  
183 simulation and pedigree manipulation, characterization and viewing. *Molecular Ecology  
184 Resources*, 10(4), 711–719. doi:[10.1111/j.1755-0998.2009.02817.x](https://doi.org/10.1111/j.1755-0998.2009.02817.x)
- 185 Pedersen, T. L. (2025). Patchwork: The composer of plots. doi:[10.32614/CRAN.package.patchwork](https://CRAN.R-project.org/package=patchwork)

- 187 Ranaweera, T., Makalic, E., Hopper, J. L., & Bickerstaffe, A. (2018). An open-source,  
188 integrated pedigree data management and visualization tool for genetic epidemiology.  
189 *International Journal of Epidemiology*, 47(4), 1034–1039. doi:[10.1093/ije/dyy049](https://doi.org/10.1093/ije/dyy049)
- 190 Schaid, D., & Sinnwell, J. (2024). Pedgene: Gene-level variant association tests for pedigree  
191 data. doi:[10.32614/CRAN.package.pedgene](https://doi.org/10.32614/CRAN.package.pedgene)
- 192 Shaw, P. D., Graham, M., Kennedy, J., Milne, I., & Marshall, D. F. (2014). Helium: Visualiza-  
193 tion of large scale plant pedigrees. *BMC Bioinformatics*, 15(1), 259. doi:[10.1186/1471-2105-15-259](https://doi.org/10.1186/1471-2105-15-259)
- 195 Sinnwell, J. P., Therneau, T. M., & Schaid, D. J. (2014). The kinship2 r package for pedigree  
196 data. *Human Heredity*, 78, 91–93. doi:[10.1159/000363105](https://doi.org/10.1159/000363105)
- 197 Vigeland, M. D. (2021b). *Pedigree analysis in r*. London: Academic Press, an imprint of  
198 Elsevier. Retrieved from <https://shop.elsevier.com/books/pedigree-analysis-in-r/vigeland/978-0-12-824430-2>
- 200 Vigeland, M. D. (2021a). *Pedigree analysis in {r}*. doi:[10.32614/CRAN.package.pedtools](https://doi.org/10.32614/CRAN.package.pedtools)
- 201 Vigeland, M. D. (2022). QuickPed: An online tool for drawing pedigrees and analysing  
202 relatedness. *BMC Bioinformatics*, 23(1), 220. doi:[10.1186/s12859-022-04759-y](https://doi.org/10.1186/s12859-022-04759-y)
- 203 Wickham, H. (2016). *ggplot2: Use R!* Cham: Springer International Publishing.  
204 doi:[10.1007/978-3-319-24277-4](https://doi.org/10.1007/978-3-319-24277-4)
- 205 Wickham, H., Averick, M., Bryan, J., Chang, W., McGowan, L., François, R., Grolemund, G.,  
206 et al. (2019). Welcome to the tidyverse. *Journal of Open Source Software*, 4(43), 1686.  
207 doi:[10.21105/joss.01686](https://doi.org/10.21105/joss.01686)
- 208 Zhang, R., Jia, G., & Diao, X. (2023). geneHapR: An r package for gene haplotypic statistics  
209 and visualization. *BMC Bioinformatics*, 24(1), 199. doi:[10.1186/s12859-023-05318-9](https://doi.org/10.1186/s12859-023-05318-9)