

Package ‘RCarb’

October 31, 2018

Type Package

Title Dose Rate Modelling of Carbonate-Rich Samples

Version 0.1.0

Author Sebastian Kreutzer [aut, trl, cre, dtr] (<<https://orcid.org/0000-0002-0734-2199>>),
Roger P. Nathan [aut, cph],
Barbara Mauz [aut, cph] (<<https://orcid.org/0000-0003-1504-333X>>)

Maintainer Sebastian Kreutzer <sebastian.kreutzer@u-bordeaux-montaigne.fr>

Description Dose rate modelling for carbonate-rich samples in the context of trapped charged dating (e.g., luminescence dating) applications.

Depends R (>= 3.3.0), utils

Imports interp (>= 1.0), matrixStats (>= 0.50.0)

Suggests R.srp (>= 0.42.0)

License GPL-3

Encoding UTF-8

LazyData true

VignetteBuilder R.srp

RoxygenNote 6.1.0

NeedsCompilation no

R topics documented:

| | |
|---------------------|----------|
| RCarb-package | 1 |
| Example_Data | 2 |
| model_DoseRate | 3 |
| Reference_Data | 4 |
| write_InputTemplate | 5 |
| Index | 6 |

RCarb-package

RCarb - Dose Rate Modelling of Carbonate-Rich Samples

Description

The package provides a dose rate modelling for carbonate-rich samples in the context of trapped charged dating (e.g., luminescence dating) applications.

Package: RCarb
Type: Package
Version: 0.1.0
Date: 2018-10-03
License: GPL-3

References

This package bases on a MATLAB programme with name 'Carb', details can be found the following references:

Mauz, B., Hoffmann, D., 2014. What to do when carbonate replaced water: Carb, the model for estimating the dose rate of carbonate-rich samples. *Ancient TL* 32, 24–32.

Nathan, R.P., Mauz, B., 2008. On the dose-rate estimate of carbonate-rich sediments for trapped charge dating. *Radiation Measurements* 43, 14–25. doi:10.1016/j.radmeas.2007.12.012

Example_Data

Example data

Description

Example data

Format

Example_Data: [data.frame](#)

Version

0.1.0

Examples

```
## show first 5 elements of the METADATA and DATA elements in the terminal
data(Example_Data, envir = environment())
head(Example_Data)
```

| | |
|----------------|--|
| model_DoseRate | <i>Model dose rate evolution in carbonate-rich samples</i> |
|----------------|--|

Description

This function models the dose rate evolution in carbonate enrich environments. For the calculation internal functions are called.

Usage

```
model_DoseRate(data, length_step = 1L, max_time = 500L, n.MC = 100,
  method_control = list(), txtProgressBar = TRUE, verbose = TRUE,
  plot = TRUE, ...)
```

Arguments

| | |
|----------------|---|
| data | data.frame (required) : input data following the structure given in the example data set data(Example_Data). The input data.frame should have at least one row (i.e. values for one sample). For multiple rows the function is automatically re-called. |
| length_step | numeric (with default): step length used for the calculation |
| max_time | numeric (with default): maximum temporal search range |
| n.MC | numeric (with default): number of Monte Carlo runs used for the error calculation |
| method_control | <i>(optional)</i> : additional arguments that can be provided to the control the the modelling. See details for further information. |
| txtProgressBar | logical (with default): enables/disables the txtProgressBar for the MC runs |
| verbose | logical (with default): enables/disables verbose mode |
| plot | logical (with default): enables/disables plot output |
| ... | further arguments passed to the underlying plot functions, see also details for further information. Supported standard arguments are mfrow, xlim, xlab. |

Details

TODO

Value

The function returns numerical and graphical output

[NUMERICAL OUTPUT]

- A **data.frame** which is the combination of the input and values calculated by this function.

[GRAPHICAL OUTPUT]

- Two plots are returned: ##TODO

Function version

0.1.0

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, Université Bordeaux Montagne (France); based on MATLAB code given in Carb_2007a

References

Mauz, B., Hoffmann, D., 2014. What to do when carbonate replaced water: Carb, the model for estimating the dose rate of carbonate-rich samples. *Ancient TL* 32, 24–32.

Nathan, R.P., Mauz, B., 2008. On the dose-rate estimate of carbonate-rich sediments for trapped charge dating. *Radiation Measurements* 43, 14–25. doi:10.1016/j.radmeas.2007.12.012

Examples

```
##load example data
data("Example_Data", envir = environment())

##run the function for one sample from
##the dataset
model_DoseRate(
  data = Example_Data[14,],
  n.MC = 2,
  txtProgressBar = FALSE
)
```

Reference_Data*Reference data*

Description

Reference data

Formatref: [data.frame](#)**Version**

0.1.0

| | |
|---------------------|-----------------------------------|
| write_InputTemplate | <i>Write table input template</i> |
|---------------------|-----------------------------------|

Description

This function creates a template table that can be used as input for the function [model_DoseRate](#)

Usage

```
write_InputTemplate(file = NULL, ...)
```

Arguments

| | |
|------|---|
| file | character (optional): output path, if NULL nothing is written, but a template data.frame is returned. |
| ... | additional arguments that can be passed to function write.table if file != NULL. Supported arguments are: sep, dec, fileEncoding' |

Function version

0.1.0

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

See Also

[Example_Data](#), [write.table](#)

Examples

```
write_InputTemplate()

## Not run:
##Example with file output
write_InputTemplate(file = "~/Desktop/Input.csv")

## End(Not run)
```

Index

*Topic **datasets**

Example_Data, [2](#)

Reference_Data, [4](#)

*Topic **package**

RCarb-package, [1](#)

character, [5](#)

data.frame, [2–5](#)

Example_Data, [2](#), [5](#)

logical, [3](#)

model_DoseRate, [3](#), [5](#)

numeric, [3](#)

RCarb (RCarb-package), [1](#)

RCarb-package, [1](#)

Reference_Data, [4](#)

write.table, [5](#)

write_InputTemplate, [5](#)