

Package ‘RLumCarlo’

April 1, 2017

Type Package

Title Monte-Carlo Methods for Simulating Luminescence Phenomena

Version 0.0.1

Date 2017-01-27

Author Johannes Friedrich [aut, trl, cre]

Maintainer Johannes Friedrich <johannes.friedrich@uni-bayreuth.de>

Description

A collection of functions to simulate luminescence signals with Monte-Carlo methods in the mineral feldspar based on published models.

Contact Package Developer Team <johannes.friedrich@uni-bayreuth.de>

License GPL-3

Depends R (>= 3.3.0), utils

URL <https://CRAN.R-project.org/package=RLumModel>

Collate 'calc_RLumCarlo.R' 'plot_RLumCarlo.R' 'RcppExports.R'
'RLumCarlo-package.R' 'run_MC_ISO.R' 'run_MC_CW_IRSL.R'
'run_MC_TL.R' 'run_MC_LM_OSL.R' 'utils.R'

Imports abind, doParallel, foreach, parallel, methods, magrittr, Rcpp

LinkingTo Rcpp, RcppProgress, RcppArmadillo

Suggests R.rsp

VignetteBuilder R.rsp

RoxygenNote 6.0.1

NeedsCompilation yes

R topics documented:

RLumCarlo-package	2
calc_RLumCarlo	2
plot_RLumCarlo	3
run_MC_CW_IRSL	4
run_MC_ISO	5
run_MC_LM_OSL	6
run_MC_TL	7
Index	9

RLumCarlo-package

Package: & RLumCarlo
Type: & Package
Version: & 0.0.1
Date: & 2017-01-31
License: & GPL-3

Description

Package: RLumCarlo
Type: Package
Version: 0.0.1
Date: 2017-01-31
License: GPL-3

Author(s)

Authors

calc_RLumCarlo	<i>Plot results from Monte-Carlo simulations with RLumCarlo</i>
----------------	---

Description

Plot results from Monte-Carlo simulations with RLumCarlo

Usage

```
calc_RLumCarlo(results)
```

Arguments

results [array](#):

Value

This function returns a [data.frame](#)

Function version

0.0.1 [2017-01-27]

Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

plot_RLumCarlo

Plot results from Monte-Carlo simulations with RLumCarlo

Description

Plot results from Monte-Carlo simulations with RLumCarlo

Usage

```
plot_RLumCarlo(results, times = NULL, norm = FALSE, legend = FALSE,  
  add = FALSE, ...)
```

Arguments

results	<code>data.frame</code>
times	<code>vector</code> (with default):
norm	<code>character</code> (with default):
legend	<code>logical</code> (with default):
add	<code>logical</code> (with default):
...	further arguments

Value

This function returns a graphical output

Function version

0.0.1 [2017-01-27]

Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

run_MC_CW_IRSL

*Run Monte-Carlo simulation for CW-IRSL***Description**

Run Monte-Carlo simulation for CW-IRSL

Usage

```
run_MC_CW_IRSL(A, rho, times, clusters = 10, r = NULL, N_e = 200,
  method = "par", output = "signal", ...)
```

Arguments

A	numeric
rho	numeric
times	vector (with default)
clusters	numeric (with default):
r	numeric (with default)
N_e	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Value

This function returns a list.

Function version

0.0.1 [2017-01-31]

Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

References

Pagonis 2017

Examples

```
## Not run:

##=====##
## Example 1: Simulate CW-IRSL measurement
##=====##

run_MC_CW_IRSL(A = 0.12, rho = 0.003, times = 0:1000) %>%
  calc_RLumCarlo() %>%
```

```
plot_RLumCarlo(norm = T, legend = T)

## End(Not run)
```

`run_MC_ISO`*Run Monte-Carlo simulation for isothermal measurements*

Description

Run Monte-Carlo simulation for isothermal measurements

Usage

```
run_MC_ISO(A, rho, times, clusters = 10, r = NULL, N_e = 200,
  method = "par", output = "signal", ...)
```

Arguments

A	numeric
rho	numeric
times	vector (with default)
clusters	numeric (with default):
r	numeric (with default)
N_e	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Value

This function returns a list.

Function version

0.0.1 [2017-01-27]

Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

References

Pagonis 2017

Examples

```
## Not run:
##=====##
## Example 1: Simulate isothermal measurement
##=====##

times <- seq(0, 500)
run_MC_ISO(A = 0.20,
           rho = 0.007,
           times = times) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

run_MC_LM_OSL	<i>Run Monte-Carlo simulation for LM-OSL</i>
---------------	--

Description

Run Monte-Carlo simulation for LM-OSL

Usage

```
run_MC_LM_OSL(A, rho, times, clusters = 10, r = NULL, delta.r = 0.1,
              N_e = 200, method = "par", output = "signal", ...)
```

Arguments

A	numeric
rho	numeric
times	vector (with default)
clusters	numeric (with default):
r	numeric (with default):
delta.r	numeric (with default):
N_e	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Value

This function returns a list.

Function version

0.0.1 [2017-01-27]

Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

References

Pagonis 2017

run_MC_TL

Run Monte-Carlo simulation for TL

Description

Run Monte-Carlo simulation for TL

Usage

```
run_MC_TL(s, E, rho, r_c, times, clusters = 10, N_e = 200, delta.r = 0.1,  
method = "par", output = "signal", ...)
```

Arguments

s	list
E	numeric
rho	numeric
r_c	numeric (with default)
times	vector (with default)
clusters	numeric (with default):
N_e	numeric (with default):
delta.r	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

Function version

0.0.1 [2017-01-27]

Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

References

Pagonis 2017

Examples

```
## Not run:
##=====##
## Example 1: Simulate TL measurement
##=====##

times <- seq(200, 500) # time = temperature

run_MC_TL(s = 3.5e12,
          E = 1.45,
          rho = 0.015,
          r_c = 0.85,
          times = times) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```


Index

array, [2](#), [7](#)

calc_RLumCarlo, [2](#)

character, [3–7](#)

data.frame, [2](#), [3](#)

list, [7](#)

logical, [3](#)

numeric, [4–7](#)

plot_RLumCarlo, [3](#)

RLumCarlo-package, [2](#)

run_MC_CW_IRSL, [4](#)

run_MC_ISO, [5](#)

run_MC_LM_OSL, [6](#)

run_MC_TL, [7](#)

vector, [3–7](#)