

# Package ‘RLumCarlo’

October 8, 2019

**Type** Package

**Title** Monte-Carlo Methods for Simulating Luminescence Phenomena

**Version** 0.1.0.9000-47

**Date** 2019-10-08

**Author** Johannes Friedrich [aut, trl] (<<https://orcid.org/0000-0002-0805-9547>>),  
Sebastian Kreutzer [aut, trl, cre] (<<https://orcid.org/0000-0002-0734-2199>>),  
Vasilis Pagonis [aut] (<<https://orcid.org/0000-0002-4852-9312>>),  
Christoph Schmidt [aut] (<<https://orcid.org/0000-0002-2309-3209>>)

**Maintainer** Sebastian Kreutzer <[sebastian.kreutzer@u-bordeaux-montaigne.fr](mailto:sebastian.kreutzer@u-bordeaux-montaigne.fr)>

## Description

A collection of functions to simulate luminescence signals with Monte-Carlo methods in the mineral feldspar based on published models.

**Contact** Package Developer Team <[sebastian.kreutzer@u-bordeaux-montaigne.fr](mailto:sebastian.kreutzer@u-bordeaux-montaigne.fr)>

**License** GPL-3

**BugReports** <https://github.com/R-Lum/RLumCarlo/issues>

**Depends** R (>= 3.3.0),  
utils,  
magrittr

**URL** <https://CRAN.R-project.org/package=RLumModel>

**LinkingTo** Rcpp,  
RcppProgress,  
RcppArmadillo

**Imports** abind,  
doParallel,  
foreach,  
parallel,  
methods,  
Rcpp

**Suggests** R.rsp

**Encoding** UTF-8

**VignetteBuilder** R.rsp

**RoxygenNote** 6.1.1

## R topics documented:

plot_RLumCarlo . . . . .	2
run_MC_CW_IRSL_DELOC . . . . .	3
run_MC_CW_IRSL_LOC . . . . .	4
run_MC_CW_IRSL_TUN . . . . .	6
run_MC_ISO_DELOC . . . . .	7
run_MC_ISO_LOC . . . . .	8
run_MC_ISO_TUN . . . . .	10
run_MC_LM_OSL_DELOC . . . . .	11
run_MC_LM_OSL_LOC . . . . .	12
run_MC_LM_OSL_TUN . . . . .	14
run_MC_TL_DELOC . . . . .	15
run_MC_TL_LOC . . . . .	16
run_MC_TL_TUN . . . . .	18
summary.RLumCarlo_Model_Output . . . . .	19

<b>Index</b>	<b>21</b>
--------------	-----------

---

plot_RLumCarlo	<i>Plot results from Monte-Carlo simulations with RLumCarlo</i>
----------------	---

---

## Description

Plot results from Monte-Carlo simulations with RLumCarlo

## Usage

```
plot_RLumCarlo(results, times = NULL, plot_uncertainty = TRUE,
  norm = FALSE, add = FALSE, ...)
```

## Arguments

results	<a href="#">data.frame</a> ( <b>required</b> )
times	<a href="#">numeric</a> ( <i>optinal</i> ): Optional vector for the x-axis
plot_uncertainty	<a href="#">logical</a> ( <i>with default</i> ): Enable/disable uncertainty polygon plot
norm	<a href="#">logical</a> ( <i>with default</i> ): Normalise curve to the highest intensity
add	<a href="#">logical</a> ( <i>with default</i> ): allow overplotting of results
...	further arguments that can be passed to control the plot output. Currently supported are: xlab, xlim, ylim, main, lwd, type, pch, lty,col, grid, legend

## Value

This function returns a graphical output

## Function version

0.1.0

**How to cite**

Friedrich, J., Kreutzer, S., 2019. plot\_RLumCarlo(): Plot results from Monte-Carlo simulations with RLumCarlo. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

**Author(s)**

Johannes Friedrich, University of Bayreuth (Germany), Sebastian Kreutzer, IRAMAT-CRP2A, Université Bordeaux Montaigne (France)

---

run\_MC\_CW\_IRSL\_DELOC     *Run Monte-Carlo simulation for CW-IRSL for GOT model*

---

**Description**

Runs a Monte Carlo (MC) simulation of constant wave \_ (CW-IRSL) using the generalized one trap (GOT) model.

**Usage**

```
run_MC_CW_IRSL_DELOC(A, times, clusters = 10, N_e = 200,
  n_filled = N_e, R, method = "par", output = "signal", ...)
```

**Arguments**

A	<b>numeric (required)</b> : The transition probability in cm <sup>3</sup> /s
times	<b>numeric</b> (with default): The number of MC runs
clusters	<b>numeric</b> (with default): The number of clusters.
N_e	<b>integer</b> (with default): The number of electrons.
n_filled	<b>integer</b> (with default): The number of electron traps that are filled at the beginning of the simulation.
R	<b>numeric</b> (with default): The retrapping ratio
method	<b>character</b> (with default):
output	<b>character</b> (with default):
...	further arguments

**Details**

$$I_{DELOC}(t) = -dn/dt = p(t) * (n^2 / (NR + n(1 - R)))$$

**Value**

This function returns an **array** with dimension length(times) x length(r) x clusters

**Function version**

0.1.0

**How to cite**

Kreutzer, S., 2019. run\_MC\_CW\_IRSL\_DELOC(): Run Monte-Carlo simulation for CW-IRSL for GOT model. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

**Author(s)**

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

**References**

##TODO

**Examples**

```
##=====##
## Example 1: Simulate CW-IRSL
##=====##
## Not run:
run_MC_CW_IRSL_DELOC(
  A = 0.12,
  R = 1,
  times = 0:100) %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

---

run_MC_CW_IRSL_LOC	<i>Run Monte-Carlo simulation for CW-IRSL for localised transition</i>
--------------------	--

---

**Description**

Runs a Monte Carlo (MC) simulation of constant wave infrared stimulated luminescence (CW-IRSL) using the generalized one trap (GOT) model.

**Usage**

```
run_MC_CW_IRSL_LOC(A, times, clusters = 10, n_filled = 100, r,
  method = "par", output = "signal", ...)
```

**Arguments**

A	<b>numeric (required)</b> : The transition probability in $\text{cm}^3/\text{s}$
times	<b>numeric (with default)</b> : The number of MC runs
clusters	<b>numeric (with default)</b> : The number of clusters.
n_filled	<b>integer (with default)</b> : The number of electron traps that are filled at the beginning of the simulation.
r	<b>numeric (with default)</b> : The retrapping ratio

method            **character** (with default):  
 output           **character** (with default):  
 ...               further arguments

## Details

$$I_{LOC}(t) = -dn/dt = A * (n^2 / (r + n))$$

## Value

This function returns an **array** with dimension length(times) x length(r) x clusters

## Function version

0.0.1

## How to cite

Kreutzer, S., 2019. run\_MC\_CW\_IRSL\_LOC(): Run Monte-Carlo simulation for CW-IRSL for localised transition. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

## Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

## References

##TODO

## Examples

```
##=====##
## Example 1: Simulate CW-IRSL
##=====##
## Not run:
run_MC_CW_IRSL_LOC(
  A = 0.12,
  r = 1,
  times = 0:100) %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

---

run_MC_CW_IRSL_TUN	<i>Run Monte-Carlo simulation for CW-IRSL</i>
--------------------	---

---

## Description

Run Monte-Carlo simulation for CW-IRSL

## Usage

```
run_MC_CW_IRSL_TUN(A, rho, times, clusters = 10, r = NULL, N_e = 200,
  method = "seq", output = "signal", ...)
```

## Arguments

A	numeric
rho	numeric
times	vector (with default)
clusters	numeric (with default):
r	numeric (with default)
N_e	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

## Value

This function returns a list.

## Function version

0.2.0

## How to cite

Friedrich, J., Kreutzer, S., 2019. run\_MC\_CW\_IRSL\_TUN(): Run Monte-Carlo simulation for CW-IRSL. Function version 0.2.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

## Author(s)

Johannes Friedrich, University of Bayreuth (Germany), Sebastian Kreutzer, IRAMAT-CRP2A, Université Bordeaux Montaigne (France)

## References

Pagonis 2017

**Examples**

```
## Not run:

##=====##
## Example 1: Simulate CW-IRSL measurement
##=====##

run_MC_CW_IRS_TUNL(A = 0.12, rho = 0.003, times = 0:1000) %>%
  plot_RLumCarlo(norm = T, legend = T)

## End(Not run)
```

run\_MC\_ISO\_DELOC

*Run Monte-Carlo simulation for ISO for GOT model***Description**

##TODO

**Usage**

```
run_MC_ISO_DELOC(s, E, T = 20, times, clusters = 10, N_e = 200,
  n_filled = N_e, R, method = "par", output = "signal", ...)
```

**Arguments**

s	<a href="#">numeric</a> (required)
E	<a href="#">numeric</a> (required)
T	<a href="#">numeric</a> (with default)
times	<a href="#">numeric</a> (with default)
clusters	<a href="#">numeric</a> (with default):
N_e	<a href="#">integer</a> (with default)
n_filled	<a href="#">integer</a> (with default)
R	<a href="#">numeric</a> (with default):
method	<a href="#">character</a> (with default):
output	<a href="#">character</a> (with default):
...	further arguments

**Details**

$$I_{DELOC}(t) = -dn/dt = p(t) * (n^2 / (NR + n(1 - R)))$$

**Value**

This function returns an [array](#) with dimension length(times) x length(r) x clusters

**Function version**

0.0.1

**How to cite**

Kreutzer, S., 2019. run\_MC\_ISO\_DELOC(): Run Monte-Carlo simulation for ISO for GOT model. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

**Author(s)**

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

**References**

##TODO

**Examples**

```
##=====##
## Example 1: Simulate ITL
##=====##
## Not run:
run_MC_ISO_DELOC(
  s = 3.5e12,
  E = 1.45,
  T = 200,
  R = 1,
  times = 0:10000) %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

---

run\_MC\_ISO\_LOC

---

*Run Monte-Carlo simulation for ITL for localised transition*


---

**Description**

##TODO

**Usage**

```
run_MC_ISO_LOC(s, E, T = 20, times, clusters = 10, n_filled = 100, r,
  method = "par", output = "signal", ...)
```

**Arguments**

s	numeric (required)
E	numeric (required)
T	numeric (with default)
times	numeric (with default):
clusters	numeric (with default):



n\_filled        **integer** (with default):  
 r                **numeric** (with default):  
 method         **character** (with default):  
 output         **character** (with default):  
 ...             further arguments

## Details

$$I_{LOC}(t) = -dn/dt = p(t) * (n^2/(r + n))$$

## Value

This function returns an **array** with dimension length(times) x length(r) x clusters

## Function version

0.0.1

## How to cite

Kreutzer, S., 2019. run\_MC\_ISO\_LOC(): Run Monte-Carlo simulation for ITL for localised transition. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence PhenomenaR package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

## Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

## References

##TODO

## Examples

```

##=====##
## Example 1: Simulate ITL
##=====##
## Not run:
run_MC_ISO_LOC(
  s = 3.5e12,
  E = 1.45,
  T = 200,
  r = 1,
  times = 0:10000) %>%
  plot_RLumCarlo(legend = T)

## End(Not run)

```

---

`run_MC_ISO_TUN`*Run Monte-Carlo simulation for isothermal measurements*

---

## Description

Run Monte-Carlo simulation for isothermal measurements

## Usage

```
run_MC_ISO_TUN(E, s, T = 200, rho, times, clusters = 10, r = NULL,  
  N_e = 200, method = "par", output = "signal", ...)
```

## Arguments

E	<b>numeric (required)</b>
s	<b>numeric (required)</b>
T	<b>numeric (required)</b>
rho	<b>numeric (required)</b>
times	<b>numeric (with default)</b>
clusters	<b>numeric (with default):</b>
r	<b>numeric (with default)</b>
N_e	<b>numeric (with default)</b>
method	<b>character (with default)</b>
output	<b>character (with default)</b>
...	further arguments

## Value

This function returns a list.

## Function version

0.1.0

## How to cite

Friedrich, J., Kreutzer, S., 2019. run\_MC\_ISO\_TUN(): Run Monte-Carlo simulation for isothermal measurements. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence PhenomenaR package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

## Author(s)

Johannes Friedrich, University of Bayreuth (Germany), Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

## References

Pagonis 2017

## Examples

```
## Not run:
##=====##
## Example 1: Simulate isothermal measurement
##=====##

times <- seq(0, 5000)
run_MC_ISO_TUN(
  E = 1.2,
  s = 1e10,
  T = 200,
  rho = 0.007,
  times = times) %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

---

run_MC_LM_OSL_DELOC	<i>Run Monte-Carlo simulation for LM-OSL for GOT model</i>
---------------------	--

---

## Description

##TODO

## Usage

```
run_MC_LM_OSL_DELOC(A, times, clusters = 10, N_e = 200,
  n_filled = N_e, R, method = "par", output = "signal", ...)
```

## Arguments

A	<a href="#">numeric</a> ( <i>required</i> )
times	<a href="#">numeric</a> (with default)
clusters	<a href="#">numeric</a> (with default):
N_e	<a href="#">integer</a> (with default)
n_filled	<a href="#">integer</a> (with default)
R	<a href="#">numeric</a> (with default):
method	<a href="#">character</a> (with default):
output	<a href="#">character</a> (with default):
...	further arguments

## Details

$$I_{DELOC}(t) = -dn/dt = p(t) * (n^2 / (NR + n(1 - R)))$$

## Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

**Function version**

0.1.0

**How to cite**

Kreutzer, S., 2019. run\_MC\_LM\_OSL\_DELOC(): Run Monte-Carlo simulation for LM-OSL for GOT model. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

**Author(s)**

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

**References**

##TODO

**Examples**

```
##=====##
## Example 1: Simulate LM-OSL
##=====##
## Not run:
run_MC_LM_OSL_DELOC(
  A = 0.12,
  R = 1,
  times = 0:100) %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

---

run_MC_LM_OSL_LOC	<i>Run Monte-Carlo simulation for LM-OSL for localised transition</i>
-------------------	---

---

**Description**

##TODO

**Usage**

```
run_MC_LM_OSL_LOC(A, times, clusters = 10, n_filled = 100, r,
  method = "par", output = "signal", ...)
```

**Arguments**

A	<b>numeric (required)</b>
times	<b>numeric</b> (with default):
clusters	<b>numeric</b> (with default):
n_filled	<b>integer</b> (with default):
r	<b>numeric</b> (with default):
method	<b>character</b> (with default):
output	<b>character</b> (with default):
...	further arguments

**Details**

$$I_{LOC}(t) = -dn/dt = A * (n^2 / (r + n))$$

**Value**

This function returns an **array** with dimension length(times) x length(r) x clusters

**Function version**

0.0.1

**How to cite**

Kreutzer, S., 2019. run\_MC\_LM\_OSL\_LOC(): Run Monte-Carlo simulation for LM-OSL for localised transition. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

**Author(s)**

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

**References**

##TODO

**Examples**

```
##=====##
## Example 1: Simulate LM-OSL
##=====##
## Not run:
run_MC_LM_OSL_LOC(
  A = 0.12,
  r = 1,
  times = 0:100) %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

---

run_MC_LM_OSL_TUN	<i>Run Monte-Carlo simulation for LM-OSL</i>
-------------------	--

---

## Description

Run Monte-Carlo simulation for LM-OSL

## Usage

```
run_MC_LM_OSL_TUN(A, rho, times, clusters = 10, r = NULL,
  delta.r = 0.1, N_e = 200, method = "par", output = "signal", ...)
```

## Arguments

A	numeric
rho	numeric
times	vector (with default)
clusters	numeric (with default):
r	numeric (with default):
delta.r	numeric (with default):
N_e	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

## Value

This function returns a list.

## Function version

0.1.0

## How to cite

Friedrich, J., 2019. run\_MC\_LM\_OSL\_TUN(): Run Monte-Carlo simulation for LM-OSL. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

## Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

## References

Pagonis 2017

## Examples

```
## Not run:

##TODO: Primary example, should be verified
run_MC_LM_OSL_TUN(A = 10000, rho = 0.0001, times = 1:100, clusters = 10, r = NULL,
  delta.r = 0.1,
  N_e = 200, method = "par", output = "signal") %>%
  plot_RLumCarlo(norm = T)

## End(Not run)
```

---

run\_MC\_TL\_DELOC

*Run Monte-Carlo simulation for TL for GOT model*


---

## Description

```
##TODO
```

## Usage

```
run_MC_TL_DELOC(s, E, times, clusters = 10, N_e = 200,
  n_filled = N_e, R, method = "par", output = "signal", ...)
```

## Arguments

s	numeric (required)
E	numeric (required)
times	numeric (with default)
clusters	numeric (with default):
N_e	integer (with default)
n_filled	integer (with default)
R	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

## Details

$$I_{DELOC}(t) = -dn/dt = p(t) * (n^2 / (NR + n(1 - R)))$$

## Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

**Function version**

0.0.1

**How to cite**

Kreutzer, S., 2019. run\_MC\_TL\_DELOC(): Run Monte-Carlo simulation for TL for GOT model. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

**Author(s)**

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

**References**

##TODO

**Examples**

```
##=====##
## Example 1: Simulate TL
##=====##
## Not run:
run_MC_TL_DELOC(
  s = 3.5e12,
  E = 1.45,
  R = 1,
  times = 100:450) %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

---

run\_MC\_TL\_LOC

---

*Run Monte-Carlo simulation for TL for localised transition*


---

**Description**

##TODO

**Usage**

```
run_MC_TL_LOC(s, E, times, clusters = 10, n_filled = 100, r,
  method = "par", output = "signal", ...)
```



**Arguments**

s	numeric (required)
E	numeric (required)
times	numeric (with default)
clusters	numeric (with default):
n_filled	integer (with default)
r	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

**Details**

$$I_{LOC}(t) = -dn/dt = p(t) * (n^2/(r + n))$$

**Value**

This function returns an [array](#) with dimension length(times) x length(r) x clusters

**Function version**

0.1.0

**How to cite**

Kreutzer, S., 2019. run\_MC\_TL\_LOC(): Run Monte-Carlo simulation for TL for localised transition. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

**Author(s)**

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

**References**

##TODO

**Examples**

```
##=====##
## Example 1: Simulate TL
##=====##
## Not run:
run_MC_TL_LOC(
  s = 3.5e12,
  E = 1.45,
  r = 1,
  times = 100:450) %>%
  plot_RLumCarlo(legend = T)
```

```
## End(Not run)
```

---

run_MC_TL_TUN	<i>Run Monte-Carlo simulation for TL</i>
---------------	--

---

## Description

Run Monte-Carlo simulation for TL

## Usage

```
run_MC_TL_TUN(s, E, rho, r_c, times, clusters = 10, N_e = 200,
  delta.r = 0.1, method = "par", output = "signal", ...)
```

## Arguments

s	list
E	numeric
rho	numeric
r_c	numeric (with default)
times	vector (with default)
clusters	numeric (with default):
N_e	numeric (with default):
delta.r	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

## Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

## Function version

0.1.0

## How to cite

Friedrich, J., 2019. run\_MC\_TL\_TUN(): Run Monte-Carlo simulation for TL. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

## Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

## References

Pagonis 2017

## Examples

```
## Not run:
##=====##
## Example 1: Simulate TL measurement
##=====##

times <- seq(200, 500) # time = temperature

run_MC_TL_TUN(s = 3.5e12,
              E = 1.45,
              rho = 0.015,
              r_c = 0.85,
              times = times) %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

---

```
summary.RLumCarlo_Model_Output
```

*Summarize RLumCarlo Modelling Results*

---

## Description

Summarize RLumCarlo Modelling results, so that they can be plotted easily

## Usage

```
## S3 method for class 'RLumCarlo_Model_Output'
summary(object, ...)
```

## Arguments

object	<a href="#">list</a> of class RLumCarlo_Model_Output: RLumCarlo simulation output object produced by all
...	further arguments passed to the method

## Value

This function returns a [data.frame](#)

## Function version

0.1.0

## How to cite

Friedrich, J., Kreutzer, S., 2019. summary.RLumCarlo\_Model\_Output(): Summarize RLumCarlo Modelling Results. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-47. <https://CRAN.R-project.org/package=RLumModel>

**Author(s)**

Johannes Friedrich, University of Bayreuth (Germany), Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS-Université Bordeaux Montagne (France)

# Index

array, [3](#), [5](#), [7](#), [9](#), [11](#), [13](#), [15](#), [17](#), [18](#)

character, [3](#), [5–7](#), [9–11](#), [13–15](#), [17](#), [18](#)

data.frame, [2](#), [19](#)

integer, [3](#), [4](#), [7](#), [9](#), [11](#), [13](#), [15](#), [17](#)

list, [18](#), [19](#)

logical, [2](#)

numeric, [2–4](#), [6–11](#), [13–15](#), [17](#), [18](#)

plot\_RLumCarlo, [2](#)

run\_MC\_CW\_IRSL\_DELOC, [3](#)

run\_MC\_CW\_IRSL\_LOC, [4](#)

run\_MC\_CW\_IRSL\_TUN, [6](#)

run\_MC\_ISO\_DELOC, [7](#)

run\_MC\_ISO\_LOC, [8](#)

run\_MC\_ISO\_TUN, [10](#)

run\_MC\_LM\_OSL\_DELOC, [11](#)

run\_MC\_LM\_OSL\_LOC, [12](#)

run\_MC\_LM\_OSL\_TUN, [14](#)

run\_MC\_TL\_DELOC, [15](#)

run\_MC\_TL\_LOC, [16](#)

run\_MC\_TL\_TUN, [18](#)

summary.RLumCarlo\_Model\_Output, [19](#)

vector, [6](#), [14](#), [18](#)