

Package ‘RLumCarlo’

October 7, 2019

Type Package

Title Monte-Carlo Methods for Simulating Luminescence Phenomena

Version 0.1.0.9000-16

Date 2019-10-07

Author Johannes Friedrich [aut, trl] (<<https://orcid.org/0000-0002-0805-9547>>),
Sebastian Kreutzer [aut, trl, cre] (<<https://orcid.org/0000-0002-0734-2199>>),
Vasilis Pagonis [aut] (<<https://orcid.org/0000-0002-4852-9312>>),
Christoph Schmidt [aut] (<<https://orcid.org/0000-0002-2309-3209>>)

Maintainer Johannes Friedrich <johannes.friedrich@uni-bayreuth.de>

Description

A collection of functions to simulate luminescence signals with Monte-Carlo methods in the mineral feldspar based on published models.

Contact Package Developer Team <johannes.friedrich@uni-bayreuth.de>

License GPL-3

BugReports <https://github.com/R-Lum/RLumCarlo/issues>

Depends R (>= 3.3.0),
utils,
magrittr

URL <https://CRAN.R-project.org/package=RLumModel>

LinkingTo Rcpp,
RcppProgress,
RcppArmadillo

Imports abind,
doParallel,
foreach,
parallel,
methods,
Rcpp

Suggests R.rsp

Encoding UTF-8

VignetteBuilder R.rsp

RoxygenNote 6.1.1

R topics documented:

RLumCarlo-package	2
calc_RLumCarlo	2
plot_RLumCarlo	3
run_MC_CW_IRSL	4
run_MC_CW_IRSL_DELOC	5
run_MC_CW_IRSL_LOC	6
run_MC_ISO	8
run_MC_ISO_DELOC	9
run_MC_ISO_LOC	11
run_MC_LM_OSL	12
run_MC_LM_OSL_DELOC	13
run_MC_LM_OSL_LOC	15
run_MC_TL	16
run_MC_TL_DELOC	17
run_MC_TL_LOC	19

Index	21
--------------	-----------

RLumCarlo-package	<i>Modelling luminescence signals in feldspar</i>
-------------------	---

Description

Details

Package: RLumCarlo
 Type: Package
 Version: 0.0.2
 Date: 2018-08-28
 License: GPL-3

Author(s)

Johannes Friedrich (University of Bayreuth, Germany), Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS-Université Bordeaux Montaigne (France)

calc_RLumCarlo	<i>Plot results from Monte-Carlo simulations with RLumCarlo</i>
----------------	---

Description

Plot results from Monte-Carlo simulations with RLumCarlo

Usage

```
calc_RLumCarlo(results)
```

Arguments

results [array](#):

Value

This function returns a [data.frame](#)

Function version

0.0.1 [2017-01-27]

How to cite

Friedrich, J., 2019. calc_RLumCarlo(): Plot results from Monte-Carlo simulations with RLumCarlo. Function version 0.0.1 [2017-01-27]. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

plot_RLumCarlo

Plot results from Monte-Carlo simulations with RLumCarlo

Description

Plot results from Monte-Carlo simulations with RLumCarlo

Usage

```
plot_RLumCarlo(results, times = NULL, norm = FALSE, legend = FALSE,
  add = FALSE, ...)
```

Arguments

results	data.frame (required)
times	numeric (<i>optinal</i>): Optional vector for the x-axis
norm	logical (<i>with default</i>): Normalise curve to the highest intensity
legend	logical (<i>with default</i>): Enable/disable legend
add	logical (<i>with default</i>): allow overplotting of results
...	further arguments that can be passed to control the plot output. Currently supported are: xlab, xlim, ylim, main, lwd, type

Value

This function returns a graphical output

Function version

0.1.0

How to cite

Friedrich, J., Kreutzer, S., 2019. plot_RLumCarlo(): Plot results from Monte-Carlo simulations with RLumCarlo. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Johannes Friedrich, University of Bayreuth (Germany), Sebastian Kreutzer, IRAMAT-CRP2A, Université Bordeaux Montaigne (France)

run_MC_CW_IRSL

*Run Monte-Carlo simulation for CW-IRSL***Description**

Run Monte-Carlo simulation for CW-IRSL

Usage

```
run_MC_CW_IRSL(A, rho, times, clusters = 10, r = NULL, N_e = 200,
  method = "seq", output = "signal", ...)
```

Arguments

A	numeric
rho	numeric
times	vector (with default)
clusters	numeric (with default):
r	numeric (with default)
N_e	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Value

This function returns a list.

Function version

0.0.2 [2017-01-31]

How to cite

Friedrich, J., Kreutzer, S., 2019. run_MC_CW_IRSL(): Run Monte-Carlo simulation for CW-IRSL. Function version 0.0.2 [2017-01-31]. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Johannes Friedrich, University of Bayreuth (Germany), Sebastian Kreutzer, IRAMAT-CRP2A, Université Bordeaux Montaigne (France)

References

Pagonis 2017

Examples

```
## Not run:

##=====##
## Example 1: Simulate CW-IRSL measurement
##=====##

run_MC_CW_IRSL(A = 0.12, rho = 0.003, times = 0:1000) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(norm = T, legend = T)

## End(Not run)
```

run_MC_CW_IRSL_DELOC *Run Monte-Carlo simulation for CW-IRSL for GOT model*

Description

##TODO

Usage

```
run_MC_CW_IRSL_DELOC(A, times, clusters = 10, N_e = 200,
  n_filled = N_e, R, method = "par", output = "signal", ...)
```

Arguments

A	numeric (required)
times	numeric (with default)
clusters	numeric (with default):
N_e	integer (with default)
n_filled	integer (with default)
R	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Details

$$I_{DELOC}(t) = -dn/dt = p(t) * (n^2 / (NR + n(1 - R)))$$

Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

Function version

0.0.1

How to cite

Kreutzer, S., 2019. run_MC_CW_IRSL_DELOC(): Run Monte-Carlo simulation for CW-IRSL for GOT model. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence PhenomenaR package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

References

##TODO

Examples

```
##=====##
## Example 1: Simulate CW-IRSL
##=====##
## Not run:
run_MC_CW_IRSL_DELOC(
  A = 0.12,
  R = 1,
  times = 0:100) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

run_MC_CW_IRSL_LOC

Run Monte-Carlo simulation for CW-IRSL for localised transition

Description

##TODO

Usage

```
run_MC_CW_IRSL_LOC(A, times, clusters = 10, n_filled = 100, r,
  method = "par", output = "signal", ...)
```

Arguments

A	numeric (required)
times	numeric (with default):
clusters	numeric (with default):
n_filled	integer (with default):
r	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Details

$$I_{LOC}(t) = -dn/dt = A * (n^2 / (r + n))$$

Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

Function version

0.0.1

How to cite

Kreutzer, S., 2019. run_MC_CW_IRSL_LOC(): Run Monte-Carlo simulation for CW-IRSL for localised transition. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

References

##TODO

Examples

```
##=====##
## Example 1: Simulate CW-IRSL
##=====##
## Not run:
run_MC_CW_IRSL_LOC(
  A = 0.12,
  r = 1,
```

```
times = 0:100) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

run_MC_ISO

*Run Monte-Carlo simulation for isothermal measurements***Description**

Run Monte-Carlo simulation for isothermal measurements

Usage

```
run_MC_ISO(E, s, T = 200, rho, times, clusters = 10, r = NULL,
  N_e = 200, method = "par", output = "signal", ...)
```

Arguments

E	numeric (required)
s	numeric (required)
T	numeric (required)
rho	numeric (required)
times	numeric (with default)
clusters	numeric (with default):
r	numeric (with default)
N_e	numeric (with default)
method	character (with default)
output	character (with default)
...	further arguments

Value

This function returns a list.

Function version

0.1.0

How to cite

Friedrich, J., Kreutzer, S., 2019. run_MC_ISO(): Run Monte-Carlo simulation for isothermal measurements. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Johannes Friedrich, University of Bayreuth (Germany), Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

References

Pagonis 2017

Examples

```
## Not run:
##=====##
## Example 1: Simulate isothermal measurement
##=====##

times <- seq(0, 5000)
run_MC_ISO(
  E = 1.2,
  s = 1e10,
  T = 200,
  rho = 0.007,
  times = times) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

run_MC_ISO_DELOC

Run Monte-Carlo simulation for ISO for GOT model

Description

##TODO

Usage

```
run_MC_ISO_DELOC(s, E, T = 20, times, clusters = 10, N_e = 200,
  n_filled = N_e, R, method = "par", output = "signal", ...)
```

Arguments

s	numeric (<i>required</i>)
E	numeric (<i>required</i>)
T	numeric (<i>with default</i>)
times	numeric (<i>with default</i>)
clusters	numeric (<i>with default</i>):
N_e	integer (<i>with default</i>)
n_filled	integer (<i>with default</i>)
R	numeric (<i>with default</i>):
method	character (<i>with default</i>):
output	character (<i>with default</i>):
...	further arguments

Details

$$I_{DELOC}(t) = -dn/dt = p(t) * (n^2 / (NR + n(1 - R)))$$

Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

Function version

0.0.1

How to cite

Kreutzer, S., 2019. run_MC_ISO_DELOC(): Run Monte-Carlo simulation for ISO for GOT model. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence PhenomenaR package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

References

##TODO

Examples

```
##=====##
## Example 1: Simulate ITL
##=====##
## Not run:
run_MC_ISO_DELOC(
  s = 3.5e12,
  E = 1.45,
  T = 200,
  R = 1,
  times = 0:10000) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

run_MC_ISO_LOC

*Run Monte-Carlo simulation for ITL for localised transition***Description**

##TODO

Usage

```
run_MC_ISO_LOC(s, E, T = 20, times, clusters = 10, n_filled = 100, r,
  method = "par", output = "signal", ...)
```

Arguments

s	numeric (required)
E	numeric (required)
T	numeric (with default)
times	numeric (with default):
clusters	numeric (with default):
n_filled	integer (with default):
r	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Details

$$I_{LOC}(t) = -dn/dt = p(t) * (n^2/(r + n))$$

Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

Function version

0.0.1

How to cite

Kreutzer, S., 2019. run_MC_ISO_LOC(): Run Monte-Carlo simulation for ITL for localised transition. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence PhenomenaR package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

References

##TODO

Examples

```
##=====##
## Example 1: Simulate ITL
##=====##
## Not run:
run_MC_ISO_LOC(
  s = 3.5e12,
  E = 1.45,
  T = 200,
  r = 1,
  times = 0:10000) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

run_MC_LM_OSL

Run Monte-Carlo simulation for LM-OSL

Description

Run Monte-Carlo simulation for LM-OSL

Usage

```
run_MC_LM_OSL(A, rho, times, clusters = 10, r = NULL, delta.r = 0.1,
  N_e = 200, method = "par", output = "signal", ...)
```

Arguments

A	numeric
rho	numeric
times	vector (with default)
clusters	numeric (with default):
r	numeric (with default):
delta.r	numeric (with default):
N_e	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Value

This function returns a list.

Function version

0.0.1 [2017-01-27]

How to cite

Friedrich, J., 2019. run_MC_LM_OSL(): Run Monte-Carlo simulation for LM-OSL. Function version 0.0.1 [2017-01-27]. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

References

Pagonis 2017

Examples

```
## Not run:

##TODO: Primary example, should be verified
run_MC_LM_OSL(A = 10000, rho = 0.0001, times = 1:100, clusters = 10, r = NULL,
  delta.r = 0.1,
  N_e = 200, method = "par", output = "signal") %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(norm = T)

## End(Not run)
```

run_MC_LM_OSL_DELOC	<i>Run Monte-Carlo simulation for LM-OSL for GOT model</i>
---------------------	--

Description

```
##TODO
```

Usage

```
run_MC_LM_OSL_DELOC(A, times, clusters = 10, N_e = 200,
  n_filled = N_e, R, method = "par", output = "signal", ...)
```

Arguments

A	numeric (<i>required</i>)
times	numeric (with default)
clusters	numeric (with default):
N_e	integer (with default)
n_filled	integer (with default)
R	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Details

$$I_{DELOC}(t) = -dn/dt = p(t) * (n^2 / (NR + n(1 - R)))$$

Value

This function returns an **array** with dimension length(times) x length(r) x clusters

Function version

0.0.1

How to cite

Kreutzer, S., 2019. run_MC_LM_OSL_DELOC(): Run Monte-Carlo simulation for LM-OSL for GOT model. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

References

##TODO

Examples

```
##=====##
## Example 1: Simulate LM-OSL
##=====##
## Not run:
run_MC_LM_OSL_DELOC(
  A = 0.12,
  R = 1,
  times = 0:100) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)
```

```
## End(Not run)
```

run_MC_LM_OSL_LOC	<i>Run Monte-Carlo simulation for LM-OSL for localised transition</i>
-------------------	---

Description

```
##TODO
```

Usage

```
run_MC_LM_OSL_LOC(A, times, clusters = 10, n_filled = 100, r,
  method = "par", output = "signal", ...)
```

Arguments

A	numeric (required)
times	numeric (with default):
clusters	numeric (with default):
n_filled	integer (with default):
r	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Details

$$I_{LOC}(t) = -dn/dt = A * (n^2 / (r + n))$$

Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

Function version

0.0.1

How to cite

Kreutzer, S., 2019. run_MC_LM_OSL_LOC(): Run Monte-Carlo simulation for LM-OSL for localised transition. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence PhenomenaR package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

References

##TODO

Examples

```
##=====##
## Example 1: Simulate LM-OSL
##=====##
## Not run:
run_MC_LM_OSL_LOC(
  A = 0.12,
  r = 1,
  times = 0:100) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

run_MC_TL

Run Monte-Carlo simulation for TL

Description

Run Monte-Carlo simulation for TL

Usage

```
run_MC_TL(s, E, rho, r_c, times, clusters = 10, N_e = 200,
  delta.r = 0.1, method = "par", output = "signal", ...)
```

Arguments

s	list
E	numeric
rho	numeric
r_c	numeric (with default)
times	vector (with default)
clusters	numeric (with default):
N_e	numeric (with default):
delta.r	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

Function version

0.0.1 [2017-01-27]

How to cite

Friedrich, J., 2019. run_MC_TL(): Run Monte-Carlo simulation for TL. Function version 0.0.1 [2017-01-27]. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence Phenomena R package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

References

Pagonis 2017

Examples

```
## Not run:
##=====##
## Example 1: Simulate TL measurement
##=====##

times <- seq(200, 500) # time = temperature

run_MC_TL(s = 3.5e12,
          E = 1.45,
          rho = 0.015,
          r_c = 0.85,
          times = times) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

run_MC_TL_DELOC

Run Monte-Carlo simulation for TL for GOT model

Description

```
##TODO
```

Usage

```
run_MC_TL_DELOC(s, E, times, clusters = 10, N_e = 200,
  n_filled = N_e, R, method = "par", output = "signal", ...)
```

Arguments

s	numeric (required)
E	numeric (required)
times	numeric (with default)
clusters	numeric (with default):
N_e	integer (with default)
n_filled	integer (with default)
R	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Details

$$I_{DELOC}(t) = -dn/dt = p(t) * (n^2 / (NR + n(1 - R)))$$

Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

Function version

0.0.1

How to cite

Kreutzer, S., 2019. run_MC_TL_DELOC(): Run Monte-Carlo simulation for TL for GOT model. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence PhenomenaR package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

References

##TODO

Examples

```
##=====##
## Example 1: Simulate TL
##=====##
## Not run:
run_MC_TL_DELOC(
  s = 3.5e12,
  E = 1.45,
  R = 1,
  times = 100:450) %>%
  calc_RLumCarlo() %>%
```

```

plot_RLumCarlo(legend = T)

## End(Not run)

```

run_MC_TL_LOC

*Run Monte-Carlo simulation for TL for localised transition***Description**

##TODO

Usage

```
run_MC_TL_LOC(s, E, times, clusters = 10, n_filled = 100, r,
  method = "par", output = "signal", ...)
```

Arguments

s	numeric (required)
E	numeric (required)
times	numeric (with default)
clusters	numeric (with default):
n_filled	integer (with default)
r	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

Details

$$I_{LOC}(t) = -dn/dt = p(t) * (n^2/(r + n))$$

Value

This function returns an [array](#) with dimension length(times) x length(r) x clusters

Function version

0.0.1

How to cite

Kreutzer, S., 2019. run_MC_TL_LOC(): Run Monte-Carlo simulation for TL for localised transition. Function version 0.0.1. In: Friedrich, J., Kreutzer, S., Pagonis, V., Schmidt, C., 2019. RLumCarlo: Monte-Carlo Methods for Simulating Luminescence PhenomenaR package version 0.1.0.9000-16. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France)

References

##TODO

Examples

```
##=====##
## Example 1: Simulate TL
##=====##
## Not run:
run_MC_TL_LOC(
  s = 3.5e12,
  E = 1.45,
  r = 1,
  times = 100:450) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

Index

array, [3](#), [6](#), [7](#), [10](#), [11](#), [14–16](#), [18](#), [19](#)

calc_RLumCarlo, [2](#)

character, [4](#), [5](#), [7–9](#), [11](#), [12](#), [14–16](#), [18](#), [19](#)

data.frame, [3](#)

integer, [5](#), [7](#), [9](#), [11](#), [14](#), [15](#), [18](#), [19](#)

list, [16](#)

logical, [3](#)

numeric, [3–5](#), [7–9](#), [11](#), [12](#), [14–16](#), [18](#), [19](#)

plot_RLumCarlo, [3](#)

RLumCarlo-package, [2](#)

run_MC_CW_IRSL, [4](#)

run_MC_CW_IRSL_DELOC, [5](#)

run_MC_CW_IRSL_LOC, [6](#)

run_MC_ISO, [8](#)

run_MC_ISO_DELOC, [9](#)

run_MC_ISO_LOC, [11](#)

run_MC_LM_OSL, [12](#)

run_MC_LM_OSL_DELOC, [13](#)

run_MC_LM_OSL_LOC, [15](#)

run_MC_TL, [16](#)

run_MC_TL_DELOC, [17](#)

run_MC_TL_LOC, [19](#)

vector, [4](#), [12](#), [16](#)