

# Package ‘RLumCarlo’

August 29, 2018

**Type** Package

**Title** Monte-Carlo Methods for Simulating Luminescence Phenomena

**Version** 0.0.2

**Date** 2018-08-29

**Author** Johannes Friedrich [aut, trl, cre] (<<https://orcid.org/0000-0002-0805-9547>>),  
Sebastian Kreutzer [ctb] (<<https://orcid.org/0000-0002-0734-2199>>)

**Maintainer** Johannes Friedrich <johannes.friedrich@uni-bayreuth.de>

## Description

A collection of functions to simulate luminescence signals with Monte-Carlo methods in the mineral feldspar based on published models.

**Contact** Package Developer Team <johannes.friedrich@uni-bayreuth.de>

**License** GPL-3

**BugReports** <https://github.com/R-Lum/RLumCarlo/issues>

**Depends** R (>= 3.3.0), utils, magrittr

**URL** <https://CRAN.R-project.org/package=RLumModel>

**Collate** 'calc\_RLumCarlo.R' 'plot\_RLumCarlo.R' 'RcppExports.R'  
'RLumCarlo-package.R' 'run\_MC\_ISO.R' 'run\_MC\_CW\_IRSL.R'  
'run\_MC\_TL.R' 'run\_MC\_LM\_OSL.R' 'utils.R'

**LinkingTo** Rcpp, RcppProgress, RcppArmadillo

**Imports** abind, doParallel, foreach, parallel, methods, Rcpp

**Suggests** R.rsp

**Encoding** UTF-8

**VignetteBuilder** R.rsp

**RoxygenNote** 6.1.0

**NeedsCompilation** yes

## R topics documented:

RLumCarlo-package	2
calc_RLumCarlo	2
plot_RLumCarlo	3
run_MC_CW_IRSL	4
run_MC_ISO	5
run_MC_LM_OSL	6
run_MC_TL	7

**Index** 9

---

RLumCarlo-package

*Package: & RLumCarlo*  
*Type: & Package*  
*Version: & 0.0.2*  
*Date: & 2018-08-28*  
*License: & GPL-3*

---

**Description**

Package: RLumCarlo  
Type: Package  
Version: 0.0.2  
Date: 2018-08-28  
License: GPL-3

**Author(s)**

Johannes Friedrich (University of Bayreuth, Germany), Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS-Université Bordeaux Montaigne (France)

---

calc_RLumCarlo	<i>Plot results from Monte-Carlo simulations with RLumCarlo</i>
----------------	---

---

**Description**

Plot results from Monte-Carlo simulations with RLumCarlo

**Usage**

```
calc_RLumCarlo(results)
```

**Arguments**

results      [array](#):

**Value**

This function returns a [data.frame](#)

**Function version**

0.0.1 [2017-01-27]

**Author(s)**

Johannes Friedrich, University of Bayreuth (Germany)

---

plot\_RLumCarlo

*Plot results from Monte-Carlo simulations with RLumCarlo*

---

**Description**

Plot results from Monte-Carlo simulations with RLumCarlo

**Usage**

```
plot_RLumCarlo(results, times = NULL, norm = FALSE, legend = FALSE,  
               add = FALSE, ...)
```

**Arguments**

results	<a href="#">data.frame</a>
times	<a href="#">vector</a> (with default):
norm	<a href="#">character</a> (with default):
legend	<a href="#">logical</a> (with default):
add	<a href="#">logical</a> (with default):
...	further arguments

**Value**

This function returns a graphical output

**Function version**

0.0.1 [2017-01-27]

**Author(s)**

Johannes Friedrich, University of Bayreuth (Germany)

run\_MC\_CW\_IRSL

*Run Monte-Carlo simulation for CW-IRSL***Description**

Run Monte-Carlo simulation for CW-IRSL

**Usage**

```
run_MC_CW_IRSL(A, rho, times, clusters = 10, r = NULL, N_e = 200,
  method = "seq", output = "signal", ...)
```

**Arguments**

A	numeric
rho	numeric
times	vector (with default)
clusters	numeric (with default):
r	numeric (with default)
N_e	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

**Value**

This function returns a list.

**Function version**

0.0.2 [2017-01-31]

**Author(s)**

Johannes Friedrich, University of Bayreuth (Germany), Sebastian Kreutzer, IRAMAT-CRP2A, Université Bordeaux Montaigne (France)

**References**

Pagonis 2017

**Examples**

```
## Not run:

##=====##
## Example 1: Simulate CW-IRSL measurement
##=====##

run_MC_CW_IRSL(A = 0.12, rho = 0.003, times = 0:1000) %>%
```

```
calc_RLumCarlo() %>%  
  plot_RLumCarlo(norm = T, legend = T)  
  
## End(Not run)
```

---

**run\_MC\_ISO***Run Monte-Carlo simulation for isothermal measurements*

---

## Description

Run Monte-Carlo simulation for isothermal measurements

## Usage

```
run_MC_ISO(A, rho, times, clusters = 10, r = NULL, N_e = 200,  
  method = "par", output = "signal", ...)
```

## Arguments

A	numeric
rho	numeric
times	vector (with default)
clusters	numeric (with default):
r	numeric (with default)
N_e	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

## Value

This function returns a list.

## Function version

0.0.1 [2017-01-27]

## Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

## References

Pagonis 2017

## Examples

```
## Not run:
##=====##
## Example 1: Simulate isothermal measurement
##=====##

times <- seq(0, 500)
run_MC_ISO(A = 0.20,
           rho = 0.007,
           times = times) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```

---

run_MC_LM_OSL	<i>Run Monte-Carlo simulation for LM-OSL</i>
---------------	--

---

## Description

Run Monte-Carlo simulation for LM-OSL

## Usage

```
run_MC_LM_OSL(A, rho, times, clusters = 10, r = NULL, delta.r = 0.1,
              N_e = 200, method = "par", output = "signal", ...)
```

## Arguments

A	numeric
rho	numeric
times	vector (with default)
clusters	numeric (with default):
r	numeric (with default):
delta.r	numeric (with default):
N_e	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

## Value

This function returns a list.

## Function version

0.0.1 [2017-01-27]

**Author(s)**

Johannes Friedrich, University of Bayreuth (Germany)

**References**

Pagonis 2017

**Examples**

```
## Not run:

##TODO: Primary example, should be verified
run_MC_LM_OSL(A = 10000, rho = 0.0001, times = 1:100, clusters = 10, r = NULL,
  delta.r = 0.1,
  N_e = 200, method = "par", output = "signal") %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(norm = T)

## End(Not run)
```

---

run\_MC\_TL

---

*Run Monte-Carlo simulation for TL*


---

**Description**

Run Monte-Carlo simulation for TL

**Usage**

```
run_MC_TL(s, E, rho, r_c, times, clusters = 10, N_e = 200,
  delta.r = 0.1, method = "par", output = "signal", ...)
```

**Arguments**

s	list
E	numeric
rho	numeric
r_c	numeric (with default)
times	vector (with default)
clusters	numeric (with default):
N_e	numeric (with default):
delta.r	numeric (with default):
method	character (with default):
output	character (with default):
...	further arguments

**Value**

This function returns an [array](#) with dimension length(times) x length(r) x clusters

**Function version**

0.0.1 [2017-01-27]

**Author(s)**

Johannes Friedrich, University of Bayreuth (Germany)

**References**

Pagonis 2017

**Examples**

```
## Not run:
##=====##
## Example 1: Simulate TL measurement
##=====##

times <- seq(200, 500) # time = temperature

run_MC_TL(s = 3.5e12,
          E = 1.45,
          rho = 0.015,
          r_c = 0.85,
          times = times) %>%
  calc_RLumCarlo() %>%
  plot_RLumCarlo(legend = T)

## End(Not run)
```



# Index

array, [2](#), [8](#)

calc\_RLumCarlo, [2](#)

character, [3–7](#)

data.frame, [2](#), [3](#)

list, [7](#)

logical, [3](#)

numeric, [4–7](#)

plot\_RLumCarlo, [3](#)

RLumCarlo-package, [2](#)

run\_MC\_CW\_IRSL, [4](#)

run\_MC\_ISO, [5](#)

run\_MC\_LM\_OSL, [6](#)

run\_MC\_TL, [7](#)

vector, [3–7](#)