

Package ‘RLumModel’

November 8, 2021

Type Package

Title Solving Ordinary Differential Equations to Understand Luminescence

Version 0.2.10.9000-1

Date 2021-11-08

Author Johannes Friedrich [aut, trl, cre] (<<https://orcid.org/0000-0002-0805-9547>>),
Sebastian Kreutzer [aut, ths] (<<https://orcid.org/0000-0002-0734-2199>>),
Christoph Schmidt [aut, ths] (<<https://orcid.org/0000-0002-2309-3209>>)

Maintainer Johannes Friedrich <johannes.friedrich@posteo.de>

Description A collection of functions to simulate luminescence signals in quartz and Al₂O₃ based on published models.

Contact Package Developer Team <developer@model.r-luminescence.de>

License GPL-3

BugReports <https://github.com/R-Lum/RLumModel/issues>

Depends R (>= 3.6.0),
utils,
Luminescence (>= 0.9.0)

Imports deSolve (>= 1.28),
methods,
Rcpp (>= 1.0.6)

Suggests testthat (>= 3.0.0),
R.rsp (>= 0.44.0)

URL <https://CRAN.R-project.org/package=RLumModel>

Collate RLumModel-package.R
RcppExports.R
calc_signal.R
calc_concentrations.R
create_DRT.sequence.R
create_SAR.sequence.R
extract_pars.R
model_LuminescenceSignals.R
read_SEQ2R.R
set_pars.R
simulate_CW_OSL.R
simulate_heating.R
simulate_illumination.R

```

simulate_irradiation.R
simulate_LM_OSL.R
simulate_pause.R
simulate_RF.R
simulate_RF_and_heating.R
simulate_TL.R
translate_sequence.R

```

RoxygenNote 7.1.2

Encoding UTF-8

LazyData true

VignetteBuilder R.rsp

LinkingTo Rcpp (>= 1.0.1), RcppArmadillo (>= 0.9.400.2.0)

R topics documented:

RLumModel-package	2
.set_pars	3
ExampleData.ModelOutput	4
model_LuminescenceSignals	5
read_SEQ2R	13

Index	16
--------------	-----------

RLumModel-package	<i>Solving Ordinary Differential Equations to Understand Luminescence</i>
-------------------	---

Description

Details

A collection of function to simulate luminescence signals in the mineral quartz based on published models.

Authors

Johannes Friedrich	University of Bayreuth, Germany
Sebastian Kreutzer	Geography & Earth Sciences, Aberystwyth University, United Kingdom
Christoph Schmidt	University of Bayreuth, Germany

Supervisor

Christoph Schmidt, University of Bayreuth, Germany
 Sebastian Kreutzer, Geography & Earth Sciences, Aberystwyth University, United Kingdom #'

Project source code repository

- <https://github.com/R-Lum/RLumModel>

Related package projects

- <http://r-luminescence.de>

- <https://CRAN.r-project.org/package=Luminescence>
- <https://CRAN.r-project.org/package=RLumShiny>

Package maintainer

Johannes Friedrich, University of Bayreuth, Germany
[<johannes.friedrich@posteo.de>](mailto:johannes.friedrich@posteo.de)

Acknowledgement

The work of Johannes Friedrich is gratefully supported by the DFG in framework of the project 'Modelling quartz luminescence signal dynamics relevant for dating and dosimetry' (SCHM 305114-1).

`.set_pars`
Set parameters for Different Quartz Luminescence Models

Description

This function provides all necessary model parameters to the calculation of the ODEs.

Usage

```
.set_pars(model)
```

Arguments

`model` **character (required)**: set model to be used. Available models are: "Bailey2001", "Bailey2002", "Bailey2004", "Pagonis2007", "Pagonis2008"

Details

The common model parameters are:

N: concentrations of electron/hole traps in cm^{-3} **E**: depth of the electron/hole trap in eV **s**: frequency factor in s^{-1} **A**: conduction band to electron/hole trap transition probability in s^{-1} **B**: valence band to hole trap transition probability in s^{-1} **Th**: photo-ionisation cross-section in s^{-1} **E_{th}**: 'thermal assistance' energy in eV **n**: concentrations of electron/hole traps after sample history in cm^{-3}

Value

This function returns a [list](#) with all necessary parameters for the used model.

Function version

0.1.3

How to cite

Friedrich, J., 2021. `.set_pars()`: Set parameters for Different Quartz Luminescence Models. Function version 0.1.3. In: Friedrich, J., Kreutzer, S., Schmidt, C., 2021. *RLumModel: Solving Ordinary Differential Equations to Understand Luminescence*. R package version 0.2.10.9000-1. <https://CRAN.R-project.org/package=RLumModel>

Note

n are the saved concentrations of the last step of the sample history of the used model. They will be loaded, if `simulate_sample_history = FALSE` in `model_LuminescenceSignals` is chosen.

The order of the energy-band-levels is sometimes in an different order than in the original model. This was necessary, because in the simulations the luminescence centre always has to be the last entry in every parameter. Another reason was the clear division between electron traps and hole centres. When a user wants to create his/her own parameter sets he/she only has to take care that the luminescence centre is the last entry in every vector and that the first entries are the electron traps and the last entries the hole centres.

Author(s)

Johannes Friedrich, University of Bayreuth (Germany),

References

- Bailey, R.M., 2001. Towards a general kinetic model for optically and thermally stimulated luminescence of quartz. *Radiation Measurements* 33, 17-45.
- Bailey, R.M., 2002. Simulations of variability in the luminescence characteristics of natural quartz and its implications for estimates of absorbed dose. *Radiation Protection Dosimetry* 100, 33-38.
- Bailey, R.M., 2004. Paper I-simulation of dose absorption in quartz over geological timescales and it simplifications for the precision and accuracy of optical dating. *Radiation Measurements* 38, 299-310.
- Friedrich, J., Pagonis, V., Chen, R., Kreutzer, S., Schmidt, C., 2017: Quartz radiofluorescence: a modelling approach. *Journal of Luminescence* 186, 318-325.
- Pagonis, V., Chen, R., Wintle, A.G., 2007: Modelling thermal transfer in optically stimulated luminescence of quartz. *Journal of Physics D: Applied Physics* 40, 998-1006.
- Pagonis, V., Wintle, A.G., Chen, R., Wang, X.L., 2008. A theoretical model for a new dating protocol for quartz based on thermally transferred OSL (TT-OSL). *Radiation Measurements* 43, 704-708.

Examples

```
pars <- .set_pars("Bailey2001")
```

ExampleData.ModelOutput

Example data (TL curve) simulated with parameter set from Pagonis 2007

Description

Example data (TL curve) simulated with parameter set from Pagonis 2007

Format

A `RLum.Analysis` object containing one TL curve as `RLum.Data.Curve`.

Function version

0.1.1

Note

This example has only one record (TL). The used sequence was `sequence <- list(IRR = c(temp = 20, dose = 10, DoseRate = 1), TL = c(temp_begin = 20, temp_end = 400, heating_rate = 5))`

Author(s)

Johannes Friedrich, University of Bayreuth (Germany)

Source

model_LuminescenceSignals()

References

Pagonis, V., Chen, R., Wintle, A.G., 2007: Modelling thermal transfer in optically stimulated luminescence of quartz. *Journal of Physics D: Applied Physics* 40, 998-1006.

Examples

```
data("ExampleData.ModelOutput", envir = environment())

TL_curve <- get_RLum(model.output, recordType = "TL$", drop = FALSE)

##plot TL curve
plot_RLum(TL_curve)

TL_concentrations <- get_RLum(model.output, recordType = "(TL)", drop = FALSE)
plot_RLum(TL_concentrations)
```

model_LuminescenceSignals

Model Luminescence Signals

Description

This function models luminescence signals for quartz based on published physical models. It is possible to simulate TL, (CW-) OSL, RF measurements in a arbitrary sequence. This sequence is defined as a **list** of certain abrivations. Furthermore it is possible to load a sequence direct from the Riso Sequence Editor. The output is an **RLum.Analysis**object and so the plots are done by the **plot_RLum.Analysis** function. If a SAR sequence is simulated the plot output can be disabled and SAR analyse functions can be used.

Usage

```
model_LuminescenceSignals(
  model,
  sequence,
  lab.dose_rate = 1,
  simulate_sample_history = FALSE,
  plot = TRUE,
  verbose = TRUE,
  show_structure = FALSE,
  own_parameters = NULL,
  own_state_parameters = NULL,
  own_start_temperature = NULL,
  ...
)
```

Arguments

- | | |
|-------------------------|--|
| model | character (required) : set model to be used. Available models are: "Bailey2001", "Bailey2002", "Bailey2004", "Pagonis2007", "Pagonis2008", "Friedrich2017", "Friedrich2018" and for own models "customized" (or "customised"). Note: When model = "customized" is set, the argument 'own_parameters' has to be set. |
| sequence | list (required) : set sequence to model as list or as *.seq file from the Riso sequence editor. To simulate SAR measurements there is an extra option to set the sequence list (cf. details). |
| lab.dose_rate | numeric (with default): laboratory dose rate in XXX Gy/s for calculating seconds into Gray in the *.seq file. |
| simulate_sample_history | logical (with default): FALSE (with default): simulation begins at laboratory conditions, TRUE: simulations begins at crystallization (all levels 0) process |
| plot | logical (with default): Enables or disables plot output |
| verbose | logical (with default): Verbose mode on/off |
| show_structure | logical (with default): Shows the structure of the result. Recommended to show record.id to analyse concentrations. |
| own_parameters | list (with default): This argument allows the user to submit own parameter sets. The list has to contain the following items: <ul style="list-style-type: none"> • N: Concentration of electron- and hole traps [cm^{-3}] • E: Electron/Hole trap depth [eV] • s: Frequency factor [s^{-1}] • A: Conduction band to electron trap and valence band to hole trap transition probability [$\text{s}^{-1} * \text{cm}^3$]. CAUTION: Not every publication uses the same definition of parameter A and B! See vignette "RLumModel - Usage with own parameter sets" for further details • B: Conduction band to hole centre transition probability [$\text{s}^{-1} * \text{cm}^3$]. • Th: Photo-eviction constant or photoionisation cross section, respectively • E_th: Thermal assistance energy [eV] • k_B: Boltzman constant $8.617\text{e-}05$ [eV/K] • W: activation energy 0.64 [eV] (for UV) |

- K: 2.8e7 (dimensionless constant)
- model: "customized"
- R (optional): Ionisation rate (pair production rate) equivalent to 1 Gy/s [$s^{-1} * cm^{-3}$]

For further details see Bailey 2001, Wintle 1975, vignette "RLumModel - Using own parameter sets" and example 3.

own_state_parameters

numeric (with default): Some publications (e.g. Pagonis 2009) offer state parameters. With this argument the user can submit this state parameters. For further details see vignette "RLumModel - Using own parameter sets" and example 3.

own_start_temperature

numeric (with default): Parameter to control the start temperature (in deg. C) of a simulation. This parameter takes effect only when 'model = "customized"' is choosen.

...

further arguments and graphical parameters passed to `plot.default`. See details for further information.

Details

Defining a **sequence**

Arguments	Description	Sub-arguments
TL	thermally stimulated luminescence	'temp begin' [°C], 'temp end' [°C], 'heating rate' [°C/s]
OSL	optically stimulated luminescence	'temp' [°C], 'duration' [s], 'optical_power' [%]
ILL	illumination	'temp' [°C], 'duration' [s], 'optical_power' [%]
LM_OSL	linear modulated OSL	'temp' [°C], 'duration' [s], optional: 'start_power' [%], 'end_power' [%]
RL/RF	radioluminescence	'temp' [°C], 'dose' [Gy], 'dose_rate' [Gy/s]
RF_heating	RF during heating/cooling	'temp begin' [°C], 'temp end' [°C], 'heating rate' [°C/s], 'dose_rate' [Gy/s]
IRR	irradiation	'temp' [°C], 'dose' [Gy], 'dose_rate' [Gy/s]
CH	cutheat	'temp' [°C], optional: 'duration' [s], 'heating_rate' [°C/s]
PH	preheat	'temp' [°C], 'duration' [s], optional: 'heating_rate' [°C/s]
PAUSE	pause	'temp' [°C], 'duration' [s]

Note: 100 % illumination power equates to 20 mW/cm²

Defining a **SAR-sequence**

Abrivation	Description	examples
RegDose	Dose points of the regenerative cycles [Gy]	c(0, 80, 140, 260, 320, 0, 80)
TestDose	Test dose for the SAR cycles [Gy]	50
PH	Temperature of the preheat [°C]	240
CH	Temperature of the cutheat [°C]	200
OSL_temp	Temperature of OSL read out [°C]	125
OSL_duration	Duration of OSL read out [s]	default: 40
Irr_temp	Temperature of irradiation [°C]	default: 20
PH_duration	Duration of the preheat [s]	default: 10
dose_rate	Dose rate of the laboratory irradiation source [Gy/s]	default: 1
optical_power	Percentage of the full illumination power [%]	default: 90
Irr_2recover	Dose to be recovered in a dose-recovery-test [Gy]	20

Value

This function returns an [RLum.Analysis](#) object with all TL, (LM-) OSL and RF/RL steps in the sequence. Every entry is an [RLum.Data.Curve](#) object and can be plotted, analysed etc. with further RLum-functions.

Function version

0.1.5

How to cite

Friedrich, J., Kreutzer, S., 2021. model_LuminescenceSignals(): Model Luminescence Signals. Function version 0.1.5. In: Friedrich, J., Kreutzer, S., Schmidt, C., 2021. RLumModel: Solving Ordinary Differential Equations to Understand Luminescence. R package version 0.2.10.9000-1. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Johannes Friedrich, University of Bayreuth (Germany), Sebastian Kreutzer, IRAMAT-CRP2A, Université Bordeaux Montaigne (France)

References

- Bailey, R.M., 2001. Towards a general kinetic model for optically and thermally stimulated luminescence of quartz. *Radiation Measurements* 33, 17-45.
- Bailey, R.M., 2002. Simulations of variability in the luminescence characteristics of natural quartz and its implications for estimates of absorbed dose. *Radiation Protection Dosimetry* 100, 33-38.
- Bailey, R.M., 2004. Paper I-simulation of dose absorption in quartz over geological timescales and its implications for the precision and accuracy of optical dating. *Radiation Measurements* 38, 299-310.
- Friedrich, J., Kreutzer, S., Schmidt, C., 2016. Solving ordinary differential equations to understand luminescence: 'RLumModel', an advanced research tool for simulating luminescence in quartz using R. *Quaternary Geochronology* 35, 88-100.
- Friedrich, J., Pagonis, V., Chen, R., Kreutzer, S., Schmidt, C., 2017: Quartz radiofluorescence: a modelling approach. *Journal of Luminescence* 186, 318-325.
- Pagonis, V., Chen, R., Wintle, A.G., 2007: Modelling thermal transfer in optically stimulated luminescence of quartz. *Journal of Physics D: Applied Physics* 40, 998-1006.
- Pagonis, V., Wintle, A.G., Chen, R., Wang, X.L., 2008. A theoretical model for a new dating protocol for quartz based on thermally transferred OSL (TT-OSL). *Radiation Measurements* 43, 704-708.
- Pagonis, V., Lawless, J., Chen, R., Anderson, C., 2009. Radioluminescence in Al₂O₃:C - analytical and numerical simulation results. *Journal of Physics D: Applied Physics* 42, 175107 (9pp).
- Soetaert, K., Cash, J., Mazzia, F., 2012. Solving differential equations in R. Springer Science & Business Media.
- Wintle, A., 1975. Thermal Quenching of Thermoluminescence in Quartz. *Geophysical Journal International* 41, 107-113.

See Also

[plot](#), [RLum](#), [read_SEQ2R](#)

Examples

```

##=====##
## Example 1: Simulate Bailey2001
## (cf. Bailey, 2001, Fig. 1)
##=====##

##set sequence with the following steps
## (1) Irradiation at 20 deg. C with a dose of 10 Gy and a dose rate of 1 Gy/s
## (2) TL from 20-400 deg. C with a rate of 5 K/s

sequence <-
  list(
    IRR = c(20, 10, 1),
    TL = c(20, 400, 5)
  )

##model sequence
model.output <- model_LuminescenceSignals(
  sequence = sequence,
  model = "Bailey2001"
)

##get all TL concentrations

TL_conc <- get_RLum(model.output, recordType = "(TL)", drop = FALSE)

plot_RLum(TL_conc)

##plot 110 deg. C trap concentration

TL_110 <- get_RLum(TL_conc, recordType = "conc. level 1")
plot_RLum(TL_110)

##=====##
## Example 2: compare different optical powers of stimulation light
##=====##

# call function "model_LuminescenceSignals", model = "Bailey2004"
# and simulate_sample_history = FALSE (default),
# because the sample history is not part of the sequence
# the optical_power of the LED is varied and then compared.

optical_power <- seq(from = 0, to = 100, by = 20)

model.output <- lapply(optical_power, function(x){

  sequence <- list(IRR = c(20, 50, 1),
    PH = c(220, 10, 5),
    OSL = c(125, 50, x)
  )

  data <- model_LuminescenceSignals(
    sequence = sequence,
    model = "Bailey2004",
    plot = FALSE,

```

```

        verbose = FALSE
    )

    return(get_RLum(data, recordType = "OSL$", drop = FALSE))
})

##combine output curves
model.output.merged <- merge_RLum(model.output)

##plot
plot_RLum(
  object = model.output.merged,
  xlab = "Illumination time [s]",
  ylab = "OSL signal [a.u.]",
  main = "OSL signal dependency on optical power of stimulation light",
  legend.text = paste("Optical power density", 20*optical_power/100, "mW/cm^2"),
  combine = TRUE)

##=====##
## Example 3: Usage of own parameter sets (Pagonis 2009)
##=====##

own_parameters <- list(
  N = c(2e15, 2e15, 1e17, 2.4e16),
  E = c(0, 0, 0, 0),
  s = c(0, 0, 0, 0),
  A = c(2e-8, 2e-9, 4e-9, 1e-8),
  B = c(0, 0, 5e-11, 4e-8),
  Th = c(0, 0),
  E_th = c(0, 0),
  k_B = 8.617e-5,
  W = 0.64,
  K = 2.8e7,
  model = "customized",
  R = 1.7e15
)
## Note: In Pagonis 2009 is B the valence band to hole centre probability,
## but in Bailey 2001 this is A_j. So the values of B (in Pagonis 2009)
## are A in the notation above. Also notice that the first two entries in N, A and
## B belong to the electron traps and the last two entries to the hole centres.

own_state_parameters <- c(0, 0, 0, 9.4e15)

## calculate Fig. 3 in Pagonis 2009. Note: The labels for the dose rate in the original
## publication are not correct.
## For a dose rate of 0.1 Gy/s belongs a RF signal to ~ 1.5e14 (see Fig. 6).

sequence <- list(RF = c(20, 0.1, 0.1))

model_LuminescenceSignals(
  model = "customized",
  sequence = sequence,
  own_parameters = own_parameters,
  own_state_parameters = own_state_parameters)

```

```

## Not run:
##=====##
## Example 4: Simulate Thermal-Activation-Characteristics (TAC)
##=====##

##set temperature
act.temp <- seq(from = 80, to = 600, by = 20)

##loop over temperature
model.output <- vapply(X = act.temp, FUN = function(x) {

##set sequence, note: sequence includes sample history
sequence <- list(
  IRR = c(20, 1, 1e-11),
  IRR = c(20, 10, 1),
  PH = c(x, 1),
  IRR = c(20, 0.1, 1),
  TL = c(20, 150, 5)
)
##run simulation
temp <- model_LuminescenceSignals(
  sequence = sequence,
  model = "Pagonis2007",
  simulate_sample_history = TRUE,
  plot = FALSE,
  verbose = FALSE
)
  ## "TL$" for exact matching TL and not (TL)
  TL_curve <- get_RLum(temp, recordType = "TL$")
  ##return max value in TL curve
  return(max(get_RLum(TL_curve)[,2]))
}, FUN.VALUE = 1)

##plot results
plot(
  act.temp[-(1:3)],
  model.output[-(1:3)],
  type = "b",
  xlab = "Temperature [°C]",
  ylab = "TL [a.u.]"
)

##=====##
## Example 5: Simulate SAR sequence
##=====##

##set SAR sequence with the following steps
## (1) RegDose: set regenerative dose [Gy] as vector
## (2) TestDose: set test dose [Gy]
## (3) PH: set preheat temperature in deg. C
## (4) CH: Set cutheat temperature in deg. C
## (5) OSL_temp: set OSL reading temperature in deg. C
## (6) OSL_duration: set OSL reading duration in s

sequence <- list(
  RegDose = c(0,10,20,50,90,0,10),

```

```

TestDose = 5,
PH = 240,
CH = 200,
OSL_temp = 125,
OSL_duration = 70)

# call function "model_LuminescenceSignals", set sequence = sequence,
# model = "Pagonis2007" (palaeodose = 20 Gy) and simulate_sample_history = FALSE (default),
# because the sample history is not part of the sequence

model.output <- model_LuminescenceSignals(
  sequence = sequence,
  model = "Pagonis2007",
  plot = FALSE
)

# in environment is a new object "model.output" with the results of
# every step of the given sequence.
# Plots are done at OSL and TL steps and the growth curve

# call "analyse_SAR.CWOSL" from RLum package
results <- analyse_SAR.CWOSL(model.output,
  signal.integral.min = 1,
  signal.integral.max = 15,
  background.integral.min = 601,
  background.integral.max = 701,
  fit.method = "EXP",
  dose.points = c(0,10,20,50,90,0,10))

##=====##
## Example 6: generate sequence from *.seq file and run SAR simulation
##=====##

# load example *.SEQ file and construct a sequence.
# call function "model_LuminescenceSignals", load created sequence for sequence,
# set model = "Bailey2002" (palaeodose = 10 Gy)
# and simulate_sample_history = FALSE (default),
# because the sample history is not part of the sequence

path <- system.file("extdata", "example_SAR_cycle.SEQ", package="RLumModel")

sequence <- read_SEQ2R(file = path)

model.output <- model_LuminescenceSignals(
  sequence = sequence,
  model = "Bailey2001",
  plot = FALSE
)

## call RLum package function "analyse_SAR.CWOSL" to analyse the simulated SAR cycle

results <- analyse_SAR.CWOSL(model.output,
  signal.integral.min = 1,
  signal.integral.max = 10,
  background.integral.min = 301,

```

```

background.integral.max = 401,
dose.points = c(0,8,14,26,32,0,8),
fit.method = "EXP")

print(get_RLum(results))

##=====##
## Example 7: Simulate sequence at laboratory without sample history
##=====##

##set sequence with the following steps
## (1) Irraditation at 20 deg. C with a dose of 100 Gy and a dose rate of 1 Gy/s
## (2) Preheat to 200 deg. C and hold for 10 s
## (3) LM-OSL at 125 deg. C. for 100 s
## (4) Cutheat at 200 dec. C.
## (5) Irraditation at 20 deg. C with a dose of 10 Gy and a dose rate of 1 Gy/s
## (6) Pause at 200 de. C. for 100 s
## (7) OSL at 125 deg. C for 100 s with 90 % optical power
## (8) Pause at 200 deg. C for 100 s
## (9) TL from 20-400 deg. C with a heat rate of 5 K/s
## (10) Radiofluorescence at 20 deg. C with a dose of 200 Gy and a dose rate of 0.01 Gy/s

sequence <-
list(
  IRR = c(20, 100, 1),
  PH = c(200, 10),
  LM_OSL = c(125, 100),
  CH = c(200),
  IRR = c(20, 10, 1),
  PAUSE = c(200, 100),
  OSL = c(125, 100, 90),
  PAUSE = c(200, 100),
  TL = c(20, 400, 5),
  RF = c(20, 200, 0.01)
)

# call function "model_LuminescenceSignals", set sequence = sequence,
# model = "Pagonis2008" (palaeodose = 200 Gy) and simulate_sample_history = FALSE (default),
# because the sample history is not part of the sequence

model.output <- model_LuminescenceSignals(
  sequence = sequence,
  model = "Pagonis2008"
)

## End(Not run)

```

Description

A SEQ-file created by the Risoe Sequence Editor can be imported to simulate the sequence written in the sequence editor.

Usage

```
read_SEQ2R(file, lab.dose_rate = 1, txtProgressBar = TRUE)
```

Arguments

`file` **character** (**required**): a *.seq file created by the Risoe Sequence Editor

`lab.dose_rate` **character** (with default): set the dose rate of the radiation source in the laboratory Gy/s. Default: 1 Gy/s

`txtProgressBar` **logical** (with default): enables or disables the txtProgressBar for a visuall control of the progress. Default: txtProgressBar = TRUE

Details

Supported versions: Suppored and tested: version 4.36.

Value

This function returns a **list** with the parsed *.seq file and the required steps for `model_LuminescenceSignals`.

Function version

0.1.0

How to cite

Friedrich, J., 2021. read_SEQ2R(): Parse a Risoe SEQ-file to a sequence neccessary for simulating quartz luminescence. Function version 0.1.0. In: Friedrich, J., Kreutzer, S., Schmidt, C., 2021. RLumModel: Solving Ordinary Differential Equations to Understand Luminescence. R package version 0.2.10.9000-1. <https://CRAN.R-project.org/package=RLumModel>

Author(s)

Johannes Friedrich, University of Bayreuth (Germany),

References

Riso: Sequence Editor User Manual. Available at: http://www.nutech.dtu.dk/english/-/media/Andre_Universitetsenheden/SequenceEditor.ashx?la=da

See Also

`model_LuminescenceSignals`, `readLines`

Examples

```
##search "example_SAR_cycle.SEQ" in "extdata" in package "RLumModel"  
path <- system.file("extdata", "example_SAR_cycle.SEQ", package="RLumModel")  
  
sequence <- read_SEQ2R(file = path, txtProgressBar = FALSE)
```

Index

- * **datasets**
 - ExampleData.ModelOutput, [4](#)
- * **package**
 - RLumModel-package, [2](#)
- .set_pars, [3](#)
- character, [3](#), [6](#), [14](#)
- ExampleData.ModelOutput, [4](#)
- list, [3](#), [5](#), [6](#), [14](#)
- logical, [6](#), [14](#)
- model.output (ExampleData.ModelOutput),
[4](#)
- model_LuminescenceSignals, [4](#), [5](#), [14](#)
- numeric, [6](#), [7](#)
- plot, [8](#)
- plot.default, [7](#)
- plot_RLum.Analysis, [5](#)
- read_SEQ2R, [8](#), [13](#)
- readLines, [14](#)
- RLum, [8](#)
- RLum.Analysis, [5](#), [8](#)
- RLum.Data.Curve, [8](#)
- RLumModel-package, [2](#)