

# Package ‘RLumModel’

December 12, 2015

**Type** Package

**Title** Modelling Ordinary Differential Equations Leading to  
Luminescence

**Version** 0.1.0

**Date** 2016-XX-XX

**Author** Johannes Friedrich [aut, trl, cre],  
Sebastian Kreutzer [aut, ths],  
Christoph Schmidt [aut, ths]

**Maintainer** Johannes Friedrich <johannes.friedrich@uni-bayreuth.de>

**Description** A collection of function to simulate luminescence signals in the  
mineral quartz based on published models.

**Contact** Package Developer Team <developer@model.r-luminescence.de>

**License** GPL-3

**Depends** R (>= 3.2.2), utils, Luminescence (>= 0.5.0)

**Imports** deSolve (>= 1.12)

**URL** <http://CRAN.R-project.org/package=RLumModel>

**Collate** RLumModel-package.R calc\_Signal.R model\_LuminescenceSignals.R  
read\_SEQ2R.R set\_ODE.R set\_ODE\_LM\_OSL.R set\_Pars.R  
simulate\_CW\_OSL.R simulate\_DRT.sequence.R simulate\_LM\_OSL.R  
simulate\_RL.R simulate\_SAR.sequence.R simulate\_TL.R  
simulate\_heating.R simulate\_illumination.R  
simulate\_irradiation.R simulate\_pause.R translate\_Sequence.R

**RoxygenNote** 5.0.1

**NeedsCompilation** no

## R topics documented:

RLumModel-package . . . . .	2
model_LuminescenceSignals . . . . .	3
<b>Index</b>	<b>8</b>

---

RLumModel-package

*Modelling Ordinary Differential Equations Leading to Luminescence*


---

## Description

A collection of function to simulate luminescence signals in the mineral quartz based on published models.

## Details

Package: RLumModel  
 Type: Package  
 Version: 0.1.0  
 Date: 2016-XX-XX  
 License: GPL-3

## Author(s)

### Authors

Johannes Friedrich	University of Bayreuth, Germany
Sebastian Kreutzer	IRAMAT-CRP2A, Universite Bordeaux Montaigne, France
Christoph Schmidt	University of Bayreuth, Germany

### Supervisor

Christoph Schmidt, University of Bayreuth, Germany  
 Sebastian Kreutzer, IRAMAT-CRP2A, Universite Bordeaux Montaigne, France

### Support contact

<developers@model.r-luminescence.de>

### Project source code repository

<https://github.com/R-Lum/RLumModel>

### Related projects

<http://www.r-luminescence.de>  
<http://cran.r-project.org/package=Luminescence>  
<http://shiny.r-luminescence.de>  
<http://cran.r-project.org/package=RLumShiny>

### Package maintainer

Johannes Friedrich, University of Bayreuth, Germany  
 <johannes.friedrich@uni-bayreuth.de>

### Acknowledgement

The work of Johannes Friedrich is gratefully supported by the DFG in framework of the project 'Modelling quartz luminescence signal dynamics relevant for dating and dosimetry' (SCHM 305114-1)

---

model\_LuminescenceSignals

*Model Luminescence Signals*


---

## Description

This function models luminescence signals for quartz based on published physical models. It is possible to simulate TL, (CW-) OSL, RF measurements in a arbitrary sequence. This sequence is defined as a list of certain abrivations. Furthermore it is possible to load a sequence direct from the Riso Sequence Editor. The output is an RLum.Analysis object and so the plots are done by the plot\_RLum.Analysis function. If a SAR sequence is simulated the plot output can be disabled and SAR analyse functions can be used.

## Usage

```
model_LuminescenceSignals(model, sequence, lab.DoseRate = 1,
  simulate_sample_history = FALSE, plot = TRUE, verbose = TRUE, ...)
```

## Arguments

model	<b>character (required)</b> : set model to be used
sequence	<b>list (required)</b> : set sequence to model as list or as *.seq file from the Riso sequence editor. To simulate SAR measurements there is an extra option to set the sequence list (cf. example 3): <b>(required)</b> : RegDose: <b>numeric</b> , TestDose: <b>numeric</b> , PH: <b>numeric</b> , CH: <b>numeric</b> , OSL_temp: <b>numeric</b> . With default are: DoseRate: <b>numeric</b> , Irr_temp: <b>numeric</b> , optical_power: <b>numeric</b> , OSL_duration: <b>numeric</b> , PH_duration: <b>numeric</b>
lab.DoseRate	<b>numeric</b> (with default): laboratory dose rate in XXX Gy/s for calculating seconds into Gray in the *.seq file.
simulate_sample_history	<b>logical</b> (with default): FALSE (with default): simulation begins at labour conditions, TRUE: simulations begins at crystallization (all levels 0) process
plot	<b>logical</b> (with default): Enables or disables plot output
verbose	<b>logical</b> (with default): Verbose mode on/off
...	further arguments and graphical parameters passed to <code>plot.default</code> . See details for further information

## Details

### Defining a sequence

Abrivation	Description	Arguments
TL	thermally stimulated luminescence	'temp begin', 'temp end', 'heating rate'
OSL	optically stimulated luminescence	'temp', 'duration', 'optical power'
LM_OSL	linear modulated OSL	'temp', 'duration'

RL/RF	radioluminescence	'temp','dose','dose_rate'
IRR	irradiation	'temp','dose','dose_rate'
CH	cutheat	'temp','duration'
PH	preheat	'temp','duration'
PAUSE	pause	'temp','duration'

**Value**

This function returns an `RLum.Analysis` object with all TL, (LM-) OSL and RF/RL steps in the sequence. Every entry is a `RLum.Data.Curve` object and can be plotted, analysed etc. with further `RLum` functions.

**Function version**

0.1.0

**Note**

This function can do just nothing at the moment.

**Author(s)**

Johannes Friedrich, University of Bayreuth (Germany), Sebastian Kreutzer, IRAMAT-CRP2A, Université Bordeaux Montaigne (France)

**References**

- Bailey, R.M., 2001. Towards a general kinetic model for optically and thermally stimulated luminescence of quartz. *Radiation Measurements* 33, 17-45.
- Bailey, R.M., 2002. Simulations of variability in the luminescence characteristics of natural quartz and its implications for estimates of absorbed dose. *Radiation Protection Dosimetry* 100, 33-38.
- Bailey, R.M., 2004. Paper I-simulation of dose absorption in quartz over geological timescales and its implications for the precision and accuracy of optical dating. *Radiation Measurements* 38, 299-310.
- Pagonis, V., Chen, R., Wintle, A.G., 2007: Modelling thermal transfer in optically stimulated luminescence of quartz. *Journal of Physics D: Applied Physics* 40, 998-1006.
- Pagonis, V., Wintle, A.G., Chen, R., Wang, X.L., 2008. A theoretical model for a new dating protocol for quartz based on thermally transferred OSL (TT-OSL). *Radiation Measurements* 43, 704-708.

**See Also**

[plot](#)

**Examples**

```
##=====##
## Example 1: Simulate sample history of Bailey2001
## (cf. Bailey, 2001, Fig. 1)
##=====##
```

```

##set sequence with the following steps
## (1) Irradiation at 20 deg. C with a dose of 10 Gy and a dose rate of 1 Gy/s
## (2) TL from 20-400 deg. C with a rate of 5 K/s
sequence <-
  list(
    IRR = c(20, 10, 1),
    TL = c(20, 400, 5)
  )

##model sequence
model.output <- model_LuminescenceSignals(
  sequence = sequence,
  model = "Bailey2001",
)

## Not run:
##=====##
## Example 2: Simulate sequence at labour without sample history
##=====##

##set sequence with the following steps
## (1) Irradiation at 30 deg. C with a dose of 100 Gy and a dose rate of 1 Gy/s
## (2) Preheat to 200 deg. C and hold for 10 s
## (3) LM-OSL at 125 deg. C. for 1000 s
## (4) OSL at 20 deg. C for 100 s with 90 % optical power
## (5) Cutheat at 220 deg. C
## (6) Irradiation at 20 deg. C with a dose of 10 Gy and a dose rate of 1 Gy/s
## (7) Pause at 200 deg. C for 100 s
## (8) TL from 20-400 deg. C with a heat rate of 5 K/s
## (9) Radioluminescence at 20 deg. C with a dose of 20 Gy and a dose rate of 1 Gy/s

sequence <-
  list(
    IRR = c(20, 100, 1),
    PH = c(200, 10),
    LM_OSL = c(125, 100),
    CH = c(200),
    IRR = c(20, 10, 1),
    PAUSE = c(200, 100),
    OSL = c(125, 100, 90),
    PAUSE = c(200, 100),
    TL = c(20, 400, 5),
    RF = c(20, 200, 0.01)
  )

# call function "model_LuminescenceSignals", set sequence = sequence, model = "Pagonis2008" (palaeodose = 200
# and simulate_sample_history = FALSE (default), because the sample history is not part of the sequence

model.output <- model_LuminescenceSignals(
  sequence = sequence,
  model = "Pagonis2008"
)

##=====##
## Example 3: Simulate SAR sequence

```

```

##=====##

##set SAR sequence with the following steps
## (1) RegDose: set regenerative dose [Gy] as vector
## (2) TestDose: set test dose [Gy]
## (3) PH: set preheat temperature in deg. C
## (4) CH: Set cutheat temperature in deg. C
## (5) OSL_temp: set OSL reading temperature in deg. C
## (6) OSL_duration: set OSL reading duration in s

sequence <- list(
  RegDose = c(0,10,20,50,90,0,10),
  TestDose = 5,
  PH = 240,
  CH = 200,
  OSL_temp = 125,
  OSL_duration = 70)

# call function "model_LuminescenceSignals", set sequence = sequence, model = "Pagonis2007" (palaeodose = 20
# and simulate_sample_history = FALSE (default), because the sample history is not part of the sequence

model.output <- model_LuminescenceSignals(

  sequence = sequence,
  model = "Pagonis2007",
  plot = FALSE
)

# in environment is a new object "model.output" with the results of every step of the given sequence.
# Plots are done at OSL and TL steps and the growth curve

# call "analyse_SAR.CWOSL" from RLum package
results <- analyse_SAR.CWOSL(model.output,
  signal.integral.min = 1,
  signal.integral.max = 15,
  background.integral.min = 601,
  background.integral.max = 701,
  fit.method = "EXP",
  dose.points = c(0,10,20,50,90,0,10))

##=====##
## Example 4: generate sequence from *.seq file and run SAR simulation
##=====##

## call function "model_LuminescenceSignals", load *.seq file for sequence, set model = "Bailey2002" (palaeod
## and simulate_sample_history = FALSE (default), because the sample history is not part of the sequence

model.output <- model_LuminescenceSignals(
  sequence = "inst/extdata/sample_SAR_cycle.SEQ",
  model = "Bailey2002",
  plot = FALSE
)

## call RLum package function "analyse_SAR.CWOSL" to analyse the simulated SAR cycle

```

```

results <- analyse_SAR.CWOSL(model.output,
                             signal.integral.min = 1,
                             signal.integral.max = 10,
                             background.integral.min = 601,
                             background.integral.max = 701,
                             dose.points = c(0,5,10,20,50,5,0),
                             fit.method = "EXP")

print(get_RLum(results))

##=====##
## Example 5: compare different optical powers of stimulation light
##=====##

## call function "model_LuminescenceSignals", model = "Bailey2004"
## and simulate_sample_history = FALSE (default), because the sample history is not part of the sequence
## the optical_power of the LED is varied and then compared.

optical_power <- seq(from = 0,to = 100,by = 20)

model.output <- lapply(1:length(optical_power), function(x){

sequence <- list(IRR = c(20, 50, 1),
                 PH = c(220, 10, 5),
                 OSL = c(125, 50, optical_power[x])
                 )

return(model_LuminescenceSignals(
  sequence = sequence,
  model = "Bailey2004",
  plot = FALSE
))
})

##combine output curves
model.output.merged <- merge_RLum(model.output)

##plot
plot_RLum(
  object = model.output.merged,
  xlab = "Illumination time [s]",
  ylab = "OSL signal [a.u.]",
  main = "OSL signal dependency on optical power of stimulation light",
  legend.text = paste("Optical power density", 20*optical_power/100, "mW/cm^2"),
  combine = TRUE)

## End(Not run)

```

# Index

\*Topic **package**

RLumModel-package, [2](#)

character, [3](#)

list, [3](#)

logical, [3](#)

model\_LuminescenceSignals, [3](#)

numeric, [3](#)

plot, [4](#)

plot.default, [3](#)

RLumModel (RLumModel-package), [2](#)

RLumModel-package, [2](#)