

# Package ‘rxylib’

July 6, 2017

**Type** Package

**Title** Import XY-Data into R

**Description** Provides access to the 'xylib' C library for to import xy data from powder diffraction, spectroscopy and other experimental methods.

**Version** 0.1.1

**Date** 2017-07-05

**Author** Sebastian Kreutzer [aut, trl, cre],  
Johannes Friedrich [ctb],  
RLum Team [ctb],  
Marcin Wojdyr [cph] (C++ library 'xylib'),  
Peng Zhang [cph] (C++ library 'xylib')

**Maintainer** Sebastian Kreutzer <sebastian.kreutzer@u-bordeaux-montaigne.fr>

**URL** <https://github.com/R-Lum/rxylib>

**BugReports** <https://github.com/R-Lum/rxylib/issues>

**License** GPL-3 | LGPL-2.1

**Depends** R (>= 3.3.0), utils

**Imports** Rcpp (>= 0.12.11), httr (>= 1.2.1)

**Suggests** testthat (>= 1.0.2)

**LinkingTo** Rcpp (>= 0.12.11), BH (>= 1.62.0-1)

**Encoding** UTF-8

**Collate** 'rxylib.R' 'RcppExports.R' 'read\_xyData.R'

**RoxygenNote** 6.0.1

**NeedsCompilation** yes

## R topics documented:

rxylib-package	2
read_xyData	3
<b>Index</b>	<b>4</b>

rxylib-package

*Import XY-Data into R***Description**

Provides access to the 'xylib' C library for to import xy data from powder diffraction, spectroscopy and other experimental methods, like gamma-ray spectrometry.

Package: rxylib  
 Type: Package  
 Version: 0.1.1  
 Date: 2017-07-05  
 License: GPL-3 | LGPL-2.1 (for the C++ library 'xylib')

**Details**

Currently the package uses 'xylib' in version 1.6 (unreleased).

Supported data formats

ID	NAME	DESCRIPTION	FILE EXTENSION	VALID_OPTIONS	DATATYPE	BLO
[1,]	cpi	Sietronics Sieray CPI	cpi		ascii	single
[2,]	uxd	Bruker Diffrac-AT UXD	uxd		ascii	multi
[3,]	rigaku_dat	Rigaku DAT	dat		ascii	multi
[4,]	bruker_raw	Siemens/Bruker RAW	raw		binary	multi
[5,]	bruker_spc	Bruker ESP300-E SPC	spc		binary	single
[6,]	vamas	VAMAS ISO-14976	vms		ascii	multi
[7,]	philips_udf	Philips UDF	udf		ascii	single
[8,]	spe	PI WinSpec SPE	spe		binary	multi
[9,]	pdCIF	Powder Diffraction CIF	cif		ascii	multi
[10,]	philips_rd	Philips PC-APD RD/SD	rd sd		binary	single
[11,]	xrdml	PANalytical XRDML	xrdml		ascii	multi
[12,]	canberra_mca	Canberra MCA	mca dat		binary	single
[13,]	canberra_cnf	Canberra CNF	cnf		binary	single
[14,]	xfit_xdd	XFIT XDD	xdd		ascii	single
[15,]	riet7	RIET7/LHPM/PSI_DMC	dat		ascii	single
[16,]	dbws	DBWS data	dbw rit neu		ascii	single
[17,]	chiplot	ChiPLOT data	chi		ascii	single
[18,]	spectra	Spectra / VGX 900	1 2 3 4 5 6 7 8 9		ascii	multi
[19,]	specsxy	SPECS SpecsLab2 xy	xy		ascii	multi
[20,]	csv	CSV or TSV	csv tsv tab	decimal-comma	ascii	single

**Author(s)**

Sebastian Kreutzer, IRAMAT-CRP2A, Universite Bordeaux Montaigne (France), RLum Team (family support), Marcin Wojdyr (maintainer and author of the C++ library 'xylib'), Peng Zhang (author of the C++ library 'xylib')

---

read\_xyData*Import xy-Data for Supported Formats into R*

---

## Description

The function provides access to the underlying `xylib` to import data for supported file formats into R. In most cases, only the file path is needed with further arguments to import the data. The function automatically recognises allowed formats. See [rxylib-package](#) for supported formats.

## Usage

```
read_xyData(file, options = "", verbose = TRUE)
```

## Arguments

<code>file</code>	<a href="#">character</a> ( <b>required</b> ): path and file to be imported. The argument accepts an URL.
<code>options</code>	<a href="#">character</a> (with default): set format options (see <a href="#">rxylib-package</a> )
<code>verbose</code>	<a href="#">logical</a> ( <i>with default</i> ): enables/disables verbose mode

## Value

The functions returns a [list](#) of matrices.

## Function version

0.1.0

## Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, Universite Bordeaux Montaigne (France)

## Examples

```
##load example dataset
file <- system.file("extdata/ExampleSpectrum.CNF", package = "rxylib")
results <- read_xyData(file)

##plot spectrum
plot(results[[1]],
      type = "l",
      log = "y",
      xlab = "Energy [keV]",
      ylab = "Counts",
      main = "Thorite - 1800 s")

mtext(side = 3, "Canberra Inspector 1000, 3 x 3 NaI probe")
```

# Index

## \*Topic **IO**

read\_xyData, [3](#)

## \*Topic **package**

rxylib-package, [2](#)

character, [3](#)

list, [3](#)

logical, [3](#)

read\_xyData, [3](#)

rxylib (rxylib-package), [2](#)

rxylib-package, [2](#), [3](#)