# Package 'rxylib'

June 5, 2019
Type Package
Title Import XY-Data into R
<b>Description</b> Provides access to the 'xylib' C library for to import xy data from powder diffraction, spectroscopy and other experimental methods.
Version 0.2.5.9000-1
<b>Date</b> 2019-06-05
Author Sebastian Kreutzer [aut, trl, cre] ( <a href="https://orcid.org/0000-0002-0734-2199">https://orcid.org/0000-0002-0734-2199</a> ), Johannes Friedrich [aut] ( <a href="https://orcid.org/0000-0002-0805-9547">https://orcid.org/0000-0002-0805-9547</a> ), RLum Team [ctb], Marcin Wojdyr [cph] (C++ library 'xylib'), Peng Zhang [cph] (C++ library 'xylib')
$\begin{tabular}{ll} \textbf{Maintainer} & \textbf{Sebastian Kreutzer} \\ \textbf{Sebastian Kreutzer} \\ \textbf{Qu-bordeaux-montaigne.fr} \\ Proposition of the propositi$
<pre>URL https://github.com/R-Lum/rxylib</pre>
<pre>BugReports https://github.com/R-Lum/rxylib/issues</pre>
License GPL-3   LGPL-2.1
<b>Depends</b> R (>= 3.3.0), utils
Imports methods, Rcpp (>= 0.12.11)
Suggests testthat (>= 1.0.2)
<b>LinkingTo</b> Rcpp (>= 0.12.11), BH (>= 1.62.0-1)
Encoding UTF-8
Collate 'methods_rxylib.R'     'rxylib.R'     'RcppExports.R'     'read_xyData.R'     'convert_xy2TKA.R'
RoxygenNote 6.1.1
R topics documented:
rxylib-package convert_xy2TKA methods_rxylib read_xyData

2 rxylib-package

Index 7

## Description

Provides access to the 'xylib' C++ library for to import xy data from powder diffraction, spectroscopy and other experimental methods, like gamma-ray spectrometry.

License: GPL-3 | LGPL-2.1 (for the C++ library 'xylib')

#### **Details**

#### **Funding**

Between 2017-2019, the work of Sebastian Kreutzer as maintainer of the package was supported by LabEx LaScArBxSK (ANR - n. ANR-10-LABX-52).

Supported data formats: library version: 1.6.0

ID	NAME	DESCRIPTION	FILE EXTENSION	VALID_OPTIONS	DATATYPE
[1,]	cpi	Sietronics Sieray CPI	cpi		ascii
[2,]	uxd	Bruker Diffrac-AT UXD	uxd		ascii
[3,]	rigaku_dat	Rigaku DAT	dat		ascii
[4,]	bruker_raw	Siemens/Bruker RAW	raw		binary
[5,]	bruker_spc	Bruker ESP300-E SPC	spc par		binary
[6,]	vamas	VAMAS ISO-14976	vms		ascii
[7,]	philips_udf	Philips UDF	udf		ascii
[8,]	spe	PI WinSpec SPE	spe		binary
[9,]	pdcif	Powder Diffraction CIF	cif		ascii
[10,]	philips_rd	Philips PC-APD RD/SD	rd sd		binary
[11,]	xrdml	PANalytical XRDML	xrdml		ascii
[12,]	canberra_mca	Canberra MCA	mca dat		binary
[13,]	canberra_cnf	Canberra CNF	cnf		binary
[14,]	xfit_xdd	XFIT XDD	xdd		ascii
[15,]	riet7	RIET7/LHPM/PSI_DMC	dat		ascii
[16,]	dbws	DBWS data	dbw rit neu		ascii
[17,]	chiplot	ChiPLOT data	chi		ascii
[18,]	spectra	Spectra / VGX 900	123456789		ascii
[19,]	specsxy	SPECS SpecsLab2 xy	xy		ascii
[20,]	csv	CSV or TSV	csv tsv tab	decimal-comma	ascii
[21,]	xsyg	Freiberg Instruments (FI) Lexsyg	xsyg		ascii

## Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, Université Bordeaux Montaigne (France), Johannes Friedrich (University of Bayreuth, Germany), RLum Team (family support), Marcin Wojdyr (maintainer and author of the C++ library xylib), Peng Zhang (author of the C++ library xylib)

convert\_xy2TKA 3

## Description

Convert data to the Toolkit file format (TKA) as exported by, e.g., by the software Canberra Genie 2000.

### Usage

```
convert_xy2TKA(object, file = NULL, overwrite = FALSE)
```

## Arguments

object	rxylib ( <b>required</b> ): xy data as imported by the function read_xyData. Optional a file supported by the rxylib-package can be provided as input. Arguments can be provided as list.
file	character (optional): optional file path or file name for the output to be written. If only a path is provided the output file name is derived from the input file name. Argument can be provided as list.

overwrite logical (with default): force overwriting of existing files if TRUE.

## **Details**

## **Supported formats**

- · Canberra CNF
- further formats on request ...

#### Value

Returns a list of matrix objects or an output TKA-file.

## **Function version**

0.1.0

## How to cite

Kreutzer, S., 2019. convert\_xy2TKA(): Convert xy-data to TKA. Function version 0.1.0. In: Kreutzer, S., Friedrich, J., 2019. rxylib: Import XY-Data into R R package version 0.2.5.9000-1. https://github.com/R-Lum/rxylib

## Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, Université Bordeaux Montaigne (France)

4 methods\_rxylib

#### **Examples**

```
##convert CNF data (no export to file system)
convert_xy2TKA(
  object = system.file("extdata/ExampleSpectrum.CNF", package = "rxylib"))

## Not run:
##export as file

##create temporary filepath
##(for usage replace by own path)
temp_file <- tempfile(pattern = "output", fileext = ".TKA")

##convert and write to file system
convert_xy2TKA(
  object = system.file("extdata/ExampleSpectrum.CNF", package = "rxylib"),
  file = temp_file)

## End(Not run)</pre>
```

methods\_rxylib

methods\_ryxlib

#### **Description**

S3-methods support by the package rxylib. Listed functions can be passed directly into S3 generics (e.g., plot, print) without reshaping the data.

## Usage

```
## S3 method for class 'rxylib'
print(x, ...)
## S3 method for class 'rxylib'
plot(x, block = NULL, ...)
```

#### **Arguments**

```
x (required): input opject
... further arguments that can be passed to the method
block numeric (with default): select block for plotting, e.g. c(1:2).
```

read\_xyData 5

read_xyData	read_xyData	Import xy-Data for Supported Formats into R		
-------------	-------------	---	--	--

#### **Description**

The function provides access to the underlying xylib to import data for supported file formats into R. In most cases, only the file path is needed with further arguments to import the data. The function automatically recognises allowed formats. See rxylib-package for supported formats.

#### Usage

```
read_xyData(file, options = "", verbose = TRUE, metaData = TRUE)
```

#### **Arguments**

file	$\mbox{\it character}$ ( $\mbox{\it required}$ ): path and file to be imported. The argument accepts an URL.
options	character (with default): set format options (see rxylib-package)
verbose	logical (with default): enables/disables verbose mode
metaData	logical (with default): enables/disbales the export of metadata

#### Value

The functions returns a list of matrices.

#### **Function version**

0.3.0

#### How to cite

Kreutzer, S., Friedrich, J., 2019. read\_xyData(): Import xy-Data for Supported Formats into R. Function version 0.3.0. In: Kreutzer, S., Friedrich, J., 2019. rxylib: Import XY-Data into R R package version 0.2.5.9000-1. https://github.com/R-Lum/rxylib

#### Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, UMR 5060, CNRS - Université Bordeaux Montaigne (France), Johannes Friedrich, University of Bayreuth (Germany)

## Examples

```
##load example dataset
file <- system.file("extdata/ExampleSpectrum.CNF", package = "rxylib")
results <- read_xyData(file)
results

##plot xy-spectrum
plot(results,
   type = "l",
   xlab = "Energy [keV]",</pre>
```

6 read\_xyData

```
ylab = "Counts",
main = "Thorite - 1800 s")

mtext(side = 3, "Canberra Inspector 1000, 3 x 3 NaI probe")

##plot contour for TL-spectrum
##imported from an XSYG-file
spectrum <- read_xyData(system.file("extdata/TLSpectrum.xsyg", package = "rxylib"))
contour(
    x = spectrum$dataset[[1]]$data_block[,1],
    y = 1:ncol(spectrum$dataset[[1]]$data_block[,-1]),
    z = spectrum$dataset[[1]]$data_block[,-1],
    xlab = "Wavelength [nm]",
    ylab = "#Channel",
    main = "TL Spectrum")</pre>
```

## **Index**

```
*Topic IO
    convert_xy2TKA, 3
    read_xyData, 5
*Topic package
    rxylib-package, 2
character, 3, 5
convert\_xy2TKA, 3
list, 3, 5
logical, 3, 5
matrix, 3
{\tt methods\_rxylib}, {\tt 4}
numeric, 4
plot, 4
\verb|plot.rxylib| (\verb|methods_rxylib|), 4
print,4
print.rxylib (methods_rxylib), 4
read_xyData, 3, 5
rxylib, 3
rxylib (rxylib-package), 2
rxylib-package, 2, 5
```