

Package ‘rxylib’

July 5, 2017

Type Package

Title Import XY-Data into R

Description Provides access to the 'xylib' C library for to import xy data from powder diffraction, spectroscopy and other experimental methods.

Version 0.1.1

Date 2017-07-05

Author Sebastian Kreutzer [aut, trl, cre],
RLum Team [ctb],
Marcin Wojdyr [cph] (C++ library 'xylib'),
Peng Zhang [cph] (C++ library 'xylib')

Maintainer Sebastian Kreutzer <sebastian.kreutzer@u-bordeaux-montaigne.fr>

URL <https://github.com/R-Lum/rxylib>

BugReports <https://github.com/R-Lum/rxylib/issues>

License GPL-3 | LGPL-2.1

Depends R (>= 3.3.0), utils

Imports Rcpp (>= 0.12.11), stringr (>= 1.2.0), httr (>= 1.2.1)

Suggests testthat (>= 1.0.2)

LinkingTo Rcpp (>= 0.12.11), BH (>= 1.62.0-1)

Encoding UTF-8

Collate 'rxylib.R' 'RcppExports.R' 'read_xyData.R'

RoxygenNote 6.0.1

NeedsCompilation yes

R topics documented:

rxylib-package	2
read_xyData	3

Index	4
--------------	----------

rxylib-package

*Import XY-Data into R***Description**

Provides access to the 'xylib' C library for to import xy data from powder diffraction, spectroscopy and other experimental methods, like gamma-ray spectrometry.

Package: rxylib
 Type: Package
 Version: 0.1.1
 Date: 2017-07-05
 License: GPL-3 | LGPL-2.1 (for the C++ library 'xylib')

Details

Currently the package uses 'xylib' in version 1.6 (unreleased).

Supported data formats

ID	NAME	DESCRIPTION	FILE EXTENSION	VALID_OPTIONS	DATATYPE	BLO
[1,]	cpi	Sietronics Sieray CPI	cpi		ascii	multi
[2,]	uxd	Bruker Diffrac-AT UXD	uxd		ascii	single
[3,]	rigaku_dat	Rigaku DAT	dat		ascii	single
[4,]	bruker_raw	Siemens/Bruker RAW	raw		binary	single
[5,]	bruker_spc	Bruker ESP300-E SPC	spc		binary	multi
[6,]	vamas	VAMAS ISO-14976	vms		ascii	single
[7,]	philips_udf	Philips UDF	udf		ascii	multi
[8,]	spe	PI WinSpec SPE	spe		binary	single
[9,]	pdCIF	Powder Diffraction CIF	cif		ascii	single
[10,]	philips_rd	Philips PC-APD RD/SD	rd sd		binary	multi
[11,]	xrdml	PANalytical XRDML	xrdml		ascii	single
[12,]	canberra_mca	Canberra MCA	mca dat		binary	multi
[13,]	canberra_cnf	Canberra CNF	cnf		binary	multi
[14,]	xfit_xdd	XFIT XDD	xdd		ascii	multi
[15,]	riet7	RIET7/LHPM/PSI_DMC	dat		ascii	multi
[16,]	dbws	DBWS data	dbw rit neu		ascii	multi
[17,]	chiplot	ChiPLOT data	chi		ascii	multi
[18,]	spectra	Spectra / VGX 900	1 2 3 4 5 6 7 8 9		ascii	single
[19,]	specsxy	SPECS SpecsLab2 xy	xy		ascii	single
[20,]	csv	CSV or TSV	csv tsv tab	decimal-comma	ascii	multi

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, Universite Bordeaux Montaigne (France), RLum Team (family support), Marcin Wojdyr (maintainer and author of the C++ library 'xylib'), Peng Zhang (author of the C++ library 'xylib')

read_xyData*Import xy-Data for Supported Formats into R*

Description

The function provides access to the underlying `xylib` to import data for supported file formats into R. In most cases, only the file path is needed with further arguments to import the data. The function automatically recognises allowed formats. See [rxylib-package](#) for supported formats.

Usage

```
read_xyData(file, options = "", verbose = TRUE)
```

Arguments

file	character (required): path and file to be imported. The argument accepts an URL.
options	character (with default): set format options (see rxylib-package)
verbose	logical (<i>with default</i>): enables/disables verbose mode

Value

The functions returns a [list](#) of matrices.

Function version

0.1.0

Author(s)

Sebastian Kreutzer, IRAMAT-CRP2A, Universite Bordeaux Montaigne (France)

Examples

```
##load example dataset
file <- system.file("extdata/ExampleSpectrum.CNF", package = "rxylib")
results <- read_xyData(file)

##plot spectrum
plot(results[[1]],
      type = "l",
      log = "y",
      xlab = "Energy [keV]",
      ylab = "Counts",
      main = "Thorite - 1800 s")

mtext(side = 3, "Canberra Inspector 1000, 3 x 3 NaI probe")
```

Index

*Topic **IO**

read_xyData, [3](#)

*Topic **package**

rxylib-package, [2](#)

character, [3](#)

list, [3](#)

logical, [3](#)

read_xyData, [3](#)

rxylib (rxylib-package), [2](#)

rxylib-package, [2](#), [3](#)