BERT-Based Word Embeddings for Within-Project Software Story Point Estimation

Project Statement 1 (PS-1) | Natural Language Processing

Group: Group 2
Members: Aditya Sunil Menon, Athul Anil Kumar, Johan John Koshy, Kiran Nambiar, Mohammed Omar
GitHub repository: https://github.com/R2D2-08/nlptawos
Project data: DM (TAWOS v1.1)

Abstract

In this project we evaluated contextual BERT token representations for predicting software story points using a random within-project split on the DM project. What we experimented on reserved 2813 of 14061 eligible issues for final testing and ran five-fold cross-validation on the development set. The token embeddings were produced by a frozen pretrained BERT encoder for a three-layer convolutional regression head. The final chosen CNN obtained held-out MAE 3.9559 and MdAE 1.1618. The constant-median baseline yielded MAE 5.1337 and MdAE 1.3000. Detailed validation and test results are presented separately.

1. The problem at hand

How effectively do BERT-based contextual token embeddings predict story point values from the title and description of an issue, when training and testing use distinct issues from the same project under a random split? This is an example of supervised numerical regression.

2. Methodology, Data collection and preprocessing

Dataset: Tawosi et al., TAWOS v1.1 (DOI 10.5522/04/21308124). The official database is MySQL; the extractor joins Issue and Project, using Title and Description_Text as input and Story_Point as the target. Issues explicitly changed after estimation, empty texts, invalid labels, and repeated exact descriptions are filtered. Unknown change flags remain a potential limitation.

Audit stage	Count
Source issues with project key	20065
Positive numeric labels	20065
After explicit edit filtering	14365
Final distinct cleaned issues	14061
Development data (80%)	11248
Final held-out test (20%)	2813

3. Architecture

Pretrained google-bert/bert-base-uncased, frozen and used for contextual token features. Text is tokenized with padding/truncation at 64 tokens. The token features feed Conv1d layers with [128, 64, 32] output channels, kernel size 3, ReLU and masked mean pooling; a dense head predicts story points. Fixed-epoch training uses SmoothL1 loss, AdamW learning rate 0.0007, weight decay 0.01, batch size 32, epochs 12, seed 42.

4. Validation protocol and selection

The final test set is isolated before model development. Five folds of the 80% development set each take a turn as validation data. CNN dropout candidates are chosen by lowest mean validation MAE, with mean MdAE as tie-breaker. The chosen CNN is refitted on all development examples and evaluated once on the untouched held-out test. Baselines are constant training median and Ridge regression on average BERT token features.

5. Five-fold validation results

Model	MAE mean +/- SD	MdAE mean +/- SD
cnn_dropout_0.2	3.9274 +/- 0.1804	1.2608 +/- 0.0188
cnn_dropout_0.4	3.9173 +/- 0.1534	1.1992 +/- 0.0425
dummy_median	4.9608 +/- 0.2071	1.5000 +/- 0.0000
ridge_bert_mean	5.5256 +/- 0.1093	3.1252 +/- 0.1052

The selected CNN setting based on development cross-validation was `cnn_dropout_0.4`. Individual fold observations are saved in `five_fold_results.csv`.


6. Final held-out test results (obtained by separate evaluation)

Model	MAE	MdAE
cnn_dropout_0.4	3.9559	1.1618
ridge_bert_mean	5.4835	3.0918
dummy_median	5.1337	1.3000


7. Findings

The selected CNN MAE (3.9559) is lower than the constant-median baseline MAE (5.1337). The BERT-mean Ridge comparison has held-out MAE 5.4835.


Five-fold validation MAE




Five-fold validation MdAE




Actual versus predicted story points



Held-out absolute errors



Final CNN training loss



8. Limitations and threats to validity

- Within-project estimates may not transfer to other projects with different jargon and story point scales.
- Story points are subjective and noisy.
- Frozen BERT is not software-domain fine-tuned, and token truncation may omit important issue details.

9. Conclusion

In this observed within-project experiment, cnn_dropout_0.4 obtained a held-out MAE of 3.9559 and MdAE of 1.1618 on 2813 test examples.

References

- Tawosi et al. (2022), A Versatile Dataset of Agile Open Source Software Projects, DOI 10.1145/3524842.3528029.
- TAWOS dataset: https://doi.org/10.5522/04/21308124
- Devlin et al. (2019), BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding, arXiv:1810.04805.
- Implementation and full replication commands: https://github.com/R2D2-08/nlptawos