RAW CSV DATA (Columns are comma seperated data fields)

ScaleFactor	604.71						9.98E-04						5.96E-03						0.23				
Offset+FO	0.193502						0.1916692						0.047845						0				
Units	Einsteins/m²/s						µEinsteins/m²/s						meters						v.				
Immersion	n/a						0.5664						n/a						n/a				
Cal Date	1/1/2022						1/7/2022						1/7/2022						1/7/2022				
Tag Address	2						a						a						a				
Time	QSR - S/N 10367	Minimum	Maximum	StDev	Integral	#Averaged	EoZPAR	Minimum	Maximum	StDev	Integral	#Averaged	Depth	Minimum	Maximum	StDev	Integral	#Averaged	Vin_a	Minimum	Maximum	StDev	Integral	#Averaged

FORMATTED AND DECODED DATA

	QSR Surface PAR Parameters and Data						BIS Profiler PAR Parameters and Data						BIS Profiler Depth Parameters and Data						BIS Profiler Voltage Parameters and Data					
ScaleFactor	604.71						9.98E-04						5.96E-03						0.23					
Offset+FO	0.193502						0.1916692						0.047845						0					
Units	Einsteins/m²/s						µEinsteins/m²/s						meters						volts					
Immersion	n/a						0.5664						n/a						n/a					
Cal Date	1/1/2022						1/7/2022						1/7/2022						1/7/2022					
Tag Address	2						a						a						a					
Time	Raw PAR	Minimum	Maximum	StDev	Integral	#Averaged	Raw PAR	Minimum	Maximum	StDev	Integral	#Averaged	Depth	Minimum	Maximum	StDev	Integral	#Averaged	Voltage	Minimum	Maximum	StDev	Integral	#Averaged

Notes:

Parameters apply to all columns below them. In the original csv headers, this looks like the parameters appearing in the same column as the raw value for each data type and all other fields appearing empty.

Data with a tag address of "a" comes from the submersible BIS probe (unless otherwise noted in the header).

Data with a tag address of "2" comes from the surface QSR probe (unless otherwise noted in the header).

All values in a row correspond to the time listed in the first column, regardless of device or data type.

Not all devices or data types may be present in a given file.