AI SALES AGENT

Submission guide

Project overview, deliverable index, folder structure, and the assumptions and gaps in this submission.

Phase 1 MVP · 21 October 2026 · Prepared from the canonical documents in docs/

Product

AI Sales Agent is an AI sales employee and a human sales desk for small merchants who sell through Instagram and Facebook messages, starting in Tunisia. The merchant connects a channel, imports a variant-level catalog, and records delivery, payment, and return rules. The agent answers from those records, in Tunisian Arabic, French, and Arabic, including code-switching. When a shopper is ready to buy, the agent reserves stock, creates a pending order, and stops. A person confirms payment and delivery. The product does not take payment in this phase, and it is not a storefront or a CRM.

The operator surface is a sales command center. It answers who is talking, how likely they are to buy, and what to do next. It does not ask the merchant to read every AI conversation.

Deliverables

Document	What it contains
README.pdf	This index, the folder map, and the assumptions a reader must not miss.
requirements/functional-requirements.pdf	The Phase 1 functional register, with the original identifiers, priorities, and verification methods.
requirements/non-functional-requirements.pdf	Quality attributes and measurable targets, separated from open assumptions.
requirements/user-stories.pdf	Stories and Given/When/Then acceptance criteria for the principal actors.
diagrams/use-case-diagram.pdf	Preparation, the sales loop, and oversight.
diagrams/class-diagram.pdf	Identity, catalog, conversations, and orders. Each group is on its own page so the attributes stay readable.
diagrams/sequence-diagrams.pdf	Inbound reply, purchase handoff, takeover and confirmation, and channel connection.
diagrams/activity-diagrams.pdf	Activation gates, accepting a webhook, the model decision, and purchase collection.
diagrams/component-diagram.pdf	The modular monolith and its allowed dependencies.
diagrams/deployment-diagram.pdf	The AWS runtime for one environment.
diagrams/additional-diagrams.pdf	The conversation state machine and the module package diagram.
architecture/architecture-overview.pdf	Style, modules, tenancy, and the decisions that constrain the design.
architecture/deployment-architecture.pdf	Nodes, paths, secrets, environments, and what is explicitly deferred.

Folder structure

```
submission/
├── README.pdf
├── requirements/
│   ├── functional-requirements.pdf
│   ├── non-functional-requirements.pdf
```

```
│   └── user-stories.pdf
├── diagrams/
│   ├── use-case-diagram.pdf
│   ├── class-diagram.pdf
│   ├── sequence-diagrams.pdf
│   ├── activity-diagrams.pdf
│   ├── component-diagram.pdf
│   ├── deployment-diagram.pdf
│   └── additional-diagrams.pdf
├── architecture/
│   ├── architecture-overview.pdf
│   └── deployment-architecture.pdf
└── sources/
    └── diagram-source-files/
        └── *.puml
```

How the documents relate

Actors are the visitor, owner, admin, employee, end customer, the AI agent, Meta, and the internal platform operator. The same names are used on the use-case diagrams and in the stories. Conversation statuses on the state diagram are the statuses in the class diagram and in the sequences. Orders created by the agent are pending, with payment not completed, until a person confirms them.

The requirements register is the complete behaviour list. The diagrams show the principal flows. A use case such as "manage products and variants" groups several requirements rather than drawing one oval per identifier.

Assumptions and limitations

- The ubiquitous-language file and the reference-screen file in the documentation set are empty. Class names and attributes are taken from the database design, not from that empty file. The class diagrams omit columns that are not needed to explain the model.
- The apex domain is not chosen (OQ-49). Host roles are app, api, and hooks.
- SaaS billing currency is not finally chosen (OQ-02). Catalog currency is TND and the interface shows DT.
- Targeted erasure of a customer is required. An automatic retention purge is not specified for the MVP.
- Field-level encryption of customer fields is a recorded shortcut. At-rest encryption and Secrets Manager are the MVP controls.
- Row-level security is intentionally off. Tenant isolation is an application rule.
- WhatsApp appears in the channel enumeration and is not connectable. The adapter is a stub.
- Available stock subtracts active reservations only. A reservation is committed when the pending order is created. A full inventory ledger is Should. No extra stock rule was added for this submission.
- Public task addresses, a single RDS instance, and a desired count of one are the approved MVP deployment, not an oversight. Private networking and multi-AZ database are documented as later work.
- Phase 2 and later (catalog sync, WhatsApp, payment links, advanced analytics) are out of these diagrams except where a stub or a flag is already part of the MVP shape.

Source of truth

Behaviour comes from the numbered product and engineering specifications under docs/. The founder brain dump remains the highest product authority where those specifications point to it. This submission does not modify those documents. Editable diagram sources are PlantUML files beside this PDF.