Parameter	Share object node	Parameter content
sdmx_data_query	source	complete SDMX URL, e.g.
		"KEI/PRINTO01+PRMNTO01.AUS+AUT+BEL+CAN+CHL+CZE+DNK+EST+FIN+FRA.GP.A/all?startTime=2015&endTime=2015"; mandatory
data_api_endpoint	source	SDMX API URL, e.g. http://stats.oecd.org:80/SDMX-JSON/data; mandatory
title	title	character string main title of chart; optional (null or character string)
subtitle	subtitle	character vector chart subtitle; optional (null or vector of character strings)
unit		character string to specify unit of measure (should be automatic) → to be removed – will be generated automatically
source_url	source	character string to add URL below chart; optional (null or character string with valid URL)
source_label	sourceLabel	character string to show instead of URL below chart; optional (null or character string)
logo	logo	logical include logo; optional (null or "https://upload.wikimedia.org/wikipedia/sco/0/0d/OECD_logo_new.svg" – a system-configurable link)
owner	owner	logical include copyright information; optional ("owner": null or "©OECD"; "terms"-"label": null or "Terms & Conditions"; "terms"-"link": null or
		"https://www.oecd.org/termsandconditions/")
type	type	one of BarChart, RowChart, ScatterChart, Horizontal SymbolChart, Vertical SymbolChart, TimelineChart, StackedBarChart; mandatory
width	width	integer chart width in pixel; optional (null or integer number)
height	height	integer chart height in pixel; optional (null or integer number)
path	-	path to a JSON template that can be read using jsonlite::fromJSON — a system-configurable link)
x_axis	х	optional array of float numbers:
		Only for RowChart, ScatterChart, HorizontalSymbolChart: min, max, step, pivot
		Only for TimelineChart: step
<mark>y_axis</mark>	У	optional array of float numbers:
		Only for BarChart, ScatterChart, VerticalSymbolChart, TimelineChart: min, max, step, pivot
		Only for StackedBarChart: min, max, step
chart_dimension	chartDimension	optional array of character strings:
		Only for ScatterChart: list of SDMX IDs for one dimension ("id") and two of its values ("xId" and "yID")
		Only for HorizontalSymbolChart, VerticalSymbolChart: SDMX ID for one dimension ("id")
		Only for StackedBarChart: SDMX ID for one dimension ("id") and mode ("value" or "percent")
highlights	highlight	optional array of character strings:
		Only for BarChart, RowChart, HorizontalSymbolChart, VerticalSymbolChart, TimelineChart, StackedBarChart: list of concatenated SDMX IDs
		(separated by " - ") of values of all involved dimensions, e.g. "SUBJECT_X - COUNTRY_Y"; note that StackedBarChart always involves only 1
		dimension, e.g. "SUBJECT_X" Only for ScatterChart: list of pairs of SDMX IDs for dimension ("dimensionId") and its value ("dimensionValueId")
baseline	baseline	optional (same as highlights) array of character strings:
baseline	baseline	Only for BarChart, RowChart, HorizontalSymbolChart, VerticalSymbolChart, TimelineChart, StackedBarChart: Concatenated SDMX IDs
		(separated by " - ") of values of all involved dimensions, e.g. "SUBJECT_X - COUNTRY_Y"; note that StackedBarChart always involves only 1
		dimension, e.g. "SUBJECT_X"
		Only for ScatterChart: Pair of SDMX IDs for dimension ("dimensionId") and its value ("dimensionValueId")
display	display	optional one of the options "label" (default), "code" or "both"
language	Accept-Language	Character string with ISO language identifier, e.g. "en" or "fr"; mandatory
inipane.	/ tecept Language	Sharacter string with 100 language lateritiner, e.g. cir of 11 , manaatory

- Chart Generator: <a href="http://vs-dotstattest.main.oecd.org/FrontEndDemo/sandbox/chart-generator/#/">http://vs-dotstattest.main.oecd.org/FrontEndDemo/sandbox/chart-generator/#/</a>
- Viewer: <a href="http://vs-dotstattest.main.oecd.org/FrontEndDemo/sandbox/data-viewer/?id=4deA">http://vs-dotstattest.main.oecd.org/FrontEndDemo/sandbox/data-viewer/?id=4deA</a>
- Share service: <a href="http://dotstatcor-dev2.main.oecd.org/PMShareIntranetService">http://dotstatcor-dev2.main.oecd.org/PMShareIntranetService</a>