

# Get OAuth Token

## Remarks

**Interface Functionality:**  
This interface is used to obtain a new access token by providing a refresh token without requiring the user to reauthorize. The design of this interface aims to extend the validity of a user session, avoiding frequent logins, thereby enhancing user experience while ensuring system security.

**Applicable Scenarios:**  
When the user's access token is about to expire and the user session needs to be maintained, this interface can be called to obtain a new access token without requiring the user to log in or reauthorize again. It is commonly used in applications or services that require long-term user login sessions.

**Restrictions and Considerations:**  
**Request Parameters:** The following parameters must be provided for this interface:  
grant\_type: Fixed value is refresh\_token, used to indicate that this operation is a token refresh.  
refresh\_token: The refresh token obtained in the last session, used to verify the user's identity and generate a new access token.  
**Security:** As the refresh token usually has a longer validity period, ensuring the confidentiality of the refresh token is crucial. It is recommended to use the refresh token only in a secure network environment.  
**Validity Management:** The new access token and refresh token will be returned together, and developers should properly manage the validity of the new tokens and refresh them in advance according to system requirements.  
**Rate Limiting:** Ensure that the frequency of interface calls is controlled properly to avoid triggering rate-limiting mechanisms due to frequent refresh operations.  
**Exception Handling:** If the refresh token becomes invalid or is revoked, the interface will return an appropriate error message, and the client should guide the user to log in and authorize again.

## Interface Description

| URL                           | Request Method |
|-------------------------------|----------------|
| /gas/api/v1alpha1/oauth/token | POST           |

Headers

| Name         | Parameter Value  | Required | Example | Remarks |
|--------------|------------------|----------|---------|---------|
| Content-Type | application/json | Yes      |         |         |

Body

| Name          | Type   | Required | Remarks                                                                 |
|---------------|--------|----------|-------------------------------------------------------------------------|
| grant_type    | string |          | Fill in "refresh_token"                                                 |
| refresh_token | string |          | The value of the refresh_token returned by the GetOAuthToken interface. |

Response Data

| Name          | Type   | Remarks                                                                                                                                                                                                                                |
|---------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| token_type    | string | Token Type                                                                                                                                                                                                                             |
| access_token  | string | Access Token, used for security authentication when calling openapi interfaces. It is placed in the Authorization of the request header.                                                                                               |
| refresh_token | string | Refresh Token, used in conjunction with the access_token. When the access_token expires, the refresh_token enables an application to request a new access_token without requiring the user to go through the full login process again. |
| expires_in    | null   | Expiration time, UTC timestamp, unit: milliseconds                                                                                                                                                                                     |

Reqeust

```
curl --location 'https://openapi.gs-robot.com/gas/api/v1alpha1/oauth/token'
```

```
--header 'Content-Type: application/json'
--data '{
  "grant_type": "refresh_token",
  "refresh_token": "{{refresh_token}}"
}'
```

#### Response

```
{
  "token_type": "bearer",
  "access_token": "{{token}}",
  "expires_in": 1726127118711,
  "refresh_token": "{{refresh_token}}"
}
```