

```
mysql> use nit;
```

```
Database changed
```

```
mysql> select * from student;
```

name	id	address	marks
Kalyan	12	NLR	78
Babu	13	BNG	70
cathy	17	delhi	90
alex	45	chennai	79
dolly	48	pune	67
chancy	78	mumbai	34

```
6 rows in set (0.00 sec)
```

```
mysql> alter table student add PhoneNo int;
```

```
Query OK, 0 rows affected (0.15 sec)
```

```
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> update student set PhoneNo=132;
```

```
Query OK, 6 rows affected (0.03 sec)
```

```
Rows matched: 6 Changed: 6 Warnings: 0
```

```
mysql> update student set phoneNo=456 where id=12;
```

```
Query OK, 1 row affected (0.01 sec)
```

```
Rows matched: 1 Changed: 1 Warnings: 0
```

```
mysql> desc student;
```

Field	Type	Null	Key	Default	Extra
name	varchar(30)	YES		NULL	
id	int	NO	PRI	NULL	
address	varchar(50)	YES		NULL	
marks	int	YES		NULL	
PhoneNo	int	YES		NULL	

```
5 rows in set (0.01 sec)
```

```
mysql> alter table student modify column name varchar(60);
```

```
Query OK, 0 rows affected (0.03 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> alter table student drop column PhoneNo;
Query OK, 0 rows affected (0.04 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc student;
```

Field	Type	Null	Key	Default	Extra
name	varchar(60)	YES		NULL	
id	int	NO	PRI	NULL	
address	varchar(50)	YES		NULL	
marks	int	YES		NULL	

```
4 rows in set (0.01 sec)
```

```
mysql> delete from student where name='chancy';
Query OK, 1 row affected (0.01 sec)
```

```
mysql> select sum(marks) from student;
```

sum(marks)
384

```
1 row in set (0.01 sec)
```

```
mysql> select avg(marks) from student;
```

avg(marks)
76.8000

```
1 row in set (0.00 sec)
```

```
mysql> select count(name) from student;
```

```

+-----+
| count(name) |
+-----+
|          5 |
+-----+

```

1 row in set (0.00 sec)

```
mysql> select max(marks) from student;
```

```

+-----+
| max(marks) |
+-----+
|          90 |
+-----+

```

1 row in set (0.01 sec)

```
mysql> select min(marks) from student;
```

```

+-----+
| min(marks) |
+-----+
|          67 |
+-----+

```

1 row in set (0.00 sec)

```
mysql> select * from student order by marks;
```

```

+-----+-----+-----+-----+
| name   | id   | address | marks |
+-----+-----+-----+-----+
| dolly  | 48   | pune    | 67    |
| Babu   | 13   | BNG     | 70    |
| Kalyan | 12   | NLR     | 78    |
| alex   | 45   | chennai | 79    |
| cathy  | 17   | delhi   | 90    |
+-----+-----+-----+-----+

```

5 rows in set (0.00 sec)

```
mysql> select * from student order by marks desc;
```

name	id	address	marks
cathy	17	delhi	90
alex	45	chennai	79
Kalyan	12	NLR	78
Babu	13	BNG	70
dolly	48	pune	67

5 rows in set (0.00 sec)

```
mysql> select * from student where name like 's%';
Empty set (0.01 sec)
```

```
mysql> select * from student where name like 'h%';
Empty set (0.00 sec)
```

```
mysql> select * from student where name like '%h';
Empty set (0.00 sec)
```

```
mysql> select * from student where name like '%Kalyan%';
```

name	id	address	marks
Kalyan	12	NLR	78

1 row in set (0.00 sec)

```
mysql> select * from student where name like '%kalyan%';
```

name	id	address	marks
Kalyan	12	NLR	78

1 row in set (0.00 sec)

```
mysql> select * from student where name like '_a%';
```

name	id	address	marks
Kalyan	12	NLR	78
Babu	13	BNG	70
cathy	17	delhi	90

3 rows in set (0.00 sec)

```
mysql> select * from student where name like '%s_';
Empty set (0.00 sec)
```

```
mysql> select * from student where name like '%d_';
Empty set (0.00 sec)
```

```
mysql> select * from student where name like '%_d';
Empty set (0.00 sec)
```

```
mysql> select * from student where name like '_d%';
Empty set (0.00 sec)
```

```
mysql> select * from student where name like '%d_';
Empty set (0.00 sec)
```

```
mysql> select * from student where name like 'd_%';
```

name	id	address	marks
dolly	48	pune	67

1 row in set (0.00 sec)

```
mysql> |
```