

Ex. No.: 7

Date: 26/3/25

### IPC USING SHARED MEMORY

Aim:

To write a C program to do Inter Process Communication (IPC) using shared memory between sender process and receiver process.

Algorithm:

#### sender

1. Set the size of the shared memory segment
2. Allocate the shared memory segment using shmget
3. Attach the shared memory segment using shmat
4. Write a string to the shared memory segment using sprintf
5. Set delay using sleep
6. Detach shared memory segment using shmdt

#### receiver

1. Set the size of the shared memory segment
2. Allocate the shared memory segment using shmget
3. Attach the shared memory segment using shmat
4. Print the shared memory contents sent by the sender process.
5. Detach shared memory segment using shmdt

Program Code:

#### sender.c

```
#include <stdio.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <unistd.h>

int main ()
{
    int n = 1024;
    key_t key = ftok ("shmfile", 65);
```

```
int shmid = shmget (key, size, 0666 | IPC_CREAT);  
char* shared_memory = (char*) shmat (shmid, NULL, 0);  
sprintf (shared_memory, "Hello from the sender process!");  
printf ("Sender : Message written to shared memory  
: %s\n", shared_memory);  
  
sleep(5);  
shmdt (shared_memory);  
return 0;
```

3

receiver.c

```
# include <stdio.h>
```

```
# include <sys/ipc.h>
```

```
# include <sys/shm.h>
```

```
int main()
```

```
{
```

```
    int n = 1024;
```

```
    key_t key = ftok("shmfile", 65);
```

```
    int shmid = shmget(key, size, 0666/IPC_CREAT);
```

```
    char * shared_memory = (char *) shmat(shmid, NULL, 0);
```

```
    printf("Receiver: Message read from shared memory  
           : %s\n", shared_memory);
```

```
    shmat(shared_memory);
```

```
    shmctl(shmid, IPC_RMID, NULL)
```

```
    return 0;
```

```
}
```

### Sample Output

#### **Terminal 1**

```
[root@localhost student]# gcc sender.c -o sender  
[root@localhost student]# ./sender
```

#### **Terminal 2**

```
[root@localhost student]# gcc receiver.c -o receiver  
[root@localhost student]# ./receiver  
Message Received: Welcome to Shared Memory  
[root@localhost student]#
```

### OUTPUT

Sender: Message written to shared memory: Hello from the  
Sender process!

Receiver: Message read from shared memory:  
Hello from the sender process!

#### **Result:**

Hence the code for IPC using shared  
memory has been executed successfully.

