PRODUCT GUIDE / VERSION 1.0

SponsorProof from setup to report

A practical guide to finding Twitch channels, measuring a live sponsor segment, reviewing the evidence, and helping creators and small businesses start a sponsorship conversation.

01	02	03	04
Connect Twitch	Choose a channel	Record the segment	Review the report

ALSO INCLUDED

A local sponsorship helper for creator profiles, real business opportunities, transparent matching, editable pitches, and email drafts.

The guide describes current project behavior. Twitch measurements use real samples after tracking starts; offline or historical counts are not invented or backfilled.

1. What SponsorProof does

Two workflows share one workspace. The Twitch measurement workflow needs API credentials; the sponsorship helper does not.

Area	Purpose	Output
Live monitor	Mark the beginning and end of a placement on a tracked live channel.	Segment record tied to viewer samples.
Analytics	Inspect measured retention, recovery and sample counts.	Context around the sample windows.
Streamer roster	Search Twitch or add a login; review live/offline state.	Channels sampled by this workspace.
Reports	Review, delete or print/save a segment as PDF.	A shareable report of captured samples.
Sponsorship helper	Creators describe offers; businesses post real briefs.	Sorted potential fits and editable outreach.
OBS overlay	Preview an information card.	Local preview only; not a hosted browser source.

Campaign flow

Find Browse Twitch	**Track** Keep app running	**Mark** Start and end	**Review** Analytics and report

Measurements are descriptive
Viewer changes do not prove that a sponsor caused them. The helper score sorts user-provided information; it does not verify profiles, audience numbers, or business offers.

- For local use, the web app and API both run from the project folder.
- Twitch Client ID and Secret are required for channel search, live status, and sampling.
- The sponsorship helper is stored locally unless you deploy the password-protected preview.

2. Set up the local app

One-time setup on the computer that will collect viewer samples. Keep its terminal open during a campaign.

Requirements

- Windows PowerShell and Node.js 22.13 or later.
- A Twitch Developer Application with its Client ID and Client Secret.
- Internet access to request Twitch API data.

A. Open the project folder

Run commands from the folder containing package.json. Do not start in C:\Windows\System32 and do not double-click index.html.

```
cd "C:\Users\Rakshithn\Documents\Codex\2026-11-03\c\outputs\SponsorProof"
Copy-Item backend\.env.example backend\.env
notepad backend\.env
```

B. Set Twitch credentials

In backend/.env, paste values after the equals signs. The Client Secret is private. This file is ignored by Git.

```
PORT=5000
TWITCH_CLIENT_ID=your_client_id
TWITCH_CLIENT_SECRET=your_client_secret
```

This project uses Twitch app access with Client Credentials. You do not need to log in as a broadcaster. It does not request chat access.

C. Install and launch

```
npm install
npm install --prefix backend
npm run dev
```

Open the exact local URL Vite prints, often http://localhost:5173. If busy, it may print 5174 or another port. Leave this PowerShell window open; press Ctrl+C there to stop both services.

Setup check
The sidebar should say Twitch API ready. If it says not configured, verify both environment values and restart npm run dev.

3. Find and select a streamer

Browse Twitch is available in Campaign Setup, Live Monitor, and Streamer Roster.

Step	What happens
Open Browse Twitch	Search dialog opens. Enter at least two characters.
Search	Real Twitch channel results appear. Optional filter: live channels only.
Review	See channel name, login, available category, and live/offline status.
Select	Channel is added to the roster and the page refreshes its data. Campaign Setup also fills the channel field.

Search coverage
Twitch returns channels with streamed content in the past six months. SponsorProof shows up to 20 matches per query. Try a more specific name if needed.

Expected results after selection

- Streamer Roster: row with display name, login, status, and viewers if live.
- Live Monitor: channel appears in the selector; banner and viewer field show current status.
- Campaign Setup: channel is added. Enter a sponsor and choose Prepare campaign.

Offline is a real result
Offline channels have no current viewer count. SponsorProof does not invent counts or retrieve history. The server checks status about every 30 seconds.

Manual entry

In Streamer Roster, enter a Twitch login (the part after twitch.tv/) and select Add streamer. Both manual entry and Browse Twitch resolve the real channel through Twitch.

4. Record a sponsor segment

The monitor ties a real placement window to one tracked Twitch channel. Be ready to mark the actual start and end.

Before the placement

- Add the channel as early as possible and keep SponsorProof running.
- Wait at least five minutes for a complete pre-segment baseline.
- Confirm the right streamer is selected and the status is LIVE.
- Enter the sponsor name. Start is disabled if the channel is offline or required fields are missing.

During and after

Moment	Action	Reason
Before	Track for at least five minutes.	Builds the baseline window.
Start	Select Start sponsor segment at the real placement start.	Saves the timestamp and begins the active window.
End	Select End segment when the placement finishes.	Saves the end timestamp.
After	Keep the app running for five more minutes.	Collects the recovery window.

Collection behavior

- The interface refreshes live status every 30 seconds.
- The backend polls tracked channels every 30 seconds while running.
- Only public viewer counts are sampled. Chat content and private analytics are not collected.

One active segment per streamer
The app prevents a second active sponsor segment for the same channel. Multiple channels and completed segments are supported.

5. Understand the measurements

Values use samples SponsorProof saved. They describe measured audience changes, not proof that the sponsor caused them.

Metric/window	Calculation	Minimum data
Baseline	Median count in five minutes before start.	3 samples
Active average	Average count while segment is active.	3 samples
Post average	Average count in five minutes after end.	3 samples
Retention	Active average / baseline x 100; capped at 100%.	Baseline + active
Recovery	Post average / baseline x 100.	Baseline + post

Illustrative math only

If a hypothetical campaign had a pre-segment median of 400 and an active average of 320, retention would be 320 / 400 x 100 = 80%. These are made-up numbers to explain the formula, not SponsorProof data.

Why a metric may be unavailable

- The channel was added too late, leaving fewer than three baseline samples.
- The app or backend stopped, the channel went offline, or Twitch data was unavailable.
- The five-minute post window is still being collected.
- A baseline of zero cannot be used as a denominator.

Interpret carefully
Viewer counts change for many reasons. Retention and recovery do not identify who noticed the sponsor or establish causation.

6. Review, export, and manage reports

Analytics helps inspect sample coverage. Reports provides a print-friendly segment summary.

Analytics

- Select a segment to see retention, recovery status, sample counts, and the viewer chart.
- Use pre, active, and post sample counts to judge whether results have enough data.
- Read the methodology note before interpreting the metric.

Reports

- Choose a sponsor segment from the selector.
- Review channel, brand, date, metrics, chart, and method notes.
- Choose Print / save PDF, then Save as PDF in the browser print dialog.
- Choose Delete segment only when intended; confirm the browser prompt.

What delete means
Deleting removes that segment from Analytics and Reports. It also stops an active segment. Viewer samples belong to the channel and remain for other records.

OBS overlay

The OBS Overlay page is a local preview card. It is not a hosted browser-source URL that OBS can load from another device.

Timing reference

Window	Target
Baseline	5 minutes before segment start
Active	From Start to End
Recovery	5 minutes after segment end
Sampling	About every 30 seconds while backend runs

7. Help creators and businesses connect

Sponsorship helper works without Twitch credentials and starts empty. Use real information and review each match.

Creator profile

Field	Use
Name, platform, handle	Identify creator and channel.
Category and audience	Matching inputs. Audience is self-reported.
Starting rate	Compared with opportunity budget; INR.
Description and contact	Used to prepare a pitch and email draft.

Business opportunity

Add real business name, contact email, campaign title, category, platforms, audience range, budget, and brief. Do not post confidential information in this local prototype.

Transparent fit score

Rule	Points
Platform match	30
Category match	30
Audience inside requested range	25
Budget covers creator starting rate	15
Maximum	100

Potential partnerships sort by this score and show reasons. It is a sorting aid, not a guarantee or independent verification.

Pitch and email

- Create creator pitch opens an editable draft based on profile and opportunity.
- Copy the pitch or open a prefilled email in your mail app.
- SponsorProof does not send email automatically. Review and send it yourself.

Local data only
Profiles and briefs are stored in the local SQLite database. The project does not currently provide individual accounts, profile ownership, or private online listings.

8. Data, privacy, and limits

Know what is stored before using the app with creators, brands, or agencies.

Stored locally

- Twitch IDs, logins, display names, image URLs, and added timestamps.
- Viewer samples with timestamps, counts, channel IDs, and stream IDs.
- Sponsor, channel, start/end times, status, and calculated window summaries.
- Creator profiles, business opportunity details, and contact email addresses.

Not collected or verified

- No Twitch chat messages, private analytics, or retroactive viewer history.
- No proof sponsor was spoken or shown, or verification of campaign delivery.
- No verification of audience sizes, rates, briefs, or email addresses.
- No automatic email sending, payment, contracts, or negotiation.

Database and backups

By default, data is stored in backend/sponsorproof-agency.sqlite. Back up this file to preserve local records. Do not delete it unless you intend to remove records. SQLite databases, WAL files, backend/.env, node_modules, and dist are excluded from Git.

Before inviting people
There are no personal accounts or record ownership. Render preview uses one shared username and password. Everyone with that password can manage the same workspace. Do not treat it as a public marketplace or store sensitive contact data there.

9. GitHub and optional Render preview

Publishing the project and hosting the app are separate steps. This path creates a controlled online preview.

Push to GitHub

- Create an empty repository. Do not add a database or Twitch secret.
- The local project is on branch main, with a first commit already made.
- Git ignores environment files, SQLite databases, node_modules, and built output.

```
git remote add origin https://github.com/YOUR-NAME/YOUR-REPOSITORY.git
git push -u origin main
```

Replace the example URL. Never put the Client Secret in code, a commit, README, or public issue. GitHub Actions runs a syntax check and production build after pushes.

Deploy the Render preview

Step	Action
Connect	Create a Render Blueprint from GitHub using render.yaml.
Configure	Set APP_USERNAME, APP_PASSWORD, TWITCH_CLIENT_ID and TWITCH_CLIENT_SECRET as secrets.
Review	Template uses a paid service and 1 GB persistent disk. Check current pricing.
Deploy	Render builds the frontend and starts Express. /api/health is its check.
Share	Give Basic Auth credentials only to trusted preview users. Workspace is shared.

Not a public launch
A public marketplace still needs accounts, ownership and privacy rules, moderation, abuse reporting, and contact-data protections.

10. Troubleshooting and quick checks

Use the symptom to find a next step. Restart SponsorProof after changing backend/.env.

Symptom	Check / fix
npm cannot find package.json	Change directory to the SponsorProof project folder.
Blank browser or file:///	Run npm run dev and open the http://localhost URL from Vite. Do not open index.html.
Twitch API not configured	Check backend/.env Client ID and Secret, then restart.
No search results	Enter two or more characters; try a specific name; check credentials/network. Search covers recently active channels.
Selected channel offline	Current viewer counts only exist while live. Wait for the next stream.
No viewer history	History is unavailable. Tracking starts after the channel is added.
Metrics unavailable	Each window needs three samples. Keep backend running through baseline and recovery.
Port 5173 is busy	Open the alternate URL Vite prints, often 5174.

Pre-campaign checklist

- Twitch status is ready and the correct channel is on the roster.
- Channel has been tracked five minutes before the placement.
- Monitor shows LIVE and sponsor name is correct.
- Someone will select Start and End at the placement times.
- Backend will run for the five-minute recovery window.
- Review sample coverage and report before sharing.

Support boundary
Live measurements require network access, valid Twitch app credentials, and a live channel. Offline streams do not provide current viewer data.

Companion materials: README.md, SPONSORPROOF_COMPLETE_GUIDE.md, backend/server.js, src/main.jsx, render.yaml.