

Chapter 2

Algorithm Analysis

**South China University of
Technology**
College of Software Engineering

Huang Min


Chapter 2

Algorithm Analysis

- Definitions of Big-Oh and Other Notations
- Common Functions and Growth Rates
- Simple Model of Computation
- Worst Case vs. Average Case Analysis
- How to Perform Analyses
- Comparative Examples

Algorithm Analysis


- 1. Why do we analyze algorithms?
- Suppose you are given two algorithms A and B for solving a problem.
- The running times $T_A(N)$ and $T_B(N)$ of A and B as a function of input size N are given



Which is better?

Algorithm Analysis

- 1. Why do we analyze algorithms?
 - For large N , the running time of A and B is:





Now which algorithm would you choose?

Algorithm Analysis

- 1. Why do we analyze algorithms?
- 2. How do we measure the efficiency of an algorithm?
 - › A. Measuring its running time on my computer and compare its time to that of another algorithm that has already been analyzed.
 - › B. Count how many instructions it will execute for an arbitrary input data set.

Growth Rate Graph



$$c_1 \log n < c_2 n < c_3 n \log n < c_4 n^2 < c_5 2^n < c_6 n!$$

Exercises

P71-Exercises 2.1

1) $2/N$, 37 , \sqrt{N} , N , $N \log \log N$, $N \lg N$, $N \log(N^2)$,
 $N \log^2 N$, $N^{1.5}$, N^2 , $N^2 \log N$, N^3 , $2^{N/2}$, 2^N .

2) $N \log N$ and $N \log (N^2)$ grow at the same rate

Algorithm Analysis

- Suppose there are n inputs.
- We'd like to find a **time function $T(n)$** that shows how the execution time depends on **n** .

$$T(n) = 3n + 4$$

$$T(n) = 2^n$$

$$T(n) = 2$$

Mathematical Definitions

- **Big-Oh**

$T(N) = O(f(N))$ if there are positive constants c and n_0 such that $T(N) \leq cf(N)$ when $N \geq n_0$.

- **Big-Omega**

$T(N) = \Omega(g(N))$ if there are positive constants c and n_0 such that $T(N) \geq cg(N)$ when $N \geq n_0$.

- **Big-Theta**

$T(N) = \Theta(h(N))$ if and only if $T(N) = O(h(N))$ and $T(N) = \Omega(h(N))$.

- **Little-oh**

$T(N) = o(p(N))$ if, for all positive constants c , there exists an n_0 such that $T(N) < cp(N)$ when $N > n_0$.

“Big-Oh”

$T(N) = O(f(N))$ if there are positive constants c and n_0 such that $T(N) \leq cf(N)$ when $N \geq n_0$.

We say “ $T(N)$ has order $f(N)$.” means “ $f(N)$ is an **upper bound** on $T(N)$ ”

We try to simplify $T(N)$ into one or more **common functions**.

Ex. 1 $T(N) = 3N + 4$

$T(N)$ is linear. Intuitively, $f(N)$ should be N .

More formally,

$$T(N) = 3N + 4 \leq 3N + 4N, \quad N \geq 1$$

$$T(N) \leq 7N, \quad N \geq 1$$

So $T(N)$ is of order N .


“Common Functions to Use”

$O(1)$	constant
$O(\log n)$	log base 2
$O(n)$	linear
$O(n \log n)$	
$O(n^2)$	quadratic
$O(n^3)$	cubic
$O(2^n)$ or $O(e^n)$	exponential
$O(n+m)$	
$O(nm)$	
$O(n^m)$	

Growth Rates

The **growth rate** is the rate at which the cost of the algorithm grows as the input size grows

The idea of the definitions is to establish a relative order among functions.



“simplifying rules”

Rule 1: If $T_1(N) = O(f(N))$ and $T_2(N) = O(g(N))$, then

(a) $T_1(N) + T_2(N) = O(f(N) + g(N))$

(b) $T_1(N) * T_2(N) = O(f(N) * g(N)).$

Suppose we get $T_1(N) = O(f(N))$ and $T_2(N) = O(g(N))$,

$$f(N) = 4N^2 + 6, g(N) = 3N, T(N) = T_1(N) + T_2(N) = ?$$

$$\begin{aligned} T(N) &= T_1(N) + T_2(N) = O(f(N) + g(N)) \\ &= 4N^2 + 3N + 6 \\ &= O(N^2) \end{aligned}$$

intuitively $O(\max(f(N), g(N)))$

“simplifying rules”

Rule 2: If $T(N)$ is a polynomial of degree k , then
$$T(N) = \Theta(N^k).$$

Rule 3: $\log^k N = O(N)$ for any constant k .

Rule 4: If $T(n) = O(g(n))$ and $g(n) = O(h(n))$, then $T(n) = O(h(n))$.
– transitive*

Rule 5: If $T(n) = O(kg(n))$ for any constant $k > 0$, then $T(n) = O(g(n))$. – ignore the constant*.

“Common Functions to Use”

Suppose we get $T(N) = 4N^2 + 3N + 6$.

Is $T(N) = O(N^2)$? Or Is $T(N) = O(N^3)$?

Generally, we look for the **smallest** $f(N)$ that bounds $T(N)$.

We want a common function that is a **least upper bound**.

If $T(N) = c_k N^k + c_{k-1} N^{k-1} + \dots + c_0$.

$T(N) = O(N^k)$.

N^k is the **dominant term**.

Model of Computation

- Simple Model of Computation
 - › instructions are executed sequentially
 - › has the standard repertoire of simple instructions
 - it takes exactly one time unit to do addition, multiplication, comparison, and assignment
 - › assume that the model has fixed-size integers and no fancy operations
 - › assume infinite memory

What to Analyze

- What to Analyze
 - › Running **time** required
 - › Memory or disk **space** required to run the program and store the data structure
- Main factors
 - › the algorithm used
 - › the **input** to the algorithm
 - › **Not include** the programming language, compiler,...

Analyze the **algorithms** rather than the **programs**

How to Analyze

- How to analyze
 - › Asymptotic algorithm analysis
 - Measures the efficiency of an algorithm, as the input size becomes large – **growth rate**.
 - **best-case** often of little interest
 - **average-case** often reflects typical behavior
 - **worst-case** represents a guarantee for performance on any possible input.

Need to know enough about the input data distribution to do average-case analysis

How to Analyze

Given an array containing n integers, suppose the sequential search algorithm is adopted

Q1: The cost of finding the largest value

Always $c*n$

Q2: The cost for finding a particular value K

May be different for different inputs

Best case:

if the first integer is K – examine 1 value

Worst case:

if only the last integer is K – examine n values

Average case:

If the sequential search is performed on different inputs for many times – examine $n/2$ values on average

How to Analyze

Step 1. Counting

$T(N)$

Step 2. Simplifying

$O(f(N))$

```
int sumit( int v[ ], int num) { //Loop
    sum = 0;
    for (i = 0; i < num; i++)
        sum = sum + v[i];
    return sum
}
```

$$\begin{aligned} T(\text{num}) &= c1 + c2 * \text{num} + c3 \\ &= c2 * \text{num} + (c1 + c3) \\ &= O(\text{num}) \end{aligned}$$

throw away leading constants

We say $T(n)$ of the algorithm is in $O(n)$

How to Analyze

// Nested Loops

```
int sum(int n) {  
    int sum = 0;  
    for (i=1; i<=n; i++)  
        for (j=1; j<=n; j++)  
            sum++;  
}
```

$$\begin{aligned} T(n) &= c_1 + c_2 * n^2 \\ &= O(n^2) \end{aligned}$$

We say $T(n)$ of the algorithm is in $O(n^2)$

How to Analyze

```
// compare the cost of the two loop codes  
sum = 0;  
for(k=1; k<=n; k*=2) //do log(n) times  
    for(j=1; j<=n; j++) //do n times  
        sum++;
```

In this double loop, the cost is

$$T(n) = \Theta\left(\sum_{i=1}^{\log n} n\right) = \Theta(n \log n)$$

How to Analyze

```
// compare the cost of the two loop codes  
sum = 0;  
for(k=1; k<=n; k*=2) //do log(n) times  
    for(j=1; j<=k; j++) //do k times  
        sum++;
```

In this double loop, the cost is

$$\Theta\left(\sum_{i=1}^{\log n} 2^i\right) = \Theta(2^{\log n + 1}) = \Theta(n)$$

$$\sum_{i=0}^{\log n} 2^i = 2^{\log n + 1} - 1 = 2n - 1$$

How to Analyze


```
// assume array A contains n values,  
// random takes constant time  $c_1$  and  
// sort takes  $cn \log n$  steps  
for (i=0; i<n; i++) {  
    for (j=0; j<n; j++)  
        A[j] = random(n);  
    sort(A, n);  
}
```

Determine Θ in average case

$$\Theta(n(c_1 n + cn \log n)) = \Theta(n^2 \log n)$$

How to Analyze

```
// assume A[] contains a random permutation
// of the values from 0 to n-1
sum=0;
for(i=0; i<n; i++)
    for(j=0; A[j] !=i; j++)
        sum++;
```



Determine Θ in average case
 $\Theta(n \cdot n/2) = \Theta(n^2)$

How to Analyze

// A simple assignment to an integer variable
`a = b;`

$$T(N) = \Theta(1)$$

How to Analyze

- **While loop** – similar to for loop
- **If-then-else statement** – the greater of the costs for the then and else clauses.
- **Switch statement** – the most expensive branch
- **Subroutine call** – add the cost of subroutine
- **Recursive subroutine** – express the cost by a recurrence relation and then find the closed-form solution.

How to Analyze

```
// Here || is the string concatenation operator
string t (int n){
    if (n == 1) return '(1) ';
    else return '(' || n || t(n - 1) || ' '
}
```

$T(n) = T(n-1) + c$, for $n > 1$, with $T(1) = c_1$

That is ,

$$\mathbf{T(n) = c*(n-1) + c_1 = \Theta(n)}$$

How to Analyze

// Multiple Parameters

// A picture with P pixels; each pixel take one of C color

// values; Sort the colors w.r.t. the number of pixels with

// the color ($\Theta(C \log C)$)

for (i=0; i<C; i++) // Initialize count

count[i] = 0;

for (i=0; i<P; i++) // Look at all pixels

count[value(i)]++; // Increment count

sort(count); // Sort pixel counts

The cost is $\Theta(C) + \Theta(P) + \Theta(C \log C) = \Theta(P + C \log C)$

Can we drop $\Theta(P)$ or $\Theta(C \log C)$?

notes

Best, Worst, Average-Cases

VS.

Upper, Lower Bounds

- U/L bounds refer to the algorithm's growth rate.
- B/W/A cases refer to a certain type of inputs which cause the shortest/average/longest running time among all the inputs in study.
- U/L bounds can be used to describe the running time of an algorithm in its [best, worst, average] case

Notes

- For an algorithm with $T(n) = c_1n^2 + c_2n$ in the average case ($c_1, c_2 > 0$) ,
 - › $c_1n^2 + c_2n \leq (c_1 + c_2)n^2$ for all $n > 1$, $T(n) \leq cn^2$ for $c = c_1 + c_2$ and $n_0 = 1$.
 - › $c_1n^2 + c_2n \geq c_1n^2$ for all $n > 1$, $T(n) \geq c_1n^2$ for $n_0 = 1$.
 - › $T(n)$ is in $\Theta(n^2)$ in the average case
- Reading the value from the first position in an array takes constant time regardless of the size of the array.
 - › $T(n) = c$ for the (best, worst, and average) cases.
 - › Traditionally, we say that the algorithm is in $O(1)$.

第1周SPOC线上学习内容

- 观看SPOC上的课程内容（包括视频及课件, 教材）
复习巩固：

1. Introduction、2. Algorithm Analysis

学习：

3. Lists, Stacks, and Queues