

Welcome to the RoadWatch AI community. By reporting hazards, you directly feed geo-referenced data into our AI detection engine, helping municipal corporations prioritize road repairs. Please follow these guidelines to submit high-accuracy reports safely.

1. CRITICAL SAFETY PROTOCOLS

- **Pedestrian Areas Only**

Always stand on sidewalks, footpaths, or safe verges. NEVER step onto active traffic lanes, highways, or busy expressways to capture photos.

- **The Safe Distance Rule**

Maintain a minimum distance of 5 to 10 meters from the road hazard. Zoom in with your smartphone camera rather than walking closer.

- **No In-Motion Reporting**

If you are driving or riding a motorcycle, pull over safely in a designated parking zone before attempting to log a report. NEVER use the app while driving.

- **High Visibility at Night**

If reporting in low-light conditions, wear bright or reflective clothing. Ensure you are under active streetlights and carry a flashlight.

& EMERGENCY WARNING: For catastrophic events like complete bridge collapse, massive sinkholes blocking multiple lanes, or immediate landslide threats, call local emergency services immediately instead of logging a report.

2. ACCURATE PHOTOGRAPHY PROTOCOL

STEP 1: Capture Context (Wide-Angle)

Take a picture showing the hazard in relation to the lane, traffic, and roadside markers. This helps the AI map coordinates and verify road class.

STEP 2: Capture Severity (Scale Reference)

Take a secondary picture from a 45-degree angle. If safe, place an object (like a water bottle, coin, or notepad) near the edge for visual depth scale.

STEP 3: Maintain Privacy Compliance

To protect privacy, do not take close-up shots of pedestrians, vehicle license plates, or house addresses. The AI filters these automatically, but avoiding them helps speed up verification.

3. CLASSIFICATION CHEAT SHEET

Hazard Type	Description	Typical Severity
Pothole	Bowl-shaped depression in the road surface, depth > 2cm.	Medium to High
Crocodile Cracks	Interconnected cracks resembling alligator hide. Sign of base failure.	Medium
Faded Markings	Worn-out lane divider lines, crosswalks, or directional arrows.	Low to Medium
Rutting	Longitudinal depressions formed in wheel paths due to heavy loads.	Low
Road Debris	Fallen trees, stones, spilled cargo blocking traffic lanes.	High