CupStream: project overview and development plan

CT70A9800 Full Stack Development

A live streaming web application that will be expanded into a multi-room streaming service, combining public broadcasts with private streams shared among friends. A hybrid between Twitch and Discord streaming.

I started this project a few months ago as an early prototype, but it was just supposed to be a quick way to share low-latency, high-quality streams with my friends. I will continue developing it into a fully fledged streaming platform. The end goal and main evaluation criterion are whether users can easily share live content with one another.

This document describes the current implementation, the planned scope and architecture, the main technical decisions and the implementation plan. I am developing the project alone, so the plan delivers a usable end-to-end product early and tests the riskiest part, desktop capture and packaging, with a prototype before building on it.


1. Current implementation

Frontend: React 18, TypeScript, Vite and Tailwind CSS, with React Router, TanStack Query and Zustand. The interface provides a stream player, live/offline status, viewer count and text chat.

Backend and media: Go 1.22 serves the frontend and HTTP API, MediaMTX handles WebRTC media; the Go service proxies WHEP playback signaling and the media control API. Docker Compose and GitHub Actions build/smoke-test configuration are included.

Current state: The UI targets one stream only. Viewers choose a display name and enter a shared password; there are no individual accounts. There is only one credential configured for a single broadcaster. Chat stores the latest 100 messages in memory and is lost on restart. HLS is disabled.

1.1 Current client-server architecture



2. Product scope

CupStream will let people go live from a desktop app, a browser or OBS, and watch together on the website. Rooms come in two types: Discord rooms, which follow a Discord voice channel, and link rooms, which are shared through invites and links.


2.1 In scope

- **Three ways to go live:** the CupStream desktop app for Windows and Linux (recommended), streaming from the browser (no installation, with documented limitations), and OBS over WHIP for advanced users.
- **Multi-streamer rooms:** several people can stream into the same room at once, and viewers choose one or more streams to watch.
- **Two room types:** Discord rooms, tied to a voice channel and governed by Discord permissions, and link rooms (one per user), managed entirely by CupStream.
- **Accounts:** sign-in with Google or Discord only (OAuth). Linking a Discord account is required for Discord features.
- **Friends:** chosen explicitly, with suggestions from CupStream users who share a Discord server.
- **Discord bot:** tracks voice channels, enables Discord rooms and posts live-status messages.
- **Chat:** WebSocket chat in every room; messages expire after 24 hours.
- **Viewing:** on the website only, over WebRTC with sub-second latency.
- **Live only:** no recordings.

2.2 Out of scope for now

- **LL-HLS playback:** WebRTC only at first; LL-HLS may be added later for very large public rooms.
- **Recordings and video on demand.**
- **A public discovery page:** rooms are reached through links, friends and Discord.
- **A macOS desktop app, and streaming from mobile devices:** mobile browsers cannot capture the screen.
- **A Discord Activity** (watching inside Discord): Discord routes all Activity traffic through its own proxy, which supports HTTP and WebSockets but not WebRTC, so it would need a separate playback path. Explored and dropped.
- **Code signing for the Windows app:** it ships unsigned, with a SmartScreen warning on first install.

3. Planned architecture



The Go server is the only public entry point for HTTP and WebSocket traffic. It handles sign-in, rooms, friends, the realtime WebSocket (chat, presence and stream events), the Discord bot and all WHIP/WHEP signaling, and stores its data in SQLite. MediaMTX only forwards media. Its HTTP interface listens on localhost only, so every publish and playback request has to pass Go's access checks. Media packets travel directly between clients and MediaMTX over UDP, with a TCP fallback, on port 8189.

Everything runs on one dedicated server: an AMD Ryzen 9 9950X3D (16 cores) with 128 GB of RAM, running Ubuntu Server 24.04, with a guaranteed, unmetered 1 Gbps connection. The network, not the CPU, is the capacity limit (see 9.3).

3.1 Key technical decisions

Area	Decision	Reason
Media gateway	Go forwards all WHIP (publish) and WHEP (playback) signaling to MediaMTX, which listens on localhost only.	One place decides access, OBS stream keys never reach MediaMTX, and Go records every viewer session so it can end it when access changes.
Stream paths	Each stream gets its own MediaMTX path (`s/<streamId>`) with a server-generated ID; the room a stream belongs to is only a record in Go.	Clients cannot choose or take over paths, and a stream can move between rooms without restarting.
Live state	Go knows when publishing starts from the WHIP request and reconciles with MediaMTX's API every 2 seconds.	No hook scripts; the state recovers by itself after a restart.
Database	SQLite (WAL mode) with goose migrations and sqlc-generated queries; continuous backups with Litestream.	One server and simple operations; nothing in scope needs a separate database server.
Realtime	One WebSocket per browser tab that subscribes to rooms; it carries chat, presence, stream events, notifications and viewer statistics.	A single connection covers both app-wide and room events.

Area	Decision	Reason
Authentication	OAuth only (Google OpenID Connect and Discord). Server-side sessions stored in the database, identified by an opaque HttpOnly cookie.	Logout and revocation take effect immediately, and there are no passwords to store.
Discord bot	Runs inside the Go server (discordgo) with only the non-privileged GUILDS and GUILD_VOICE_STATES intents.	It shares in-memory voice state with the access checks and needs no approval from Discord.
Codecs	H.264 without B-frames by default, AV1 optional, HEVC refused; Opus audio.	Without transcoding, every viewer must be able to decode what the sender sends.
Desktop app	Tauri 2 (Rust) with GStreamer through gstreamer-rs; WHIP through the Rust `whipclientsink` element built into the app.	Hardware encoders and per-application audio capture; the settings UI can reuse the website's React components.
Transcoding	None by default; optional on-demand low-quality versions through MediaMTX's `runOnDemand` and FFmpeg.	Forwarding keeps latency minimal, and the server's CPU allows a few transcodes when viewers need them.

4. Rooms and access control

4.1 Room types

	Discord room	Link room
Owner	The Discord server; one room per voice channel	A user; every user has exactly one link room
Who can watch	People currently in the voice channel who are signed in with Discord	Depends on visibility: everyone (no login), signed-in users, or invite only
Who can stream	Members with Discord's Video permission in the channel (default), or anyone in the channel (server setting)	The owner and the people they allowed to stream
Leaving voice	Viewers lose access and streams end after a 10–15 second grace period	No effect
Moderation	Based on Discord permissions	The owner
Discord bot	Required; posts and updates a status message in the voice channel's text chat	Not involved
Conversion	A streamer can move their own stream to their link room	Cannot become a Discord room

Each room type has exactly one source of truth for permissions, Discord or CupStream, so the rules never mix. Nobody is ever added to a room automatically: access to a Discord room is calculated from voice presence, and a link room only admits people its owner explicitly allowed.

4.2 Link rooms

- **Visibility:** *Everyone* (anyone with the link, no login needed; chatting requires sign-in), *Signed-in* (any CupStream user with the link) or *Invite only*.
- **Allowed people:** in an invite-only room, the owner chooses who may enter, usually from their friends list. They stay allowed until removed, and can be marked as able to stream (co-streamers).
- **Invite links:** anyone who opens a valid link can watch while the link is valid. The owner sets the

expiry (1 hour, 24 hours, until the stream ends, or never), an optional use limit, and whether the link allows streaming. Revoking a link removes everyone who joined through it. People using a link must sign in, and they are never added to the allowed list.

- **Kicks and bans:** the owner can kick a viewer, which ends their session and temporary access, or ban them, which also blocks invite links.

4.3 Discord rooms

- **Watching:** being in the voice channel and signed in with Discord is the only way in. Someone who opens the room's link without being in the channel is asked to join it, with a link that opens the channel in Discord. Server and channel names are only shown to members of that server.
- **Streaming:** by default the bot mirrors Discord's own rule: only members with the Video (Go Live) permission in the channel can stream. The bot calculates this from roles and channel permission overrides, which it receives without privileged intents. Server admins can instead allow anyone in the channel. If someone loses the permission while live, their stream ends after the grace period.
- **Moderation:** members with Move Members in the channel can end someone else's stream, and members with Manage Messages can delete chat messages. A viewer is removed by disconnecting them from voice in Discord; the grace-period rule does the rest.
- **Leaving voice:** viewers lose access and streams end 10–15 seconds after leaving or switching channels; rejoining within that time cancels it. A streamer sees a countdown with a *Move to my link room* button (see 4.4).
- **Status message:** the bot posts one message in the voice channel's text chat that lists the live streams and links to the room. It edits the message as streams start and stop (at most once every few seconds, because of Discord's rate limits) and deletes it when the room goes idle.
- **Reliability:** if the bot loses its connection to Discord, all kicks and stream endings pause until its voice state is up to date again, so a bot restart never ends anyone's stream. Removing the bot from a server or deleting the voice channel ends that room's streams with a clear reason.
- **Chat:** Discord rooms use the same CupStream chat, collapsed by default. It is not mirrored to Discord, because reading Discord messages requires the privileged Message Content intent.

4.4 Going live and moving streams

- **One live stream per user:** a user can only be live in one place. Going live elsewhere asks for confirmation to end the current stream first. OBS cannot show a prompt, so it is refused and the question appears on the website or in the desktop app instead. A sender reconnecting its own dropped stream does not count as a second stream.
- **Start mode:** a user setting decides where a new stream goes. With *Discord (auto)*, it goes to a Discord room when the user is in a voice channel on a server with the bot and may stream there; otherwise the user is told why and offered their link room. With *Link room*, it always goes to the user's link room.
- **Moving a stream to a link room:** a streamer can move their own stream from a Discord room into their link room, for example to keep streaming after leaving voice, or by choosing *Open to everyone*. The stream keeps its media path, so the video is not interrupted, and the chat history stays with the Discord room.
- **Who keeps watching after a move:** the link room keeps its visibility, or switches to *Everyone*. If it is invite only, people on the allowed list keep watching. The dialog lists the other current viewers with checkboxes, ticked by default; ticked viewers get temporary access until the stream ends, and nothing is saved unless the owner chooses *Always allow*.

- **No move in the other direction:** to stream in a Discord room, the user ends the stream, joins a voice channel on a server with the bot and goes live again.

5. Accounts, friends and Discord integration

5.1 Sign-in and accounts

- Sign-in uses OAuth only: Google (OpenID Connect, scopes `openid profile`) and Discord (scopes `identify guilds`). The first sign-in creates the account, so a guest arriving from a Discord message only sees one consent screen.
- The other provider can be linked later from the settings page; Discord features require a linked Discord account. Accounts are never merged automatically by email address. If an identity already belongs to another account, the user must confirm the merge or cancel.
- Handles are unique, prefilled from the Discord username or the Google name, and editable.
- Sessions are random tokens stored hashed in the database. Users can see and revoke their sessions, including desktop-app logins.

5.2 Friends

- A friendship is a request that the other person accepts. Without acceptance, anyone could add someone and see when they go live.
- Suggestions are CupStream users with a linked Discord account who share a Discord server. Users can turn individual servers off for suggestions; very large servers are off by default, using the approximate member count that Discord returns.
- Server lists change, so the Discord refresh token is stored encrypted and the list is refreshed at sign-in and daily for active users.
- Importing the Discord friends list directly is not possible without approval: the `relationships.read` scope requires applying to Discord and accepting the terms of its Social SDK, which is aimed at games.
- Friends see each other's live status only for rooms they are allowed into, and a friend can be added to the allowed list in one click.

5.3 Discord bot

- Server admins install it with the `bot` and `applications.commands` scopes and the View Channels, Send Messages and Embed Links permissions. It never joins voice.
- It tracks voice channels with the non-privileged GUILDS and GUILD_VOICE_STATES intents: a snapshot when it connects, then voice-state updates kept in memory. Voice states of people who do not use CupStream are never stored.
- Server settings use the `/cupstream settings` slash command, limited to members with Manage Server: who may stream (Video permission or anyone in the channel), status messages on or off, and which voice channels are tracked.
- Discord rooms only exist in servers, because bots cannot see direct-message or group calls. Discord requires verification once a bot is in more than 100 servers.

6. Streaming clients

6.1 Going live

The interface promotes the desktop app first, then streaming from the browser, with OBS as an advanced option. The go-live dialog offers:

1. **CupStream app (recommended).** While it runs in the tray, the app keeps a WebSocket connection to the server, so the website knows it is available and can ask it to open its screen picker. If the app is installed but not running, a `cupstream://` link starts it; otherwise the website offers the download for the visitor's operating system.
2. **Stream from this browser,** with the limitations of the current browser shown inline and a suggestion to use the app when they apply.
3. **OBS (advanced),** collapsed by default: WHIP server URL, stream key and start mode.

All three use the same API: the client asks the server to start a stream, receives a WHIP URL and a token that is valid for that stream only, and publishes. OBS uses its stream key as the token.

6.2 Desktop app (Windows and Linux)

A tray application with one button to go live, a Discord-style picker for screens and windows, quality settings, audio that leaves out Discord, and the choice of room. After going live, it copies the room link to the clipboard. It is built with Tauri 2 and GStreamer.

	Windows	**Linux (Ubuntu 24.04+, Fedora, Arch)**
Capture	Windows.Graphics.Capture (`d3d11screencapturesrc`) with the app's own picker showing windows and monitors with thumbnails	The system screen-sharing dialog (xdg-desktop-portal) and PipeWire; a saved restore token avoids asking every time; `ximagesrc` on X11
Encoders	NVENC, AMF, Quick Sync, Media Foundation; x264 as fallback	VA-API (Intel, AMD), NVENC; x264 or OpenH264 as fallback
Audio without Discord	WASAPI process loopback that excludes Discord's process tree (`wasapi2src`); needs Windows build 20348 or later, in practice Windows 11. Windows 10 falls back to all system audio with a warning	A PipeWire virtual sink that receives every application's audio except Discord and Vesktop (the approach used by venmic); no exclusion on PulseAudio-only systems
Tray	Native	AppIndicator; GNOME needs an extension (Ubuntu ships it, Fedora does not), so the app also works from a small window
Packages	Unsigned NSIS installer (per user, no admin rights) with a trimmed GStreamer bundle	.deb and .rpm packages that use the system's GStreamer and GPU drivers; an AUR package for Arch
Updates	Tauri updater with signed update files	Tauri updater (supports .deb and .rpm since plugin version 2.10) or the package manager

- **Sign-in:** the app opens the CupStream login page in the system browser, which redirects back to the app on a local port (OAuth with PKCE). The app keeps a revocable refresh token in the operating system's keychain.
- **Settings:** resolution and frame-rate presets up to 4K at 60 fps, codec (H.264 or AV1), bitrate (automatic or manual), encoder (detected automatically), audio mode (everything except Discord, everything, one application, or none), start mode and link-room visibility. A global

hotkey starts and stops the stream; on Wayland it uses the GlobalShortcuts portal.

- **Quality:** the app can publish a second, low-quality version of the stream for viewers on slow connections, and adjusts its bitrate when the server reports that viewers are struggling.
- **Limits:** only the Discord desktop app can be excluded; Discord running in a browser tab cannot be separated from the browser's other audio. A streamer watching their own stream on the same computer has to mute it to avoid an echo.
- **Unsigned Windows build:** the first install shows SmartScreen's *Windows protected your PC* warning (More info, then Run anyway), which the download page explains. Updates installed by the app normally do not trigger it. Antivirus false positives are possible, because screen capture, audio capture and uploading look suspicious to heuristics, so every release publishes checksums.
- **Fedora:** Fedora's own Mesa drivers disable hardware H.264 encoding (VA-API) on AMD and Intel GPUs for patent reasons. The app detects this, uses NVENC, AV1 hardware encoding or OpenH264 instead, and points to RPM Fusion's drivers.

6.3 Streaming from the browser

The browser's screen capture (`getDisplayMedia`) is published over WHIP. It needs no installation, but audio support depends on the browser and the browser controls encoding. Warnings are based on what was actually captured rather than on the browser's name.

Browser	Screen audio	What the user sees
Chrome or Edge on Windows, Chrome on recent macOS	All system audio	“Viewers will hear your Discord call” and a suggestion to use the desktop app
Chromium-based browsers on Linux	Tab audio only (to be verified)	An audio device picker that includes “Monitor of…” sources
Firefox and Safari	None	An audio device picker
Mobile browsers	Screen capture unavailable	Viewing only

- **Settings:** resolution and frame-rate presets, motion or detail priority (`contentHint`), codec preference (H.264 by default, AV1 optional) and a maximum bitrate.
- **While live:** the page uploads a small thumbnail every few seconds, adjusts its bitrate when the server asks, reconnects automatically and warns before the tab is closed.

6.4 OBS

- One fixed WHIP URL (`https://<domain>/whip`) with the user's stream key as the bearer token. The key is stored hashed and can be regenerated.
- The destination follows the user's start mode. OBS cannot show warnings, so *Discord (auto)* has a fallback setting for when no Discord room is possible: stream to the link room (default) or refuse.
- OBS reconnects automatically. After a stream in a Discord room ends because the user left voice, the key is refused for about two minutes so the reconnect does not quietly continue in the link room; rejoining voice within that time reconnects into the Discord room.
- A setup guide recommends H.264 or AV1, B-frames off, a 1–2 second keyframe interval and Opus audio; HEVC is refused. OBS 32.1 added simulcast over WHIP, but MediaMTX support for it is unconfirmed, so it is treated as unsupported.

7. Viewing and stream quality

7.1 Room page

- Members with presence and live badges, and a card with a thumbnail for each live stream. Clicking a card starts playback, which also satisfies browsers' autoplay rules for sound; each watched stream is one WHEP connection.
- Focus and grid layouts, volume per stream (only the focused stream is unmuted by default), fullscreen and the chat panel.
- Initial limits: eight live streams per room and four watched streams per viewer.
- Viewing works on phones, since WebRTC with H.264 is supported on iOS and Android; the layout is responsive.

7.2 Bandwidth warnings

- **Before opening another stream:** the server sends each stream's current bitrate over the WebSocket. The first time a viewer watches more than one stream, the page measures their connection with a short download test against the server, then refines the estimate from the throughput they actually sustain. If the total would exceed about 80% of their capacity, they are warned before the stream opens. The browser's own estimate cannot be used: Chrome caps it at 10 Mbps, and Firefox and Safari do not provide it.
- **While watching:** every two seconds the player reads the WebRTC statistics of each stream: packet loss, freezes and dropped frames. If all streams get worse together, the viewer's connection is the bottleneck, and a banner suggests closing a stream, pausing background streams or switching to a low-quality version. If only one stream gets worse, the problem is that streamer's connection, so the stream shows a badge instead; the server can confirm this from its incoming statistics.

7.3 Quality adaptation

- MediaMTX sends every viewer the same stream without re-encoding it, so quality is adapted at the sender, which is also how Discord handles screen sharing.
- Viewers report their statistics, and the server sends each sender a target bitrate: the browser applies it with `RTCRtpSender.setParameters`, the desktop app through its encoder. Viewers who are over their own capacity are ignored and there is a minimum, so one viewer cannot lower the quality for everyone. OBS cannot be controlled remotely.
- **Low-quality versions:** the desktop app publishes its own. For OBS and browser streams, the server can create one on demand with FFmpeg through MediaMTX's `runOnDemand`, only while someone is watching it. A 1080p60 source costs roughly one to two CPU cores, so about six to ten can run at once (to be confirmed by a load test). The low-quality version adds about 200–500 ms of latency.

7.4 Chat

- WebSocket chat in every room, stored in SQLite and deleted after 24 hours.
- Chatting requires sign-in. Messages are rate-limited per user and can be deleted by the room owner (link rooms) or by Discord moderators (Discord rooms).

8. Data model

The main SQLite tables:

Table	Purpose	Main columns
`users`	Accounts	id, handle (unique), display_name, avatar_url, created_at
`identities`	Google and Discord identities of a user	user_id, provider, subject, username
`sessions`	Website and desktop-app sessions	token_hash, user_id, kind, device_name, expires_at, last_seen_at
`discord_tokens`	Encrypted Discord refresh tokens	user_id, encrypted_refresh_token, updated_at
`user_guilds`	A user's Discord servers, for friend suggestions	user_id, guild_id, name, approx_members, suggestions_enabled
`user_settings`	Per-user settings	user_id, start_mode (discord_auto, link), obs_fallback (link, refuse)
`stream_keys`	OBS stream keys	user_id, key_hash (unique), created_at, revoked_at
`rooms`	Both room types	id, kind (link, discord), slug; link rooms: owner_id, visibility (everyone, signed_in, invite_only); Discord rooms: guild_id, channel_id (unique together)
`room_allowed`	People allowed into a link room	room_id, user_id, can_stream
`invites`	Invite links	id, token_hash, room_id, can_stream, expires_at or until_stream_end, max_uses, uses, revoked_at
`room_passes`	Temporary access from invite links and moved streams	room_id, user_id, invite_id, expires_at, can_stream
`room_bans`	Bans from a link room	room_id, user_id
`friendships`	Friend requests and friends	user_a, user_b, status (pending, accepted), requested_by
`discord_guilds`	Bot settings per Discord server	guild_id, stream_policy (video_permission, anyone_in_channel), announce, tracked_channels
`streams`	Stream history	id, room_id, user_id, source (app, web, obs), started_at, ended_at, end_reason, peak_viewers
`chat_messages`	Room chat, kept for 24 hours	id, room_id, user_id, body, created_at

Access to Discord rooms is never stored: it is calculated from the bot's in-memory voice state and permissions. Live stream state, presence and thumbnails are also kept in memory.

9. Security, privacy and operations

9.1 Security

- The session cookie is HttpOnly, Secure and SameSite=Lax. State-changing requests and WebSocket connections check the Origin header, which also fixes the current chat WebSocket that accepts connections from any website.
- OAuth uses the state parameter, PKCE where the provider supports it and a nonce for Google, with minimal scopes. Google tokens are not stored.
- Stream keys, invite tokens and session tokens are 128-bit random values stored as SHA-256

hashes.

- MediaMTX's HTTP and API ports listen on localhost only, and the firewall opens only TCP 80 and 443 and UDP/TCP 8189. The MediaMTX version is pinned instead of using `latest`.
- Cloudflare moves from Flexible SSL, which sends traffic unencrypted between Cloudflare and the server, to Full (strict) with a Cloudflare Origin CA certificate. ICE candidates must contain the server's real IP address, because Cloudflare cannot carry UDP. WebSockets send a ping every 30 seconds, because Cloudflare closes idle connections after about 100 seconds.
- Rate limits on sign-in, chat and stream creation, security headers including a Content Security Policy, and an admin kill switch to end any stream or ban a user.

9.2 Privacy

- Privacy policy and terms pages, which Discord verification and Google's consent screen require.
- Data minimisation: no Google tokens, no stored voice states of people who do not use CupStream, encrypted Discord refresh tokens, and chat deleted after 24 hours.
- Deleting an account removes all of the user's data (GDPR).

9.3 Capacity

- 1 Gbps carries about 125 viewer-streams at 8 Mbps (1080p60) or about 40 at 25 Mbps (4K60). Above roughly 800 Mbps of outgoing traffic, measured on the network interface, new viewers are refused with a clear message.
- The CPU is not the limit for forwarding encrypted media. Linux UDP buffer sizes are raised for high packet rates.
- A TURN server (coturn on port 443) can be added later for networks that block UDP and port 8189.

9.4 Deployment and operations

- Docker Compose runs the Go server and MediaMTX, as today; the systemd and OpenRC service files remain as alternatives.
- SQLite is backed up continuously with Litestream to S3-compatible storage.
- Structured logs (slog), a health endpoint, and an admin page that shows live streams, viewers and bandwidth.
- Repository layout: `server/` (the renamed `auth-svc`), `web/`, `companion/`, `deploy/` and `docs/`. TypeScript types are generated from the Go API types, so the website and the desktop app share them.

10. Testing

- **Go:** a table of access-control cases (room type, visibility, allowed list, temporary access, voice presence, permissions, and the action: watch, stream, chat or moderate), store tests on a temporary SQLite database, OAuth callbacks against a mock provider, and the bot's voice tracking with synthetic Discord events.
- **Media in CI:** MediaMTX in a container, a GStreamer test source publishing over WHIP, and headless Chromium (Playwright) playing over WHEP, checking that frames are decoded.
- **Website:** Vitest for components, and Playwright end-to-end tests with a development-only login provider (enabled by an environment variable, on localhost only), since OAuth-only sign-in

cannot be automated otherwise.

- **Desktop app:** CI builds for Windows and Linux, pipeline smoke tests with test sources, and a manual test matrix of GPU vendor, operating system and X11/Wayland.
- **Load test:** synthetic WHEP viewers to find where the server saturates.

11. Implementation plan

The phases are ordered so that each one ends with something usable and testable.

Phase	Work	Done when
0. Groundwork	Restructure the repository, upgrade Go, structured logging and configuration, SQLite with goose, sqlc and Litestream, a development setup with a pinned MediaMTX and the development login, CI for Go and the website, Cloudflare Full (strict), MediaMTX restricted to localhost	CI passes on the new layout and the development environment starts with one command
1. Identity	Google and Discord sign-in, accounts, sessions, handles, account linking, Discord server-list sync, settings page; remove the shared-password login	A user can sign in with either provider and link the other
2. Rooms and media gateway	Room types, access checks with the test table, WHIP and WHEP gateway with session tracking, live-state reconciliation, OBS stream keys, start mode and the one-live-stream rule	Two OBS instances stream into one link room; an allowed browser watches both, others are refused
Desktop prototype	A command-line pipeline on Windows and Linux: capture, hardware encoding, WHIP and audio without Discord	Both operating systems publish to the development server with Discord excluded
3. Realtime	WebSocket gateway, presence, stream events, chat with expiry and moderation, viewer statistics	Two browsers see each other's presence and chat; messages disappear after 24 hours
4. Viewer interface	Home page, room page with focus and grid layouts and several streams, invites, allowed list, bans, thumbnails, bandwidth warnings	A viewer watches several streams and is warned when their connection cannot keep up
5. Browser streaming	Go-live dialog, capture, presets, compatibility warnings, audio device picker, bitrate control, reconnection	A user goes live from Chrome and from Firefox and sees the correct warnings
6. Discord	Bot, voice tracking, Discord rooms, Video permission, grace periods, status messages, server settings, moving streams to link rooms, friends with requests and suggestions	People in a voice channel can watch a stream there, and leaving the channel removes access after 10–15 seconds
7. Desktop app	Tauri app, tray, sign-in, picker, encoders, audio modes, low-quality version, bitrate control, installers and updates	A user installs the app on Windows or Linux and goes live in two clicks
8. Hardening	Admission control, on-demand low-quality versions, TURN, load test, admin page, privacy pages	The server refuses viewers cleanly at capacity and passes the load test

Browser streaming comes before the desktop app because it is a fraction of the work and gives a complete end-to-end loop for testing; the interface still promotes the desktop app once it exists. The desktop prototype runs right after phase 2 because GStreamer, platform capture and packaging are the largest technical risks.

12. Risks and open points

Risk	Impact	Mitigation
Importing Discord friends requires approval (`relationships.read`)	No automatic friends list	Friend suggestions from shared servers
Audio without Discord needs Windows 11	Windows 10 users capture all system audio	A warning; possibly a custom capture element later, since OBS uses the same API on Windows 10 2004 and later
Fedora lacks hardware H.264 encoding by default	Higher CPU use, or AV1 only	Encoder detection, AV1, OpenH264 and an RPM Fusion guide
Unsigned Windows app	SmartScreen warning and possible antivirus false positives	Download-page guidance, checksums and false-positive reports
MediaMTX details (simulcast, ending a viewer's session from Go) are unverified	Parts of the design may change	Verify early in phase 2
No server-side transcoding by default	Viewers on slow connections may stall	Bandwidth warnings, the app's low-quality version and on-demand transcodes
Networks that block UDP	Some viewers cannot connect	ICE over TCP on port 8189; TURN later
Discord bot outages	Viewers could be removed incorrectly	Kicks pause until the voice state is fresh
Bot in more than 100 servers	Discord verification required	Apply for verification when needed

12 October 2026 - Radu Stoiana