```
/*
    libxbee - a C library to aid the use of Digi's Series 1 XBee modules
              running in API mode (AP=2).

    Copyright (C) 2009  Attie Grande (attie@attie.co.uk)

    This program is free software: you can redistribute it and/or modify
    it under the terms of the GNU General Public License as published by
    the Free Software Foundation, either version 3 of the License, or
    (at your option) any later version.

    This program is distributed in the hope that it will be useful,
    but WITHOUT ANY WARRANTY; without even the implied warranty of
    MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
    GNU General Public License for more details.

    You should have received a copy of the GNU General Public License
    along with this program.  If not, see <http://www.gnu.org/licenses/>.
*/

#ifndef XBEE_H
#define XBEE_H

#if !defined(__GNUC__) && !defined(_WIN32)
#error "This library is only currently compatible with Linux and Win32"
#endif

#include <stdarg.h>

enum xbee_types {
  xbee_unknown,

  xbee_localAT,       /* frame ID */
  xbee_remoteAT,

  xbee_16bitRemoteAT, /* frame ID */
  xbee_64bitRemoteAT, /* frame ID */

  xbee_16bitData,     /* frame ID for ACKs */
  xbee_64bitData,     /* frame ID for ACKs */

  xbee_16bitIO,
  xbee_64bitIO,

  xbee_txStatus,
  xbee_modemStatus
};
typedef enum xbee_types xbee_types;

struct xbee_con {
  unsigned int tAddr64       : 1;
  unsigned int atQueue       : 1; /* queues AT commands until AC is sent */
  unsigned int txDisableACK  : 1;
  unsigned int txBroadcast   : 1; /* broadcasts to PAN */
  unsigned int __spare__     : 4;
  xbee_types type;
  unsigned char frameID;
  unsigned char tAddr[8];         /* 64-bit 0-7   16-bit 0-1 */
  struct xbee_con *next;
};
typedef struct xbee_con xbee_con;

struct xbee_sample {
  /* X  A5 A4 A3 A2 A1 A0 D8    D7 D6 D5 D4 D3 D2 D1 D0  */
  unsigned short IOmask;          /*                   IO */
  /* X  X  X  X  X  X  X  D8    D7 D6 D5 D4 D3 D2 D1 D0  */
  unsigned short IOdigital;       /*                   IO */
  /* X  X  X  X  X  D  D  D     D  D  D  D  D  D  D  D   */
  unsigned short IOanalog[6];     /*                   IO */
};
typedef struct xbee_sample xbee_sample;

struct xbee_pkt {
  unsigned int sAddr64        : 1; /* yes / no */
  unsigned int dataPkt        : 1; /* if no - AT packet */
  unsigned int txStatusPkt    : 1;
  unsigned int modemStatusPkt : 1;
  unsigned int remoteATPkt    : 1;
  unsigned int IOPkt          : 1;
  unsigned int __spare__      : 2;

  unsigned char frameID;          /* AT        Status    */
  unsigned char atCmd[2];         /* AT                  */

  unsigned char status;           /* AT  Data  Status    */ /* status / options */
```

```
  unsigned char samples;
  unsigned char RSSI;             /*     Data            */

  unsigned char Addr16[2];        /* AT  Data            */

  unsigned char Addr64[8];        /* AT  Data            */

  unsigned char data[128];        /* AT  Data            */

  unsigned int datalen;
  xbee_types type;

  struct xbee_pkt *next;

  xbee_sample IOdata[1];  /* this array can be extended by using a this trick:
                             p = calloc(sizeof(xbee_pkt) + (sizeof(xbee_sample) * (samples - 1))) */
};
typedef struct xbee_pkt xbee_pkt;

int xbee_setup(char *path, int baudrate);
int xbee_setuplog(char *path, int baudrate, int logfd);
int xbee_setupAPI(char *path, int baudrate, char cmdSeq, int cmdTime);
int xbee_setuplogAPI(char *path, int baudrate, int logfd, char cmdSeq, int cmdTime);

int xbee_end(void);

xbee_con *xbee_newcon(unsigned char frameID, xbee_types type, ...);

void xbee_flushcon(xbee_con *con);

#define xbee_endcon(x) xbee_endcon2((xbee_con **)&x)
void xbee_endcon2(xbee_con **con);

#ifdef __GNUC__ /* ---- */
int xbee_senddata(xbee_con *con, char *format, ...) __attribute__ ((format (printf,2,3)));
int xbee_vsenddata(xbee_con *con, char *format, va_list ap) __attribute__ ((format (printf,2,0)));
#else /* -------------- */
int xbee_senddata(xbee_con *con, char *format, ...);
int xbee_vsenddata(xbee_con *con, char *format, va_list ap);

/* oh and just 'cos windows has rubbish memory management rules... this too */
void xbee_free(void *ptr);
#endif /* ------------- */

int xbee_nsenddata(xbee_con *con, char *data, int length);

xbee_pkt *xbee_getpacketwait(xbee_con *con);
xbee_pkt *xbee_getpacket(xbee_con *con);

int xbee_hasdigital(xbee_pkt *pkt, int sample, int input);
int xbee_getdigital(xbee_pkt *pkt, int sample, int input);

int xbee_hasanalog(xbee_pkt *pkt, int sample, int input);
double xbee_getanalog(xbee_pkt *pkt, int sample, int input, double Vref);

const char *xbee_svn_version(void);

void xbee_listen_stop(void);

#endif
```