

```
1:  /*
2:      libxbee - a C library to aid the use of Digi's Series 1 XBee modules
3:                running in API mode (AP=2).
4:
5:      Copyright (C) 2009 Attie Grande (attie@attie.co.uk)
6:
7:      This program is free software: you can redistribute it and/or modify
8:      it under the terms of the GNU General Public License as published by
9:      the Free Software Foundation, either version 3 of the License, or
10:     (at your option) any later version.
11:
12:     This program is distributed in the hope that it will be useful,
13:     but WITHOUT ANY WARRANTY; without even the implied warranty of
14:     MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
15:     GNU General Public License for more details.
16:
17:     You should have received a copy of the GNU General Public License
18:     along with this program. If not, see <http://www.gnu.org/licenses/>.
19: */
20:
21: /* this file contains code that is used by Linux ONLY */
22: #ifndef __GNUC__
23: #error "This file should only be used on a Linux system"
24: #endif
25:
26: /* ##### */
27: /* ### Linux Code ##### */
28: /* ##### */
29:
30: #define xbee_thread_create(a,b,c) pthread_create(&(a),NULL,(void (*)(void *))(b),(void *)(c))
31: #define xbee_thread_kill(a,b) pthread_kill((a),(b))
32:
33: #define xbee_mutex_init(a) pthread_mutex_init(&(a),NULL)
34: #define xbee_mutex_destroy(a) pthread_mutex_destroy(&(a))
35: #define xbee_mutex_lock(a) pthread_mutex_lock(&(a))
36: #define xbee_mutex_trylock(a) pthread_mutex_trylock(&(a))
37: #define xbee_mutex_unlock(a) pthread_mutex_unlock(&(a))
38:
39: #define xbee_write(a,b) fwrite((a),1,(b),xbee.tty)
40: #define xbee_read(a,b) fread((a),1,(b),xbee.tty)
41: #define xbee_close(a) fclose((a))
```