

Version
1.0

pbdR Core Team

Setting up a pbdR Environment

Installing MPI, R, and pbdR

Setting Up a pbdR Environment

Installing MPI, R, and pbdR

Version 1.0

Prepared by the pbdR Core Team:

Drew Schmidt

*Remote Data Analysis and Visualization Center,
University of Tennessee, Knoxville*

Wei-Chen Chen

*Computer Science and Mathematics Division,
Oak Ridge National Laboratory*

Pragneskumar Patel

*Remote Data Analysis and Visualization Center,
University of Tennessee, Knoxville*

George Ostrouchov

*Computer Science and Mathematics Division,
Oak Ridge National Laboratory*

© 2013 pbdR Core Team. All rights reserved.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions, except that this permission notice may be stated in a translation approved by the pbdR Core Team.

This publication was typeset using L^AT_EX.

Contents

1	Allocation	1
2	Quick Introduction	1
2.1	Installing R	1
2.2	Installing MPI	1
2.3	Installing pbdR Packages	1
3	Windows	2
3.1	Installing R	2
3.2	Installing Rtools	5
3.3	Installing MPI	8
3.4	Installing pbdR Packages	12
3.4.1	Installing from Github	12
3.4.2	Installing from Downloaded Source	13
4	Running pbdR Scripts	15
5	Installation Problems	15
5.1	R and MPI	16
5.2	pbdR	16

1 Allocation

We have tried to make the installation process as simple as possible, and these instructions as thorough as possible. However, this is not an entirely labor-free procedure, and does not even get into the really difficult side of large-scale computing: managing the system.

If you affiliated with a United States institution and are engaged in research that requires large-scale computing resources, [we encourage you to consider getting an allocation with us](#) . Not only can we tailor our pbdR development to help your research, but we can manage the hardware, operating system, and software utilities for you, so that you can focus entirely on the thing that matters, your research.

2 Quick Introduction

In this guide, we will detail the necessary steps for how to set up a pbdR environment. What follows in the remaining sections is a very lengthy list of installation instructions; however, most users should find the process fairly straight-forward, and may not need (or want) all of the details we will provide unless something goes wrong. In any case, the short version for setting up a pbdR environment is to:

1. install R (and Rtools for Windows); see <http://cran.r-project.org/>
2. install an MPI library; <http://www.open-mpi.org/>, or <http://www.mpich.org/> for Windows
3. install the pbdR packages; see <http://r-pbd.org/>

Items 1 and 2 are interchangeable, and so if you already have R (and additionally Rtools for Windows) and/or an MPI library installed, then merely skip this/these step(s); there is no need to reinstall anything.

2.1 Installing R

This should be fairly painless. R has binary packages for every operating system you have heard of (and some you haven't), and the install should go fine. Of course, since R is open source, you are free to compile it yourself, should have have reason or need to do so. You can find both the source as well as binaries at the R project's main site: <http://cran.r-project.org/>.

Additionally, you may wish to customize your R build by compiling from source. For example, you may wish to link R with a high performance linear algebra library, such as MKL. See the *R Installation and Administration Manual* at <http://cran.r-project.org/doc/manuals/R-admin.html> for full details.

2.2 Installing MPI

Windows users should install MPICH2, available from <http://www.mpich.org/> .

2.3 Installing pbdR Packages

All released pbdR packages are available from <http://cran.r-project.org/> which is the Comprehensive R Archive Network (CRAN). This is similar to the CPAN for perl or CTAN for L^AT_EX, although with many improvements and benefits over its competitors.

It is also possible to link pbdR with high performance linear algebra libraries, such as MKL. Figure 1 offers some insight into the package organization. See the pbdSLAP vignette for more details.




Figure 1: pbdR Relationships to Libraries


3 Windows

Officially, the pbdR team does not support gaming consoles (only kidding!). Jokes aside, it is possible to install a pbdR environment on Windows, but it is not necessarily the easiest. This guide will explain the basics of getting R, OpenMPI, and pbdR installed on your Windows system. The instructions and screenshots for this document are for version 2.15.1 of R, but later versions should be very similar, if not identical.


If you are completely new to R, then you may find the [R for Windows FAQ](#) useful. Additionally, there is also an [R FAQ](#) which may also be useful for those who know very little about R. To learn more about programming with R, then you may find the [Introduction to R](#) guide useful.

3.1 Installing R


1. Download R: <http://cran.r-project.org/bin/windows/base/>




2. Open the saved file from 1 above to begin the installation. At the first setup screen, click 'Next' to continue.




3. When prompted with the license, click 'Next' to continue.




4. When prompted for the location to install R, we strongly encourage you to use the default. When you have made your decision, click 'Next'.




5. When prompted with the components to install, you should select a 'User installation'. Then click 'Next'.



6. When prompted with the option to alter the startup options, we suggest selecting No (accept defaults). When you have made your decision, click 'Next'.




7. When prompted with the start menu folder options, make your choice and then click 'Next'.



8. When prompted with the additional tasks options, we suggest making sure that **Save version number in registry** and **Associate R with .RData files** are both **checked**. When you have

made your decisions, click 'Next'.



9. To complete the R installation, select 'Finish'.




Once R is finished installing, you need to install the [rlecuyer](#) package. To install it from an interactive R session, simply start an R session and issue the command


```
1 install.packages("rlecuyer")
```

3.2 Installing Rtools


1. Download Rtools: <http://cran.r-project.org/bin/windows/base/>




- Open the saved file from 1 above to begin the installation. At the first setup screen, click 'Next' to continue.




- When prompted with the license, click 'Next' to continue.




- When prompted for the location to install R, we strongly encourage you to use the default. When you have made your decision, click 'Next'.




5. When prompted with the components to install, you should select a 'User installation'. Then click 'Next'.




6. When prompted with the option to alter the startup options, we suggest selecting No (accept defaults). When you have made your decision, click 'Next'.



7. When prompted with the start menu folder options, make your choice and then click 'Next'.




8. To complete the Rtools installation, select 'Finish'.




3.3 Installing MPI

Before proceeding, please be aware that this installation requires **administrative privileges**.


1. Download both the 32-bit [mpich2-1.4.1p1-win-i32.msi](http://www.mpich.org/) and the 64-bit [mpich2-1.4.1p1-win-x86-64.msi](http://www.mpich.org/) installers from: <http://www.mpich.org/> .




2. Open the saved file from 1 above to begin the installation. At the first setup screen, click 'Next' to continue.




3. When prompted with the system requirements, click 'Next' to continue.



4. When prompted with the license, click "I agree" and then click 'Next' to continue.





5. When prompted with the 'Process Manager setup' screen, choose a passphrase and then click 'Next' to continue.




6. At the 'Select Installation Folder' screen, we recommend you keep the default folders. By default, the 32-bit application will be installed in `C:\Program Files (x86)\MPICH2\` and the 64bit application will be installed in `C:\Program Files\MPICH2\`.


Additionally, you should make the selection for whether or not MPICH2 should be available to all users of this system or just yourself. When you are ready to proceed, click 'Next'.



7. When prompted to confirm the installation, click 'Next' to proceed.



8. To complete the MPICH2 installation, select 'Close'.



3.4 Installing pbdR Packages

Unfortunately, we do not distribute pbdR binary packages on the CRAN for Windows. This means that you must install our packages from source on Windows, and the process may be foreign. We will present two approaches; the short way, installing from github using the **devtools** package, and a longer way, installing from a downloaded source file. However, do be aware that each of these methods requires the installation of the Rtools package from Section 3.2 (so that step cannot be skipped).

3.4.1 Installing from Github

This is probably the simplest method, assuming that you have Rtools installed and set up correctly. If Rtools is not in your PATH, then you may need to enter something like the following:

```

1 rtools <- "C:\\Rtools\\bin\\"
2 mingw <- "C:\\Rtools\\gcc-4.6.3\\bin\\"
3
4 PATH <- Sys.getenv("PATH")
5 new.PATH <- paste(rtools, mingw, PATH, sep = ";")
6 Sys.setenv(PATH=new.PATH)

```

Where the **rtools** and **mingw** directories are as they are on your machine.

Once that is settled, installing is fairly simple. You simply load the **devtools** package and install from our github repo as follows:

```

1 library(devtools)
2
3 install_github(repo="pbdMPI", username="RBigData")
4 install_github(repo="pbdSLAP", username="RBigData")
5 install_github(repo="pbdNCDF4", username="RBigData")
6 install_github(repo="pbdBASE", username="RBigData")
7 install_github(repo="pbdDMAT", username="RBigData")
8 install_github(repo="pbdDEMO", username="RBigData")

```

You can also install *really* new package builds, which will be very current in terms of features, but also bugs (or even complete package breakage). If you're sure you want these packages, then you can install them as follows:

```

1 # dev repo 1
2 install_github(repo="pbdMPI", username="snoweye")
3 install_github(repo="pbdSLAP", username="snoweye")
4 install_github(repo="pbdNCDF4", username="snoweye")
5 # dev repo 2
6 install_github(repo="pbdBASE", username="wrathematics")
7 install_github(repo="pbdDMAT", username="wrathematics")
8 install_github(repo="pbdDEMO", username="wrathematics")

```

3.4.2 Installing from Downloaded Source

1. To help simplify things, we offer a simple [install script](#) which makes managing the PATH slightly simpler. By default, this is for R version 2.15.3 and **pbdMPI** version 0.1-6. If you have a different version of R or want to install a different version of **pbdMPI**, simply change lines 4 and/or 5 of the install script to match your needs.

```

@ECHO OFF

rem ### Set environment variables.
SET RTOOLS=C:\Rtools\bin\
SET MINGW=C:\Rtools\gcc-4.6.3\bin

IF NOT DEFINED PATH_ORG SET PATH_ORG=%PATH%
SET PATH=%RTOOLS%;%MINGW%;%PATH_ORG%

rem ### Set "MPI_ROOT_32" and "MPI_ROOT_64" if they are not in the default
rem ### installation path or you have different MPI systems.
rem ### "Makevars.win" uses default if the following two are remarked.
rem SET MPI_ROOT_64=C:\Program Files\MPICH2
rem SET MPI_ROOT_32=C:\Program Files (x86)\MPICH2

rem ### Build windows binary.
C:\PROGRA~1\R\R-2.15.1\bin\R CMD INSTALL --build --html pbdMPI_0.1-1.tar.gz
C:\PROGRA~1\R\R-2.15.1\bin\R CMD INSTALL pbdMPI_0.1-1.zip

"build_pbdMPI.bat" 19L, 674C written 19,0-1 All

```

2. Open a command prompt either from the start menu, or by entering the command Windows key then R, and then entering cmd in the “run” dialog box.


```

>PATH
PATH=C:\Program Files (x86)\NVIDIA Corporation\PhysX\Common;C:\Program Files\NVIDIA GPU Computing Toolkit\CUDA\v4.2\bin;C:\Program Files\NVIDIA GPU Computing Toolkit\CUDA\v4.2\libnvvp;C:\Program Files\Microsoft Shared\Windows Live;C:\Program Files (x86)\Common Files\Microsoft Shared\Windows Live;C:\Program Files (x86)\MikTeX 2.9\miktex\bin;C:\Windows\system32;C:\Windows;C:\Windows\System32\Wbem;C:\Windows\System32\WindowsPowerShell\v1.0\;C:\Program Files (x86)\Common Files\Roxio Shared\DLLShared\;C:\Program Files (x86)\Common Files\Roxio Shared\OEM\DLLShared\;C:\Program Files (x86)\Common Files\Roxio Shared\OEM\12.0\DLLShared\;C:\Program Files (x86)\Roxio\OEM\AudioCore\bin;C:\Program Files (x86)\Windows Live\Shared;C:\Program Files (x86)\Subversion\bin;C:\Program Files (x86)\QuickTime\QTSystem\bin;C:\ProgramData\NVIDIA Corporation\NVIDIA GPU Computing SDK 4.2\C\common\bin;C:\Users\snoweye\AppData\Roaming\MikTeX\2.9\miktex\bin\
>_

```


3. Before proceeding further, it is probably a good idea to test the installation of MPICH2. The following commands utilize MPICH2 to do some fairly trivial things (do not copy SHELL> if you are copying and pasting from the lines below):

```
SHELL> C:\PROGRA~1\MPICH2\bin\mpiexec -np 2 hostname.exe
SHELL> C:\PROGRA~1\R\R-2.15.1\bin\R --vanilla --slave -e "ls()"
SHELL> C:\PROGRA~1\R\R-2.15.1\bin\Rscript --vanilla --slave -e "ls()"
```



```
Administrator: Command Prompt

>C:\PROGRA~1\MPICH2\bin\mpiexec -np 2 hostname.exe
User credentials needed to launch processes:
account (domain\user) [WOLF_DELL\snoweye]: snoweye
password:
WOLF_DELL
WOLF_DELL


>C:\PROGRA~2\MPICH2\bin\mpiexec -np 2 hostname.exe
WOLF_DELL
WOLF_DELL

>C:\PROGRA~1\R\R-2.15.1\bin\R --vanilla --slave -e "ls()"
character(0)

>C:\PROGRA~1\R\R-2.15.1\bin\Rscript --vanilla --slave -e "ls()"
character(0)

>
```

4. Download the [source](#) for **pbdMPI** package. Put it in the same directory as your build_pbdMPI.bat file, and then execute build_pbdMPI.bat from the command prompt to install the package.



```
Administrator: Command Prompt


>dir
Volume in drive C is OSDisk
Volume Serial Number is 5AB5-15E1

Directory of C:\Users\snoweye\Desktop\DESKTOP-MY\George\code\pbd\windows

10/17/2012  04:29 PM    <DIR>          .
10/17/2012  04:29 PM    <DIR>          ..
10/17/2012  04:03 PM             704 build_pbdMPI.bat
10/17/2012  04:28 PM    <DIR>          figures
10/17/2012  03:28 PM      8,769,536 mpich2-1.4.1p1-win-ia32.msi
10/17/2012  03:28 PM      9,809,408 mpich2-1.4.1p1-win-x86-64.msi
10/02/2012  03:39 PM      337,013 pbdMPI_0.1-1.tar.gz
10/17/2012  02:26 PM     49,354,275 R-2.15.1-win.exe
10/17/2012  04:29 PM       65,018 rlecuyer_0.3-3.zip
10/17/2012  02:37 PM     31,120,628 Rtools216.exe
              7 File(s)      99,456,582 bytes
              3 Dir(s)  110,782,427,136 bytes free

>build_pbdMPI_
```

5. If the process is done without errors, you can see the binary package is installed.



```

Administrator: Command Prompt
cc_comm      html
dd_info      html
dd_prob      html
dd_wait      html
ww_get.jid   html
ww_print_cat html
ww_seed      html
xx_g.sort    html
yy_api.apply html
zz_internal  html
zz_spmc.internal
** building package indices
** installing vignettes
'pbdMPI-guide.Rnw'
** testing if installed package can be loaded
*** arch - i386
*** arch - x64
* MD5 sums
packaged installation of 'pbdMPI' as pbdMPI_0.1-1.zip

* DONE (pbdMPI)
* installing to library 'C:/Program Files/R/R-2.15.1/library'
package 'pbdMPI' successfully unpacked and MD5 sums checked
>

```

4 Running pbdR Scripts

This information is covered in *much* more detail in the [pbdDEMO](#) vignette, and should not be considered a substitute. However, there are two key points one needs to understand in order to use pbdR tools. Namely,

- pbdR codes are written in Single Program/Multiple Data style
- pbdR codes are executed in batch

For full details, see the pbdDEMO package vignette.

Below is a simple pbdR script. This will help you know if things are installed properly or not. To understand what the script is doing, or to learn how to do much more substantial things, you should see the pbdDEMO package vignette.

```

1 library(pbdMPI, quiet = TRUE)
2 init()
3
4 x <- comm.rank()
5
6 comm.print(x, all.rank = TRUE)
7
8 finalize()

```

To run the script, you must do so in batch (i.e., non-interactively). First save its contents to the file `my_script.r`, and then open a command prompt. On Windows, you should execute the command:

```
mpiexec.exe -np 2 Rscript my_script.r
```

5 Installation Problems

During the course of installation, you may run into unrecoverable issues. The pbdR team does not support MPI libraries or R core, so if you have problems during that portion of the installation phase,

we probably can not directly help you. However, there are still many great resources at your disposal, maintained by those individual projects.

5.1 R and MPI

If you have problems installing or customizing R, see the *R Installation and Administration Manual* at <http://cran.r-project.org/doc/manuals/R-admin.html> for help.

If you are having trouble installing an MPI library, you should see that library's official documentation. For OpenMPI, see <http://www.open-mpi.org/community/help/> and for MPICH, see <http://www.mpich.org/documentation/guides/>.

For the remainder, we will be addressing installation issues with pbdR packages.

5.2 pbdR

This is a quick list of potential problems you could encounter when installing pbdR packages. For additional troubleshooting or installation options, each package has a vignette which may offer additional useful information.

- **When compiling pbdMPI from source**, you may be required to pass a configure argument at compile time. So for example, if you have OpenMPI installed and were installing from the command line, then you would issue the command:

```
R CMD INSTALL pbdMPI_0.1-6.tar.gz \
  --configure-args='--with-Rmpi-type=OPENMPI'
```

or if installing from R:

```
1 install.packages("pbdMPI", configure.args='--with-Rmpi-type=
  OPENMPI')
```

See the **pbdMPI** vignette for more details.

- **If you are installing on a cluster** where you must install on the login node which can not execute `mpirun`, then pass the install option `--no-test-load`. So for example, if installing from the command line, then you would issue the command:

```
R CMD INSTALL pbdMPI_0.1-6.tar.gz --no-test-load
```

or if installing from R:

```
1 install.packages("pbdMPI", INSTALL_opts='--no-test-load')
```

- **If you are installing binaries on MAC OS X**, do not use the gui. You can install from source using the gui, or you can install binaries (or from source) using the terminal. But you can not install binaries using the gui. So if you want to install binaries, you should open Finder, then navigate to **Applications/Utilities/** and select **Terminal**. Next, type R and press enter. Now try to install the packages.