

From 1 Core to Thousands: R to pbdR

Drew Schmidt¹, George Ostrouchov², Wei-Chen Chen²,
Pragneshkumar Patel¹

1. University of Tennessee, USA
2. Oak Ridge National Laboratory, USA

August 8, 2013



Affiliations and Support

The pbdR Core Team

<http://r-pbd.org>

Wei-Chen Chen¹, George Ostrouchov^{1,2}, Pragneshkumar Patel², Drew Schmidt¹

Ostrouchov, Patel, and Schmidt were supported in part by the project “NICS Remote Data Analysis and Visualization Center” funded by the Office of Cyberinfrastructure of the U.S. National Science Foundation under Award No. ARRA-NSF-OCI-0906324 for NICS-RDAV center.

Chen and Ostrouchov were supported in part by the project “Visual Data Exploration and Analysis of Ultra-large Climate Data” funded by U.S. DOE Office of Science under Contract No. DE-AC05-00OR22725.

¹Computer Science and Mathematics Division, Oak Ridge National Laboratory, Oak Ridge, TN

²Remote Data Analysis and Visualization Center, University of Tennessee, Knoxville, TN

About This Presentation

Downloads

This presentation and supplemental materials are available at:

<http://r-pbd.org/tutorial>

Sample R scripts and pbs job scripts available on Nautilus from:
`/lustre/medusa/mschmid3/tutorial/scripts.tar.gz`

Contents

- 1 Introduction to R
- 2 Parallel Hardware and R
- 3 pbdR
- 4 Benchmarks
- 5 Challenges

Contents

- 1 Introduction to R
 - What is R?
 - Syntax for Data Science

What is R?

- *lingua franca* for data analytics and statistical computing.
- Part programming language, part data analysis package.
- Dialect of S (Bell Labs).
- Syntax designed for data. scoping semantics, and 2 official OOP systems.

Who uses R?

Google, Pfizer, Merck, Bank of America, Shell^a,
Oracle^b, Facebook, bing, Mozilla, okcupid^c,
ebay^d,
kickstarter^e, the New York Times^f

^ahttps://www.nytimes.com/2009/01/07/technology/business-computing/07program.html?_r=0

^b<http://www.oracle.com/us/corporate/features/features-oracle-r-enterprise-498732.html>


^c<http://www.revolutionanalytics.com/what-is-open-source-r/companies-using-r.php>

^d<http://blog.revolutionanalytics.com/2012/09/using-r-in-production-industry-experts-share-their-experiences.html>

^e<http://blog.revolutionanalytics.com/2012/09/kickstarter-facilitates-50m-in-indie-game-funding.html>

^f<http://blog.revolutionanalytics.com/2012/05/nyt-charts-the-facebook-ipo-with-r.html>

Language Paradigms



Data Types

- Storage: logical, int, double, double complex, character
- Structures: vector, matrix, array, list, dataframe
- Caveats: (Logical) TRUE, FALSE, NA

For the remainder of the tutorial, we will restrict ourselves to real number matrix computations.

High Level Syntax

```
1 x <- matrix(rnorm(30), nrow=10)
2 x <- x[-1, 2:5]
3 x <- log(abs(x) + 1)
4 xtx <- t(x) %*% x
5 ans <- svd(solve(xtx))
```

More than just a Matlab clone. . .

- Data science (machine learning, statistics, data mining, . . .) is mostly matrix algebra.

So what about Matlab/Python/Julia/. . . ?

- Depends on your “religion”
- As a *data analysis* package, R is king.

High Level Syntax *for Data*


```
1 pca <- prcomp(x, retx=TRUE, scale=TRUE)
2 prop_var <- cumsum(pca$sdev)/sum(pca$sdev)
3 i <- min(which(prop_var > 0.9)) - 1
4
5 y <- pca$x[, 1:i]
```

Contents


- 2 Parallel Hardware and R
 - Parallel Hardware
 - R Interfaces to Parallel Hardware

Three Basic Flavors of Hardware

Distributed Memory



Shared Memory



Co-Processor




GPU: Graphical Processing Unit


MIC: Many Integrated Core

Your Laptop or Desktop


Distributed Memory



Shared Memory




Co-Processor




GPU: Graphical Processing Unit
MIC: Many Integrated Core

A Server or Cluster

Distributed Memory



Shared Memory




Co-Processor




GPU: Graphical Processing Unit
MIC: Many Integrated Core


Server to Supercomputer




Knowing the Right Words




“Native” Programming Models and Tools




R Interfaces to Native Tools




30+ Years of Parallel Computing Research




Last 10 years of Advances



Putting It All Together Challenge



pbdR Focus on Data Parallelism



Contents

3 pbdR

- The pbdR Project
- pbdR Paradigms

Programming with Big Data in R (pbdR)



Striving for *Productivity, Portability, Performance*



- *Free^a* R packages.
- Bridging high-performance C with high-productivity of R
- Scalable, big data analytics.
- Distributed data details implicitly managed.
- Methods have syntax *identical* to R.
- Powered by state of the art numerical libraries (MPI, ScaLAPACK, ...)

^aMPL, BSD, and GPL licensed

pbdR Packages



pbdR on HPC Resources

pbdR is currently installed and maintained on:

- Nautilus, UTK
- Kraken, UTK
- Newton, UTK
- Lens, ORNL
- Titan, ORNL
- tara, UMBC

If you are interested in maintaining pbdR, contact us at

RBigData@gmail.com

Example Syntax

```
1 x <- x[-1, 2:5]
2 x <- log(abs(x) + 1)
3 xtx <- t(x) %*% x
4 ans <- svd(solve(xtx))
```

Look familiar?

The above runs on 1 core with R or 10,000 cores with pbdR

pbdR Paradigms

Programs that use pbdR utilize:

- Batch execution
- Single Program/Multiple Data (SPMD) style

And generally utilize:

- Data Parallelism

Batch Execution

- Non-interactive
- Use

```
1 Rscript my_script.r
```

or

```
1 R CMD BATCH my_script.r
```

- In parallel:

```
1 mpirun -np 2 Rscript my_par_script.r
```

Single Program/Multiple Data (SPMD)

- Difficult to describe, easy to do. . .
- Only one program is written, executed in batch on all processors.
- Different processors are autonomous; there is no manager.
- The dominant programming model for large machines.

Contents

- 1 Introduction to R
- 2 Parallel Hardware and R
- 3 pbdR
- 4 Benchmarks**
- 5 Challenges

Non-Optimal Choices Throughout

- 1 Only libre software used (no MKL, ACML, etc.).
- 2 1 core = 1 MPI process.
- 3 No tuning for data distribution.


Benchmark Data

- 1 Random normal $N(100, 10000)$.
- 2 Local problem size of $\approx 43.4 \text{ MiB}$.
- 3 Three sets: 500, 1000, and 2000 columns.
- 4 Several runs at different core sizes within each set.

Covariance Code

```
1 x <- ddmatrix("rnorm", nrow=n, ncol=p, mean=mean, sd=sd)
2
3 cov.x <- cov(x)
```


cov()




Linear Model Code

```
1 x <- ddmatrix("rnorm", nrow=n, ncol=p, mean=mean, sd=sd)
2 beta_true <- ddmatrix("runif", nrow=p, ncol=1)
3
4 y <- x %*% beta_true
5
6 beta_est <- lm.fit(x=x, y=y)$coefficients
```


Data Generation



```
lm.fit()
```



lm.fit()




Contents

- 1 Introduction to R
- 2 Parallel Hardware and R
- 3 pbdR
- 4 Benchmarks
- 5 Challenges**

Challenges

- Perceptions.
- Library loading.
- Profiling.

Covariance Revisited: Distributed Data Parameter Calibration



Tutorials

- SC13, November 17-22, Denver, Colorado, USA

Invited Talks

- IASC, Aug 22-23, Seoul
- World Statistics Congress, August 25-30, Hong Kong

Thanks for coming!

Questions?

Be sure to stick around for the tutorial