

Introducing R: From Your Laptop to HPC and Big Data

George Ostrouchov and Drew Schmidt

SC14



Wei-Chen Chen¹
George Ostrouchov^{2,3}
Pragneshkumar Patel³
Drew Schmidt³



Support

This work used resources of [National Institute for Computational Sciences](#) at the University of Tennessee, Knoxville, which is supported by the Office of Cyberinfrastructure of the U.S. National Science Foundation under Award No. ARRA-NSF-OCI-0906324 for NICS-RDAV center. This work also used resources of the [Oak Ridge Leadership Computing Facility](#) at the Oak Ridge National Laboratory, which is supported by the Office of Science of the U.S. Department of Energy under Contract No. DE-AC05-00OR22725.

¹Department of Ecology and Evolutionary Biology
University of Tennessee, Knoxville TN, USA

²Computer Science and Mathematics Division
Oak Ridge National Laboratory, Oak Ridge TN, USA

³Joint Institute for Computational Sciences
University of Tennessee, Knoxville TN, USA



About This Presentation

Downloads

This presentation is available at: <http://r-pbd.org/tutorial>

About This Presentation

Installation Instructions

Installation instructions for setting up a **pbR** environment are available:

<http://r-pbd.org/install.html>

This includes instructions for installing R, MPI, and **pbR**.

Contents

- 1 Profiling and Benchmarking
- 2 Wrapup

Contents

- 1 Profiling and Benchmarking
 - Profiling R Code
 - Advanced R Profiling
 - Summary

1 Profiling and Benchmarking

- Profiling R Code
- Advanced R Profiling
- Summary

Timings

Getting simple timings as a basic measure of performance is easy, and valuable.

- `system.time()` — timing blocks of code.
- `Rprof()` — timing execution of R functions.
- `Rprofmem()` — reporting memory allocation in R .
- `tracemem()` — detect when a copy of an R object is created.
- The **rbenchmark** package — Benchmark comparisons.

Performance Profiling Tools: `system.time()`

`system.time()` is a basic R utility for timing expressions

```
1 x <- matrix(rnorm(20000*750), nrow=20000, ncol=750)
2
3 system.time(t(x) %*% x)
4 #      user  system elapsed
5 #    2.187    0.032    2.324
6
7 system.time(crossprod(x))
8 #      user  system elapsed
9 #    1.009    0.003    1.019
10
11 system.time(cov(x))
12 #      user  system elapsed
13 #    6.264    0.026    6.338
```

Performance Profiling Tools: Rprof()

Rprof() times the execution of all R functions:

```
Rprof(filename="Rprof.out", append=FALSE, interval=0.02,  
memory.profiling=FALSE, gc.profiling=FALSE,  
line.profiling=FALSE, numfiles=100L, bufsize=10000L)
```

```
1 x <- matrix(rnorm(10000*250), nrow=10000, ncol=250)  
2  
3 Rprof(interval=.99)  
4 invisible(prcomp(x))  
5 Rprof(NULL)  
6  
7 summaryRprof()
```

Performance Profiling Tools: Rprof()

```

1 $by.self
2           self.time self.pct total.time total.pct
3 "La.svd"          0.68   69.39         0.72   73.47
4 "%*%"            0.12   12.24         0.12   12.24
5 "aperm.default"   0.04    4.08         0.04    4.08
6 "array"           0.04    4.08         0.04    4.08
7 "matrix"          0.04    4.08         0.04    4.08
8 "sweep"           0.02    2.04         0.10   10.20
9 ### output truncated by presenter
10
11 $by.total
12           total.time total.pct self.time self.pct
13 "prcomp"          0.98   100.00         0.00    0.00
14 "prcomp.default"  0.98   100.00         0.00    0.00
15 "svd"             0.76   77.55         0.00    0.00
16 "La.svd"          0.72   73.47         0.68   69.39
17 ### output truncated by presenter
18
19 $sample.interval
20 [1] 0.02
21
22 $sampling.time
23 [1] 0.98

```

Performance Profiling Tools: Rprof()

```
1 $by.self
2 [1] self.time self.pct total.time total.pct
3 <0 rows> (or 0-length row.names)
4
5 $by.total
6 [1] total.time total.pct self.time self.pct
7 <0 rows> (or 0-length row.names)
8
9 $sample.interval
10 [1] 0.99
11
12 $sampling.time
13 [1] 0
```

Performance Profiling Tools: rbenchmark

rbenchmark is a simple package that easily benchmarks different functions:

```
1 x <- matrix(rnorm(10000*500), nrow=10000, ncol=500)
2
3 f <- function(x) t(x) %*% x
4 g <- function(x) crossprod(x)
5
6 library(rbenchmark)
7 benchmark(f(x), g(x))
8
9 #   test replications elapsed relative
10 # 1 f(x)           100   64.153     2.063
11 # 2 g(x)           100   31.098     1.000
```

1 Profiling and Benchmarking

- Profiling R Code
- Advanced R Profiling
- Summary

Other Profiling Tools

- perf
- PAPI
- MPI profiling: fpmapi, mpiP, TAU

Profiling MPI Codes with pbdPROF

1. Rebuild pbdR packages


```
R CMD INSTALL pbdMPI_0.2-1.tar.gz \
  --configure-args= \
  "--enable-pbdPROF"
```

2. Run code

```
mpirun -np 64 Rscript my_script.R
```

3. Analyze results

```
1 library(pbdPROF)
2 prof <- read.prof( "output.mpiP")
3 plot(prof, plot.type="messages2")
```



Profiling with pbdPAPI

- Bindings for Performance Application Programming Interface (PAPI)
- Gathers detailed hardware counter data.
- High and low level interfaces



Function	Description of Measurement
<code>system.flips()</code>	Time, floating point instructions, and Mflips
<code>system.flops()</code>	Time, floating point operations, and Mflops
<code>system.cache()</code>	Cache misses, hits, accesses, and reads
<code>system.epc()</code>	Events per cycle
<code>system.idle()</code>	Idle cycles
<code>system.cpuormem()</code>	CPU or RAM bound*
<code>system.utilization()</code>	CPU utilization*

1 Profiling and Benchmarking

- Profiling R Code
- Advanced R Profiling
- Summary

Summary

- *Profile, profile, profile.*
- Use `system.time()` to get a general sense of a method.
- Use **rbenchmark**'s `benchmark()` to compare 2 methods.
- Use `Rprof()` for more detailed profiling.
- Other tools exist for more hardcore applications (**pbdPAPI** and **pbdPROF**).

Contents

2 Wrapup

Summary

- Profile your code to understand your bottlenecks.
- **pb**dR makes distributed parallelism with R easier.
- Distributing data to multiple nodes
- For truly large data, I/O must be parallel as well.

The pbdR Project

- Our website: <http://r-pbd.org/>
- Email us at: RBigData@gmail.com
- Our google group: <http://group.r-pbd.org/>

Where to begin?

- The **pbdDEMO** package
<http://cran.r-project.org/web/packages/pbdDEMO/>
- The **pbdDEMO** Vignette: <http://goo.gl/HZkRt>

Thanks for coming!

Questions?



<http://r-pbd.org/>

Come see our poster on Wednesday at 5:30!